

SPECIFICATIONS – Fabricated Signs

A. General

Supplied signs shall meet the requirements of the Michigan Department of Transportation (MDOT) 2020 Standard Specifications For Construction, Section 919. All sign panels shall be either Type III or V, except for the following signs which shall be 0.063" aluminum sheets:

- DEAD END – RIGHT SPECIAL 36"x9" FLRSCNT YLW
- DEAD END – LEFT SPECIAL 36"x9" FLRSCNT YLW
- NO OUTLET – RIGHT W14-2AR(MOD)36"x9" FLRSCNT YLW
- NO OUTLET – LEFT W14-2AR(MOD)36"x9" FLRSCNT YLW

Sign sheeting shall comply with Section 919.02B and Table 919-3. Sign reflective sheeting is for highway signs and other traffic control devices to assure optimum day and night visibility when exposed to a light source in dry and wet weather conditions.

Bids shall specify brand name and manufacturer of the sheeting used to fabricate signs and that the materials are listed on MDOT's Qualified Products List (QPL).

B. Fabrication

Signs shall be fabricated in accordance with the current MDOT Traffic Safety Standard Highway Signs Manual and the attached RCOC special sign details. Sign sheeting materials shall be listed on the MDOT QPL and accord with the MDOT Reflective Sign Sheeting Guidelines.

C. Sign Face

Fabricated signs shall conform to all the standards specified herein, including holes in the aluminum as specified. No splices shall be in the sign face. Design of the sign face shall conform to detailed drawings of standard signs in the current Michigan Manual of Uniform Traffic Control Devices (MMUTCD) and to the RCOC's attached sign details for special and modified signs. All sign faces shall bear the following information in characters not to exceed one half inch in height:

- 1) The initials RCOC in uppercase letters.
- 2) The 2-digit month/2-digit year of fabrication.
- 3) Uppercase initials of the sheeting manufacturer (i.e., "3M" for the 3M Company).
- 4) Uppercase initials (4-character max), representing the supplier fabricating the sign.

This information string shall be on or near the sign border at the bottom, lower left portion of the decal.

D. Packaging and Shipping

Fabricated signs shall be packaged to ensure protection from damage in transit and readiness for use upon delivery. Packaged cartons of signs shall weigh no more than 60 pounds and be plastic banded with each sign face protected with the glossy side of slip sheet paper against the sign face.

Pallet skids of signs shall be protected, and plastic banded with each sign face protected with the glossy side of slip sheet paper against the sign face. Banding, stacking, or crating in accord with commercially accepted standards shall ensure adequate support and protection of all sign faces and shall prevent movement and chafing that may damage signs during transit and delivery. Sheeting, decals, and fabricated signs shall not become wet in transit.

Each carton or pallet skid of fabricated signs shall be delivered clearly marked stating contents, quantity, RCOC item stock code number as shown on the RCOC purchase order, and any special packaging or handling requirements of the manufacturer.

E. Certification

The supplier shall certify that all materials furnished under this contract are new or refurbished aluminum like new, as determined by the RCOC, and that all work will be good quality, free from faults and defects and in conformance with the contract documents. All work not conforming to these specifications, including substitutions not approved and authorized, may be considered defective. Samples shall be furnished, if requested by the RCOC, to confirm acceptability.