

#Session: 2

File Processing

1. Develop an implementation package using 'C' program to process a FILE containing student details for the given queries.

A student record has the following format:

Std_rollno, Std_name, Dept, C1, C1_c, C1_g, C2, C2_c, C2_g, C3, C3_c, C3_g

Note: C1 refers to Course1, C1_c refers to credit of the course, C1_g refers to the grade in course and so on. that

Every student should have a unique rollno.

A student should have at least 3 courses and maximum four.

A grade point is in integer: S - 10; A - 9; B - 8; C - 7; D - 6; E - 5; F - 0.

Create a file and develop a menu driven system for the following queries.

- a. Insert at least 5 student records.
- b. Create a column 'GPA' for all the students.
- c. For a student with four courses, delete(deregister) a course name.
- d. For the same student you deleted in 'c', insert a new course name.
- e. Update the name of a course for two different students.
- f. Calculate GPA of all students using the GPA formula. Refer the following:
https://www.nitt.edu/home/academics/rules/BTech_Regulations_2019.pdf
- g. Upgrade the grade point of a student who has secured '7' in a course.
- h. Calculate the updated GPA of the student in 'g'.
- i. Generate a Grade report of a student given the roll no. or name.

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <string.h>
```

```
#define MAX_COURSES 4
```

```
#define MAX_STUDENTS 100
```

```
typedef struct {
```

```
    char name[50];
```

```
    int credits;
```

```
    int grade;
```

```
} Course;
```

```
typedef struct {
```

```
    int rollno;
```

```
    char name[50];
```

```

char dept[10];
Course courses[MAX_COURSES];
int course_count;
float gpa;
} Student;

Student students[MAX_STUDENTS];
int student_count = 0;
void readStudentsFromFile(const char *filename) {
    FILE *file = fopen(filename, "r");
    if (!file) {
        printf("Error opening file.\n");
        return;
    }

    student_count = 0;
    while (fscanf(file, "%d,%49[^\n],%9[^\n]", &students[student_count].rollno, students[student_count].name,
students[student_count].dept) == 3) {
        for (int i = 0; i < MAX_COURSES; i++) {
            if (fscanf(file, ",%49[^\n],%d,%d", students[student_count].courses[i].name,
&students[student_count].courses[i].credits, &students[student_count].courses[i].grade) != 3) {
                break;
            }
            students[student_count].course_count++;
        }
        student_count++;
    }
    fclose(file);
}

void writeStudentsToFile(const char *filename) {
    FILE *file = fopen(filename, "w");
    if (!file) {
        printf("Error opening file.\n");
        return;
    }

```

```

for (int i = 0; i < student_count; i++) {
    fprintf(file, "%d,%s,%s", students[i].rollno, students[i].name, students[i].dept);
    for (int j = 0; j < students[i].course_count; j++) {
        fprintf(file, ",%s,%d,%d", students[i].courses[j].name, students[i].courses[j].credits,
students[i].courses[j].grade);
    }
    fprintf(file, "\n");
}
fclose(file);
}

void insertStudent() {
    if (student_count >= MAX_STUDENTS) {
        printf("Maximum student limit reached.\n");
        return;
    }

```

```

Student new_student;
printf("Enter roll number: ");
scanf("%d", &new_student.rollno);
printf("Enter name: ");
scanf("%s", new_student.name);
printf("Enter department: ");
scanf("%s", new_student.dept);

```

```

printf("Enter number of courses (3 or 4): ");
scanf("%d", &new_student.course_count);
if (new_student.course_count < 3 || new_student.course_count > 4) {
    printf("Invalid number of courses.\n");
    return;
}

```

```

for (int i = 0; i < new_student.course_count; i++) {
    printf("Enter course %d name: ", i + 1);
    scanf("%s", new_student.courses[i].name);
    printf("Enter course %d credits: ", i + 1);
    scanf("%d", &new_student.courses[i].credits);
}

```

```

    printf("Enter course %d grade: ", i + 1);
    scanf("%d", &new_student.courses[i].grade);
}

students[student_count++] = new_student;
writeStudentsToFile("students.txt");
}

void calculateGPA(Student *student) {
    int total_credits = 0;
    int total_points = 0;

    for (int i = 0; i < student->course_count; i++) {
        total_credits += student->courses[i].credits;
        total_points += student->courses[i].credits * student->courses[i].grade;
    }

    student->gpa = (float)total_points / total_credits;
}

void calculateAllGPAs() {
    for (int i = 0; i < student_count; i++) {
        calculateGPA(&students[i]);
    }
    writeStudentsToFile("students.txt");
}

void deregisterCourse(int rollno) {
    for (int i = 0; i < student_count; i++) {
        if (students[i].rollno == rollno && students[i].course_count == 4) {
            printf("Enter course name to deregister: ");
            char course_name[50];
            scanf("%s", course_name);

            int found = 0;
            for (int j = 0; j < students[i].course_count; j++) {
                if (strcmp(students[i].courses[j].name, course_name) == 0) {
                    found = 1;

```

```

        for (int k = j; k < students[i].course_count - 1; k++) {
            students[i].courses[k] = students[i].courses[k + 1];
        }
        students[i].course_count--;
        break;
    }
}

```

```

if (!found) {
    printf("Course not found.\n");
} else {
    writeStudentsToFile("students.txt");
    printf("Course deregistered successfully.\n");
}
return;
}

```

```

}
printf("Student with roll number %d having four courses not found.\n", rollno);
}

```

```

void insertCourse(int rollno) {
    for (int i = 0; i < student_count; i++) {
        if (students[i].rollno == rollno && students[i].course_count == 3) {
            printf("Enter new course name: ");
            scanf("%s", students[i].courses[students[i].course_count].name);
            printf("Enter new course credits: ");
            scanf("%d", &students[i].courses[students[i].course_count].credits);
            printf("Enter new course grade: ");
            scanf("%d", &students[i].courses[students[i].course_count].grade);

            students[i].course_count++;
            writeStudentsToFile("students.txt");
            printf("Course inserted successfully.\n");
            return;
        }
    }
}

```

```

printf("Student with roll number %d having three courses not found.\n", rollno);

```

```

}

void updateCourseName() {
    for (int i = 0; i < 2; i++) {
        printf("Enter roll number for student %d: ", i + 1);
        int rollno;
        scanf("%d", &rollno);

        int found = 0;
        for (int j = 0; j < student_count; j++) {
            if (students[j].rollno == rollno) {
                printf("Enter old course name to update: ");
                char old_name[50];
                scanf("%s", old_name);
                printf("Enter new course name: ");
                char new_name[50];
                scanf("%s", new_name);

                for (int k = 0; k < students[j].course_count; k++) {
                    if (strcmp(students[j].courses[k].name, old_name) == 0) {
                        strcpy(students[j].courses[k].name, new_name);
                        found = 1;
                        break;
                    }
                }
            }

            if (!found) {
                printf("Course not found for student %d.\n", rollno);
            } else {
                printf("Course name updated successfully.\n");
            }
            break;
        }
    }

    if (!found) {
        printf("Student with roll number %d not found.\n", rollno);
    }
}

```

```

    }
}
writeStudentsToFile("students.txt");
}

void upgradeGrade(int rollNo) {
    for (int i = 0; i < student_count; i++) {
        if (students[i].rollNo == rollNo) {
            for (int j = 0; j < students[i].course_count; j++) {
                if (students[i].courses[j].grade == 7) {
                    students[i].courses[j].grade = 8;
                }
            }
            writeStudentsToFile("students.txt");
            printf("Grades upgraded successfully.\n");
            return;
        }
    }
    printf ("Student with roll number %d not found.\n", rollNo);
}

void generateGradeReport (int rollNo) {
    for (int i = 0; i < student_count; i++) {
        if (students[i].rollNo == rollNo) {
            printf("Grade Report for Roll Number: %d\n", rollNo);
            printf("Name: %s\n", students[i].name);
            printf("Department: %s\n", students[i].dept);
            printf("Courses:\n");
            for (int j = 0; j < students[i].course_count; j++) {
                printf("%s: Credits = %d, Grade = %d\n", students[i].courses[j].name,
students[i].courses[j].credits, students[i].courses[j].grade);
            }
            printf("GPA: %.2f\n", students[i].gpa);
            return;
        }
    }
    printf("Student with roll number %d not found.\n", rollNo);
}

```

```
void menu() {
    int choice;
    do {
        printf("\n1. Insert Student Records\n");
        printf("2. Calculate GPAs\n");
        printf("3. Deregister a Course\n");
        printf("4. Insert a New Course\n");
        printf("5. Update Course Names\n");
        printf("6. Upgrade Grade\n");
        printf("7. Generate Grade Report\n");
        printf("8. Exit\n");
        printf("Enter your choice: ");
        scanf("%d", &choice);

        switch (choice) {
            case 1:
                insertStudent();
                break;
            case 2:
                calculateAllGPAs();
                break;
            case 3: {
                int rollno;
                printf("Enter roll number: ");
                scanf("%d", &rollno);
                deregisterCourse(rollno);
                break;
            }
            case 4: {
                int rollno;
                printf("Enter roll number: ");
                scanf("%d", &rollno);
                insertCourse(rollno);
                break;
            }
            case 5:
```



```

        updateCourseName();
        break;
case 6: {
    int rollNo;
    printf("Enter roll number: ");
    scanf("%d", &rollNo);
    upgradeGrade(rollNo);
    break;
}
case 7: {
    int rollNo;
    printf("Enter roll number: ");
    scanf("%d", &rollNo);
    generateGradeReport(rollNo);
    break;
}
case 8:
    printf("Exiting...\n");
    break;
default:
    printf("Invalid choice. Please try again.\n");
}
} while (choice != 8);
}

int main() {
    readStudentsFromFile("students.txt");menu();
    return 0;
}

```

Structured Query Language (SQL)

1. Create a Student schema using the student details given in Q.No.1 and execute the following basic queries.

Note: When defining the schema, exclude the following columns: Course_credit and Course_grade for all the courses.

Make sure you have the following constraints: Course is declared in char datatype.

DoB should be in date (dd/mm/yyyy) format. Provide a not-null constraint for dob. Email should have the following format: xxx@nitt.edu

```
CREATE TABLE student (
rollnum INT PRIMARY KEY,
name VARCHAR(50),
dept VARCHAR(10),
dob DATE NOT NULL,
email VARCHAR(50) CHECK (email LIKE '%@nitt.edu'),
course1 VARCHAR(50),
course2 VARCHAR(50),
course3 VARCHAR(50),
course4 VARCHAR(50)
);
```

```
mysql> describe student;
```

```
+-----+-----+-----+-----+-----+
| Field | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+
| rollnum | int       | NO   | PRI | NULL    |      |
| name   | varchar(50) | YES  |     | NULL    |      |
| dept   | varchar(10) | YES  |     | NULL    |      |
| dob    | date      | NO   |     | NULL    |      |
| email   | varchar(50) | YES  |     | NULL    |      |
| course1 | varchar(50) | YES  |     | NULL    |      |
| course2 | varchar(50) | YES  |     | NULL    |      |
| course3 | varchar(50) | YES  |     | NULL    |      |
| course4 | varchar(50) | YES  |     | NULL    |      |
+-----+-----+-----+-----+-----+
```

A.Insert at least 5 student records into the Student table.

```
INSERT INTO student (rollnum, name, dept, dob, email, course1, course2, course3, course4)
VALUES
(106122034, 'deepak', 'cse', '2022-08-22', '106122034@nitt.edu', 'DBMS', 'OS', 'CYK', 'FLAT'),
(106122036, 'dev', 'cse', '2022-08-22', '106122036@nitt.edu', 'DBMS', 'M1', 'M2', 'CHEM'),
(106122122, 'sudhanshu', 'cse', '2022-08-22', '106122122@nitt.edu', 'DBMS', 'PHYSICS', 'CHEM', 'MECH'),
(106122056, 'himanshu', 'cse', '2022-08-22', '106122056@nitt.edu', 'ROL', 'THKI', 'CHIK', 'M3');
mysql> select * from student;
```

rollnum	name	dept	dob	email	course1	course2	course3	course4
106122034	deepak	cse	2022-08-22	106122034@nitt.edu	DBMS	OS	CYK	FLAT
106122036	dev	cse	2022-08-22	106122036@nitt.edu	DBMS	M1	M2	CHEM
106122056	himanshu	cse	2022-08-22	106122056@nitt.edu	ROL	THKI	CHIK	M3
106122122	sudhanshu	cse	2022-08-22	106122122@nitt.edu	DBMS	PHYSICS	CHEM	MECH

B. Delete Course2 and Course3 attributes from the Student table.

```
ALTER TABLE student
```

```
DROP COLUMN course2,
```

```
DROP COLUMN course3;
```

```
mysql> select * from student;
```

rollnum	name	dept	dob	email	course1	course4
106122034	deepak	cse	2022-08-22	106122034@nitt.edu	DBMS	FLAT
106122036	dev	cse	2022-08-22	106122036@nitt.edu	DBMS	CHEM
106122056	himanshu	cse	2022-08-22	106122056@nitt.edu	ROL	M3
106122122	sudhanshu	cse	2022-08-22	106122122@nitt.edu	DBMS	MECH

C. Insert two new columns DoB and email into the Student table.

Already done while make the table

D. Change Course1 datatype to varchar2.

```
ALTER TABLE student
```

```
MODIFY course1 VARCHAR2(50);
```

```
mysql> describe student;
```

Field	Type	Null	Key	Default	Extra
rollnum	int	NO	PRI	NULL	
name	varchar(50)	YES		NULL	
dept	varchar(10)	YES		NULL	
dob	date	NO		NULL	
email	varchar(50)	YES		NULL	

```
| course1 | varchar(50) | YES | | NULL | |
```

```
| course4 | varchar(50) | YES | | NULL | |
```

```
+-----+-----+-----+-----+-----+-----+
```

7 rows in set (0.00 sec)

E. Update the column name 'Std_rollno' to 'Std_rno'.

```
ALTER TABLE student
```

```
RENAME COLUMN rollnum TO std_rno;
```

```
mysql> select * from student;
```

```
+-----+-----+-----+-----+-----+-----+
```

```
| std_rno | name | dept | dob | email | course1 | course4 |
```

```
+-----+-----+-----+-----+-----+-----+
```

```
| 106122034 | deepak | cse | 2022-08-22 | 106122034@nitt.edu | DBMS | FLAT |
```

```
| 106122036 | dev | cse | 2022-08-22 | 106122036@nitt.edu | DBMS | CHEM |
```

```
| 106122056 | himanshu | cse | 2022-08-22 | 106122056@nitt.edu | ROL | M3 |
```

```
| 106122122 | sudhanshu | cse | 2022-08-22 | 106122122@nitt.edu | DBMS | MECH |
```

```
+-----+-----+-----+-----+-----+-----+
```

4 rows in set (0.00 sec)

F. Update all student records who pursue a course named "DBMS" to "OS".

```
UPDATE student
```

```
SET course1 = 'OS'
```

```
WHERE course1 = 'DBMS';
```

```
mysql> select * from student;
```

```
+-----+-----+-----+-----+-----+-----+
```

```
| std_rno | name | dept | dob | email | course1 | course4 |
```

```
+-----+-----+-----+-----+-----+-----+
```

```
| 106122034 | deepak | cse | 2022-08-22 | 106122034@nitt.edu | OS | FLAT |
```

```
| 106122036 | dev | cse | 2022-08-22 | 106122036@nitt.edu | OS | CHEM |
```

```
| 106122056 | himanshu | cse | 2022-08-22 | 106122056@nitt.edu | ROL | M3 |
```

```
| 106122122 | sudhanshu | cse | 2022-08-22 | 106122122@nitt.edu | OS | MECH |
```

```
+-----+-----+-----+-----+-----+-----+
```

4 rows in set (0.00 sec)

G. Delete a student record with student name starting with letter 'S'.

DELETE FROM student

WHERE name LIKE 'S%';

mysql> select * from student;

std_rno	name	dept	dob	email	course1	course4
106122034	deepak	cse	2022-08-22	106122034@nitt.edu	OS	FLAT
106122036	dev	cse	2022-08-22	106122036@nitt.edu	OS	CHEM
106122056	himanshu	cse	2022-08-22	106122056@nitt.edu	ROL	M3

H. Display all records in which a student has born after the year 2005.

SELECT * FROM student

WHERE dob > '2005-01-01';

mysql> SELECT * FROM student WHERE dob > '2005-01-01';

std_rno	name	dept	dob	email	course1	course4
106122034	deepak	cse	2022-08-22	106122034@nitt.edu	OS	FLAT
106122036	dev	cse	2022-08-22	106122036@nitt.edu	OS	CHEM
106122056	himanshu	cse	2022-08-22	106122056@nitt.edu	ROL	M3

3 rows in set (0.00 sec)

I. Simulate DROP and TRUNATE commands with the database you created.

DROP TABLE student;

TRUNCATE TABLE student;