

## Assignment -4

### Python Programming

Assignment Date	29-10-2022
Student Name	KAVITHA R
Student Roll Number	921819104015
Maximum Marks	2 MARKS

#### Question 1:

**Import the necessary libraries**

Solution:

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import pad_sequences
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping
```

#### Question2:

**Download the Dataset**

Solution:

Dataset Downloaded and uploaded to drive <https://www.kaggle.com/code/kredy10/simple-lstm-for-textclassification/data>

#### Question3:

**Read dataset and do pre-processing**

Solution:

Read dataset

```
In [21]: df = pd.read_csv('/content/drive/MyDrive/spam.csv', delimiter=',', encoding='latin-1')
df.head()
```

```
Out[21]:
```

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy.. Available only ...	NaN	NaN	NaN
1	ham	Ok lar... Joking wif u oni...	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...	NaN	NaN	NaN
3	ham	U dun say so early hor... U c already then say...	NaN	NaN	NaN
4	ham	Nah I don't think he goes to usf, he lives aro...	NaN	NaN	NaN

## Pre-processing the Dataset

```
In [22]: df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
df.info()
```

```
RangeIndex: 5572 entries, 0 to 5571
Data columns (total 2 columns):
#   Column  Non-Null Count  Dtype
---  ------  -
0    v1      5572 non-null     object
1    v2      5572 non-null     object
dtypes: object(2)
memory usage: 87.2+ KB
```

```
In [23]: X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

```
In [24]: X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)
```

```
In [25]: max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = pad_sequences(sequences,maxlen=max_len)
```

```
In [26]: inputs = Input(name='inputs',shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(64)(layer)
layer = Dense(256,name='FC1')(layer)
layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1,name='out_layer')(layer)
layer = Activation('sigmoid')(layer)
model = Model(inputs=inputs,outputs=layer)

model.summary()
```

Hoael. -mdel 1'

LCyer (type)	Output Shape	Paraa 0
inputs (InputLayer)	[(None, 150)]	0
embedding_1 (Embedding)	(None, 150, 50)	50000
Lstm_1 (LSTM)	(None, 64)	29440
FC1 (Dense)	(scene, 256)	16668
activation_2 (Activation)	(None, 256)	0
dropout_1 (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	0.57
activation_3 (Activation)	(None, 1)	0

Total paraas: 96,337

Trainable paras: 96,337

Non-trainable paraas: 8

```
mdaz.caqi11e(loss='binary_crossentropy', metrics=['accuracy'])
```

```
sequences_matrix, Y_train, batch_size=128, epochs=10,  
validation_split=0.2)
```

```
Epoch 1/10  
3a/3a [-----] - 10s 264ms/step - loss: 0.3182 - accuracy: 0.8788 - val_loss: 0.1571 - val_accuracy: 0.9715  
Epoch 7/10  
30/30 [-----] - 7s 274ms/step - loss: 0.0805 - accuracy: 0.9742 - val_loss: 0.0862 - val_accuracy: 0.9778  
Epoch 1/10  
30/30 [-----] - 7s 137ms/step - loss: 0.4443 - accuracy: 0.9881 - val_loss: 0.0869 - val_accuracy: 0.9781  
30/30 [-----] - 7s 245ms/step - loss: 0.8171 - accuracy: 0.9929 - val_loss: 0.0846 - val_accuracy: 0.9778  
30/30 [-----] - 7s 242ms/step - loss: 0.0220 - accuracy: 0.9937 - val_loss: 0.0820 - val_accuracy: 0.9800  
78/10 [-----] - 7s 246ms/step - loss: 0.0178 - accuracy: 0.9935 - val_loss: 0.0887 - val_accuracy: 0.9789  
Epoch 7/10  
30/30 [-----] - 7s 243ms/step - loss: 0.0158 - accuracy: 0.9935 - val_loss: 0.0869 - val_accuracy: 0.9566  
36/30 [-----] - 7s 241ms/step - loss: 0.0162 - accuracy: 0.9958 - val_loss: 0.0901 - val_accuracy: 0.9768  
36/30 [-----] - 7s 246ms/step - loss: 0.0099 - accuracy: 0.9968 - val_loss: 0.1284 - val_accuracy: 0.9789  
Epoch 10/10  
30/30 [-----] - 7s 247ms/step - loss: 0.8355 - accuracy: 0.9781 - val_loss: 0.1761 - val_accuracy: 0.9776
```

Save The Model

```
model.save('sn5_classification.h5')
```

ipynb ngthatenom

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = pad_sequences(test_sequences, maxlen=m4x_len)
```

Testing the Model

```
model.evaluate(test_sequences_matrix, Y_test)
```

```
27/27 [.....] * 1s 7ms/step * Loss: 0.0886 * Accuracy: 0.9821
```

```
print('Test set\n loss: %.3f\n accuracy: %.2f' % (loss, acc))
```

Test set

loss: 0.089

accuracy: 0.982