Critical fields by use case — where each comes from in our data today

Ticket: RA-643. Output for the product page; feeds the spec and ongoing data modelling.

Basis and how to read this

"Source today" is our own databases: the ReEx database, the operator backend (**OJ**, `accreditationApplications`) and the case management backend (**CM**, `workItems` / `payload`). For each field the table says what each system holds. Where a field is held in none of them, the row says **Gap**, and the gap is listed at the end for a separate ticket on how to source it. Nothing here proposes a fix.

What this is built from (and nothing else):

- **ReEx — read from the code.** `DEFRA/epr-backend`, `main` @ `09fb1f4`, 2026-10-16 (a read-only clone). I read the stored data model (the Joi schemas under `src/repositories/organisations/schema/` and `src/overseas-sites/repository/schema.js`), the organisation read-model adapter and the response schema of its route, the public register transformer, the accreditation date helpers, the exporter summary log validation, the reports schema and the PRN model. Field names below are the stored ones. **Not read:** the waste balance module, the forms-ingest transformation, Mongo indexes, and any live data.
- **OJ and CM — from the two data-model docs** (`operator-reaccreditation-data-model.md` @ `dd71432`, `casemanagement-reaccreditation-data-model.md` @ `ef6a005`), with spot checks in the code marked **checked**.
- **What each use case needs** (not where it comes from): the public register CSV of 8 Oct 2026 (28 columns, UC1) and the exporter summary log template V5.1 with its GOV.UK guidance (UC4, UC5, UC8).

Not established by any of these: which years each system is the authority for. The data models do not say, so the table does not assume it (see the open questions at the end).

Gap / notes starts with **OK** (held in at least one system in a usable form), **Partial** (held, but stale, snapshot-only, or missing part of what the use case needs) or **Gap** (held in none). Where a field is in one system and not another, the note says which.

"History needed" is my proposal for product to confirm: None / Current / Point-in-time / Full history. "Point-in-time" means the use case asks about a past date.

Not covered: the interim sites log (the application attachment). The PDF supplied renders only its banner and the metals "conditions of export" box; its columns are not readable. The exporter summary log's interim-site columns are covered below.

What the three data models look like together

1. **ReEx holds the organisation, its registrations and its accreditations.** One accreditation record per year per registration (the year is the year of its `validFrom`). It also has modules for PRNs, reports, summary logs and waste balances. OJ and CM hold a different thing: a re-accreditation **application** per organisation + registration + material + year, seeded from a ReEx snapshot and not refreshed. They carry seed-time copies of organisation and registration data, which go stale.
2. **ReEx effective-dates what an accreditation is.** It holds `validFrom` and `validTo` on each accreditation, and a `statusHistory` of `{ status, updatedAt, updatedBy }` entries on organisations, registrations and accreditations (the current status is the latest entry). Its summary log validation already reads them at a date. OJ and CM hold none of this; their only history is OJ's per-section `versions[]` snapshots (stamped with the *submission* time, never returned by the API) and the CM audit log (application lifecycle events).
3. **Two different "statuses".** OJ's `applicationStatus` and CM's `stateId` describe the application (`Saved` … `Approved`, `Rejected`, `Withdrawn`; `Approved` is terminal in OJ). ReEx holds the registration's and accreditation's own status: registrations `created | approved | cancelled | rejected`, accreditations the same plus `suspended`. The register publishes `Approved`, `Suspended` and `Cancelled`; OJ and CM cannot record the last two.
4. **ReEx already serves an organisation read model.** `GET /organisations/{organisationNumber}` (optional `?year=`) exists in the code, built from the same data (ADR-0052). Its response schema decides what is served, and I use it for the "Served by ReEx's route today" column. I did not check whether it is deployed.
5. **Identifier trap (RA-503):** `organisationId` is ReEx's internal ObjectId (never show); `orgId` is the visible organisation number (500027 in the register); `LinkedDefraOrganisation.OrgId` is an unrelated Defra UUID.

Use cases

#	Use case	Question it answers
UC1	Public register	Who is registered and accredited, for what, and where?
UC2	Operator dashboard	What does my organisation hold, and what state is it in?
UC3	Regulator dashboard	What does this organisation hold, and what state is it in?
UC4	Summary log validation: accreditation status	Was this registration accredited on the date of this row?
UC5	Summary log validation: ORS and interim sites	Was this ORS or interim site approved for this accreditation on this date?
UC6	PRN issuing: tonnage band	Is this PRN within the tonnage band in force when it is issued?
UC7	PRN issuing: signatories	Was this person an authorised signatory for this accreditation when they signed?

#	Use case	Question it answers
UC8	Annual reporting	How does the year's activity compare with the business plan?
UC9	Status management (potential)	What is the current status before I suspend, cancel or reinstate?

What a summary log row carries (UC4, UC5). The accredited exporter template has three dates per load: *Date received for export*, *Date of export* and *Date received by approved overseas reprocessor*. In ReEx's validation the accreditation must cover **Date of export and Date received by overseas reprocessor**, and the overseas site must be approved by **Date of export**. The row also names the overseas site and interim site by ID (`OSR_ID`, `INTERIM_SITE_ID`), plus `OSR_NAME`, `OSR_COUNTRY`, `BASEL_EXPORT_CODE` and `DID_WASTE_PASS_THROUGH_AN_INTERIM_SITE`. There are four templates by registration type; ReEx picks "registered-only" when the registration has no linked accreditation with an accreditation number.

The purpose, and the "served today" column

The mapping feeds the design of an API that serves ReEx's organisation read model **plus the other use cases above**. The read model was written for one client, so it will not cover them all. The **Served by ReEx's route today** column says what its response schema returns now (verified in code):

- **Served:** returned by the route. "(via statusTimeline)" means as a dated status timeline built from `statusHistory`.
- **Not served, held:** ReEx stores it but the route does not return it.
- **Not held:** ReEx does not store it.

Mapping table

Route column: **green = served** · **amber = held, not served** · **red = not held**. Gap / notes bar: **green = OK** · **amber = Partial** · **red = Gap**

Organisation

Field	Level	Meaning	Used by	History needed	Served by ReEx route today	In ReEx (stored)	In OJ / CM	Gap / notes
organisationNumber	Organisation	Business reference; the register's "Org ID"	All	None	Served	`orgId`	OJ `orgId`; CM `payload.operatorOrgNumber`	**OK.**
organisationId	Organisation	ReEx's internal id	UC2, UC3, UC9 (as a key)	None	Not served, held	`id` (ObjectId string)	OJ `organisationId`; CM `payload.operatorOrganisationId`	**OK** as a key. Never user-visible (RA-503).
name	Organisation	Company name ("Business name")	UC1, UC2, UC3	Current	Served	`companyDetails.name`	OJ `organisationName`; CM `payload.organisationName`	**OK** in ReEx. The OJ and CM copies are seed-time snapshots, never refreshed.
tradingName	Organisation	Trading name	UC1, UC2, UC3	Current	Served	`companyDetails.tradingName` (optional)	Not held	**OK** in ReEx only. Register data quality: several trading names are numbers (for example `11678700`, `3799128960`, `14868589`).
companiesHouseNumber	Organisation	Companies House number	UC1	Current	Not served, held	`companyDetails.companiesHouseNumber` (optional, 8 characters)	OJ `companiesHouseNumber`; CM payload copy	**OK** in ReEx. Blank on some register rows (overseas and some UK bodies). OJ and CM copies are snapshots.
registeredOffice	Organisation	Registered office / head office / main place of business in the UK	UC1, UC3	Current	Not served, held	`companyDetails.registeredAddress` (the register falls back to `companyDetails.address`)	OJ `companyRegisteredAddress`, `companyRegisterAddressPostcode`, `isUkRegisteredAddress`; CM payload copies	**OK** in ReEx (address parts, or `fullAddress`). OJ and CM hold a concatenated string plus postcode. Register rows include non-UK addresses.
linkedDefraOrganisation	Organisation	The Defra organisation an operator signs in as	UC2	Current	Served (`linkedBy.id` not served)	`linkedDefraOrganisation` (`orgId` uuid, `orgName`, `linkedBy` email and id, `linkedAt`)	Not stored. OJ resolves it per request through `GET api/v1/organisations/{id}/defra-link`	**OK** in ReEx.
contacts	Organisation	Submitter and management contacts	UC3	Current	Not served, held	`submitterContactDetails`, `managementContactDetails` (name, email, phone, job title); registrations hold `submitterContactDetails`, `applicationContactDetails`, `approvedPersons`; `users[]` collates the people with roles	OJ `submittedBy`, `submitterContactDetails`; CM payload copies	**OK** in ReEx. OJ and CM hold only the latest submitter.

Field	Level	Meaning	Used by	History needed	Served by ReEx route today	In ReEx (stored)	In OJ / CM	Gap / notes
organisationStatus	Organisation	created, approved, active, rejected	UC2, UC3	Current	Served (`status`; no org timeline)	`statusHistory[]` (`status`, `updatedAt`, `updatedBy`); the current status is the latest entry	Not held	**OK** in ReEx. The `status` field itself is computed, not written.

Registration

Field	Level	Meaning	Used by	History needed	Served by ReEx route today	In ReEx (stored)	In OJ / CM	Gap / notes
registrationId	Registration	ReEx's id for the registration	UC2, UC3, UC4, UC9 (as a key)	None	Not served, held	`id`	OJ `registrationId`; CM `payload.operatorRegistrationId`	**OK** as a key.
registrationNumber	Registration	Public registration number (register "Registration number", for example `R26ER5000270036WO`)	UC1, UC2, UC3, UC4	Current (plus previous numbers)	Served (the key)	`registrationNumber` (required once approved)	OJ `registrationReference` (server-owned), `previousRegistrationNumbers[]`; CM `payload.registrationNumber`	**Partial.** Two writers: OJ can generate or regenerate the number when CM asks (`…/registration-number`), so OJ's value is not only a copy of ReEx's.
wasteProcessingType	Registration	Reprocessor or exporter (register "Type")	UC1, UC2, UC3, UC5, UC8	Current	Served	`wasteProcessingType`	OJ `wasteProcessingType`, `isExporter`; CM payload copy	**OK.**
material	Registration	Packaging waste category (Plastic, Paper and board, Glass-remelt, Glass-other …)	UC1, UC2, UC3, UC6, UC8	Current	Served (glass split as `glass_re_melt` / `glass_other`)	`material` (plain `glass` for glass) plus `glassRecyclingProcess[]`; the register and route combine them	OJ `materialType` plus `glassRecyclingProcess`; CM `payload.material`, `glassRecyclingProcess`	**Partial.** The glass split is derived from the process list in ReEx's code; OJ and CM hold `Glass` plus a flag.
annexIIProcess	Registration	Recycling process code on the register: R3, R4 or R5	UC1	Current	Not served, derivable	Not stored. Derived from `material` in the register transformer (`getAnnexIIProcess`)	Not held	**OK**, as a derivation from material.
appropriateAgency	Registration	Regulator: EA, NRW, SEPA or NIEA	UC1, UC3	Current	Served (`submittedToRegulator.code`)	`submittedToRegulator` (ea, nrw, sepa, niea) on the registration	OJ `nation`; CM `payload.nation`	**OK.** OJ and CM hold a nation, taken from the registration's regulator at seed (RA-526); mapping England, Wales, Scotland, NorthernIreland to the four agencies.
reprocessingSite	Registration	Registered reprocessing site address (reprocessors only)	UC1, UC2, UC3	Current	Served (country, region not served)	`site.address` (`line1`, `postcode` required; also `gridReference`, `siteCapacity`)	OJ `siteAddress`; CM `payload.siteAddress`, `payload.siteAddressPostcode`	**OK** in ReEx. OJ and CM hold a snapshot string; the CM adapter extracts the postcode from it.
permitNumbers	Registration	Waste management permit numbers	UC1, UC3	Current	Not served, held	`wasteManagementPermits[]`	OJ `permitNumbers[]`; CM payload copy	**OK.** Not a register column.
registrationStatus	Registration	approved, cancelled (also created, rejected before approval)	UC1, UC2, UC3, UC9	Point-in-time	Served (`status`, `statusTimeline`)	`statusHistory[]` on the registration; a registration is never suspended	Not held	**OK** in ReEx. `applicationStatus` in OJ and CM is the application, not the registration.
registrationDates	Registration	Date the registration took effect, and any end	UC1, UC3, UC9	Point-in-time	Served (`validFrom` only)	`validFrom` (required once approved). The registration schema has no `validTo`	Not held	**Partial.** A start date; an end is only visible as a `cancelled` entry in the status history.
registeredNotAccredited	Registration	A registration with no accreditation	UC1, UC2, UC3	Current	Served (numbered registrations only)	Registrations exist independently; `accreditationId` is an optional link	Not representable (no application, no record)	**OK** in ReEx.

Accreditation

Field	Level	Meaning	Used by	History needed	Served by ReEx route today	In ReEx (stored)	In OJ / CM	Gap / notes
accreditationNumber	Accreditation	Public accreditation number (register "Accreditation No", for example `A26ER5000270063WO`)	UC1, UC2, UC3, UC4, UC5, UC6, UC7	Current (plus previous numbers)	Served	`accreditationNumber` (required once approved or suspended)	OJ `accreditationReference` (server-owned), `previousAccreditationNumbers[]`; CM `payload.accreditationId` (written at approval)	**OK** in ReEx. In OJ and CM it exists only once an application is approved.

Field	Level	Meaning	Used by	History needed	Served by ReEx route today	In ReEx (stored)	In OJ / CM	Gap / notes
accreditationYear	Accreditation	The scheme year	UC1, UC2, UC3, UC8	Current	Served (as the key)	Not stored. Derived: the year of `validFrom` (`deriveAccreditationYear`)	OJ `year`, `sourceYear`; CM `payload.accreditationYear`, `previousAccreditationYear`	**Partial.** CM re-stamps the year from the `Accreditation:CurrentYear` config at approval; do not treat it as a start date (QA bug recorded at `SlaService.cs:190`).
accreditationLink	Accreditation	Link between an application and an earlier accreditation	UC1, UC4, UC9	Full history	Not served	ReEx holds one accreditation record per year per registration (`accreditationsForRegistration`)	OJ `sourceReExAccreditationId`, `sourceYear`, `previousAccreditationNumbers[]` point back at the ReEx accreditation	**Partial.** One OJ key joins an application to a ReEx accreditation. Neither model holds a single history spanning both.
activeDate	Accreditation	Date the accreditation takes effect (register "Active Date")	UC1, UC4, UC5, UC6, UC7	Point-in-time	Not served, held	Accreditation `validFrom` (the register's Active Date is exactly this)	CM `payload.accreditationStartDate`, stamped at approval and derived from the configured year (**checked**). Not in OJ	**OK** in ReEx. **Partial** in CM: its value cannot hold the mid-year dates the register shows (for example 19/01/2026, 15/07/2026).
accreditationEndDate	Accreditation	Date the accreditation ends	UC1, UC4, UC5, UC6, UC7	Point-in-time	Not served, held	Accreditation `validTo` (required once approved or suspended); kept after a cancellation	Not held (**checked**)	**OK** in ReEx. **Gap** in OJ and CM.
accreditationStatus	Accreditation	Approved, Suspended or Cancelled (register "Accreditation status")	UC1, UC2, UC3, UC4, UC9	Point-in-time	Served (`status`)	Accreditation `statusHistory[]` (created, approved, suspended, cancelled, rejected); the current status is the latest entry	OJ `applicationStatus`; CM `stateId` (application lifecycle only)	**OK** in ReEx. **Gap** in OJ and CM: no suspended or cancelled state, and `Approved` is terminal in OJ.
statusLastChanged	Accreditation	Date the status last changed (register "Date status last changed")	UC1, UC3, UC9	Current	Served (via statusTimeline, adjusted)	Accreditation `statusHistory[]`, `updatedAt` of the last entry (what the register publishes)	CM audit log; OJ `caseManagementStatusUpdatedAt` (last push only)	**OK** in ReEx. **Partial** in OJ and CM (application lifecycle only). The route's timeline moves the approval to `validFrom`, so its latest date can differ from the register's. On the register it is often earlier than Active Date (for example 31/12/2025 against 01/01/2026), so they are separate dates.
statusHistory	Accreditation	Dated status events that can be read at a date	UC4, UC9	Full history	Served (via statusTimeline)	Accreditation `statusHistory[]`; ReEx already reads it at a date (`statusHeldAt`, `isSuspendedOrCancelledAtDate`)	CM audit log (application only; a display log, not a query surface)	**OK** in ReEx. **Gap** in OJ and CM: no suspend or cancel events can be recorded.
summaryLogClassification	Registration and accreditation	Which of the four summary log templates applies, and whether a row falls inside the accreditation	UC4	Point-in-time	Not served; logic is in ReEx's backend	Template is "registered-only" when the registration has no linked accreditation number; each row must lie inside `validFrom`..`validTo` and outside any suspended or cancelled period at Date of export and Date received by overseas reprocessor (`isAccreditedAtDates`)	Not derivable	**OK** in ReEx. **Gap** in OJ and CM.
applicationStatus	Application	Where the application is in its lifecycle	UC2, UC3, UC9	Current	Not served (unapproved records are not served)	Unapproved registrations and accreditations hold status `created` or `rejected`	OJ `applicationStatus` (driven partly by CM pushes); CM `stateId`	**OK.** OJ and CM can disagree if a push is lost (RA-606).
withdrawalReason	Application	Why an application was withdrawn	UC3	Current	Not served	Not seen	OJ `withdrawalReason`	**OK** in OJ.

Overseas reprocessing sites (ORS) and interim sites (exporters)

The public register does not list ORS or interim sites, so these rows serve UC3 and UC5.

Field	Level	Meaning	Used by	History needed	Served by ReEx route today	In ReEx (stored)	In OJ / CM	Gap / notes
orsId	ORS	Summary log `OSR_ID`: 3-digit ID of the approved overseas reprocessor	UC3, UC5	None	Served (as the key)	Registration `overseasSites`, keyed by a 3-digit `orsId` and pointing at a shared overseas-site record (`overseasSiteId`)	OJ `overseasSites.sites[].orsId` (server-owned string); `siteId` (int)	**Partial.** The guidance says the regulator generates the ID on accreditation, unique to that operator. OJ allocates `orsId` itself for sites added in an application (`UpdateIfOrsIdAbsentAsync`); whether those match the regulator-issued ones was not established. Keep it a string (`001` is no longer reduced to `1`, template change of 19 Jan 2026).
ORS name	ORS	Summary log `OSR_NAME`	UC5	Current	Served	Overseas-site `name`	OJ `siteName`; CM payload copy	**OK.**

Field	Level	Meaning	Used by	History needed	Served by ReEx route today	In ReEx (stored)	In OJ / CM	Gap / notes
ORS country	ORS	Summary log `OSR_COUNTRY` (drop-down, for example `Vietnam-VN`)	UC5	Current	Served	Overseas-site `country` (free string)	OJ `country` (free text such as `Germany`); CM payload copy	**Partial.** The template's value format (name plus code) differs from what either system stores; no mapping exists.
ORS address, coordinates	ORS	Location of the site	UC3	Current	Served	Overseas-site `address` (`line1`, `line2`, `townOrCity`, `stateOrRegion`, `postcode`), `coordinates`	OJ `siteAddress`, `addressLine1/2`, `townOrCity`, `coordinates`; CM payload copy	**OK.** ReEx-seeded sites carry only name, address, coordinates and approval date into OJ, so other details can be missing there (RA-597).
ORS isEu / isOecd	ORS	EU or OECD country	UC5	Current	Not held	Not held (the overseas-site schema has no such flag)	OJ `isEu`, `isOecd`; CM payload copy	**OK** in OJ and CM; not in ReEx. Drives whether BES evidence is required.
ORS approval	ORS	Approved for this accreditation, and the date	UC5	Point-in-time	Served (`approvedOn`, the same for every accreditation year)	Overseas-site `validFrom` (one nullable date per site). ReEx checks the site is approved at Date of export (`isOrsApprovedAtDate`)	OJ `validFrom` (raw ReEx ORS-A approval date) and `selected` (**checked**)	**Partial.** One date per site, not per accreditation year, and no end. In OJ, `selected` is inclusion in an application, not approval, and a site added in an application has no approval date.
ORS approvalEnd	ORS	End of a site's approval	UC5	Point-in-time	Not held	Not held	Not held	**Gap.**
ORS Basel codes and operations	ORS	Summary log `BASEL_EXPORT_CODE`; what the site does	UC3, UC5	Current	Not held	Not held. The summary log row's Basel code is validated as a value, not against a site	OJ `code1/2/3`, `operationCodes`, `repatriatedLoads`, `conditionsOfExport`; CM can correct `operationCodes` (audited)	**Partial.** Operator-entered in OJ only.
ORS BES evidence	ORS	Broadly equivalent standards evidence	UC3, UC5	Point-in-time	Not held	Only the uploaded forms, as `orsFileUploads` file links on the registration and accreditation; no dates	OJ `besEvidence.besEvidenceUploads[]` with `besEvidenceValidFromDate`, `besEvidenceExpiryDate`	**Partial.** Validity periods exist in OJ only; file metadata only, files in S3. For steel and aluminium exported outside the EU to a non-OECD country, an exporter who agrees the log's conditions need not submit BES evidence but must still hold it, so an absent upload is not always a gap.
interimSite ID	Interim site	Summary log `INTERIM_SITE_ID`: 3-digit code	UC5	None	Not held	Not held. ReEx only checks the row's ID has three digits when `DID_WASTE_PASS_THROUGH_AN_INTERIM_SITE` is Yes; it has no interim-site records	OJ `interimSites[].siteNumber` (string, `001` style); `siteId` (int)	**Partial.** In OJ only. The guidance says the regulators provide the ID during accreditation; OJ allocates `siteNumber` itself (`UpdateIfInterimSiteNumberAbsentAsync`).
interimSite details	Interim site	Name, address, country, contact, operations (R12/R13)	UC3, UC5	Current	Not held	Not held	OJ `interimSites[]`: `siteName`, address, `country`, contact, `operationCodes`	**OK** in OJ only.
interimSite active period	Interim site	When the interim site was added and removed, and approved	UC5	Point-in-time	Not held	Not held	OJ `createdAt`, `removedAt` (null means active; soft delete)	**Gap** for approval. **Partial** for an active period: `createdAt` is when the operator entered it and is null on legacy documents.

PRN tonnage band and signatories

Field	Level	Meaning	Used by	History needed	Served by ReEx route today	In ReEx (stored)	In OJ / CM	Gap / notes
tonnageBand	Accreditation	Tonnage band (register: Up to 500, Up to 5,000, Up to 10,000, Over 10,000 tonnes)	UC1, UC2, UC3, UC6	Point-in-time	Not served, held	Accreditation `prnIssuance.tonnageBand` (required). The register and PRN tonnage monitoring read it from the registration's resolved accreditation	OJ `prns.plannedTonnageBand` (UpTo500, UpTo5000, UpTo10000, Over10000); CM payload copy	**OK** in ReEx (one band per accreditation record). **Partial** in OJ and CM: the operator's **planned** band, not necessarily the approved one. Labels map one-to-one to the register's.
tonnageBand history	Accreditation	Earlier bands and when each applied	UC6	Full history	Not held	One band per accreditation record (one per year per registration)	OJ `prns.versions[]` (snapshot at each submit and resubmit, `versionedAt`; never returned by the API)	**Partial.** A band per year, not per day; OJ's snapshots carry a submission time, not an effective date.
signatories	Accreditation	People authorised to sign PRNs	UC7	Point-in-time	Not served, held	Accreditation `prnIssuance.signatories[]` (name, email, phone, job title; at least one). The org's `users[]` gets signatories' name and email with roles from the accreditation's current status	OJ `prns.authorisers[]` (`fullName`, `email`, `isNew`); CM payload copy	**Partial.** No identifier ties a person to a sign-in in any system. OJ and CM hold name and email only (no job title or phone). ReEx's PRN route infers the signatory actor from the PRN's status, "until the auth system carries actor identity".
signatory authorised period	Accreditation	When each person was authorised and when that ended	UC7	Point-in-time	Not held	Not held (ReEx signatories carry no dates)	Not held; OJ history only in `prns.versions[]` (submission time)	**Gap.** With one accreditation record per year, "signatory for the accreditation" is answerable per year, not per day.

Field	Level	Meaning	Used by	History needed	Served by ReEx route today	In ReEx (stored)	In OJ / CM	Gap / notes
prnIssuanceGate	Accreditation	Whether PRNs may be issued now	UC6, UC7, UC9	Current	Not served; logic is in ReEx's backend	ReEx blocks PRN issuing while the accreditation is `suspended` or `cancelled` (`issuanceRefusal`), using the current status	Not derivable	**OK** in ReEx (current status, not as at a date). **Gap** in OJ and CM.

Business plan, reports and annual reporting

Field	Level	Meaning	Used by	History needed	Served by ReEx route today	In ReEx (stored)	In OJ / CM	Gap / notes
businessPlan	Accreditation	Planned split of PRN income across seven categories, each with a description and an explanation	UC8	Point-in-time (the plan for the year reported)	Not served, held	Accreditation `prnIssuance.incomeBusinessPlan[7]` (`percentIncomeSpent`, `usageDescription`, `detailedExplanation`); stored, read by nothing beyond the forms ingest	OJ `businessPlan`: seven `*Percent` ints, seven `*Detail` strings; CM payload copy	**Partial.** Percentages only, no amounts. In OJ, one plan per application year, with `versions[]` snapshots.
report submission dates	Accreditation	Date each monthly or quarterly report was submitted (register: Jan to Sep and Q1 to Q3 columns; `N/A` where not due)	UC1, UC8	Full history	Not served	Reports module: periodic reports with `submittedAt` per period and submission number; the register shows the original submission date. Cadence is monthly when the registration has an accreditation number, otherwise quarterly	Not held	**OK** in ReEx.
actual activity	Accreditation	PRNs issued, income received and spent in the year	UC8	Full history	Not served	Reports: PRN `issuedTonnage`, `averagePricePerTonne`, `totalRevenue`, `freeTonnage`; recycling and export activity tonnages (suppliers, overseas sites, refused, stopped, repatriated)	Not held	**Partial.** Income (`totalRevenue`) and tonnages are held in ReEx; spend by business plan category is not (no field), so UC8's plan-versus-actual comparison cannot be made. The waste balance module was not read.
complianceIssuesReported	Application	Count of compliance issues reported	UC8, UC3	Current	Not served	Not seen	CM `payload.complianceIssuesReported` (written by OJ at submit)	**Partial.** Where OJ takes the value from was not traced.

What ReEx's route does not serve today, by use case

Use case	Needs that the route does not serve
UC1 Public register	Companies House number, registered office, tonnage band and Active Date (`validFrom`) are held but not served; permits not served; report submission dates (reports module) not served. Annex II is derivable from material. The register's "Date status last changed" is the last raw `statusHistory` entry, which the served timeline can shift.
UC2 Operator dashboard	Contacts not served; application status for unapproved records not served; anything held only in OJ and CM.
UC3 Regulator dashboard	Contacts, permits, `approvedPersons` not served; ORS detail beyond name, address and coordinates; applications.
UC4 Accreditation status at a date	The route serves a status timeline, but not the accreditation `validFrom` / `validTo` window that ReEx's own validation uses. OJ and CM hold neither.
UC5 ORS and interim sites at a date	Per-site `approvedOn` is served (one date, no end, the same for every year). Interim sites, Basel codes, EU/OECD flags and BES evidence are not held in ReEx.
UC6 Tonnage band at issue	Tonnage band held but not served.
UC7 Signatory at signing	Signatories held but not served; authorised period not held.
UC8 Annual reporting	Business plan held but not served; report data not served; spend by category not held.
UC9 Status management	Registration and accreditation `statusTimeline` are served. OJ and CM cannot record suspend or cancel.

Gaps (for a separate ticket on how to source them)

Held in none of the three systems

- ORS approval end date, and approval per accreditation year (ReEx and OJ hold one `validFrom` per site).
- Regulator approval of an interim site, and an approval date for it (ReEx holds no interim-site records at all; OJ holds only what the operator entered).

- Signatory authorised period at day level; an identifier tying a signatory to a sign-in.
- Spend by business plan category (reports hold income and tonnage, not spend).

Held in ReEx but not in OJ or CM (matters if OJ or CM data has to serve these)

- Accreditation `validTo`, a start date that can be mid-year, and suspended or cancelled status with its history.
- The summary log and PRN issuing logic that depends on those.
- Trading name, `approvedPersons`, signatory job title and phone, registration status and start date.
- Reports (including submission dates) and PRNs.

Held in OJ or CM but not in ReEx

- ORS EU/OECD flags, Basel codes, operations and BES validity periods.
- Interim site records.
- Application lifecycle status, withdrawal reason and the CM audit log.

Held, but not good enough

- OJ and CM copies of organisation and registration data are seed-time snapshots.
- ReEx's served `statusTimeline` is built from `statusHistory` and moves the approval to `validFrom` ("until ADR-0051's events exist"), so it is not the raw history.
- Glass is `glass` plus a process flag in every stored source; the split is derived.
- ORS and interim site IDs are allocated by OJ; the guidance says the regulator issues them. The country value format differs from the summary log's.
- The operator's planned tonnage band (OJ, CM) is not necessarily the approved band.

Not examined

- The waste balance module, the forms-ingest transformation, PRN stored fields beyond status, and live data in either system.

Held, but unreachable (OJ)

- `prns.versions[]`, `previousSites` and the other `versions[]` are never returned by the API; the CM audit log is a display log, not a query surface.

Open questions (not assumed anywhere above)

1. **Which years is each system the authority for?** The team's understanding is that ReEx holds accreditation data up to 2026 and OJ and CM hold 2027 onwards. Neither data model says so, so the table does not rely on it. If it holds, the "Held in ReEx but not in OJ or CM" gaps become gaps for 2027 onwards.
2. **Where do PRNs, reports and summary logs for later accreditations live?** The ReEx code has those modules; nothing in the data models says how an accreditation held only in OJ and CM reaches them.
3. **Should the API serve OJ and CM data as well as ReEx's?** Several rows depend on it.