# Block Level and Inline Elements

**Block-level elements:**

- Block-level elements are those that create a "block" or a new line in the document flow.
- They typically start on a new line and take up the full width available, extending horizontally to the left and right edges of their containing element.
- Examples of block-level elements include **‹div›, ‹p›, ‹h1› to ‹h6›, ‹ul›, ‹ol›, ‹li›, ‹table› etc.**

**Inline elements:**

- Inline elements, on the other hand, do not start on a new line and only take up as much width as necessary.
- They flow within the content and do not create new blocks within the document flow.
- Examples of inline elements include **‹span›**, **‹strong›**, **‹em›** etc.

Let us learn about an important block-level tag i.e ‹div› tag.

**‹div›**

‹div › element is a block-level container that is commonly used to group together other HTML elements and apply styles or layout to them. It doesn't have any specific semantic meaning on its own, but it's useful for organising and structuring the content on a web page. Tag is used to contain other HTML elements. It is a block element, that means it blocks the entire width and also inserts a line break before and after.

**Syntax**

```
<div>
  <!-- Content goes here -->
</div>
```

You can also place more than one element in a single ‹div› element.

| HTML Code | Output |
|---|---|
| <br><h1>This is a Div Example</h1><br> div1:This is some content inside a div. <br><ul><br><li>Item 1</li><br><li>Item 2</li><br><li>Item 3</li><br></ul><br> <br><br> <br> div2:This is some content inside another div. <br> | **This is a Div Example**<br>**div1:**This is some content inside a div.<br>• Item 1<br>• Item 2<br>• Item 3<br>**div2:**This is some content inside another div. |

Above code will create two divisions in your page. The first  will have an <h1> tag, a  tag, a  tag and an unordered list (<ul>) with three list items. The second  will have a  tag with .

Let us learn about an important inline tag i.e  tag.

****

The  element is an inline-level container used to apply styles or manipulate specific parts of text within a larger block of content. Like the , it doesn't have any inherent semantic meaning.

| HTML Code | Output |
|---|---|
| <body><br> This is a blue word in a sentence. <br></body> | This is a blue word in a sentence. |

The code showcases the usage of headings, paragraphs, and the  tag to highlight specific portions of text, emphasising the "magic of span tag" and its utilisation of global attributes for formatting.