Creating Buttons

What are Buttons?	
Buttons are commonly used in forms, dialog boxes, and various user interface components to facilitate user interactions on a webpage. Let us learn how to create buttons on a web page.	***Alt text:*** *Various Types of Buttons*

The <button> tag is used to create clickable buttons. You can put anything inside a button element like text, image, or any other tag.

Syntax

```
<button>Any Text</button>
```

Create a Button

HTML Code	Output

`<body>`
`  <h2> Button</h2>`
`  <button>Click me</button>`
`</body>`
	Button
	click me

Attributes of <button> Tag:

To style the buttons we can use following attributes:

a. Name
b. Type
c. value
d. disabled

a. **name**- Specifies a name for the button. This attribute is used to identify the button in the context of a form. It is typically used when multiple buttons are present within a form, allowing you to distinguish between them.

b. **type**- Specifies the type for the button. Common values for the type attribute are Submit, Reset, and Button.
   - button: (default) A standard button.
   - submit: A button that submits the form data to the server.
   - reset: A button that resets the form to its default values.

c. **value**- Specifies an initial value for the button.

d. **disabled**: If present, the button is disabled and cannot be clicked. This attribute does not need a value; its presence alone disables the button.

Let us see how to use the attributes of button through code:

HTML Code	Output
<body> <h2> Button</h2> <button type="button" name="myButton" value="Click me">Click me</button><html lang="en">> </body>	**Button** Click me

Note: To disable a button in HTML, you can use the disabled attribute.
<button disabled>Disabled Button</button>

Buttons in HTML: Integration of Images

You can also include an image inside the button along with the text.

HTML Code	Output

`<!DOCTYPE html>`
`<html lang="en">`
`<head>`
`  <title>Button Example</title>`
`</head>`
`<body>`
 	
`  <!-- Button with text -->`
`  <button>Click me</button>`
 	
`  <!-- Button with an image -->`
`  <button>`
`  <img src="icon.png" alt="Button Icon"> Click here to Download`
`  </button>`
`</body>`
`</html>`	

```
<button>Click me</button>
```

This line creates a button with the text "Click me". When clicked, this button can perform various actions, such as submitting a form or triggering JavaScript code (though no specific action is defined in this code).

```
<button>
  <img src="icon.png" alt="Button Icon"> Click here to Download
</button>
```

This creates another button that contains an image (**icon.png**) along with text content ("Click here to Download"). When clicked, this button can also perform actions, but none are specified in this code.