Embedding Content

Embedding content involves integrating external elements, such as videos, audio, maps, or other HTML documents, seamlessly within a webpage.

Embedding Audio

To embed audio content on a web page using HTML, you can use the <audio> tag, specifying the audio file's source using the "src" attribute.
<audio> -The <audio> tag is used to embed audio content on a web page.

Syntax:

```
<audio controls>
   <source src="audiofile.mp3" type="audio/mp3">
   Your browser does not support the audio element.
</audio>
```

Attributes:

- **src**: Specifies the URL of the audio file to be embedded.
- **controls**: Adds playback controls (play, pause, volume, etc.) to the audio player.
- **autoplay**: Automatically starts playing the audio when the page is loaded.
- **loop**: Specifies that the audio will start over again, every time it is finished.
- **preload**: Specifies whether the audio should be loaded when the page loads. It can take values such as "auto", "metadata", or "none".
- **muted**: Specifies that the audio output should be muted by default.
- **volume**: Specifies the default volume of the audio player, ranging from 0.0 to 1.0.
- **type**:The 'type' attribute specifies the **MIME** type of the media file.

Note: Within the <audio> tag, you can use one or more <source> tags to specify different audio files in different formats. This allows the browser to choose the most suitable format based on its capabilities.

Embedding Video

<video>-The <video> tag is used to embed video content on a web page.

Syntax:

```
<video width="640" height="360" controls>
       <source src="videofile.mp4" type="video/mp4">
         Your browser does not support the video element.
</video>
```

Attributes:

- **src**: Specifies the URL of the video file to be embedded.
- **controls**: Adds playback controls (play, pause, volume, etc.) to the video player.
- **autoplay**: Automatically starts playing the video when the page is loaded.
- **loop**: Specifies that the video will start over again, every time it is finished.
- **preload**: Specifies whether the video should be loaded when the page loads. It can take values such as "auto", "metadata", or "none".
- **muted**: Specifies that the video output should be muted by default.
- **poster**: Specifies an image to be displayed while the video file is downloading, or until the user hits the play button.
- **width**: Specifies the width of the video player.
- **height**: Specifies the height of the video player.
- **autoplay**: Specifies that the video will start playing automatically, without requiring any user input.

Note: The <source> tag specifies the source file and its type.

Embedding Audio and Video

HTML Code

```
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width,
initial-scale=1.0">
    <title>Audio and Video Example</title>
 </head>
 <body>
     <h2>Embedded Audio</h2>
```

```
    <audio controls>
       <source src="audio/sample.mp3" type="audio/mp3">
       Your browser does not support the audio element.
    </audio>
     <h2>Embedded Video</h2>
    <video width="640" height="360" controls>
       <source src="video/sample.mp4" type="video/mp4">
       Your browser does not support the video element.
    </video>
  </body>
```

NOTE: Make sure to replace "audio/sample.mp3" and "video/sample.mp4" with the actual paths to your audio and video files. This code will create a simple webpage with embedded audio and video elements, allowing users to play and control the media. The text "Your browser does not support the audio/video element." is placed after the <source> tag. If the browser cannot play the specified audio/video file, it will display this message as **fallback** content.

Embedding iframes

iframes:

An <iframe> (Inline Frame) is an HTML element used to embed another HTML document or external content within the current HTML document. It allows you to include content from another source, such as a different webpage or media, seamlessly within your page.

Syntax:

```
<iframe src="url-to-external-content" width="600"
height="400" frameborder="0" allowfullscreen></iframe>
```

Attributes:

- **src (source):** Specifies the URL of the content you want to embed within the iframe.
- **width and height:** Set the dimensions (width and height) of the iframe.
- **frameborder**: Defines whether or not to display a border around the iframe. A value of "0" means no border.
- **allowfullscreen:** Enables the iframe to be displayed in fullscreen mode. This is often used for embedded videos.

Embedding an External Website

HTML Code	Output