Heading and Paragraphs

Heading tags- Headings are used to define headings of a page. In HTML you will have six levels of headings h1 to h6. Tag for the headings are <h1></h1>, ------<h6></h6>. Every tag displays the heading in a different style and font size.

H1 heading will be of highest font size and h6 will be of lowest font size.

Syntax:

<h1>this is my first heading</h1>

```
<body>
  <h1>This is most important
heading</h1>
        <h2>This is
subheading</h2>
        <h3>This is Sub-
subheading</h3>
        <h4>This is Sub-sub
subheading</h4>
        <h5>This is Sub-Sub-sub
subheading</h5>
        <h6>This is least
important heading</h6>
</body>
```

This is most important heading

This is subheading

This is Sub-subheading

This is Sub-sub subheading

This is Sub-Sub-sub subheading

This is least important heading

The code represents a basic structure of a webpage's body with hierarchical headings. It includes heading tags **<h1>** to **<h6>** indicating different levels of importance, with **<h1>** being the most important and **<h6>** being the least important. The content within each heading tag corresponds to the respective level of heading.

Paragraph- tag is used to create paragraphs. Whatever you will write between

 tags will be displayed in a single line.

Syntax:
this is my first paragraph

HTML Code	Output
this is my first paragraph This is my first paragraph	this is my first paragraph This is the second line

The code contains two sentences within a single paragraph defined by ** ** tags, and to separate them into distinct paragraphs, you can use two separate ** ** tags.

Attributes of heading, and tags-

In HTML 5 the attributes of headings and paragraph tags are the same. Let us see the attributes.

a. class
b. id
c. style
d. title

a. class- The class attribute in heading tags and the tag assigns names to them, making it easy to style or apply behaviours to multiple headings and paragraphs with the same name. This helps maintain a consistent design and makes web development more efficient by applying the same styles or behaviours to all elements sharing a class. For example,

```
<h1 class="main-heading">Main Heading</h1>

<p class="intro">This is an introductory paragraph</p>
```

Every <h1> element on the web page will be marked with the class "main-heading," and each element will be identified with the class "intro." These class designations will be utilised for applying styles to these specific elements.

b. id- The "id" attribute acts like a special name for tags, such as <h1> and <p>. It helps create links to that specific tag within the same or different pages. This unique identifier makes it easy to refer to and identify particular elements, improving organisation and navigation on a website.

```
<h1 id="section-heading">Section Heading</h1>

<p id="first-para">First Paragraph</p>
```

c. style- The "style" attribute in HTML gives precise instructions to elements. Specifically, useful for headings (<h1>) and paragraphs (<p>), it allows customization of their appearance, covering colour, size, and alignment. You can use multiple properties with the same style tag and they should be separated by a semicolon (;) between them.

```
<h1 style="color: blue; font-size: 24px;">Styled Heading</h1>

<p style="text-align: center; line-height: 1.5;">This is a styled paragraph. </p>
```

Syntax

<tagname style="property:value;">

- **tagname**: The HTML tag for the element you want to style.
- **property**: The property you want to apply for.
- **value**: The value for the specified property.

<h1 style="color: blue" > this is first heading</h1>

Tag Attribute Property value

d. title- The "title" attribute can be employed to offer a brief description. This information is displayed when the user **hovers** the mouse pointer over the element, providing context or supplementary details.

```
<h1 title="Important Heading">Main Heading</h1>
<p title="Note">Important Note here. < /p>
```


 Tag

It is used to insert line breaks within the paragraph. It does not have the closing tag. Insert this tag where ever you want to insert the line break.

HTML Code	Output
`<body>` `  <p>this is my first paragraph` `  This is the second line but will not have a line break and  ` `  This is the third line</p>` `</body>`	this is my first paragraph This is the second line but will not have a line break and This is the the third line

<hr> Tag

It typically displays a horizontal line across the width of its containing element. It is often used to separate different sections of content. It is an empty tag. You can change the colour, width, and style of the line using CSS.

`<p>This the first paragraph</p>`
`<hr>`
`<p>This is the second paragraph</p>`
	This the first paragraph
	--- 	
	This is the second paragraph

Comment

HTML code comments are used to include notes or annotations that are not displayed on the webpage but provide information for developers or anyone else looking at the code.

Comments can be added by using <!-- and -->.
or

```
<!--
 This is a multi-line comment in HTML.
 It allows you to add comments that span multiple lines.
 Comments are not displayed and are used for documentation.-->
```

HTML Code	Output
<body> <h1>This is most important heading</h1> <!—single line comments--> <!-- <h2>This is subheading</h2> <h3>This is Sub-subheading</h3> <h4>This is Sub-sub subheading</h4> <h5>This is Sub-Sub-sub subheading</h5> <h6>This is least important heading</h6>--> </body>	**This is most important heading**

The code that is enclosed in between <!-- --> are not displayed on screen.