Reliance Foundation

N·S·D·C
RE IMAGINE FUTURE

Text Formatting

< Tags >

Text Formatting Tags

Text formatting tags in HTML are used to modify the appearance of text on a web page.

HTML provides a variety of text formatting tags like the bold tag or ‘b’), the italic tag ('i') , the underline tag ('u') and the strong tag ('strong'), that allow you to control the appearance and structure of text content on a web page.

‹b›

‹sub›

‹i›

‹s›

‹strong›

‹u›

‹sup›

<b> – Bold

b tag is used to enclose text that should be displayed in bold.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Job Information</title>
</head>
<body>
    <h1>Job Details</h1>
    <p><b>JOB TITLE: </b>Software
Engineer</p>
    <p><b>Department:
</b>Engineering</p>
</body>
</html>
```

<!DOCTYPE html> is the document type declaration and it defines the document type and version of HTML being used. In this case, it indicates that the document is an HTML5 document.

In this code snippet, b tag is used to write the text in bold font.

<b> – Bold

b tag is used to enclose text that should be displayed in bold.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Job Information</title>
</head>
<body>
    <h1>Job Details</h1>
    <p><b>JOB TITLE: </b>Software
Engineer</p>
    <p><b>Department:
</b>Engineering</p>
</body>
</html>
```

<html lang="en"> tag defines the root element of the HTML document. The lang attribute specifies the language of the document, in this case, it's set to English.

<b> – Bold

b tag is used to enclose text that should be displayed in bold.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Job Information</title>
</head>
<body>
    <h1>Job Details</h1>
    <p><b>JOB TITLE: </b>Software
Engineer</p>
    <p><b>Department:
</b>Engineering</p>
</body>
</html>
```

Head section contains meta-information about the HTML document, such as character set, title, styles, and more.

<b> – Bold

b tag is used to enclose text that should be displayed in bold.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Job Information</title>
</head>
<body>
    <h1>Job Details</h1>
    <p><b>JOB TITLE: </b>Software
Engineer</p>
    <p><b>Department:
</b>Engineering</p>
</body>
</html>
```

meta tag declares the character encoding for the document. In this case, it's set to UTF-8, which is a widely used character encoding that supports a wide range of characters.

<b> – Bold

b tag is used to enclose text that should be displayed in bold.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Job Information</title>
</head>
<body>
    <h1>Job Details</h1>
    <p><b>JOB TITLE: </b>Software
Engineer</p>
    <p><b>Department:
</b>Engineering</p>
</body>
</html>
```

This is a paragraph element (<p>) containing text. Within the paragraph, there is a bold (<b>) element used to make the text "JOB TITLE:" bold, and then the actual job title "Software Engineer" follows.

<b> – Bold

b tag is used to enclose text that should be displayed in bold.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Job Information</title>
</head>
<body>
    <h1>Job Details</h1>
    <p><b>JOB TITLE: </b>Software
Engineer</p>
    <p><b>Department:
</b>Engineering</p>
</body>
</html>
```

Similar to the previous line, this paragraph contains information about the department. The department name "Engineering" is presented following the bolded label "Department:"

Reliance Foundation

N·S·D·C RE IMAGINE FUTURE

Tag	Purpose	Name	Code	Output
****	Converts enclosed text to bold	Bold	Developers	**Developers**
****	Converts enclosed text to italics	Italic	Developers	*Developers*
<u>	underlines the enclosed text	Underline	<u>Developers</u>	Developers
<del>	strikes through the enclosed text	Delete Text	<del>Developers</del>	~~Developers~~
<sub>	displays text as subscript	Subscript	Dev_{elopers}	Dev$_{\text{elopers}}$
<sup>	renders text as superscript	Superscript	^{Dev}elopers	^{Dev}elopers