

GoLangExam1

Name: Abouelfetouh Ashraf Moussa

Question 1 : What is the output?

1-

```
func main() {  
    ch := make(chan int, 3)  
    ch <- 1  
    ch <- 2  
  
    fmt.Println(len(ch), cap(ch))  
  
    <-ch  
    fmt.Println(len(ch), cap(ch))  
  
    ch <- 3  
    ch <- 4  
    fmt.Println(len(ch), cap(ch))  
}
```

2 3

1 3

3 3

2-

```
func main() {  
    ch := make(chan int, 3)  
    ch <- 10  
    ch <- 20  
    ch <- 30  
  
    for v := range ch {  
        fmt.Println(v)  
    }  
    fmt.Println("after loop")  
}
```

10

20

30

error: deadlock!

Because we not use close(ch) to end channel waiting
wait

3-

```
func main() {  
    var a chan int  
    defer func() { fmt.Println("recovered:", recover()) }()  
    close(a)  
}
```

runtime error

Closing a nil channel causes a runtime panic.

Question 2 : Write Go Lang Code To Solve These Problems:

Answer will be files in Question 2 folder next to that pdf

1. Given a slice `nums []int` and a window size `k`, return a slice of the maximum value in each window of size `k` as it slides from left to right.

Input: `nums = [1,3,-1,-3,5,3,6,7], k = 3` → **Output:**
`[3,3,5,5,6,7]`

```
sliding_window_max.go
```

2- Given a list of words, group the anagrams together.

Input: `["eat","tea","tan","ate","nat","bat"]`

Output: `[["eat","tea","ate"],["tan","nat"],["bat"]]`

ANSWER : `group_anagrams.go` File

```
group_anagrams.go
```

3 - Define a `Student` struct (name, id, grades map). Implement:

- A method `Average() float64`
- A function `TopStudent(students []Student) *Student` returning a pointer to the student with the highest average.

```
student_grades.go
```

4- Implement `sort.Interface` for a `ByAge []Person` type to sort people by age. Then implement a custom `Ranker` interface to sort any rankable collection.

```
sort_interface_demo.go
```

5-Retry with Exponential Backoff .

Write `Retry(times int, fn func() error) error` that calls `fn` up to `times` times, returning the last error if all attempts fail. Wrap the final error with `fmt.Errorf("after %d attempts: %w", ...)`.

retry.go

6-If a goroutine panics and nothing recovers it, what happens to the program?

The whole program crashes — `recover` only works in the goroutine where the panic occurred. Write a worker pool where each worker recovers its own panics and reports them on an error channel.

worker_pool_recover.go

7-Implement a rate limiter that allows at most `rate` operations per second using `time.Ticker`, and process 20 tasks through it.

ticker_rate_limiter.go

8-Split a large slice into N chunks, sum each in its own goroutine using

`sync.WaitGroup`, and combine the results. `func`

`ParallelSum(nums []int, workers int) int`

parallel_sum.go

Question 3 : Mini Project?

Answer will be in Question 3 folder next to that pdf

- `Task` struct with `ID`, `Name`, `Payload map[string]any`, and `Priority int`.

mini_project_task.go

- A `Handler interface` (`Handle(ctx context.Context, t Task) error`) with at least 3 implementations (e.g. `EmailHandler`, `ResizeImageHandler`, `ReportHandler`), registered in a `map` keyed by task type.

Still work on

- A **worker pool** consuming tasks from a **channel**, with a configurable number of workers and graceful shutdown using `context`.

Still work on

- Handlers sometimes return errors; use **custom error types** and **wrapping**. Failures with `RetryableError` are retried up to 3 times.

Still work on

- Handlers sometimes **panic**; recover them per task so one bad task never kills a worker, and convert them to errors.

Still work on

- Collect results into a **slice** and print a summary: succeeded, failed, retried, and panicked counts, plus average duration.

Still work on

- Protect shared stats with a mutex or atomics.



