CS 341 Assignment 3

Devansh Jain, 190100044

September 11, 2021

Contents

1 5 Stage, without forwarding or hazard detection

Code

```
.text

main:
    addi s0 zero 5
    add s1 s0 zero
```

Behaviour

Expectation: At the end of the program, we expect registers `s0` and `s1` to have value 5.
Reality: At the end of the program, only register `s0` has value 5. (`s1` is default to 0)

Explanation

The incorrect value is due to data hazard.
To be more specific, we face a **read-before-write (RAW) data hazard**.
`addi s0 zero 5` writes to register `s0` in WB stage during 4th cycle.
`add s1 s0 zero` reads from register `s0` in ID stage during 2nd cycle.
The value read here is not updated yet causing the incorrect computation.

Screenshots



Figure 1: Without hazard detection; Without forwarding;



Figure 2: With hazard detection; Without forwarding;

2 5 Stage, without forwarding, with hazard detection

a.

Code

```
.text

main:
    addi s0 zero 5
    add s1 s0 zero
```

Behaviour

At the end of the program, we expect registers `s0` and `s1` to have value 5.
Without forwarding, we observe that ID for second instruction takes 3 cycles (2 stalls).
There are no stalls with forwarding.

Screenshots



Figure 3: With hazard detection; Without forwarding;



Figure 4: With hazard detection; With forwarding;