

FACE Prep

Operating System - Coding | REC | 3 Feb

Back To Practice

Completed

First-Come,First-Served CPU Scheduling Algorithm

Write a C program to implement the First-Come, First-Served (FCFS) CPU Scheduling Algorithm. The program should take the number of processes, their Arrival Times (AT), and Burst Times (BT) as input. Calculate and display the Completion Time (CT), Turnaround Time (TAT), and Waiting Time (WT) for each process, along with the Average Turnaround Time and Average Waiting Time.

To evaluate the performance of the algorithm, we use the following formulas:

- **Completion Time (CT):** The time at which a process finishes execution.
- **Turnaround Time (TAT):** Total time taken from arrival to completion.
- $TAT = CT - AT$
- **Waiting Time (WT):** The time a process spends waiting in the ready queue.
- $WT = TAT - BT$

Input Format

1. The first input line contains an integer representing the number of processes.
2. The next lines contain two integers for each process, where the first integer represents the Arrival Time (AT) and the second integer represents the Burst Time (BT).

Output Format

The output displays the Average Turnaround Time and the Average Waiting Time.

Select Language : C (GCC 9.2.0)

```
1 #include <stdio.h>
2
3 int main() {
4     int n, i;
5
6     printf("Enter number of processes: \n");
7     scanf("%d", &n);
8
9     int AT[n], BT[n], CT[n], TAT[n], WT[n];
10
11     for(i = 0; i < n; i++) {
12         printf("Enter Arrival Time and Burst Time for P%d: \n", i+1);
13         scanf("%d %d", &AT[i], &BT[i]);
14     }
15
16     CT[0] = AT[0] + BT[0];
17
18     for(i = 1; i < n; i++) {
19         if(CT[i-1] < AT[i]) {
20             CT[i] = AT[i] + BT[i]; // CPU idle case
21         } else {
22             CT[i] = CT[i-1] + BT[i];
23         }
24     }
25
26     float totalTAT = 0, totalWT = 0;
27
28     for(i = 0; i < n; i++) {
29         TAT[i] = CT[i] - AT[i];
30         WT[i] = TAT[i] - BT[i];
31
32         totalTAT += TAT[i];
33         totalWT += WT[i];
34     }
```

Test Cases 2

Custom Test Case

Custom Test

Run Sample Cases

Run All Cases

Ask Gemini

Devyesh

To easily get back to sites that you've visited, sync your history and tabs to devyesh1211@gmail.com

Turn on

Save 1 item in account

Passwords and autofill

Manage your Google Account

Customise profile

Your account in Chrome

Sign out of Chrome

Other Chrome profiles

DILLIBABU (rajalakshmi.edu.in)

Add Chrome profile

Open guest profile

Manage Chrome profiles

Success

FACE Prep

Operating System - Coding | REC | 3 Feb

Back To Practice

Completed

Non-Preemptive Shortest Job First CPU Scheduling Algorithm

Write a C program to implement the Non-Preemptive Shortest Job First (SJF) CPU Scheduling Algorithm. The program should accept the number of processes, their Arrival Times (AT), and Burst Times (BT). At any given time, the process with the minimum burst time among the arrived processes must be executed first. Calculate the Completion Time (CT), Turnaround Time (TAT), and Waiting Time (WT) for each process and find the overall average TAT and WT.

Core Logic

Selection: Out of all processes that have arrived by the current time, the one with the minimum Burst Time is chosen.

Formulae:

- \$Turnaround Time (TAT) = Completion Time (CT) - Arrival Time (AT)\$
- \$Waiting Time (WT) = Turnaround Time (TAT) - Burst Time (BT)\$

Input Format

- The first line of input contains an integer representing the number of processes.
- The next lines contain two integers for each process, where the first integer denotes the Arrival Time (AT) of the process and the second integer denotes the Burst Time (BT) of the process.

Output Format

The output displays the Average Turnaround Time and the Average Waiting Time.

Select Language : C (GCC 9.2.0)

```
1 #include <stdio.h>
2 #include <limits.h>
3
4 int main() {
5     int n, i, completed = 0, currentTime = 0, shortest;
6
7     printf("Enter number of processes: \n");
8     scanf("%d", &n);
9
10    int AT[n], BT[n], CT[n], TAT[n], WT[n];
11    int isCompleted[n];
12
13    for(i = 0; i < n; i++) {
14        printf("Enter Arrival Time and Burst Time for P%d: \n", i+1);
15        scanf("%d %d", &AT[i], &BT[i]);
16        isCompleted[i] = 0;
17    }
18
19    float totalTAT = 0, totalWT = 0;
20
21    while(completed != n) {
22        shortest = -1;
23        int minBT = INT_MAX;
```

Test Cases 2

Custom Test Case

> Custom Test

Sample Test Case

> Test Case - 1

> Test Case - 2

D

Devyesh

To easily get back to sites that you've visited, sync your history and tabs to devyesh1211@gmail.com

Turn on

Save 1 item in account

Passwords and autofill

Manage your Google Account

Customise profile

Your account in Chrome

Sign out of Chrome

Other Chrome profiles

DILLIBABU (rajalakshmi.edu.in)

Add Chrome profile

Open guest profile

Manage Chrome profiles

Back To Practice

Non-Preemptive Priority Scheduling algorithm

Write a C program to implement the Non-Preemptive Priority Scheduling algorithm. The program should accept number of processes their Arrival Time (AT), Burst Time (BT), and Priority for each process. The process with the highest priority (lowest numerical value) must be executed first among those that have arrived. Calculate the Average Waiting Time and Average Turnaround Time.

Input Format

The first line contains an integer representing the number of processes.

The next lines contain three integers for each process, where

- The first integer denotes the Arrival Time (AT)
- The second integer denotes the Burst Time (BT)
- The third integer denotes the Priority of the process.

A lower numerical value indicates a higher priority.

Output Format

The output displays the Average Turnaround Time and the Average Waiting Time.

Example 1

Sample Input 1

3
0 5 2

Select Language : C (GCC 9.2.0)

```
1 #include <stdio.h>
2 #include <limits.h>
3
4 int main() {
5     int n, i, completed = 0, currentTime = 0, highestPriority;
6
7     printf("Enter number of processes: \n");
8     scanf("%d", &n);
9
10    int AT[n], BT[n], Priority[n];
11    int CT[n], TAT[n], WT[n];
12    int isCompleted[n];
13
14    for(i = 0; i < n; i++) {
15        printf("Enter AT, BT and Priority for P%d: \n", i+1);
16        scanf("%d %d %d", &AT[i], &BT[i], &Priority[i]);
17        isCompleted[i] = 0;
18    }
19
20    float totalTAT = 0, totalWT = 0;
21
22    while(completed != n) {
23        highestPriority = -1;
```

Test Cases 2

Custom Test Case

> Custom Test

Sample Test Case

> Test Case - 1

> Test Case - 2



Devyesh

To easily get back to sites that you've visited, sync your history and tabs to devyesh1211@gmail.com

Turn on

- Save 1 item in account
- Passwords and autofill
- Manage your Google Account
- Customise profile
- Your account in Chrome
- Sign out of Chrome

Other Chrome profiles

DILLIBABU (rajalakshmi.edu.in)

- Add Chrome profile
- Open guest profile
- Manage Chrome profiles

FACE Prep

Operating System - Coding | REC | 3 Feb

Back To Practice

Completed

Round Robin CPU Scheduling Algorithm

Write a C program to implement the Round Robin (RR) CPU Scheduling Algorithm. The program should accept the number of processes, their Arrival Times (AT), Burst Times (BT), and a Time Quantum (TQ). The CPU should rotate through the processes in the ready queue, granting each a maximum of one TQ of execution time. Calculate the Completion Time (CT), Turnaround Time (TAT), and Waiting Time (WT) for each process and the overall averages.

Input Format

1. The first line of input contains an integer representing the number of processes.
2. The second line contains an integer representing the Time Quantum.
3. The next lines contain two integers for each process, where

- The first integer denotes the Arrival Time (AT)
- The second integer denotes the Burst Time (BT) of the process.

Output Format

The output displays the Average Turnaround Time and the Average Waiting Time.

Sample Input 1

3

2

0 5

1 3

Select Language: C (GCC 9.2.0)

```
1 #include <stdio.h>
2
3 int main() {
4     int n, tq;
5
6     printf("Enter number of processes: \n");
7     scanf("%d", &n);
8
9     printf("Enter Time Quantum: \n");
10    scanf("%d", &tq);
11
12    int AT[n], BT[n], CT[n], TAT[n], WT[n];
13    int remainingBT[n];
14    int i;
15
16    for(i = 0; i < n; i++) {
17        printf("Enter AT and BT for P%d: \n", i+1);
18        scanf("%d %d", &AT[i], &BT[i]);
19        remainingBT[i] = BT[i];
20    }
21
22    int completed = 0, currentTime = 0;
23
24    while(completed != n) {
25
26        int executed = 0;
27
28        for(i = 0; i < n; i++) {
29
30            if(AT[i] <= currentTime && remainingBT[i] > 0) {
31
32                executed = 1;
33            }
34        }
35    }
```

Test Cases 2

Custom Test Case

Run Sample Cases

Run All Cases

Devyesh

To easily get back to sites that you've visited, sync your history and tabs to devyesh1211@gmail.com

Turn on

Save 1 item in account

Passwords and autofill

Manage your Google Account

Customise profile

Your account in Chrome

Sign out of Chrome

Other Chrome profiles

DILLIBABU (rajalakshmi.edu.in)

Add Chrome profile

Open guest profile

Manage Chrome profiles