

Schema documentation for DR-GW-OrganisationBlock.xsd

november 5, 2024

Table of Contents

Namespace: "DR-GW-Interface/DR-GW-OrganisationBlock"	2
Schema(s)	2
Main schema DR-GW-OrganisationBlock.xsd	2
Element(s)	2
Element Org_Get	2
Element Org_Get / orgblockId	2
Element Org_GetList	3
Element Org_GetList / orgblockId	3
Namespace: "DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes"	4
Schema(s)	4
Imported schema DR-GW-OrganisationBlock.CommonTypes.xsd	4
Element(s)	4
Element typeOrganisationBlockId / orgblockId	4
Element typeOrganisationBlockIdNormal / id1	5
Element typeOrganisationBlockIdNormal / id2	5
Element typeOrganisationBlockIdNormal / id3	5
Element typeOrganisationBlockIdNormal / id4	5
Element typeOrganisationBlockIdNormal / id5	6
Element typeOrganisationBlockIdNormal / id6	6
Element typeOrganisationBlockId / orgblockIdSimple	6
Element typeOrganisationBlock / orgblockId	6
Element typeOrganisationBlock / alias	7
Complex Type(s)	7
Complex Type typeOrganisationBlockId	7
Complex Type typeOrganisationBlockIdNormal	7
Complex Type typeOrganisationBlock	8
Simple Type(s)	8
Simple Type typeOrganisationBlockIdSimple	8
Namespace: "DR-GW-Interface/CommonTypes"	9
Schema(s)	9
Imported schema CommonTypes.xsd	9
Element(s)	9
Element ct:typeRequest / ct:requestId	9
Element ct:typeResult / ct:responseCode	9
Element ct:typeResult / ct:sourceSystem	10
Element ct:typeResult / ct:result	10
Element ct:typeTSI / ct:mnc	10
Element ct:typeTSI / ct:mcc	10
Element ct:typeTSI / ct:ssi	11
Element ct:typeExternal / ct:gatewayNumber	11
Element ct:typeExternal / ct:number	11
Element ct:typeSubscriberAddress / ct:ssi	11
Element ct:typeSubscriberAddress / ct:tsi	11
Element ct:typeAddress / ct:subscriber	12
Element ct:typeAddress / ct:alias	12
Element ct:typeAddress / ct:msisdn	13
Element ct:typeAddress / ct:fssn	13
Element ct:typeAddress / ct:external	13
Element ct:typeAddress / ct:opta	13
Element ct:typeAddress / ct:cell	14
Element ct:typeResponse / ct:requestId	14
Element ct:typeResponse / ct:result	14
Element ct:typeEvent / ct:requestId	15
Element ct:typeEvent / ct:result	15
Complex Type(s)	15
Complex Type ct:typeRequest	15
Complex Type ct:typeResult	16
Complex Type ct:typeTSI	16
Complex Type ct:typeExternal	16
Complex Type ct:typeSubscriberAddress	17

Complex Type ct:typeAddress	17
Complex Type ct:typeResponse	18
Complex Type ct:typeEvent	18
Complex Type ct:typeEmpty	18
Simple Type(s)	19
Simple Type ct:typeResponseCode	19
Simple Type ct:typeSourceSystem	19
Simple Type ct:typeDialString	19
Simple Type ct:typeOPTA	20
Simple Type ct:typeAddressingStyle	20

Namespace: "DR-GW-Interface/DR-GW-OrganisationBlock"

Schema(s)

Main schema DR-GW-OrganisationBlock.xsd

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock
Annotations	Version 1.2
Properties	attribute form default: unqualified
	element form default: qualified

Element(s)

Element Org_Get

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock
Annotations	
Diagram	
Type	extension of ct:typeRequest
Type hierarchy	<ul style="list-style-type: none"> ct:typeRequest
Properties	content: complex
Model	ct:requestId , orgblockId
Children	ct:requestId, orgblockId
Instance	<pre><Org_Get xmlns="DR-GW-Interface/DR-GW-OrganisationBlock" xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:requestId>{1,1}</ct:requestId> <orgblockId>{1,1}</orgblockId> </Org_Get></pre>
Source	<pre><xs:element name="Org_Get"> <xs:annotation> <xs:documentation/> </xs:annotation> <xs:complexType> <xs:complexContent> <xs:extension base="ct:typeRequest"> <xs:sequence> <xs:element name="orgblockId" type="ct0:typeOrganisationBlockId" /> </xs:sequence> </xs:extension> </xs:complexContent> </xs:complexType> </xs:element></pre>

Element Org_Get / orgblockId

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock
-----------	---

Diagram	
Type	typeOrganisationBlockId
Properties	content: complex
Model	orgblockId orgblockIdSimple
Children	orgblockId, orgblockIdSimple
Instance	<pre><orgblockId xmlns="DR-GW-Interface/DR-GW-OrganisationBlock" xmlns:ctO="DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes"> <ctO:orgblockId>{1,1}</ctO:orgblockId> <ctO:orgblockIdSimple>{1,1}</ctO:orgblockIdSimple> </orgblockId></pre>
Source	<pre><xs:element name="orgblockId" type="ctO:typeOrganisationBlockId" /></pre>

Element Org_GetList

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock
Annotations	
Diagram	
Type	extension of ct:typeRequest
Type hierarchy	<ul style="list-style-type: none"> ct:typeRequest
Properties	content: complex
Model	ct:requestId , orgblockId{0,1}
Children	ct:requestId, orgblockId
Instance	<pre><Org_GetList xmlns="DR-GW-Interface/DR-GW-OrganisationBlock" xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:requestId>{1,1}</ct:requestId> <orgblockId>{0,1}</orgblockId> </Org_GetList></pre>
Source	<pre><xs:element name="Org_GetList"> <xs:annotation> <xs:documentation/> </xs:annotation> <xs:complexType> <xs:complexContent> <xs:extension base="ct:typeRequest"> <xs:sequence> <xs:element name="orgblockId" type="ctO:typeOrganisationBlockId" minOccurs="0"/> </xs:sequence> </xs:extension> </xs:complexContent> </xs:complexType> </xs:element></pre>

Element Org_GetList / orgblockId

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock
-----------	---

Diagram					
Type	typeOrganisationBlockId				
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	complex	minOccurs:	0
content:	complex				
minOccurs:	0				
Model	orgblockId orgblockIdSimple				
Children	orgblockId, orgblockIdSimple				
Instance	<pre><orgblockId xmlns="DR-GW-Interface/DR-GW-OrganisationBlock" xmlns:ctO="DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes"> <ctO:orgblockId>{1,1}</ctO:orgblockId> <ctO:orgblockIdSimple>{1,1}</ctO:orgblockIdSimple> </orgblockId></pre>				
Source	<pre><xs:element name="orgblockId" type="ctO:typeOrganisationBlockId" minOccurs="0" /></pre>				

Namespace: "DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes"

Schema(s)

Imported schema DR-GW-OrganisationBlock.CommonTypes.xsd

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes				
Annotations	Version 1.2				
Properties	<table> <tr> <td>attribute form default:</td><td>unqualified</td></tr> <tr> <td>element form default:</td><td>qualified</td></tr> </table>	attribute form default:	unqualified	element form default:	qualified
attribute form default:	unqualified				
element form default:	qualified				

Element(s)

Element typeOrganisationBlockId / orgblockId

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes		
Diagram			
Type	typeOrganisationBlockIdNormal		
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> </table>	content:	complex
content:	complex		
Model	id1 {0,1} , id2 {0,1} , id3 {0,1} , id4 {0,1} , id5 {0,1} , id6 {0,1}		
Children	id1, id2, id3, id4, id5, id6		
Instance	<pre><orgblockId xmlns="DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes"> <id1>{0,1}</id1></pre>		

	<pre> <id2>{0,1}</id2> <id3>{0,1}</id3> <id4>{0,1}</id4> <id5>{0,1}</id5> <id6>{0,1}</id6> </orgblockId> </pre>
Source	<pre> <xs:element name="orgblockId" type="typeOrganisationBlockIdNormal"/> </pre>

Element typeOrganisationBlockIdNormal / id1

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes				
Diagram					
Type	xs:unsignedShort				
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0
content:	simple				
minOccurs:	0				
Source	<pre> <xs:element name="id1" type="xs:unsignedShort" minOccurs="0"/> </pre>				

Element typeOrganisationBlockIdNormal / id2

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes				
Diagram					
Type	xs:unsignedShort				
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0
content:	simple				
minOccurs:	0				
Source	<pre> <xs:element name="id2" type="xs:unsignedShort" minOccurs="0"/> </pre>				

Element typeOrganisationBlockIdNormal / id3

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes				
Diagram					
Type	xs:unsignedShort				
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0
content:	simple				
minOccurs:	0				
Source	<pre> <xs:element name="id3" type="xs:unsignedShort" minOccurs="0"/> </pre>				

Element typeOrganisationBlockIdNormal / id4

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes
Diagram	

Type	xs:unsignedShort
Properties	content: simple
	minOccurs: 0
Source	<code><xs:element name="id4" type="xs:unsignedShort" minOccurs="0"/></code>

Element typeOrganisationBlockIdNormal / id5

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes
Diagram	
Type	xs:unsignedShort
Properties	content: simple
	minOccurs: 0
Source	<code><xs:element name="id5" type="xs:unsignedShort" minOccurs="0"/></code>

Element typeOrganisationBlockIdNormal / id6

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes
Diagram	
Type	xs:unsignedShort
Properties	content: simple
	minOccurs: 0
Source	<code><xs:element name="id6" type="xs:unsignedShort" minOccurs="0"/></code>

Element typeOrganisationBlockId / orgblockIdSimple

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes
Diagram	
Type	typeOrganisationBlockIdSimple
Properties	content: simple
Facets	<p>pattern</p> <pre>(([0-9] [1-9]\d{0,3} [1-5]\d{4} 6[0-4]\d{3} 65[0-4]\d{2} 655[0-2]\d 6553[0-5])-(0,5)([0-9] [1-9]\d{0,3} [1-5]\d{4} 6[0-4]\d{3} 65[0-4]\d{2} 655[0-2]\d 6553[0-5])</pre>
Source	<code><xs:element name="orgblockIdSimple" type="typeOrganisationBlockIdSimple"/></code>

Element typeOrganisationBlock / orgblockId

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes
-----------	---

Diagram	
Type	typeOrganisationBlockId
Properties	content: complex
Model	orgblockId orgblockIdSimple
Children	orgblockId, orgblockIdSimple
Instance	<pre><orgblockId xmlns="DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes"> <orgblockId>{1,1}</orgblockId> <orgblockIdSimple>{1,1}</orgblockIdSimple> </orgblockId></pre>
Source	<pre><xs:element name="orgblockId" type="typeOrganisationBlockId" /></pre>

Element typeOrganisationBlock / alias

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes
Diagram	
Type	xs:normalizedString
Properties	content: simple
Source	<pre><xs:element name="alias" type="xs:normalizedString" /></pre>

Complex Type(s)

Complex Type typeOrganisationBlockId

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes
Annotations	
Diagram	
Used by	Elements Org_Get/orgblockId, Org_GetList/orgblockId, typeOrganisationBlock/orgblockId
Model	orgblockId orgblockIdSimple
Children	orgblockId, orgblockIdSimple
Source	<pre><xs:complexType name="typeOrganisationBlockId"> <xs:annotation> <xs:documentation/> </xs:annotation> <xs:choice> <xs:element name="orgblockId" type="typeOrganisationBlockIdNormal" /> <xs:element name="orgblockIdSimple" type="typeOrganisationBlockIdSimple" /> </xs:choice> </xs:complexType></pre>

Complex Type typeOrganisationBlockIdNormal

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes
Annotations	

Diagram	
Used by	Element typeOrganisationBlockId/orgblockId
Model	id1 {0,1} , id2 {0,1} , id3 {0,1} , id4 {0,1} , id5 {0,1} , id6 {0,1}
Children	id1, id2, id3, id4, id5, id6
Source	<pre> <xs:complexType name="typeOrganisationBlockIdNormal"> <xs:annotation> <xs:documentation/> </xs:annotation> <xs:sequence> <xs:element name="id1" type="xs:unsignedShort" minOccurs="0"/> <xs:element name="id2" type="xs:unsignedShort" minOccurs="0"/> <xs:element name="id3" type="xs:unsignedShort" minOccurs="0"/> <xs:element name="id4" type="xs:unsignedShort" minOccurs="0"/> <xs:element name="id5" type="xs:unsignedShort" minOccurs="0"/> <xs:element name="id6" type="xs:unsignedShort" minOccurs="0"/> </xs:sequence> </xs:complexType> </pre>

Complex Type typeOrganisationBlock

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes
Annotations	
Diagram	
Model	orgblockId , alias
Children	alias, orgblockId
Source	<pre> <xs:complexType name="typeOrganisationBlock"> <xs:annotation> <xs:documentation/> </xs:annotation> <xs:sequence> <xs:element name="orgblockId" type="typeOrganisationBlockId"/> <xs:element name="alias" type="xs:normalizedString"/> </xs:sequence> </xs:complexType> </pre>

Simple Type(s)

Simple Type typeOrganisationBlockIdSimple

Namespace	DR-GW-Interface/DR-GW-OrganisationBlock.CommonTypes
Annotations	Organisation block send as simple normalized string. The pattern is: id1-id2-id3-id4-id5-id6
Diagram	
Type	restriction of xs:normalizedString

Facets	pattern	(([0-9] [1-9]\d{0,3} [1-5]\d{4} 6[0-4]\d{3} 65[0-4]\d{2} 655[0-2]\d 6553[0-5])-\{0,5\}([0-9] [1-9]\d{0,3} [1-5]\d{4} 6[0-4]\d{3} 65[0-4]\d{2} 655[0-2]\d 6553[0-5]))
Used by	Element	typeOrganisationBlockId/orgblockIdSimple
Source	<pre><xs:simpleType name="typeOrganisationBlockIdSimple"> <xs:annotation> <xs:documentation>Organisation block send as simple normalized string. The pattern is: id1-id2-id3-id4-id5-id6</xs:documentation> </xs:annotation> <xs:restriction base="xs:normalizedString"> <xs:pattern value="((([0-9] [1-9]\d{0,3} [1-5]\d{4} 6[0-4]\d{3} 65[0-4]\d{2} 655[0-2]\d 6553[0-5])-\{0,5\}([0-9] [1-9]\d{0,3} [1-5]\d{4} 6[0-4]\d{3} 65[0-4]\d{2} 655[0-2]\d 6553[0-5]))"/> </xs:restriction> </xs:simpleType></pre>	

Namespace: "DR-GW-Interface/CommonTypes"

Schema(s)

Imported schema CommonTypes.xsd

Namespace	DR-GW-Interface/CommonTypes
Annotations	Version 1.2
Properties	attribute form default: unqualified element form default: qualified

Element(s)

Element ct:typeRequest / ct:requestId

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedLong
Properties	content: simple
Source	<pre><xs:element name="requestId" type="xs:unsignedLong" /></pre>

Element ct:typeResult / ct:responseCode

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeResponseCode
Properties	content: simple
Facets	enumeration success enumeration final_response_pending enumeration error enumeration not_authorized_error enumeration temporary_failure enumeration subscription_failed

Source	<code><xs:element name="responseCode" type="ct:typeResponseCode" /></code>
--------	--

Element `ct:typeResult` / `ct:sourceSystem`

Namespace	DR-GW-Interface/CommonTypes								
Diagram									
Type	ct:typeSourceSystem								
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0				
content:	simple								
minOccurs:	0								
Facets	<table> <tr> <td>enumeration</td><td>DR-GW</td></tr> <tr> <td>enumeration</td><td>TCS-API</td></tr> <tr> <td>enumeration</td><td>TETRA</td></tr> <tr> <td>enumeration</td><td>TACTILON-API</td></tr> </table>	enumeration	DR-GW	enumeration	TCS-API	enumeration	TETRA	enumeration	TACTILON-API
enumeration	DR-GW								
enumeration	TCS-API								
enumeration	TETRA								
enumeration	TACTILON-API								
Source	<code><xs:element name="sourceSystem" type="ct:typeSourceSystem" minOccurs="0" /></code>								

Element `ct:typeResult` / `ct:result`

Namespace	DR-GW-Interface/CommonTypes				
Diagram					
Type	xs:unsignedLong				
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0
content:	simple				
minOccurs:	0				
Source	<code><xs:element name="result" type="xs:unsignedLong" minOccurs="0" /></code>				

Element `ct:typeTSI` / `ct:mnc`


Namespace	DR-GW-Interface/CommonTypes		
Diagram			
Type	xs:unsignedShort		
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> </table>	content:	simple
content:	simple		
Source	<code><xs:element name="mnc" type="xs:unsignedShort" /></code>		

Element `ct:typeTSI` / `ct:mcc`


Namespace	DR-GW-Interface/CommonTypes		
Diagram			
Type	xs:unsignedShort		
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> </table>	content:	simple
content:	simple		

Source	<code><xs:element name="mcc" type="xs:unsignedShort" /></code>
--------	--


Element `ct:typeTSI` / `ct:ssi`

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedLong
Properties	content: simple
Source	<code><xs:element name="ssi" type="xs:unsignedLong" /></code>


Element `ct:typeExternal` / `ct:gatewayNumber`

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedLong
Properties	content: simple
Source	<code><xs:element name="gatewayNumber" type="xs:unsignedLong" /></code>

Element `ct:typeExternal` / `ct:number`

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeDialString
Properties	content: simple
Facets	maxLength 24
Source	<code><xs:element name="number" type="ct:typeDialString" /></code>

Element `ct:typeSubscriberAddress` / `ct:ssi`

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedLong
Properties	content: simple
Source	<code><xs:element name="ssi" type="xs:unsignedLong" /></code>

Element `ct:typeSubscriberAddress` / `ct:tsi`

Namespace	DR-GW-Interface/CommonTypes
-----------	-----------------------------

Diagram	
Type	ct:typeTSI
Properties	content: complex
Model	ct:mnc , ct:mcc , ct:ssi
Children	ct:mcc, ct:mnc, ct:ssi
Instance	<pre><ct:tsi xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:mnc>{1,1}</ct:mnc> <ct:mcc>{1,1}</ct:mcc> <ct:ssi>{1,1}</ct:ssi> </ct:tsi></pre>
Source	<pre><xs:element name="tsi" type="ct:typeTSI"/></pre>

Element ct:typeAddress / ct:subscriber

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeSubscriberAddress
Properties	content: complex minOccurs: 0
Model	ct:ssi ct:tsi
Children	ct:ssi, ct:tsi
Instance	<pre><ct:subscriber xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:ssi>{1,1}</ct:ssi> <ct:tsi>{1,1}</ct:tsi> </ct:subscriber></pre>
Source	<pre><xs:element name="subscriber" type="ct:typeSubscriberAddress" minOccurs="0"/></pre>


Element ct:typeAddress / ct:alias

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:normalizedString
Properties	content: simple minOccurs: 0
Source	<pre><xs:element name="alias" type="xs:normalizedString" minOccurs="0"/></pre>


Element `ct:typeAddress / ct:msisdn`

Namespace	DR-GW-Interface/CommonTypes		
Diagram	<div><div>msisdn</div><div>—</div><div><div><div></div></div>ct:typeDialString</div><div><div>Allowed characters are digits 0 - 9, *, #, A, B, C and D. Maximum length is 24 characters.</div></div></div>		
Type	ct:typeDialString		
Properties	content:	simple	
	minOccurs:	0	
Facets	maxLength	24	
Source	<xs:element name="msisdn" type="ct:typeDialString" minOccurs="0"/>		

Element `ct:typeAddress / ct:fssn`


Namespace	DR-GW-Interface/CommonTypes		
Annotations	Fleet specific short number		
Diagram			
Type	xs:unsignedLong		
Properties	content:	simple	
	minOccurs:	0	
Source	<pre><xs:element name="fssn" type="xs:unsignedLong" minOccurs="0"> <xs:annotation> <xs:documentation>Fleet specific short number</xs:documentation> </xs:annotation> </xs:element></pre>		

Element `ct:typeAddress / ct:external`


Namespace	DR-GW-Interface/CommonTypes		
Diagram			
Type	ct:typeExternal		
Properties	content:	complex	
	minOccurs:	0	
Model	ct:gatewayNumber , ct:number		
Children	ct:gatewayNumber, ct:number		
Instance	<pre><ct:external xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:gatewayNumber>{1,1}</ct:gatewayNumber> <ct:number>{1,1}</ct:number> </ct:external></pre>		
Source	<pre><xs:element name="external" type="ct:typeExternal" minOccurs="0"/></pre>		

Element `ct:typeAddress / ct:opta`


Namespace	DR-GW-Interface/CommonTypes		
-----------	-----------------------------	--	--

Diagram					
Type	ct:typeOPTA				
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0
content:	simple				
minOccurs:	0				
Facets	<table> <tr> <td>maxLength</td><td>24</td></tr> </table>	maxLength	24		
maxLength	24				
Source	<code><xs:element name="opta" type="ct:typeOPTA" minOccurs="0"/></code>				


Element ct:typeAddress / ct:cell

Namespace	DR-GW-Interface/CommonTypes				
Diagram					
Type	xs:short				
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0
content:	simple				
minOccurs:	0				
Source	<code><xs:element name="cell" type="xs:short" minOccurs="0"/></code>				

Element ct:typeResponse / ct:requestId

Namespace	DR-GW-Interface/CommonTypes		
Diagram			
Type	xs:unsignedLong		
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> </table>	content:	simple
content:	simple		
Source	<code><xs:element name="requestId" type="xs:unsignedLong"/></code>		

Element ct:typeResponse / ct:result

Namespace	DR-GW-Interface/CommonTypes		
Diagram			
Type	ct:typeResult		
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> </table>	content:	complex
content:	complex		
Model	ct:responseCode , ct:sourceSystem {0,1} , ct:result {0,1}		
Children	ct:responseCode, ct:result, ct:sourceSystem		
Instance	<code><ct:result xmlns:ct="DR-GW-Interface/CommonTypes"></code>		

	<pre> <ct:responseCode>{1,1}</ct:responseCode> <ct:sourceSystem>{0,1}</ct:sourceSystem> <ct:result>{0,1}</ct:result> </ct:result> </pre>
Source	<pre> <xs:element name="result" type="ct:typeResult"/> </pre>

Element ct:typeEvent / ct:requestId

Namespace	DR-GW-Interface/CommonTypes				
Diagram					
Type	xs:unsignedLong				
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0
content:	simple				
minOccurs:	0				
Source	<pre> <xs:element name="requestId" type="xs:unsignedLong" minOccurs="0"/> </pre>				

Element ct:typeEvent / ct:result

Namespace	DR-GW-Interface/CommonTypes				
Diagram					
Type	ct:typeResult				
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	complex	minOccurs:	0
content:	complex				
minOccurs:	0				
Model	ct:responseCode , ct:sourceSystem{0,1} , ct:result{0,1}				
Children	ct:responseCode, ct:result, ct:sourceSystem				
Instance	<pre> <ct:result xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:responseCode>{1,1}</ct:responseCode> <ct:sourceSystem>{0,1}</ct:sourceSystem> <ct:result>{0,1}</ct:result> </ct:result> </pre>				
Source	<pre> <xs:element name="result" type="ct:typeResult" minOccurs="0"/> </pre>				

Complex Type(s)

Complex Type ct:typeRequest

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Used by	Elements Org_Get, Org_GetList
Model	ct:requestId
Children	ct:requestId
Source	<pre> <xs:complexType name="typeRequest"> <xs:sequence> <xs:element name="requestId" type="xs:unsignedLong"/> </pre>

```
</xs:sequence>
</xs:complexType>
```

Complex Type ct:typeResult

Namespace	DR-GW-Interface/CommonTypes
Annotations	Common result values used in every response and optional specific subsystem result codes.
Diagram	<p>Common result values used in every response and optional specific subsystem result codes.</p>
Used by	Elements ct:typeEvent/ct:result, ct:typeResponse/ct:result
Model	ct:responseCode , ct:sourceSystem{0,1} , ct:result{0,1}
Children	ct:responseCode, ct:result, ct:sourceSystem
Source	<pre><xs:complexType name="typeResult"> <xs:annotation> <xs:documentation>Common result values used in every response and optional specific subsystem result codes.</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="responseCode" type="ct:typeResponseCode" /> <xs:element name="sourceSystem" type="ct:typeSourceSystem" minOccurs="0"/> <xs:element name="result" type="xs:unsignedLong" minOccurs="0"/> </xs:sequence> </xs:complexType></pre>

Complex Type ct:typeTSI

Namespace	DR-GW-Interface/CommonTypes
Annotations	Basic type for TETRA subscriber identity containing Network code(MNC) and Country code(MCC).
Diagram	<p>Basic type for TETRA subscriber identity containing Network code(MNC) and Country code(MCC).</p>
Used by	Element ct:typeSubscriberAddress/ct:tsi
Model	ct:mnc , ct:mcc , ct:ssi
Children	ct:mcc, ct:mnc, ct:ssi
Source	<pre><xs:complexType name="typeTSI"> <xs:annotation> <xs:documentation>Basic type for TETRA subscriber identity containing Network code(MNC) and Country code(MCC).</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="mnc" type="xs:unsignedShort" /> <xs:element name="mcc" type="xs:unsignedShort" /> <xs:element name="ssi" type="xs:unsignedLong" /> </xs:sequence> </xs:complexType></pre>

Complex Type ct:typeExternal

Namespace	DR-GW-Interface/CommonTypes
Annotations	External number consiting of Gateway number + DialString

Diagram	
Used by	Element ct:typeAddress/ct:external
Model	ct:gatewayNumber , ct:number
Children	ct:gatewayNumber, ct:number
Source	<pre> <xs:complexType name="typeExternal"> <xs:annotation> <xs:documentation>External number consisting of Gateway number + DialString</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="gatewayNumber" type="xs:unsignedLong" /> <xs:element name="number" type="ct:typeDialString" /> </xs:sequence> </xs:complexType> </pre>

Complex Type ct:typeSubscriberAddress

Namespace	DR-GW-Interface/CommonTypes
Annotations	
Diagram	
Used by	Element ct:typeAddress/ct:subscriber
Model	ct:ssi ct:tsi
Children	ct:ssi, ct:tsi
Source	<pre> <xs:complexType name="typeSubscriberAddress"> <xs:annotation> <xs:documentation/> </xs:annotation> <xs:choice> <xs:element name="ssi" type="xs:unsignedLong" /> <xs:element name="tsi" type="ct:typeTSI" /> </xs:choice> </xs:complexType> </pre>

Complex Type ct:typeAddress

Namespace	DR-GW-Interface/CommonTypes
Annotations	Basic type for all possible TETRA address types (SSI, TSI, MSISDN, FSSN, OPTA).
Diagram	
Model	ct:subscriber{0,1} , ct:alias{0,1} , ct:msisdn{0,1} , ct:fssn{0,1} , ct:external{0,1} , ct:opta{0,1} , ct:cell{0,1}

Children	ct:alias, ct:cell, ct:external, ct:fssn, ct:msisdn, ct:opta, ct:subscriber
Source	<pre> <xs:complexType name="typeAddress"> <xs:annotation> <xs:documentation>Basic type for all possible TETRA address types (SSI, TSI, MSISDN, FSSN, OPTA).</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="subscriber" type="ct:typeSubscriberAddress" minOccurs="0"/> <xs:element name="alias" type="xs:normalizedString" minOccurs="0"/> <xs:element name="msisdn" type="ct:typeDialString" minOccurs="0"/> <xs:element name="fssn" type="xs:unsignedLong" minOccurs="0"> <xs:annotation> <xs:documentation>Fleet specific short number</xs:documentation> </xs:annotation> </xs:element> <xs:element name="external" type="ct:typeExternal" minOccurs="0"/> <xs:element name="opta" type="ct:typeOPTA" minOccurs="0"/> <xs:element name="cell" type="xs:short" minOccurs="0"/> </xs:sequence> </xs:complexType> </pre>

Complex Type ct:typeResponse

Namespace	DR-GW-Interface/CommonTypes
Annotations	Response contains result of execution of any method.
Diagram	
Model	ct:requestId, ct:result
Children	ct:requestId, ct:result
Source	<pre> <xs:complexType name="typeResponse"> <xs:annotation> <xs:documentation>Response contains result of execution of any method.</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="requestId" type="xs:unsignedLong"/> <xs:element name="result" type="ct:typeResult"/> </xs:sequence> </xs:complexType> </pre>

Complex Type ct:typeEvent

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Model	ct:requestId{0,1}, ct:result{0,1}
Children	ct:requestId, ct:result
Source	<pre> <xs:complexType name="typeEvent"> <xs:sequence> <xs:element name="requestId" type="xs:unsignedLong" minOccurs="0"/> <xs:element name="result" type="ct:typeResult" minOccurs="0"/> </xs:sequence> </xs:complexType> </pre>

Complex Type ct:typeEmpty

Namespace	DR-GW-Interface/CommonTypes
Annotations	Explicit type specification for elements that shall be empty.
Diagram	

Source	<pre> <xs:complexType name="typeEmpty"> <xs:annotation> <xs:documentation>Explicit type specification for elements that shall be empty.</ </xs:annotation> </xs:complexType> </pre>
--------	--

Simple Type(s)

Simple Type ct:typeResponseCode

Namespace	DR-GW-Interface/CommonTypes												
Diagram													
Type	restriction of xs:normalizedString												
Facets	<table> <tr><td>enumeration</td><td>success</td></tr> <tr><td>enumeration</td><td>final_response_pending</td></tr> <tr><td>enumeration</td><td>error</td></tr> <tr><td>enumeration</td><td>not_authorized_error</td></tr> <tr><td>enumeration</td><td>temporary_failure</td></tr> <tr><td>enumeration</td><td>subscription_failed</td></tr> </table>	enumeration	success	enumeration	final_response_pending	enumeration	error	enumeration	not_authorized_error	enumeration	temporary_failure	enumeration	subscription_failed
enumeration	success												
enumeration	final_response_pending												
enumeration	error												
enumeration	not_authorized_error												
enumeration	temporary_failure												
enumeration	subscription_failed												
Used by	Element ct:typeResult/ct:responseCode												
Source	<pre> <xs:simpleType name="typeResponseCode"> <xs:restriction base="xs:normalizedString"> <xs:enumeration value="success"/> <xs:enumeration value="final_response_pending"/> <xs:enumeration value="error"/> <xs:enumeration value="not_authorized_error"/> <xs:enumeration value="temporary_failure"/> <xs:enumeration value="subscription_failed"/> </xs:restriction> </xs:simpleType> </pre>												

Simple Type ct:typeSourceSystem

Namespace	DR-GW-Interface/CommonTypes								
Diagram									
Type	restriction of xs:normalizedString								
Facets	<table> <tr><td>enumeration</td><td>DR-GW</td></tr> <tr><td>enumeration</td><td>TCS-API</td></tr> <tr><td>enumeration</td><td>TETRA</td></tr> <tr><td>enumeration</td><td>TACTILON-API</td></tr> </table>	enumeration	DR-GW	enumeration	TCS-API	enumeration	TETRA	enumeration	TACTILON-API
enumeration	DR-GW								
enumeration	TCS-API								
enumeration	TETRA								
enumeration	TACTILON-API								
Used by	Element ct:typeResult/ct:sourceSystem								
Source	<pre> <xs:simpleType name="typeSourceSystem"> <xs:restriction base="xs:normalizedString"> <xs:enumeration value="DR-GW"/> <xs:enumeration value="TCS-API"/> <xs:enumeration value="TETRA"/> <xs:enumeration value="TACTILON-API"/> </xs:restriction> </xs:simpleType> </pre>								

Simple Type ct:typeDialString

Namespace	DR-GW-Interface/CommonTypes
-----------	-----------------------------

Annotations	Allowed characters are digits 0 - 9, *, #, A, B, C and D. Maximum length is 24 characters.
Diagram	
Type	restriction of xs:normalizedString
Facets	maxLength 24
Used by	Elements ct:typeAddress/ct:msisdn, ct:typeExternal/ct:number
Source	<pre><xs:simpleType name="typeDialString"> <xs:annotation> <xs:documentation>Allowed characters are digits 0 - 9, *, #, A, B, C and D. Maximum length is 24 characters.</xs:documentation> </xs:annotation> <xs:restriction base="xs:normalizedString"> <xs:maxLength value="24"/> </xs:restriction> </xs:simpleType></pre>

Simple Type ct:typeOPTA

Namespace	DR-GW-Interface/CommonTypes
Annotations	OPTA string. Maximum length is 24 characters.
Diagram	
Type	restriction of xs:normalizedString
Facets	maxLength 24
Used by	Element ct:typeAddress/ct:opta
Source	<pre><xs:simpleType name="typeOPTA"> <xs:annotation> <xs:documentation>OPTA string. Maximum length is 24 characters.</xs:documentation> </xs:annotation> <xs:restriction base="xs:normalizedString"> <xs:maxLength value="24"/> </xs:restriction> </xs:simpleType></pre>

Simple Type ct:typeAddressingStyle

Namespace	DR-GW-Interface/CommonTypes
Annotations	Describes the IP addressing style. Unicast or multicast.
Diagram	
Type	restriction of xs:normalizedString
Facets	enumeration ucast enumeration mcast
Source	<pre><xs:simpleType name="typeAddressingStyle"> <xs:annotation> <xs:documentation>Describes the IP addressing style. Unicast or multicast.</xs:documentation> </xs:annotation> <xs:restriction base="xs:normalizedString"> <xs:enumeration value="ucast"/> <xs:enumeration value="mcast"/> </xs:restriction> </xs:simpleType></pre>

<pre></xs:restriction> </xs:simpleType></pre>
