

# Schema documentation for DR-GW-Call.xsd

november 5, 2024

## Table of Contents

Namespace: "DR-GW-Interface/DR-GW-Call"	2
Schema(s)	2
Main schema DR-GW-Call.xsd	2
Element(s)	2
Element Call_Select	2
Element Call_Select / sel	3
Element Call_Request	3
Element Call_Request / action	4
Element Call_Request / attributes	5
Element Call_Request / callingParty	6
Element Call_Request / calledParty	6
Element Call_Request / workstationId	7
Element Call_PTTRequest	7
Element Call_PTTRequest / action	8
Element Call_PTTRequest / attributes	9
Element Call_PTTRequest / talkingParty	9
Element Call_PTTRequest / workstationId	10
Element Call_KeyExchange	10
Element Call_KeyExchange / action	11
Namespace: "DR-GW-Interface/CommonTypes"	11
Schema(s)	11
Imported schema CommonTypes.xsd	11
Element(s)	12
Element ct:typeRequest / ct:requestId	12
Element ct:typeAddress / ct:subscriber	12
Element ct:typeSubscriberAddress / ct:ssi	12
Element ct:typeSubscriberAddress / ct:tsi	12
Element ct:typeTSI / ct:mnc	13
Element ct:typeTSI / ct:mcc	13
Element ct:typeTSI / ct:ssi	13
Element ct:typeAddress / ct:alias	14
Element ct:typeAddress / ct:msisdn	14
Element ct:typeAddress / ct:fssn	14
Element ct:typeAddress / ct:external	14
Element ct:typeExternal / ct:gatewayNumber	15
Element ct:typeExternal / ct:number	15
Element ct:typeAddress / ct:opta	15
Element ct:typeAddress / ct:cell	16
Element ct:typeResult / ct:responseCode	16
Element ct:typeResult / ct:sourceSystem	16
Element ct:typeResult / ct:result	16
Element ct:typeResponse / ct:requestId	17
Element ct:typeResponse / ct:result	17
Element ct:typeEvent / ct:requestId	17
Element ct:typeEvent / ct:result	18
Complex Type(s)	18
Complex Type ct:typeRequest	18
Complex Type ct:typeAddress	18
Complex Type ct:typeSubscriberAddress	19
Complex Type ct:typeTSI	19
Complex Type ct:typeExternal	20
Complex Type ct:typeResult	20
Complex Type ct:typeResponse	21
Complex Type ct:typeEvent	21
Complex Type ct:typeEmpty	21
Simple Type(s)	22
Simple Type ct:typeDialString	22
Simple Type ct:typeOPTA	22
Simple Type ct:typeResponseCode	22
Simple Type ct:typeSourceSystem	23
Simple Type ct:typeAddressingStyle	23
Namespace: "DR-GW-Interface/DR-GW-Call.CommonTypes"	24
Schema(s)	24

Imported schema DR-GW-Call.CommonTypes.xsd .....	24
Element(s) .....	24
Element typeSelection / level .....	24
Element typeSelection / target .....	24
Element typeCallAttributes / hook .....	25
Element typeCallAttributes / mode .....	25
Element typeCallAttributes / commtype .....	25
Element typeCallAttributes / priority .....	26
Element typeCallAttributes / encryption .....	26
Element typeCallAttributes / ambienceListen .....	26
Element typeCallAttributes / req2speak .....	26
Element typeCallAttributes / demandPriority .....	27
Element typeCallAttributes / txCoverageInfo .....	27
Element typeTxGranted / txGrant .....	27
Element typeTxGranted / talkingParty .....	28
Element typeTxGranted / encryption .....	28
Element typeTxGranted / txPriority .....	29
Element typeTxGranted / txCoverageInfo .....	29
Element typeTxGranted / txInterrupt .....	29
Element typeTxGranted / txRepeat .....	30
Element typeTxGranted / workstationId .....	30
Element typeDisconnectCause / protocol .....	30
Element typeDisconnectCause / code .....	31
Element typeDisconnectCause / text .....	31
Complex Type(s) .....	32
Complex Type typeSelection .....	32
Complex Type typeCallAttributes .....	32
Complex Type typeTxGranted .....	33
Complex Type typeDisconnectCause .....	34
Simple Type(s) .....	34
Simple Type typeSelectionLevel .....	34
Simple Type typeActionRequest .....	35
Simple Type typeCallMode .....	36
Simple Type typeCallType .....	37
Simple Type typeTxDemandPriority .....	37
Simple Type typeTxCoverageInfo .....	37
Simple Type typeWorkstationId .....	38
Simple Type typeActionPTTRequest .....	39
Simple Type typeKeyExchangeAction .....	39
Simple Type typeActionEvent .....	39
Simple Type typeTxPriority .....	40
Simple Type typeTxGrant .....	41
Simple Type typeAudioCodec .....	41
Simple Type typeKeyExchangeState .....	42
Simple Type typeKeyExchangeCode .....	42
Simple Type typeKeyExchangeText .....	43
Simple Type typeKeyExchangeTextPriority .....	43
Simple Type typeKeyManagementTextPriority .....	43
Simple Type typeUnitInEmergencyType .....	44
Simple Type typeEmergencyInfo .....	44

## Namespace: "DR-GW-Interface/DR-GW-Call"

### Schema(s)

#### Main schema DR-GW-Call.xsd

Namespace	DR-GW-Interface/DR-GW-Call
Annotations	Version 1.2
Properties	attribute form default: unqualified
	element form default: qualified

### Element(s)

#### Element Call\_Select

Namespace	DR-GW-Interface/DR-GW-Call
Annotations	The method reserves speech line for the targets of selection operation, sets

	the selection level of the targets of selection operation to given values.
Diagram	
Type	extension of ct:typeRequest
Type hierarchy	<ul style="list-style-type: none"> <li>ct:typeRequest</li> </ul>
Properties	content: complex
Model	ct:requestId, sel
Children	ct:requestId, sel
Instance	<pre>&lt;Call_Select xmlns="DR-GW-Interface/DR-GW-Call" xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:requestId&gt;{1,1}&lt;/ct:requestId&gt;   &lt;sel&gt;{1,1}&lt;/sel&gt; &lt;/Call_Select&gt;</pre>
Source	<pre>&lt;xs:element name="Call_Select"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;The method reserves speech line for the targets of selection operation, sets the selection level of the targets of selection operation to given values.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:complexType&gt;     &lt;xs:complexContent&gt;       &lt;xs:extension base="ct:typeRequest"&gt;         &lt;xs:sequence&gt;           &lt;xs:element name="sel" type="ctC:typeSelection" /&gt;         &lt;/xs:sequence&gt;       &lt;/xs:extension&gt;     &lt;/xs:complexContent&gt;   &lt;/xs:complexType&gt; &lt;/xs:element&gt;</pre>

### Element Call\_Select / sel

Namespace	DR-GW-Interface/DR-GW-Call
Diagram	
Type	typeSelection
Properties	content: complex
Model	level, target
Children	level, target
Instance	<pre>&lt;sel xmlns="DR-GW-Interface/DR-GW-Call" xmlns:ctC="DR-GW-Interface/DR-GW-Call.CommonTypes"&gt;   &lt;ctC:level&gt;{1,1}&lt;/ctC:level&gt;   &lt;ctC:target&gt;{1,1}&lt;/ctC:target&gt; &lt;/sel&gt;</pre>
Source	<pre>&lt;xs:element name="sel" type="ctC:typeSelection" /&gt;</pre>

### Element Call\_Request

Namespace	DR-GW-Interface/DR-GW-Call
Annotations	DR-GW-Call request. All call related operations are accomplished using this service.

Diagram	
Type	extension of ct:typeRequest
Type hierarchy	<ul style="list-style-type: none"> <li>ct:typeRequest</li> </ul>
Properties	content: complex
Model	ct:requestId , action , attributes{0,1} , callingParty{0,1} , calledParty{0,1} , workstationId{0,1}
Children	action, attributes, calledParty, callingParty, ct:requestId, workstationId
Instance	<pre>&lt;Call_Request xmlns="DR-GW-Interface/DR-GW-Call" xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:requestId&gt;{1,1}&lt;/ct:requestId&gt;   &lt;action&gt;{1,1}&lt;/action&gt;   &lt;attributes&gt;{0,1}&lt;/attributes&gt;   &lt;callingParty&gt;{0,1}&lt;/callingParty&gt;   &lt;calledParty&gt;{0,1}&lt;/calledParty&gt;   &lt;workstationId&gt;{0,1}&lt;/workstationId&gt; &lt;/Call_Request&gt;</pre>
Source	<pre>&lt;xs:element name="Call_Request"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;DR-GW-Call request. All call related operations are accomplished using this     service.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:complexType&gt;     &lt;xs:complexContent&gt;       &lt;xs:extension base="ct:typeRequest"&gt;         &lt;xs:sequence&gt;           &lt;xs:element name="action" type="ctC:typeActionRequest" /&gt;           &lt;xs:element name="attributes" type="ctC:typeCallAttributes" minOccurs="0"/&gt;           &lt;xs:element name="callingParty" type="ct:typeAddress" minOccurs="0"/&gt;           &lt;xs:element name="calledParty" type="ct:typeAddress" minOccurs="0"/&gt;           &lt;xs:element name="workstationId" type="ctC:typeWorkstationId" minOccurs="0"/&gt;         &lt;/xs:sequence&gt;       &lt;/xs:extension&gt;     &lt;/xs:complexContent&gt;   &lt;/xs:complexType&gt; &lt;/xs:element&gt;</pre>

### Element Call\_Request / action

Namespace	DR-GW-Interface/DR-GW-Call
Diagram	
Type	typeActionRequest
Properties	content: simple

Facets	enumeration	setup	This method is used to initiate a new call setup. For a call setup to be successful it is required that the resources have been reserved prior this method call.
	enumeration	connect	This method is used to connect an incoming call.
	enumeration	hold	This method requests to put an individual call to hold.
	enumeration	unhold	This method is a request for resuming an individual call from hold.
	enumeration	disconnect	This method is used to disconnect a call.
	enumeration	transfer	This method is used to transfer an individual call to a new recipient.
	enumeration	releasecall	This method is used to release radio subscriber's individual call.
Source	<code>&lt;xs:element name="action" type="ctC:typeActionRequest"/&gt;</code>		

## Element Call\_Request / attributes

Namespace	DR-GW-Interface/DR-GW-Call		
Diagram	<div><div><div>attributes</div><div>TypectC:typeCallAttributes</div></div><div><div><div>ctC:typeCallAttributes</div><div><div>hook</div><div>mode</div><div>commtype</div><div>priority</div><div>encryption</div><div>ambienceListen</div><div>req2speak</div><div>demandPriority</div><div>txCoverageInfo</div></div></div><div>Contains all attributes of the TETRA voice call.</div></div></div>		
Type	typeCallAttributes		
Properties	content:	complex	
	minOccurs:	0	
Model	hook{0,1} , mode{0,1} , commtype{0,1} , priority{0,1} , encryption{0,1} , ambienceListen{0,1} , req2speak{0,1} , demandPriority{0,1} , txCoverageInfo{0,1}		
Children	ambienceListen, commtype, demandPriority, encryption, hook, mode, priority, req2speak, txCoverageInfo		
Instance	<pre>&lt;attributes xmlns="DR-GW-Interface/DR-GW-Call" xmlns:ctC="DR-GW-Interface/DR-GW-Call.CommonTypes"&gt;   &lt;ctC:hook&gt;{0,1}&lt;/ctC:hook&gt;   &lt;ctC:mode&gt;{0,1}&lt;/ctC:mode&gt;   &lt;ctC:commtype&gt;{0,1}&lt;/ctC:commtype&gt;   &lt;ctC:priority&gt;{0,1}&lt;/ctC:priority&gt;   &lt;ctC:encryption&gt;{0,1}&lt;/ctC:encryption&gt;   &lt;ctC:ambienceListen&gt;{0,1}&lt;/ctC:ambienceListen&gt;   &lt;ctC:req2speak&gt;{0,1}&lt;/ctC:req2speak&gt;   &lt;ctC:demandPriority&gt;{0,1}&lt;/ctC:demandPriority&gt; &lt;/attributes&gt;</pre>		

	<code>&lt;ctC:txCoverageInfo&gt;{0,1}&lt;/ctC:txCoverageInfo&gt;</code> <code>&lt;/attributes&gt;</code>
Source	<code>&lt;xs:element name="attributes" type="ctC:typeCallAttributes" minOccurs="0"/&gt;</code>

## Element Call\_Request / callingParty

Namespace	DR-GW-Interface/DR-GW-Call				
Diagram					
Type	ct:typeAddress				
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	complex	minOccurs:	0
content:	complex				
minOccurs:	0				
Model	ct:subscriber{0,1} , ct:alias{0,1} , ct:msisdn{0,1} , ct:fssn{0,1} , ct:external{0,1} , ct:opta{0,1} , ct:cell{0,1}				
Children	ct:alias, ct:cell, ct:external, ct:fssn, ct:msisdn, ct:opta, ct:subscriber				
Instance	<pre> &lt;callingParty xmlns="DR-GW-Interface/DR-GW-Call" xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:subscriber&gt;{0,1}&lt;/ct:subscriber&gt;   &lt;ct:alias&gt;{0,1}&lt;/ct:alias&gt;   &lt;ct:msisdn&gt;{0,1}&lt;/ct:msisdn&gt;   &lt;ct:fssn&gt;{0,1}&lt;/ct:fssn&gt;   &lt;ct:external&gt;{0,1}&lt;/ct:external&gt;   &lt;ct:opta&gt;{0,1}&lt;/ct:opta&gt;   &lt;ct:cell&gt;{0,1}&lt;/ct:cell&gt; &lt;/callingParty&gt; </pre>				
Source	<code>&lt;xs:element name="callingParty" type="ct:typeAddress" minOccurs="0"/&gt;</code>				

## Element Call\_Request / calledParty

Namespace	DR-GW-Interface/DR-GW-Call
-----------	----------------------------

Diagram	
Type	ct:typeAddress
Properties	content: complex minOccurs: 0
Model	ct:subscriber{0,1} , ct:alias{0,1} , ct:msisdn{0,1} , ct:fssn{0,1} , ct:external{0,1} , ct:opta{0,1} , ct:cell{0,1}
Children	ct:alias, ct:cell, ct:external, ct:fssn, ct:msisdn, ct:opta, ct:subscriber
Instance	<pre>&lt;calledParty xmlns="DR-GW-Interface/DR-GW-Call" xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:subscriber&gt;{0,1}&lt;/ct:subscriber&gt;   &lt;ct:alias&gt;{0,1}&lt;/ct:alias&gt;   &lt;ct:msisdn&gt;{0,1}&lt;/ct:msisdn&gt;   &lt;ct:fssn&gt;{0,1}&lt;/ct:fssn&gt;   &lt;ct:external&gt;{0,1}&lt;/ct:external&gt;   &lt;ct:opta&gt;{0,1}&lt;/ct:opta&gt;   &lt;ct:cell&gt;{0,1}&lt;/ct:cell&gt; &lt;/calledParty&gt;</pre>
Source	<code>&lt;xs:element name="calledParty" type="ct:typeAddress" minOccurs="0"/&gt;</code>

### Element Call\_Request / workstationId

Namespace	DR-GW-Interface/DR-GW-Call
Diagram	
Type	typeWorkstationId
Properties	content: simple minOccurs: 0
Source	<code>&lt;xs:element name="workstationId" type="ctC:typeWorkstationId" minOccurs="0"/&gt;</code>

### Element Call\_PTTRequest

Namespace	DR-GW-Interface/DR-GW-Call
Annotations	DR-GW-Call PTTRequest. Only "DemandTx" and "CeaseTx" actions only.

Diagram	
Type	extension of ct:typeRequest
Type hierarchy	<ul style="list-style-type: none"> <li>ct:typeRequest</li> </ul>
Properties	content: complex
Model	ct:requestId , action , attributes {0,1} , talkingParty {0,1} , workstationId {0,1}
Children	action, attributes, ct:requestId, talkingParty, workstationId
Instance	<pre>&lt;Call_PTTRRequest xmlns="DR-GW-Interface/DR-GW-Call" xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:requestId&gt;{1,1}&lt;/ct:requestId&gt;   &lt;action&gt;{1,1}&lt;/action&gt;   &lt;attributes&gt;{0,1}&lt;/attributes&gt;   &lt;talkingParty&gt;{0,1}&lt;/talkingParty&gt;   &lt;workstationId&gt;{0,1}&lt;/workstationId&gt; &lt;/Call_PTTRRequest&gt;</pre>
Source	<pre>&lt;xs:element name="Call_PTTRRequest"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;DR-GW-Call PTTRRequest. Only "DemandTx" and "CeaseTx" actions only.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:complexType&gt;     &lt;xs:complexContent&gt;       &lt;xs:extension base="ct:typeRequest"&gt;         &lt;xs:sequence&gt;           &lt;xs:element name="action" type="ctC:typeActionPTTRRequest"/&gt;           &lt;xs:element name="attributes" type="ctC:typeCallAttributes" minOccurs="0"/&gt;           &lt;xs:element name="talkingParty" type="ct:typeAddress" minOccurs="0"/&gt;           &lt;xs:element name="workstationId" type="ctC:typeWorkstationId" minOccurs="0"/&gt;         &lt;/xs:sequence&gt;       &lt;/xs:extension&gt;     &lt;/xs:complexContent&gt;   &lt;/xs:complexType&gt; &lt;/xs:element&gt;</pre>

## Element Call\_PTTRRequest / action

Namespace	DR-GW-Interface/DR-GW-Call		
Diagram			
Type	typeActionPTTRRequest		
Properties	content:	simple	
Facets	enumeration	demandtx	This method can be used to request a speech item for a connected call.
	enumeration	ceasetx	This method is used to inform the system that the speech item is not needed any more.



Source	<code>&lt;xs:element name="action" type="ctC:typeActionPTTRequest" /&gt;</code>
--------	---

## Element Call\_PTTRequest / attributes

Namespace	DR-GW-Interface/DR-GW-Call				
Diagram	<pre> graph TD     Root((ctC:typeCallAttributes)) --- hook((hook ⊕))     Root --- mode((mode ⊕))     Root --- commtype((commtype ⊕))     Root --- priority((priority ⊕))     Root --- encryption((encryption ⊕))     Root --- ambienceListen((ambienceListen ⊕))     Root --- req2speak((req2speak ⊕))     Root --- demandPriority((demandPriority ⊕))     Root --- txCoverageInfo((txCoverageInfo ⊕))   </pre> <p>Contains all attributes of the TETRA voice call.</p>				
Type	typeCallAttributes				
Properties	<table border="1"> <tr> <td>content:</td> <td>complex</td> </tr> <tr> <td>minOccurs:</td> <td>0</td> </tr> </table>	content:	complex	minOccurs:	0
content:	complex				
minOccurs:	0				
Model	hook{0,1} , mode{0,1} , commtype{0,1} , priority{0,1} , encryption{0,1} , ambienceListen{0,1} , req2speak{0,1} , demandPriority{0,1} , txCoverageInfo{0,1}				
Children	ambienceListen, commtype, demandPriority, encryption, hook, mode, priority, req2speak, txCoverageInfo				
Instance	<pre> &lt;attributes xmlns="DR-GW-Interface/DR-GW-Call" xmlns:ctC="DR-GW-Interface/DR-GW-Call.CommonTypes"&gt;   &lt;ctC:hook&gt;{0,1}&lt;/ctC:hook&gt;   &lt;ctC:mode&gt;{0,1}&lt;/ctC:mode&gt;   &lt;ctC:commtype&gt;{0,1}&lt;/ctC:commtype&gt;   &lt;ctC:priority&gt;{0,1}&lt;/ctC:priority&gt;   &lt;ctC:encryption&gt;{0,1}&lt;/ctC:encryption&gt;   &lt;ctC:ambienceListen&gt;{0,1}&lt;/ctC:ambienceListen&gt;   &lt;ctC:req2speak&gt;{0,1}&lt;/ctC:req2speak&gt;   &lt;ctC:demandPriority&gt;{0,1}&lt;/ctC:demandPriority&gt;   &lt;ctC:txCoverageInfo&gt;{0,1}&lt;/ctC:txCoverageInfo&gt; &lt;/attributes&gt; </pre>				
Source	<code>&lt;xs:element name="attributes" type="ctC:typeCallAttributes" minOccurs="0" /&gt;</code>				

## Element Call\_PTTRequest / talkingParty

Namespace	DR-GW-Interface/DR-GW-Call
-----------	----------------------------

Diagram	
Type	ct:typeAddress
Properties	content: complex minOccurs: 0
Model	ct:subscriber{0,1} , ct:alias{0,1} , ct:msisdn{0,1} , ct:fssn{0,1} , ct:external{0,1} , ct:opta{0,1} , ct:cell{0,1}
Children	ct:alias, ct:cell, ct:external, ct:fssn, ct:msisdn, ct:opta, ct:subscriber
Instance	<pre>&lt;talkingParty xmlns="DR-GW-Interface/DR-GW-Call" xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:subscriber&gt;{0,1}&lt;/ct:subscriber&gt;   &lt;ct:alias&gt;{0,1}&lt;/ct:alias&gt;   &lt;ct:msisdn&gt;{0,1}&lt;/ct:msisdn&gt;   &lt;ct:fssn&gt;{0,1}&lt;/ct:fssn&gt;   &lt;ct:external&gt;{0,1}&lt;/ct:external&gt;   &lt;ct:opta&gt;{0,1}&lt;/ct:opta&gt;   &lt;ct:cell&gt;{0,1}&lt;/ct:cell&gt; &lt;/talkingParty&gt;</pre>
Source	<code>&lt;xs:element name="talkingParty" type="ct:typeAddress" minOccurs="0"/&gt;</code>

## Element Call\_PTTRequest / workstationId

Namespace	DR-GW-Interface/DR-GW-Call
Diagram	
Type	typeWorkstationId
Properties	content: simple minOccurs: 0
Source	<code>&lt;xs:element name="workstationId" type="ctC:typeWorkstationId" minOccurs="0"/&gt;</code>

## Element Call\_KeyExchange

Namespace	DR-GW-Interface/DR-GW-Call
Annotations	For triggering the group key exchange. Key exchange events are sent in Call_KeyXEvent.

Diagram	
Type	extension of ct:typeRequest
Type hierarchy	<ul style="list-style-type: none"> <li>ct:typeRequest</li> </ul>
Properties	content: complex
Model	ct:requestId , action
Children	action, ct:requestId
Instance	<pre>&lt;Call_KeyExchange xmlns="DR-GW-Interface/DR-GW-Call" xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:requestId&gt;{1,1}&lt;/ct:requestId&gt;   &lt;action&gt;{1,1}&lt;/action&gt; &lt;/Call_KeyExchange&gt;</pre>
Source	<pre>&lt;xs:element name="Call_KeyExchange"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;For triggering the group key exchange. Key exchange events are sent in     Call_KeyXEvent.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:complexType&gt;     &lt;xs:complexContent&gt;       &lt;xs:extension base="ct:typeRequest"&gt;         &lt;xs:sequence&gt;           &lt;xs:element name="action" type="ctC:typeKeyExchangeAction" /&gt;         &lt;/xs:sequence&gt;       &lt;/xs:extension&gt;     &lt;/xs:complexContent&gt;   &lt;/xs:complexType&gt; &lt;/xs:element&gt;</pre>

### Element Call\_KeyExchange / action

Namespace	DR-GW-Interface/DR-GW-Call				
Diagram					
Type	typeKeyExchangeAction				
Properties	content: simple				
Facets	<table border="1"> <tr> <td>enumeration</td> <td>start</td> </tr> <tr> <td>enumeration</td> <td>stop</td> </tr> </table>	enumeration	start	enumeration	stop
enumeration	start				
enumeration	stop				
Source	<pre>&lt;xs:element name="action" type="ctC:typeKeyExchangeAction"/&gt;</pre>				

## Namespace: "DR-GW-Interface/CommonTypes"


### Schema(s)

#### Imported schema CommonTypes.xsd


Namespace	DR-GW-Interface/CommonTypes				
Annotations	Version 1.2				
Properties	<table border="1"> <tr> <td>attribute form default:</td> <td>unqualified</td> </tr> <tr> <td>element form default:</td> <td>qualified</td> </tr> </table>	attribute form default:	unqualified	element form default:	qualified
attribute form default:	unqualified				
element form default:	qualified				

## Element(s)


### Element `ct:typeRequest` / `ct:requestId`

Namespace	DR-GW-Interface/CommonTypes
Diagram	 <p>The diagram shows the <code>requestId</code> element connected to the <code>xs:unsignedLong</code> datatype. A callout box states: "Built-in derived type. The unsignedLong datatype is derived from nonNegativeInteger by setting the value of..."</p>
Type	<code>xs:unsignedLong</code>
Properties	content: simple
Source	<pre>&lt;xs:element name="requestId" type="xs:unsignedLong" /&gt;</pre>

### Element `ct:typeAddress` / `ct:subscriber`


Namespace	DR-GW-Interface/CommonTypes
Diagram	 <p>The diagram shows the <code>subscriber</code> element connected to a complex type container. Inside the container is the <code>ct:typeSubscriberAddress</code> type, which contains two child elements: <code>ssi</code> and <code>tsi</code>, both with a cardinality of 1 (indicated by a '+' sign).</p>
Type	<code>ct:typeSubscriberAddress</code>
Properties	content: complex minOccurs: 0
Model	<code>ct:ssi   ct:tsi</code>
Children	<code>ct:ssi</code> , <code>ct:tsi</code>
Instance	<pre>&lt;ct:subscriber xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:ssi&gt;{1,1}&lt;/ct:ssi&gt;   &lt;ct:tsi&gt;{1,1}&lt;/ct:tsi&gt; &lt;/ct:subscriber&gt;</pre>
Source	<pre>&lt;xs:element name="subscriber" type="ct:typeSubscriberAddress" minOccurs="0" /&gt;</pre>

### Element `ct:typeSubscriberAddress` / `ct:ssi`


Namespace	DR-GW-Interface/CommonTypes
Diagram	 <p>The diagram shows the <code>ssi</code> element connected to the <code>xs:unsignedLong</code> datatype. A callout box states: "Built-in derived type. The unsignedLong datatype is derived from nonNegativeInteger by setting the value of..."</p>
Type	<code>xs:unsignedLong</code>
Properties	content: simple
Source	<pre>&lt;xs:element name="ssi" type="xs:unsignedLong" /&gt;</pre>

### Element `ct:typeSubscriberAddress` / `ct:tsi`


Namespace	DR-GW-Interface/CommonTypes
-----------	-----------------------------

Diagram	
Type	ct:typeTSI
Properties	content: complex
Model	ct:mnc , ct:mcc , ct:ssi
Children	ct:mcc, ct:mnc, ct:ssi
Instance	<pre>&lt;ct:tsi xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:mnc&gt;{1,1}&lt;/ct:mnc&gt;   &lt;ct:mcc&gt;{1,1}&lt;/ct:mcc&gt;   &lt;ct:ssi&gt;{1,1}&lt;/ct:ssi&gt; &lt;/ct:tsi&gt;</pre>
Source	<pre>&lt;xs:element name="tsi" type="ct:typeTSI"/&gt;</pre>


#### Element ct:typeTSI / ct:mnc

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedShort
Properties	content: simple
Source	<pre>&lt;xs:element name="mnc" type="xs:unsignedShort"/&gt;</pre>

#### Element ct:typeTSI / ct:mcc

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedShort
Properties	content: simple
Source	<pre>&lt;xs:element name="mcc" type="xs:unsignedShort"/&gt;</pre>

#### Element ct:typeTSI / ct:ssi

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedLong

Properties	content: simple
Source	<code>&lt;xs:element name="ssi" type="xs:unsignedLong"/&gt;</code>

### Element `ct:typeAddress` / `ct:alias`

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:normalizedString
Properties	content: simple minOccurs: 0
Source	<code>&lt;xs:element name="alias" type="xs:normalizedString" minOccurs="0"/&gt;</code>

### Element `ct:typeAddress` / `ct:msisdn`

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeDialString
Properties	content: simple minOccurs: 0
Facets	maxLength 24
Source	<code>&lt;xs:element name="msisdn" type="ct:typeDialString" minOccurs="0"/&gt;</code>

### Element `ct:typeAddress` / `ct:fssn`

Namespace	DR-GW-Interface/CommonTypes
Annotations	Fleet specific short number
Diagram	
Type	xs:unsignedLong
Properties	content: simple minOccurs: 0
Source	<pre> &lt;xs:element name="fssn" type="xs:unsignedLong" minOccurs="0"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Fleet specific short number&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;/xs:element&gt; </pre>

### Element `ct:typeAddress` / `ct:external`

Namespace	DR-GW-Interface/CommonTypes
-----------	-----------------------------

Diagram	
Type	ct:typeExternal
Properties	content: complex minOccurs: 0
Model	ct:gatewayNumber , ct:number
Children	ct:gatewayNumber, ct:number
Instance	<pre>&lt;ct:external xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:gatewayNumber&gt;{1,1}&lt;/ct:gatewayNumber&gt;   &lt;ct:number&gt;{1,1}&lt;/ct:number&gt; &lt;/ct:external&gt;</pre>
Source	<code>&lt;xs:element name="external" type="ct:typeExternal" minOccurs="0" /&gt;</code>

### Element ct:typeExternal / ct:gatewayNumber

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedLong
Properties	content: simple
Source	<code>&lt;xs:element name="gatewayNumber" type="xs:unsignedLong" /&gt;</code>

### Element ct:typeExternal / ct:number

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeDialString
Properties	content: simple
Facets	maxLength 24
Source	<code>&lt;xs:element name="number" type="ct:typeDialString" /&gt;</code>

### Element ct:typeAddress / ct:opta

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeOPTA
Properties	content: simple minOccurs: 0

Facets	maxLength	24
Source	<xs:element name="opta" type="ct:typeOPTA" minOccurs="0"/>	

**Element ct:typeAddress / ct:cell**

Namespace	DR-GW-Interface/CommonTypes	
Diagram		
Type	xs:short	
Properties	content:	simple
	minOccurs:	0
Source	<xs:element name="cell" type="xs:short" minOccurs="0"/>	

**Element ct:typeResult / ct:responseCode**

Namespace	DR-GW-Interface/CommonTypes	
Diagram		
Type	ct:typeResponseCode	
Properties	content:	simple
Facets	enumeration	success
	enumeration	final_response_pending
	enumeration	error
	enumeration	not_authorized_error
	enumeration	temporary_failure
	enumeration	subscription_failed
Source	<xs:element name="responseCode" type="ct:typeResponseCode"/>	

**Element ct:typeResult / ct:sourceSystem**

Namespace	DR-GW-Interface/CommonTypes	
Diagram		
Type	ct:typeSourceSystem	
Properties	content:	simple
	minOccurs:	0
Facets	enumeration	DR-GW
	enumeration	TCS-API
	enumeration	TETRA
	enumeration	TACTILON-API
Source	<xs:element name="sourceSystem" type="ct:typeSourceSystem" minOccurs="0"/>	

**Element ct:typeResult / ct:result**

Namespace	DR-GW-Interface/CommonTypes	
Diagram		



Type	xs:unsignedLong	
Properties	content:	simple
	minOccurs:	0
Source	<code>&lt;xs:element name="result" type="xs:unsignedLong" minOccurs="0"/&gt;</code>	

**Element `ct:typeResponse` / `ct:requestId`**

Namespace	DR-GW-Interface/CommonTypes	
Diagram		
Type	xs:unsignedLong	
Properties	content:	simple
Source	<code>&lt;xs:element name="requestId" type="xs:unsignedLong"/&gt;</code>	


**Element `ct:typeResponse` / `ct:result`**

Namespace	DR-GW-Interface/CommonTypes	
Diagram		
Type	ct:typeResult	
Properties	content:	complex
Model	ct:responseCode , ct:sourceSystem{0,1} , ct:result{0,1}	
Children	ct:responseCode, ct:result, ct:sourceSystem	
Instance	<pre>&lt;ct:result xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:responseCode&gt;{1,1}&lt;/ct:responseCode&gt;   &lt;ct:sourceSystem&gt;{0,1}&lt;/ct:sourceSystem&gt;   &lt;ct:result&gt;{0,1}&lt;/ct:result&gt; &lt;/ct:result&gt;</pre>	
Source	<code>&lt;xs:element name="result" type="ct:typeResult"/&gt;</code>	


**Element `ct:typeEvent` / `ct:requestId`**

Namespace	DR-GW-Interface/CommonTypes	
Diagram		
Type	xs:unsignedLong	
Properties	content:	simple
	minOccurs:	0
Source	<code>&lt;xs:element name="requestId" type="xs:unsignedLong" minOccurs="0"/&gt;</code>	

**Element `ct:typeEvent` / `ct:result`**

Namespace	DR-GW-Interface/CommonTypes				
Diagram					
Type	ct:typeResult				
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	complex	minOccurs:	0
content:	complex				
minOccurs:	0				
Model	ct:responseCode , ct:sourceSystem{0,1} , ct:result{0,1}				
Children	ct:responseCode, ct:result, ct:sourceSystem				
Instance	<pre>&lt;ct:result xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:responseCode&gt;{1,1}&lt;/ct:responseCode&gt;   &lt;ct:sourceSystem&gt;{0,1}&lt;/ct:sourceSystem&gt;   &lt;ct:result&gt;{0,1}&lt;/ct:result&gt; &lt;/ct:result&gt;</pre>				
Source	<pre>&lt;xs:element name="result" type="ct:typeResult" minOccurs="0"/&gt;</pre>				

**Complex Type(s)****Complex Type `ct:typeRequest`**

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Used by	Elements Call_KeyExchange, Call_PTTRrequest, Call_Request, Call_Select
Model	ct:requestId
Children	ct:requestId
Source	<pre>&lt;xs:complexType name="typeRequest"&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="requestId" type="xs:unsignedLong"/&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt;</pre>

**Complex Type `ct:typeAddress`**

Namespace	DR-GW-Interface/CommonTypes
Annotations	Basic type for all possible TETRA address types (SSI, TSI, MSISDN, FSSN, OPTA).

Diagram		
Used by	Elements	Call_PTTRequest/talkingParty, Call_Request/calledParty, Call_Request/callingParty, typeSelection/target, typeTxGranted/talkingParty
Model	ct:subscriber{0,1} , ct:alias{0,1} , ct:msisdn{0,1} , ct:fssn{0,1} , ct:external{0,1} , ct:opta{0,1} , ct:cell{0,1}	
Children	ct:alias, ct:cell, ct:external, ct:fssn, ct:msisdn, ct:opta, ct:subscriber	
Source	<pre> &lt;xs:complexType name="typeAddress"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Basic type for all possible TETRA address types (SSI, TSI, MSISDN, FSSN, OPTA).&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="subscriber" type="ct:typeSubscriberAddress" minOccurs="0"/&gt;     &lt;xs:element name="alias" type="xs:normalizedString" minOccurs="0"/&gt;     &lt;xs:element name="msisdn" type="ct:typeDialString" minOccurs="0"/&gt;     &lt;xs:element name="fssn" type="xs:unsignedLong" minOccurs="0"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Fleet specific short number&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:element&gt;     &lt;xs:element name="external" type="ct:typeExternal" minOccurs="0"/&gt;     &lt;xs:element name="opta" type="ct:typeOPTA" minOccurs="0"/&gt;     &lt;xs:element name="cell" type="xs:short" minOccurs="0"/&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>	

### Complex Type ct:typeSubscriberAddress

Namespace	DR-GW-Interface/CommonTypes	
Annotations		
Diagram		
Used by	Element	ct:typeAddress/ct:subscriber
Model	ct:ssi   ct:tsi	
Children	ct:ssi, ct:tsi	
Source	<pre> &lt;xs:complexType name="typeSubscriberAddress"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation/&gt;   &lt;/xs:annotation&gt;   &lt;xs:choice&gt;     &lt;xs:element name="ssi" type="xs:unsignedLong"/&gt;     &lt;xs:element name="tsi" type="ct:typeTSI"/&gt;   &lt;/xs:choice&gt; &lt;/xs:complexType&gt; </pre>	

### Complex Type ct:typeTSI

Namespace	DR-GW-Interface/CommonTypes
-----------	-----------------------------

Annotations	Basic type for TETRA subscriber identity containing Network code(MNC) and Country code(MCC).
Diagram	<pre> graph LR     typeTSI[Basic type for TETRA subscriber identity containing Network code(MNC) and Country code(MCC)] --- mnc[mnc]     typeTSI --- mcc[mcc]     typeTSI --- ssi[ssi]     </pre>
Used by	Element ct:typeSubscriberAddress/ct:tsi
Model	ct:mnc , ct:mcc , ct:ssi
Children	ct:mcc, ct:mnc, ct:ssi
Source	<pre> &lt;xs:complexType name="typeTSI"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Basic type for TETRA subscriber identity containing Network code(MNC) and Country code(MCC).&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="mnc" type="xs:unsignedShort" /&gt;     &lt;xs:element name="mcc" type="xs:unsignedShort" /&gt;     &lt;xs:element name="ssi" type="xs:unsignedLong" /&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>

### Complex Type ct:typeExternal

Namespace	DR-GW-Interface/CommonTypes
Annotations	External number consisting of Gateway number + DialString
Diagram	<pre> graph LR     typeExternal[External number consisting of Gateway number + DialString] --- gatewayNumber[gatewayNumber]     typeExternal --- number[number]     </pre>
Used by	Element ct:typeAddress/ct:external
Model	ct:gatewayNumber , ct:number
Children	ct:gatewayNumber, ct:number
Source	<pre> &lt;xs:complexType name="typeExternal"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;External number consisting of Gateway number + DialString&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="gatewayNumber" type="xs:unsignedLong" /&gt;     &lt;xs:element name="number" type="ct:typeDialString" /&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>

### Complex Type ct:typeResult

Namespace	DR-GW-Interface/CommonTypes
Annotations	Common result values used in every response and optional specific subsystem result codes.
Diagram	<pre> graph LR     typeResult[Common result values used in every response and optional specific subsystem result codes.] --- responseCode[responseCode]     typeResult --- sourceSystem[sourceSystem]     typeResult --- result[result]     </pre>

Used by	Elements ct:typeEvent/ct:result, ct:typeResponse/ct:result
Model	ct:responseCode , ct:sourceSystem{0,1} , ct:result{0,1}
Children	ct:responseCode, ct:result, ct:sourceSystem
Source	<pre> &lt;xs:complexType name="typeResult"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Common result values used in every response and optional specific subsystem     result codes.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="responseCode" type="ct:typeResponseCode"/&gt;     &lt;xs:element name="sourceSystem" type="ct:typeSourceSystem" minOccurs="0"/&gt;     &lt;xs:element name="result" type="xs:unsignedLong" minOccurs="0"/&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>

## Complex Type ct:typeResponse

Namespace	DR-GW-Interface/CommonTypes
Annotations	Response contains result of execution of any method.
Diagram	
Model	ct:requestId , ct:result
Children	ct:requestId, ct:result
Source	<pre> &lt;xs:complexType name="typeResponse"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Response contains result of execution of any method.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="requestId" type="xs:unsignedLong"/&gt;     &lt;xs:element name="result" type="ct:typeResult"/&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>

## Complex Type ct:typeEvent

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Model	ct:requestId{0,1} , ct:result{0,1}
Children	ct:requestId, ct:result
Source	<pre> &lt;xs:complexType name="typeEvent"&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="requestId" type="xs:unsignedLong" minOccurs="0"/&gt;     &lt;xs:element name="result" type="ct:typeResult" minOccurs="0"/&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>

## Complex Type ct:typeEmpty

Namespace	DR-GW-Interface/CommonTypes
Annotations	Explicit type specification for elements that shall be empty.
Diagram	
Source	<pre> &lt;xs:complexType name="typeEmpty"&gt;   &lt;xs:annotation&gt; </pre>

```

    <xs:documentation>Explicit type specification for elements that shall be empty.</
xs:documentation>
</xs:annotation>
</xs:complexType>

```

## Simple Type(s)

### Simple Type `ct:typeDialString`

Namespace	DR-GW-Interface/CommonTypes
Annotations	Allowed characters are digits 0 - 9, *, #, A, B, C and D. Maximum length is 24 characters.
Diagram	
Type	restriction of <code>xs:normalizedString</code>
Facets	maxLength 24
Used by	Elements <code>ct:typeAddress/ct:msisdn</code> , <code>ct:typeExternal/ct:number</code>
Source	<pre> &lt;xs:simpleType name="typeDialString"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Allowed characters are digits 0 - 9, *, #, A, B, C and D. Maximum length is 24 characters.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:maxLength value="24"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>

### Simple Type `ct:typeOPTA`

Namespace	DR-GW-Interface/CommonTypes
Annotations	OPTA string. Maximum length is 24 characters.
Diagram	
Type	restriction of <code>xs:normalizedString</code>
Facets	maxLength 24
Used by	Element <code>ct:typeAddress/ct:opta</code>
Source	<pre> &lt;xs:simpleType name="typeOPTA"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;OPTA string. Maximum length is 24 characters.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:maxLength value="24"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>

### Simple Type `ct:typeResponseCode`

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	restriction of <code>xs:normalizedString</code>

Facets	enumeration	success
	enumeration	final_response_pending
	enumeration	error
	enumeration	not_authorized_error
	enumeration	temporary_failure
	enumeration	subscription_failed
Used by	Element	ct:typeResult/ct:responseCode
Source	<pre> &lt;xs:simpleType name="typeResponseCode"&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="success"/&gt;     &lt;xs:enumeration value="final_response_pending"/&gt;     &lt;xs:enumeration value="error"/&gt;     &lt;xs:enumeration value="not_authorized_error"/&gt;     &lt;xs:enumeration value="temporary_failure"/&gt;     &lt;xs:enumeration value="subscription_failed"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>	

### Simple Type ct:typeSourceSystem

Namespace	DR-GW-Interface/CommonTypes	
Diagram		
Type	restriction of xs:normalizedString	
Facets	enumeration	DR-GW
	enumeration	TCS-API
	enumeration	TETRA
	enumeration	TACTILON-API
Used by	Element	ct:typeResult/ct:sourceSystem
Source	<pre> &lt;xs:simpleType name="typeSourceSystem"&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="DR-GW"/&gt;     &lt;xs:enumeration value="TCS-API"/&gt;     &lt;xs:enumeration value="TETRA"/&gt;     &lt;xs:enumeration value="TACTILON-API"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>	

### Simple Type ct:typeAddressingStyle

Namespace	DR-GW-Interface/CommonTypes	
Annotations	Describes the IP addressing style. Unicast or multicast.	
Diagram		
Type	restriction of xs:normalizedString	
Facets	enumeration	ucast
	enumeration	mcast
Source	<pre> &lt;xs:simpleType name="typeAddressingStyle"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Describes the IP addressing style. Unicast or multicast.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="ucast"/&gt;     &lt;xs:enumeration value="mcast"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>	

```
</xs:restriction>
</xs:simpleType>
```

## Namespace: "DR-GW-Interface/DR-GW-Call.CommonTypes"

### Schema(s)

#### Imported schema DR-GW-Call.CommonTypes.xsd


Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Annotations	Version 1.2
Properties	attribute form default: unqualified element form default: qualified

### Element(s)

#### Element typeSelection / level

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
Diagram			
Type	typeSelectionLevel		
Properties	content:	simple	
Facets	enumeration	no	No selection. Used to remove selection.
	enumeration	event	Event monitoring.
	enumeration	audio	Audio monitoring.
	enumeration	use	Selection level use.
	enumeration	a_use	Selection level active use.
Source	<xs:element name="level" type="typeSelectionLevel"/>		

#### Element typeSelection / target

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Diagram	



Type	ct:typeAddress
Properties	content: complex
Model	ct:subscriber{0,1} , ct:alias{0,1} , ct:msisdn{0,1} , ct:fssn{0,1} , ct:external{0,1} , ct:opta{0,1} , ct:cell{0,1}
Children	ct:alias, ct:cell, ct:external, ct:fssn, ct:msisdn, ct:opta, ct:subscriber
Instance	<pre>&lt;target xmlns="DR-GW-Interface/DR-GW-Call.CommonTypes" xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:subscriber&gt;{0,1}&lt;/ct:subscriber&gt;   &lt;ct:alias&gt;{0,1}&lt;/ct:alias&gt;   &lt;ct:msisdn&gt;{0,1}&lt;/ct:msisdn&gt;   &lt;ct:fssn&gt;{0,1}&lt;/ct:fssn&gt;   &lt;ct:external&gt;{0,1}&lt;/ct:external&gt;   &lt;ct:opta&gt;{0,1}&lt;/ct:opta&gt;   &lt;ct:cell&gt;{0,1}&lt;/ct:cell&gt; &lt;/target&gt;</pre>
Source	<code>&lt;xs:element name="target" type="ct:typeAddress"/&gt;</code>

## Element typeCallAttributes / hook

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Diagram	
Type	xs:boolean
Properties	content: simple minOccurs: 0
Source	<code>&lt;xs:element name="hook" type="xs:boolean" minOccurs="0"/&gt;</code>

## Element typeCallAttributes / mode

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Diagram	
Type	typeCallMode
Properties	content: simple minOccurs: 0
Facets	enumeration: simplex enumeration: duplex
Source	<code>&lt;xs:element name="mode" type="typeCallMode" minOccurs="0"/&gt;</code>

## Element typeCallAttributes / commtype

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Diagram	
Type	typeCallType
Properties	content: simple minOccurs: 0
Facets	enumeration: p2p enumeration: p2mp

	enumeration      bcast
Source	<code>&lt;xs:element name="commtype" type="typeCallType" minOccurs="0"/&gt;</code>

**Element typeCallAttributes / priority**

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes						
Diagram							
Type	xs:unsignedByte						
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>default:</td><td>1</td></tr> </table>	content:	simple	minOccurs:	0	default:	1
content:	simple						
minOccurs:	0						
default:	1						
Source	<code>&lt;xs:element name="priority" type="xs:unsignedByte" default="1" minOccurs="0"/&gt;</code>						

**Element typeCallAttributes / encryption**

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes						
Diagram							
Type	xs:boolean						
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>default:</td><td>true</td></tr> </table>	content:	simple	minOccurs:	0	default:	true
content:	simple						
minOccurs:	0						
default:	true						
Source	<code>&lt;xs:element name="encryption" type="xs:boolean" default="true" minOccurs="0"/&gt;</code>						

**Element typeCallAttributes / ambienceListen**

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes						
Diagram							
Type	xs:boolean						
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>default:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0	default:	0
content:	simple						
minOccurs:	0						
default:	0						
Source	<code>&lt;xs:element name="ambienceListen" type="xs:boolean" default="0" minOccurs="0"/&gt;</code>						

**Element typeCallAttributes / req2speak**

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Diagram	
Type	xs:boolean

Properties	content:	simple
	minOccurs:	0
	default:	1
Source	<code>&lt;xs:element name="req2speak" type="xs:boolean" default="1" minOccurs="0"/&gt;</code>	

## Element typeCallAttributes / demandPriority

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes	
Diagram		
Type	typeTxDemandPriority	
Properties	content:	simple
	minOccurs:	0
	default:	normal
Facets	enumeration	normal
	enumeration	preemptive
	enumeration	emergency
Source	<code>&lt;xs:element name="demandPriority" type="typeTxDemandPriority" default="normal" minOccurs="0"/&gt;</code>	

## Element typeCallAttributes / txCoverageInfo

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
Diagram			
Type	typeTxCoverageInfo		
Properties	content:	simple	
	minOccurs:	0	
	default:	dummy	
Facets	enumeration	dummy	Coverage information is not valid.
	enumeration	all	All resources were successfully reserved within group area.
	enumeration	partial	Resources were reserved only partly within group area.
	enumeration	none	No resources were reserved within group area.
Source	<code>&lt;xs:element name="txCoverageInfo" type="typeTxCoverageInfo" minOccurs="0" default="dummy"/&gt;</code>		

## Element typeTxGranted / txGrant

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes	
Diagram		
Type	typeTxGrant	
Properties	content:	simple
Facets	enumeration	granted

	enumeration	notGranted
	enumeration	queued
	enumeration	granted2another
Source	<xs:element name="txGrant" type="typeTxGrant"/>	

## Element typeTxGranted / talkingParty

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes				
Diagram	<p>Diagram illustrating the structure of the <code>ct:typeAddress</code> complex type. It is a container for several optional elements: <code>subscriber</code>, <code>alias</code>, <code>msisdn</code>, <code>fssn</code>, <code>external</code>, <code>opta</code>, and <code>cell</code>. A note indicates it is the basic type for all possible TETRA address types (SSI, TSI, MSISDN, FSSN, OPTA).</p>				
Type	ct:typeAddress				
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	complex	minOccurs:	0
content:	complex				
minOccurs:	0				
Model	ct:subscriber{0,1} , ct:alias{0,1} , ct:msisdn{0,1} , ct:fssn{0,1} , ct:external{0,1} , ct:opta{0,1} , ct:cell{0,1}				
Children	ct:alias, ct:cell, ct:external, ct:fssn, ct:msisdn, ct:opta, ct:subscriber				
Instance	<pre>&lt;talkingParty xmlns="DR-GW-Interface/DR-GW-Call.CommonTypes" xmlns:ct="DR-GW-Interface/CommonTypes"&gt;   &lt;ct:subscriber&gt;{0,1}&lt;/ct:subscriber&gt;   &lt;ct:alias&gt;{0,1}&lt;/ct:alias&gt;   &lt;ct:msisdn&gt;{0,1}&lt;/ct:msisdn&gt;   &lt;ct:fssn&gt;{0,1}&lt;/ct:fssn&gt;   &lt;ct:external&gt;{0,1}&lt;/ct:external&gt;   &lt;ct:opta&gt;{0,1}&lt;/ct:opta&gt;   &lt;ct:cell&gt;{0,1}&lt;/ct:cell&gt; &lt;/talkingParty&gt;</pre>				
Source	<xs:element name="talkingParty" type="ct:typeAddress" minOccurs="0"/>				

## Element typeTxGranted / encryption

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes						
Diagram	<p>Diagram illustrating the structure of the <code>encryption</code> element, which is connected to the <code>xs:boolean</code> primitive type. A note states it is a built-in primitive type defining boolean values true and false.</p>						
Type	xs:boolean						
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>default:</td><td>true</td></tr> </table>	content:	simple	minOccurs:	0	default:	true
content:	simple						
minOccurs:	0						
default:	true						

Source	<code>&lt;xs:element name="encryption" type="xs:boolean" default="true" minOccurs="0"/&gt;</code>
--------	---

## Element typeTxGranted / txPriority

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
Diagram			
Type	typeTxPriority		
Properties	content:	simple	
	minOccurs:	0	
	default:	normal	
Facets	enumeration	normal	
	enumeration	emergency	
Source	<code>&lt;xs:element name="txPriority" type="typeTxPriority" minOccurs="0" default="normal"/&gt;</code>		

## Element typeTxGranted / txCoverageInfo

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
Diagram			
Type	typeTxCoverageInfo		
Properties	content:	simple	
	minOccurs:	0	
	default:	dummy	
Facets	enumeration	dummy	Coverage information is not valid.
	enumeration	all	All resources were successfully reserved within group area.
	enumeration	partial	Resources were reserved only partly within group area.
	enumeration	none	No resources were reserved within group area.
Source	<code>&lt;xs:element name="txCoverageInfo" type="typeTxCoverageInfo" minOccurs="0" default="dummy"/&gt;</code>		

## Element typeTxGranted / txInterrupt

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
Annotations	Defines whether previous speaker's speech item was interrupted by this speech item. Valid only when txGrant is granted2another.		
Diagram			
Type	xs:boolean		
Properties	content:	simple	
	minOccurs:	0	
	default:	false	

Source	<pre> &lt;xs:element name="txInterrupt" type="xs:boolean" default="false" minOccurs="0"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Defines whether previous speaker's speech item was interrupted by this speech     item. Valid only when txGrant is granted2another.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;/xs:element&gt; </pre>
--------	--

## Element typeTxGranted / txRepeat

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes						
Annotations	Timer to repeat the PTT. Units are seconds. Always suggested by the DF-gateway. Only valid when txGrant=granted.						
Diagram							
Type	xs:unsignedLong						
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>default:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0	default:	0
content:	simple						
minOccurs:	0						
default:	0						
Source	<pre> &lt;xs:element name="txRepeat" type="xs:unsignedLong" minOccurs="0" default="0"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Timer to repeat the PTT. Units are seconds. Always suggested by the DF-     gateway. Only valid when txGrant=granted.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;/xs:element&gt; </pre>						

## Element typeTxGranted / workstationId

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes				
Annotations	Id of the currently speaking workstation, used for "neighbours" feature. Only valid when txGrant=granted and when supplied by the DF-client in PTT request.				
Diagram					
Type	xs:normalizedString				
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0
content:	simple				
minOccurs:	0				
Source	<pre> &lt;xs:element name="workstationId" type="xs:normalizedString" minOccurs="0"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Id of the currently speaking workstation, used for "neighbours" feature. Only     valid when txGrant=granted and when supplied by the DF-client in PTT request.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;/xs:element&gt; </pre>				

## Element typeDisconnectCause / protocol

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Diagram	
Type	restriction of xs:normalizedString

Properties	content: simple
Facets	enumeration DR-GW
	enumeration TCS-API
Source	<pre>&lt;xs:element name="protocol"&gt;   &lt;xs:simpleType&gt;     &lt;xs:restriction base="xs:normalizedString"&gt;       &lt;xs:enumeration value="DR-GW"/&gt;       &lt;xs:enumeration value="TCS-API"/&gt;     &lt;/xs:restriction&gt;   &lt;/xs:simpleType&gt; &lt;/xs:element&gt;</pre>

## Element typeDisconnectCause / code

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Annotations	Value according to DR-GW-Reason header in DR-GW-Interface specification. It should only be present if action is "disconnected" and holds the reason for call disconnection.
Diagram	<p>The diagram shows an element named 'code' with a note: "Value according to DR-GW-Reason header in DR-GW-Interface specification. It should only be present if action is 'disconnected' and holds the reason for call disconnection." It is connected to the 'xs:unsignedInt' datatype, which has a note: "Built-in derived type. The unsignedInt datatype is derived from unsignedLong by setting the value of maxInclusive to be..."</p>
Type	xs:unsignedInt
Properties	content: simple
Source	<pre>&lt;xs:element name="code" type="xs:unsignedInt"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Value according to DR-GW-Reason header in DR-GW-Interface specification. It should only be present if action is "disconnected" and holds the reason for call disconnection.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt; &lt;/xs:element&gt;</pre>

## Element typeDisconnectCause / text

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Annotations	Optional textual representation of the cause.
Diagram	<p>The diagram shows an element named 'text' with a note: "Optional textual representation of the cause." It is connected to the 'restricts: xs:normalizedString' datatype, which has a plus sign indicating a restriction.</p>
Type	restriction of xs:normalizedString
Properties	content: simple minOccurs: 0
Facets	maxLength 80
Source	<pre>&lt;xs:element name="text" minOccurs="0"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Optional textual representation of the cause.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:simpleType&gt;     &lt;xs:restriction base="xs:normalizedString"&gt;       &lt;xs:maxLength value="80"/&gt;     &lt;/xs:restriction&gt;   &lt;/xs:simpleType&gt; &lt;/xs:element&gt;</pre>

## Complex Type(s)

### Complex Type typeSelection

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Annotations	
Diagram	
Used by	Element Call_Select/sel
Model	level , target
Children	level, target
Source	<pre> &lt;xs:complexType name="typeSelection"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation/&gt;   &lt;/xs:annotation&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="level" type="typeSelectionLevel"/&gt;     &lt;xs:element name="target" type="ct:typeAddress"/&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>

### Complex Type typeCallAttributes

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Annotations	Contains all attributes of the TETRA voice call.
Diagram	
Used by	Elements Call_PTTRRequest/attributes, Call_Request/attributes
Model	hook{0,1} , mode{0,1} , commtype{0,1} , priority{0,1} , encryption{0,1} , ambienceListen{0,1} , req2speak{0,1} , demandPriority{0,1} , txCoverageInfo{0,1}
Children	ambienceListen, commtype, demandPriority, encryption, hook, mode, priority, req2speak, txCoverageInfo
Source	<pre> &lt;xs:complexType name="typeCallAttributes"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Contains all attributes of the TETRA voice call.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="hook" type="xs:boolean" minOccurs="0"/&gt;     &lt;xs:element name="mode" type="typeCallMode" minOccurs="0"/&gt;     &lt;xs:element name="commtype" type="typeCallType" minOccurs="0"/&gt;     &lt;xs:element name="priority" type="xs:unsignedByte" default="1" minOccurs="0"/&gt;     &lt;xs:element name="encryption" type="xs:boolean" default="true" minOccurs="0"/&gt;     &lt;xs:element name="ambienceListen" type="xs:boolean" default="0" minOccurs="0"/&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>



```

<xs:element name="req2speak" type="xs:boolean" default="1" minOccurs="0"/>
<xs:element name="demandPriority" type="typeTxDemandPriority" default="normal" minOccurs="0"/>
<xs:element name="txCoverageInfo" type="typeTxCoverageInfo" minOccurs="0" default="dummy"/>
</xs:sequence>
</xs:complexType>

```

## Complex Type typeTxGranted

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Annotations	This event is used to inform of granted transmission request. This event is called when the transmission is granted to client, to another user or the request has been queued.
Diagram	
Model	txGrant , talkingParty{0,1} , encryption{0,1} , txPriority{0,1} , txCoverageInfo{0,1} , txInterrupt{0,1} , txRepeat{0,1} , workstationId{0,1}
Children	encryption, talkingParty, txCoverageInfo, txGrant, txInterrupt, txPriority, txRepeat, workstationId
Source	<pre> &lt;xs:complexType name="typeTxGranted"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;This event is used to inform of granted transmission request. This event is called when the transmission is granted to client, to another user or the request has been queued.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="txGrant" type="typeTxGrant"/&gt;     &lt;xs:element name="talkingParty" type="ct:typeAddress" minOccurs="0"/&gt;     &lt;xs:element name="encryption" type="xs:boolean" default="true" minOccurs="0"/&gt;     &lt;xs:element name="txPriority" type="typeTxPriority" minOccurs="0" default="normal"/&gt;     &lt;xs:element name="txCoverageInfo" type="typeTxCoverageInfo" minOccurs="0" default="dummy"/&gt;     &lt;xs:element name="txInterrupt" type="xs:boolean" default="false" minOccurs="0"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Defines whether previous speaker's speech item was interrupted by this speech item. Valid only when txGrant is granted2another.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:element&gt;     &lt;xs:element name="txRepeat" type="xs:unsignedLong" minOccurs="0" default="0"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Timer to repeat the PTT. Units are seconds. Always suggested by the DF-gateway. Only valid when txGrant=granted.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:element&gt;     &lt;xs:element name="workstationId" type="xs:normalizedString" minOccurs="0"&gt; </pre>

```

<xs:annotation>
  <xs:documentation>Id of the currently speaking workstation, used for "neighbours"
  feature. Only valid when txGrant=granted and when supplied by the DF-client in PTT request.</
xs:documentation>
</xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>

```

## Complex Type typeDisconnectCause

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Diagram	<pre> graph LR     typeDisconnectCause[typeDisconnectCause] --- protocol[protocol]     typeDisconnectCause --- code[code]     typeDisconnectCause --- text[text]     protocol --- plus1[+]     code --- plus2[+]     text --- plus3[+]     </pre> <p>Value according to DR-GW-Reason header in DR-GW-Interface specification. It should only be present if action is...</p> <p>Optional textual representation of the cause.</p>
Model	protocol , code , text{0,1}
Children	code, protocol, text
Source	<pre> &lt;xs:complexType name="typeDisconnectCause"&gt;   &lt;xs:sequence&gt;     &lt;xs:element name="protocol"&gt;       &lt;xs:simpleType&gt;         &lt;xs:restriction base="xs:normalizedString"&gt;           &lt;xs:enumeration value="DR-GW"/&gt;           &lt;xs:enumeration value="TCS-API"/&gt;         &lt;/xs:restriction&gt;       &lt;/xs:simpleType&gt;     &lt;/xs:element&gt;     &lt;xs:element name="code" type="xs:unsignedInt"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Value according to DR-GW-Reason header in DR-GW-Interface specification.         It should only be present if action is "disconnected" and holds the reason for call         disconnection.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:element&gt;     &lt;xs:element name="text" minOccurs="0"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Optional textual representation of the cause.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;       &lt;xs:simpleType&gt;         &lt;xs:restriction base="xs:normalizedString"&gt;           &lt;xs:maxLength value="80"/&gt;         &lt;/xs:restriction&gt;       &lt;/xs:simpleType&gt;     &lt;/xs:element&gt;   &lt;/xs:sequence&gt; &lt;/xs:complexType&gt; </pre>

## Simple Type(s)

### Simple Type typeSelectionLevel

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Annotations	Defines how the target is monitored.
Diagram	<pre> graph LR     typeSelectionLevel[typeSelectionLevel] --- xsNormalizedString[xs:normalizedString]     typeSelectionLevel --- plus[+]     xsNormalizedString --- plus2[+]     </pre> <p>Defines how the target is monitored.</p> <p>Built-in derived type. The normalizedString datatype represents white space normalized strings. The base type of...</p>

Type	restriction of xs:normalizedString		
Facets	enumeration	no	No selection. Used to remove selection.
	enumeration	event	Event monitoring.
	enumeration	audio	Audio monitoring.
	enumeration	use	Selection level use.
	enumeration	a_use	Selection level active use.
Used by	Element	typeSelection/level	
Source	<pre>&lt;xs:simpleType name="typeSelectionLevel"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Defines how the target is monitored.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="no"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;No selection. Used to remove selection.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="event"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Event monitoring.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="audio"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Audio monitoring.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="use"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Selection level use.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="a_use"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Selection level active use.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>		

## Simple Type typeActionRequest

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
Annotations	All possible call actions.		
Diagram			
Type	restriction of xs:normalizedString		
Facets	enumeration	setup	This method is used to initiate a new call setup. For a call setup to be successful it is required that the resources have been reserved prior this method call.
	enumeration	connect	This method is used to connect an incoming call.
	enumeration	hold	This method requests to put an individual call to hold.
	enumeration	unhold	This method is a request for resuming an individual call from hold.
	enumeration	disconnect	This method is used to disconnect a call.
	enumeration	transfer	This method is used to transfer an individual call to a new recipient.
	enumeration	releasecall	This method is used to release radio subscriber's individual

	call.
Used by	Element Call_Request/action
Source	<pre> &lt;xs:simpleType name="typeActionRequest"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;All possible call actions.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="setup"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This method is used to initiate a new call setup. For a call setup to be successful it is required that the resources have been reserved prior this method call.&lt;/ xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="connect"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This method is used to connect an incoming call.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="hold"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This method requests to put an individual call to hold.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="unhold"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This method is a request for resuming an individual call from hold.&lt;/ xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="disconnect"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This method is used to disconnect a call.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="transfer"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This method is used to transfer an individual call to a new recipient.&lt;/ xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="releasecall"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This method is used to release radio subscriber's individual call.&lt;/ xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>

## Simple Type typeCallMode

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes				
Annotations	Call mode attribute. Choices are simplex or duplex.				
Diagram					
Type	restriction of xs:normalizedString				
Facets	<table> <tr> <td>enumeration</td><td>simplex</td></tr> <tr> <td>enumeration</td><td>duplex</td></tr> </table>	enumeration	simplex	enumeration	duplex
enumeration	simplex				
enumeration	duplex				
Used by	Element typeCallAttributes/mode				
Source	<pre> &lt;xs:simpleType name="typeCallMode"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Call mode attribute. Choices are simplex or duplex.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="simplex"/&gt;     &lt;xs:enumeration value="duplex"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>				

## Simple Type typeCallType

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes						
Annotations	Call type attribute. Choices are PointToPoint, Point2MultiPoint or Broadcast.						
Diagram							
Type	restriction of xs:normalizedString						
Facets	<table> <tr> <td>enumeration</td><td>p2p</td></tr> <tr> <td>enumeration</td><td>p2mp</td></tr> <tr> <td>enumeration</td><td>bcast</td></tr> </table>	enumeration	p2p	enumeration	p2mp	enumeration	bcast
enumeration	p2p						
enumeration	p2mp						
enumeration	bcast						
Used by	Element typeCallAttributes/commtype						
Source	<pre> &lt;xs:simpleType name="typeCallType"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Call type attribute. Choices are PointToPoint, Point2MultiPoint or Broadcast.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="p2p"/&gt;     &lt;xs:enumeration value="p2mp"/&gt;     &lt;xs:enumeration value="bcast"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>						

## Simple Type typeTxDemandPriority

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes						
Annotations	Defines priority of speech item request: normal, pre-emptive, or emergency.						
Diagram							
Type	restriction of xs:normalizedString						
Facets	<table> <tr> <td>enumeration</td><td>normal</td></tr> <tr> <td>enumeration</td><td>preemptive</td></tr> <tr> <td>enumeration</td><td>emergency</td></tr> </table>	enumeration	normal	enumeration	preemptive	enumeration	emergency
enumeration	normal						
enumeration	preemptive						
enumeration	emergency						
Used by	Element typeCallAttributes/demandPriority						
Source	<pre> &lt;xs:simpleType name="typeTxDemandPriority"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Defines priority of speech item request: normal, pre-emptive, or emergency.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="normal"/&gt;     &lt;xs:enumeration value="preemptive"/&gt;     &lt;xs:enumeration value="emergency"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>						

## Simple Type typeTxCoverageInfo

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Annotations	Specifies transmission coverage information in a group call. Group area definition affects how the system tries to reserve resources. Group area can be defined as fixed or shifting area. If group area is defined as fixed, the system tries to reserve all cells that belong to the group area. If group area is defined as shifting area, the system tries to reserve only those cells where the group members are located.

Diagram	<div><div></div></div>		
Type	restriction of xs:string		
Facets	enumeration	dummy	Coverage information is not valid.
	enumeration	all	All resources were successfully reserved within group area.
	enumeration	partial	Resources were reserved only partly within group area.
	enumeration	none	No resources were reserved within group area.
Used by	Elements	typeCallAttributes/txCoverageInfo, typeTxGranted/txCoverageInfo	
Source	<pre>&lt;xs:simpleType name="typeTxCoverageInfo"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Specifies transmission coverage information in a group call. Group area     definition affects how the system tries to reserve resources. Group area can be defined as fixed     or shifting area. If group area is defined as fixed, the system tries to reserve all cells that     belong to the group area. If group area is defined as shifting area, the system tries to reserve     only those cells where the group members are located.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:string"&gt;     &lt;xs:enumeration value="dummy"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Coverage information is not valid.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="all"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;All resources were successfully reserved within group area.&lt;/ xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="partial"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Resources were reserved only partly within group area.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="none"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;No resources were reserved within group area.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>		

### Simple Type typeWorkstationId

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
Annotations	Optional parameter is used to support the "neighbours" feature.		
Diagram	<p>Optional parameter is used to support the "neighbours" feature.</p> <p>Built-in derived type. The normalizedString datatype represents white space normalized strings. The base type of...</p>		
Type	xs:normalizedString		
Used by	Elements	Call_PTTRRequest/workstationId, Call_Request/workstationId	
Source	<pre>&lt;xs:simpleType name="typeWorkstationId"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Optional parameter is used to support the "neighbours" feature.&lt;/ xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;/xs:restriction&gt;   &lt;/xs:simpleType&gt;</pre>		

## Simple Type typeActionPTTRequest

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
Annotations	All possible PTT requests.		
Diagram			
Type	restriction of xs:normalizedString		
Facets	enumeration	demandtx	This method can be used to request a speech item for a connected call.
	enumeration	ceasetx	This method is used to inform the system that the speech item is not needed any more.
Used by	Element	Call_PTTRequest/action	
Source	<pre>&lt;xs:simpleType name="typeActionPTTRequest"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;All possible PTT requests.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="demandtx"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This method can be used to request a speech item for a connected call.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="ceasetx"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This method is used to inform the system that the speech item is not needed any more.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>		

## Simple Type typeKeyExchangeAction

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
Annotations	Action type for key exchange request.		
Diagram			
Type	restriction of xs:normalizedString		
Facets	enumeration	start	
	enumeration	stop	
Used by	Element	Call_KeyExchange/action	
Source	<pre>&lt;xs:simpleType name="typeKeyExchangeAction"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Action type for key exchange request.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="start"/&gt;     &lt;xs:enumeration value="stop"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>		

## Simple Type typeActionEvent

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
-----------	--	--	--

Annotations	All possible call actions.		
Diagram			
Type	restriction of xs:normalizedString		
Facets	enumeration	incoming	This event fired when there is an incoming call. This is the first indication of a new incoming call.
	enumeration	connected	This event is used to inform that call has been connected and call setup is finished.
	enumeration	held	This event is used to inform TCS Client that individual call was put to hold.
	enumeration	resumed	This event is used to inform that individual call has been taken from hold.
	enumeration	disconnected	This event is used to inform that the call was disconnected.
	enumeration	transferred	This event is a response to transfer method call and indicates the result of the request.
Source	<pre>&lt;xs:simpleType name="typeActionEvent"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;All possible call actions.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="incoming"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This event fired when there is an incoming call. This is the first indication of a new incoming call.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="connected"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This event is used to inform that call has been connected and call setup is finished.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="held"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This event is used to inform TCS Client that individual call was put to hold.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="resumed"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This event is used to inform that individual call has been taken from hold.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="disconnected"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This event is used to inform that the call was disconnected.&lt;/ xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="transferred"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;This event is a response to transfer method call and indicates the result of the request.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt;</pre>		

## Simple Type typeTxPriority

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Annotations	Defines the priority of the transmission.



Diagram					
Type	restriction of xs:normalizedString				
Facets	<table> <tr> <td>enumeration</td><td>normal</td></tr> <tr> <td>enumeration</td><td>emergency</td></tr> </table>	enumeration	normal	enumeration	emergency
enumeration	normal				
enumeration	emergency				
Used by	Element typeTxGranted/txPriority				
Source	<pre> &lt;xs:simpleType name="typeTxPriority"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Defines the priority of the transmission.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="normal"/&gt;     &lt;xs:enumeration value="emergency"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>				

### Simple Type typeTxGrant

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes								
Annotations	Defines to whom speech item was granted.								
Diagram									
Type	restriction of xs:normalizedString								
Facets	<table> <tr> <td>enumeration</td><td>granted</td></tr> <tr> <td>enumeration</td><td>notGranted</td></tr> <tr> <td>enumeration</td><td>queued</td></tr> <tr> <td>enumeration</td><td>granted2another</td></tr> </table>	enumeration	granted	enumeration	notGranted	enumeration	queued	enumeration	granted2another
enumeration	granted								
enumeration	notGranted								
enumeration	queued								
enumeration	granted2another								
Used by	Element typeTxGranted/txGrant								
Source	<pre> &lt;xs:simpleType name="typeTxGrant"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Defines to whom speech item was granted.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="granted"/&gt;     &lt;xs:enumeration value="notGranted"/&gt;     &lt;xs:enumeration value="queued"/&gt;     &lt;xs:enumeration value="granted2another"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>								

### Simple Type typeAudioCodec

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
Annotations	Audio codecs enumeration type. Currently supported are G.711 alaw, G.711 ulaw and TETRA audio codec.		
Diagram			
Type	restriction of xs:normalizedString		
Facets	<table> <tr> <td>enumeration</td><td>alaw</td></tr> </table>	enumeration	alaw
enumeration	alaw		

	enumeration          ulaw
	enumeration          tetra
Source	<pre> &lt;xs:simpleType name="typeAudioCodec"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Audio codecs enumeration type. Currently supported are G.711 alaw, G.711 ulaw     and TETRA audio codec.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="alaw"/&gt;     &lt;xs:enumeration value="ulaw"/&gt;     &lt;xs:enumeration value="tetra"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>

### Simple Type typeKeyExchangeState

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
Annotations	Represents current key state.		
Diagram			
Type	restriction of xs:normalizedString		
Facets	enumeration	keyValid	current key is valid, no user action required.
	enumeration	keyInvalid	Key invalid, user must request key exchange.
	enumeration	keyExchangeInProgress	Key exchange in progress, user may abort exchange or wait until it gets finished.
Source	<pre> &lt;xs:simpleType name="typeKeyExchangeState"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Represents current key state.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="keyValid"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;current key is valid, no user action required.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="keyInvalid"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Key invalid, user must request key exchange.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;     &lt;xs:enumeration value="keyExchangeInProgress"&gt;       &lt;xs:annotation&gt;         &lt;xs:documentation&gt;Key exchange in progress, user may abort exchange or wait until it gets         finished.&lt;/xs:documentation&gt;       &lt;/xs:annotation&gt;     &lt;/xs:enumeration&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>		

### Simple Type typeKeyExchangeCode

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes		
Annotations	See "Table 5.3: Status words of the commands" of the E-to-E Encryption SIM-ME Interface (Version 4.0.5) for all possible code values.		
Diagram			
Type	restriction of xs:hexBinary		
Facets	length	2	
Source	<pre> &lt;xs:simpleType name="typeKeyExchangeCode"&gt; </pre>		

```

<xs:annotation>
  <xs:documentation>See "Table 5.3: Status words of the commands" of the E-to-E Encryption SIM-ME
  Interface (Version 4.0.5) for all possible code values.</xs:documentation>
</xs:annotation>
<xs:restriction base="xs:hexBinary">
  <xs:length value="2"/>
</xs:restriction>
</xs:simpleType>

```

### Simple Type typeKeyExchangeText

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Annotations	The textual information supplied by the BOS-simcard and sent from the DF-Gateway to the DF-client.
Diagram	
Type	restriction of xs:normalizedString
Facets	maxLength 100
Source	<pre> &lt;xs:simpleType name="typeKeyExchangeText"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;The textual information supplied by the BOS-simcard and sent from the DF-     Gateway to the DF-client.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:maxLength value="100"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>

### Simple Type typeKeyExchangeTextPriority

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Annotations	Defines the priority of the KeyExchange information.
Diagram	
Type	restriction of xs:normalizedString
Facets	enumeration normal enumeration high
Source	<pre> &lt;xs:simpleType name="typeKeyExchangeTextPriority"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Defines the priority of the KeyExchange information.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="normal"/&gt;     &lt;xs:enumeration value="high"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>

### Simple Type typeKeyManagementTextPriority

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes
Annotations	Defines the priority of the keymanagement information.
Diagram	
Type	restriction of xs:normalizedString

Facets	enumeration	normal
	enumeration	high
Source	<pre> &lt;xs:simpleType name="typeKeyManagementTextPriority"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Defines the priority of the keymanagement information.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="normal"/&gt;     &lt;xs:enumeration value="high"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>	

### Simple Type typeUnitInEmergencyType

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes	
Annotations	Defines type of the subscriber. Refer to type tcsCallSubscriberType_t of the TCS-API.	
Diagram		
Type	restriction of xs:normalizedString	
Facets	enumeration	dummy
	enumeration	ms
	enumeration	g4wif
	enumeration	external
	enumeration	ws
Source	<pre> &lt;xs:simpleType name="typeUnitInEmergencyType"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Defines type of the subscriber. Refer to type tcsCallSubscriberType_t of the TCS-API.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="dummy"/&gt;     &lt;xs:enumeration value="ms"/&gt;     &lt;xs:enumeration value="g4wif"/&gt;     &lt;xs:enumeration value="external"/&gt;     &lt;xs:enumeration value="ws"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>	

### Simple Type typeEmergencyInfo

Namespace	DR-GW-Interface/DR-GW-Call.CommonTypes	
Annotations	Defines action taken by user in emergency.	
Diagram		
Type	restriction of xs:normalizedString	
Facets	enumeration	addTx
	enumeration	add
	enumeration	ceased
	enumeration	demandTx
	enumeration	removed
	enumeration	emergencyCallDisconnected
Source	<pre> &lt;xs:simpleType name="typeEmergencyInfo"&gt;   &lt;xs:annotation&gt;     &lt;xs:documentation&gt;Defines action taken by user in emergency.&lt;/xs:documentation&gt;   &lt;/xs:annotation&gt;   &lt;xs:restriction base="xs:normalizedString"&gt;     &lt;xs:enumeration value="addTx"/&gt;     &lt;xs:enumeration value="add"/&gt;     &lt;xs:enumeration value="ceased"/&gt;     &lt;xs:enumeration value="demandTx"/&gt;     &lt;xs:enumeration value="removed"/&gt;     &lt;xs:enumeration value="emergencyCallDisconnected"/&gt;   &lt;/xs:restriction&gt; &lt;/xs:simpleType&gt; </pre>	

```
</xs:annotation>
<xs:restriction base="xs:normalizedString">
  <xs:enumeration value="addTx"/>
  <xs:enumeration value="add"/>
  <xs:enumeration value="ceased"/>
  <xs:enumeration value="demandTx"/>
  <xs:enumeration value="removed"/>
  <xs:enumeration value="emergencyCallDisconnected"/>
</xs:restriction>
</xs:simpleType>
```