

Schema documentation for DR-GW-Recording.Events.xsd

july 28, 2026

Table of Contents

Namespace: "DR-GW-Interface/DR-GW-Recording.Events"	2
Schema(s)	2
Main schema DR-GW-Recording.Events.xsd	2
Element(s)	2
Element Record_Response	2
Element Record_GroupEvent	2
Element typeRecordEvent / sel	3
Element Record_IndividualEvent	3
Complex Type(s)	4
Complex Type typeRecordEvent	4
Namespace: "DR-GW-Interface/DR-GW-Recording.CommonTypes"	5
Schema(s)	5
Imported schema DR-GW-Recording.CommonTypes.xsd	5
Element(s)	5
Element typeRecordingTarget / level	5
Element typeRecordingTarget / target	5
Complex Type(s)	6
Complex Type typeRecordingTarget	6
Simple Type(s)	6
Simple Type typeRecordingLevel	6
Namespace: "DR-GW-Interface/CommonTypes"	7
Schema(s)	7
Imported schema CommonTypes.xsd	7
Element(s)	7
Element ct:typeResponse / ct:requestId	7
Element ct:typeResponse / ct:result	7
Element ct:typeResult / ct:responseCode	8
Element ct:typeResult / ct:sourceSystem	8
Element ct:typeResult / ct:result	8
Element ct:typeEvent / ct:requestId	8
Element ct:typeEvent / ct:result	9
Element ct:typeAddress / ct:subscriber	9
Element ct:typeSubscriberAddress / ct:ssi	10
Element ct:typeSubscriberAddress / ct:tsi	10
Element ct:typeTSI / ct:mnc	10
Element ct:typeTSI / ct:mcc	10
Element ct:typeTSI / ct:ssi	11
Element ct:typeAddress / ct:alias	11
Element ct:typeAddress / ct:msisdn	11
Element ct:typeAddress / ct:fssn	11
Element ct:typeAddress / ct:external	12
Element ct:typeExternal / ct:gatewayNumber	12
Element ct:typeExternal / ct:number	12
Element ct:typeAddress / ct:opta	13
Element ct:typeAddress / ct:cell	13
Element ct:typeRequest / ct:requestId	13
Complex Type(s)	13
Complex Type ct:typeResponse	13
Complex Type ct:typeResult	14
Complex Type ct:typeEvent	14
Complex Type ct:typeAddress	14
Complex Type ct:typeSubscriberAddress	15
Complex Type ct:typeTSI	15
Complex Type ct:typeExternal	16
Complex Type ct:typeRequest	16
Complex Type ct:typeEmpty	16
Simple Type(s)	17
Simple Type ct:typeResponseCode	17
Simple Type ct:typeSourceSystem	17
Simple Type ct:typeDialString	18

Simple Type ct:typeOPTA	18
Simple Type ct:typeAddressingStyle	18

Namespace: "DR-GW-Interface/DR-GW-Recording.Events"

Schema(s)

Main schema DR-GW-Recording.Events.xsd

Namespace	DR-GW-Interface/DR-GW-Recording.Events
Annotations	Version 1.2 DR-GW-Recording. Use for Archive recording applications.
Properties	attribute form default: unqualified element form default: qualified


Element(s)

Element Record_Response


Namespace	DR-GW-Interface/DR-GW-Recording.Events
Diagram	
Type	ct:typeResponse
Properties	content: complex
Model	ct:requestId, ct:result
Children	ct:requestId, ct:result
Instance	<pre><Record_Response xmlns="DR-GW-Interface/DR-GW-Recording.Events" xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:requestId>{1,1}</ct:requestId> <ct:result>{1,1}</ct:result> </Record_Response></pre>
Source	<pre><xs:element name="Record_Response" type="ct:typeResponse"/></pre>

Element Record_GroupEvent

Namespace	DR-GW-Interface/DR-GW-Recording.Events
Annotations	The method is used to inform about the result of placing group under either statistical(signaling and data) or active(audio and data) recording.

Diagram	
Type	typeRecordEvent
Type hierarchy	- ct.typeEvent - typeRecordEvent
Properties	content: complex
Model	ct:requestId{0,1} , ct:result{0,1} , sel
Children	ct:requestId, ct:result, sel
Instance	<pre><Record_GroupEvent xmlns="DR-GW-Interface/DR-GW-Recording.Events" xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:requestId>{0,1}</ct:requestId> <ct:result>{0,1}</ct:result> <sel>{1,1}</sel> </Record_GroupEvent></pre>
Source	<pre><xs:element name="Record_GroupEvent" type="typeRecordEvent"> <xs:annotation> <xs:documentation>The method is used to inform about the result of placing group under either statistical(signaling and data) or active(audio and data) recording.</xs:documentation> </xs:annotation> </xs:element></pre>

Element typeRecordEvent / sel

Namespace	DR-GW-Interface/DR-GW-Recording.Events
Diagram	
Type	typeRecordingTarget
Properties	content: complex
Model	level , target
Children	level, target
Instance	<pre><sel xmlns="DR-GW-Interface/DR-GW-Recording.Events" xmlns:ctR="DR-GW-Interface/DR-GW-Recording.CommonTypes"> <ctR:level>{1,1}</ctR:level> <ctR:target>{1,1}</ctR:target> </sel></pre>
Source	<pre><xs:element name="sel" type="ctR:typeRecordingTarget"/></pre>

Element Record_IndividualEvent

Namespace	DR-GW-Interface/DR-GW-Recording.Events
Annotations	The method is used to inform about the result of placing individual subscriber under either statistical(signaling and data) or active(audio and data) recording.

Diagram	The method is used to inform about the result of placing individual subscriber under either statistical(signaling and...
Type	typeRecordEvent
Type hierarchy	- ct.typeEvent - typeRecordEvent
Properties	content: complex
Model	ct:requestId{0,1} , ct:result{0,1} , sel
Children	ct:requestId, ct:result, sel
Instance	<pre><Record_IndividualEvent xmlns="DR-GW-Interface/DR-GW-Recording.Events" xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:requestId>{0,1}</ct:requestId> <ct:result>{0,1}</ct:result> <sel>{1,1}</sel> </Record_IndividualEvent></pre>
Source	<pre><xs:element name="Record_IndividualEvent" type="typeRecordEvent"> <xs:annotation> <xs:documentation>The method is used to inform about the result of placing individual subscriber under either statistical(signaling and data) or active(audio and data) recording.</ </xs:documentation> </xs:annotation> </xs:element></pre>

Complex Type(s)

Complex Type typeRecordEvent

Namespace	DR-GW-Interface/DR-GW-Recording.Events
Diagram	
Type	extension of ct.typeEvent
Type hierarchy	- ct.typeEvent - typeRecordEvent
Used by	Elements Record_GroupEvent, Record_IndividualEvent
Model	ct:requestId{0,1} , ct:result{0,1} , sel
Children	ct:requestId, ct:result, sel
Source	<pre><xs:complexType name="typeRecordEvent"> <xs:complexContent></pre>

```
<xs:extension base="ct:typeEvent">
  <xs:sequence>
    <xs:element name="sel" type="ctR:typeRecordingTarget"/>
  </xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
```

Namespace: "DR-GW-Interface/DR-GW-Recording.CommonTypes"

Schema(s)

Imported schema DR-GW-Recording.CommonTypes.xsd

Namespace	DR-GW-Interface/DR-GW-Recording.CommonTypes
Properties	attribute form default: unqualified
	element form default: qualified

Element(s)

Element typeRecordingTarget / level

Namespace	DR-GW-Interface/DR-GW-Recording.CommonTypes		
Diagram			
Type	typeRecordingLevel		
Properties	content:	simple	
Facets	enumeration	no	No recording. Used to stop the recording.
	enumeration	active	AR active recording level.
	enumeration	statistical	AR statistical recording level.
Source	<xs:element name="level" type="typeRecordingLevel"/>		

Element typeRecordingTarget / target

Namespace	DR-GW-Interface/DR-GW-Recording.CommonTypes		
Diagram			

Type	ct:typeAddress
Properties	content: complex
Model	ct:subscriber{0,1} , ct:alias{0,1} , ct:msisdn{0,1} , ct:fssn{0,1} , ct:external{0,1} , ct:opta{0,1} , ct:cell{0,1}
Children	ct:alias, ct:cell, ct:external, ct:fssn, ct:msisdn, ct:opta, ct:subscriber
Instance	<pre><target xmlns="DR-GW-Interface/DR-GW-Recording.CommonTypes" xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:subscriber>{0,1}</ct:subscriber> <ct:alias>{0,1}</ct:alias> <ct:msisdn>{0,1}</ct:msisdn> <ct:fssn>{0,1}</ct:fssn> <ct:external>{0,1}</ct:external> <ct:opta>{0,1}</ct:opta> <ct:cell>{0,1}</ct:cell> </target></pre>
Source	<pre><xs:element name="target" type="ct:typeAddress"/></pre>

Complex Type(s)

Complex Type typeRecordingTarget

Namespace	DR-GW-Interface/DR-GW-Recording.CommonTypes
Annotations	
Diagram	
Used by	Element typeRecordEvent/sel
Model	level , target
Children	level, target
Source	<pre><xs:complexType name="typeRecordingTarget"> <xs:annotation> <xs:documentation/> </xs:annotation> <xs:sequence> <xs:element name="level" type="typeRecordingLevel"/> <xs:element name="target" type="ct:typeAddress"/> </xs:sequence> </xs:complexType></pre>

Simple Type(s)

Simple Type typeRecordingLevel

Namespace	DR-GW-Interface/DR-GW-Recording.CommonTypes		
Annotations	Defines if the target is statistically or actively monitored.		
Diagram			
Type	restriction of xs:normalizedString		
Facets	enumeration	no	No recording. Used to stop the recording.
	enumeration	active	AR active recording level.
	enumeration	statistical	AR statistical recording level.
Used by	Element	typeRecordingTarget/level	
Source	<pre><xs:simpleType name="typeRecordingLevel"> <xs:annotation> <xs:documentation>Defines if the target is statistically or actively monitored.</ xs:documentation> </xs:annotation> <xs:restriction base="xs:normalizedString"></pre>		

```
<xs:enumeration value="no">
  <xs:annotation>
    <xs:documentation>No recording. Used to stop the recording.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="active">
  <xs:annotation>
    <xs:documentation>AR active recording level.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="statistical">
  <xs:annotation>
    <xs:documentation>AR statistical recording level.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
```

Namespace: "DR-GW-Interface/CommonTypes"

Schema(s)

Imported schema CommonTypes.xsd

Namespace	DR-GW-Interface/CommonTypes
Annotations	Version 1.2
Properties	attribute form default: unqualified element form default: qualified

Element(s)

Element ct:requestResponse / ct:requestId

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedLong
Properties	content: simple
Source	<xs:element name="requestId" type="xs:unsignedLong"/>

Element ct:requestResponse / ct:result

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeResult
Properties	content: complex
Model	ct:responseCode , ct:sourceSystem{0,1} , ct:result{0,1}

Children	ct:responseCode, ct:result, ct:sourceSystem
Instance	<pre><ct:result xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:responseCode>{1,1}</ct:responseCode> <ct:sourceSystem>{0,1}</ct:sourceSystem> <ct:result>{0,1}</ct:result> </ct:result></pre>
Source	<pre><xs:element name="result" type="ct:typeResult"/></pre>

Element ct:typeResult / ct:responseCode

Namespace	DR-GW-Interface/CommonTypes												
Diagram													
Type	ct:typeResponseCode												
Properties	content: simple												
Facets	<table border="1"> <tr><td>enumeration</td><td>success</td></tr> <tr><td>enumeration</td><td>final_response_pending</td></tr> <tr><td>enumeration</td><td>error</td></tr> <tr><td>enumeration</td><td>not_authorized_error</td></tr> <tr><td>enumeration</td><td>temporary_failure</td></tr> <tr><td>enumeration</td><td>subscription_failed</td></tr> </table>	enumeration	success	enumeration	final_response_pending	enumeration	error	enumeration	not_authorized_error	enumeration	temporary_failure	enumeration	subscription_failed
enumeration	success												
enumeration	final_response_pending												
enumeration	error												
enumeration	not_authorized_error												
enumeration	temporary_failure												
enumeration	subscription_failed												
Source	<pre><xs:element name="responseCode" type="ct:typeResponseCode"/></pre>												

Element ct:typeResult / ct:sourceSystem

Namespace	DR-GW-Interface/CommonTypes								
Diagram									
Type	ct:typeSourceSystem								
Properties	<table border="1"> <tr><td>content:</td><td>simple</td></tr> <tr><td>minOccurs:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0				
content:	simple								
minOccurs:	0								
Facets	<table border="1"> <tr><td>enumeration</td><td>DR-GW</td></tr> <tr><td>enumeration</td><td>TCS-API</td></tr> <tr><td>enumeration</td><td>TETRA</td></tr> <tr><td>enumeration</td><td>TACTILON-API</td></tr> </table>	enumeration	DR-GW	enumeration	TCS-API	enumeration	TETRA	enumeration	TACTILON-API
enumeration	DR-GW								
enumeration	TCS-API								
enumeration	TETRA								
enumeration	TACTILON-API								
Source	<pre><xs:element name="sourceSystem" type="ct:typeSourceSystem" minOccurs="0"/></pre>								

Element ct:typeResult / ct:result

Namespace	DR-GW-Interface/CommonTypes				
Diagram					
Type	xs:unsignedLong				
Properties	<table border="1"> <tr><td>content:</td><td>simple</td></tr> <tr><td>minOccurs:</td><td>0</td></tr> </table>	content:	simple	minOccurs:	0
content:	simple				
minOccurs:	0				
Source	<pre><xs:element name="result" type="xs:unsignedLong" minOccurs="0"/></pre>				

Element ct:typeEvent / ct:requestId

Namespace	DR-GW-Interface/CommonTypes
-----------	-----------------------------

Diagram	
Type	xs:unsignedLong
Properties	content: simple minOccurs: 0
Source	<code><xs:element name="requestId" type="xs:unsignedLong" minOccurs="0"/></code>

Element ct:typeEvent / ct:result

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeResult
Properties	content: complex minOccurs: 0
Model	ct:responseCode , ct:sourceSystem {0,1} , ct:result {0,1}
Children	ct:responseCode, ct:result, ct:sourceSystem
Instance	<pre><ct:result xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:responseCode>{1,1}</ct:responseCode> <ct:sourceSystem>{0,1}</ct:sourceSystem> <ct:result>{0,1}</ct:result> </ct:result></pre>
Source	<code><xs:element name="result" type="ct:typeResult" minOccurs="0"/></code>

Element ct:typeAddress / ct:subscriber

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeSubscriberAddress
Properties	content: complex minOccurs: 0
Model	ct:ssi ct:tsi
Children	ct:ssi, ct:tsi
Instance	<pre><ct:subscriber xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:ssi>{1,1}</ct:ssi> <ct:tsi>{1,1}</ct:tsi> </ct:subscriber></pre>

Source	<code><xs:element name="subscriber" type="ct:typeSubscriberAddress" minOccurs="0"/></code>
--------	--

Element ct:typeSubscriberAddress / ct:ssi

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedLong
Properties	content: simple
Source	<code><xs:element name="ssi" type="xs:unsignedLong"/></code>

Element ct:typeSubscriberAddress / ct:tsi

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeTSI
Properties	content: complex
Model	ct:mnc , ct:mcc , ct:ssi
Children	ct:mcc, ct:mnc, ct:ssi
Instance	<pre><ct:tsi xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:mnc>{1,1}</ct:mnc> <ct:mcc>{1,1}</ct:mcc> <ct:ssi>{1,1}</ct:ssi> </ct:tsi></pre>
Source	<code><xs:element name="tsi" type="ct:typeTSI"/></code>

Element ct:typeTSI / ct:mnc

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedShort
Properties	content: simple
Source	<code><xs:element name="mnc" type="xs:unsignedShort"/></code>

Element ct:typeTSI / ct:mcc

Namespace	DR-GW-Interface/CommonTypes
-----------	-----------------------------

Diagram	
Type	xs:unsignedShort
Properties	content: simple
Source	<code><xs:element name="mcc" type="xs:unsignedShort"/></code>

Element ct:typeTSI / ct:ssi

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedLong
Properties	content: simple
Source	<code><xs:element name="ssi" type="xs:unsignedLong"/></code>

Element ct:typeAddress / ct:alias

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:normalizedString
Properties	content: simple minOccurs: 0
Source	<code><xs:element name="alias" type="xs:normalizedString" minOccurs="0"/></code>

Element ct:typeAddress / ct:msisdn

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeDialString
Properties	content: simple minOccurs: 0
Facets	maxLength 24
Source	<code><xs:element name="msisdn" type="ct:typeDialString" minOccurs="0"/></code>

Element ct:typeAddress / ct:fssn

Namespace	DR-GW-Interface/CommonTypes
Annotations	Fleet specific short number

Diagram	
Type	xs:unsignedLong
Properties	content: simple minOccurs: 0
Source	<pre><xs:element name="fssn" type="xs:unsignedLong" minOccurs="0"> <xs:annotation> <xs:documentation>Fleet specific short number</xs:documentation> </xs:annotation> </xs:element></pre>

Element ct:typeAddress / ct:external

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeExternal
Properties	content: complex minOccurs: 0
Model	ct:gatewayNumber , ct:number
Children	ct:gatewayNumber, ct:number
Instance	<pre><ct:external xmlns:ct="DR-GW-Interface/CommonTypes"> <ct:gatewayNumber>{1,1}</ct:gatewayNumber> <ct:number>{1,1}</ct:number> </ct:external></pre>
Source	<pre><xs:element name="external" type="ct:typeExternal" minOccurs="0"/></pre>

Element ct:typeExternal / ct:gatewayNumber

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	xs:unsignedLong
Properties	content: simple
Source	<pre><xs:element name="gatewayNumber" type="xs:unsignedLong"/></pre>

Element ct:typeExternal / ct:number

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Type	ct:typeDialString

Properties	content:	simple
Facets	maxLength	24
Source	<code><xs:element name="number" type="ct:typeDialString"/></code>	

Element `ct:typeAddress` / `ct:opta`

Namespace	DR-GW-Interface/CommonTypes	
Diagram		
Type	ct:typeOPTA	
Properties	content:	simple
	minOccurs:	0
Facets	maxLength	24
Source	<code><xs:element name="opta" type="ct:typeOPTA" minOccurs="0"/></code>	

Element `ct:typeAddress` / `ct:cell`

Namespace	DR-GW-Interface/CommonTypes	
Diagram		
Type	xs:short	
Properties	content:	simple
	minOccurs:	0
Source	<code><xs:element name="cell" type="xs:short" minOccurs="0"/></code>	

Element `ct:typeRequest` / `ct:requestId`

Namespace	DR-GW-Interface/CommonTypes	
Diagram		
Type	xs:unsignedLong	
Properties	content:	simple
Source	<code><xs:element name="requestId" type="xs:unsignedLong"/></code>	


Complex Type(s)

Complex Type `ct:typeResponse`


Namespace	DR-GW-Interface/CommonTypes	
Annotations	Response contains result of execution of any method.	
Diagram		

Used by	Element Record_Response
Model	ct:requestId , ct:result
Children	ct:requestId, ct:result
Source	<pre> <xs:complexType name="typeResponse"> <xs:annotation> <xs:documentation>Response contains result of execution of any method.</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="requestId" type="xs:unsignedLong"/> <xs:element name="result" type="ct:typeResult"/> </xs:sequence> </xs:complexType> </pre>

Complex Type ct : typeResult

Namespace	DR-GW-Interface/CommonTypes
Annotations	Common result values used in every response and optional specific subsystem result codes.
Diagram	
Used by	Elements ct:typeEvent/ct:result, ct:typeResponse/ct:result
Model	ct:responseCode , ct:sourceSystem{0,1} , ct:result{0,1}
Children	ct:responseCode, ct:result, ct:sourceSystem
Source	<pre> <xs:complexType name="typeResult"> <xs:annotation> <xs:documentation>Common result values used in every response and optional specific subsystem result codes.</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="responseCode" type="ct:typeResponseCode"/> <xs:element name="sourceSystem" type="ct:typeSourceSystem" minOccurs="0"/> <xs:element name="result" type="xs:unsignedLong" minOccurs="0"/> </xs:sequence> </xs:complexType> </pre>

Complex Type ct : typeEvent

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Used by	Complex Type typeRecordEvent
Model	ct:requestId{0,1} , ct:result{0,1}
Children	ct:requestId, ct:result
Source	<pre> <xs:complexType name="typeEvent"> <xs:sequence> <xs:element name="requestId" type="xs:unsignedLong" minOccurs="0"/> <xs:element name="result" type="ct:typeResult" minOccurs="0"/> </xs:sequence> </xs:complexType> </pre>

Complex Type ct : typeAddress

Namespace	DR-GW-Interface/CommonTypes
Annotations	Basic type for all possible TETRA address types (SSI, TSI, MSISDN, FSSN, OPTA).


Diagram	
Used by	Element typeRecordingTarget/target
Model	ct:subscriber{0,1} , ct:alias{0,1} , ct:msisdn{0,1} , ct:fssn{0,1} , ct:external{0,1} , ct:opta{0,1} , ct:cell{0,1}
Children	ct:alias, ct:cell, ct:external, ct:fssn, ct:msisdn, ct:opta, ct:subscriber
Source	<pre> <xs:complexType name="typeAddress"> <xs:annotation> <xs:documentation>Basic type for all possible TETRA address types (SSI, TSI, MSISDN, FSSN, OPTA).</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="subscriber" type="ct:typeSubscriberAddress" minOccurs="0"/> <xs:element name="alias" type="xs:normalizedString" minOccurs="0"/> <xs:element name="msisdn" type="ct:typeDialString" minOccurs="0"/> <xs:element name="fssn" type="xs:unsignedLong" minOccurs="0"> <xs:annotation> <xs:documentation>Fleet specific short number</xs:documentation> </xs:annotation> </xs:element> <xs:element name="external" type="ct:typeExternal" minOccurs="0"/> <xs:element name="opta" type="ct:typeOPTA" minOccurs="0"/> <xs:element name="cell" type="xs:short" minOccurs="0"/> </xs:sequence> </xs:complexType> </pre>

Complex Type ct:typeSubscriberAddress


Namespace	DR-GW-Interface/CommonTypes
Annotations	
Diagram	
Used by	Element ct:typeAddress/ct:subscriber
Model	ct:ssi ct:tsi
Children	ct:ssi, ct:tsi
Source	<pre> <xs:complexType name="typeSubscriberAddress"> <xs:annotation> <xs:documentation/> </xs:annotation> <xs:choice> <xs:element name="ssi" type="xs:unsignedLong"/> <xs:element name="tsi" type="ct:typeTSI"/> </xs:choice> </xs:complexType> </pre>

Complex Type ct:typeTSI


Namespace	DR-GW-Interface/CommonTypes
Annotations	Basic type for TETRA subscriber identity containing Network code(MNC) and

	Country code(MCC).
Diagram	
Used by	Element ct:typeSubscriberAddress/ct:tsi
Model	ct:mnc , ct:mcc , ct:ssi
Children	ct:mcc, ct:mnc, ct:ssi
Source	<pre> <xs:complexType name="typeTsi"> <xs:annotation> <xs:documentation>Basic type for TETRA subscriber identity containing Network code(MNC) and Country code(MCC).</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="mnc" type="xs:unsignedShort"/> <xs:element name="mcc" type="xs:unsignedShort"/> <xs:element name="ssi" type="xs:unsignedLong"/> </xs:sequence> </xs:complexType> </pre>

Complex Type ct:typeExternal


Namespace	DR-GW-Interface/CommonTypes
Annotations	External number consisting of Gateway number + DialString
Diagram	
Used by	Element ct:typeAddress/ct:external
Model	ct:gatewayNumber , ct:number
Children	ct:gatewayNumber, ct:number
Source	<pre> <xs:complexType name="typeExternal"> <xs:annotation> <xs:documentation>External number consisting of Gateway number + DialString</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="gatewayNumber" type="xs:unsignedLong"/> <xs:element name="number" type="ct:typeDialString"/> </xs:sequence> </xs:complexType> </pre>

Complex Type ct:typeRequest

Namespace	DR-GW-Interface/CommonTypes
Diagram	
Model	ct:requestId
Children	ct:requestId
Source	<pre> <xs:complexType name="typeRequest"> <xs:sequence> <xs:element name="requestId" type="xs:unsignedLong"/> </xs:sequence> </xs:complexType> </pre>


Complex Type ct:typeEmpty

Namespace	DR-GW-Interface/CommonTypes
-----------	-----------------------------


Annotations	Explicit type specification for elements that shall be empty.
Diagram	
Source	<pre><xs:complexType name="typeEmpty"> <xs:annotation> <xs:documentation>Explicit type specification for elements that shall be empty.</ </xs:annotation> </xs:complexType></pre>

Simple Type(s)

Simple Type ct : typeResponseCode

Namespace	DR-GW-Interface/CommonTypes												
Diagram													
Type	restriction of xs:normalizedString												
Facets	<table border="1"> <tr><td>enumeration</td><td>success</td></tr> <tr><td>enumeration</td><td>final_response_pending</td></tr> <tr><td>enumeration</td><td>error</td></tr> <tr><td>enumeration</td><td>not_authorized_error</td></tr> <tr><td>enumeration</td><td>temporary_failure</td></tr> <tr><td>enumeration</td><td>subscription_failed</td></tr> </table>	enumeration	success	enumeration	final_response_pending	enumeration	error	enumeration	not_authorized_error	enumeration	temporary_failure	enumeration	subscription_failed
enumeration	success												
enumeration	final_response_pending												
enumeration	error												
enumeration	not_authorized_error												
enumeration	temporary_failure												
enumeration	subscription_failed												
Used by	Element ct:typeResult/ct:responseCode												
Source	<pre><xs:simpleType name="typeResponseCode"> <xs:restriction base="xs:normalizedString"> <xs:enumeration value="success"/> <xs:enumeration value="final_response_pending"/> <xs:enumeration value="error"/> <xs:enumeration value="not_authorized_error"/> <xs:enumeration value="temporary_failure"/> <xs:enumeration value="subscription_failed"/> </xs:restriction> </xs:simpleType></pre>												

Simple Type ct : typeSourceSystem

Namespace	DR-GW-Interface/CommonTypes								
Diagram									
Type	restriction of xs:normalizedString								
Facets	<table border="1"> <tr><td>enumeration</td><td>DR - GW</td></tr> <tr><td>enumeration</td><td>TCS - API</td></tr> <tr><td>enumeration</td><td>TETRA</td></tr> <tr><td>enumeration</td><td>TACTILON - API</td></tr> </table>	enumeration	DR - GW	enumeration	TCS - API	enumeration	TETRA	enumeration	TACTILON - API
enumeration	DR - GW								
enumeration	TCS - API								
enumeration	TETRA								
enumeration	TACTILON - API								
Used by	Element ct:typeResult/ct:sourceSystem								
Source	<pre><xs:simpleType name="typeSourceSystem"> <xs:restriction base="xs:normalizedString"> <xs:enumeration value="DR-GW"/> </xs:restriction> </xs:simpleType></pre>								

```
<xs:enumeration value="TCS-API"/>
<xs:enumeration value="TETRA"/>
<xs:enumeration value="TACTILON-API"/>
</xs:restriction>
</xs:simpleType>
```

Simple Type ct:typeDialString

Namespace	DR-GW-Interface/CommonTypes
Annotations	Allowed characters are digits 0 - 9, *, #, A, B, C and D. Maximum length is 24 characters.
Diagram	
Type	restriction of xs:normalizedString
Facets	maxLength 24
Used by	Elements ct:typeAddress/ct:msisdn, ct:typeExternal/ct:number
Source	<pre><xs:simpleType name="typeDialString"> <xs:annotation> <xs:documentation>Allowed characters are digits 0 - 9, *, #, A, B, C and D. Maximum length is 24 characters.</xs:documentation> </xs:annotation> <xs:restriction base="xs:normalizedString"> <xs:maxLength value="24"/> </xs:restriction> </xs:simpleType></pre>

Simple Type ct:typeOPTA

Namespace	DR-GW-Interface/CommonTypes
Annotations	OPTA string. Maximum length is 24 characters.
Diagram	
Type	restriction of xs:normalizedString
Facets	maxLength 24
Used by	Element ct:typeAddress/ct:opta
Source	<pre><xs:simpleType name="typeOPTA"> <xs:annotation> <xs:documentation>OPTA string. Maximum length is 24 characters.</xs:documentation> </xs:annotation> <xs:restriction base="xs:normalizedString"> <xs:maxLength value="24"/> </xs:restriction> </xs:simpleType></pre>

Simple Type ct:typeAddressingStyle

Namespace	DR-GW-Interface/CommonTypes
Annotations	Describes the IP addressing style. Unicast or multicast.
Diagram	
Type	restriction of xs:normalizedString

Facets	enumeration ucast
	enumeration mcast
Source	<pre> <xs:simpleType name="typeAddressingStyle"> <xs:annotation> <xs:documentation>Describes the IP addressing style. Unicast or multicast.</xs:documentation> </xs:annotation> <xs:restriction base="xs:normalizedString"> <xs:enumeration value="ucast"/> <xs:enumeration value="mcast"/> </xs:restriction> </xs:simpleType> </pre>