# *1. Description*

1.1. Project

Project Name	HFT-Core-Module_TrueSTUDIO
Board Name	HFT-Core-Module_TrueSTUDIO
Generated with:	STM32CubeMX 4.25.0
Date	05/07/2018

1.2. MCU

MCU Series	STM32L4
MCU Line	STM32L4x6
MCU name	STM32L496ZGTxP
MCU Package	LQFP144
MCU Pin number	144

2. Pinout Configuration

3. Pins Configuration

Pin Number LQFP144	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
1	PE2 *	I/O	GPIO_Input	
2	PE3	I/O	SAI1_SD_B	
3	PE4 *	I/O	GPIO_Input	
4	PE5 *	I/O	GPIO_Input	
6	VBAT	Power		
7	PC13	I/O	SYS_WKUP2	
8	PC14-OSC32_IN (PC14)	I/O	RCC_OSC32_IN	
9	PC15-OSC32_OUT (PC15)	I/O	RCC_OSC32_OUT	
10	PF0	I/O	I2C2_SDA	
11	PF1	I/O	I2C2_SCL	
12	PF2 *	I/O	GPIO_Input	
13	PF3	I/O	ADC3_IN6	
16	VSS	Power		
17	VDD	Power		
18	PF6	I/O	TIM5_CH1	
19	PF7	I/O	TIM5_CH2	
20	PF8	I/O	TIM5_CH3	
21	PF9	I/O	TIM5_CH4	
22	PF10 *	I/O	EVENTOUT	
23	PH0-OSC_IN (PH0)	I/O	RCC_OSC_IN	
25	NRST	Reset		
26	PC0 *	I/O	GPIO_Output	
27	PC1 *	I/O	GPIO_Output	
28	PC2 *	I/O	GPIO_Output	
29	PC3 *	I/O	GPIO_Output	
30	VSSA	Power		
31	VREF-	Power		
32	VREF+	MonoIO	VREFBUF_OUT	
33	VDDA	Power		
34	PA0	I/O	USART2_CTS	
36	PA2	I/O	USART2_TX	
38	VSS	Power		
39	VDD	Power		
42	PA6	I/O	USART3_CTS	
43	PA7	I/O	TIM3_CH2	LED_G (TIM3_CH2)
44	PC4	I/O	USART3_TX	

Pin Number LQFP144	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
45	PC5	I/O	USART3_RX	
46	PB0	I/O	TIM3_CH3	LED_B (TIM3_CH3)
47	PB1	I/O	USART3_RTS	
49	PF11	I/O	ADC1_EXTI11	
50	PF12 *	I/O	GPIO_Output	
51	VSS	Power		
52	VDD	Power		
53	PF13 *	I/O	GPIO_Input	
54	PF14	I/O	I2C4_SCL	
55	PF15	I/O	ADC1_EXTI15	
56	PG0 *	I/O	GPIO_Input	
57	PG1 *	I/O	GPIO_Input	
58	PE7 *	I/O	GPIO_Input	
59	PE8	I/O	SAI1_SCK_B	
60	PE9	I/O	SAI1_FS_B	
61	VSS	Power		
62	VDD	Power		
63	PE10	I/O	SAI1_MCLK_B	
64	PE11 *	I/O	GPIO_Output	
65	PE12 *	I/O	GPIO_Output	
66	PE13	I/O	SPI1_SCK	
67	PE14	I/O	SPI1_MISO	
68	PE15	I/O	SPI1_MOSI	
69	PB10 *	I/O	GPIO_Input	
70	VDD12	Power		
71	VSS	Power		
72	VDD	Power		
73	PB12 *	I/O	GPIO_Input	
74	PB13	I/O	SAI2_SCK_A	
75	PB14 *	I/O	GPIO_Input	
78	PD9 *	I/O	GPIO_Input	
79	PD10 *	I/O	GPIO_Input	
80	PD11	I/O	SAI2_SD_A	
81	PD12	I/O	SAI2_FS_A	
82	PD13	I/O	I2C4_SDA	
83	VSS	Power		
84	VDD	Power		
85	PD14 *	I/O	GPIO_Input	
86	PD15 *	I/O	GPIO_Input	

Pin Number LQFP144	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
89	PG4 *	I/O	EVENTOUT	
92	PG7	I/O	I2C3_SCL	
93	PG8	I/O	I2C3_SDA	
94	VSS	Power		
95	VDDIO2	Power		
96	PC6	I/O	TIM3_CH1	LED_R (TIM3_CH1)
98	PC8 *	I/O	GPIO_Input	
99	PC9 *	I/O	GPIO_Output	
100	PA8	I/O	RCC_MCO	
101	PA9	I/O	USB_OTG_FS_VBUS	
103	PA11	I/O	USB_OTG_FS_DM	
104	PA12	I/O	USB_OTG_FS_DP	
105	PA13 (JTMS/SWDIO)	I/O	SYS_JTMS-SWDIO	
106	VDDUSB	Power		
107	VSS	Power		
108	VDD	Power		
109	PA14 (JTCK/SWCLK)	I/O	SYS_JTCK-SWCLK	
111	PC10	I/O	SPI3_SCK	
112	PC11	I/O	SPI3_MISO	
113	PC12	I/O	SPI3_MOSI	
114	PD0 *	I/O	GPIO_Input	
115	PD1 *	I/O	GPIO_Input	
116	PD2 *	I/O	GPIO_Input	
117	PD3 *	I/O	GPIO_Output	
118	PD4	I/O	USART2_RTS	
119	PD5 *	I/O	GPIO_Output	
120	VSS	Power		
121	VDD	Power		
122	PD6	I/O	USART2_RX	
123	PD7 *	I/O	GPIO_Input	
124	PG9	I/O	USART1_TX	
125	PG10	I/O	USART1_RX	
126	PG11	I/O	USART1_CTS	
127	PG12	I/O	USART1_RTS	
128	PG13	I/O	I2C1_SDA	
129	PG14	I/O	I2C1_SCL	
130	VSS	Power		
131	VDDIO2	Power		
132	PB3 (JTDO/TRACESWO) *	I/O	GPIO_Input	

Pin Number LQFP144	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
134	PB5 *	I/O	GPIO_Input	
135	PB6 *	I/O	GPIO_Input	
136	PB7 *	I/O	GPIO_Input	
138	PB8	I/O	TIM16_CH1	
140	PE0 *	I/O	EVENTOUT	
141	PE1	I/O	TIM17_CH1	
142	VDD12	Power		
143	VSS	Power		
144	VDD	Power		

 * The pin is affected with an I/O function

4. Clock Tree Configuration

5. IPs and Middleware Configuration

5.1. ADC1

mode: Temperature Sensor Channel

mode: Vbat Channel

mode: Vrefint Channel

Conversion Trigger: Regular and Injected Conversion Trigger

5.1.1. Parameter Settings:

ADCs_Common_Settings:

Mode	Independent mode

ADC_Settings:

Clock Prescaler	Asynchronous clock mode divided by 1
Resolution	ADC 12-bit resolution
Data Alignment	Right alignment
Scan Conversion Mode	Disabled
Continuous Conversion Mode	Disabled
Discontinuous Conversion Mode	Disabled
DMA Continuous Requests	Disabled
End Of Conversion Selection	End of single conversion
Overrun behaviour	Overrun data preserved
Low Power Auto Wait	Disabled

ADC_Regular_ConversionMode:

Enable Regular Conversions	Enable
Enable Regular Oversampling	Disable
Number Of Conversion	1
External Trigger Conversion Source	EXTI Line11
External Trigger Conversion Edge	Trigger detection on the rising edge
Rank	1
Channel	Channel Temperature Sensor
Sampling Time	2.5 Cycles
Offset Number	No offset

ADC_Injected_ConversionMode:

Enable Injected Conversions	Disable

Analog Watchdog 1:

Enable Analog WatchDog1 Mode	false

Analog Watchdog 2:

Enable Analog WatchDog2 Mode	false
Analog Watchdog 3:	
Enable Analog WatchDog3 Mode	false

5.2. ADC3

IN6: IN6 Single-ended

5.2.1. Parameter Settings:

ADC_Settings:

Clock Prescaler	Asynchronous clock mode divided by 1
Resolution	ADC 12-bit resolution
Data Alignment	Right alignment
Scan Conversion Mode	Disabled
Continuous Conversion Mode	Disabled
Discontinuous Conversion Mode	Disabled
DMA Continuous Requests	Disabled
End Of Conversion Selection	End of single conversion
Overrun behaviour	Overrun data preserved
Low Power Auto Wait	Disabled

ADC_Regular_ConversionMode:

Enable Regular Conversions	Enable
Enable Regular Oversampling	Disable
Number Of Conversion	1
External Trigger Conversion Source	Regular Conversion launched by software
External Trigger Conversion Edge	None
Rank	1
Channel	Channel 6
Sampling Time	2.5 Cycles
Offset Number	No offset

ADC_Injected_ConversionMode:

Enable Injected Conversions	Disable
Analog Watchdog 1:	
Enable Analog WatchDog1 Mode	false
Analog Watchdog 2:	
Enable Analog WatchDog2 Mode	false
Analog Watchdog 3:	
Enable Analog WatchDog3 Mode	false

5.3. CRC

mode: Activated

5.3.1. Parameter Settings:

Basic Parameters:

Default Polynomial State	Enable
Default Init Value State	Enable

Advanced Parameters:

Input Data Inversion Mode	None
Output Data Inversion Mode	Disable
Input Data Format	Bytes

5.4. DFSDM1

mode: Parallel input
mode: Parallel input

5.4.1. Filter 0:

regular channel selection:

regular channel selection	**Channel 0 ***
Continuous Mode	Continuous Mode
Trigger to start regular conversion	Software trigger
Fast Mode	Disable
Dma Mode	Disable

injected channel selection:

Channel0 as injected channel	Disable
Channel1 as injected channel	Disable
Channel2 as injected channel	Disable
Channel3 as injected channel	Disable
Channel4 as injected channel	Disable
Channel5 as injected channel	Disable
Channel6 as injected channel	Disable
Channel7 as injected channel	Disable

Filter parameters:

Sinc Order	FastSinc filter type
Fosr	1
Iosr	1

5.4.2. Filter 1:

regular channel selection:

regular channel selection	**Channel 1 ***
Continuous Mode	Continuous Mode
Trigger to start regular conversion	Software trigger
Fast Mode	Disable
Dma Mode	Disable

injected channel selection:

Channel0 as injected channel	Disable
Channel1 as injected channel	Disable
Channel2 as injected channel	Disable
Channel3 as injected channel	Disable
Channel4 as injected channel	Disable
Channel5 as injected channel	Disable
Channel6 as injected channel	Disable
Channel7 as injected channel	Disable

Filter parameters:

Sinc Order	FastSinc filter type
Fosr	1
Iosr	1

5.4.3. Filter 2:

regular channel selection:

regular channel selection	- None -

injected channel selection:

Channel0 as injected channel	Disable
Channel1 as injected channel	Disable
Channel2 as injected channel	Disable
Channel3 as injected channel	Disable
Channel4 as injected channel	Disable
Channel5 as injected channel	Disable
Channel6 as injected channel	Disable
Channel7 as injected channel	Disable

5.4.4. Filter 3:

regular channel selection:

regular channel selection	- None -

injected channel selection:

Channel0 as injected channel	Disable
Channel1 as injected channel	Disable
Channel2 as injected channel	Disable
Channel3 as injected channel	Disable
Channel4 as injected channel	Disable
Channel5 as injected channel	Disable
Channel6 as injected channel	Disable
Channel7 as injected channel	Disable

5.4.5. Channel 0:

Channel 0 Parallel input selection:

Multiplexer_Internal_CH0	Data are taken from internal register

Channel 0 parameters:

Data Packing	Standard data packing mode
Right Bit Shift	**0x00 ***

5.4.6. Channel 1:

Channel 1 Parallel input selection:

Multiplexer_Internal_CH1	Data are taken from internal register

Channel 1 parameters:

Data Packing	Standard data packing mode
Right Bit Shift	**0x00 ***

5.5. DMA2D

mode: Activated

5.5.1. Parameter Settings:

Basic Parameters:

Transfer Mode	Memory to Memory
Color Mode	ARGB8888
Output Offset	0

Foreground layer Configuration:

DMA2D Input Color Mode	ARGB8888
DMA2D ALPHA MODE	No modification of the alpha channel value
Input Alpha	0
Input Offset	0
DMA2D ALPHA Inversion	Regular Alpha
DMA2D Red and Blue swap	Regular mode (RGB or ARGB)

5.6. I2C1

I2C: I2C

5.6.1. Parameter Settings:

Timing configuration:

I2C Speed Mode	**Fast Mode ***
I2C Speed Frequency (KHz)	400
Rise Time (ns)	0
Fall Time (ns)	0
Coefficient of Digital Filter	0
Analog Filter	Enabled
Timing	**0x0010061A ***

Slave Features:

Clock No Stretch Mode	Disabled
General Call Address Detection	Disabled
Primary Address Length selection	7-bit
Dual Address Acknowledged	Disabled
Primary slave address	0

5.7. I2C2

I2C: I2C

5.7.1. Parameter Settings:

Timing configuration:

I2C Speed Mode	**Fast Mode** *
I2C Speed Frequency (KHz)	400
Rise Time (ns)	0
Fall Time (ns)	0
Coefficient of Digital Filter	0
Analog Filter	Enabled
Timing	**0x0010061A** *

Slave Features:

Clock No Stretch Mode	Disabled
General Call Address Detection	Disabled
Primary Address Length selection	7-bit
Dual Address Acknowledged	Disabled
Primary slave address	0

5.8. I2C3

I2C: I2C

5.8.1. Parameter Settings:

Timing configuration:

I2C Speed Mode	**Fast Mode** *
I2C Speed Frequency (KHz)	400
Rise Time (ns)	0
Fall Time (ns)	0
Coefficient of Digital Filter	0
Analog Filter	Enabled
Timing	**0x0010061A** *

Slave Features:

Clock No Stretch Mode	Disabled
General Call Address Detection	Disabled
Primary Address Length selection	7-bit
Dual Address Acknowledged	Disabled
Primary slave address	0

5.9. I2C4

I2C: I2C

5.9.1. Parameter Settings:

Timing configuration:

I2C Speed Mode	**Fast Mode ***
I2C Speed Frequency (KHz)	400
Rise Time (ns)	0
Fall Time (ns)	0
Coefficient of Digital Filter	0
Analog Filter	Enabled
Timing	**0x0010061A ***

Slave Features:

Clock No Stretch Mode	Disabled
General Call Address Detection	Disabled
Primary Address Length selection	7-bit
Dual Address Acknowledged	Disabled
Primary slave address	0

5.10. RCC

High Speed Clock (HSE): BYPASS Clock Source
Low Speed Clock (LSE) : Crystal/Ceramic Resonator
mode: Master Clock Output
CRS SYNC: CRS SYNC Source USB

5.10.1. Parameter Settings:

System Parameters:

VDD voltage (V)	3.3
Instruction Cache	Enabled
Prefetch Buffer	**Enabled ***
Data Cache	Enabled
Flash Latency(WS)	4 WS (5 CPU cycle)

RCC Parameters:

HSI Calibration Value	64
MSI Calibration Value	0
MSI Auto Calibration	Disabled
HSE Startup Timout Value (ms)	100

LSE Startup Timout Value (ms)	5000
LSE Drive Capability	LSE oscillator low drive capability

Power Parameters:

Power Regulator Voltage Scale	Power Regulator Voltage Scale 1

CRS Parameters:

CRS Synchro Divider	1
CRS Synchro Polarity	Active on rising edge
CRS Synchro Reload Value Type	Automatic
CRS Synchro frequency (Hz)	1000
Error limit Value	34
HSI48 Calibration Value	32

5.11. RNG
mode: Activated

5.12. RTC
mode: Activate Clock Source
mode: Activate Calendar
Alarm A: Internal Alarm A
Alarm B: Internal Alarm B
WakeUp: Internal WakeUp

5.12.1. Parameter Settings:

General:

Hour Format	Hourformat 24
Asynchronous Predivider value	127
Synchronous Predivider value	255

Calendar Time:

Data Format	**Binary data format ***
Hours	0
Minutes	0
Seconds	0
Day Light Saving: value of hour adjustment	Daylightsaving None
Store Operation	Storeoperation Reset

Calendar Date:

Week Day	Monday
Month	January

Date	1
Year	**18 ***

Alarm A:

Hours	0
Minutes	0
Seconds	0
Sub Seconds	0
Alarm Mask Date Week day	**Enable ***
Alarm Mask Hours	**Enable ***
Alarm Mask Minutes	**Enable ***
Alarm Mask Seconds	**Enable ***
Alarm Sub Second Mask	All Alarm SS fields are masked.
Alarm Date Week Day Sel	Date
Alarm Date	1

Alarm B:

Hours	0
Minutes	0
Seconds	0
Sub Seconds	0
Alarm Mask Date Week day	Disable
Alarm Mask Hours	Disable
Alarm Mask Minutes	Disable
Alarm Mask Seconds	Disable
Alarm Sub Second Mask	All Alarm SS fields are masked.
Alarm Date Week Day Sel	Date
Alarm Date	1

Wake UP:

Wake Up Clock	RTCCLK / 16
Wake Up Counter	0

5.13. SAI1

Mode: Master with Master Clock Out
mode: I2S/PCM Protocol

5.13.1. Parameter Settings:

SAI B:

Basic Parameters

Audio Mode	Master Transmit
Output Mode	Stereo
Companding Mode	No companding mode
SAI SD Line Output Mode	Driven
Protocol Parameters	
Protocol	I2S Standard
Data Size	16 Bits
Number of Slots (only Even Values)	2
Clock Parameters	
Master Clock Divider	Enabled
Audio Frequency	192 KHz
Real Audio Frequency	0
Error between Selected	0
Advanced Parameters	
Fifo Threshold	Empty
Output Drive	Disabled
Synchronization External	Disabled

5.14. SAI2

Mode: Asynchronous Slave
mode: I2S/PCM Protocol

5.14.1. Parameter Settings:

SAI A:

Basic Parameters	
Audio Mode	Slave Receive
Output Mode	Stereo
Companding Mode	No companding mode
SAI SD Line Output Mode	Driven
Protocol Parameters	
Protocol	I2S Standard
Data Size	16 Bits
Number of Slots (only Even Values)	2
Clock Parameters	
Advanced Parameters	
Fifo Threshold	Empty
Output Drive	Disabled
Synchronization External	Disabled

5.15. SPI1

Mode: Full-Duplex Master

5.15.1. Parameter Settings:

Basic Parameters:

Frame Format	Motorola
Data Size	**8 Bits ***
First Bit	MSB First

Clock Parameters:

Prescaler (for Baud Rate)	**4 ***
Baud Rate	**20.0 MBits/s ***
Clock Polarity (CPOL)	Low
Clock Phase (CPHA)	1 Edge

Advanced Parameters:

CRC Calculation	Disabled
NSSP Mode	Enabled
NSS Signal Type	Software

5.16. SPI3

Mode: Full-Duplex Master

5.16.1. Parameter Settings:

Basic Parameters:

Frame Format	Motorola
Data Size	**8 Bits ***
First Bit	MSB First

Clock Parameters:

Prescaler (for Baud Rate)	**4 ***
Baud Rate	**20.0 MBits/s ***
Clock Polarity (CPOL)	Low
Clock Phase (CPHA)	1 Edge

Advanced Parameters:

CRC Calculation	Disabled
NSSP Mode	Enabled
NSS Signal Type	Software

5.17. SYS

Debug: Serial Wire
mode: System Wake-Up 2
Power Voltage Detector In: Power Voltage Detector In (Internal analog voltage)
VREFBUF Mode: Internal voltage reference
Timebase Source: TIM2

5.17.1. Parameter Settings:

Programmable_Voltage_Detector_Settings:

PVD detection Level	PWR PVD LEVEL 0 (2.0 V)
PWR PVD Mode	basic mode is used

Voltage_Reference_Buffer_Settings:

Trimming Mode	Factory Trimming
Internal Voltage reference scale	SCALE 0: around 2.048 V

5.18. TIM1

Clock Source   : Internal Clock

5.18.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value)	0
Counter Mode	Up
Counter Period (AutoReload Register - 16 bits value)	0
Internal Clock Division (CKD)	No Division
Repetition Counter (RCR - 8 bits value)	0
auto-reload preload	Disable

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit)	Disable (Trigger input effect not delayed)
Trigger Event Selection TRGO	Reset (UG bit from TIMx_EGR)
Trigger Event Selection TRGO2	Reset (UG bit from TIMx_EGR)

5.19. TIM3

Clock Source   : Internal Clock
Channel1: PWM Generation CH1
Channel2: PWM Generation CH2
Channel3: PWM Generation CH3

5.19.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value)	0
Counter Mode	Up
Counter Period (AutoReload Register - 16 bits value)	0
Internal Clock Division (CKD)	No Division
auto-reload preload	**Enable ***

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit)	Disable (Trigger input effect not delayed)
Trigger Event Selection TRGO	Reset (UG bit from TIMx_EGR)

Clear Input:

Clear Input Source	Disable

PWM Generation Channel 1:

Mode	PWM mode 1
Pulse (16 bits value)	0
Fast Mode	Disable
CH Polarity	High

PWM Generation Channel 2:

Mode	PWM mode 1
Pulse (16 bits value)	0
Fast Mode	Disable
CH Polarity	High

PWM Generation Channel 3:

Mode	PWM mode 1
Pulse (16 bits value)	0
Fast Mode	Disable
CH Polarity	High

5.20. TIM5

Clock Source   : Internal Clock

Channel1: Input Capture direct mode

Channel2: Input Capture direct mode

Channel3: Input Capture direct mode

Channel4: Input Capture direct mode

5.20.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value)	0
Counter Mode	Up
Counter Period (AutoReload Register - 32 bits value)	0
Internal Clock Division (CKD)	No Division
auto-reload preload	**Enable ***

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit)	Disable (Trigger input effect not delayed)
Trigger Event Selection TRGO	Reset (UG bit from TIMx_EGR)

Input Capture Channel 1:

Polarity Selection	Rising Edge
IC Selection	Direct
Prescaler Division Ratio	No division
Input Filter (4 bits value)	0

Input Capture Channel 2:

Polarity Selection	Rising Edge
IC Selection	Direct
Prescaler Division Ratio	No division
Input Filter (4 bits value)	0

Input Capture Channel 3:

Polarity Selection	Rising Edge
IC Selection	Direct
Prescaler Division Ratio	No division
Input Filter (4 bits value)	0

Input Capture Channel 4:

Polarity Selection	Rising Edge
IC Selection	Direct
Prescaler Division Ratio	No division
Input Filter (4 bits value)	0

5.21. TIM16

mode: Activated

Channel1: Output Compare CH1

5.21.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value)	0
Counter Mode	Up
Counter Period (AutoReload Register - 16 bits value)	0
Internal Clock Division (CKD)	No Division
Repetition Counter (RCR - 8 bits value)	0
auto-reload preload	Disable

Break And Dead Time management - BRK Configuration:

BRK State	Disable
BRK Polarity	High
BRK Filter (4 bits value)	0
BRK Sources Configuration	
- Digital Input	Disable
- COMP1	Disable
- COMP2	Disable
- DFSDM	Disable

Break And Dead Time management - Output Configuration:

Automatic Output State	Disable
Off State Selection for Run Mode (OSSR)	Disable
Off State Selection for Idle Mode (OSSI)	Disable
Lock Configuration	Off

Output Compare Channel 1:

Mode	Frozen (used for Timing base)
Pulse (16 bits value)	0
CH Polarity	High
CH Idle State	Reset

5.22. TIM17

mode: Activated

Channel1: Output Compare CH1

5.22.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value)	0
Counter Mode	Up
Counter Period (AutoReload Register - 16 bits value)	0
Internal Clock Division (CKD)	No Division
Repetition Counter (RCR - 8 bits value)	0
auto-reload preload	Disable

Break And Dead Time management - BRK Configuration:

BRK State	Disable
BRK Polarity	High
BRK Filter (4 bits value)	0
BRK Sources Configuration	
- Digital Input	Disable
- COMP1	Disable
- COMP2	Disable
- DFSDM	Disable

Break And Dead Time management - Output Configuration:

Automatic Output State	Disable
Off State Selection for Run Mode (OSSR)	Disable
Off State Selection for Idle Mode (OSSI)	Disable
Lock Configuration	Off

Output Compare Channel 1:

Mode	Frozen (used for Timing base)
Pulse (16 bits value)	0
CH Polarity	High
CH Idle State	Reset

5.23. USART1

Mode: Asynchronous

Hardware Flow Control (RS232): CTS/RTS

5.23.1. Parameter Settings:

Basic Parameters:

Baud Rate	**38400 ***
Word Length	**8 Bits (including Parity) ***
Parity	None
Stop Bits	1

Advanced Parameters:

Data Direction	Receive and Transmit
Over Sampling	16 Samples
Single Sample	Disable

Advanced Features:

Auto Baudrate	Disable
TX Pin Active Level Inversion	Disable
RX Pin Active Level Inversion	Disable
Data Inversion	Disable
TX and RX Pins Swapping	Disable
Overrun	Enable
DMA on RX Error	Enable
MSB First	Disable

5.24. USART2

Mode: Asynchronous
Hardware Flow Control (RS232): CTS/RTS

5.24.1. Parameter Settings:

Basic Parameters:

Baud Rate	**38400 ***
Word Length	**8 Bits (including Parity) ***
Parity	None
Stop Bits	1

Advanced Parameters:

Data Direction	Receive and Transmit
Over Sampling	16 Samples
Single Sample	Disable

Advanced Features:

Auto Baudrate	Disable
TX Pin Active Level Inversion	Disable
RX Pin Active Level Inversion	Disable
Data Inversion	Disable

TX and RX Pins Swapping	Disable
Overrun	Enable
DMA on RX Error	Enable
MSB First	Disable

5.25. USART3

Mode: Asynchronous

Hardware Flow Control (RS232): CTS/RTS

5.25.1. Parameter Settings:

Basic Parameters:

Baud Rate	**38400 ***
Word Length	**8 Bits (including Parity) ***
Parity	None
Stop Bits	1

Advanced Parameters:

Data Direction	Receive and Transmit
Over Sampling	16 Samples
Single Sample	Disable

Advanced Features:

Auto Baudrate	Disable
TX Pin Active Level Inversion	Disable
RX Pin Active Level Inversion	Disable
Data Inversion	Disable
TX and RX Pins Swapping	Disable
Overrun	Enable
DMA on RX Error	Enable
MSB First	Disable

5.26. USB_OTG_FS

Mode: Device_Only

Activate_VBUS: VBUS sensing

5.26.1. Parameter Settings:

Speed	Full Speed 12MBit/s
Endpoint 0 Max Packet size	64 Bytes
Enable internal IP DMA	Disabled
Low power	Disabled
Battery charging	**Disabled ***
Link Power Management	**Enabled ***
Use dedicated end point 1 interrupt	Disabled
VBUS sensing	Enabled
Signal start of frame	**Enabled ***

5.27. FREERTOS

mode: Enabled

5.27.1. Config parameters:

Versions:

FreeRTOS version	9.0.0
CMSIS-RTOS version	1.02

Kernel settings:

USE_PREEMPTION	Enabled
CPU_CLOCK_HZ	SystemCoreClock
TICK_RATE_HZ	1000
MAX_PRIORITIES	7
MINIMAL_STACK_SIZE	128
MAX_TASK_NAME_LEN	16
USE_16_BIT_TICKS	Disabled
IDLE_SHOULD_YIELD	Enabled
USE_MUTEXES	Enabled
USE_RECURSIVE_MUTEXES	Disabled
USE_COUNTING_SEMAPHORES	**Enabled ***
QUEUE_REGISTRY_SIZE	8
USE_APPLICATION_TASK_TAG	**Enabled ***
ENABLE_BACKWARD_COMPATIBILITY	**Disabled ***
USE_PORT_OPTIMISED_TASK_SELECTION	Enabled
USE_TICKLESS_IDLE	Disabled
USE_TASK_NOTIFICATIONS	Enabled

Memory management settings:

Memory Allocation	Dynamic
TOTAL_HEAP_SIZE	**8192 ***
Memory Management scheme	heap_4

Hook function related definitions:

USE_IDLE_HOOK	Disabled
USE_TICK_HOOK	Disabled
USE_MALLOC_FAILED_HOOK	**Enabled ***
USE_DAEMON_TASK_STARTUP_HOOK	Disabled
CHECK_FOR_STACK_OVERFLOW	**Option2 ***

Run time and task stats gathering related definitions:

GENERATE_RUN_TIME_STATS	**Enabled ***
USE_TRACE_FACILITY	**Enabled ***
USE_STATS_FORMATTING_FUNCTIONS	**Enabled ***

Co-routine related definitions:

USE_CO_ROUTINES	Disabled
MAX_CO_ROUTINE_PRIORITIES	2

Software timer definitions:

USE_TIMERS	Enabled
TIMER_TASK_PRIORITY	2
TIMER_QUEUE_LENGTH	10
TIMER_TASK_STACK_DEPTH	256

Interrupt nesting behaviour configuration:

LIBRARY_LOWEST_INTERRUPT_PRIORITY	15
LIBRARY_MAX_SYSCALL_INTERRUPT_PRIORITY	5

5.27.2. Include parameters:

Include definitions:

vTaskPrioritySet	Enabled
uxTaskPriorityGet	Enabled
vTaskDelete	Enabled
vTaskCleanUpResources	**Enabled ***
vTaskSuspend	Enabled
vTaskDelayUntil	**Enabled ***
vTaskDelay	Enabled
xTaskGetSchedulerState	Enabled
xTaskResumeFromISR	Enabled
xQueueGetMutexHolder	**Enabled ***
xSemaphoreGetMutexHolder	**Enabled ***

pcTaskGetTaskName	**Enabled ***
uxTaskGetStackHighWaterMark	**Enabled ***
xTaskGetCurrentTaskHandle	**Enabled ***
eTaskGetState	**Enabled ***
xEventGroupSetBitFromISR	**Enabled ***
xTimerPendFunctionCall	**Enabled ***
xTaskAbortDelay	**Enabled ***
xTaskGetHandle	**Enabled ***

5.28. USB_DEVICE

Class For FS IP: Communication Device Class (Virtual Port Com)

5.28.1. Parameter Settings:

Basic Parameters:

USBD_MAX_NUM_INTERFACES (Maximum number of supported interfaces)	1
USBD_MAX_NUM_CONFIGURATION (Maximum number of supported configuration)	1
USBD_MAX_STR_DESC_SIZ (Maximum size for the string descriptors)	512
USBD_SUPPORT_USER_STRING (Enable user string descriptor)	Disabled
USBD_SELF_POWERED (Enabled self power)	**Disabled ***
USBD_DEBUG_LEVEL (USBD Debug Level)	0: No debug message
USBD_LPM_ENABLED (Link Power Management)	1: Link Power Management supported

Class Parameters:

USB CDC Rx Buffer Size	2048
USB CDC Tx Buffer Size	2048

5.28.2. Device Descriptor:

Device Descriptor:

VID (Vendor IDentifier)	1155
LANGID_STRING (Language Identifier)	English(United States)
MANUFACTURER_STRING (Manufacturer Identifier)	**HSMA HFT Laborities ***

Device Descriptor FS:

PID (Product IDentifier)	22336
PRODUCT_STRING (Product Identifier)	**HFT-Core_Module ***
SERIALNUMBER_STRING (Serial number)	**000000000001 ***
CONFIGURATION_STRING (Configuration Identifier)	CDC Config

INTERFACE_STRING (Interface Identifier)   CDC Interface

* User modified value

6. System Configuration

6.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
ADC1	PF11	ADC1_EXTI11	External Interrupt Mode with Rising edge trigger detection	No pull-up and no pull-down	n/a	
	PF15	ADC1_EXTI15	External Interrupt Mode with Rising edge trigger detection	No pull-up and no pull-down	n/a	
ADC3	PF3	ADC3_IN6	Analog mode for ADC conversion	No pull-up and no pull-down	n/a	
I2C1	PG13	I2C1_SDA	Alternate Function Open Drain	Pull-up	**Very High** *	
	PG14	I2C1_SCL	Alternate Function Open Drain	Pull-up	**Very High** *	
I2C2	PF0	I2C2_SDA	Alternate Function Open Drain	Pull-up	**Very High** *	
	PF1	I2C2_SCL	Alternate Function Open Drain	Pull-up	**Very High** *	
I2C3	PG7	I2C3_SCL	Alternate Function Open Drain	Pull-up	**Very High** *	
	PG8	I2C3_SDA	Alternate Function Open Drain	Pull-up	**Very High** *	
I2C4	PF14	I2C4_SCL	Alternate Function Open Drain	Pull-up	**Very High** *	
	PD13	I2C4_SDA	Alternate Function Open Drain	Pull-up	**Very High** *	
RCC	PC14-OSC32_IN (PC14)	RCC_OSC32_IN	n/a	n/a	n/a	
	PC15-OSC32_OUT (PC15)	RCC_OSC32_OUT	n/a	n/a	n/a	
	PH0-OSC_IN (PH0)	RCC_OSC_IN	n/a	n/a	n/a	
	PA8	RCC_MCO	Alternate Function Push Pull	No pull-up and no pull-down	Low	
SAI1	PE3	SAI1_SD_B	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PE8	SAI1_SCK_B	Alternate Function Push Pull	No pull-up and no pull-down	Low	

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
	PE9	SAI1_FS_B	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PE10	SAI1_MCLK_B	Alternate Function Push Pull	No pull-up and no pull-down	Low	
SAI2	PB13	SAI2_SCK_A	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PD11	SAI2_SD_A	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PD12	SAI2_FS_A	Alternate Function Push Pull	No pull-up and no pull-down	Low	
SPI1	PE13	SPI1_SCK	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PE14	SPI1_MISO	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PE15	SPI1_MOSI	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
SPI3	PC10	SPI3_SCK	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PC11	SPI3_MISO	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PC12	SPI3_MOSI	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
SYS	PC13	SYS_WKUP2	n/a	n/a	n/a	
	VREF+	VREFBUF_OUT	n/a	n/a	n/a	
	PA13 (JTMS/SWDIO)	SYS_JTMS-SWDIO	n/a	n/a	n/a	
	PA14 (JTCK/SWCLK)	SYS_JTCK-SWCLK	n/a	n/a	n/a	
TIM3	PA7	TIM3_CH2	Alternate Function Push Pull	**Pull-down ***	Low	LED_G (TIM3_CH2)
	PB0	TIM3_CH3	Alternate Function Push Pull	**Pull-down ***	Low	LED_B (TIM3_CH3)
	PC6	TIM3_CH1	Alternate Function Push Pull	**Pull-down ***	Low	LED_R (TIM3_CH1)
TIM5	PF6	TIM5_CH1	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PF7	TIM5_CH2	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PF8	TIM5_CH3	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PF9	TIM5_CH4	Alternate Function Push Pull	No pull-up and no pull-down	Low	
TIM16	PB8	TIM16_CH1	Alternate Function Push Pull	No pull-up and no pull-down	Low	
TIM17	PE1	TIM17_CH1	Alternate Function Push Pull	No pull-up and no pull-down	Low	
USART1	PG9	USART1_TX	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PG10	USART1_RX	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PG11	USART1_CTS	Alternate Function Push Pull	No pull-up and no pull-down	**Very High**	

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
					*	
	PG12	USART1_RTS	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
USART2	PA0	USART2_CTS	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PA2	USART2_TX	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PD4	USART2_RTS	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PD6	USART2_RX	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
USART3	PA6	USART3_CTS	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PC4	USART3_TX	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PC5	USART3_RX	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PB1	USART3_RTS	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
USB_OTG_FS	PA9	USB_OTG_FS_VBUS	Input mode	No pull-up and no pull-down	n/a	
	PA11	USB_OTG_FS_DM	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
	PA12	USB_OTG_FS_DP	Alternate Function Push Pull	No pull-up and no pull-down	**Very High** *	
GPIO	PE2	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PE4	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PE5	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PF2	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PF10	EVENTOUT	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PC0	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PC1	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PC2	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PC3	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PF12	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PF13	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PG0	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PG1	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
	PE7	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PE11	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PE12	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PB10	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PB12	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PB14	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PD9	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PD10	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PD14	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PD15	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PG4	EVENTOUT	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PC8	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PC9	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PD0	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PD1	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PD2	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PD3	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PD5	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PD7	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PB3 (JTDO/TRACESWO)	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PB5	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PB6	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PB7	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	
	PE0	EVENTOUT	Alternate Function Push Pull	No pull-up and no pull-down	Low	

6.2. DMA configuration

nothing configured in DMA service

6.3. NVIC configuration

Interrupt Table	Enable	Preenmption Priority	SubPriority
Non maskable interrupt	true	0	0
Hard fault interrupt	true	0	0
Memory management fault	true	0	0
Prefetch fault, memory access fault	true	0	0
Undefined instruction or illegal state	true	0	0
System service call via SWI instruction	true	0	0
Debug monitor	true	0	0
Pendable request for system service	true	15	0
System tick timer	true	15	0
RTC wake-up interrupt through EXTI line 20	true	5	0
TIM2 global interrupt	true	0	0
RTC alarm interrupt through EXTI line 18	true	5	0
DFSDM1 filter0 global interrupt	true	0	0
DFSDM1 filter1 global interrupt	true	0	0
USB OTG FS global interrupt	true	5	0
PVD/PVM1/PVM2/PVM3/PVM4 interrupts through EXTI lines 16/35/36/37/38	unused		
Flash global interrupt	unused		
RCC global interrupt	unused		
ADC1 and ADC2 interrupts	unused		
TIM1 break interrupt and TIM15 global interrupt	unused		
TIM1 update interrupt and TIM16 global interrupt	unused		
TIM1 trigger and commutation interrupts and TIM17 global interrupt	unused		
TIM1 capture compare interrupt	unused		
TIM3 global interrupt	unused		
I2C1 event interrupt	unused		
I2C1 error interrupt	unused		
I2C2 event interrupt	unused		
I2C2 error interrupt	unused		
SPI1 global interrupt	unused		
USART1 global interrupt	unused		
USART2 global interrupt	unused		
USART3 global interrupt	unused		
EXTI line[15:10] interrupts	unused		
ADC3 global interrupt	unused		
TIM5 global interrupt	unused		
SPI3 global interrupt	unused		

HFT-Core-Module_TrueSTUDIO Project
Configuration Report

Interrupt Table	Enable	Preenmption Priority	SubPriority
I2C3 event interrupt		unused	
I2C3 error interrupt		unused	
SAI1 global interrupt		unused	
SAI2 global interrupt		unused	
HASH and RNG global interrupts		unused	
FPU global interrupt		unused	
CRS global interrupt		unused	
I2C4 event interrupt		unused	
I2C4 error interrupt		unused	
DMA2D global interrupt		unused	

* User modified value

7. Power Consumption Calculator report

7.1. Microcontroller Selection

Series	STM32L4
Line	STM32L4x6
MCU	STM32L496ZGTxP
Datasheet	029173_Rev2

7.2. Parameter Selection

Temperature	25
Vdd	3.6

7.3. SMPS Selection

SMPS	SMPS1_User
Vin	3.3 V
Vout	1.2 V
OffCurrent	250.0 nA
QCurrent	500.0 nA
Efficiency	85 %

7.4. Sequence

Step	Step1
Mode	RUN
SMPS	CONNECTED
Vdd	3.6
Voltage Source	Battery
Range	Range1-High
Fetch Type	FLASH
Clock Configuration	HSE BYP PLL Flash-ON
Clock Source Frequency	4 MHz
CPU Frequency	80 MHz
Peripherals	ADC1:fs_10_ksps ADC2:fs_10_ksps ADC3:fs_10_ksps AHB_APB1_Bridge AHB_APB2_Bridge CAN1 CAN2 CRC DAC1:OUT1+OUT2-Buffer_OFF-Middle_code DCMI DFSDM1 DMA1 DMA2 DMA2D FMC FW GPIOA GPIOB GPIOC GPIOD GPIOE GPIOF GPIOG GPIOH I2C1 I2C2 I2C3 I2C4 IWDG LCD:Buffer_OFF LPTIM1 LPTIM2 LPUART1 OPAMP1:Low_Power OPAMP2:Low_Power PVD/BOR PWR QUADSPI RNG RTC SAI1 SAI2 SDMMC1 SPI1 SPI2 SPI3 SWPMI1 SYS-VREFBUF/COMP1:COMP_High_Speed-Square_VREFBUF_OFF SYS-VREFBUF/COMP2:COMP_High_Speed-Square_VREFBUF_OFF TIM1 TIM2 TIM3 TIM4 TIM5 TIM6 TIM7 TIM8 TIM15 TIM16 TIM17 TS TSC UART4 UART5 USART1 USART2 USART3 USB_OTG_FS WWDG
Additional Cons.	0 mA
Average Current	25.41 mA
Duration	1 ms
DMIPS	0.0
Ta Max	102.07
Category	Measurements

7.5. RESULTS

Sequence Time	1 ms	Average Current	25.41 mA
Battery Life	0	Average DMIPS	100.0 DMIPS

7.6. Chart

8. Software Project

8.1. Project Settings

Name	Value
Project Name	HFT-Core-Module_TrueSTUDIO
Project Folder	C:\Users\habel\git\HFT-Core-Module__SW\SW\TrueSTUDIO
Toolchain / IDE	TrueSTUDIO
Firmware Package Name and Version	STM32Cube FW_L4 V1.11.0

8.2. Code Generation Settings

Name	Value
STM32Cube Firmware Library Package	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	No
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power consumption)	No

9. Software Pack Report