

## PyBoard and WiPy Editor: Small Python Text Editor

Looking for a code editor that would fit onto Pyboard (and now WiPy), I made my way through the Micropython forum and found **pfalkon**'s Python editor code, which I took and ported it to PyBoard. It's really impressive how few lines of code pfalkon needed to implement a reasonable amount of functionality. Since the code looked clean, and it seemed so easy to add features, I could not resist adding a little bit, using some ideas of **dhylands** for screen and keyboard handling, and yes, it got a little bit larger. The file size increased by a factor of 5 (only some of that caused by commenting), and the footprint in memory by a factor of 2 (now 14k), depending on what you keep. It still contains the code for the Linux/Darwin environment, so you can run it in Linux/Mac MicroPython (if you install the os module) or Python3. I sprayed C Preprocessor statements in it (arrgh!), so you can use cpp to remove the stuff which is not needed for PyBoard or WiPy. So, what did I change and add:

- Use USB\_VCP or UART for input and output on PyBoard, stdin/stdout on WiPy.
- Changed the read keyboard function to comply with slow char-by-char input on serial lines.
- Added support for TAB, BACKTAB, SAVE, FIND, REPLACE, GOTO Line, YANK (delete line into buffer), ZAP (insert buffer), REDRAW, UNDO, INDENT, UN-INDENT and GET (file).
- Join lines by Delete Char at the end or Backspace at the beginning, Autoindent for Enter.
- Moved main into a function with an option for Pipe'ing in on Linux & Python3
- Added a status line and single line prompts for Quit, Save, Find, Replace, Goto and Get file. The status line can be turned (almost) off for slow connections.
- Support of the basic mouse functions scrolling up/down and setting the cursor (\*).

The editor works in Insert mode. Cursor Keys, Home, End, PgUp and PgDn work as you would expect. Some functions are available with Ctrl-Keys. Keyboard Mapping:

Keys	Alternative	Function
Up		Move the <b>cursor up</b> one line.
Down		Move the <b>cursor down</b> one line.
Left		Move the <b>cursor left</b> by one char; skipping over to the previous line (*).
Right		Move the <b>cursor right</b> by one char; skipping over to the next line. (*)
PgUp		Move the <b>cursor up</b> by one screen height.
PgDn		Move the <b>cursor down</b> by one screen height.
Home		Toggle between the <b>start-of-line</b> and <b>start-of-text</b> .
End		Move to the <b>end-of-line</b> .
Mouse Button 1		Set the cursor. (*)
Mouse Scroll Wheel		Scroll Up/Down the screen content by 3 lines per tick. The cursor stays visible and will be moved in the content if required. (*)
Enter	\n	<b>Insert a line break</b> at the cursor position. Auto-indent is supported.
Backspace	Ctrl-H	<b>Delete the char left</b> hand to the cursor. If the mark is set, just delete the marked line range. At the beginning of the line Backspace joins the previous line. (*)
Del		<b>Delete char</b> under cursor. At the end of the line join the next line. If the mark is set, delete the marked line range. In line edit prompts, Del deletes the whole entry.
Tab	Ctrl-I	<b>Tab.</b> Insert spaces at the cursor position up to the next tab location, moving the cursor. If the mark is set, indent the lines between the mark and cursor.

BackTab	Ctrl-U	<b>Back Tab.</b> Remove spaces left to the cursor position up to the next tab location or the next non-space char, and moves the cursor. If the mark is set, un-indent the lines between the mark and the cursor.
Ctrl-Q	Ctrl-C	<b>Quit</b> the editor or the line edit mode. If the edited text was changed, ask for confirmation.
Ctrl-S		<b>Save</b> to file. The file name will be prompted for. If the mark is set, save the marked region only (*)
Ctrl-E		<b>Redraw</b> the screen according to the actual screen parameters width, height. With MicroPython, as a side effect, garbage collection is performed and the available memory displayed. With Linux/CPython, window size changes result in an automatic redraw.
Ctrl-F		<b>Find</b> text. Whether the search is case sensitive or not, can be set by the Ctrl-A command. The last search string is memorized. Search stops at the end.
Ctrl-N		<b>Repeat find</b> starting at the column right to the cursor.
Ctrl-R		Find and <b>replace</b> . If the mark is set, it affects the marked region only. (*)
Ctrl-G		<b>Go to</b> Line. It prompts for the line number.
Ctrl-A		<b>Settings.</b> Sets the state of search case sensitivity, auto-indent, tab size and write-tabs. Enter 'y' or 'n' or a number in up to three, comma separated fields (e.g. n,y,4,n). An empty field leaves the respective value unchanged. The default values are case sensitive: n, auto-indent: y, tab-size: 4, Write Tabs: n (*)
Ctrl-B	Ctrl-End	<b>Go to last line</b> (kind of obsolete, go to line 99999 will do the same). (*)
Ctrl-T	Ctrl-Home	<b>Go to first line</b> (kind of obsolete, go to line 1 will do the same). (*)
Ctrl-L	Mouse Button 2	Mark/Unmark the current line. This affects Delete, Cut lines, Copy lines, Tab, Backtab, Save and Replace. Right Click on the Mouse will set the Cursor and Mark/Unmark it. (*)
Ctrl-X	Ctrl-Del	<b>Delete delete a line or the area between the mark and the current line</b> and keep it in the paste buffer. Together with the Ctrl-V this implements the Cut & Paste feature. The mark is cleared.
Ctrl-D		<b>Copy a line or the area between the mark and the current line</b> to a buffer. Together with the Ctrl-V this implements the Copy & Paste feature.
Ctrl-V		<b>Insert</b> the content of the <b>buffer</b> before the actual line.
Ctrl-O		<b>Insert</b> the content of a <b>file</b> before the actual line. (*)
Ctrl-Z		<b>Undo</b> the last change(s). Every char sequence change/replaced item/deleted line/inserted line(s) counts as a single change. The default for the undo stack is 50 with PyBoard/WiPy and 500 with Linux/Darwin systems. It can be changed in the call to <code>pye()</code> .

Functions denoted with (\*) are not supported in the minimal version (WiPy, see below). The editor is contained in the file `pye.py`. Start `pye` from the REPL prompt e.g. with

```
from pye import pye
res = pye([object][, tabsize][, undo][, device][, baud])
```

If *object* is a string, it's considered as the name of a file to be edited, and the name of the file will be returned. If *object* is a list of strings, these will be edited, and the edited list will be returned.

Otherwise, `pye()` will give you an empty screen, creating a list of strings, unless you save to a file. In that case, the file name will be returned. Optional named parameters:

tabsize=n	Tab step (integer). The default is 4
undo=n	Size of the undo stack (integer). A value of 0 or False disables undo.
device=n	Device to be used for screen/keyboard on PyBoard (integer). On PyBoard, 0 is USB_VCP. 1 is UART 1, and so on. The default is 0 (USB_VCP). This Option is not available on WiPy. You'll get the output on UART by redirecting the REPL prompt.
baud=n	UART baud rate (integer). The default is 115200.

The Linux/Darwin version can be called from the command line with:

```
python3 pye.py [filename]
```

Using python3 (not micropython), content can also be redirected or pipe'd into the editor.

When reading files, tab characters (`\x09`) in the text are replaced by spaces, tab size 8, and white space at the end of a line is discarded. When you save the file, you have the option to replace sequences of spaces by tabs, tab size 8. However, the original state will NOT be restored. So be careful when editing files with tab characters.

The size of a file that can be edited on PyBoard/WiPy is limited by its memory. You may use REDRAW to determine how much space is left. Besides the file itself, both buffer operations and especially undo consume memory. The undo stack is cleared on saving or can be limited in the call to pye, the buffer size can be reduced again by copying a single line into it after a cursor move. Up to about 300 lines on WiPy and 600 lines on PyBoard should be safe to edit. The largest suitable file size is in the same order of what WiPy/PyBoard can handle as source file.

When you save a file on PyBoard/WiPy, these changes may not be visible in the file system of a connected PC until you disconnect and reconnect the Pyboard/WiPy drive. See also the related discussion in the MicroPython Forum.

The file pye.py is pretty large for PyBoard and way too large for WiPy. As told, it contains C pre-processor statements allowing trimming it down a little bit. For that reason, comments start with `##` instead of `#`. So for PyBoard, you might run:

```
cpp -D PYBOARD -D DEFINES pye.py >pe.py
```

That will result in a file with all functions supplied, but smaller footprint when loaded. The directive `-D DEFINES` will replace symbolic key names with numeric constants, reducing the file size and the demand for symbol space. You may strip down the file size (not the compiled footprint) by removing comments and empty lines (that's what I do), e.g. by:

```
cpp -D PYBOARD -D DEFINES pye.py | sed "s/#.*$//" | sed "/^$/d" >pe.py
```

Doing that also removes dead code like the one for the Linux environment. If the footprint is still too large, you may choose:

```
cpp -D BASIC -D PYBOARD -D DEFINES pye.py | sed "s/#.*$//" | sed "/^$/d" >pemin.py
```

That removes the code for Mouse support, Replace, Goto first line, Goto last line, line join by backspace, indent, un-indent, flag settings, get file, and write tabs. There are still lines left like `"if sys.platform == "pyboard"`. If you do not like these, delete them manually (and take care of the indents). If you just want to get rid of the cpp preprocessor stuff, run:

```
cpp -D PYBOARD -D LINUX -D WIPY pye.py | grep -v "^#.*$" >pe.py
```

The WiPy version will be generated with:

```
cpp -D BASIC -D WIPY -D DEFINES pye.py | sed "s/#.*$//" | sed "/^$/d" >wipye.py
```

**Only this minimal version runs on WiPy.**

### Notes:

- The keyboard mapping assumes VT100. For those interested, I collected the key codes issue by terminal emulators, all claiming VT100 compatible. Picocom seems sometimes to send the Linux Terminal codes. If the KEYMAP is too large, and you know which terminal you are working on, delete or comment out the obsolete lines. If your terminal is different, just change the control codes.

Key	Putty VT100 & Xterm	Putty esc-[~	Putty Linux	Minicom	GtkTerm	Picocom	Linux Terminal
Up	\e[A	\e[A	\e[A	\e[A	\e[A	\e[A	\e[A
Down	\e[B	\e[B	\e[B	\e[B	\e[B	\e[B	\e[B
Left	\e[D	\e[D	\e[D	\e[D	\e[D	\e[D	\e[D
Right	\e[C	\e[C	\e[C	\e[C	\e[C	\e[C	\e[C
Home	\e[1~	\e[1~	\e[1~	\e[1~	\eOH	\eOH	\e[H
End	\e[4~	\e[4~	\e[4~	\eOF	\eOF	\eOF	\e[F
Ins	\e[2~	\e[2~	\e[2~	\e[2~	\e[2~	\e[2~	\e[2~
Del	\e[3~	\e[3~	\e[3~	\e[3~	\e[3~	\e[3~	\e[3~
PgUp	\e[5~	\e[5~	\e[5~	\e[5~	\e[5~	\e[5~	\e[5~
PgDn	\e[6~	\e[6~	\e[6~	\e[6~	\e[6~	\e[6~	\e[6~
Backspace	\x7f	\x7f	\x7f	\x7f	\x08	\x7f	\x7f
Ctrl-Home				\e[1;5H		\e[1;5H	\e[1;5H
Ctrl-End				\e[1;5F		\e[1;5F	\e[1;5F
Ctrl-Del				\e[3;5~	\e[3;5~	\e[3;5~	\e[3;5~
Tab	\x09	\x09	\x09	\x09	\x09	\x09	\x09
BackTab	\e[Z	\e[Z	\e[Z	\e[Z	\e[Z	\e[Z	\e[Z

- For those who wonder why sending data to the screen on PyBoard is more than a simple write(): for USB\_VCP.write() stumbles over a large amount of data to be sent in short time. The difference is, that UART.write() waits internally until all has been sent, whereas USB\_VCP.write() stops when it cannot send more data. So we have to see what's coming back. And, b.t.w., PyBoard's UART.write() does not like empty strings, which in turn is accepted by USB\_VCP.write() or WiPy's UART.write().
- Windows terminal emulators behave inconsistent. Putty does not report the mouse actions at all. TeraTerm, IVT terminal and Xsh20 just report the mouse click, but not the scroll wheel actions. ZOC reports mouse positions constantly, and sends no key codes for Home, End, PgUp, PGDn and Del. The latter holds also for PowerVT. I could not get Qodem working. Hyperterminal's VT100 emulation is crap. So, after all, I consider TeraTerm, Xsh20 or Putty as the best choices for Windows.
- Gnome terminal sometimes does not send the first mouse wheel code, after the pointer was moved into the window. Mate and XFCE4 terminal do, but have slightly different keyboard mappings.
- Serial connection on WiPy is not stable (yet), especially with fast auto-repeat (Maybe flow control is needed).
- Saving to internal flash of PyBoard is really slow, so don't get nervous. Watch the red LED.
- Ctrl-C as input in WiPy Telnet sessions is caught, such that the editor is not interrupted, but the next input byte is lost, which causes garbage by cursor/function keys.
- WiPY telnet sessions sometimes seemed to be closed unexpected, but pye kept on running. On reconnection, some garbage was displayed. Not seen in recent versions of WiPy (Nov 18).