

### NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices

Edition No. : 23.0.0.5.26

Edition Issue Date : 29/04/2019

Author : NM NOP/B2B Team

Reference : B2B/23.0.0/Flow

Copy No. :  $\leftarrow$  stamp here

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

### **Document Control**

#### **Copyright Notice**

© 2019 European Organisation for the Safety of Air Navigation (EUROCONTROL). All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without the prior written permission of EUROCONTROL.

#### **Document Identification**

Full Title:	NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices
Total Number of Pages:	279

### **Table of Contents**

References 1	
Terminology	. 18
1 Introduction	. 19
1.1 Identification	. 19
2 Context	. 20
3 Port Types	. 21
3.1 TrafficCountsService Port Type	
3.1.1 Overview	
3.1.1.1 Introduction	
3.1.2 Traffic Count List by Aircraft Operator	
3.1.2.1 SOAP	
3.1.2.2 TrafficCountsByAircraftOperatorRequest	
3.1.2.3 TrafficCountsByAircraftOperatorReply	
3.1.3 Traffic Count List by Aerodrome	
3.1.3.1 SOAP	
3.1.3.2 TrafficCountsByAerodromeRequest	
3.1.3.3 TrafficCountsByAerodromeReply	
3.1.4 Traffic Count List by Aerodrome Set	
3.1.4.1 SOAP	
3.1.4.2 TrafficCountsByAerodromeSetRequest	
3.1.4.3 TrafficCountsByAerodromeSetReply	
3.1.5 Traffic Count List by Airspace	
3.1.5.1 SOAP	
3.1.5.2 TrafficCountsByAirspaceRequest	
3.1.5.3 TrafficCountsByAirspaceReply	
3.1.6 Traffic Count List by Point	
3.1.6.1 SOAP	
3.1.6.2 TrafficCountsByPointRequest	
3.1.6.3 TrafficCountsByPointReply	
3.1.7 Traffic Count List by Traffic Volume	
3.1.7.1 SOAP	
3.1.7.2 TrafficCountsByTrafficVolumeRequest	
3.1.7.3 TrafficCountsByTrafficVolumeReply	
3.2 MeasuresService Port Type	
3.2.1 Overview	
3.2.1.1 Introduction	
3.2.1.2 Update Pattern	
3.2.1.3 Transaction and Errors	
3.2.1.4 Allowed Times for Retrievals and Updates	
3.2.1.4.1 Forecast and Operational Datasets	
3.2.1.4.2 Past	. აგ

3.2.1.6 Overload protection 3.2.2 Regulation List	20
	30
00010	
3.2.2.1 SOAP	
3.2.2.2 RegulationListRequest	39
3.2.2.3 RegulationListReply	41
3.2.3 Regulation Creation	
3.2.3.1 SOAP	
3.2.3.2 RegulationCreationRequest	
3.2.3.3 RegulationCreationReply4	45
3.2.4 Regulation Update	
3.2.4.1 SOAP4	
3.2.4.2 RegulationUpdateRequest4	46
3.2.4.3 RegulationUpdateReply	
3.2.5 Regulation Cancellation	
3.2.5.1 SOAP	
3.2.5.2 RegulationCancelRequest4	49
3.2.5.3 RegulationCancelReply	
3.2.6 Regulation Proposal List	
3.2.6.1 SOAP5	
3.2.6.2 RegulationProposalListRequest	51
3.2.6.3 RegulationProposalListReply	53
3.2.7 Regulation Proposal Filing	
3.2.7.1 SOAP5	
3.2.7.2 RegulationProposalFilingRequest	
3.2.7.3 RegulationProposalFilingReply	
3.2.8 Updating a filed Regulation Proposal	
3.2.8.1 SOAP5	
2 2 9 2 PagulatianDranacalUndataDaguact	
3.2.8.2 RegulationProposalUpdateRequest6	
3.2.8.3 RegulationProposalUpdateReply6	62
3.2.8.3 RegulationProposalUpdateReply	62 63
3.2.8.3 RegulationProposalUpdateReply	62 63 63
3.2.8.3 RegulationProposalUpdateReply	62 63 63 63
3.2.8.3 RegulationProposalUpdateReply	62 63 63 63 65
3.2.8.3 RegulationProposalUpdateReply	62 63 63 65 66
3.2.8.3 RegulationProposalUpdateReply 6 3.2.9 Regulation Proposal Revocation 6 3.2.9.1 SOAP 6 3.2.9.2 RegulationProposalRevocationRequest 6 3.2.9.3 RegulationProposalRevocationReply 6 3.2.10 Rerouting List 6 3.2.10.1 SOAP 6	62 63 63 65 66 66
3.2.8.3 RegulationProposalUpdateReply 3.2.9 Regulation Proposal Revocation 3.2.9.1 SOAP 3.2.9.2 RegulationProposalRevocationRequest 3.2.9.3 RegulationProposalRevocationReply 3.2.10 Rerouting List 3.2.10.1 SOAP 3.2.10.2 ReroutingListRequest	62 63 63 65 66 66
3.2.8.3 RegulationProposalUpdateReply 3.2.9 Regulation Proposal Revocation 6 3.2.9.1 SOAP 6 3.2.9.2 RegulationProposalRevocationRequest 6 3.2.9.3 RegulationProposalRevocationReply 6 3.2.10 Rerouting List 6 3.2.10.1 SOAP 6 3.2.10.2 ReroutingListRequest 6 3.2.10.3 ReroutingListReply 6	62 63 63 65 66 66 66
3.2.8.3 RegulationProposalUpdateReply 3.2.9 Regulation Proposal Revocation 6 3.2.9.1 SOAP 6 3.2.9.2 RegulationProposalRevocationRequest 7 3.2.9.3 RegulationProposalRevocationReply 7 3.2.10 Rerouting List 7 3.2.10.1 SOAP 7 3.2.10.2 ReroutingListRequest 7 3.2.10.3 ReroutingListReply 7 3.2.11 Rerouting Creation 7 6 6 6 6 7 6 7 7 7 7 7 7 7 7 7 7 7 7 7	62 63 63 65 66 66 68 69
3.2.8.3 RegulationProposalUpdateReply 3.2.9 Regulation Proposal Revocation 3.2.9.1 SOAP 3.2.9.2 RegulationProposalRevocationRequest 3.2.9.3 RegulationProposalRevocationReply 3.2.10 Rerouting List 3.2.10.1 SOAP 3.2.10.2 ReroutingListRequest 3.2.10.3 ReroutingListReply 3.2.11 Rerouting Creation 3.2.11.1 SOAP	62 63 63 65 66 66 68 69 69
3.2.8.3 RegulationProposalUpdateReply 3.2.9 Regulation Proposal Revocation 6 3.2.9.1 SOAP 6 3.2.9.2 RegulationProposalRevocationRequest 7 3.2.9.3 RegulationProposalRevocationReply 7 3.2.10 Rerouting List 7 3.2.10.1 SOAP 7 3.2.10.2 ReroutingListRequest 7 3.2.10.3 ReroutingListReply 7 3.2.11 Rerouting Creation 7 3.2.11.1 SOAP 7 3.2.11.2 ReroutingCreationRequest 7 3.2.11.2 ReroutingCreation	62 63 63 65 66 66 68 69 69
3.2.8.3 RegulationProposalUpdateReply       6         3.2.9 Regulation Proposal Revocation       6         3.2.9.1 SOAP       6         3.2.9.2 RegulationProposalRevocationRequest       6         3.2.9.3 RegulationProposalRevocationReply       6         3.2.10 Rerouting List       6         3.2.10.1 SOAP       6         3.2.10.2 ReroutingListRequest       6         3.2.10.3 ReroutingListReply       6         3.2.11 Rerouting Creation       6         3.2.11.2 ReroutingCreationRequest       6         3.2.11.3 ReroutingCreationReply       7	62 63 63 65 66 66 69 69 71
3.2.8.3 RegulationProposalUpdateReply 3.2.9 Regulation Proposal Revocation 63.2.9.1 SOAP 73.2.9.2 RegulationProposalRevocationRequest 73.2.9.3 RegulationProposalRevocationReply 73.2.10 Rerouting List 73.2.10.1 SOAP 73.2.10.2 ReroutingListRequest 73.2.10.3 ReroutingListRequest 73.2.10.3 ReroutingListReply 73.2.11 Rerouting Creation 73.2.11.1 SOAP 73.2.11.2 ReroutingCreationRequest 73.2.11.3 ReroutingCreationReply 73.2.12 ReroutingUpdate 73.2.12 ReroutingUpdat	62 63 63 65 66 66 69 69 71
3.2.8.3 RegulationProposalUpdateReply 3.2.9 Regulation Proposal Revocation 3.2.9.1 SOAP 3.2.9.2 RegulationProposalRevocationRequest 3.2.9.3 RegulationProposalRevocationReply 3.2.10 Rerouting List 3.2.10.1 SOAP 3.2.10.2 ReroutingListRequest 3.2.10.3 ReroutingListReply 3.2.11 Rerouting Creation 3.2.11.1 SOAP 3.2.11.2 ReroutingCreationRequest 3.2.11.3 ReroutingCreationRequest 3.2.12 Rerouting Update 3.2.12 Rerouting Update 3.2.12 Rerouting Update 3.2.12 SOAP	62 63 63 65 66 66 69 71 71
3.2.8.3 RegulationProposalUpdateReply       6         3.2.9 Regulation Proposal Revocation       6         3.2.9.1 SOAP       6         3.2.9.2 RegulationProposalRevocationRequest       6         3.2.9.3 RegulationProposalRevocationReply       6         3.2.10 Rerouting List       6         3.2.10.1 SOAP       6         3.2.10.2 ReroutingListRequest       6         3.2.11 Rerouting Creation       6         3.2.11.1 SOAP       6         3.2.11.2 ReroutingCreationRequest       6         3.2.12 Rerouting Update       7         3.2.12.1 SOAP       7         3.2.12.2 ReroutingUpdateRequest       7	62 63 63 65 66 66 69 71 71 71
3.2.8.3 RegulationProposalUpdateReply 3.2.9 Regulation Proposal Revocation 3.2.9.1 SOAP 3.2.9.2 RegulationProposalRevocationRequest 3.2.9.3 RegulationProposalRevocationReply 3.2.10 Rerouting List 3.2.10.1 SOAP 3.2.10.2 ReroutingListRequest 3.2.10.3 ReroutingListReply 3.2.11 Rerouting Creation 3.2.11.1 SOAP 3.2.11.2 ReroutingCreationRequest 3.2.11.3 ReroutingCreationRequest 3.2.12 Rerouting Update 3.2.12 Rerouting Update 3.2.12 Rerouting Update 3.2.12 SOAP	62 63 63 65 66 66 69 71 71 72 73

3.2.13.1 SOAP	74
3.2.13.2 ReroutingCancelRequest	74
3.2.13.3 ReroutingCancelReply	75
3.2.14 MCDMOnly List	76
3.2.14.1 SOAP	76
3.2.14.2 MCDMOnlyListRequest	76
3.2.14.3 MCDMOnlyListReply	78
3.2.15 MCDMOnly Creation	79
3.2.15.1 SOAP	79
3.2.15.2 MCDMOnlyCreationRequest	80
3.2.15.3 MCDMOnlyCreationReply	81
3.2.16 MCDMOnly Update	82
3.2.16.1 SOAP	82
3.2.16.2 MCDMOnlyUpdateRequest	82
3.2.16.3 MCDMOnlyUpdateReply	83
3.2.17 MCDMOnly Cancellation	84
3.2.17.1 SOAP	84
3.2.17.2 MCDMOnlyCancelRequest	84
3.2.17.3 MCDMOnlyCancelReply	85
3.2.18 Measure Operational Log Retrieval	86
3.2.18.1 SOAP	
3.2.18.2 MeasureOpLogRetrievalRequest	86
3.2.18.3 MeasureOpLogRetrievalReply	87
3.2.19 Update Flights in Measure	88
3.2.19.1 SOAP	88
3.2.19.2 UpdateFlightsInMeasureRequest	88
3.2.19.3 UpdateFlightsInMeasureReply	90
3.2.20 ATFCM Situation Retrieval	90
3.2.20.1 SOAP	
3.2.20.2 ATFCMSituationRequest	91
3.2.20.3 ATFCMSituationReply	92
3.2.21 Retrieve Network Impact Assessment	
3.2.21.1 SOAP	
3.2.21.2 NetworkImpactAssessmentRetrievalRequest	93
3.2.21.3 NetworkImpactAssessmentRetrievalReply	95
3.3 McdmService Port Type	
3.3.1 Overview	
3.3.1.1 Introduction	
3.3.1.2 MCDM Operations	
3.3.1.3 Update Pattern	
3.3.2 MCDM Topic List	
3.3.2.1 SOAP	
3.3.2.2 MCDMTopicListRequest	
3.3.2.3 MCDMTopicListReply	
3.3.3 MCDM Topic Update	
3.3.3.1 SOAP	
3.3.3.2 MCDMTopicUpdateRequest	103

3.3.3.3 MCDMTopicUpdateReply	. 103
3.3.4 MCDM Topic Message Retrieval	. 104
3.3.4.1 SOAP	. 104
3.3.4.2 MCDMTopicMessageRetrievalRequest	. 104
3.3.4.3 MCDMTopicMessageRetrievalReply	. 105
3.3.5 MCDM State Update	
3.3.5.1 SOAP	. 105
3.3.5.2 MCDMStateUpdateRequest	. 106
3.3.5.3 MCDMStateUpdateReply	. 107
3.4 TacticalUpdatesService Port Type	. 108
3.4.1 Overview	. 108
3.4.1.1 Introduction	
3.4.1.2 CACD Retrievals vs. Tactical Situation	. 108
3.4.1.3 Daily Plan Update Pattern	
3.4.1.4 Transactions and Errors	
3.4.1.5 Allowed Times for Retrievals and Updates	
3.4.1.5.1 Forecast and Operational Datasets	
3.4.1.5.2 Past	
3.4.2 Retrieve a Sector Configuration Plan	
3.4.2.1 SOAP	
3.4.2.2 SectorConfigurationPlanRetrievalRequest	
3.4.2.3 SectorConfigurationPlanRetrievalReply	
3.4.3 Update a Sector Configuration Plan	
3.4.3.1 SOAP	
3.4.3.2 SectorConfigurationPlanUpdateRequest	
3.4.3.3 SectorConfigurationPlanUpdateReply	
3.4.4 Retrieve a Capacity Plan	
3.4.4.1 SOAP	
3.4.4.2 CapacityPlanRetrievalRequest	
3.4.4.3 CapacityPlanRetrievalReply	
3.4.5 Update a Capacity Plan	
3.4.5.1 SOAP	
3.4.5.2 CapacityPlanUpdateRequest	
3.4.5.3 CapacityPlanUpdateReply	
3.4.6 Retrieve a Traffic Volume Activation Plan	
3.4.6.1 SOAP	
3.4.6.2 TrafficVolumeActivationPlanRetrievalRequest	
3.4.6.3 TrafficVolumeActivationPlanRetrievalReply	
3.4.7 Update a Traffic Volume Activation Plan	
3.4.7.1 SOAP	
3.4.7.2 TrafficVolumeActivationPlanUpdateRequest	
3.4.7.3 TrafficVolumeActivationPlanUpdateReply	
3.4.8 Retrieve an OTMV Plan	
3.4.8.1 SOAP	
3.4.8.2 OTMVPlanRetrievalRequest	
3.4.8.3 OTMVPlanRetrievalReply	
3.4.9 Update an OTMV Plan	. 125

3.4.9.1 SOAP	125
3.4.9.2 OTMVPlanUpdateRequest	125
3.4.9.3 OTMVPlanUpdateReply	126
3.4.10 Retrieve a runway configuration plan	
3.4.10.1 SOAP	
3.4.10.2 RunwayConfigurationPlanRetrievalRequest	127
3.4.10.3 RunwayConfigurationPlanRetrievalReply	127
3.4.11 Update a runway configuration plan	
3.4.11.1 SOAP	
3.4.11.2 RunwayConfigurationPlanUpdateRequest	128
3.4.11.3 RunwayConfigurationPlanUpdateReply	129
3.4.12 Hotspot List	129
3.4.12.1 SOAP	129
3.4.12.2 HotspotListRequest	130
3.4.12.3 HotspotListReply	132
3.4.13 Hotspot Plan Update	132
3.4.13.1 SOAP	132
3.4.13.2 HotspotPlanUpdateRequest	133
3.4.13.3 HotspotPlanUpdateReply	134
3.5 SimulationsService Port Type	
3.5.1 Overview	
3.5.1.1 Introduction	
3.5.1.2 Simulations	
3.5.2 Simulation List	
3.5.2.1 SOAP	
3.5.2.2 SimulationListRequest	
3.5.2.3 SimulationListReply	
3.5.3 Simulation Availability List	
3.5.3.1 SOAP	
3.5.3.2 SimulationAvailabilityRequest	
3.5.3.3 SimulationAvailabilityReply	
3.5.4 Simulation Start	_
3.5.4.1 SOAP	
3.5.4.2 SimulationStartRequest	
3.5.4.3 SimulationStartReply	
3.5.5 Simulation Stop	
3.5.5.1 SOAP	
3.5.5.2 SimulationStopRequest	
3.5.5.3 SimulationStopReply	
3.6 Scenario Repository Port Type	
3.6.1 Overview	
3.6.1.2 Scenario Repository	
3.6.2.1 SOAP	
3.6.2.2 ScenarioRegulationRetrievalRequest	
3.6.2.3 ScenarioRegulationRetrievalReply	
3.0.2.0 Scenar tonegulationneth tevalnepty	14/

	3.6.3 Retrieve list of Reroutings from Scenario	14/
	3.6.3.1 SOAP	
	3.6.3.2 ScenarioReroutingRetrievalRequest	148
	3.6.3.3 ScenarioReroutingRetrievalReply	148
	3.6.4 Retrieve list of MCDMOnly from Scenario	149
	3.6.4.1 SOAP	
	3.6.4.2 ScenarioMCDMOnlyRetrievalRequest	149
	3.6.4.3 ScenarioMCDMOnlyRetrievalReply	
	3.6.5 List of Scenarios	
	3.6.5.1 SOAP	
	3.6.5.2 ScenarioListRequest	
	3.6.5.3 ScenarioListReply	152
4	Data Types	
	4.1 AerodromeLocation	
	4.2 AirspaceLocation	
	4.3 AllFlightsLocation	
	4.4 ANDedReroutingConstraints	
	4.5 AoLocation	
	4.6 ATFCMSituationCounts	
	4.7 ATFCMSituationDelays	
	4.8 ATFCMSituationRegulation	
	4.9 < <enumeration>&gt; AvoidAirspaceReroutingKind</enumeration>	
	4.10 AvoidViaAirspaceReroutingConstraint	
	4.11 AvoidViaPointReroutingConstraint	
	4.12 < <enumeration>&gt; AvoidViaReroutingType</enumeration>	
	4.13 typedef <int> Capacity</int>	
	4.14 CapacityPlans	
	4.15 CherryPickedLocation	
	4.16 Counts	
	4.17 < <enumeration>&gt; CountsCalculationType</enumeration>	
	4.18 CountsCalculationTypeAndInterval	
	4.19 CountsInterval	
	4.20 typedef <int> CountsValue</int>	
	4.21 DatasetReference	
	4.22 < <strict enumeration="">&gt; DatasetReferenceType</strict>	
	4.23 DelayLocation	
	4.24 DeltaATFCMSituation	
	4.25 DeltaATFCMSituationCounts	
	4.26 DeltaATFCMSituationDelays	
	4.27 DeltaATFCMSituationRegulation	
	4.28 DeltaCounts	
	4.29 DeltaLevelReroutingConstraint	
	4.30 ExcludeReIncludeFlightInRegulation	
	4.31 FlightAtfcmMcdmOnlyLocation	
	4.32 < <abstract>&gt; FlightAtfcmMeasureLocation</abstract>	165

Edition: 23.0.0.5.26

8

4.33	FlightAtfcmRegulationLocation166			
4.34	4 FlightAtfcmReroutingLocation1			
4.35	FlightHotspotLocation	167		
4.36	FlightMCDMInfo	167		
4.37	FlightRegulationLocation	168		
4.38	Flow	168		
4.39	typedef <string> FlowId</string>	169		
4.40	<pre>&lt;<enumeration>&gt; FlowRoleSelection</enumeration></pre>	169		
4.41	< <enumeration>&gt; FlowType</enumeration>	170		
4.42	ForceFlightInRegulation	171		
4.43	< <enumeration>&gt; FreezeTP</enumeration>	172		
4.44	<pre>&lt;<enumeration>&gt; GroupReroutingIndicator</enumeration></pre>	172		
	Hotspot			
4.46	< <enumeration>&gt; HotspotField</enumeration>	173		
4.47	HotspotId	174		
	< <enumeration>&gt; HotspotKind</enumeration>			
4.49	HotspotPlans	175		
4.50	<pre>&lt;<enumeration>&gt; HotspotSeverity</enumeration></pre>	176		
4.51	<pre>&lt;<enumeration>&gt; HotspotStatus</enumeration></pre>	176		
4.52	<pre>&lt;<enumeration>&gt; KindOfRestriction</enumeration></pre>	177		
4.53	LevelAndSpeedReroutingConstraint	177		
	<pre>&lt;<enumeration>&gt; LevelConstraintKind</enumeration></pre>			
4.55	LifeCycleEvent	178		
	<pre>&lt;<enumeration>&gt; LifeCycleEventType</enumeration></pre>			
	< <abstract>&gt; Location</abstract>			
4.58	<pre>&lt;<enumeration>&gt; MCDMApprovalState</enumeration></pre>	179		
4.59	<pre>&lt;<enumeration>&gt; MCDMCoordinationLevel</enumeration></pre>	179		
	MCDMDeadlines			
	MCDMFlightTopic			
	MCDMHotspotTopic			
4.63	MCDMMeasureTopic	183		
4.64	MCDMMessage	185		
4.65	< <enumeration>&gt; MCDMMessageType</enumeration>	185		
	MCDMOnly			
	< <enumeration>&gt; MCDMOnlyField</enumeration>			
	< <enumeration>&gt; MCDMRole</enumeration>			
	MCDMRoleUserCategory			
	< <enumeration>&gt; MCDMState</enumeration>			
	< <abstract>&gt; MCDMStatefulTopic</abstract>			
	< <abstract>&gt; MCDMTopic</abstract>			
	< <enumeration>&gt; MCDMTopicField</enumeration>			
	typedef <string> MCDMTopicId</string>			
	MCDMTopicListRequestSelector			
	MCDMUserAndRole			
4.77	< <enumeration>&gt; MCDMUserCategory</enumeration>	197		

4.78	MCDMUserRoleAndApprovalState	197	
	< <abstract>&gt; Measure</abstract>		
4.80	MeasureFromScenarioRepository	201	
4.81	MeasureId		
4.82	MeasureIdAndTV	202	
4.83	MeasureListReplyData	202	
4.84	< <abstract>&gt; MeasureListRequest</abstract>		
	< <enumeration>&gt; MeasureSubType</enumeration>		
4.86	NMOCManagedSimulation		
4.87	OtherReroutingConstraint	206	
4.88	OTMV	206	
4.89	OtmvAlert	207	
4.90	OTMVPeak	207	
4.91	OTMVPlan	207	
4.92	OTMVPlanForDuration	209	
4.93	OTMVPlans	210	
4.94	< <enumeration>&gt; OtmvStatus</enumeration>	211	
4.95	OTMVSustained	212	
4.96	typedef <int> OTMVThreshold</int>	212	
4.97	OTMVWithDuration	212	
4.98	< <strict enumeration="">&gt; PlanDataSource</strict>	213	
4.99	PlannedCapacities	213	
4.100	) PlannedCapacity	214	
4.101	PlannedOTMV	215	
4.102	PlannedRunwayConfigurations	216	
4.103	B PlannedSectorConfigurationActivation	217	
	PlannedTrafficVolumeActivation		
4.105	5 PlannedTrafficVolumeActivations	219	
4.106	S PointLocation	220	
4.107	<sup>7</sup> Regulation	220	
4.108	RegulationCause	221	
4.109	RegulationExceptionalConstraint	221	
4.110	) < <enumeration>&gt; RegulationField</enumeration>	222	
4.111	typedef <string> RegulationId</string>	223	
4.112	<pre>2 typedef<string> RegulationIdWildcard</string></pre>	224	
4.113	RegulationInitialConstraint	224	
4.114	<pre>&lt;<enumeration>&gt; RegulationLocationCategory</enumeration></pre>	224	
4.115	<pre>5 &lt;<abstract>&gt; RegulationOrMCDMOnly</abstract></pre>	225	
4.116	RegulationOrMCDMOnlyListReplyData	229	
4.117	<pre>' &lt;<abstract>&gt; RegulationOrMCDMOnlyListRequest</abstract></pre>	230	
4.118	RegulationProposal	231	
	<pre>&gt; &lt;<enumeration>&gt; RegulationProposalAction</enumeration></pre>		
	<pre>&gt; &lt;<enumeration>&gt; RegulationProposalField</enumeration></pre>		
4.121	<pre>&lt;<enumeration>&gt; RegulationProposalKind</enumeration></pre>	235	
4.122	<pre>2 &lt;<enumeration>&gt; RegulationProposalState</enumeration></pre>	235	

4.123	< <enumeration>&gt; RegulationReason</enumeration>	236
4.124	<pre>&lt;<enumeration>&gt; RegulationState</enumeration></pre>	236
4.125	RegulationSupplementaryConstraint	237
4.126	<pre>&lt;<enumeration>&gt; RepositoryId</enumeration></pre>	. 237
	Rerouting	
4.128	< <enumeration>&gt; ReroutingApplyKind</enumeration>	240
4.129	< <abstract>&gt; ReroutingConstraint</abstract>	241
4.130	<pre>&lt;<enumeration>&gt; ReroutingField</enumeration></pre>	. 241
4.131	ReroutingHorizontalConstraints	. 242
4.132	typedef <string> ReroutingId</string>	243
4.133	typedef <string> ReroutingIdWildcard</string>	. 243
4.134	ReroutingManualConstraints	243
4.135	< <enumeration>&gt; ReroutingMeasureState</enumeration>	244
4.136	ReroutingSourcesAndConstraints	. 245
4.137	RestrictionLocation	246
	RunwayConfiguration	
4.139	RunwayConfigurationPlan	. 247
4.140	< <enumeration>&gt; RunwayUsage</enumeration>	. 249
4.141	ScenarioAttributes	. 250
4.142	typedef <string> ScenarioEvent</string>	. 252
4.143	typedef <string> ScenarioId</string>	252
4.144	ScenarioImpact	253
4.145	ScenarioLevelConstraint	. 253
4.146	ScenarioMeasureRetrievalRequest	254
	typedef <string> ScenarioName</string>	
4.148	<pre>&lt;<enumeration>&gt; ScenarioPublicationStatus</enumeration></pre>	. 255
	<pre>&lt;<enumeration>&gt; ScenarioTrafficVolumeMatchingKind</enumeration></pre>	
4.150	< <enumeration>&gt; ScenarioType</enumeration>	256
	typedef <string> SectorConfigurationId</string>	
4.152	SectorConfigurationPlan	. 257
	SegmentLocation	
4.154	SetOfAerodromesLocation	. 259
4.155	SignificantDeltaCount	259
	SignificantDeltaDuration	
4.157	< <abstract>&gt; Simulation</abstract>	. 260
	SimulationAvailability	
	typedef <string> SimulationName</string>	
	< <enumeration>&gt; SimulationType</enumeration>	
	StandaloneSimex	
	<pre>&lt;<enumeration>&gt; SubTotalsTrafficCountsType</enumeration></pre>	
	< <abstract>&gt; TacticalConfigurationPlan</abstract>	
	< <abstract>&gt; TacticalConfigurationRetrievalRequest</abstract>	
	< <abstract>&gt; TrafficCountsReplyData</abstract>	
	< <abstract>&gt; TrafficCountsRequest</abstract>	
4.167	TrafficVolumeActivationPlan	269

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

4.168	TrafficVolumeActivationPlans	271
4.169	typedef <string> TrafficVolumeId</string>	272
4.170	TrafficVolumeLocation	273
4.171	TrafficVolumeScenarios	274
4.172	UpdateFlightInMeasure	275
4.173	UpdateFlightInMeasureChoice	275
4.174	UserManagedSimulation	276
5 PRE-C	PS Testing	278
DOCUM	ENT FINAL PAGE	279

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices		B2B/23.0.0/Flow

### **List of Figures**

3.1 TrafficCountsByAircraftOperatorRequest Class Diagram	22
3.2 TrafficCountsByAircraftOperatorReply Class Diagram	23
3.3 TrafficCountsByAerodromeRequest Class Diagram	24
3.4 TrafficCountsByAerodromeReply Class Diagram	
3.5 TrafficCountsByAerodromeSetRequest Class Diagram	26
3.6 TrafficCountsByAerodromeSetReply Class Diagram	27
3.7 TrafficCountsByAirspaceRequest Class Diagram	28
3.8 TrafficCountsByAirspaceReply Class Diagram	29
3.9 TrafficCountsByPointRequest Class Diagram	30
3.10 TrafficCountsByPointReply Class Diagram	31
3.11 TrafficCountsByTrafficVolumeRequest Class Diagram	32
3.12 TrafficCountsByTrafficVolumeReply Class Diagram	34
3.13 RegulationListRequest Class Diagram	39
3.14 RegulationListReply Class Diagram	
3.15 RegulationCreationRequest Class Diagram	
3.16 RegulationCreationReply Class Diagram	
3.17 RegulationUpdateRequest Class Diagram	
3.18 RegulationUpdateReply Class Diagram	
3.19 RegulationCancelRequest Class Diagram	
3.20 RegulationCancelReply Class Diagram	
3.21 RegulationProposalListRequest Class Diagram	
3.22 RegulationProposalListReply Class Diagram	
3.23 RegulationProposalFilingRequest Class Diagram	
3.24 RegulationProposalFilingReply Class Diagram	
3.25 RegulationProposalUpdateRequest Class Diagram	
3.26 RegulationProposalUpdateReply Class Diagram	
3.27 RegulationProposalRevocationRequest Class Diagram	
3.28 RegulationProposalRevocationReply Class Diagram	
3.29 ReroutingListRequest Class Diagram	
3.30 ReroutingListReply Class Diagram	
3.31 ReroutingCreationRequest Class Diagram	
3.32 ReroutingCreationReply Class Diagram	
3.33 ReroutingUpdateRequest Class Diagram	
3.34 ReroutingUpdateReply Class Diagram	
3.35 ReroutingCancelRequest Class Diagram	
3.36 ReroutingCancelReply Class Diagram	
3.37 MCDMOnlyListRequest Class Diagram	
3.38 MCDMOnlyListReply Class Diagram	
3.39 MCDMOnlyCreationRequest Class Diagram	
3.40 MCDMOnlyCreationReply Class Diagram	
3.41 MCDMOnlyUpdateRequest Class Diagram	
3.42 MCDMOnlyUpdateReply Class Diagram	
3.43 MCDMOnlyCancelRequest Class Diagram	84

3.44 M	MCDMOnlyCancelReply Class Diagram	85
3.45 N	MeasureOpLogRetrievalRequest Class Diagram	86
3.46 N	MeasureOpLogRetrievalReply Class Diagram	. 87
	JpdateFlightsInMeasureRequest Class Diagram	
3.48 L	JpdateFlightsInMeasureReply Class Diagram	. 90
	ATFCMSituationRequest Class Diagram	
	ATFCMSituationReply Class Diagram	
	NetworkImpactAssessmentRetrievalRequest Class Diagram	
	NetworkImpactAssessmentRetrievalReply Class Diagram	
	MCDMTopicListRequest Class Diagram	
	MCDMTopicListReply Class Diagram	
	MCDMTopicUpdateRequest Class Diagram	
	MCDMTopicMessageRetrievalRequest Class Diagram	
	MCDMTopicMessageRetrievalReply Class Diagram	
	MCDMStateUpdateRequest Class Diagram	
	MCDMStateUpdateReply Class Diagram	
	SectorConfigurationPlanRetrievalRequest Class Diagram	
	SectorConfigurationPlanRetrievalReply Class Diagram	
	SectorConfigurationPlanUpdateRequest Class Diagram	
	SectorConfigurationPlanUpdateReply Class Diagram	
	CapacityPlanRetrievalRequest Class Diagram	
	CapacityPlanRetrievalReply Class Diagram	
	CapacityPlanUpdateRequest Class Diagram	
	CapacityPlanUpdateReply Class Diagram	
	TrafficVolumeActivationPlanRetrievalRequest Class Diagram	
	TrafficVolumeActivationPlanRetrievalReply Class Diagram	
	TrafficVolumeActivationPlanUpdateRequest Class Diagram TrafficVolumeActivationPlanUpdateReply Class Diagram	
	OTMVPlanRetrievalRequest Class Diagram	
	OTMVPlanRetrievalReply Class Diagram	
	OTMVPlanUpdateRequest Class Diagram	
	OTMVPlanUpdateReply Class Diagram	
	RunwayConfigurationPlanRetrievalRequest Class Diagram	
	RunwayConfigurationPlanRetrievalReply Class Diagram	
	RunwayConfigurationPlanUpdateRequest Class Diagram	
	RunwayConfigurationPlanUpdateReply Class Diagram	
	HotspotListRequest Class Diagram	
	HotspotListReply Class Diagram	
	HotspotPlanUpdateRequest Class Diagram	
	SimulationListRequest Class Diagram	
	SimulationListReply Class Diagram	
	SimulationAvailabilityRequest Class Diagram	
	SimulationAvailabilityReply Class Diagram	
	SimulationStartRequest Class Diagram	
	SimulationStartReply Class Diagram	

3.89 SimulationStopRequest Class Diagram	. 143
3.90 SimulationStopReply Class Diagram	. 144
3.91 ScenarioRegulationRetrievalRequest Class Diagram	. 146
3.92 ScenarioRegulationRetrievalReply Class Diagram	
3.93 ScenarioReroutingRetrievalRequest Class Diagram	. 148
3.94 ScenarioReroutingRetrievalReply Class Diagram	
3.95 ScenarioMCDMOnlyRetrievalRequest Class Diagram	. 149
3.96 ScenarioMCDMOnlyRetrievalReply Class Diagram	
3.97 ScenarioListRequest Class Diagram	. 151
3.98 ScenarioListReply Class Diagram	. 152
4.1 DeltaATFCMSituation Class Diagram	. 162
4.2 < <abstract>&gt; Location Class Diagram</abstract>	. 179
4.3 MCDMFlightTopic Class Diagram	
4.4 MCDMHotspotTopic Class Diagram	. 182
4.5 MCDMMeasureTopic Class Diagram	. 183
4.6 MCDM0nly Class Diagram	. 186
4.7 MCDM transition diagram	. 190
4.8 < <abstract>&gt; MCDMStatefulTopic Class Diagram</abstract>	. 192
4.9 < <abstract>&gt; MCDMTopic Class Diagram</abstract>	. 194
4.10 < <abstract>&gt; Measure Class Diagram</abstract>	. 198
4.11 MeasureFromScenarioRepository Class Diagram	. 201
4.12 < <abstract>&gt; MeasureListRequest Class Diagram</abstract>	. 203
4.13 Regulation Class Diagram	. 220
4.14 < <abstract>&gt; RegulationOrMCDMOnly Class Diagram</abstract>	. 225
4.15 < <abstract>&gt; RegulationOrMCDMOnlyListRequest Class Diagram</abstract>	. 230
4.16 RegulationProposal Class Diagram	. 231
4.17 Rerouting Class Diagram	
4.18 < <abstract>&gt; ReroutingConstraint Class Diagram</abstract>	. 241
4.19 ReroutingSourcesAndConstraints Class Diagram	. 245
4.20 ScenarioAttributes Class Diagram	. 250
4.21 ScenarioLevelConstraint Class Diagram	. 253
4.22 ScenarioMeasureRetrievalRequest Class Diagram	. 254
4.23 < <enumeration>&gt; ScenarioPublicationStatus Class Diagram</enumeration>	. 255
4.24 < <enumeration>&gt; ScenarioTrafficVolumeMatchingKind Class Diagram</enumeration>	. 255
4.25 < <enumeration>&gt; ScenarioType Class Diagram</enumeration>	. 256
4.26 < <abstract>&gt; Simulation Class Diagram</abstract>	
4.27 < <abstract>&gt; TacticalConfigurationRetrievalRequest Class Diagram</abstract>	. 265
4.28 < <abstract>&gt; TrafficCountsReplyData Class Diagram</abstract>	
4.29 < <abstract>&gt; TrafficCountsRequest Class Diagram</abstract>	. 267

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### **List of Tables**

4.1	< <enumeration>&gt;</enumeration>	GroupReroutingIndicator	173
		MCDMTopicField	
4.3	< <enumeration>&gt;</enumeration>	OtmvStatus	212
4.4	< <enumeration>&gt;</enumeration>	RegulationProposalAction	234
4.5	< <enumeration>&gt;</enumeration>	RegulationProposalState	236
4.6	< <enumeration>&gt;</enumeration>	RegulationState	237

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### References

### **NM**

- [1] NOP/B2B Reference Manuals CommonServices
- [2] NOP/B2B Reference Manuals AirspaceServices
- [3] NOP/B2B Reference Manuals FlightServices

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### **Terminology**

### **Main Abbreviations and Acronyms**

STAM (Short-Term ATFCM Measures)

An approach to smooth sector workloads by reducing traffic peaks through short-term application of minor ground delays, appropriate flight level capping and exiguous rerouting to a limited number of flights.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### **Chapter 1. Introduction**

#### 1.1. Identification

- (1) This document forms part of the set of the NM 23.0.0 NOP/B2B Reference Manuals, which all together form the NM 23.0.0 NOP/B2B Documentation.
- (2) Its reference is B2B/23.0.0/Flow.
- (3) Its title is NM 23.0.0 NOP/B2B Reference Manuals FlowServices.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### **Chapter 2. Context**

(1) The FlowServices service group is intended to provide services in the flow and capacity management domain.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### **Chapter 3. Port Types**

#### 3.1. TrafficCountsService Port Type

#### 3.1.1. Overview

#### 3.1.1.1. Introduction

- (1) This service is intended to provide querying of traffic counts. The requests currently available are:
  - a) <u>TrafficCountsByAircraftOperatorRequest</u> / <u>TrafficCountsByAircraftOperatorReply</u>
  - b) <u>TrafficCountsByAerodromeRequest</u> / <u>TrafficCountsByAerodromeReply</u>
  - c) <u>TrafficCountsByAerodromeSetRequest</u> / <u>TrafficCountsByAerodromeSetReply</u>
  - d) <u>TrafficCountsByAirspaceRequest</u> / <u>TrafficCountsByAirspaceReply</u>
  - e) <u>TrafficCountsByPointRequest</u> / <u>TrafficCountsByPointReply</u>
  - f) TrafficCountsByTrafficVolumeRequest / TrafficCountsByTrafficVolumeReply

#### 3.1.2. Traffic Count List by Aircraft Operator

#### 3.1.2.1. SOAP

(1) The associated SOAP operation is:

TrafficCountsByAircraftOperatorReply queryTrafficCountsByAircraftOperator(
TrafficCountsByAircraftOperatorRequest request
)

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### 3.1.2.2. TrafficCountsByAircraftOperatorRequest




Figure 3.1. TrafficCountsByAircraftOperatorRequest Class Diagram

- (1) Request to query the NM traffic counts for an aircraft operator.
- (2) Inherits from: TrafficCountsRequest
- (3) Attributes:
  - a) AircraftOperatorICAOId aircraftOperator (Mandatory)
    The Aircraft operator ICAO Id for which traffic counts are requested.
  - b) <u>CountsCalculationType</u> calculationType (Mandatory) Indicates what is the calculation type of the count (entry or occupancy).

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### 3.1.2.3. TrafficCountsByAircraftOperatorReply




Figure 3.2. TrafficCountsByAircraftOperatorReply Class Diagram

- (1) Reply returned in response to <u>TrafficCountsByAircraftOperatorRequest</u>.
- (2) See <u>TrafficCountsReplyData</u>.
- (3) <u>Inherits from:</u> Reply

#### 3.1.3. Traffic Count List by Aerodrome

#### 3.1.3.1. SOAP

(1) The associated SOAP operation is:

```
TrafficCountsByAerodromeReply queryTrafficCountsByAerodrome(
TrafficCountsByAerodromeRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### 3.1.3.2. TrafficCountsByAerodromeRequest




Figure 3.3. TrafficCountsByAerodromeRequest Class Diagram

- (1) Request to query the NM traffic ENTRY counts for an aerodrome.
- (2) <u>Inherits from: TrafficCountsRequest</u>
- (3) Attributes:
  - a) AerodromeICAOId aerodrome (Mandatory) ICAO id of the aerodrome.
  - b) <u>AerodromeRole</u> aerodromeRole (Mandatory)

Specifies whether the aerodrome is meant to be departure, arrival or both.

If aerodromeRole is set to AerodromeRole. DEPARTURE, the traffic window specifies that only those flights taking off in the time window are requested.

If aerodromeRole is set to AerodromeRole. ARRIVAL, the traffic window specifies that only those flights arriving in the time window are requested.

If aerodromeRole is set to AerodromeRole. BOTH, the traffic window specifies that only those flights taking off or arriving in the time window are requested.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manual FlowServices	B2B/23.0.0/Flow

c) boolean includeInvisibleFlights (Optional) Indicates whether invisible flights (VFR, OAT, STAY, IFPSTOP) shall be included in the traffic counts. Defaults to false.

#### 3.1.3.3. TrafficCountsByAerodromeReply




Figure 3.4. TrafficCountsByAerodromeReply Class Diagram

- (1) Reply returned in response to <u>TrafficCountsByAerodromeRequest</u>.
- (2) See <u>TrafficCountsReplyData</u>.
- (3) Inherits from: Reply

#### 3.1.4. Traffic Count List by Aerodrome Set

#### 3.1.4.1. SOAP

(1) The associated SOAP operation is:

```
TrafficCountsByAerodromeSetReply queryTrafficCountsByAerodromeSet(
TrafficCountsByAerodromeSetRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### 3.1.4.2. TrafficCountsByAerodromeSetRequest




Figure 3.5. TrafficCountsByAerodromeSetRequest Class Diagram

- (1) Request to query the NM traffic ENTRY counts for an aerodrome set.
- (2) <u>Inherits from: TrafficCountsRequest</u>
- (3) Attributes:
  - a) AerodromeSetId aerodromeSet (Mandatory) Id of the aerodrome set.
  - b) <u>AerodromeRole</u> aerodromeRole (Mandatory)

Specifies whether the aerodrome is meant to be departure, arrival or both.

If aerodromeRole is set to AerodromeRole. DEPARTURE, the traffic window specifies that only those flights taking off in the time window are requested.

If aerodromeRole is set to AerodromeRole. ARRIVAL, the traffic window specifies that only those flights arriving in the time window are requested.

If aerodromeRole is set to AerodromeRole. BOTH, the traffic window specifies that only those flights taking off or arriving in the time window are requested.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

c) boolean includeInvisibleFlights (Optional) Indicates whether invisible flights (VFR, OAT, STAY, IFPSTOP) shall be included in the traffic counts. Defaults to false.

#### 3.1.4.3. TrafficCountsByAerodromeSetReply




Figure 3.6. TrafficCountsByAerodromeSetReply Class Diagram

- (1) Reply returned in response to <u>TrafficCountsByAerodromeSetRequest</u>.
- (2) See <u>TrafficCountsReplyData</u>.
- (3) Inherits from: Reply

#### 3.1.5. Traffic Count List by Airspace

#### 3.1.5.1. SOAP

(1) The associated SOAP operation is:

```
TrafficCountsByAirspaceReply queryTrafficCountsByAirspace(
TrafficCountsByAirspaceRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### 3.1.5.2. TrafficCountsByAirspaceRequest




Figure 3.7. TrafficCountsByAirspaceRequest Class Diagram

- (1) Request to query the NM traffic counts for an airspace.
- (2) <u>Inherits from:</u> <u>TrafficCountsRequest</u>
- (3) Attributes:
  - a) AirspaceId airspace (Mandatory) Id of the airspace.
  - b) <u>CountsCalculationType</u> calculationType (Mandatory) Indicates what is the calculation type of the count (entry or occupancy).

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### 3.1.5.3. TrafficCountsByAirspaceReply




Figure 3.8. TrafficCountsByAirspaceReply Class Diagram

- (1) Reply returned in response to <u>TrafficCountsByAirspaceRequest</u>.
- (2) See <u>TrafficCountsReplyData</u>.
- (3) <u>Inherits from:</u> Reply

#### 3.1.6. Traffic Count List by Point

#### 3.1.6.1. SOAP

(1) The associated SOAP operation is:

```
TrafficCountsByPointReply queryTrafficCountsByPoint(
    TrafficCountsByPointRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### 3.1.6.2. TrafficCountsByPointRequest




Figure 3.9. TrafficCountsByPointRequest Class Diagram

- (1) Request to query the NM traffic ENTRY counts for a point.
- (2) <u>Inherits from:</u> <u>TrafficCountsRequest</u>
- (3) Attributes:
  - a) **PublishedPointId point** (Mandatory) Id of the published point.
  - b) **FlightLevelRange flightLevelRange** (Mandatory) The range in which the flight level should be over the point.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manual FlowServices	B2B/23.0.0/Flow

#### 3.1.6.3. TrafficCountsByPointReply




Figure 3.10. TrafficCountsByPointReply Class Diagram

- (1) Reply returned in response to <u>TrafficCountsByPointRequest</u>.
- (2) See <u>TrafficCountsReplyData</u>.
- (3) <u>Inherits from:</u> Reply

#### 3.1.7. Traffic Count List by Traffic Volume

#### 3.1.7.1. SOAP

(1) The associated SOAP operation is:

```
TrafficCountsByTrafficVolumeReply queryTrafficCountsByTrafficVolume(
TrafficCountsByTrafficVolumeRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### 3.1.7.2. TrafficCountsByTrafficVolumeRequest




Figure 3.11. TrafficCountsByTrafficVolumeRequest Class Diagram

- (1) Request to query the NM traffic counts for a traffic volume.
- (2) Inherits from: <u>TrafficCountsRequest</u>
- (3) Attributes:
  - a) <u>IrafficVolumeId</u> trafficVolume (Mandatory) Id of the traffic volume.
  - b) CountsCalculationType calculationType (Mandatory)
    Indicates what is the calculation type of the count (entry or occupancy).
    Note: Occupancy counts for traffic volumes are only supported for traffic volumes defined on an airspace.
    Constraint: See INCONSISTENT COUNTS TYPE AND COMPUTE OTMV ALERTS
  - c) **boolean computeOtmvAlerts** (Optional)
    Indicates if OTMV alerts need to be computed (e.g., is the flight in an OTMV peak and during what count periods; see <a href="OtmvAlert">OtmvAlert</a>) or not.
    Default is false.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

#### **Constraints:**

- i) See INCONSISTENT COUNTS TYPE AND COMPUTE OTMV ALERTS
- ii) See <a href="INCONSISTENT\_FLOW\_TYPE\_AND\_COMPUTE\_OTMV\_ALERTS">INCONSISTENT\_FLOW\_TYPE\_AND\_COMPUTE\_OTMV\_ALERTS</a>

#### d) FlowType computeFlowCounts (Optional)

Indicates if traffic counts need to be computed by linked or associated or scenario flows. By default (i.e., if computeFlowCounts is not specified), traffic counts are not computed by flow.

Note that computing scenario flow counts is subject the special authorization (as it is a heavy field to compute).

Constraint: See INCONSISTENT FLOW TYPE AND COMPUTE OTMV ALERTS

#### e) boolean includeInvisibleFlights (Optional)

Indicates whether invisible flights (VFR, OAT, STAY, IFPSTOP) shall be included in the traffic counts.

Defaults to false.

#### (4) Constraints:

a)	Name	INCONSISTENT_COUNTS_TYPE_AND_COMPUTE_OTMV_ALERTS
	Attributes	<pre>calculationType, computeOtmvAlerts</pre>
		If attribute computeOtmvAlerts is true then attribute calculationType must be OCCUPANCY and attribute countsInterval.step must be one minute (0001).

b)	Name	INCONSISTENT_FLOW_TYPE_AND_COMPUTE_OTMV_ALERTS
	Attributes	<pre>computeFlowCounts, computeOtmvAlerts</pre>
	•	If attribute computeFlowCounts is SCENARIOthen the attribute computeOt-mvAlerts must be false).

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

#### 3.1.7.3. TrafficCountsByTrafficVolumeReply




Figure 3.12. TrafficCountsByTrafficVolumeReply Class Diagram

- (1) Reply returned in response to TrafficCountsByTrafficVolumeRequest.
- (2) See TrafficCountsReplyData.
- (3) Inherits from: Reply

#### 3.2. MeasuresService Port Type

#### 3.2.1. Overview

#### 3.2.1.1. Introduction

- This service is intended to provide querying and update capabilities on ATFCM measures. The requests currently available are:
  - a) RegulationListRequest / RegulationListReply
  - b) RegulationCreationRequest / RegulationCreationReply
  - c) RegulationUpdateRequest / RegulationUpdateReply
  - d) RegulationCancelRequest / RegulationCancelReply
  - e) RegulationProposalListRequest / RegulationProposalListReply
  - f) RegulationProposalFilingRequest / RegulationProposalFilingReply

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- g) RegulationProposalUpdateRequest / RegulationProposalUpdateReply
- h) RegulationProposalRevocationRequest / RegulationProposalRevocationReply
- i) ReroutingListRequest / ReroutingListReply
- j) ReroutingCreationRequest / ReroutingCreationReply
- k) ReroutingUpdateRequest / ReroutingUpdateReply
- I) ReroutingCancelRequest / ReroutingCancelReply
- m) MCDMOnlyListRequest / MCDMOnlyListReply
- n) MCDMOnlyCreationReguest / MCDMOnlyCreationReply
- o) MCDMOnlyUpdateRequest / MCDMOnlyUpdateReply
- p) <u>MCDMOnlyCancelRequest</u> / <u>MCDMOnlyCancelReply</u>
- q) <u>MeasureOpLogRetrievalRequest</u> / <u>MeasureOpLogRetrievalReply</u>
- r) UpdateFlightsInMeasureRequest / UpdateFlightsInMeasureReply
- s) ATFCMSituationReguest / ATFCMSituationReply
- t) <u>NetworkImpactAssessmentRetrievalRequest / NetworkImpactAssessmentRetrievalReply</u>

#### 3.2.1.2. Update Pattern

- (1) The pattern used for all measure updates is the update of one measure at the time. There can only exist 1 contiguous measure with the same id per day.
- When updating a measure, the B2B client can send a delta containing only those fields that need to be updated. Alternatively the B2B client can send the full object with all relevant data fields.
- When the user wants to update an existing (normal) measure via a proposal, then the user needs to send the full object with all relevant data fields. On the other hand, when the B2B client wants to update a proposal measure (before NM has started reviewing), then he can send a delta containing only those fields that need to be updated.
- (4) Any of the measures and proposal measures may be updated via B2C and/or B2B and/or by NMOC, and by different operators. When an operator updates a measure via B2C, the next B2B retrieve operation will include these changes done via B2C. The pattern used on the backend side to deal with concurrent updates is the following:
  - a) Each measure is returned with a data id that expresses a data version number (equivalent to a timestamp).
  - b) Before updating a measure (via a proposal or directly), the updater must first get the measure and subsequently pass the associated data id when updating it. IMPORTANT:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices		B2B/23.0.0/Flow

note that this data id is also related to the dataset in use, i.e. a data id obtained from a dataset cannot be used with another dataset: doing so would result in an error.

- c) A concurrent update is defined as an update that took place earlier (i.e. before the update that the updater wants to execute now) but after the timestamp associated to the data id passed within the update to execute now. For example:
  - A B2B client shows in a local screen a regulation corresponding to datald I1.
  - ii) A NM client in a parallel modifies the same regulation (for the same measure id) via B2B or B2C -> latest version in NM systems : datald I2.
  - iii) The B2B client end-user modifies some values of the regulation and tries to commit them as a proposal to modify the regulation (includes sending to NM; changes wrt I1).
  - iv) As the B2B client end-user started from datald I1 but the measure was also conflictingly modified in parallel CONFLICTING\_UPDATE ReplyStatus is returned.
- d) From the concurrency perspective, a measure update or proposal to modify a measure is successful if:
  - i) There was no concurrent update, or
  - There were identical concurrent updates.
- e) IMPORTANT: NM insists that the B2B client only does a measure update in case something has changed for that measure.
- The data id is an opaque identifier of the version of the global state of the backend system related to CACD or tactical updatable related data (not pure flight data: so including capacity updates, measures,). Whenever dataId is passed in an update request, the system verifies if there have been conflicting updates between what the B2B client tried to update (wrt the state of the system linked to the dataid) and the latest state. Note that the datald represent the global state of the backend system (not linked to specific locations). It changes continuously (between subsequent retrieve requests). However the fact that it changes continuously does not impact the B2B client, as it is only used to detect if there have been conflicting parallel updates between the latest state and what the B2B client changed in the update request.
- Unlike with capacity plan updates (See Tactical updates : Update Pattern) there is only 1 valid pattern to use the dataId:
  - a) B2C/NMOC (via phone coordination) can update the concerned measures. The dataId (in combination with the CONFLICTING\_UPDATE error reply) must be used to detect conflicting parallel updates and report those to the end user so that he can decide what to do.
  - b) So the detailed steps for a regulation update (via proposal) would be :
    - i) On the create of a regulation R (via proposal regulation),

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- ii) B2B.fileRegulationProposal is used without datald. The reply contains a datald PR1
- iii) Each next update for proposal R or to the MCDM state of R, would use the dataId returned by the previous update (PR1,PR2,...). Alternatively when updating a proposal R, the B2B client uses as dataId, the dataId from the regulation object as it was retrieved for showing to the client. In that case the dataId corresponds to the regulation version from which the client started to make changes.
- iv) If the NM systems detect a conflicting parallel update between the time corresponding to the datald PR1/PR2.. and the latest NM state wrt proposal regulation PR or MCDM of PR, the reply contains a CONFLICTING\_UPDATE error. In that case the client system must warn the operator that a conflicting parallel update has occurred and would show the local data and the NM data to allow the operator to choose (and optionally update any local system as well). When the B2b client, wants to create a proposal to update/cancel the normal regulation R, then B2B.fileRegulationProposal is used with normalRegulationDataId = NR2 and no datald. The reply contains proposal regulation datald PR5. Alternatively the NM systems detect a conflicting parallel update between the time corresponding to the datald NR2 and the latest NM state wrt normal regulation R or MCDM of R. In that case the reply contains a CONFLICTING\_UPDATE error. In that case the client system must warn the operator that a conflicting parallel update has occurred and would show the local data and the NM data to allow the operator to choose (and optionally update any local system as well).
- (7) If measure S is updated, then data Id of measure S (S1) needs to be used.
- (8) Note that this pattern is also used by a.o. NM systems:
  - a) When an normal regulation needs to be updated (proposal for modification), first the NM data is shown and in the screen data the associated datald NR1 is kept. (the user has seen the NM data corresponding to datald NR1).
    When the user applies his changes, this data Id NR1 is then used in the RegulationProposalFilingRequest. In case there were parallel conflicting updates, the user is notified and he needs to redo his update (including first looking at the latest NM data). The main reason behind: multiple operators at different terminals (including NMOC) can do conflicting updates and they need to be notified.
  - b) When a proposal regulation needs to be updated, first the NM proposal data is shown and in the screen data the associated datald PR1 is kept. (the user has seen the NM proposal data corresponding to datald PR1).

    When the user applies his changes, this data Id PR1 is then used in the RegulationProposalRevocationRequest, RegulationProposalUpdateRequest or MCDMStateUpdateRequest. In case there were parallel conflicting updates, the user is notified and he needs to redo his update (including first looking at the latest NM data).

#### 3.2.1.3. Transaction and Errors

(1) See Transactions and Errors.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

# 3.2.1.4. Allowed Times for Retrievals and Updates

### 3.2.1.4.1. Forecast and Operational Datasets

(1) See <u>Forecast and Operational Datasets</u>.

#### 3.2.1.4.2. Past

- Unlike with the tactical updates (See tactical updates : Past) , measure updates can modify the past:
- (2) A typical scenario is: a runway got broken and since X minutes no flights were allowed to takeoff. In such a case a regulation can be created that starts e.g. 30 minutes in the past and that
  gives the impacted flights a new CTOT in the future. In NM systems there is the slot change
  control that allows to control which flights must be changed and which flights cannot be changed
  or impacted when modifying regulations. By default only flights which have an EOBT of Y minutes
  or more in the future can be changed (See ATFCM reference manual). If the B2B client needs to
  change more/less flights, then this needs to be coordinated via phone with NMOC.
- (3) So when the B2B client updates a regulation or submits a proposal to update a regulation that has already started and it is not the purpose to change the past, then the B2B client should not modify the past (a.o. archiving reasons). So the B2B clients should not change the start of the regulation but rather split the "current" period inside the initialConstraints in two parts: one for that past (unchanged) and one for the future part (somewhat similar to the remote updates that can not change the past but only change the future: (See tactical updates: Past)).

### 3.2.1.5. Simulations

(1) See <u>Simulations</u>.

### 3.2.1.6. Overload protection

- (1) There are some technical limitations to the amount of outstanding proposals that can exist at the same time from a given FMP and the amount of proposals that may be sent in a day. The objective of these limits is to protect the NM systems from excessive or faulty demand (e.g. communication errors that triggers a loop of proposals being sent).
  - a) Classic Regulation Proposals:
    - i) A maximum of 15 outstanding (not accepted, nor rejected) ATFM regulation proposals can exist at a time per FMP.
  - b) Cherry picked Regulation Proposals:
    - i) A maximum of 1 CP regulation proposal in MCMState PROPOSED can exist at a time per FMP.
    - ii) A maximum of 5 CP regulation proposals can be sent per day and per FMP.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- iii) A maximum of 50 CP regulation proposals with regulationState="APPLIED" can exist at the same time (for all users combined).
- Note that if the required number exceeds the figures above the request shall be coordinated via telephone.

# 3.2.2. Regulation List

### 3.2.2.1. SOAP

(1) The associated SOAP operation is:

```
RegulationListReply queryRegulations(
RegulationListRequest request
)
```

### 3.2.2.2. RegulationListReguest




Figure 3.13. RegulationListRequest Class Diagram

- (1) Request to query regulation.
- (2) The reply will only contain "real" regulations (not any proposal regulations).
- (3) <u>Inherits from:</u> RegulationOrMCDMOnlyListRequest
- (4) Attributes:
  - a) Set<<u>RegulationField</u>> requestedRegulationFields (Mandatory)

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

The reply returns only the requested regulation fields in this set, and only if the values of these requested fields are available at NM. Note that the regulation id is always returned. Constraint: Size must be comprised between 0 and 24.

# b) Set<RegulationState> regulationStates (Optional)

Selects the regulations with a state that matches an entry in this set. By default, regulations are selected regardless to their state. Constraint: Size must be comprised between 1 and 5.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.2.3. RegulationListReply




Figure 3.14. RegulationListReply Class Diagram

- (1) Reply returned in response to <u>RegulationListRequest</u>.
- (2) See <u>RegulationOrMCDMOnlyListReplyData</u>.
- (3) Inherits from: Reply

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices		B2B/23.0.0/Flow

# (4) <u>Attributes:</u>

a) Set<<u>Regulation</u>> regulations (Mandatory)
Set of regulations that matched the <u>RegulationListRequest</u> criteria.

Can be empty (meaning that no regulation matched the criteria).

Constraint: Size must be comprised between 0 and 10000.

# 3.2.3. Regulation Creation

# 3.2.3.1. SOAP

(1) The associated SOAP operation is:

RegulationCreationReply createRegulation(
RegulationCreationRequest request
)

DNM		EUROCONTROL	
Document Title:		Document Reference:	
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow	

# 3.2.3.2. RegulationCreationRequest




Figure 3.15. RegulationCreationRequest Class Diagram

(1) Request to create a regulation.

# (2) Note 1

The RegulationCreationRequest is trial related: it is only accessible (authorized) during specific trials or on specific test platforms or in simulations. In STAM trials context only the creation of cherry picked regulations are authorized.

# (3) Note 2

The creation of the regulation is synchronous but the activation is asynchronous. So before flights can be added, the regulation needs to have been activated in the system. A typical client will poll until the regulationState has become active, before forcing flights or requesting flightlists onMeasure. In simulation context the creation of the regulation is completely synchronous.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

(4) <u>Inherits from:</u> Request

# (5) <u>Attributes:</u>

a) Dataset dataset (Mandatory)
Dataset on which the regulation needs to be created.

b) **Regulation** regulation (Mandatory)

The filed regulation.

Constraint: See INVALID MEASURE APPLICABILITY PERIOD

c) **boolean computeNetworkImpactAssessment** (Optional)
In simulation dataset, indicates if the network impact assesment needs to be computed (See NetworkImpactAssessmentRetrievalRequest)

# (6) Constraint:

a)	Name	INVALID_MEASURE_APPLICABILITY_PERIOD
	Attribute	regulation
	_	Invalid regulation(measure) applicability period should overlap Dataset period

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.3.3. RegulationCreationReply




Figure 3.16. RegulationCreationReply Class Diagram

- (1) Reply returned in response to <u>RegulationCreationRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Regulation regulation (Mandatory)
    The regulation with fields set by the NM system.

# 3.2.4. Regulation Update

# 3.2.4.1. SOAP

(1) The associated SOAP operation is:

```
RegulationUpdateReply updateRegulation(
RegulationUpdateRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.4.2. RegulationUpdateRequest




Figure 3.17. RegulationUpdateRequest Class Diagram

(1) Request to update (modify) an existing regulation. As a result the regulation will be modified and all concerned flights will be updated accordingly.

# (2) Note 1

The RegulationUpdateRequest is trial related: it is only accessible (authorized) during specific trials or on specific test platforms and only for externally editable regulations. In STAM trials context only the update of externally editable cherry picked regulations are authorized. In simulation context all regulations are considered externally editable.

# (3) Note 2

The activation of the updated regulation is asynchronous (See regulationCreationRequest).

(4) <u>Inherits from:</u> Request

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# (5) <u>Attributes:</u>

a) **Dataset dataset** (Mandatory)

Dataset on which the regulation needs to be updated.

b) **Regulation** regulation (Mandatory)

The regulation fields to be updated.

Note that only those fields that need to be updated, need to be non null. The other fields simply remain unchanged.

Constraint: See INVALID\_MEASURE\_APPLICABILITY\_PERIOD

c) boolean computeNetworkImpactAssessment (Optional)

In simulation dataset, indicates if the network impact assesment needs to be computed (See <a href="NetworkImpactAssessmentRetrievalRequest">NetworkImpactAssessmentRetrievalRequest</a>)

### (6) Constraint:

a)	Name	INVALID_MEASURE_APPLICABILITY_PERIOD
	Attribute	<u>regulation</u>
	Description	Invalid regulation(measure) applicability period should overlap Dataset period

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.4.3. RegulationUpdateReply




Figure 3.18. RegulationUpdateReply Class Diagram

- (1) Reply returned in response to <u>RegulationUpdateRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Regulation regulation (Mandatory)
    The updated regulation with all fields set by the NM system.

# 3.2.5. Regulation Cancellation

### 3.2.5.1. SOAP

(1) The associated SOAP operation is:

```
RegulationCancelReply cancelRegulation(
RegulationCancelRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.5.2. RegulationCancelRequest




Figure 3.19. RegulationCancelReguest Class Diagram

- (1) Request to cancel a regulation. As a result the regulation will be cancelled and all concerned flights will be updated and de-regulated if no other regulations impact the flight.
- Note that the RegulationCancelRequest is trial related: it is only accessible (authorized) during specific trials or on specific test platforms and only for externally editable regulations. In STAM trials context only the cancel of externally editable cherry picked regulations are authorized. In simulation context all regulations are considered externally editable.
- (3) <u>Inherits from:</u> Request
- (4) Attributes:
  - a) Dataset dataset (Mandatory)
    Dataset on which the regulation has to be cancelled.
  - b) RegulationId regulationId (Mandatory)
    The identifier of the regulation to be cancelled.
  - c) <u>DateYearMonthDay</u> dayOfOperation (Mandatory) Day for which the regulation has to be cancelled.
  - d) PlanDataId dataId (Mandatory)
    Opaque identifier representing the version of the regulation to revoke. The caller shall always keep this value unchanged.
  - e) **boolean computeNetworkImpactAssessment** (Optional)
    In simulation dataset, indicates if the network impact assesment needs to be computed (See NetworkImpactAssessmentRetrievalRequest)

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.5.3. RegulationCancelReply




Figure 3.20. RegulationCancelReply Class Diagram

- (1) Reply returned in response to <u>RegulationCancelRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Regulation regulation (Mandatory)
    The regulation that has been cancelled.

# 3.2.6. Regulation Proposal List

# 3.2.6.1. SOAP

(1) The associated SOAP operation is:

```
RegulationProposalListReply queryRegulationProposals(
RegulationProposalListRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.6.2. RegulationProposalListRequest




Figure 3.21. RegulationProposalListRequest Class Diagram

- (1) Request to query regulation proposals.
- (2) Regulation proposals are proposals to NM for creation/modification/cancellation of a regulation.
- (3) Regulation proposals do not impact any flights directly.
- (4) There are 2 types of regulation proposals: Those that support proposal flights and those that do not.
- (5) Regulation proposals without proposal flights are basically filled in template for NM to accept/reject.
- (6) Regulation proposals with proposal flights are cherry picked regulations (with initially no flights forced). When the users delays some flights, the real flight do not get delayed. Instead proposal flights are created that are reflected in the (with includeProposalFlights) flightlist and counts.
- (7) NM can accept or reject a regulation proposal. If a proposal is rejected (<a href="MCDMApprovalState">MCDMState</a> ABANDONED), the user can refile a new proposal. When NM accepts a regulation creation proposal (optionally modifying some attributes:a.o. regulationld), then a real regulation is created (retrievable via the RegulationListRequest) and the regulation proposal has its <a href="MCDMApprovalState">MCDMApprovalState</a> set to ACCEPTED and <a href="MCDMState">MCDMState</a> set to IMPLEMENTED). When NM accepts a regulation modification/cancellation proposal (optionally modifying some attributes), then the real regulation is modified/cancelled.
- (8) Note that the RegulationProposalListRequest is subject to authorization.
- (9) <u>Inherits from:</u> <u>RegulationOrMCDMOnlyListRequest</u>
- (10) Attributes:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# a) Set<<u>RegulationProposalField</u>> requestedRegulationProposalFields (Mandatory)

The reply returns only the requested regulation proposal fields in this set, and only if the values of these requested fields are available at NM. Note that the regulation proposal id is always returned.

Constraint: Size must be comprised between 0 and 27.

# b) Set<<u>MCDMApprovalState</u>> approvalStates (Optional)

Selects the regulation proposals with a NMOC approval state that matches an entry in this set.

By default, regulation proposals are selected regardless to their state.

Constraint: Size must be comprised between 1 and 4.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.6.3. RegulationProposalListReply




Figure 3.22. RegulationProposalListReply Class Diagram

- (1) Reply returned in response to <u>RegulationProposalListRequest</u>.
- (2) See <u>RegulationOrMCDMOnlyListReplyData</u>.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

(3) <u>Inherits from:</u> Reply

# (4) Attributes:

a) Set<RegulationProposal> proposals (Mandatory)
Set of regulation proposals that matched the RegulationProposalListRequest criteria.
Can be empty (meaning that no regulation proposal matched the criteria).
Constraint: Size must be comprised between 0 and 10000.

# 3.2.7. Regulation Proposal Filing

# 3.2.7.1. SOAP

(1) The associated SOAP operation is:

RegulationProposalFilingReply fileRegulationProposal(
RegulationProposalFilingRequest request
)

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manual FlowServices	B2B/23.0.0/Flow

# 3.2.7.2. RegulationProposalFilingRequest




Figure 3.23. RegulationProposalFilingRequest Class Diagram

- (1) Request to file a proposal to create a regulation or to file a proposal to update a regulation (non-proposal regulation from a RegulationListRequest) or to file a proposal to cancel a regulation (non-proposal regulation from a RegulationListRequest)
- (2) When NMOC accepts the proposal, the end result corresponds to a:
- (3) a) RegulationCreationRequest: when ACTION=CREATION. So concerned flights get a CTOT or a CTOT update (in case they already had a CTOT).
  - b) RegulationUpdateRequest: when ACTION=UPDATE. So concerned flights get a CTOT (in case the regulation period has been enlarged) or a CTOT update.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

- c) RegulationCancelRequest: when ACTION=CANCELLATION. So all concerned flights will be updated and de-regulated: no more CTOT (if there are no other regulations impacting the flight)
- (4) See also RegulationProposalListRequest

# (5) **Note 1**

The RegulationProposalFilingRequest is subject to authorization.

# (6) Note 2

The creation of the cherry picked regulations is synchronous but the activation is asynchronous. So before flights can be added, the regulation needs to have been activated in the system. A typical client will poll until the regulationState has become active, before adding flights or requesting flightlists on Measure.

# (7) Note 3

If there is already a proposal regulation that has not been accepted, nor rejected by NMOC, then RegulationProposalFilingRequest is not to be used. Instead RegulationProposalUpdateRequest or RegulationProposalRevocationRequest should be used.

# (8) Note 4

There are limitation on the number of proposal regulations that can be requested per day: See Overload protections.

# (9) **Note 5**

Once a proposal regulation has been accepted by NMOC, it becomes visible in the RegulationListReply. Before it is only visible in the ProposalListRequest. When a proposal is filed to update a regulation, then this regulation remains unchanged and visible in the RegulationListRequest. The proposal itself becomes visible via the ProposalListRequest (or the previously accepted or rejected proposal is replaced with the new proposal for the ProposalListRequest).

# (10) Note 6

- a) ACTION=CREATION is only allowed if no (non-proposal) regulation exists yet (via regulationListReply) with that regulationId.
- b) ACTION=UPDATE is only allowed if a (non-proposal) regulation already exists (via regulationListReply) with that regulationId.
- c) ACTION=UPDATE is not supported for CherryPick regulations via B2B (via B2B only adding/removing flights is allowed for accepted CherryPick regulations). Modyfing accepted cherry pick regulation data (e.g. remark) needs to be coordinated via phone.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

d) ACTION=CANCELLATION is supported for CherryPicked regulations but only as a RegulationProposalWithoutProposalFlights (meaning there is no possibility to see the what-if proposal flights before submitting to NM for approval)

# (11) Note 7

When creating a proposal regulation, the reason hotspot can be passed inside the RegulationProposal to indicate the original hotspot that will be solved via the proposal regulation. This does not imply that this hotspot needs to exist in NM systems as a hotspot object, nor that the hotspot will be created automatically by NM systems, nor that the B2B client should first create the hotspot nor that the B2B client needs to keep the hotspot field updated at all times. The hotspot field is only for informational awareness and can guide different actors in their decision process.

(12) Inherits from: Request

### (13) Attributes:

a) **Dataset dataset** (Mandatory)

Dataset on which the regulation proposal is filed.

See Forecast and Operational Datasets.

b) RegulationProposal proposal (Mandatory)

The regulation proposal to be filled.

Note that only those fields that need to be updated, need to be non null. The other fields simply remain unchanged.

Constraints:

- i) See INVALID ACTION
- ii) See INVALID MEASURE APPLICABILITY PERIOD
- c) PlanDataId normalRegulationDataId (Optional)

In case it concerns a proposal to update/cancel an existing regulation, then normalRegulationDataId must contain the dataId of that regulation (i.e. the dataId returned in the RegulationListRequest for the regulation with the same proposal.regulationId. See Update Pattern.

<u>Constraint:</u> See <u>INVALID\_NORMAL\_REGULATION\_DATA\_ID\_VALUE</u>

### (14) Constraints:

a)	Name	INVALID_ACTION
	Attribute	proposal
	•	The value for <u>proposal.action</u> should be set to <u>CREATION</u> when <u>propos-</u>
		al.kind is RegulationProposalWithProposalFlights.

b)	Name	INVALID_NORMAL_REGULATION_DATA_ID_VALUE
----	------	---

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices		B2B/23.0.0/Flow

Attribute	<u>normalRegulationDataId</u>	
Description	From regulationProposal.action value the normalRegulationDataId field can take different values as follows:	
	i) if the regulation proposal action is set as CREATION then the normalReg- ulationDataId must be null	
	ii) if the regulation proposal action is set as UPDATE then the normalRegulationDataId cannot be null	
	iii) if the regulation proposal action is set as CANCELLATION then the normalRegulationDataId cannot be null	

c)	Name	INVALID_MEASURE_APPLICABILITY_PERIOD	
Attribute proposal		proposal	
	Description	Invalid proposal (measure) applicability period should overlap Dataset period	

# 3.2.7.3. RegulationProposalFilingReply




Figure 3.24. RegulationProposalFilingReply Class Diagram

(1) Reply returned in response to <u>RegulationProposalFilingRequest</u>.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- (2) Special error conditions:
- (3) a) INVALID\_DATASET [Temporary error] If the FORECAST update was rejected due to D-1 forecast update cut-off or if the OPERATIONAL update was rejected due to D-1 plan not transferred yet.
  - b) CONFLICTING\_UPDATE [Permanent error] If the update failed due to incompatible concurrent changes.
  - c) OBJECT\_NOT\_FOUND [Permanent error] If the Traffic Volume is not known.
  - d) Note that there are also the INVALID\_INPUT replyStatus errors, that cover the errors detected by the backend (See Transaction and Errors). For example: action=CREATE for a regulation proposal when there is already a normal (non-proposal) regulation with that regulationId.
- (4) Inherits from: Reply
- (5) Attributes:
  - a) RegulationProposal proposal (Mandatory)

The regulation proposal with fields set by the NM system.

For RegulationProposalWithoutProposalFlights, the resulting MCDM state will be set to PROPOSED.

For RegulationProposalWithProposalFlights, the resulting MCDM state will be set to DRAFT.

### 3.2.8. Updating a filed Regulation Proposal

### 3.2.8.1. SOAP

(1) The associated SOAP operation is:

RegulationProposalUpdateReply updateRegulationProposal(
RegulationProposalUpdateRequest request
)

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.8.2. RegulationProposalUpdateRequest




Figure 3.25. RegulationProposalUpdateRequest Class Diagram

- (1) Request to update a filed regulation proposal before it has been accepted, nor rejected by NMOC.
- The B2B client has filed a regulation proposal but he changed his mind (or the solution was not sufficient enough after evaluating the proposal counts and flightlists) and the B2B client wants to make some changes before NMOC starts reviewing the proposal regulation.
- (3) Note 1

The RegulationProposalUpdateRequest is subject to authorization.

# (4) Note 2

The creation of the cherry picked regulations is synchronous but the activation is asynchronous. So before flights can be added, the regulation needs to have been activated in

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

the system. A typical client will poll until the regulationState has become active after a RegulationProposalUpdateRequest, before adding flights or requesting flightlists on Measure.

# (5) **Note 3**

If there is no proposal regulation or the proposal regulation has already been acknowledged, accepted or rejected by NMOC, then RegulaRegulationProposalUpdateRequest is not to be used (so it is only allowed if MCDMState is DRAFT or PROPOSED). Instead RegulationProposalFilingRequest should be used. For RegulationProposal-WithProposalFlights, RegulationProposalUpdateRequest is only allowed if the regulationState = APPLIED.

# (6) Note 4

In RegulationProposalUpdateRequest, RegulationProposalKind is immutable (w.r.t. RegulationProposalKind from the RegulationProposalFilingRequest).

- (7) <u>Inherits from:</u> Request
- (8) Attributes:
  - a) Dataset dataset (Mandatory)

Dataset on which the regulation proposal is updated.

See Forecast and Operational Datasets.

b) RegulationProposal proposal (Mandatory)

The regulation proposal fields to be updated.

Constraints:

- i) See <a href="INVALID\_ACTION">INVALID\_ACTION</a>
- ii) See INVALID MEASURE APPLICABILITY PERIOD
- (9) Constraints:

a)	Name	INVALID_ACTION
	Attribute	proposal
	Description	The value for <u>proposal.action</u> should be set to <u>CREATION</u> when <u>propos-</u>
		al.kind is RegulationProposalWithProposalFlights.

b)	Name	INVALID_MEASURE_APPLICABILITY_PERIOD
	Attribute proposal	
	Description	Invalid proposal (measure) applicability period should overlap Dataset period

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.8.3. RegulationProposalUpdateReply




Figure 3.26. RegulationProposalUpdateReply Class Diagram

- (1) Reply returned in response to RegulationProposalUpdateRequest.
- (2) Special error conditions:
- (3) a) INVALID\_DATASET [Temporary error] If the FORECAST update was rejected due to D-1 forecast update cut-off or if the OPERATIONAL update was rejected due to D-1 plan not transferred yet.
  - b) CONFLICTING\_UPDATE [Permanent error] If the update failed due to incompatible concurrent changes.
  - c) OBJECT\_NOT\_FOUND [Permanent error] If the Traffic Volume is not known.
  - d) Note that there are also the INVALID\_INPUT replyStatus errors, that cover the errors detected by the backend (See Transaction and Errors). For example: trying to change the regulation from cherry picked to non cherry picked or the other way around.
- (4) Inherits from: Reply
- (5) Attributes:
  - a) RegulationProposal proposal (Mandatory)

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

The updated regulation proposal.

For RegulationProposalWithoutProposalFlights, the resulting MCDM state will be set to proposed.

For RegulationProposalWithProposalFlights, the resulting MCDM state will be set to draft.

# 3.2.9. Regulation Proposal Revocation

### 3.2.9.1. SOAP

(1) The associated SOAP operation is:

```
RegulationProposalRevocationReply revokeRegulationProposal(
RegulationProposalRevocationRequest request
)
```

### 3.2.9.2. RegulationProposalRevocationRequest




Figure 3.27. RegulationProposalRevocationRequest Class Diagram

- (1) Request to revoke a regulation proposal.
- (2) The B2B client has filed a regulation proposal but he changed his mind and wants to undo: remove the proposal.
- (3) For example: if the B2B client has filed a regulation proposal and it has been accepted by NMOC, and afterwards the B2B client adds or changes some flights, then a revoke will simply remove this new proposal but leaves the already accepted regulation and flights unchanged. Note that RegulationProposalFilingRequest with ACTION=CANCELLATION is a proposal to cancel a regulation. So when the cancellation is accepted it will update and de-regulate the already accepted flights.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# (4) Note 1

The RegulationProposalRevocationRequest is subject to authorization.

# (5) Note 2

Revoking a never applied cherry pick regulation, results in cancelling the proposal regulation (so the regulationId can no longer be re-used in other proposal regulations). The cancellation of a cherry picked regulation is is asynchronous. So it can take some times (typically a few seconds) before all flights are de-regulated and the regulation state becomes cancelled.

# (6) Note 3

If there is no proposal regulation or the proposal regulation has already been acknowledged, accepted or rejected by NMOC, then RegulaRegulationProposalRevocationRequest is not to be used (so it is only allowed if MCDMState is DRAFT or PROPOSED). Instead RegulationProposalFilingRequest should be used. For RegulationProposalWithProposalFlights, RegulationProposalRevocationRequest is only allowed if the regulationState = APPLIED.

# (7) <u>Inherits from:</u> Request

### (8) <u>Attributes:</u>

### a) **Dataset dataset** (Mandatory)

Dataset on which the regulation proposal has to be revoked.

See Forecast and Operational Datasets.

### b) RegulationId regulationId (Mandatory)

The id of the regulation for which this proposal is to be revoked.

### c) DateYearMonthDay dayOfOperation (Mandatory)

Day for which the proposal is to be revoked.

Constraint: See INVALID\_DAY\_OF\_OPERATION

### d) PlanDataId dataId (Mandatory)

Opaque identifier representing the version of the regulation proposal to revoke. The caller shall always keep this value unchanged.

See Update Pattern.

### e) string remark (Optional)

Updated remark field of the proposal. The client can indicate the reason for the revocation to NM.

### (9) Constraint:

a)	Name	INVALID_DAY_OF_OPERATION
	Attribute	dayOfOperation

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices		B2B/23.0.0/Flow

Description Invalid day0f0peration should be within Dataset period -1 day(yesterday including)

# 3.2.9.3. RegulationProposalRevocationReply




Figure 3.28. RegulationProposalRevocationReply Class Diagram

- (1) Reply returned in response to <u>RegulationProposalRevocationRequest</u>.
- (2) Special error conditions:
- (3) a) INVALID\_DATASET [Temporary error] If the FORECAST update was rejected due to D-1 forecast update cut-off or if the OPERATIONAL update was rejected due to D-1 plan not transferred yet.
  - b) CONFLICTING\_UPDATE [Permanent error] If the update failed due to incompatible concurrent changes.
  - c) OBJECT\_NOT\_FOUND [Permanent error] If the proposal regulation is not known.
  - d) Note that there are also the INVALID\_INPUT replyStatus errors, that cover the errors detected by the backend (See Transaction and Errors). For example: trying to revoke a proposal regulation that has already been acknowledged (MCDMState = COORDINATED).

(4) Inherits from: Reply

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

# (5) <u>Attributes:</u>

a) RegulationProposal proposal (Mandatory)
 The regulation proposal that has been revoked.
 The resulting MCDM state will be set to ABANDONED.

# 3.2.10. Rerouting List

### 3.2.10.1. SOAP

(1) The associated SOAP operation is:

```
ReroutingListReply queryReroutings(
ReroutingListRequest request
)
```

# 3.2.10.2. ReroutingListRequest




Figure 3.29. ReroutingListRequest Class Diagram

- (1) Request to query reroutings.
- (2) Reroutings are measures to level cap or reroute flights to avoid an airspace/point or to find shorter/cheaper routes. Typically they are used for ATFCM reasons (for example to avoid a zero rate regulation) or for STAM or for Flight Efficiency or to handle forecast expected flows (for example NAT traffic).
- (3) Rerouting can either create a proposal flight (containing a proposed route) or they can modify the FTFM/RTFM point profile directly (used in forecast and simulations) or they can generate proposed routes in operational log messages.
- (4) <u>Inherits from: MeasureListRequest</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# (5) <u>Attributes:</u>

a) Set<<u>ReroutingIdWildcard</u>> reroutings (Optional)

The set of rerouting ids or wildcards if specified, the reply returns only the requested reroutings. The logical OR operator is meant between the items in the set. Constraint: Size must be comprised between 1 and 100.

b) **Set<ReroutingField>** requestedReroutingFields (Mandatory)

The reply returns only the requested rerouting fields in this set, and only if the values of these requested fields are available at NM. Note that the rerouting id is always returned.

Constraint: Size must be comprised between 0 and 18.

c) Set<ReroutingMeasureState> reroutingStates (Optional)
Selects the reroutings with a state that matches an entry in this set.
By default, reroutings are selected regardless to their state.
Constraint: Size must be comprised between 1 and 4.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.10.3. ReroutingListReply




Figure 3.30. ReroutingListReply Class Diagram

- (1) Reply returned in response to <u>ReroutingListRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Set<Rerouting> reroutings (Mandatory)
     Set of reroutings that matched the ReroutingListRequest criteria.
     Can be empty (meaning that no rerouting matched the criteria).

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Constraint: Size must be comprised between 0 and 10000.

# 3.2.11. Rerouting Creation

### 3.2.11.1. SOAP

(1) The associated SOAP operation is:

```
ReroutingCreationReply createRerouting(
ReroutingCreationRequest request
)
```

# 3.2.11.2. ReroutingCreationRequest




Figure 3.31. Rerouting Creation Request Class Diagram

(1) Request to create a rerouting.

# (2) Note 1

The ReroutingCreationRequest is trial related: it is only accessible (authorized) during specific trials or on specific test platforms.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# (3) Note 2

The creation of the rerouting is asynchronous. So if the service returns, the request is validated but the processing is not finished yet: in general it takes about 1-2 minutes to create and activate the rerouting. Before flights can be added, the rerouting needs to have been created and activated in the system. A typical client will poll until the rerouting-State has become active, before adding flights. Note that in simulation context, the creation of the rerouting is synchronous.

(4) <u>Inherits from:</u> Request

### (5) Attributes:

a) Dataset dataset (Mandatory)
 Dataset on which the rerouting needs to be created.

b) Rerouting rerouting (Mandatory)
The rerouting that is going to be created.
Constraint: See INVALID MEASURE APPLICABILITY PERIOD

c) boolean computeNetworkImpactAssessment (Optional) In simulation dataset, indicates if the networkImpactAssessment needs to be computed (See NetworkImpactAssessmentRetrievalRequest)

# (6) Constraint:

a)	Name	INVALID_MEASURE_APPLICABILITY_PERIOD
	Attribute	rerouting
	-	Invalid rerouting(measure) applicability period should overlap Dataset period

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.11.3. ReroutingCreationReply




Figure 3.32. ReroutingCreationReply Class Diagram

- (1) Reply returned in response to <u>ReroutingCreationRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Rerouting rerouting (Mandatory)
    The rerouting with fields set by the NM system.

# 3.2.12. Rerouting Update

# 3.2.12.1. SOAP

(1) The associated SOAP operation is:

```
ReroutingUpdateReply updateRerouting(
ReroutingUpdateRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.12.2. ReroutingUpdateRequest




Figure 3.33. ReroutingUpdateRequest Class Diagram

(1) Request to update (modify) an existing rerouting.

### (2) Note 1

The ReroutingUpdateRequest is trial related: it is only accessible (authorized) during specific trials or on specific test platforms and only for externally editable reroutings.

### (3) Note 2

The update of a rerouting is asynchronous. (See rerouting creation request). A typical client will poll until the reroutingState has become active and the dataId of the existing rerouting has changed, before adding flights (except when in simulation context).

- (4) <u>Inherits from:</u> Request
- (5) Attributes:
  - a) Dataset dataset (Mandatory)
     Dataset on which the rerouting needs to be updated.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

## b) Rerouting rerouting (Mandatory)

The rerouting fields to be updated.

Note that only those fields that need to be updated, need to be non null. The other fields simply remain unchanged.

Constraint: See INVALID MEASURE APPLICABILITY PERIOD

## c) boolean computeNetworkImpactAssessment (Optional)

In simulation dataset, indicates if the network impact assessment needs to be computed (See <a href="NetworkImpactAssessmentRetrievalRequest">NetworkImpactAssessmentRetrievalRequest</a>)

### (6) Constraint:

a)	Name	INVALID_MEASURE_APPLICABILITY_PERIOD
	Attribute	rerouting
		Invalid rerouting(measure) applicability period should overlap Dataset
		period

## 3.2.12.3. ReroutingUpdateReply




Figure 3.34. ReroutingUpdateReply Class Diagram

(1) Reply returned in response to <u>ReroutingUpdateRequest</u>.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Rerouting rerouting (Mandatory)
     The updated rerouting with all fields set by the NM system.

## 3.2.13. Rerouting Cancellation

#### 3.2.13.1. SOAP

(1) The associated SOAP operation is:

```
ReroutingCancelReply cancelRerouting(
ReroutingCancelRequest request
)
```

# 3.2.13.2. ReroutingCancelRequest




Figure 3.35. ReroutingCancelRequest Class Diagram

(1) Request to cancel a rerouting. Undo the effect on the flights.

### (2) Note

The ReroutingCancelRequest is trial related: it is only accessible (authorized) during specific trials or on specific test platforms and only for externally editable reroutings. In STAM trials context only the cancel of externally editable cherry picked reroutings are authorized. In simulation context all rerouting are considered externally editable.

- (3) <u>Inherits from:</u> Request
- (4) Attributes:

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

- a) <u>Dataset</u> dataset (Mandatory)
   Dataset on which the rerouting proposal has to be cancelled.
- b) ReroutingId reroutingId (Mandatory)
  The identifier of the rerouting to be cancelled.
- c) <u>DateYearMonthDay</u> dayOfOperation (Mandatory)
  Day for which the rerouting has to be cancelled.
- d) PlanDataId dataId (Mandatory)
   Opaque identifier representing the version of the rerouting to revoke. The caller shall always keep this value unchanged.
- e) **boolean computeNetworkImpactAssessment** (Optional)
  In simulation dataset, indicates if the network impact assesment needs to be computed (See NetworkImpactAssessmentRetrievalRequest)

## 3.2.13.3. ReroutingCancelReply




Figure 3.36. ReroutingCancelReply Class Diagram

- (1) Reply returned in response to <u>ReroutingCancelRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

a) Rerouting rerouting (Mandatory)
The rerouting that has been cancelled.

## 3.2.14. MCDMOnly List

#### 3.2.14.1. SOAP

(1) The associated SOAP operation is:

```
MCDMOnlyListReply queryMCDMOnly(
MCDMOnlyListRequest request
)
```

## 3.2.14.2. MCDMOnlyListRequest




Figure 3.37. MCDMOnlyListRequest Class Diagram

- (1) Request to query mcdm0nly measures. mcdm0nly measures are pure text coordination measures. The remark field actually describes what kind of measure this is and what is expected. They allow to associate flights to mcdm0nly measures and follow the MCDM process. However there are no proposal flights associated to mcdm0nly measures, so no what-if counts and flightlists can be done to evaluate any potential impact.
- (2) <u>Inherits from:</u> <u>RegulationOrMCDMOnlyListRequest</u>
- (3) Attributes:
  - a) Set<<u>MCDMOnlyField</u>> requestedMCDMOnlyFields (Mandatory)

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

The reply returns only the requested mcdmOnly fields in this set, and only if the values of these requested fields are available at NM. Note that the mcdm only id is always returned. Constraint: Size must be comprised between 0 and 24.

b) Set<RegulationState> mcdmOnlyStates (Optional)
Selects the mcdmOnlys with a state that matches an entry in this set.
By default, mcdmOnlys are selected regardless to their state.
Constraint: Size must be comprised between 1 and 5.

DNM		EUROCONTROL	
Document Title:		Document Reference:	
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow	

# 3.2.14.3. MCDMOnlyListReply




Figure 3.38. MCDMOnlyListReply Class Diagram

- (1) Reply returned in response to MCDMOnlyListRequest.
- (2) See <u>RegulationOrMCDMOnlyListReplyData</u>.
- (3) Inherits from: Reply

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## (4) <u>Attributes:</u>

a) Set<MCDMOnly> mcdmOnlySet (Mandatory)
Set of mcdm only that matched the MCDMOnlyListRequest criteria.
Can be empty (meaning that no mcdm only matched the criteria).
Constraint: Size must be comprised between 0 and 10000.

## 3.2.15. MCDMOnly Creation

## 3.2.15.1. SOAP

(1) The associated SOAP operation is:

MCDMOnlyCreationReply createMCDMOnly(
MCDMOnlyCreationRequest request
)

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.15.2. MCDMOnlyCreationRequest




Figure 3.39. MCDMOnlyCreationRequest Class Diagram

- (1) Request to create a mcdmOnly.
- Note that the MCDMOnlyCreationRequest is trial related: it is only accessible (authorized) during specific trials or on specific test platforms. In STAM trials context only the creation of cherry picked mcdmOnlys are authorized.
- (3) <u>Inherits from:</u> Request
- (4) Attributes:
  - a) Dataset dataset (Mandatory)
    Dataset on which the mcdmOnly needs to be created.
  - b) MCDMOnly mcdmOnly (Mandatory)
    The filed mcdmOnly.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

Constraint: See INVALID MEASURE APPLICABILITY PERIOD

## (5) Constraint:

a)	Name	INVALID_MEASURE_APPLICABILITY_PERIOD	
	Attribute	mcdm0nly	
	Description	Invalid mcdm0nly(measure) applicability period should overlap Dataset period	

# 3.2.15.3. MCDMOnlyCreationReply




Figure 3.40. MCDMOnlyCreationReply Class Diagram

- (1) Reply returned in response to MCDMOnlyCreationRequest.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) MCDMOnly mcdmOnly (Mandatory)
     The mcdm only with fields set by the NM system.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manual FlowServices	B2B/23.0.0/Flow

## 3.2.16. MCDMOnly Update

#### 3.2.16.1. SOAP

(1) The associated SOAP operation is:

```
MCDMOnlyUpdateReply updateMCDMOnly(
MCDMOnlyUpdateRequest request
)
```

## 3.2.16.2. MCDMOnlyUpdateRequest




Figure 3.41. MCDMOnlyUpdateRequest Class Diagram

- (1) Request to update a mcdmOnly.
- (2) Note that the MCDMOnlyUpdateRequest is trial related: it is only accessible (authorized) during specific trials or on specific test platforms and only for externally editable mcdmOnlys. In STAM trials context only the update of externally editable cherry picked mcdmOnlys are authorized.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B References	ce Manuals - B2B/23.0.0/Flow

- (3) <u>Inherits from:</u> Request
- (4) <u>Attributes:</u>
  - a) Dataset dataset (Mandatory)
     Dataset on which the mcdmOnly needs to be updated.
  - b) MCDMOnly mcdmOnly (Mandatory)

The mcdmOnly fields to be updated.

Note that only those fields that need to be updated, need to be non null. The other fields simply remain unchanged.

Constraint: See INVALID MEASURE APPLICABILITY PERIOD

### (5) Constraint:

a)	Name	INVALID_MEASURE_APPLICABILITY_PERIOD
Attribute mcdm0nly		mcdm0nly
	Description	Invalid mcdm0nly(measure) applicability period should overlap Dataset period

# 3.2.16.3. MCDMOnlyUpdateReply




Figure 3.42. MCDMOnlyUpdateReply Class Diagram

(1) Reply returned in response to MCDMOnlyUpdateRequest.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) MCDMOnly mcdmOnly (Mandatory)
     The updated mcdmOnly with all fields set by the NM system.

### 3.2.17. MCDMOnly Cancellation

#### 3.2.17.1. SOAP

(1) The associated SOAP operation is:

```
MCDMOnlyCancelReply cancelMCDMOnly(
MCDMOnlyCancelRequest request
)
```

## 3.2.17.2. MCDMOnlyCancelRequest




Figure 3.43. MCDMOnlyCancelRequest Class Diagram

- (1) Request to cancel a mcdmOnly.
- Note that the MCDMOnlyCancelRequest is trial related: it is only accessible (authorized) during specific trials or on specific test platforms and only for externally editable mcdmOnlys. In STAM trials context only the cancel of externally editable cherry picked mcdmOnlys are authorized.
- (3) <u>Inherits from:</u> Request
- (4) Attributes:
  - a) Dataset dataset (Mandatory)
     Dataset on which the mcdmOnly has to be cancelled.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- b) RegulationId mcdmOnlyId (Mandatory)
  The identifier of the mcdmOnly to be cancelled.
- c) <u>DateYearMonthDay</u> dayOfOperation (Mandatory) Day for which the mcdmOnly has to be cancelled.
- d) PlanDataId dataId (Mandatory)
  Opaque identifier representing the version of the mcdmOnly to revoke. The caller shall always keep this value unchanged.

## 3.2.17.3. MCDMOnlyCancelReply




Figure 3.44. MCDMOnlyCancelReply Class Diagram

- (1) Reply returned in response to MCDMOnlyCancelRequest.
- (2) <u>Inherits from: Reply</u>
- (3) Attributes:
  - a) MCDMOnly mcdmOnly (Mandatory)
    The mcdmOnly that has been cancelled.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.2.18. Measure Operational Log Retrieval

#### 3.2.18.1. SOAP

(1) The associated SOAP operation is:

```
MeasureOpLogRetrievalReply retrieveMeasureOpLog(
MeasureOpLogRetrievalRequest request
)
```

### 3.2.18.2. MeasureOpLogRetrievalRequest




Figure 3.45. MeasureOpLogRetrievalRequest Class Diagram

- (1) Request to retrieve operational logs of a particular measure.
- For a rerouting, the returned operational logs contain the global results of the rerouting (considering all rerouted and non rerouted flights):
  - a) The network impact: additional or avoided regulations, violated restrictions if no good solution could be found, the important traffic volumes where there is a change (i.e. those traffic volumes that are overloaded/have a peak/sustained traffic counts alert)
  - b) The complete set of impacted On-Loaded/Off-loaded sectors
  - c) For the unsuccessfully rerouted flights: the reason why they could not be rerouted
  - d) For the successfully rerouted flights: the additional /gained distance/fuel/time

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- e) Per rerouted flight: the rerouting result, a.o., did the flight reroute according to the proposed route or not
- f) For a cherry picked regulation: it contains per flight the network impact of the delay
- (3) <u>Inherits from:</u> Request
- (4) Attributes:
  - a) Dataset dataset (Mandatory)
     Dataset on which the measure operational logs are requested.
  - b) MeasureId measureId (Mandatory)

    Measure id for which the operational logs must be retrieved.

## 3.2.18.3. MeasureOpLogRetrievalReply




Figure 3.46. MeasureOpLogRetrievalReply Class Diagram

- (1) Reply returned in response to MeasureOpLogRetrievalRequest.
- (2) Inherits from: Reply

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## (3) Attributes:

a) Set<<u>FlightOperationalLogEntry</u>> opLogs (Mandatory)

A set of operational log entries that matched the <u>MeasureOpLogRetrievalRequest</u> criteria. Can be empty (meaning that no opLog matched the criteria).

The result can contain a mix of operational logs concerning the measure as a whole (etfm-sId = 0) or concerning individual flights (etfmsId > 0). In addition, for the flight related operational logs, the IFPL id is not always set.

Constraint: Size must be comprised between 0 and 10000.

## 3.2.19. Update Flights in Measure

#### 3.2.19.1. SOAP

(1) The associated SOAP operation is:

```
UpdateFlightsInMeasureReply updateFlightsInMeasure(
UpdateFlightsInMeasureRequest request
)
```

### 3.2.19.2. UpdateFlightsInMeasureRequest




Figure 3.47. UpdateFlightsInMeasureRequest Class Diagram

(1) Request to add/remove/modify flights in a measure (for example: change the CTOT of a flight for a regulation).

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- For a cherry picked measure, forceFlightInRegulation allows to initially associate the flight to a measure (and give or change the CTOT) or afterwards add additional flights or modify already added flights. For a cherry picked measure unforceFlightInRegulation allows to unforce ("remove") a flight from a regulation (becomes exempted again).
- (3) If it is not a cherry picked measure, the service can be used to create a proposal (to e.g. exclude a flight from a regulation) for NMOC to review and accept/reject. (MCDM services can be used to check the status of the request).

# (4) Regulation proposal context:

The update kinds forceFlightInRegulation/unforceFlightInRegulation are accessible (authorized) when the user has access to cherry pick proposalRegulationFiling. In that case it is limited to adding proposal flights to a regulation or creating a proposal flight to remove (re-exempt) a flight from the cherry picked regulation.

Adding/removing flights results in proposal flights that are forced. When NMOC accepts the regulation proposal, the proposal flight is removed and the normal flights gets a CTOT or CTOT cancellation.

Adding/removing flights (forceFlightInRegulation/unforceFlightInRegulation) is only allowed if the MCDMState of the cherry picked proposal regulation is (re-)set to DRAFT and the regulationActivity is applied. For forceFlightInRegulation, the Flights need to have their CTOT in the future and CTOT can not be earlier than ETOT.

Flights should not be ATC\_ACTIVATED yet. Flights can be only be added if hey have the ETO (expected time over according to FTFM) or ATO (actual time over according to CTFM: e.g. for TACT\_ACTIVATED flights due to DPI) inside the regulation period.

forceFlightInRegulation/unforceFlightInRegulation, removes any previous proposal flight and creates a new proposal flight.

The forceFlightInRegulation results in an updated regulation proposal applicability period if the regulation period needs to be extended or reduced (See ATFCM reference manual).

In that case the B2B client needs to wait until the regulationActivity is APPLIED again before doing any subsequent UpdateFlightsInMeasuresRequests.

## (5) **Note 1**

The full service (adding/removing flights to rerouting, etc.) is trial related (STAM): it is only accessible (authorized) during specific trials or on specific test platforms.

- (6) <u>Inherits from: Request</u>
- (7) Attributes:
  - a) **Dataset dataset** (Mandatory)

Dataset in which the flights need to be updated in one or more measures. See <u>Forecast and Operational Datasets</u>.

b) Set<<u>UpdateFlightInMeasure</u>> flights (Mandatory)

Flights to be updated in one or more measures.

Constraint: Size must be comprised between 1 and 100.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.19.3. UpdateFlightsInMeasureReply




Figure 3.48. UpdateFlightsInMeasureReply Class Diagram

- (1) Reply returned in response to <u>UpdateFlightsInMeasureRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Set<<u>UpdateFlightInMeasure</u>> updatedFlights (Optional)
     Flights added successfully to the measure.
     <u>Constraint</u>: Size must be comprised between 1 and 100.
  - b) Map<FlightKeys, string> unsuccessfullyUpdatedFlights (Optional)
    A reason description is given for every flights that was not updated successfully.
    Constraint: Size must be comprised between 1 and 100.

#### 3.2.20. ATFCM Situation Retrieval

### 3.2.20.1. SOAP

(1) The associated SOAP operation is:

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

ATFCMSituationReply retrieveATFCMSituation( ATFCMSituationRequest request )

## 3.2.20.2. ATFCMSituationRequest




Figure 3.49. ATFCMSituationRequest Class Diagram

- (1) Request to retrieve the ATFCM situation of a given day.
- (2) <u>Inherits from:</u> Request
- (3) Attributes:
  - a) Dataset dataset (Mandatory)
     Dataset from which the ATFCM situation must be retrieved.
     Constraint: See INCONSISTENT DAY AND DATASET TYPE
  - b) DateYearMonthDay day (Mandatory)
    Day for which the ATFCM situation is requested.
    Constraint: See INCONSISTENT\_DAY\_AND\_DATASET\_TYPE

### (4) Constraint:

a)	Name	INCONSISTENT_DAY_AND_DATASET_TYPE		
	Attributes	day, dataset		
	Description	The day must be in [D-5, D] depending on dataset type i.e.:		
		i) day must be in [D-5, D] in an F0RECAST context.		
		ii) day must be in [D-1, D] in an OPERATIONAL context.		
iii) day has no range constraint in a		iii) day has no range constraint in a SIMULATION context.		

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.2.20.3. ATFCMSituationReply




Figure 3.50. ATFCMSituationReply Class Diagram

- (1) Reply returned in response to <u>ATFCMSituationRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) **DateTimeSecond lastUpdated** (Mandatory) Indicates when the ATFCM situation was last updated.
  - b) ATFCMSituationCounts counts (Mandatory) ATFCM situation counts.
  - c) <u>ATFCMSituationDelays</u> delays (Mandatory) ATFCM situation delays.
  - d) Set<<u>ATFCMSituationRegulation</u>> regulations (Optional) ATFCM situation regulations. <u>Constraint:</u> Size must be comprised between 1 and 10000.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.2.21. Retrieve Network Impact Assessment

#### 3.2.21.1. SOAP

(1) The associated SOAP operation is:

```
NetworkImpactAssessmentRetrievalReply retrieveNetworkImpactAssessment(
NetworkImpactAssessmentRetrievalRequest request
)
```

## 3.2.21.2. NetworkImpactAssessmentRetrievalRequest




Figure 3.51. NetworkImpactAssessmentRetrievalRequest Class Diagram

- (1) Request to retrieve the NetworkImpactAssessment for a regulation or rerouting creation/modification/cancellation.
- When the user e.g. creates a regulation in a simulation the NetworkImpactAssessmentRetrievalRequest will return a summary of the impact:
- (3) a) In terms of delay changes in the directly or indirectly impacted regulations (via a Delta AT-FCMSituation) (See also <u>ATFCMSituationRequest</u>)
  - b) In terms of count changes in the directly or indirectly impacted traffic volumes (via delta counts).
- (4) The user would then typically request to see the detailed counts/flightlists on those impacted traffic volumes where the B2B client could e.g. show the before and after situation (by doing a flightlist/count query and showing the delta as returned by the <a href="NetworkImpactAssessmentRetriev-alRequest">NetworkImpactAssessmentRetriev-alRequest</a>).
- (5) The NetworkImpactAssessmentRetrievalRequest returns which traffic volumes are impacted and gives a summary of the impact. The summary includes the impacted active traffic volumes and the non impacted active traffic volumes: i.e. traffic volumes/counts that had or have

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

otmv alerts or that were or are in overload. (if the user is only interrested in the changed counts, it is up to the B2B client to filter out unnecessary counts/traffic volumes).

- (6) In simulation dataset context:
- (7) a) Returns the Delta ATFCMSituation (See also <u>ATFCMSituationRequest</u>) comparing the before and after situation.
  - b) Returns the relevant active traffic volumes and the delta counts and otmv alerts.
- (8) In forecast/operational dataset context:
- (9) a) Returns no Delta ATFCMSituation.
  - b) Returns the relevant count changes in the active traffic volumes comparing normal vs proposal flights: supporting rerouting with proposal flights and proposal cherry picked regulations (both with proposal flights).
- Note that in simulation context the user needs to have asked explicitly to computeNetworkImpactAssessment in the regulation/rerouting request. (see e.g. RegulationCreationRequest)
- Note that in simulation context, this operation can take some time (depending on the number of flights directly and indirectly impacted). It could take ~ 1 minute to compute.
- (12) Inherits from: Request
- (13) Attributes:
  - a) Dataset dataset (Mandatory)
     Dataset on which the regulation needs to be created.
  - b) MeasureId forMeasure (Mandatory)

The regulation or rerouting for which to retrieve the NetworkImpactAssessment of the last creation or modification or cancellation.

c) Set<<u>TrafficVolumeId</u>> tvSets (Optional)

In the NetworkImpactAssessmentReply for the counts, only returns the traffic volumes belonging to at least one of the given traffic volume sets. Constraint: Size must be comprised between 0 and  $\infty$ .

d) boolean computeOtmvAlerts (Optional)

Indicates if OTMV alerts need to be computed (e.g., is the flight in an OTMV peak and during what count periods; see OtmvAlert) or not.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.2.21.3. NetworkImpactAssessmentRetrievalReply




Figure 3.52. NetworkImpactAssessmentRetrievalReply Class Diagram

- (1) Reply to the <u>NetworkImpactAssessmentRetrievalRequest</u> for a regulation or rerouting creation/modification/cancellation.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) **DateTimeSecond lastUpdated** (Mandatory) Last updated.
  - b) <u>DeltaATFCMSituation</u> atfcmSituationChanges (Optional)
  - c) Map<TrafficVolumeId, Map<CountsCalculationTypeAndInterval, Map<Date-TimeMinutePeriodWithUFN, DeltaCounts>>> countsChanges (Optional)

    Describes the delta counts, grouped by concerned traffic volume (See also NetworkImpactAssessmentRetrievalRequest) for which counts/traffic volumes are returned) and CountsCalculationTypeAndInterval (basically entry or occupancy) and counts period.

The countsChanges contains the OTMV alerts before/after and a list of before/after counts. Note that in case there is only 1 single e.g. entry count impacted, the Date-TimeMinute-PeriodWithUFN is not a period but the unt time is null. Otherwise e.g. for a period [10:00, 11:20] with entry counts (step is 20 minutes, duration is 60 minutes: See <a href="CountsInterval">CountsInterval</a>) then there are 5 delta counts: the first one representing the count [10:00, 11:00] the second one: [10:20, 11:20]... and the last one [11:20, 12:20]

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- i) Size must be comprised between 0 and  $\infty$ .
- ii) Item size must be comprised between 0 and  $\infty$ .
- iii) Item size must be comprised between 0 and  $\infty$ .

# 3.3. McdmService Port Type

#### 3.3.1. Overview

#### 3.3.1.1. Introduction

- (1) MCDM operations provide requests that aim at managing MCDM coordination:
  - a) MCDMTopicListRequest / MCDMTopicListReply
  - b) MCDMTopicUpdateRequest / MCDMTopicUpdateReply
  - c) MCDMTopicMessageRetrievalReguest / MCDMTopicMessageRetrievalReply
  - d) MCDMStateUpdateRequest / MCDMStateUpdateReply

## 3.3.1.2. MCDM Operations

- The MCDM operations are providing a collaboration facility, which allows coordination between ATFM actors for the implementation of a measure or the resolution of a hotspot.
- (2) It provides facilities to each actor to:
  - a) Monitor and update the state of coordination.
  - b) Organise their work according to deadlines with the help of ordered tasks and visual timelines.
  - c) Communicate with each other using an instant messaging tool for coordination topics.
- (3) The MCDM operations allows coordination on 3 levels:
  - a) On the hotspot: Actors can use the coordination tool to comment on the hotspot and give some more context and describe alternatives.
  - b) On measures: Actors can comment/approve/reject individual measures and manage the actors.
  - c) On flights linked to a measure: Actors can comment/approve/reject on individual flights and manage the actors.
- (4) In the context of regulation proposals a subset of the full MCDM process is used:
  - a) MCDM messaging or MCDM deadlines are not used. Actors can not be changed or set: only the initiator and NMOC are involved.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- b) There is no MCDM on hotspots. There is only MCDM for measures and in case of cherry pick regulations there is also MCDM for the flights.
- c) Measure MCDM allows B2B clients to see when NMOC has acknowledged the reception of a proposal regulation and when NMOC has accepted or rejected the proposal regulation or when afterwards the regulation got cancelled (due to other reasons).
- d) Flight MCDM allows B2B clients to track for cherry picked regulation which flights got accepted and which flights got rejected and which flights got unforced or deregulated afterwards due to other reasons.
- e) The B2B client can update the MCDM state for RegulationProposalWithProposalFlights (via MCDMStateUpdateRequest): limited to (re-)setting the MCDM state of the proposal regulation to DRAFT or to PROPOSED. In addition the B2B client can query the MCDM data (measures and flights) via MCDMTopicListRequest (based on a measureId) or via the flightlist (atfcm\_measure\_locations field) or via the RegulationProposalListRequest. The regulation proposal MCDM services are accessible (authorized) when the user has access to cherry pick proposalRegulationFiling.
- Note that the full set of MCDM related services are trial related (a.o. STAM): it is only accessible (authorized) during specific trials or on specific test platforms.

### 3.3.1.3. Update Pattern

- (1) Similar to: See <u>Update Pattern</u>.
- (2) However in the context of regulation proposals, the dataId to be used in MCDMStateUpdate-Request, can be either the dataId retrieved via the MCDMTopicListRequest or retrieved via the RegulationProposalListRequest.

### 3.3.2. MCDM Topic List

#### 3.3.2.1. SOAP

(1) The associated SOAP operation is:

MCDMTopicListReply queryMCDM( MCDMTopicListRequest request )

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.3.2.2. MCDMTopicListRequest




Figure 3.53. MCDMTopicListRequest Class Diagram

- (1) Request to query a list of MCDM related summary information, as well as to retrieve the MCDM topic details. See also MCDM service Port type for more info. This query method allows the caller to select the topic fields requested in the reply (see requestedTopicFields). NM kindly requests its customers to apply the following strategy:
  - a) As a rule, client applications should never request topic fields that they do not need
  - b) Client applications typically implement a query/retrieve pattern:
    - Query the small number of most relevant topic fields to display to the end user (using this MCDMTopicListRequest)

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

- ii) Retrieve more details for a given regulation when the end user has selected a topic from the list (also using this MCDMTopicListRequest, but with other requested fields)
- (2) The logical AND operator applies between all the query fields described below.
- (3) Note:

Note that this service is subject to authorization: it can only be used in regulation proposal related context or trail related context (e.g. STAM)

- (4) <u>Inherits from:</u> Request
- (5) Attributes:
  - a) Dataset dataset (Mandatory)
    Dataset on which the MCDM summary is requested
    See Forecast and Operational Datasets
  - b) <u>DateYearMonthDay</u> date (Mandatory)
    Day of operation for which the MCDM summary is requested
  - c) MCDMTopicListRequestSelector selector (Mandatory)
    Selects topics either by topic ids or by measure ids or by hotstpot ids or by actor ids.
  - d) **boolean activeOnly** (Mandatory)

If true, then the reply returns only the active MCDM topics (i.e. those that have an MCDM State that is not yet abandoned or finshed).

e) <u>DateTimeSecond</u> messagesSince (Optional)

Indicates since when the MCDM messages have to be retrieved.

Typically the client would give the previous <a href="Reply.requestReceptionTime">Reply.requestReceptionTime</a> to get all the messages that were posted since the previous request. (Using the previous <a href="Reply.sendTime">Reply.sendTime</a> can lead to messages being lost due to race conditions). However this can lead to receiving messages twice, so the client should filter out duplicates (especially for those that have a timestamp between [lastReply.requestReceptionTime, lastReply.sendTime]) Constraints:

- i) See MESSAGES SINCE CANNOT BE NULL IF REQUESTED
- ii) See MESSAGES SINCE CANNOT BE OLDER THAN FOUR HOURS
- iii) See MESSAGES SINCE MUST BE NULL IF NOT REQUESTED
- f) Set<MCDMTopicField> requestedMCDMTopicFields (Mandatory)
  The reply returns only the requested topic fields in this set, and only if the values of these requested fields are available at NM. Note that the topic id is always returned.
  Constraints:
  - i) Size must be comprised between 0 and 7.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- ii) See <u>MESSAGES\_SINCE\_CANNOT\_BE\_NULL\_IF\_REQUESTED</u>
- iii) See <u>MESSAGES\_SINCE\_MUST\_BE\_NULL\_IF\_NOT\_REQUESTED</u>

## (6) Constraints:

- Attributes MESSAGES\_SINCE\_MUST\_BE\_NULL\_IF\_NOT\_REQUESTED

  Attributes messagesSince, requestedMCDMTopicFields

  Description The attribute messagesSince must be null if requestedMCDMTopicFields.messages is not requested.
- Name MESSAGES\_SINCE\_CANNOT\_BE\_NULL\_IF\_REQUESTED

  Attributes messagesSince, requestedMCDMTopicFields

  Description The attribute messagesSince is mandatory if requestedMCDMTopicFields.messages is requested.
- c) Name MESSAGES\_SINCE\_CANNOT\_BE\_OLDER\_THAN\_FOUR\_HOURS

  Attribute messagesSince

  Description The date time messagesSince cannot be before the requested time minus 4 hours.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.3.2.3. MCDMTopicListReply




Figure 3.54. MCDMTopicListReply Class Diagram

- (1) Reply returned in response to MCDMTopicListRequest.
- (2) Inherits from: Reply
- (3) Attributes:
  - a) Set<MCDMHotspotTopic> hotspotTrees (Optional)
    A set of hotspot topic details that matched the MCDMTopicListRequest criteria.
    Can be empty (meaning that no hotspot topics matched the criteria).

#### Note:

Note that hotspotTrees will only be present if the measures that have an associated hotspot in the measure data (for example regulation proposals can have a

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

hotspot inside the regulation proposal data). So when querying on for example a measureId or a topicId, the results can be returned inside hotspotTrees.measureTopics (which only has 1 measure when quering on measureId) and inside this measureTopic, one would find the MCDMState of all flights concerned.

Constraint: Size must be comprised between 1 and ∞.

### b) Set<<u>MCDMMeasureTopic</u>> measureWithoutHotspotTrees (Optional)

A set of measure topic details which are not linked to a hotspot, that matched the <u>MCDMTopicListRequest</u> criteria.

Can be empty (meaning that no such measure topics matched the criteria). Constraints:

- i) Size must be comprised between 1 and  $\infty$ .
- ii) See <u>HOTSPOT\_ID\_CANNOT\_BE\_SET\_IN\_MEASURE\_TOPICS</u>

### (4) Constraint:

a)	Name	HOTSPOT_ID_CANNOT_BE_SET_IN_MEASURE_TOPICS	
	Attribute	<u>measureWithoutHotspotTrees</u>	
Description For every measure topics from the measureWithoutHotspotI the hotspotId attribute must be null.			

## 3.3.3. MCDM Topic Update

### 3.3.3.1. SOAP

(1) The associated SOAP operation is:

```
MCDMTopicUpdateReply updateMCDM(
MCDMTopicUpdateRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.3.3.2. MCDMTopicUpdateRequest




Figure 3.55. MCDMTopicUpdateRequest Class Diagram

- (1) Request to update a MCDM topic (e.g., change a vote or change the roles and approvals for users).
- (2) Note:

Note that this sevice is trial related (e.g. STAM). So it is only available during specific trials or on specific test platforms.

- (3) <u>Inherits from:</u> Request
- (4) Attributes:
  - a) Dataset dataset (Mandatory)
     Dataset on which the MCDM topic update is requested
  - b) DateYearMonthDay date (Mandatory)
    Day of operation for which the MCDM topic update is requested
  - c) <u>AirNavigationUnitId</u> impersonatedUser (Mandatory) The user on behalf the update is done or the message is sent.
  - d) MCDMTopic topic (Mandatory)
    The topic to be updated

# 3.3.3. MCDMTopicUpdateReply

- (1) Reply returned in response to <u>MCDMTopicUpdateRequest</u>.
- (2) <u>Inherits from:</u> Reply

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## (3) Attributes:

a) MCDMTopic topic (Mandatory)
The updated MCDM topic details.

## 3.3.4. MCDM Topic Message Retrieval

### 3.3.4.1. SOAP

(1) The associated SOAP operation is:

```
MCDMTopicMessageRetrievalReply retrieveMCDMMessages(
MCDMTopicMessageRetrievalRequest request
)
```

## 3.3.4.2. MCDMTopicMessageRetrievalRequest




Figure 3.56. MCDMTopicMessageRetrievalRequest Class Diagram

(1) Request to retrieve all messages to/from all actors for a given topic.

## (2) Note:

Note that this sevice is trial related (e.g. STAM). So it is only available during specific trials or on specific test platforms.

- (3) Inherits from: Request
- (4) <u>Attributes:</u>
  - a) MCDMTopicId topicId (Mandatory)
     The MCDM topic identifier for which we want to retrieve all the MCDM messages.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.3.4.3. MCDMTopicMessageRetrievalReply




Figure 3.57. MCDMTopicMessageRetrievalReply Class Diagram

- (1) Reply returned in response to <u>MCDMTopicMessageRetrievalRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Set<<u>MCDMMessage</u>> messages (Mandatory)

A set of MCDM messages that matched the <u>MCDMTopicMessageRetrievalRequest</u> criteria. Can be empty (meaning that no messages matched the criteria). <u>Constraint:</u> Size must be comprised between 0 and 10000.

## 3.3.5. MCDM State Update

### 3.3.5.1. SOAP

(1) The associated SOAP operation is:

MCDMStateUpdateReply updateMCDMState( MCDMStateUpdateRequest request )

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.3.5.2. MCDMStateUpdateRequest




Figure 3.58. MCDMStateUpdateRequest Class Diagram

(1) Request to update the MCDMState of a regulation (typically used in the context of regulation proposals).

## (2) Note 1:

Note that this service is subject to authorization: it can only be used in regulation proposal related context or trial related context (e.g. STAM).

## (3) Note 2:

Note that in regulation proposal context, it is only allowed to change he MCDM state of the regulation when NMOC is not yet reviewing the regulation or when the review has been completed (so then MCDMState is DRAFT, PROPOSED, IMPLEMENTED, ABANDONED or INTERUPTED)

Except when the regulationState is CANCELLED or TERMINATED, then it is no longer possible to update the MCDMState. The MCDM state can only be changed to PROPOSED from the DRAFT MCDMState.

- (4) <u>Inherits from:</u> Request
- (5) Attributes:
  - a) PlanDataId dataId (Mandatory)
     Opaque identifier representing the version of the MCDM state to update. See <u>Update Pattern</u>.
  - b) **Dataset dataset** (Mandatory)

    Dataset to which the regulation belongs. See <u>Forecast and Operational Datasets</u>.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

- c) RegulationId regulationId (Mandatory)
  The unique id of the regulation or regulation proposal.
- d) MCDMState newMCDMState (Optional)

The new MCDM state.

In the context of regulation proposals, only DRAFT or PROPOSED are allowed (DRAFT when the B2B client wants to update a regulation or a regulation proposal and PROPOSED when the B2B client wants NMOC to review): See MCDM service Port type.

### 3.3.5.3. MCDMStateUpdateReply




Figure 3.59. MCDMStateUpdateReply Class Diagram

(1) Reply to a MCDMStateUpdateRequest.

# (2) Special error conditions:

- a) INVALID\_DATASET [Temporary error] If the FORECAST update was rejected due to D-1 forecast update cut-off or if the OPERATIONAL update was rejected due to D-1 plan not transferred yet.
- b) CONFLICTING\_UPDATE [Permanent error] If the update failed due to incompatible concurrent changes.
- c) OBJECT\_NOT\_FOUND [Permanent error] If the measure is not known or if it has no MCDM.
- d) Note that there are also the INVALID\_INPUT replyStatus errors, that cover the errors detected by the backend (See Transaction and Errors). For example: trying to change the MCDMState to FINISHED in the context of regulation proposal).
- (3) Inherits from: Reply
- (4) <u>Attributes:</u>
  - a) MCDMState newMCDMState (Mandatory)

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

The resulting MCDM state.

# 3.4. Tactical Updates Service Port Type

#### 3.4.1. Overview

#### 3.4.1.1. Introduction

- (1) This service is intended to provide querying and update capabilities on Tactical updates. The requests currently available are:
  - a) <u>SectorConfigurationPlanRetrievalRequest</u> / <u>SectorConfigurationPlanRetrievalReply</u>
  - b) SectorConfigurationPlanUpdateRequest / SectorConfigurationPlanUpdateReply
  - c) CapacityPlanRetrievalRequest / CapacityPlanRetrievalReply
  - d) <u>CapacityPlanUpdateRequest</u> / <u>CapacityPlanUpdateReply</u>
  - e) <u>TrafficVolumeActivationPlanRetrievalRequest</u> / <u>TrafficVolumeActivationPlanRetrievalReply</u>
  - f) <u>TrafficVolumeActivationPlanUpdateRequest</u> / <u>TrafficVolumeActivationPlanUpdateReply</u>
  - g) <u>OTMVPlanRetrievalRequest</u> / <u>OTMVPlanRetrievalReply</u>
  - h) OTMVPlanUpdateRequest / OTMVPlanUpdateReply
  - i) RunwayConfigurationPlanRetrievalReguest / RunwayConfigurationPlanRetrievalReply
  - j) RunwayConfigurationPlanUpdateRequest / RunwayConfigurationPlanUpdateReply
  - k) <u>HotspotListRequest</u> / <u>HotspotListReply</u>
  - I) HotspotPlanUpdateRequest / HotspotPlanUpdateReply

#### 3.4.1.2. CACD Retrievals vs. Tactical Situation

- (1) The current situation is that the airspace data involved in the Daily Plan is maintained in two systems:
  - a) The NM CACD (airspace) system for AIRAC definitions
  - b) NM flow system for tactical updates
- (2) The export of related CACD objects (consistently with the export of other CACD objects) does not take into account the tactical updates done via the NM flow system (pre-tactical and tactical situations). Hence:
  - a) When retrieving a daily plan (see below), the caller receives the superset of CACD values on periods that were not updated (pre-)tactically and of the tactical updates.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- b) The caller can only input the tactical updates. These should not include the CACD values (providing the CACD values has the effect of overwriting all that has been planned in CACD see below).
- c) To retrieve a Daily Plan:
  - Retrieve a Sector Configuration Plan;
  - · Retrieve a Capacity Plan;
  - Retrieve a Traffic Volume Activation Plan;
  - Retrieve an OTMV Plan;
  - Retrieve a Runway Configuration Plan.

#### 3.4.1.3. Daily Plan Update Pattern

- (1) The pattern used for all tactical updates is the update of the entire list of values for a day. This list of values must be a consistent and complete time partition for the whole day. For each time period the user can specify whether new values or the existing CACD values should be used.
- (2) More precisely, the client system will be able to update in one shot:
  - a) The plan of runway configurations for an entire day and an aerodrome;
  - b) The plan of sector configuration activations for an entire day and an airspace (AUA or sector cluster);
  - c) The plan of capacities for an entire day and a traffic volume;
  - d) The plan of traffic volume activations for an entire day and a traffic volume;
  - e) The plan of OTMVs for an entire day and a traffic volume for a duration;
- (3) As mentioned above, each daily plan is a complete time partition of the day, meaning that each daily plan update which is made of values defined over periods must be such that its periods do not overlap and cover the whole day. Providing a daily plan that is not a time partition will result in an error.
- (4) The data value associated to each period of the plan must be:
  - either an indication that for this period the CACD data is to be used (note that for some plans, e.g. for some capacity plans, there is no data defined in CACD for certain locations/traffic volumes)
  - b) or the specific values to be used for that period.
- (5) So, it is up to the B2B client to either always pass the plan with the full CACD values (which are copied over, hence overwritten) when not updated, or to pass only the actual tactical updates and indications that CACD values should be used in the absence of tactical updates.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- (6) Any of the plans mentioned above may be updated via B2C and/or B2B, and in both cases by different operators. When an operator updates a plan via B2C, the next B2B retrieve plan operation will include these changes done via B2C. The pattern used on the backend side to deal with concurrent updates is the following:
  - a) Each daily plan is returned with a data id that expresses a data version number (equivalent to a timestamp)
  - b) Before updating a daily plan, the updater must first get the plan and subsequently pass the associated data id when updating it. <a href="MMPORTANT:">IMPORTANT:</a> note that this data id is also related to the dataset in use, i.e. a data id obtained from a dataset cannot be used with another dataset: doing so would result in an error.
  - c) A concurrent update is defined as an update that took place earlier (i.e. before the update that the updater wants to execute now) but after the timestamp associated to the data id passed within the update to execute now. For example:
    - i) A B2B client shows in a local screen a daily plan.corresponding to datald I1
    - ii) A NM client in a parallel modifies the same daily plan (for the same location and updated periods) via B2B or B2C -> latest version in NM systems : datald I2.
    - iii) The B2B client end-user modifies some values of the plan and tries to commit them (includes sending to NM; changes wrt I1)
    - iv) As the B2B client end-user started from datald I1 but the periods that were modified were also conflictingly modified in parallel CONFLICTING\_UPDATE ReplyStatus is returned
  - d) From the concurrency perspective, a daily plan update is successful if:
    - i) There was no concurrent update, or
    - ii) There were identical concurrent updates, and/or
    - iii) There were concurrent updates that did not involve time periods overlapping with the time periods for which there is a change in the newly updated plan.
  - e) <u>IMPORTANT:</u> NM insists that the B2B client only does a tactical update to a plan in case something has changed for that plan. Updates that do not change anything are logged. In case too many of such non-updates are logged, then access can be restricted. This ensures that the backend responsible for the (pre-) tactical updates, does not get overloaded with non-updates.
- The data id is an opaque identifier of the version of the global state of the backend system related to CACD or tactical updatable related data (not pure flight data). Whenever dataId is passed in an update request, the system verifies if there have been conflicting updates between what the B2B client tried to update (wrt the state of the system linked to the dataid) and the latest state. Note that the dataId represent the global state of the backend system (not linked to specific

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

locations). It changes continuously (between subsequent retrievePlan requests). However the fact that it changes continuously does not impact the B2B client, as it is only used to detect if there have been conflicting parallel updates between the latest state and what the B2B client changed in the update request.

- (8) There are basically 2 ways (operationally) to use dataId:
  - a) In case B2C/NMOC (via phone coordination) will not be used anymore to update daily plans concerning the B2B client (nor in tactical, nor in forecast (PREDICT) and B2B is not used by any other systems to update the concerned daily plans and the master repository of the data is inside the B2B client's systems, then the B2B client can just before each update first do a query to retrieve the relevant daily plan (and its associated dataId. So the detailed steps for a sector configuration update would be:
    - i) Retrieve the sector configuration plan for the AUA (Reply S1 includes dataId1)
    - ii) Produce the sectorConfigurationPlanUpdateRequest based on the client's local systems (using dataId1 and optionally merging/keeping S1 past data (if NM systems could/would be used as contingency repository and as such past data could have become different))
    - iii) B2B.updateRunwayConfigurationPlan with this sectorConfigurationPlanUpdate-Request. This usage pattern, would on each update systematically wipe out any changes applied via B2C/NMOC/other B2B systems). Note that in case NM systems are used as contingency repository, on restart the B2B client may want to import the data again into the local system.
  - b) In case the B2C/NMOC (via phone coordination) could still occasionally be used to update the concerned daily plans (e.g. contingency) or B2B is used by other systems to update the concerned daily plans or the B2B client system is not the master repository of the data (e.g. runway configurations that could be done by FMP or by tower), then the dataId (in combination with the CONFLICTING\_UPDATE error reply) can be used to detect conflicting parallel updates and report those to the end user so that he can decide what to do. So the detailed steps for a sector configuration update would be:
    - i) On the first update for a specific AUA A for a specific day X, the B2B client would first do a retrieveSectorConfigurationPlan to get a datald A1. In the returned sectorConfigurationPlan there should not be any periods that have a data source tactical and that are different with the data in the local system. In case of differences, the operator is notified and needs to decide what values to choose.
    - ii) B2B.updateRunwayConfigurationPlan is used with datald A1. The reply contains a datald A2.
    - iii) Each next update for AUA A for day X, would use the dataId returned by the previous update (A2,A3,...).
    - iv) If the NM systems detect a conflicting parallel update between the time corresponding to the datald A1/A2.. and the latest NM state wrt AUA A and day X, the reply contains a CONFLICTING\_UPDATE error. In that case the client system would warn the oper-

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

ator that a conflicting parallel update has occurred and would show the local data and the NM data to allow the operator to choose (and optionally update any local system as well)

v) If AUA B for Day X is updated, then data Id B1 needs to be associated to AUA B. This usage pattern, would make sure that no changes are lost un-expectedly and the operator is in full control if updates are done via B2C or by the NM plan transfer of forecast data into operational.

Note that this second pattern is a bit more robust (operationally speaking) and can also handle the case were B2C is no longer used (point a above).

Note that it is this second pattern that a.o. NM systems use: when an AUA I is updated, first the NM data is shown and in the screen data the associated datald I1 is kept. (the user has seen the NM data corresponding to datald I1).

When the user applies his changes, this data Id I1 is then used in the sectorConfu-grationPlanUpdateRequest. In case there were parallel conflicting updates, the user is notified and he needs to redo his update (including first looking at the latest NM data). The main reason behind: multiple operators at different terminals can do conflicting updates and they need to be notified.

Note that technically the B2B client can also use this pattern to detect parallel conflicting updates between different operators inside the client's own organization. (in case it is needed/useful).

#### 3.4.1.4. Transactions and Errors

- (1) If any change in the plan fails to be successfully processed by the NM system, the whole new plan is rejected so that the previous version of the pl an remains unchanged.
- In some cases, the B2B layer can not do all validations involved in tactical updates. Some validations are done by the backend system. These errors are reported as a reply with ReplyStatus INVALID\_INPUT and the error message string describes the problem. This error message string cannot be considered by the B2B client as part of the B2B contract (that string may change any time).
- (3) As seen below, some error conditions are permanent in the sense that retrying the transaction later will never solve the problem (typically because the data in the request violates some validation rule), and a few others are temporary, e.g. the transaction failed because the NM system is itself in some temporar y state that prevents it from processing the request (e.g. the daily plan is being transferred see below). In any case, the temporary error conditions are always w ell identified within the reply so that the B2B client knows when it is worth retrying a few minutes later NM insists that the updates that failed due to a temporary condition are only retried a few minutes later, not a few seconds later and even less a few milliseconds later.
- (4) Note that violations of the input constraints mentioned in the B2B model below will be reported in a structured way so that the B2B client will be a ble to decide what to do with them.
- (5) Also note that permanent errors due to unknown references to airspace elements (like aerodrome ids, sector configurations ids, traffic volume ids) will NOT be returned formally. They are returned as a reply with ReplyStatus OBJECT\_NOT\_FOUND and an error message describing what attribute can not be found.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.4.1.5. Allowed Times for Retrievals and Updates

#### 3.4.1.5.1. Forecast and Operational Datasets

- (1) See also <u>Forecast and Operational Datasets</u>.
- The forecast and operational datasets are concepts that the NM customers (ANSPs in particular) are already familiar with. In short, the NM system prepares the plan between D-6 (6 days in advance) and D-1 (1 day in advance) within the forecast dataset, which is transferred to the operational dataset on D-1 around 16:00 UTC.
- The plan remains available in the forecast dataset after transfer, until the end of D (day of operations), even though it does not evolve anymore in that dataset.
- (4) To summarize:
  - a) The plan can be updated:
    - i) In the forecast dataset: in [ D-5 (5 days in the future), D-1 16:00 UTC]
    - ii) In the operational dataset: at any point in time on D-1 and D via B2B, D-1 updates are only allowed after the plan has been transferred (the ability to update the plan in the operational dataset before the plan has been transferred exists but is reserved to the NM OPS Room and in exceptional circumstances)
  - b) The plan can be retrieved:
    - i) From the forecast dataset: at any time in [ D-5, D ]
    - ii) From the operational dataset: at any point in time in [ D-1, D ]. The most up-to-date plan for a specific day X can be found in operational if the plan has already been transferred for day X. If the plan has not been transferred yet for day X, then the most up-to-date plan for day X can be found in forecast.
- (5) Regarding the plan transfer, the updates to the forecast dataset are rejected from a cut-off time on D-1 that is 16:00 UTC; the NM OPS Room may then fine tune the plan for a little while, and finally transfers it to the operational dataset. The time elapsed between the cut-off time of the forecast dataset and the time at which the plan has been actually transferred to the operational dataset is typically around 10 minutes. This elapsed time may exceptionally be longer though, e.g. in case of unexpected change of the network situation (like unexpected strike or weather conditions), so that the plan can exceptionally be transferred a few hours after the cut-off time. The B2B client designer is invited to take this variability into consideration. Updates to the plan, in the forecast or operational datasets, are rejected during this elapsed time.
- The B2B caller knows whether the plan has been transferred or not via the planTransferred attribute of a plan. Similarly, the B2B caller knows that the forecast update cut-off time has been reached or not via the planCutOffReached attribute of a plan.

  This will be tentatively solved in NM 19.0.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### 3.4.1.5.2. Past

(1) A tactical update is rejected if it attempts to update the past. More precisely, the period associated to any update in the plan must start after the clock of the NM system. So when doing an tactical update at e.g. 13:00 for the remainder of day D, the clientschedule needs to also contain all the periods before 13:00 unaltered: i.e. as they were in a previously retrieved/send clientschedule. So all past periods marked with CACD need to be kept CACD (i.e. AIRSPACE datasource) and past all periods marked as tactically updated need to be kept tactically updated (TACTICAL datasource with the corresponding past data). Changing for a period, the datasource AIRSPACE (CACD) to TACTICAL is considered a change (because a TACTICAL updated period hides the CACD (AIRSPACE) data for that period and as such subsequent CACD changes are "ignored" for a tactically updated period)

Hence, an attempt to modify the past results in a permanent error.

This error will be formally identified as such if the modification is requested for D+1 (yesterday) or earlier.

But in case the attempt is made to modify the past within D, the resulting permanent error will not be formally identified as an attempt to update the past within D: the only way for the B2B client to investigate why the request failed will be to log and exploit the returned informal error message (string).

- (2) In order to support changes on existing tactical updates, an existing period, starting in the past and ending in the future, can be split into a shorter period, starting at the same moment as the initial one but ending earlier, as long as the first new period still finishes in the future (i.e. the second new period starts in the future), and the data associated to the first new period is left unchanged.
- (3) Retrievals in the past are limited to the past within D, i.e. the whole daily plan is returned for D but the B2B client cannot request the plans for D+1 or earlier.

  This permanent error will be formally identified.

#### 3.4.2. Retrieve a Sector Configuration Plan

#### 3.4.2.1. SOAP

(1) The associated SOAP operation is:

SectorConfigurationPlanRetrievalReply retrieveSectorConfigurationPlan(
SectorConfigurationPlanRetrievalRequest request
)

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

# 3.4.2.2. SectorConfigurationPlanRetrievalRequest




Figure 3.60. SectorConfigurationPlanRetrievalRequest Class Diagram

- (1) Request to retrieve the sector configuration plan for a given AUA or sector cluster on a given day.
- (2) <u>Inherits from: TacticalConfigurationRetrievalRequest</u>
- (3) Attributes:
  - a) AirspaceId airspace (Mandatory)
     AUA or sector cluster for which the sector configuration plan is requested.

# 3.4.2.3. SectorConfigurationPlanRetrievalReply




Figure 3.61. SectorConfigurationPlanRetrievalReply Class Diagram

- (1) Reply to a <u>SectorConfigurationPlanRetrievalRequest</u>.
- (2) Special error conditions:
- (3) a) OBJECT\_NOT\_FOUND If the airspace is neither an AUA, nor a sector cluster, or if there is no sector configuration defined in CACD for this AUA/sector cluster.
- (4) <u>Inherits from:</u> Reply
- (5) Attributes:

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

a) SectorConfigurationPlan plan (Mandatory)
The complete sector configuration plan for a given AUA or sector cluster on a given day.

## 3.4.3. Update a Sector Configuration Plan

#### 3.4.3.1. SOAP

(1) The associated SOAP operation is:

```
SectorConfigurationPlanUpdateReply updateSectorConfigurationPlan(
SectorConfigurationPlanUpdateRequest request
)
```

### 3.4.3.2. SectorConfigurationPlanUpdateRequest




Figure 3.62. SectorConfigurationPlanUpdateRequest Class Diagram

- (1) Request to update the sector configuration plan for a given AUA or sector cluster on a given day.
- (2) <u>Inherits from:</u> Request
- (3) Attributes:
  - a) <u>SectorConfigurationPlan</u> plan (Mandatory)
     Sector configuration plan reflecting the requested updates.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

# 3.4.3.3. SectorConfigurationPlanUpdateReply




Figure 3.63. SectorConfigurationPlanUpdateReply Class Diagram

- (1) Reply to a <u>SectorConfigurationPlanUpdateRequest</u>.
- (2) Special error conditions:
- (3) a) INVALID\_DATASET [Temporary error] If the FORECAST update was rejected due to D-1 forecast update cut-off or if the OPERATIONAL update was rejected due to D-1 plan not transferred yet.
  - b) CONFLICTING\_UPDATE [Permanent error] If the update failed due to incompatible concurrent changes.
  - c) OBJECT\_NOT\_FOUND [Permanent error] If the airspace is neither an AUA, nor a sector cluster, or if there is no sector configuration defined in CACD for this AUA/sector cluster.
  - d) Note that there are also the INVALID\_INPUT replyStatus errors, that cover the errors detected by the backend (See <u>Transaction and Errors</u>). For example: errors when modifying the past (See Airspace Past)
- (4) <u>Inherits from:</u> Reply
- (5) Attributes:
  - a) SectorConfigurationPlan plan (Mandatory)
    The complete sector configuration plan for a given AUA or sector cluster on a given day, resulting from the update.

### 3.4.4. Retrieve a Capacity Plan

#### 3.4.4.1. SOAP

(1) The associated SOAP operation is:

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

CapacityPlanRetrievalReply retrieveCapacityPlan(
CapacityPlanRetrievalRequest request
)

## 3.4.4.2. CapacityPlanRetrievalRequest




Figure 3.64. CapacityPlanRetrievalRequest Class Diagram

- (1) Request to retrieve the capacity plan for a given traffic volume on a given day.
- (2) <u>Inherits from: TacticalConfigurationRetrievalRequest</u>
- (3) <u>Attributes:</u>
  - a) **Set<<u>TrafficVolumeId</u>> trafficVolumes** (Mandatory) The traffic volume for which the capacity plan is requested. Constraint: Size must be comprised between 0 and ∞.

## 3.4.4.3. CapacityPlanRetrievalReply




Figure 3.65. CapacityPlanRetrievalReply Class Diagram

- (1) Reply to a <u>CapacityPlanRetrievalRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

a) <u>CapacityPlans</u> plans (Mandatory)

The complete capacity plan for a given traffic volume on a given day.

## 3.4.5. Update a Capacity Plan

#### 3.4.5.1. SOAP

(1) The associated SOAP operation is:

```
CapacityPlanUpdateReply updateCapacityPlan(
CapacityPlanUpdateRequest request
)
```

## 3.4.5.2. CapacityPlanUpdateRequest




Figure 3.66. CapacityPlanUpdateRequest Class Diagram

- (1) Request to update the capacity plan for a given traffic volume on a given day.
- (2) The update of several traffic volumes is possible in the same B2B request.
- (3) <u>Inherits from:</u> Request
- (4) Attributes:
  - a) <u>CapacityPlans</u> plans (Mandatory)
     Capacity plan reflecting the requested updates.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.4.5.3. CapacityPlanUpdateReply




Figure 3.67. CapacityPlanUpdateReply Class Diagram

- (1) Reply to a <u>CapacityPlanUpdateRequest</u>.
- (2) Special error conditions:
- (3) a) INVALID\_DATASET [Temporary error] If the FORECAST update was rejected due to D-1 forecast update cut-off or if the OPERATIONAL update was rejected due to D-1 plan not transferred yet.
  - b) CONFLICTING\_UPDATE [Permanent error] If the update failed due to incompatible concurrent changes.
  - c) OBJECT NOT FOUND [Permanent error] If the Traffic Volume is not known.
  - d) Note that there are also the INVALID\_INPUT replyStatus errors, that cover the errors detected by the backend (See <u>Transaction and Errors</u>). For example: errors when modifying the past (See <u>Airspace Past</u>)
- (4) Inherits from: Reply
- (5) Attributes:
  - a) <u>CapacityPlans</u> plans (Mandatory)
     The complete capacity plan for a given traffic volume on a given day, resulting from the update.

## 3.4.6. Retrieve a Traffic Volume Activation Plan

#### 3.4.6.1. SOAP

(1) The associated SOAP operation is:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

TrafficVolumeActivationPlanRetrievalReply retrieveTrafficVolumeActivationPlan( TrafficVolumeActivationPlanRetrievalRequest request )

## 3.4.6.2. TrafficVolumeActivationPlanRetrievalRequest




Figure 3.68. TrafficVolumeActivationPlanRetrievalRequest Class Diagram

- (1) Request to retrieve the traffic volume activation plan for a given traffic volume on a given day.
- (2) <u>Inherits from: TacticalConfigurationRetrievalRequest</u>
- (3) <u>Attributes:</u>
  - a) Set<<u>TrafficVolumeId</u>> trafficVolumes (Mandatory)
     The traffic volumes for which according activation plans are requested.
     Constraint: Size must be comprised between 0 and ∞.

# 3.4.6.3. TrafficVolumeActivationPlanRetrievalReply




Figure 3.69. TrafficVolumeActivationPlanRetrievalReply Class Diagram

- (1) Reply to a <u>TrafficVolumeActivationPlanRetrievalRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

a) <u>TrafficVolumeActivationPlans</u> plans (Mandatory)

The complete activation plans for a given traffic volumes on a given day.

## 3.4.7. Update a Traffic Volume Activation Plan

#### 3.4.7.1. SOAP

(1) The associated SOAP operation is:

TrafficVolumeActivationPlanUpdateReply updateTrafficVolumeActivationPlan(
TrafficVolumeActivationPlanUpdateRequest request
)

## 3.4.7.2. TrafficVolumeActivationPlanUpdateRequest




Figure 3.70. TrafficVolumeActivationPlanUpdateRequest Class Diagram

- (1) Request to update the traffic volume activation plan for a given traffic volume on a given day.
- (2) The update of several traffic volumes is possible in the same B2B request.
- (3) <u>Inherits from:</u> Request
- (4) Attributes:
  - a) <u>TrafficVolumeActivationPlans</u> plans (Mandatory)
     Traffic volumes activation plans reflecting the requested updates.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

# 3.4.7.3. TrafficVolumeActivationPlanUpdateReply




Figure 3.71. TrafficVolumeActivationPlanUpdateReply Class Diagram

- (1) Reply to a <u>TrafficVolumeActivationPlanUpdateRequest</u>.
- (2) Special error conditions:
- (3) a) INVALID\_DATASET [Temporary error] If the FORECAST update was rejected due to D-1 forecast update cut-off or if the OPERATIONAL update was rejected due to D-1 plan not transferred yet.
  - b) CONFLICTING\_UPDATE [Permanent error] If the update failed due to incompatible concurrent changes.
  - c) OBJECT NOT FOUND [Permanent error] If the Traffic Volume is not known.
  - d) Note that there are also the INVALID\_INPUT replyStatus errors, that cover the errors detected by the backend (See <u>Transaction and Errors</u>). For example: errors when modifying the past (See <u>Airspace Past</u>)
- (4) Inherits from: Reply
- (5) Attributes:
  - a) <u>TrafficVolumeActivationPlans</u> plans (Mandatory)

    The complete traffic volume activation plans for a given traffic volumes on a given day, resulting from the update.

#### 3.4.8. Retrieve an OTMV Plan

#### 3.4.8.1. SOAP

(1) The associated SOAP operation is:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow



## 3.4.8.2. OTMVPlanRetrievalRequest




Figure 3.72. OTMVPlanRetrievalRequest Class Diagram

- (1) Request to retrieve for a given day, the OTMV plans for a given traffic volume (for all applicable OTMV durations) or to retrieve the OTMV plan for a specific (traffic volume, OTMV duration) pair.
- (2) <u>Inherits from: TacticalConfigurationRetrievalRequest</u>
- (3) Attributes:
  - a) Set<<u>OTMVWithDuration</u>> otmvsWithDuration (Mandatory)
     The Set of OTMVWithDuration objects, which contain traffic volume and the OTMV plan is requested.

Constraint: Size must be comprised between 0 and  $\infty$ .

# 3.4.8.3. OTMVPlanRetrievalReply




Figure 3.73. OTMVPlanRetrievalReply Class Diagram

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- (1) Reply to a <u>OTMVPlanRetrievalRequest</u>.
- (2) Special error conditions:
- (3) a) OBJECT\_NOT\_FOUND If the Traffic Volume is not known or if the associated reference location is not an airspace.
- (4) <u>Inherits from:</u> Reply
- (5) Attributes:
  - a) OTMVPlans plans (Mandatory)
    The complete OTMV plan for a given (traffic volume, OTMV duration) pair on a given day.

### 3.4.9. Update an OTMV Plan

#### 3.4.9.1. SOAP

(1) The associated SOAP operation is:

```
OTMVPlanUpdateReply updateOTMVPlan(
OTMVPlanUpdateRequest request
)
```

### 3.4.9.2. OTMVPlanUpdateRequest




Figure 3.74. OTMVPlanUpdateRequest Class Diagram

- (1) Request to update the OTMV plan for a given (traffic volume, OTMV duration) pair on a given day.
- (2) The update of several traffic volumes is possible in the same B2B request.
- (3) Inherits from: Request
- (4) Attributes:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

a) OTMVPlans plans (Mandatory)
 OTMV plans reflecting the requested updates.

## 3.4.9.3. OTMVPlanUpdateReply




Figure 3.75. OTMVPlanUpdateReply Class Diagram

- (1) Reply to a <u>OTMVPlanUpdateRequest</u>.
- (2) Special error conditions:
- (3) a) INVALID\_DATASET [Temporary error] If the FORECAST update was rejected due to D-1 forecast update cut-off or if the OPERATIONAL update was rejected due to D-1 plan not transferred yet.
  - b) CONFLICTING\_UPDATE [Permanent error] If the update failed due to incompatible concurrent changes.
  - c) OBJECT\_NOT\_FOUND [Permanent error] If the Traffic Volume is not known or if the associated reference location is not an airspace.
  - d) Note that there are also the INVALID\_INPUT replyStatus errors, that cover the errors detected by the backend (See <u>Transaction and Errors</u>). For example: errors when modifying the past (See <u>Airspace Past</u>)
- (4) Inherits from: Reply
- (5) Attributes:
  - a) <u>OTMVPlans</u> plans (Mandatory)
    The complete OTMV plan for a given (traffic volume, OTMV duration) pair on a given day, resulting from the update.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### 3.4.10. Retrieve a runway configuration plan

#### 3.4.10.1. SOAP

(1) The associated SOAP operation is:

```
RunwayConfigurationPlanRetrievalReply retrieveRunwayConfigurationPlan(
RunwayConfigurationPlanRetrievalRequest request
)
```

## 3.4.10.2. RunwayConfigurationPlanRetrievalRequest




Figure 3.76. RunwayConfigurationPlanRetrievalRequest Class Diagram

- (1) Request to retrieve the runway configuration plan for a given aerodrome on a given day.
- (2) <u>Inherits from: TacticalConfigurationRetrievalRequest</u>
- (3) Attributes:
  - a) AerodromeICA0Id aerodrome (Mandatory)
     The aerodrome for which the runway configuration plan is requested.

## 3.4.10.3. RunwayConfigurationPlanRetrievalReply




Figure 3.77. RunwayConfigurationPlanRetrievalReply Class Diagram

(1) Reply to a <u>RunwayConfigurationPlanRetrievalRequest</u>.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) RunwayConfigurationPlan plan (Mandatory)

    The complete runway configuration plan for a given aerodrome on a given day.

# 3.4.11. Update a runway configuration plan

#### 3.4.11.1. SOAP

(1) The associated SOAP operation is:

RunwayConfigurationPlanUpdateReply updateRunwayConfigurationPlan( RunwayConfigurationPlanUpdateRequest request )

# 3.4.11.2. RunwayConfigurationPlanUpdateRequest




Figure 3.78. RunwayConfigurationPlanUpdateRequest Class Diagram

- (1) Request to update the runway configuration plan for a given aerodrome on a given day.
- (2) <u>Inherits from: Request</u>
- (3) Attributes:
  - a) RunwayConfigurationPlan plan (Mandatory)
    Runway configuration plan reflecting the requested updates.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

# 3.4.11.3. RunwayConfigurationPlanUpdateReply




Figure 3.79. RunwayConfigurationPlanUpdateReply Class Diagram

- (1) Reply to a <u>RunwayConfigurationPlanUpdateRequest</u>.
- (2) Special error conditions:
- (3) a) INVALID\_DATASET [Temporary error] If the FORECAST update was rejected due to D-1 forecast update cut-off or if the OPERATIONAL update was rejected due to D-1 plan not transferred yet.
  - b) CONFLICTING\_UPDATE [Permanent error] If the update failed due to incompatible concurrent changes.
  - c) OBJECT NOT FOUND [Permanent error] If the aerodrome is not known.
  - d) INVALID\_INPUT [Permanent error] If an unknown runway for this aerodrome is used, or if not all runways are specified for TACTICAL updated periods..
  - e) Note that there are also the INVALID\_INPUT replyStatus errors, that cover the errors detected by the backend (See <u>Transaction and Errors</u>). For example: errors when modifying the past (See Airspace Past)
- (4) Inherits from: Reply
- (5) Attributes:
  - a) RunwayConfigurationPlan plan (Mandatory)

    The complete runway configuration plan for a given aerodrome on a given day.

## 3.4.12. Hotspot List

#### 3.4.12.1. SOAP

(1) The associated SOAP operation is:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

HotspotListReply queryHotspots( HotspotListRequest request )

## 3.4.12.2. HotspotListRequest




Figure 3.80. HotspotListRequest Class Diagram

- (1) Request to retrieve for a given day and a hotspotKind, the hotspots for all traffic volumes and for all applicable durations or the hotspots for a given traffic volume for all applicable durations, or to retrieve the hotspots for a specific (traffic volume, duration) pair.
- (2) There exists 2 types of hotspots: LOCATION\_OF\_INTEREST hotspots and PROBLEM hotspots (see <a href="https://hotspots.nd">hotspots.nd</a>). Basically: Location of interest hotspots are used operationally to raise awarness about potential hotspots or problems.
- (3) LOCATION\_OF\_INTEREST hotspots hotspot lists are subject to authorization. PROBLEM hotspots are STAM related hotspots and are linked to a demand-capacity inbalance. PROBLEM hotspots are only accessible (authorized) during specific trials or on test platforms. Only PROBLEM hotspots are visible in flightlist and regulations.
- (4) Specific error conditions:
  - a) Permanent error: 0BJECT\_NOT\_FOUND reply status if the traffic volume is not known or if it is a traffic volume that does not have as reference location an airspace.
- (5) <u>Inherits from:</u> Request
- (6) Attributes:
  - a) Dataset dataset (Mandatory)
     Dataset for which the hotspot list is requested. See <u>Forecast and Operational Datasets</u>.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## b) <u>DateYearMonthDay</u> day (Mandatory)

Day for which the hotspot list is requested.

### c) <u>TrafficVolumeId</u> trafficVolume (Contextual)

The traffic volume for which the hotspot list is requested. If not present then all hotspots of hotspotKind are returned.

#### Presence:

- i) Optional in <u>HotspotListRequest</u>
- ii) Mandatory otherwise.

#### d) <u>DurationHourMinute</u> duration (Optional)

Selects the hotspots applying to the given traffic volume according to their duration. When not specified, all duration are considered.

<u>Constraint:</u> See <u>DURATION MUST BE 0001 WITH LOCATION OF INTEREST</u>

### e) **HotspotKind** hotspotKind (Mandatory)

The kind of hotspot.

Constraint: See DURATION MUST BE 0001 WITH LOCATION OF INTEREST

### (7) Constraint:

a)	Name	DURATION_MUST_BE_0001_WITH_LOCATION_OF_INTEREST
	Attributes	duration, hotspotKind
	Description	The duration must be 0001 when hotspotKind is LOCATION_OF_INTEREST.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manual FlowServices	B2B/23.0.0/Flow

## 3.4.12.3. HotspotListReply




Figure 3.81. HotspotListReply Class Diagram

- (1) Reply returned in response to <u>HotspotListRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) HotspotPlans plans (Mandatory)
    All hotspots for a given (traffic volume, duration) pair on a given day.

### 3.4.13. Hotspot Plan Update

#### 3.4.13.1. SOAP

(1) The associated SOAP operation is:

```
HotspotPlanUpdateReply updateHotspots(
HotspotPlanUpdateRequest request
)
```

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

## 3.4.13.2. HotspotPlanUpdateRequest




Figure 3.82. HotspotPlanUpdateRequest Class Diagram

- (1) Request to update the hotspot plans for a set of (traffic volume, duration) pairs on a given day.
- Note that the service is trial related (STAM): it is only accessible (authorized) during specific trials or on test platforms.
- (3) Note that the service includes Hotspot creation and Hotspot cancellation.
- (4) Specific error conditions:
  - a) Temporary error: INVALID\_DATASET reply status if the F0RECAST update was rejected due to D-1 forecast update cut-off or if the 0PERATIONAL update was rejected due to D-1 plan not transferred yet.
  - b) Permanent error: CONFLICTING\_UPDATE reply status if the update failed due to incompatible concurrent changes.
  - c) Permanent error: OBJECT\_NOT\_FOUND reply status if one of the traffic volumes is not known or if there is PROBLEM hotspot with a traffic volume that does not have as reference location an airspace.
  - d) Note that there are also the INVALID\_INPUT replyStatus errors, that cover the errors detected by the backend (See <u>Transaction and Errors</u>). For example: errors when modifying the past (See <u>Airspace Past</u>)
  - e) If errors are detected with at least one of the hotspot plans, then none of the hotspotplans are updated in NM systems.
- (5) <u>Inherits from:</u> Request
- (6) Attributes:
  - a) <u>HotspotPlans</u> plans (Mandatory)

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Hotspot plans reflecting the requested updates.

## 3.4.13.3. HotspotPlanUpdateReply

- (1) Reply returned in response to <u>HotspotPlanUpdateRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) **HotspotPlans** plans (Mandatory)

The complete hotspot plans for the given (traffic volume, duration) pairs on a given day, resulting from the update.

# 3.5. SimulationsService Port Type

#### **3.5.1. Overview**

#### 3.5.1.1. Introduction

- (1) This service is intended to provide querying and management capabilities of Simulations. The requests currently available are:
  - a) SimulationListRequest / SimulationListReply
  - b) <u>SimulationAvailabilityRequest</u> / <u>SimulationAvailabilityReply</u>
  - c) SimulationStartReguest / SimulationStartReply
  - d) SimulationStopRequest / SimulationStopReply

#### 3.5.1.2. Simulations

- (1) NM supports "flow simulation" features, where NM prepares simulations (airspace, traffic, strike scenarios). A simulation is basically a sandboxed environment containing some environment data, some traffic and a plan. It allows different actors to look at effects of a specific user scenario that is simulated and allows the different actors to interact with the simulation (for example: updating runway activations/sector configurations, regulations). In addition (selected) changes can be pushed back to the server.
  - There can be more than 1 such simulations ongoing at the same time, each evaluating different What-If scenarios. Each such simulation is identified by a simulationId.
- For this reason, the dataset types presented below are not limited to "forecast" and "operational" as indicated above, but include also "simulation" datasets. More details can be found below within the DatasetType and Dataset type descriptions.
- (3) There are 4 main type of simulations:
  - Simulations on OPERATIONAL: Such simulations are started with a snapshot of the data contained in OPERATIONAL. Flights and regulations are automatically loaded from the OPERA-

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

TIONAL dataset when such a simulation is started for the simulationPeriod (i.e. The period that is being simulated). The user can then modify regulations and reroutings and tactical updates and query the results via flightlist, counts, regulations list etc. Optionally the B2B user can compare the results (e.g. counts) of the simulation with the results on the reference dataset (i.e. the operational dataset itself).

- Simulations on FORECAST: Such simulations are started with a snapshot of the data contained in FORECAST. The user can then modify regulations and reroutings and tactical updates and query the results via flightlist, counts, regulations list etc. Optionally the B2B user can compare the results (e.g. counts) of the simulation with the results on the reference dataset (i.e. the forecast dataset itself).
- STANDALONE\_SIMEX: The simulation is a standalone SIMulation Experiment (SIMEX). Special
  future events are typically prepared and simulated on SIMEX with specially modified environment
  (CACD) data and forecasted traffic for a date in the future. These type of simulation are managed
  (start/stop) and prepared by NMOC for the other users (B2B and B2C) to have a look at the
  results. Optionally the B2B user can make changes to this STANDALONE\_SIMEX. There can
  be more than one STANDALONE\_SIMEX: NMOC can prepare multiple independent future
  events at the same time.
- Simulations on a STANDALONE\_SIMEX: Such simulations are started with a snapshot of the data contained in a STANDALONE\_SIMEX reference dataset. The user can then modify regulations and reroutings and tactical updates and query the results via flightlist, counts, regulations list etc. Optionally the B2B user can compare the results (e.g. counts) of the simulation with the results on the reference dataset (i.e. the STANDALONE\_SIMEX dataset itself).
- (4) A simulation can be managed by NMOC or by B2B (or NOP) users. For a NMOC managed simulation, the typical workflow is:
  - NMOC first starts and prepares a simulation.
  - The B2B user then queries the simulations currently running in NM systems (via the querySimulations service request). The result contains the details of the different simulations and the datasets of those simulations.
  - Then the B2B user can do counts, flightlist, regulation list, create or modify regulations or reroutings etc by specifying the dataset on which to do the requested operation.
- (5) For a simulation managed by the B2B client:
  - The B2B client first queries the available simulations that can be used to start a simulation. (via queryAvailableSimulations). There is only a limited pool of user managed simulations available.
  - If there are still simulations available, the B2B user Starts a new simulation on the desired reference: so either a simulation on OPERATIONAL or on FORECAST or or a STAN-DALONE\_SIMEX.
  - Once the user is done with the simulation, the simulation needs to be stopped (via stopSimulation) to make it available again for the next startSimulation request.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

(6) If for a simulation, the simulationPeriod (i.e. The period that is being simulated) is in the past, then counts, flightlist, etc can no longer retrieve any data (as e.g. flightlist and count querying expects the queried date to be inside of the reference data set period). So the simulation needs to be stopped. See also SimulationListRequest.

#### 3.5.2. Simulation List

#### 3.5.2.1. SOAP

(1) The associated SOAP operation is:

```
SimulationListReply querySimulations(
SimulationListRequest request
)
```

## 3.5.2.2. SimulationListRequest




Figure 3.83. SimulationListRequest Class Diagram

- (1) Request to guery the published simulations.
- (2) A simulation is basically a sandboxed environment containing some environment data, some traffic and a plan. It allows different actors to look at effects of a specific user scenario that is simulated and allows the different actors to interact with the simulation (for example: updating runway activations/sector configurations, regulations). In addition (selected) changes can be pushed back to the server.
- (3) Simulations can be started via B2C and/or B2B and/or by NMOC.
- When an NMOC user starts a simulation, the NMOC user can decide to publish the simulation (i.e. make the simulation accessable via B2C and B2B). The simulation remains accessible via B2C and B2B until the simulation is unpublished or until the simulation is stopped.
- When a simulation is started via B2C and/or B2B, then that simulation is considered always published (accessible via B2C and B2B) until the simulation is stopped via B2C or B2B.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- (6) A simulation typically is based on a reference: starting the simulation implies copying all the flight, regulation, environment, and tactical-updates related data into the simulation from a reference dataset: typically operational or forecast. This is the reference from which the data has been loaded. The user can then, after having created or modified some regulations or reroutings, compare the results with the data in the reference dataset.
- (7) There is a limited number of simulation engines available for the users to start and stop. The user needs to stop a simulation after having started it, in order to make the simulation engine available again for the users.
- (8) A simulation only support processing one request in parallel. So the B2B user should serialise the simulation requests (e.g. counts and flightlist and regulation creations and...).
- (9) See also general text on simulations.
- (10) <u>Inherits from: Request</u>
- (11) Attributes:
  - a) SimulationId retrieveFilter (Optional)
    Retrieves the simulation corresponding to a specific simulation. By default all simulations are returned.
  - b) <u>DatasetReference</u> datasetReference (Optional)

    Retrieves the simulation corresponding to a specific reference data set. By default all simulations are returned.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manual FlowServices	B2B/23.0.0/Flow

# 3.5.2.3. SimulationListReply




Figure 3.84. SimulationListReply Class Diagram

- (1) Reply returned in response to <u>SimulationListRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Set<Simulation> simulations (Optional)
     Set of simulations that matched the SimulationListRequest criteria.
     Can be empty (meaning that no simulation matched the criteria).
     Constraint: Size must be comprised between 0 and ∞.

### 3.5.3. Simulation Availability List

## 3.5.3.1. SOAP

(1) The associated SOAP operation is:

```
SimulationAvailabilityReply queryAvailableSimulations(
SimulationAvailabilityRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.5.3.2. SimulationAvailabilityRequest




Figure 3.85. SimulationAvailabilityRequest Class Diagram

- (1) Request to query the available (user managed) simulation engines that can be used to start a simulation.
- (2) <u>Inherits from:</u> Request
- (3) Attributes:
  - a) <u>DatasetReference</u> datasetReference (Optional)

Retrieves the available user managed simulations corresponding to a specific reference data set.

By default all available user\_managed simulations are returned

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.5.3.3. SimulationAvailabilityReply




Figure 3.86. SimulationAvailabilityReply Class Diagram

- (1) Reply returned in response to <u>SimulationAvailabilityRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Map<<u>DatasetReference</u>, Set<<u>SimulationAvailability</u>>> simulationAvailabilities (Optional)

The simulation availability per reference dataset. Constraints:

- i) Size must be comprised between 0 and  $\infty$ .
- ii) Item size must be comprised between 0 and ∞.

#### 3.5.4. Simulation Start

#### 3.5.4.1. SOAP

(1) The associated SOAP operation is:

```
SimulationStartReply startSimulation(
SimulationStartRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.5.4.2. SimulationStartRequest




Figure 3.87. SimulationStartRequest Class Diagram

- (1) Request to start a UserManagedSimulation based on a reference.
- (2) All environment (CACD) data, tactical updates, flights and measures are initially loaded from the reference.
- (3) Note that, once the flights have been loaded into the simulation, the flighs are not updated, except for timers related events (like terminating the flights when they should have landed) and actions done in the similation (like creating or modifying regulations or rerouting). So new radar info or flight Update related info is not processed in the simulation.
- Note that starting the simulation and loading the flights can take some time. (typically around 30 seconds to 1 minute)
- Note that when the user is done with the simulation, the user needs to use the StopSimulation service to free the simulation again.
- (6) <u>Inherits from:</u> Request
- (7) <u>Attributes:</u>
  - a) <u>UserManagedSimulation</u> newSimulation (Mandatory)

The simulation to start.

The reference dataset shall indicate the reference for the new simulation.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 3.5.4.3. SimulationStartReply




Figure 3.88. SimulationStartReply Class Diagram

- (1) Reply returned in response to <u>SimulationStartRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) <u>UserManagedSimulation</u> startedSimulation (Mandatory)
  - 3.5.5. Simulation Stop
  - 3.5.5.1. SOAP
- (1) The associated SOAP operation is:

```
SimulationStopReply stopSimulation(
SimulationStopRequest request
)
```

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

# 3.5.5.2. SimulationStopRequest




Figure 3.89. SimulationStopRequest Class Diagram

- (1) Request to stop a user\_managed\_simulation. This will free the simulation and make it available to start again.
- Note that stopping a simulation can take some time (typically around 1 or 2 minutes).
- (3) <u>Inherits from: Request</u>
- (4) <u>Attributes:</u>
  - a) Dataset simulation (Mandatory)
    The dataset of the UserManagedSimulation that needs to be stopped.
    Constraint: See INVALID\_SIMULATION\_TYPE

## (5) Constraint:

a)	Name	INVALID_SIMULATION_TYPE
	Attribute	simulation
	· •	The simulationType needs to be set to UserManagedSimulation in stop Simulation.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.5.5.3. SimulationStopReply




Figure 3.90. SimulationStopReply Class Diagram

- (1) Reply returned in response to <u>SimulationStopRequest</u>.
- (2) Inherits from: Reply

# 3.6. Scenario Repository Port Type

#### 3.6.1. Overview

#### 3.6.1.1. Introduction

- This service is intended to provide querying and update capabilities on the ScenarioRepository. The requests currently available are:
  - a) <u>ScenarioRegulationRetrievalReguest</u> / <u>ScenarioRegulationRetrievalReply</u>
  - b) <u>ScenarioReroutingRetrievalRequest</u> / <u>ScenarioReroutingRetrievalReply</u>
  - c) <u>ScenarioMCDMOnlyRetrievalRequest</u> / <u>ScenarioMCDMOnlyRetrievalReply</u>
  - d) <u>ScenarioListRequest</u> / <u>ScenarioListReply</u>

#### 3.6.1.2. Scenario Repository

(1) The scenario repository contains pre-defined (and pre-agreed) solutions to handle an overload: scenarios.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- (2) Typically the solutions make the flight reroute horizontally or vertically to avoid a congested airspace.
- (3) To handle an overload an FMP can decide to either regulate the concerned traffic volume(s) or the FMP can implement one or more FL or RR type scenarios.
- (4) Those scenarios contain a zero rate suspending regulation "forcing" the flights to reroute outside of the congested airspace. Those scenarios also contain a rerouting. The rerouting allows to evaluate the impact of applying the 0 rate suspending regulation: applying the rerouting shows how the flights are expected to fly.
- Note it is the Airspace user that decides how he will file to avoid the congested airspace. The rerouting gives a possible way to reroute: it represents the most likely or most efficient way for the flights to reroute.
- (6) STAM scenario typically contain only cherry picked rerouting. When applied, the Airspace User receives from NM systems an RRN message indicating that airspace user should reroute. In this STAM case, the flights are not suspended.
- Note that a scenario can have multiple measures: for example a contingency scenario contains multiple measures (on different traffic volumes) that can be used to handle the contingency. When such a scenario is applied one or more measures of the scenario are applied (but not necessarily all measures of the scenario).
- (8) The scenario from the scenario repository are published to the external users (AO, FMP,..) via the public portal and via B2B.
- (9) The scenario allow airspace users to have an idea how to refile and it allows FMP to know where the typical on-load and off-load areas are in case he scenario is applied.
- (10) The B2B user can query, via flightlist and traffic count, the applicableScenarios for a problem traffic volume (e.g. "overloaded").
  The result will include all the different scenarios (on different traffic volumes) that can off-load the problem traffic volume.
- The <u>queryScenarioRepository</u> service request can be used to retrieve the details about the scenarios.
- (12) The <u>retrieveRegulationsFromScenario</u> and <u>retrieveReroutingsFromScenario</u> service requests can then be used to retrieve the applicable measures themselves from these scenarios.
- (13) The scenario regulations can then be applied via B2B in:
  - A NM simulation (to evaluate the impact) via the <u>createRegulation</u> service request for a simulation dataset
  - or can be requested for implementation in FORECAST or in OPERATIONAL via the <u>fileRegulationProposal</u> service request.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- (14) The scenario rerouting can then be applied via B2B in:
  - A NM simulation (to evaluate the impact) via the <u>createRerouting</u> service request for a simulation dataset.
  - FORECAST or in OPERATIONAL via <u>createRerouting</u> service: only supported for cherry picked rerouting (e.g. STAM type scenario) with a scenario reference pointing to an existing scenario measure Note that in that case, the traffic volume of the rerouting needs to match the traffic volume of the scenario measure.
- Note that in specific trial contexts, NM test systems can be configured to also accept creating any type of rerouting in FORECAST or OPERATIONAL.
- (16) Note that the scenario repository is shared between FORECAST and OPERATIONAL. So when querying the scenario repository, it will return the same result for FORECAST or OPERATIONAL or any simulation that has as reference forecast or operational.

### 3.6.2. Retrieve list of Regulations from Scenario

#### 3.6.2.1. SOAP

(1) The associated SOAP operation is:

```
ScenarioRegulationRetrievalReply retrieveRegulationsFromScenario(
ScenarioRegulationRetrievalRequest request
)
```

### 3.6.2.2. ScenarioRegulationRetrievalRequest




Figure 3.91. ScenarioRegulationRetrievalReguest Class Diagram

- (1) Request to retrieve the regulation(s) contained in scenario from the scenario repository.
- (2) <u>Inherits from: ScenarioMeasureRetrievalRequest</u>
- (3) Attributes:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

a) Set<RegulationField> requestedRegulationFields (Mandatory)
The reply returns only the requested regulation fields in this set, and only if the values of these requested fields are available at NM. Note that the regulation id is always returned.

Constraint: Size must be comprised between 0 and 24.

### 3.6.2.3. ScenarioRegulationRetrievalReply




Figure 3.92. ScenarioRegulationRetrievalReply Class Diagram

- (1) Reply returned in response to <u>ScenarioRegulationRetrievalRequest</u>.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Set<Regulation> regulations (Mandatory)
    Constraint: Size must be comprised between 0 and ∞.

#### 3.6.3. Retrieve list of Reroutings from Scenario

#### 3.6.3.1. SOAP

(1) The associated SOAP operation is:

```
ScenarioReroutingRetrievalReply retrieveReroutingsFromScenario(
ScenarioReroutingRetrievalRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.6.3.2. ScenarioReroutingRetrievalRequest




Figure 3.93. ScenarioReroutingRetrievalRequest Class Diagram

- (1) Request to retrieve rerouting contained in scenario from the scenario repository.
- (2) <u>Inherits from: ScenarioMeasureRetrievalRequest</u>
- (3) Attributes:
  - a) Set<ReroutingField> requestedReroutingFields (Mandatory)
    The reply returns only the requested rerouting fields in this set, and only if the values of these requested fields are available at NM. Note that the regulation id is always returned.

    Constraint: Size must be comprised between 0 and 18.

### 3.6.3.3. ScenarioReroutingRetrievalReply




Figure 3.94. ScenarioReroutingRetrievalReply Class Diagram

- (1) Reply to a <u>ScenarioReroutingRetrievalRequest</u>.
- (2) Inherits from: Reply

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

### (3) Attributes:

a) Set<Rerouting> reroutings (Mandatory)
Constraint: Size must be comprised between 0 and ∞.

#### 3.6.4. Retrieve list of MCDMOnly from Scenario

#### 3.6.4.1. SOAP

(1) The associated SOAP operation is:

```
ScenarioMCDMOnlyRetrievalReply retrieveMCDMOnlyFromScenario(
ScenarioMCDMOnlyRetrievalRequest request
)
```

### 3.6.4.2. ScenarioMCDMOnlyRetrievalRequest




Figure 3.95. ScenarioMCDMOnlyRetrievalRequest Class Diagram

- (1) Request to retrieve the MCDM-only measures contained in scenario from the scenario repository (See also MCDMOnlyRetrievalRequest).
- (2) <u>Inherits from: ScenarioMeasureRetrievalRequest</u>
- (3) Attributes:
  - a) Set<MCDMOnlyField> requestedMCDMOnlyFields (Mandatory)
    The reply returns only the requested MCDM only fields in this set, and only if the values of these requested fields are available at NM.
    Constraint: Size must be comprised between 0 and 24.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.6.4.3. ScenarioMCDMOnlyRetrievalReply




Figure 3.96. ScenarioMCDMOnlyRetrievalReply Class Diagram

- (1) Reply to the scenario MCDM only retrieval.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Set<MCDMOnly> mcdmOnlySet (Mandatory)
    Constraint: Size must be comprised between 0 and ∞.
  - 3.6.5. List of Scenarios
  - 3.6.5.1. SOAP
- (1) The associated SOAP operation is:

```
ScenarioListReply queryScenarioRepository(
ScenarioListRequest request
)
```

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### 3.6.5.2. ScenarioListRequest




Figure 3.97. ScenarioListRequest Class Diagram

- (1) Request to guery the scenario and the scenario attributes from the scenario repository.
- (2) <u>Inherits from:</u> Request
- (3) Attributes:
  - a) Dataset dataset (Mandatory)
    Dataset for which the scenario list is requested. See Forecast and Operational Datasets.
  - b) **DateTimeSecond scenarioModifiedSince** (Optional) Selects scenario only that have been modified since this time.
  - c) Set<<u>TrafficVolumeId</u>> concerningTrafficVolumes (Optional)
    Selects scenario only with a traffic volume that matches an entry in this set.
    Constraint: Size must be comprised between 0 and ∞.
  - d) Set<ScenarioId> fromScenarios (Optional)
     Selects only scenario that matches an entry in this set.
     Constraint: Size must be comprised between 0 and ∞.
  - e) Set<ScenarioName> fromPublicationIds (Optional) Selects only scenario that matches an entry in this set.
    Constraint: Size must be comprised between 0 and ∞.
  - f) Set<AirNavigationUnitId> ownerFMPs (Optional)
    Selects scenario only with a owner (FMP) that matches an entry in this set.
    Constraint: Size must be comprised between 0 and ∞.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 3.6.5.3. ScenarioListReply




Figure 3.98. ScenarioListReply Class Diagram

- (1) Reply to the query scenario attributes from the scenario repository.
- (2) <u>Inherits from:</u> Reply
- (3) Attributes:
  - a) Set<<u>ScenarioAttributes</u>> attributes (Optional)
     List of scenario attributes.

     Constraint: Size must be comprised between 0 and ∞.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

# **Chapter 4. Data Types**

### 4.1. AerodromeLocation

- (1) Aerodrome location.
- (2) <u>Inherits from: Location</u>.

# 4.2. AirspaceLocation

- (1) Airspace location.
- (2) <u>Inherits from: Location</u>.

## 4.3. AllFlightsLocation

- (1) All flights location.
- (2) Inherits from: Location.

## 4.4. ANDedReroutingConstraints

- (1) Describes a set of rerouting constraints that are ANDed together.
- (2) Attributes:
  - a) Set<ReroutingConstraint> constraints (Mandatory)
     A list of ordered rerouting constraints that apply to the reroutings (can be empty).
     Constraint: Size must be comprised between 0 and ∞.
- (3) <u>Used by: ReroutingSourcesAndConstraints.</u>

### 4.5. AoLocation

- (1) Aircraft operator location.
- (2) Inherits from: Location.

### 4.6. ATFCMSituationCounts

- (1) ATFCM situation counts.
- (2) Attributes:
  - a) <u>CountsValue</u> nrLandedTraffic (Mandatory)

Number of flights which are landed.

Includes all flights whose status is either ATC terminated, TACT terminated, expecting FSA, or TACT terminated without expecting FSA.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### b) <u>CountsValue</u> nrAirborneTraffic (Mandatory)

Number of flights which are airborne.

Includes all flights whose status is either ATC activated, TACT activated expecting FSA, or TACT activated without expecting FSA.

- c) <u>CountsValue</u> nrExpectedTraffic (Mandatory)
  Number of flights that have not taken off as of <u>ATFCMSituationReply.lastUpdated</u>.
- d) <u>CountsValue</u> nrFlightsUndefinedSlotCompliance (Mandatory) Includes all regulated and not suspended flights for which slot compliance information is not known.
- e) <u>CountsValue</u> nrFlightsDepBeforeSlot (Mandatory) Includes all regulated and not suspended flights whose ATOT is before (CTOT-5) minutes.
- f) CountsValue nrFlightsCompliedWithSlot (Mandatory)
  Includes all regulated and not suspended flights whose ATOT is either at or between (CTOT-5) and (CTOT+10) minutes.
- g) <u>CountsValue</u> nrFlightsDepAfterSlot (Mandatory)
  Includes all regulated and not suspended flights whose ATOT is after (CTOT+10) minutes.
- h) CountsValue suspendedFlightsDueToATFMMeasure (Mandatory)
  Number of flights which are suspended due to an ATFM measure.
  Includes all suspended flights whose suspension status is either REGULATION\_CONFIRM-ATION or TRAFFIC\_VOLUMES\_CONDITION.
- i) CountsValue suspendedFlightsDueToFAM (Mandatory)
   Number of flights which are suspended due to FAM.
   Includes all suspended flights whose suspension status is NOT\_REPORTED\_AS\_AIR-BORNE.
- j) <u>CountsValue</u> flightsDelayedByMoreThan30Min (Mandatory) Number of flights which are delayed by more than 30 minutes.
- (3) <u>Used by: ATFCMSituationReply</u>.

## 4.7. ATFCMSituationDelays

- (1) ATFCM situation delays.
- (2) Attributes:
  - a) LongDurationHourMinute enRouteDelay (Mandatory)
    Includes all regulated and not suspended flights which are subject to a most penalising regulation whose reference location is not an airport or a set of airports.
  - b) LongDurationHourMinute airportDelay (Mandatory)
    Includes all regulated and not suspended flights which are subject to a most penalising regulation whose reference location is an airport or a set of airports.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

c) Map<<u>RegulationReason</u>, <u>LongDurationHourMinute</u>> delaysPerRegulation-Reason (Mandatory)

Total delays per regulation reasons.

Constraint: Size must be comprised between 1 and 15.

(3) <u>Used by: ATFCMSituationReply.</u>

## 4.8. ATFCMSituationRegulation

- (1) Regulation in ATFCM situation.
- (2) Attributes:
  - a) RegulationId regulationId (Mandatory) Regulation unique identifier.
  - b) **DateTimeMinutePeriod period** (Mandatory) Period.
  - c) <u>TrafficVolumeId</u> trafficVolumeId (Mandatory)
    Traffic volume id.
  - d) RegulationState regulationState (Mandatory) Regulation state.
  - e) RegulationReason regulationReason (Mandatory) Regulation reason.
  - f) LongDurationHourMinute delay (Mandatory)
    Total delay due to the regulation.
  - g) CountsValue nrImpactedFlights (Mandatory)
    Number of flights which are impacted by the regulation.
  - h) AerodromeICAOId protectedAerodrome (Optional)
    The protected aerodrome of the regulation.
- (3) Used by: DeltaATFCMSituationRegulation, ATFCMSituationReply.

# 4.9. <<enumeration>> AvoidAirspaceReroutingKind

- (1) Enumeration of possible Avoid Airspace Kinds.
- (2) Values:
  - a) **HORIZONTAL**
  - b) **VERTICAL**
- (3) <u>Used by: AvoidViaAirspaceReroutingConstraint.</u>

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

# 4.10. AvoidViaAirspaceReroutingConstraint

- (1) Describes a manual rerouting constraint to avoid an airspace or to force the flights to cross an airspace. The AvoidViaAirspaceReroutingConstraint applies to both horizontal and vertical rerouting constraints.
- (2) <u>Inherits from: ReroutingConstraint.</u>
- (3) Attributes:
  - a) AvoidViaReroutingType type (Mandatory)
    The kind of restriction.
  - b) **AirspaceId location** (Mandatory) The airspace identifier.
  - c) AvoidAirspaceReroutingKind avoidKind (Optional)

    If it concerns an avoid airspace rerouting constraint, indicates how the airspace is to be avoided (horizontally or vertically) If not present, then the default is used: if the vertical (or speed) rerouting source is used, then defaults to Vertical otherwise horizontal. Note the typical use case is: a vertical roerouting that sometimes has to change horizontally.

# 4.11. AvoidViaPointReroutingConstraint

- (1) Describes a manual rerouting constraint to avoid a point or to force the flights to cross point. This type of constraint only applies for horizontal rerouting constraints.
- (2) Inherits from: ReroutingConstraint.
- (3) Attributes:
  - a) AvoidViaReroutingType type (Mandatory)
    The kind of restriction.
  - b) **DBEOrPublishedPointId location** (Mandatory) The point identifier.

# 4.12. <<enumeration>> AvoidViaReroutingType

- (1) Enumerates the two possible AvoidVia rerouting constraint types: AVOID and VIA.
- (2) <u>Values:</u>
  - a) AVOID
  - b) VIA
- (3) Used by: AvoidViaPointReroutingConstraint, AvoidViaAirspaceReroutingConstraint.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 4.13. typedef<int> Capacity

- (1) Capacity on a traffic volume, expressed as a number of flights per hour.
- (2) Range: [0,998[.
- (3) Used by: PlannedCapacity.

## 4.14. CapacityPlans

- (1) Capacity plans for one or more traffic volumes on a given day.
- (2) A capacity plan is a special plan in the sense that, there can be cases where no capacity is defined in CACD. So there exist traffic volumes for which the capacity is not known at all or not known for some periods.
- (3) In addition, regulation measures can overrule the capacity values defined (either in CACD or by the B2B update capacity service). This (optional) overruling regulation info can be found back in the nmSchedule attribute. However in the client schedule the non regulated capacities are maintained (just in case the regulation can be cancelled before the end of its applicability period).
- (4) In a retrieval context, the plan is said to be 'complete' in the sense that it contains all the plan entries from all involved data sources (including NO\_DATA data source in case no info is known).
- (5) In an update context, the plan can be complete (if the B2B client designer decided to overwrite the default CACD values) or limited to the (full list) of (pre-)tactical updates with the gaps marked as AIRSPACE datasource (to obtain a complete time partition).
- (6) In any case, periods in the time partition marked as AIRSPACE datasource correspond to removing any potential (pre-)tactical update and hence reset the corresponding values to the CACD definition for that period.
- (7) Inherits from: <u>TacticalConfigurationPlan</u>.
- (8) <u>Attributes:</u>
  - a) Map<<u>TrafficVolumeId</u>, <u>PlannedCapacities</u>> tvCapacities (Mandatory) Constraints:
    - i) Size must be comprised between 0 and  $\infty$ .
    - ii) See <u>INCOMPLETE SCHEDULE</u>
- (9) Constraint:

a)	Name	INCOMPLETE_SCHEDULE
	Attribute	tvCapacities
	-	tvCapacities has gaps and/or overlaps in the time partition or is not covering exactly one day.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

(10) <u>Used by: CapacityPlanRetrievalReply, CapacityPlanUpdateReply, CapacityPlanUpdateRequest.</u>

## 4.15. CherryPickedLocation

- (1) Cherry picked location.
- (2) Inherits from: Location.

#### **4.16.** Counts

- (1) Container for traffic counts values, for a given <u>DateTimeMinutePeriod</u> and <u>TrafficType</u>.
- (2) Attributes:
  - a) <u>CountsValue</u> totalCounts (Mandatory)
    Total traffic counts.
  - b) Map<<u>FlowId</u>, <u>CountsValue</u>> flowCounts (Optional)

Traffic counts by flow.

This attribute is set only when requested (i.e., <u>TrafficCountsByTrafficVolumeRequest.computeFlowCounts</u> has been set to true)

Note that if there are more than 50 flows (e.g. in case of scenario flow counts), then only the first 50 are shown here while <u>TrafficCountsReply.flows</u> does show them all. <u>Constraint:</u> Size must be comprised between 0 and 50.

c) Map<<u>SubTotalsTrafficCountsType</u>, <u>CountsValue</u>> subTotalsCounts (Optional) Sub total traffic counts.

This attribute is set only when requested (i.e., <u>TrafficCountsRequest.computeSub-Totals</u> has been set to true)

Constraint: Size must be comprised between 7 and 7.

(3) <u>Used by: TrafficCountsReplyData</u>.

# 4.17. <<enumeration>> CountsCalculationType

- (1) Enumeration of possible counts calculation type.
- (2) <u>Values:</u>
  - a) ENTRY

Only flights taking off and/orlanding, or being over a point, or entering a sector in the trafficWindow are considered.

- b) **OCCUPANCY** 
  - Only flights occupying a sector or being airborne in the trafficWindow are considered.
- (3) <u>Used by:</u> <u>FlightListByAircraftOperatorRequest</u>, <u>LoadStateAtReferenceLocation</u>, <u>CountsCalculationTypeAndInterval</u>, <u>TrafficCountsByAircraftOperatorRequest</u>, <u>TrafficCountsByAirspaceRequest</u>,

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

FlightListRequest, FlightListByTrafficVolumeRequest, FlightListByAirspaceRequest, TrafficCounts-ByTrafficVolumeRequest.

## 4.18. CountsCalculationTypeAndInterval

(1)

#### (2) Attributes:

- a) <u>CountsCalculationType</u> calculationType (Mandatory) Indicates what is the calculation type of the count (entry or occupancy).
- b) <u>DurationHourMinute</u> duration (Mandatory)
  Specifies the duration used to calculate the counts (or the duration used to calculate the flightlist corresponding to those counts): each count period, concerns a period of duration.
- c) <u>DurationHourMinute</u> step (Mandatory)
  Specifies the every x minutes a count need to be done: determines how many counts are returned for a requested period. It also determines the rounding of the trafficWindow.
- (3) <u>Used by: NetworkImpactAssessmentRetrievalReply.</u>

#### 4.19. CountsInterval

- (1) Description what is the interval that is used to compute the counts / flight list.
- (2) For ENTRY counts, the typical value is: show counts every 20 minutes and each count period has a duration of 60 minutes.
- (3) For OCCUPANCY counts, the step is typically 1 minute while the duration can vary (depending on the location)
- (4) Attributes:
  - a) <u>DurationHourMinute</u> duration (Mandatory)

Specifies the duration used to calculate the counts (or the duration used to calculate the flightlist corresponding to those counts): each count period, concerns a period of duration. So if a user does a TrafficCounts request with a trafficWindow from [10:00,10:01[ with a countsInterval with step 1 and duration 10 minutes, the single count period returned has a duration of 10 minutes ([10:00,10:10[).

A duration of 1 minute, means that no extension of the trafficWindow is done. Constraints:

- i) See <u>INVALID COUNTS INTERVAL</u>
- ii) See INVALID DURATION RANGE
- b) <u>DurationHourMinute</u> step (Mandatory)

Specifies the every x minutes a count need to be done: determines how many counts are returned for a requested period. It also determines the rounding of the trafficWindow.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

So if a user does a TrafficCounts request with a trafficWindow from [09:59,11:20[ with a countsInterval with step 20 and duration 60 minutes, the 5 count periods returned are ([09:40,10:40[,[10:00,11:00[,[10:20,11:20[,[10:40,11:40[,[11:00,12:00[).]]]]]) This corresponds to an effectiveTrafficWindow of [09:40, 12:00[:flights from within this periods have been considered in the counts.

Note that the start of the count periods is rounded to a multiple of step. Constraints:

- i) See <a href="INVALID\_COUNTS\_INTERVAL">INTERVAL</a>
- ii) See <a href="INVALID\_STEP\_RANGE">INVALID\_STEP\_RANGE</a>

#### (5) Constraints:

a)	Name	INVALID_DURATION_RANGE
	Attribute	duration
	Description	The allowed duration value must be between 1 minute (0001) and 24 hours (2400).

b)	Name	INVALID_STEP_RANGE
	Attribute	step
	-	The allowed step value must be between 1 minute (0001) and 24 hours (2400) and must be a divisor of 24 hours.

c)	Name	INVALID_COUNTS_INTERVAL
	Attributes	duration, step
	Description	The duration must be a multiple of step.

(6) Used by: FlightListByLocationRequest, TrafficCountsRequest.

# 4.20. typedef<int> CountsValue

- (1) Range: [0,100000].
- (2) <u>Used by: DeltaATFCMSituationRegulation, ScenarioImpact, SignificantDeltaCount, ATFCMSituationCounts, Counts, ATFCMSituationRegulation, DeltaCounts.</u>

### 4.21. DatasetReference

(1) A simulation can be based on a reference (i.e. from which environment data has been copied and where initially the flights and measures have been copied from). This DataSetReference class represents these references.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- For a simulation based on a STANDALONE\_SIMEX reference, then <a href="type">type</a> must be STAN-DALONE\_SIMEX and the simulationId must be value of <a href="simulationIdentifier.SimulationId">SimulationIdentifier.SimulationId</a>.
- (3) For a simulation based on a OPERATIONAL/FORECAST reference, then <u>type</u> must be OPER-ATIONAL/FORECAST and the simulationId is not allowed.
- (4) Attributes:
  - a) **DatasetReferenceType type** (Mandatory) The type of reference dataset.
  - b) **SimulationId simulationId** (Optional)

The <u>StandaloneSimex</u> simulation identifier on which a <u>UserManagedSimulation</u> or a <u>NMOCManagedSimulation</u> is based

For a simulation based on a STANDALONE\_SIMEX reference, the simulationId is value of SimulationIdentifier.SimulationId.

For a simulation based on a OPERATIONAL/FORECAST reference, the simulationId is not allowed.

Constraint: See INVALID SIMULATION ID

#### (5) Constraint:

a)	Name	INVALID_SIMULATION_ID
	Attribute	simulationId
	•	Invalid Simulation Id. If the type is STANDALONE_SIMEX then simulationId should not be null.

(6) <u>Used by: NMOCManagedSimulation, SimulationAvailabilityRequest, SimulationListRequest, SimulationAvailabilityReply, UserManagedSimulation.</u>

# 4.22. <<strict enumeration>> DatasetReferenceType

- (1) Possible reference dataset types for simulations.
- (2) Values:
  - a) **FORECAST**
  - b) **OPERATIONAL**
  - c) **STANDALONE SIMEX**
- (3) Used by: DatasetReference.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 4.23. DelayLocation

- (1) Delay location.
- (2) <u>Inherits from: Location</u>.

### 4.24. DeltaATFCMSituation




Figure 4.1. DeltaATFCMSituation Class Diagram

- (1)
- (2) Attributes:
  - a) **DeltaATFCMSituationCounts countsChanges** (Mandatory) ATFCM situation counts.
  - b) <u>DeltaATFCMSituationDelays</u> delaysChanges (Mandatory) ATFCM situation delays.
  - c) Set<<u>DeltaATFCMSituationRegulation</u>> regulationsChanges (Optional)
     ATFCM situation regulations.
     <u>Constraint:</u> Size must be comprised between 0 and ∞.
- (3) <u>Used by: NetworkImpactAssessmentRetrievalReply.</u>

### 4.25. DeltaATFCMSituationCounts

- (1) Delta ATFCM situation counts.
- (2) <u>Attributes:</u>
  - a) SignificantDeltaCount nrLandedTraffic (Mandatory)
     Number of flights which are landed.
     Includes all flights whose status is either ATC terminated, TACT terminated, expecting FSA, or TACT terminated without expecting FSA.
  - b) **SignificantDeltaCount nrAirborneTraffic** (Mandatory) Number of flights which are airborne.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Includes all flights whose status is either ATC activated, TACT activated expecting FSA, or TACT activated without expecting FSA.

- c) <u>SignificantDeltaCount</u> nrExpectedTraffic (Mandatory)
  Number of flights that have not taken off as of <u>ATFCMSituationReply.lastUpdated</u>.
- d) <u>SignificantDeltaCount</u> nrFlightsUndefinedSlotCompliance (Mandatory) Includes all regulated and not suspended flights for which slot compliance information is not known.
- e) <u>SignificantDeltaCount</u> nrFlightsDepBeforeSlot (Mandatory) Includes all regulated and not suspended flights whose ATOT is before (CTOT-5) minutes.
- f) SignificantDeltaCount nrFlightsCompliedWithSlot (Mandatory) Includes all regulated and not suspended flights whose ATOT is either at or between (CTOT-5) and (CTOT+10) minutes.
- g) **SignificantDeltaCount nrFlightsDepAfterSlot** (Mandatory) Includes all regulated and not suspended flights whose ATOT is after (CTOT+10) minutes.
- h) <u>SignificantDeltaCount</u> suspendedFlightsDueToATFMMeasure (Mandatory) Number of flights which are suspended due to an ATFM measure. Includes all suspended flights whose suspension status is either REGULATION\_CONFIRM-ATION or TRAFFIC\_VOLUMES\_CONDITION.
- i) SignificantDeltaCount suspendedFlightsDueToFAM (Mandatory) Number of flights which are suspended due to FAM. Includes all suspended flights whose suspension status is NOT\_REPORTED\_AS\_AIR-BORNE.
- j) <u>SignificantDeltaCount</u> flightsDelayedByMoreThan30Min (Mandatory) Number of flights which are delayed by more than 30 minutes.
- (3) Used by: DeltaATFCMSituation.

# 4.26. DeltaATFCMSituationDelays

- (1) Delta ATFCM situation delays.
- (2) <u>Attributes:</u>
  - a) SignificantDeltaDuration enRouteDelay (Mandatory)
    Includes all regulated and not suspended flights which are subject to a most penalising regulation whose reference location is not an airport or a set of airports.
  - b) <u>SignificantDeltaDuration</u> airportDelay (Mandatory) Includes all regulated and not suspended flights which are subject to a most penalising regulation whose reference location is an airport or a set of airports.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

c) Map<<u>RegulationReason</u>, <u>SignificantDeltaDuration</u>> delaysPerRegulation-Reason (Mandatory)

Total delays per regulation reasons.

Constraint: Size must be comprised between 1 and 15.

(3) <u>Used by: DeltaATFCMSituation</u>.

## 4.27. DeltaATFCMSituationRegulation

- (1) Compares a before and after situation and indicates if the change is significant. An insignificant change is a change that is considered not relevant.
- (2) Attributes:
  - a) <u>ATFCMSituationRegulation</u> afterSituation (Mandatory)
  - b) LongDurationHourMinute delayBefore (Mandatory)
    Total delay due to the regulation before the change.
  - c) <u>CountsValue</u> numberOfImpactedFlightsBefore (Mandatory)
    Number of flights which were impacted by the regulation before the change.
  - d) boolean isSignificantChange (Mandatory)
- (3) Used by: DeltaATFCMSituation.

#### 4.28. DeltaCounts

- (1) Compares a before and after situation and represent the differences (counts and OTMV alerts) between the before and after situation for a certain TV with a CountsCalculationTypeAndInterval for a certain count period.
- (2) Attributes:
  - a) Set<<u>OtmvAlert</u>> otmvAlertsBefore (Mandatory) Constraint: Size must be comprised between 0 and ∞.
  - b) Set< $\frac{0 \text{tmvAlert}}{}$  otmvAlertsAfter (Mandatory) Constraint: Size must be comprised between 0 and  $\infty$ .
  - c) <u>CountsValue</u>[] countsBefore (Mandatory) <u>Constraint:</u> Size must be comprised between 0 and ∞.
  - d) <u>CountsValue[]</u> countsAfter (Mandatory) <u>Constraint:</u> Size must be comprised between 0 and ∞.
- (3) <u>Used by:</u> <u>NetworkImpactAssessmentRetrievalReply</u>.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 4.29. DeltaLevelReroutingConstraint

- (1) Describes a delta level rerouting constraint.
- (2) <u>Inherits from:</u> <u>ReroutingConstraint</u>.
- (3) Attributes:
  - a) **DBEOrPublishedPointId pointId** (Mandatory)
  - b) **int deltaFlightLevel** (Mandatory) Constraint: Range: [-998,998[.

## 4.30. ExcludeReIncludeFlightInRegulation

- (1) Allows to exclude or re-include a flight in 1 or more regulations.
- (2) Attributes:
  - a) Set<RegulationId> excludeFromRegulations (Mandatory)
     Regulations to additionally exclude or re-include.
     Constraint: Size must be comprised between 1 and 20.
  - b) boolean flightProposal (Mandatory)
    Determines if the flight is to be excluded/re-included as a proposal or not.
    Typically in simulations, one would exclude directly while in operational dataset context, one needs to submit a proposal for NMOC to review.
- (3) <u>Used by: UpdateFlightInMeasureChoice</u>.

# 4.31. FlightAtfcmMcdmOnlyLocation

- (1) Flight ATFCM MCDM only location.
- (2) <u>Inherits from: FlightAtfcmMeasureLocation</u>.
- (3) Attributes:
  - a) RegulationId mcdmOnlyMeasureId (Mandatory)
    The id of the MCDM only measure.

# 4.32. <<abstract>> FlightAtfcmMeasureLocation

- (1) Abstract ancestor for all flight atfcm measure locations.
- This type is equivalent to the <u>FlightRegulationLocation</u> but extended to cope with the different types of measure (regulation/rerouting/...)
- (3) Attributes:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

a) ReferenceLocation referenceLocation (Optional)

Reference location on which the measure applies.

Mandatory for regulation

Optional for rerouting: not present if there is no such reference location.

- b) <u>MeasureSubType</u> measureSubType (Mandatory)
- c) HotspotId hotspotId (Optional)

The Id of the problem hotspot associated to the measure.

Note that problem hotspot related fields are trial related (STAM) fields: they are only accessible/filled during specific trials or on test platforms.

In addition, the hotspot id is not immutable as it contains the applicability period and the applicability period of a hotspot can change depending on traffic evolution.

d) MCDMState mcdmState (Optional)

The mcdm state of the measure (null if this measure is not under MCDM)

- (4) <u>Extended by: FlightAtfcmRegulationLocation, FlightAtfcmReroutingLocation, FlightAtfcmMcdmOnly-</u> Location.
- (5) Used by: Flight.

## 4.33. FlightAtfcmRegulationLocation

- (1) Flight ATFCM regulation location.
- (2) Inherits from: FlightAtfcmMeasureLocation.
- (3) Attributes:
  - a) RegulationId regulationId (Mandatory)
    The regulation identifier.
  - b) **boolean toConfirm** (Mandatory)
    True if the regulation must still be confirmed.

# 4.34. FlightAtfcmReroutingLocation

- (1) Flight ATFCM rerouting location. It contains info about what the type of rerouting and about the outcome of the rerouting (basically success or no alternative/better route found).
- (2) <u>Inherits from: FlightAtfcmMeasureLocation</u>.
- (3) Attributes:
  - a) ReroutingId reroutingId (Mandatory)
    The rerouting unique identifier.
  - b) **ReroutingApplyKind** reroutingApplyKind (Mandatory)

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

c) <u>GroupReroutingIndicator</u> groupReroutingIndicator (Mandatory)

## 4.35. FlightHotspotLocation

- The hotspot is used to indicate a period when there is too much traffic in a traffic volume according to occupancy counts or complexity analysis for a specific occupancy traffic count duration.
- (2) Attributes:
  - a) Hotspot hotspot (Mandatory)
     A hotspot by which the flight is or was concerned.
  - b) ReferenceLocation referenceLocation (Mandatory)
    Reference location of the traffic volume on which the hotspot applies.
- (3) Used by: Flight.

## 4.36. FlightMCDMInfo

- Flight M-CDM (Measure Collaborative Decision Making)information: a flight can be concerned by 0 or more measures (regulation/rerouting/M-CDM only) involved in M-CDM.
- (2) Attributes:
  - a) MeasureId firstAssociatedMCDMMeasure (Mandatory)

The first/most relevant measure that is impacting/penalizing the flight (somewhat equivalent to the most penalizing regulation but generalized to different types of measure)

b) **int nrAssociatedMCDMRegulations** (Mandatory)

Constraint: Range: [0,∞[.

c) int nrAssociatedMCDMReroutings (Mandatory)

Constraint: Range: [0,∞[.

d) int nrAssociatedMCDMOnlyMeasures (Mandatory)

Constraint: Range: [0,∞[.

e) MCDMState worstMCDMState (Mandatory)

The worst flight MCDM state of the different measures affecting the flight, if any. Following values are possible and listed from the most worst state to the less worst state:

- i) DRAFT
- ii) PROPOSED
- iii) INTERRUPTED
- iv) COORDINATED
- v) IMPLEMENTING

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- vi) IMPLEMENTED
- vii) FINISHED

Basically the worstMCDMState gives the MCDM state of the least advanced MCDM measure impacting the flight.

ABANDONED MCDM states are not considered (except for the <u>queryFlightsByMeasure</u> service).

(3) Used by: Flight.

# 4.37. FlightRegulationLocation

- (1) Describes the location of a regulation based on the reference location of the traffic volume to which the regulation applies.
- (2) Attributes:
  - a) RegulationId regulationId (Mandatory) Id of the regulation.
  - b) ReferenceLocation referenceLocation (Mandatory)
    Reference location in the traffic volume on which the regulation applies.
  - c) **boolean toConfirm** (Mandatory)

    True if the regulation must still be confirmed.
- (3) Used by: Flight.

#### 4.38. Flow

- (1) Flow identification.
- (2) Attributes:
  - a) **FlowId id** (Mandatory)

Flow id or the scenario traffic volume id (in case of scenario flow counts).

b) **FlowType type** (Mandatory)

Flow type.

**Constraints:** 

- i) See <u>FLOW\_ROLE\_MUST\_BE\_NULL</u>
- ii) See <u>SCENARIO IMPACT AND APPLICABLE SCENARIO CANNOT BE NULL</u>
- c) FlowRoleSelection role (Optional)

Flow role selection.

Constraint: See FLOW ROLE MUST BE NULL

d) <u>TrafficVolumeScenarios</u> applicableScenarios (Optional)

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Describes the applicable scenarios that have measures on the traffic volume corresponding to id.

Note that even scenario are returned that have no scenarioImpact (e.g. no flights for the selected period captured by the traffic volume).

This allows the B2B client to also use this field to query more generally the scenario repository: what are all the scenario impacting a traffic volume (not looking at specific dates or flights).

Constraint: See SCENARIO\_IMPACT\_AND\_APPLICABLE\_SCENARIO\_CANNOT\_BE\_NULL

e) <u>ScenarioImpact</u> scenarioImpact (Optional)

Scenario impact.

Constraint: See SCENARIO IMPACT AND APPLICABLE SCENARIO CANNOT BE NULL

#### (3) Constraints:

a)	Name	FLOW_ROLE_MUST_BE_NULL
	Attributes	role, type
	Description	The role must be null if type is ASSOCIATED.

b)	Name	SCENARIO_IMPACT_AND_APPLICABLE_SCENARIO_CANNOT_BE_NULL		
	Attributes	applicableScenarios, scenarioImpact, type		
	•	The scenarioImpact and applicableScenario can not be null if type is SCENARIO and must be null otherwise.		

(4) <u>Used by: TrafficCountsReplyData.</u>

## 4.39. typedef<string> FlowId

- (1) Pattern: TEXT{1,8}
- (2) <u>Used by: FlightListByHotspotRequest, FlightListByTrafficVolumeRequest, Rerouting, Counts, Flow.</u>

### 4.40. <<enumeration>> FlowRoleSelection

- (1) The selection flow role (for <u>FlowType.LINKED</u> flows of traffic volume).
- (2) Values:

#### a) **EXCLUDED**

Flights on EXCLUDED flows are not considered part of the traffic volume (so they are not taken into account in flight lists or counts or regulations on that traffic volume).

b) **EXEMPTED** 

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Flights on EXEMPTED flows are considered part of the traffic volume if there are no INCLUDED / INCLUDED\_AND\_EXEMPTED flows (so they are taken into account in flight lists or counts on that traffic volume). However, w.r.t. regulations and delay: the flights are exempted. This means only exceptional constraint regulations can impact the flight.

#### c) INCLUDED

Flights on INCLUDED flows are considered part of the traffic volume. If there are INCLUDED or INCLUDED\_AND\_EXEMPTED flows, then any flight that is not on an INCLUDED or IN-CLUDED\_AND\_EXEMPTED flow, is considered not part of the traffic volume.

#### d) INCLUDED AND EXEMPTED

Flights on an INCLUDED\_AND\_EXEMPTED flow, are considered part of the traffic volume. However hey are also considered as an INCLUDED flow (w.r.t. other flights that are not on an INCLUDED flow) and as an EXEMPTED flow (w.r.t. regulations).

(3) <u>Used by: Flow</u>.

## 4.41. <<enumeration>> FlowType

- (1) Enumerates the possible flow types.
- (2) Values:

#### a) **ASSOCIATED**

The counts correspond to the traffic of each one of the ASSOCIATED flows and the 0HERS flow specified on the reference location that intersects the traffic inside the traffic volume excluding the traffic of the <a href="EXCLUDED">EXCLUDED</a> flows. The returned counts is per ASSOCIATED and 0THERS flow.

Following possibilities exist:

- Traffic volume without flows: the returned counts contain traffic counts for the traffic of each ASSOCIATED flow.
- ii) Traffic volume with included flows: the returned counts contain traffic counts for the traffic of each ASSOCIATED flow intersecting with the traffic of the <a href="INCLUDED">INCLUDED</a> flows. The traffic counts are equal to the counts of the traffic intersection (common traffic) of each ASSOCIATED flow with the <a href="INCLUDED">INCLUDED</a> flows.
- iii) Traffic volume with excluded flows: the returned counts contain traffic counts for the traffic of each ASSOCIATED flow and the 0THERS flow, excluding the traffic of the excluded flows. The traffic counts are equal to the counts of the traffic of each ASSO-CIATED and 0THERS flow minus the traffic of the excluded flows.
- iv) Traffic volume with included and excluded flows: the returned counts contain traffic counts for the traffic of each ASSOCIATED flow with traffic intersecting the traffic of the <a href="INCLUDED">INCLUDED</a> flows, excluding the traffic of the excluded flows. The traffic counts are equal to the counts of the traffic intersection (common traffic) of each ASSOCIATED flow with the <a href="INCLUDED">INCLUDED</a> flows minus the traffic of the excluded flows.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

Note that it is possible that a traffic volume has no associated nor linked flows.

#### b) LINKED

The counts correspond to the traffic inside each one of the <u>INCLUDED</u>, <u>EXEMPTED</u> and <u>INCLUDED AND EXEMPTED</u> flows that are specified on the traffic volume. The counts are per INCLUDED, EXEMPTED and INCLUDED AND EXEMPTED flow.

#### c) SCENARIO

When querying flowcounts for scenario type flows, the flow counts show one flow per scenario traffic volume. This allows to show for a trafficvolume, which scenarios can be applied to off-load that traffic volume and by how much (inside the scenario flow count numbers)

In this case, the flow counts correspond to the common traffic (intersection) between

- i) the traffic inside the traffic volume (excluding the traffic of the EXCLUDED flows)
- ii) the traffic on the traffic volumes of the applicable scenarios and their measures See also Class <u>TrafficVolumeScenarios</u> and general into inside scenario repository. Querying the scenario flow counts is a heavy field for the NM systems.
- (3) <u>Used by: Flow, TrafficCountsByTrafficVolumeRequest.</u>

## 4.42. ForceFlightInRegulation

- (1) Flight in regulation.
- (2) Attributes:
  - a) RegulationId regulationId (Mandatory)
    The regulation unique identifier.
  - b) **DateTimeMinute** newCto (Optional)

The new calculated time over the regulation. Constraints:

- i) See <u>BOTH NEW CTO AND CTOT MUST BE SET</u>
- ii) See <u>EITHER NEW CTO OR CTOT MUST BE SET</u>
- c) **DateTimeMinute** newCtot (Optional)

The new calculated take-off time.

Constraints:

- i) See <u>BOTH NEW CTO AND CTOT MUST BE SET</u>
- ii) See <u>EITHER NEW CTO OR CTOT MUST BE SET</u>
- d) **boolean flightProposal** (Mandatory)

Determines if this Force action needs to be done on the normal flight or if a proposal flight needs to be created.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Typically in simulations, one would force directly while in operational dataset context, one needs to submit a proposal for NMOC to review: in the context of a proposal cherry picked regulation (See fileRegulationProposal service) or in the context of modifying the CTOT of a flight in a normal (non-cherry-picked) regulation.

## e) **boolean immediatelyUnforce** (Mandatory)

Determines if this flight needs to be unforced after the forcing (i.e. to allow improvements/deteriorations).

#### (3) Constraints:

a)	Name	EITHER_NEW_CTO_OR_CTOT_MUST_BE_SET
	Attributes	newCto, newCtot
	Context	UpdateFlightsInMeasureRequest
	Description	Only one of either newCto or newCtot attribute must be set.

b)	Name	BOTH_NEW_CTO_AND_CTOT_MUST_BE_SET
	Attributes	newCto, newCtot
Context UpdateFlightsInMeasureReply  Description Both newCto and newCtot attributes must be set.		<pre>UpdateFlightsInMeasureReply</pre>
		Both newCto and newCtot attributes must be set.

(4) <u>Used by: UpdateFlightInMeasureChoice</u>.

### 4.43. <<enumeration>> FreezeTP

- (1) Enumeration of possible freeze terminal procedure.
- (2) Values:
  - a) FREEZE SID STAR
  - b) FREEZE\_SID\_STAR\_AND\_CONNECTING\_POINTS
  - c) **NO**
- (3) <u>Used by: ReroutingHorizontalConstraints.</u>

# 4.44. <<enumeration>> GroupReroutingIndicator

- (1) Group rerouting indicator.
- (2) Values:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices		B2B/23.0.0/Flow

Value	Description	
EXECUTED	Rerouting executed and new route stored in the RTFM of the flight	
INTERESTING	Group rerouting for indication attempted and an alternative route found	
NO_REROUTING	No rerouting attempted or no rerouting executed	
OPPORTUNITY	Group rerouting for opportunity attempted and an opportunity found	
UNINTERESTING	No rerouting proposal	

Table 4.1. <<enumeration>> GroupReroutingIndicator

(3) <u>Used by: FlightAtfcmReroutingLocation</u>.

### 4.45. Hotspot

- (1) The hotspot is used to indicate a period when there is too much traffic in a traffic volume according to occupancy counts or complexity analysis for a specific occupancy traffic count duration.
- (2) Attributes:
  - a) **HotspotId hotspotId** (Mandatory)

The identifier of the hotspot.

Note that hotspot id is not immutable as it contains the applicability period and the applicability period of a hotspot can change depending on traffic evolution.

b) <u>HotspotSeverity</u> severity (Mandatory)

The severity of the hotspot.

c) HotspotStatus status (Mandatory)

The status of the hotspot.

d) string remark (Optional)

Free text used for remarks and notes

<u>Constraint:</u> Pattern: (ALPHA|DIGIT|'|\(|\)|+|,|=|?|.|/|:| ){0,255}

e) string trafficVolumeDescription (Contextual)

The traffic volume description to which the hotspot applies.

Presence:

- i) Must be null in <a href="https://hotspotPlanUpdateRequest">HotspotPlanUpdateRequest</a>
- ii) Optional otherwise.
- (3) <u>Used by: HotspotPlans, FlightHotspotLocation</u>.

# 4.46. <<enumeration>> HotspotField

(1) Enumeration of possible severity levels for a hotspot.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### (2) Values:

- a) **DIARY**
- b) **MEASURE**
- c) **SEVERITY**
- d) STATUS

## 4.47. HotspotId

- (1) The identifier of an hotspot.
- (2) Attributes:
  - a) **DateTimeMinutePeriod applicabilityPeriod** (Mandatory)

The applicability period of the hotspot.

The applicability period of a hotspot indicates that in the corresponding occupancy traffic counts (step = 1 minute, duration of the HotspotId), for the count periods/intervals that start in the applicabilityPeriod there is a capacity/complexity problem.

- b) <u>TrafficVolumeId</u> trafficVolume (Mandatory) Traffic volume to which this hotspot applies.
- c) <u>DurationHourMinute</u> duration (Mandatory) The duration of this hotspot.
- (3) <u>Used by: MCDMTopicListRequestSelector, FlightListByHotspotRequest, Measure, Hotspot, FlightAtfcmMeasureLocation, MCDMHotspotTopic, MCDMStatefulTopic.</u>

# 4.48. <<enumeration>> HotspotKind

- (1) Identifies the kind of hotspot.
- (2) Values:
  - a) LOCATION OF INTEREST

Location of interest hotspots are used raise awarness about potential hotspots or problems in the context of the daily plan: For example weather or special events (a.o. Soyuz rocket launches that imply a closure of some airspaces for a period of time).

#### b) **PROBLEM**

Problem hotspots are STAM related hotspots and are linked to a demand-capacity inbalance. Typically a Location of interest hotspot can evolve into a problem hotspot if the potential risk metrializes and introduces a real demand-capacity inbalance for a specific period.

(3) <u>Used by: HotspotPlans, HotspotListRequest.</u>

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

### 4.49. HotspotPlans

- (1) Hotspot plan for a given traffic volume and day.
- (2) Attributes:
  - a) PlanDataId dataId (Mandatory)
    Opaque identifier representing the version of this hotspot plan.
  - b) **Dataset dataset** (Mandatory)

    Dataset to which the hotspot plan belongs.
  - c) <u>DateYearMonthDay</u> day (Mandatory) Day for which this hotspot plan is valid.
  - d) boolean planTransferred (Optional) Indicates if the plan has been transferred to the 0PERATIONAL dataset. When false, it means that the most up-to-date data can be found in the F0RECAST dataset.
  - e) **boolean planCutOffReached** (Optional)
    Indicates if the plan can still be updated in the FORECAST dataset, i.e. if the forecast cut-off time has been reached or not.
  - f) HotspotKind hotspotKind (Mandatory)
    The kind of hotspot.
  - g) Map<<u>TrafficVolumeId</u>,Map<<u>DurationHourMinute</u>,Set<<u>Hotspot</u>>>> schedules (Mandatory)

(Pre-)tactical hotspots associated to their applicability period for a set of specific traffic volumes and duration. The schedule exposes the complete time partition of the hotspots for the day. Missing periods in the time partition correspond to not having any hotspot for that period.

Constraints:

- i) Size must be comprised between 0 and 1000.
- ii) Item size must be comprised between 0 and 1000.
- iii) Item size must be comprised between 0 and 1000.
- iv) See <a href="INVALID\_SCHEDULE">INVALID\_SCHEDULE</a>
- v) See ONLY ONE ENTRY CAN BE UPDATED IN SCHEDULE

#### (3) Constraints:

a)	Name	INVALID_SCHEDULE
	Attribute	schedules

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices		B2B/23.0.0/Flow

Description	The duration key used in each of the schedules map attribute has to be
	equal to the duration of all hotspots linked to that duration key.

b)	Name	ONLY_ONE_ENTRY_CAN_BE_UPDATED_IN_SCHEDULE
	Attribute	schedules
	Context	HotspotPlanUpdateRequest
		Only one entry in each of the schedules map attribute can be updated (i.e., for one duration).

(4) <u>Used by:</u> <u>HotspotPlanUpdateRequest</u>, <u>HotspotListReply</u>, <u>HotspotPlanUpdateReply</u>.

## 4.50. <<enumeration>> HotspotSeverity

- (1) Enumeration of possible severity levels for a hotspot.
- (2) Values:
  - a) **HIGH**
  - b) LOW
  - c) **MEDIUM**
- (3) <u>Used by: Hotspot</u>.

# 4.51. <<enumeration>> HotspotStatus

- (1) Enumeration of possible severity levels for a hotspot.
- (2) Values:

#### a) **ACCEPTABLE**

After analysis it appeared that the problem was not a real problem and does not require action to be solved. Note that if a Hotspot is really no longer required it is simply removed completely.

The ACCEPTABLE state is solely intended to indicate that a Hotspot has been accepted as a problem that can be tolerated (e.g. no resolution action such as a STAM needs to be applied).

#### b) ACTIVE

The problem is confirmed and must be solved (e.g. by a STAM)

#### c) DRAFT

A potential problem (peak) has been identified and it is still needed to verify if it is a real problem or not.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### d) SOLVED

The problem has been solved (e.g. by a STAM)

(3) Used by: Hotspot.

### 4.52. <<enumeration>> KindOfRestriction

- (1) Enumeration of possible restriction location.
- (2) Values:
  - a) AC
  - b) CF
  - c) DCT
  - d) RAD
  - e) SC
- (3) <u>Used by: RestrictionLocation</u>.

# 4.53. LevelAndSpeedReroutingConstraint

- (1) Describes a level and speed rerouting constraint.
- (2) <u>Inherits from: ReroutingConstraint.</u>
- (3) Attributes:
  - a) DBEOrPublishedPointId fromPoint (Optional)

From this point onwards the level and/or speed needs to be adapted. If not present, the level and/or speed is updated from the departure aerodrome.

b) DBEOrPublishedPointId untilPoint (Optional)

The level and/or speed needs to be adapted until untilPoint. If not present, the level and/or speed is updated until the arrival aerodrome or until the next flightlevel constraint.

- c) **FlightLevel level** (Mandatory)
- d) AirSpeed airSpeed (Optional)

  If not present, then the speed of the flights is not updated.

### 4.54. <<enumeration>> LevelConstraintKind

(2) Values:

Edition: **23.0.0.5.26** 177

(1)

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- a) ABOVE
- b) **BELOW**
- (3) <u>Used by: ScenarioLevelConstraint.</u>

### 4.55. LifeCycleEvent

- (1) Describes when and by whom an object has been last updated.
- (2) Attributes:
  - a) DateTimeSecond eventTime (Mandatory)

    The time at which the last update was done (by a user explicitly or by the system).

    If this is the first event for this measure, then it is the time when the measure was created
  - b) DateTimeSecond userUpdateEventTime (Optional)
    If the eventTime is the event time of a system triggered event, then the userUpdateEventTime indicates the time at which the last user triggered update was done.
    If this is the first event for this measure, then it is the time when the measure was created.
  - c) <u>LifeCycleEventType</u> userUpdateType (Mandatory)
    The update type of the last user update.
  - d) UserId userId (Mandatory)
     Id of the user who created, last updated or deleted the object.
- (3) Used by: Measure.

# 4.56. <<enumeration>> LifeCycleEventType

- (1) Lifecycle event type.
- (2) Values:
  - a) **CREATION**
  - b) **DELETION**Note that DELETION for a regulation in fact means that the regulation was cancelled.
  - c) **UPDATE**
- (3) Used by: LifeCycleEvent.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices		B2B/23.0.0/Flow

### 4.57. <<abstract>> Location




Figure 4.2. <<abstract>> Location Class Diagram

- (1) Ancestor structure for all locations.
- (2) <u>Extended by: AirspaceLocation, SegmentLocation, AerodromeLocation, DelayLocation, AllFlights-Location, SetOfAerodromesLocation, RestrictionLocation, PointLocation, TrafficVolumeLocation, CherryPickedLocation, AoLocation.</u>
- (3) Used by: Rerouting.

## 4.58. <<enumeration>> MCDMApprovalState

- (1) Enumeration of possible types for a MCDM approval state (e.g. after casting a vote).
- (2) In regulation proposal context, the NMOC actor can have any of the 4 different states. The initiator can only be in UNKNOWN (default) or REJECTED (when the B2B client revokes a proposal)
- (3) Values:
  - a) ACKNOWLEDGED

Actor acknowledges the request and starts thinking about the response.

b) APPROVED

Actor approves the measure.

c) **REJECTED** 

Actor disapproves the measure.

d) UNKNOWN

Default state, no response has been given by the actor.

(4) <u>Used by:</u> <u>RegulationProposalListRequest</u>, <u>MCDMUserRoleAndApprovalState</u>, <u>RegulationProposal</u>.

### 4.59. <<enumeration>> MCDMCoordinationLevel

- (1) The MCDM coordination level.
- (2) Values:
  - a) FLIGHT
  - b) **MEASURE**

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices		B2B/23.0.0/Flow

(3) <u>Used by: MCDMRoleUserCategory</u>.

#### 4.60. MCDMDeadlines

- (1) All measure deadlines.
- (2) Attributes:
  - a) DateTimeMinute timeToCoordinate (Contextual)
    The deadline to finish the coordination activities.
    Presence:
    - i) Optional in <a href="MCDMTopicUpdateRequest">MCDMTopicUpdateRequest</a>
    - ii) Optional otherwise.

Constraint: See AT LEAST ONE DEADLINE MUST BE SET

- b) **DateTimeMinute timeToStartImplement** (Contextual) The deadline to start the implementation activities. Presence:
  - i) Optional in <a href="MCDMTopicUpdateRequest">MCDMTopicUpdateRequest</a>
  - ii) Optional otherwise.

<u>Constraint:</u> See <u>AT\_LEAST\_ONE\_DEADLINE\_MUST\_BE\_SET</u>

- c) <u>DateTimeMinute</u> timeToImplement (Contextual)
  The deadline to finish the implementation activities.
  <u>Presence:</u>
  - i) Optional in <u>MCDMTopicUpdateRequest</u>
  - ii) Optional otherwise.

Constraint: See AT LEAST ONE DEADLINE MUST BE SET

- (3) Constraint:

(4) <u>Used by: MCDMMeasureTopic</u>.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 4.61. MCDMFlightTopic




Figure 4.3. MCDMFlightTopic Class Diagram

- (1) Represents a flight MCDM topic.
- (2) Note:

Note that in regulation proposal context, only cherry picked flights have MCDMFlightTopic.

- (3) <u>Inherits from: MCDMStatefulTopic</u>.
- (4) <u>Attributes:</u>
  - a) FlightKeys flightKeys (Mandatory)

The flight keys.

Note: The keys are not unique and have to be used together with the topicId.

(5) <u>Used by: MCDMMeasureTopic</u>.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 4.62. MCDMHotspotTopic




Figure 4.4. MCDMHotspotTopic Class Diagram

- (1) Represents a hotspot MCDM topic.
- (2) <u>Inherits from: MCDMTopic</u>.
- (3) Attributes:
  - a) HotspotId hotspotId (Contextual)

The related hotspot.

Presence:

- i) Must be null in <a href="MCDMTopicUpdateRequest">MCDMTopicUpdateRequest</a>
- ii) Mandatory otherwise.

Constraint: See SAME HOTSPOT ID MUST BE SET IN MEASURE TOPICS

b) Set<<a href="MCDMMeasureTopic">MCDMMeasureTopic</a>> measureTopics (Contextual)

A set of MCDM measure topics related to this MCDM hotspot topic. In <a href="MCDMTopicUpdateRequest">MCDMTopicUpdateRequest</a> context, only one MCDM measure topic can be updated. <a href="Presence:">Presence:</a>

- i) Optional in <u>MCDMTopicUpdateReply</u>, <u>MCDMTopicUpdateRequest</u>
- ii) Mandatory otherwise.

Constraints:

- i) Size must be comprised between 1 and 10000.
- ii) See <u>AT\_LEAST\_MESSAGES\_OR\_MEASURE\_TOPICS\_MUST\_BE\_SET</u>
- iii) See ONLY\_ONE\_MEASURE\_TOPIC\_CAN\_BE\_UPDATED
- iv) See <u>SAME HOTSPOT ID MUST BE SET IN MEASURE TOPICS</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### (4) <u>Constraints:</u>

a)	Name	SAME_HOTSPOT_ID_MUST_BE_SET_IN_MEASURE_TOPICS	
	Attributes	hotspotId, measureTopics	
	-	The hotspotId of all MCDM measure topic from measureTopics must be the same as the hotspotId of this MCDM hotspot topic.	

b)	Name	AT_LEAST_MESSAGES_OR_MEASURE_TOPICS_MUST_BE_SET
	Attribute	measureTopics
	Context MCDMTopicUpdateRequest	
Description At least messages or measureTopics must be set.		At least messages or measureTopics must be set.

c)	Name	ONLY_ONE_MEASURE_TOPIC_CAN_BE_UPDATED
	Attribute	measureTopics
	Context	MCDMTopicUpdateRequest
	Description Only one measure topic of this hotspot topic can be updated.	

(5) <u>Used by: MCDMTopicListReply</u>.

# 4.63. MCDMMeasureTopic




Figure 4.5. MCDMMeasureTopic Class Diagram

- (1) Represents a measure MCDM topic.
- (2) <u>Inherits from: MCDMStatefulTopic</u>.
- (3) <u>Attributes:</u>

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### a) Set<<u>MCDMRoleUserCategory</u>> userCategories (Optional)

A set of user categories (actor and role) of the given topic.

Present if <u>MCDMTopicField.userCategories</u> has been requested. Note that it can be an empty set when in transient state i.e. when the measure has been created but the topic has not been updated yet via <u>MCDMTopicUpdateRequest</u>.

Constraint: Size must be comprised between 0 and 1000.

### b) MCDMDeadlines deadlines (Optional)

The measure's deadlines.

Present if MCDMTopicField.deadlines has been requested.

#### c) Set<<a href="MCDMFlightTopic">MCDMFlightTopic</a> flightTopics (Optional)

An optional set of MCDM flight topics related to this MCDM measure topic. Constraints:

- i) Size must be comprised between 1 and 1000.
- ii) See <u>SAME HOTSPOT ID MUST BE SET IN FLIGHT TOPICS</u>
- iii) See <u>SAME MEASURE ID MUST BE SET IN FLIGHT TOPICS</u>

# d) Set<<u>MCDMUserAndRole</u>> predefinedUsersForFlightCoordinationLevel (Optional)

The pre-defined actors (and their role) for the per-flight coordination. Normally the flight actors (and their role) are computed based on the given userCategories and the profiles of the flights.

However if the user wants to control explicitly which actors should be involved in the flight coordination process, then he can define PredefinedUsersForFlightCoordinationLevel. If userCategories indicates that no flight coordination is needed, then NM systems will compute flight-by-flight the involved flight-coordination actors (and their role) based on the Predefined-UsersForFlightCoordinationLevel.

<u>Constraint:</u> Size must be comprised between 0 and ∞.

#### e) string remark (Optional)

Constraint: Pattern: MULTILINE\_TEXT{1,1000}

### (4) Constraints:

a)	Name	SAME_HOTSPOT_ID_MUST_BE_SET_IN_FLIGHT_TOPICS
	Attribute	flightTopics
	-	The hotspotId of all MCDM flight topic from flightTopics must be the same of the hotspotId as this MCDM measure topic.

b)	Name	SAME_MEASURE_ID_MUST_BE_SET_IN_FLIGHT_TOPICS
	Attribute	<u>flightTopics</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Description	The measureId of all MCDM flight topic from flightTopics must be the
	same as the measureId of this MCDM measure topic.

(5) <u>Used by: Measure, MCDMTopicListReply, MCDMHotspotTopic.</u>

### 4.64. MCDMMessage

- (1) Free text used for message in MCDM collaboration environment.
- (2) Attributes:
  - a) **DateTimeSecond time** (Contextual)

The time when NM received the message.

Presence:

- i) Must be null in <a href="MCDMTopicUpdateRequest">MCDMTopicUpdateRequest</a>
- ii) Mandatory otherwise.
- b) AirNavigationUnitId user (Contextual)

The user's agency.

Not set when system message.

Presence:

- i) Must be null in <a href="MCDMTopicUpdateRequest">MCDMTopicUpdateRequest</a>
- ii) Optional otherwise.
- c) **string message** (Mandatory)

The message.

Constraint: Pattern: ANY {0, 1024}

d) <u>MCDMMessageType</u> type (Contextual)

Type of the message.

Presence:

- i) Must be null in <a href="MCDMTopicUpdateRequest">MCDMTopicUpdateRequest</a>
- ii) Mandatory otherwise.
- (3) <u>Used by: MCDMTopic, MCDMTopicMessageRetrievalReply.</u>

# 4.65. <<enumeration>> MCDMMessageType

- (1) Enumeration of possible types for a MCDM topic message.
- (2) Values:
  - a) INCOMING

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Messages that are incoming w.r.t. the current user: messages that other user have sent.

#### b) **OUTGOING**

Messages that are outgoing w.r.t. the current user: messages that this user has sent.

#### c) SYSTEM

Messages that are generated by the system (typically when the MCDM state of a measure is changed, then the system will update the MCDM states of the concerned flights correspondingly).

(3) <u>Used by: MCDMMessage</u>.

### 4.66. MCDMOnly




Figure 4.6. MCDMOnly Class Diagram

- An mcdm0nly measure. MCDM0nly measures are pure text coordination measures. The remark field actually describes what kind of measure this is and what is expected. They allow to associate flights to mcdm0nly measures and follow the MCDM process. However there are no proposal flights associated to mcdmOnly measures, so no what-if counts and flightlists can be done to evaluate any potential impact.
- (2) <u>Inherits from: RegulationOrMCDMOnly</u>.
- (3) Attributes:
  - a) RegulationState mcdmOnlyState (Contextual)
     Current state of the mcdm only.
     When requested, this attribute is never left null.
     Presence:
    - i) Must be null in <a href="MCDMOnlyCreationRequest">MCDMOnlyUpdateRequest</a>

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- ii) Optional otherwise.
- (4) <u>Used by: MCDMOnlyCreationReply, MCDMOnlyCreationRequest, ScenarioMCDMOnlyRetrievalReply, MCDMOnlyUpdateReply, MCDMOnlyUpdateRequest, MCDMOnlyListReply.</u>

# 4.67. <<enumeration>> MCDMOnlyField

- (1) Enumerates the fields that the caller may request to be returned in <u>MCDMOnly</u> objects when returned by <u>MCDMOnlyListRequest</u>.
- (2) As a rule, client applications should never request mcdmOnly fields that they do not need. Client applications typically implement a query/retrieve pattern:
  - a) Query the small number of most relevant mcdmOnly fields to display to the end user
  - b) Retrieve more details for a given mcdmOnly when the end user has selected a mcdmOnly from the list
- (3) Values:
  - a) applicability
  - b) autolink
  - c) createdByFMP
  - d) dataId
  - e) delayConfirmationThreshold
  - f) delayTVSet
  - g) **externallyEditable**
  - h) initialConstraints
  - i) lastUpdate
  - j) linkedRegulations
  - k) location
  - ncdmOnlyState
  - m) mcdmRequired
  - n) measureCherryPicked
  - o) noDelayWindow

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- p) protectedLocation
- q) reason
- r) **remark**
- s) scenarioReference
- t) sourceHotspot
- u) subType
- v) **supplementaryConstraints**
- w) updateCapacityRequired
- x) updateTVActivationRequired
- (4) <u>Used by: ScenarioMCDMOnlyRetrievalRequest, MCDMOnlyListRequest.</u>

### 4.68. <<enumeration>> MCDMRole

- (1) Enumeration of possible roles for an actor working with MCDM topic.
- (2) In regulation proposal context, only a subset of the roles are used: APPROVAL, INITIATOR and NOT\_INVOLVED are the only ones that can occur. NMOC is implicitly considered the implementer.
- (3) Values:
  - a) **APPROVAL**

The user needs to approve.

b) **IMPLEMENTER** 

The user needs to implement the measure/action on a flight.

c) INFO

The user is informed about the MCDM.

d) INITIATOR

The user is the initiator of the measure/action on a flight.

e) NOT INVOLVED

The user is not involved in the measure/action on a flight.

f) ROLE INFO

There are multiple ANUs found for a specific IMPLEMTENTER / APPROVAL (AO/tower). The first one was selected as for approval or for implementation. The others have the R0LE\_INFO. They need to manually check that the correct ANU gets the APPROVAL or IMPLEMENTER role.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

(4) <u>Used by: MCDMUserRoleAndApprovalState, MCDMRoleUserCategory, MCDMUserAndRole</u>.

### 4.69. MCDMRoleUserCategory

- (1) Structure that contains mapping of a MCDM user category and its associated role.
- In the MCDM process, actor categories also have roles. They pilot how NM systems computes the default actors and their role. For example having ALL\_FMP wih role for INFO for the measure means that all the FMP concerned (by the flights of the measure) will be inside the MCDMUser-RoleAndApprovalState for the measure with a default role for INFO.
- (3) Attributes:
  - a) MCDMUserCategory category (Mandatory)
    The user category.
  - b) <u>MCDMCoordinationLevel</u> coordinationLevel (Mandatory) The coordination level (flight or measure).
  - c) MCDMRole role (Mandatory)
    The role for a category.
    Constraint: See NOT INVOLVED ROLE NOT ALLOWED
- (4) Constraint:

a)	Name	NOT_INVOLVED_ROLE_NOT_ALLOWED
	Attribute	role
	Context	MCDMTopicListRequest
	Description	The role cannot be NOT_INVOLVED.

(5) <u>Used by: MCDMMeasureTopic</u>.

## 4.70. <<enumeration>> MCDMState

- (1) Enumeration of possible types for a MCDM state.
- (2) In regulation proposal context, FINISHED does not occur.
- (3) The nominal finite state transaction flows for the trial related MCDM process (not the regulation proposal subset) are pictured below.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

(4)




Figure 4.7. MCDM transition diagram

#### (5) Values:

#### a) ABANDONED

The measure will not occur or the flight will not be included in the measure. The measure was forced to abandoned by a manual user action by the initiator (e.g. a revoke of a proposal regulation by the initiator) or in regulation proposal context: NMOC has rejected the measure. Alternatively the MCDMState of a flight is set to abandoned because this flight specifically has been rejected by NMOC (a.o. due to RAD violations)

#### b) **COORDINATED**

In full MCDM context: All the concerned actors have agreed that:

- i) the measure should/could occur
- or that a flight should be included in the measure and that the proposed action is accepted.

However the initiator is waiting for the for the expected capacity problem to materialize. In regulation proposal context: COORDINATED means that NMOC has acknowledged the regulation proposal ans started handling the request.

#### c) DRAFT

A measure is being created to solve a hotspot/problem area. It is too early to start MCDM approval: the solution is in the process of being evaluated by the initiator. The measure/flight is draft even while it is incomplete, for example the FMP has selected that there will be cherry picking but has not yet selected the flights.

The measure/flight may be reset from subsequent states to Draft when the proposed measure/proposed action on a flight cannot is not sufficient and it needs to be changed (for example in regulation proposal context: when additional flights need to be added). If required, the measure/flight may also be forced by the Initiator to Abandoned state at this stage (for example: in regulation proposal context when revoking a proposal).

#### d) **FINISHED**

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

This state is a simple combination of Implemented and the end time of the hotspot being in the past.

Note that in regulation proposal context, this state does not occur.

#### e) **IMPLEMENTED**

The actor who should implement the measure/flight action has agreed to implement it at the relevant time - that is at or before the implementation time limit. Implemented may mean that an action will be taken, for example ATC may do something when the flight appears, or implemented may mean that the action has already been taken, for example the aircraft operator may have submitted a change to his flight plan. In the context of regulation proposals, it means that the proposal has been accepted and that the "real" flight (i.e. non-proposal flight) has received a CTOT.

#### f) IMPLEMENTING

When the Initiator decides the measure/flight action is really needed, the measure/flight is moved from Coordinated to For Implementation and the job of implementation can begin. In the context of regulation proposals, it is a temporary state required by NM systems to indicate that the transformation of proposal flight CTOT into nomal flight CTOT has started, but not all flights have been processed yet.

#### g) **INTERRUPTED**

The measure will not occur or the flight became excluded from the measure.

The measure was forced to abandoned by the system or by NMOC after it had been acceted (for example: a measure could get interrupted after NMOC cancelled the measure ater having accepted the proposal to create it).

Alternativley the aircraft operator refiled and avoided a cherry pick regulation.

#### h) **PROPOSED**

The measure/flight is being shown via B2 or NOP to all concerned actors in order to get their agreement that the measure should/could occur or that the flight should be included in the measure.

Note that in regulation proposal context, it means that the B2B client wants NMOC to review the proposal but NMOC has not started looking at it yet.

(6) <u>Used by: FlightMCDMInfo, RegulationProposal, MCDMStateUpdateRequest, MCDMStateUpdateReply, FlightAtfcmMeasureLocation, MCDMStatefulTopic.</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 4.71. <<abstract>> MCDMStatefulTopic




Figure 4.8. <<abstract>> MCDMStatefulTopic Class Diagram

- (1) Defines the common attributes of MCDM topics that have state (measure and flight).
- (2) <u>Inherits from: MCDMTopic</u>.
- (3) Attributes:
  - a) MeasureId measureId (Contextual)

The related measure.

Presence:

- i) Must be null in <a href="MCDMTopicUpdateRequest">MCDMTopicUpdateRequest</a>
- ii) Mandatory otherwise.
- b) **HotspotId** hotspotId (Contextual)

The related hotspot.

Presence:

- i) Must be null in <a href="MCDMTopicUpdateRequest">MCDMTopicUpdateRequest</a>
- ii) Optional otherwise.
- c) MCDMState state (Contextual)
  The MCDM Topic state.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

#### Presence:

- i) Optional in <a href="MCDMTopicUpdateReply">MCDMTopicUpdateRequest</a>
- ii) Mandatory otherwise.

Constraint: See INTERRUPTED MCDM STATE NOT ALLOWED

d) AirNavigationUnitId initiator (Optional)

The initiator.

Present if MCDMTopicField.initiator was requested.

e) boolean initiatorIsImplementer (Optional)

Flag indicating whether the initiator is the implementer or not.

Present if MCDMTopicField.initiator was requested.

Constraint: See INITIATOR IS IMPLEMENTER MUST BE NULL

f) Set<MCDMUserRoleAndApprovalState> userRolesAndApprovalStates (Optional)
A set of user with their role and optionally an approval state.

In regulation proposal context, the NM systems maintain this: there is the intiator and NMOC actor and in case of cherry picked regulations, also all other potentially impacts FMP are present (with NOT\_INVOLVED role).

When NMOC accepts/rejects a measure or flight, the corresponding NMOC approval state becomes accepted or rejected.

When the FMP afterwards changes the MCDMState of the regulation back to DRAFT, the NMOC actor approvalState is reset to UNKNOWN.

Present if MCDMTopicField.userRolesAndApprovalStates has been requested.

Can be null if no actors are defined yet.

Constraint: Size must be comprised between 1 and ∞.

#### (4) Constraints:

a)	Name	INTERRUPTED_MCDM_STATE_NOT_ALLOWED
	Attribute	state
Context MCDMTopicUpdateRequest		MCDMTopicUpdateRequest
Description The attribute state cannot be INTERRUPTED.		The attribute state cannot be INTERRUPTED.

b)	Name	INITIATOR_IS_IMPLEMENTER_MUST_BE_NULL
Attribute <u>initiatorIsImp</u>		initiatorIsImplementer
	Context	MCDMTopicUpdateRequest
	•	The attribute initiatorIsImplementer must be null when the topic to be updated is a <a href="MCDMFlightTopic">MCDMFlightTopic</a> .

(5) <u>Extended by: MCDMFlightTopic, MCDMMeasureTopic</u>.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 4.72. <<abstract>> MCDMTopic




Figure 4.9. <<abstract>> MCDMTopic Class Diagram

- (1) An abstract object that defines the common attributes of MCDM topics (hotspot, measure, flight).
- (2) Attributes:
  - a) MCDMTopicId topicId (Mandatory)
    The unique identifier of the topic.
  - b) PlanDataId dataId (Mandatory)
    An opaque identifier, representing the version of this MCDM topic.
    See MCDM Update pattern.
  - c) Set<MCDMMessage> messages (Optional)
    Conversation history, usualy comments as part of collaboration between different actors.
    Only present if MCDMTopicField.messages is requested.
    Constraints:
    - i) Size must be comprised between 1 and 10000.
    - ii) See ONLY ONE MESSAGE CAN BE SENT

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### (3) Constraint:

a)	Name	ONLY_ONE_MESSAGE_CAN_BE_SENT
	Attribute	messages
	Context	MCDMTopicUpdateRequest
	Description	Only one message can be sent.

- (4) <u>Extended by: MCDMHotspotTopic, MCDMStatefulTopic.</u>
- (5) <u>Used by: MCDMTopicUpdateReply, MCDMTopicUpdateRequest.</u>

# 4.73. <<enumeration>> MCDMTopicField

- (1) Enumerates the fields that the caller may request to be returned in <u>MCDMTopic</u> objects when returned by <u>MCDMTopicListRequest</u>.
- (2) As a rule, client applications should never request topic fields that they do not need. Client applications typically implement a query/retrieve pattern:
  - a) Query the small number of most relevant topic fields to display to the end user
  - b) Retrieve more details for a given topic when the end user has selected a topic from the list
- Note that the MCDM deadlines field is trial related (STAM): it is only accessible (authorized) during specific trials or on specific test platforms.
- (4) Note that the MCDM messages field is trial related (STAM): it is only accessible (authorized) during specific trials or on specific test platforms.

#### (5) Values:

Value	Weight
deadlines	Light
initiator	Light
messages	Light
predefinedUsersForFlightCoordinationLevel	Light
remark	Light
userCategories	Light
userRolesAndApprovalStates	Light

Table 4.2. <<enumeration>> MCDMTopicField

(6) <u>Used by: MCDMTopicListRequest.</u>

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

# 4.74. typedef<string> MCDMTopicId

- (1) A unique identifier of a MCDM topic.
- (2) Pattern: (H|M|F) (ALPHA|DIGIT| ){1,300}
- (3) <u>Used by: MCDMTopicListRequestSelector, MCDMTopicMessageRetrievalRequest, MCDMTopic.</u>

# 4.75. MCDMTopicListRequestSelector

- (1) Selector used in MCDMTopicListRequest.
- (2) Choices:
  - a) Set<MCDMTopicId> topics
     Selects the topics that match one of the topic identifiers in this set.
  - b) **Set<<u>MeasureId</u>> measures**Selects the topics with a measure that matches an entry in this set.
  - Set<<u>HotspotId</u>> hotspots
     Selects the topics with a hotspot that matches an entry in this set.

#### Note:

Note that querying MCDM based on hotspots is trial related (STAM): it is only accessible (authorized) during specific trials or on specific test platforms.

d) Set<<u>AirNavigationUnitId</u>> actors

Selects the topics with an actor that matches an entry in this set.

### Note:

Note that querying MCDM based on actors is trial related (STAM): it is only accessible (authorized) during specific trials or on specific test platforms.

(3) Used by: MCDMTopicListRequest.

### 4.76. MCDMUserAndRole

- (1) A user and its role.
- (2) Attributes:
  - a) AirNavigationUnitId user (Mandatory) The user.
  - b) MCDMRole role (Contextual)
    The role.
    Presence:

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- i) Optional in <a href="MCDMTopicUpdateRequest">MCDMTopicUpdateRequest</a>
- ii) Mandatory otherwise.

  <u>Constraint:</u> See <u>MCDM\_ROLE\_IS\_MANDATORY</u>

#### (3) Constraint:

a) Name MCDM_ROLE_IS_MANDATORY		MCDM_ROLE_IS_MANDATORY
	Attribute	role
	Context	MCDMTopicUpdateRequest
	Description	MCDMRole is mandatory.

(4) <u>Used by: MCDMMeasureTopic</u>.

# 4.77. <<enumeration>> MCDMUserCategory

- (1) Enumeration of possible possible categories of actors working with MCDM topics.
- (2) <u>Values:</u>
  - a) ADJACENT FMP
  - b) **AIRCRAFT\_OPERATOR**
  - c) ALL FMP
  - d) NMOC
  - e) TOWER
- (3) <u>Used by: MCDMRoleUserCategory</u>.

# 4.78. MCDMUserRoleAndApprovalState

- (1) A user, its role and its optional approval state.
- (2) Attributes:
  - a) AirNavigationUnitId user (Mandatory)
    The user.
  - b) MCDMRole role (Contextual)
    The role.

Presence:

- i) Optional in <a href="MCDMTopicUpdateRequest">MCDMTopicUpdateRequest</a>
- ii) Mandatory otherwise.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

c) <u>MCDMApprovalState</u> approvalState (Contextual)

The approval state.

Presence:

- i) Optional in <a href="MCDMTopicUpdateRequest">MCDMTopicUpdateRequest</a>
- ii) Mandatory otherwise.
- (3) <u>Used by: MCDMStatefulTopic.</u>

### 4.79. <<abstract>> Measure




Figure 4.10. <<abstract>> Measure Class Diagram

- (1) Abstract ancestor of a measure.
- (2) <u>Attributes:</u>
  - a) PlanDataId dataId (Contextual)

Opaque identifier representing the version of this measure.

The caller shall always keep this value unchanged.

See **Update Pattern**.

Presence:

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

- i) Must be null in <a href="MCDMOnlyCreationRequest">MCDMOnlyCreationRequest</a>, <a href="RegulationProposalFilingRequest">RegulationProposalFilingRequest</a>, <a href="ReroutingCreationRequest">ReroutingCreationRequest</a>
- ii) Optional otherwise.

#### b) **DateTimeMinutePeriod applicability** (Contextual)

The period of time during which the measure affects the flights entering the traffic volumes of this regulation.

This period extends to maximum 24 hours.

When requested, this attribute is never left null.

#### NOTE:

For cherry picked regulation, NM adapts the applicability based on the flights in the regulation.

### Presence:

- i) Mandatory in MCDMOnlyCreationRequest, MCDMOnlyUpdateRequest, RegulationCreationRequest, RegulationProposalFilingRequest, RegulationProposalUpdateRequest, RegulationUpdateRequest, ReroutingCreationRequest, ReroutingUpdateRequest
- ii) Optional otherwise.

Constraint: See APPLICABILITY PERIOD CANNOT BE GREATER THAN 24 HOURS

#### c) boolean measureCherryPicked (Contextual)

Indicates if this regulation was created for flight cherry picking (only the selected cherry picked flights are subject to the measure, e.g., will have a delay). When requested, this attribute is never left null. Presence:

- i) Mandatory in <u>MCDMOnlyCreationRequest</u>, <u>RegulationCreationRequest</u>, <u>RegulationProposalFilingRequest</u>, <u>ReroutingCreationRequest</u>
- ii) Must be null in MCDMOnlyUpdateRequest, RegulationProposalUpdateRequest, RegulationUpdateRequest, ReroutingUpdateRequest
- iii) Optional otherwise.

#### d) <u>LifeCycleEvent</u> lastUpdate (Contextual)

Provides the last update life cycle event.

When requested, this attribute is never left null. Presence:

- i) Must be null in MCDMOnlyCreationRequest, MCDMOnlyUpdateRequest, RegulationCreationRequest, RegulationProposalFilingRequest, RegulationProposalUpdateRequest, RegulationUpdateRequest, ReroutingCreationRequest, ReroutingUpdateRequest
- ii) Optional otherwise.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

### e) **boolean externallyEditable** (Contextual)

Indicates that the FMP is entitled to modify the regulation, either because the regulation is part of a regulation proposal, or because NMOC flagged this regulation as being externally editable.

When requested, this attribute is never left null.

#### Presence:

- i) Must be null in MCDMOnlyCreationRequest, MCDMOnlyUpdateRequest, RegulationCreationRequest, RegulationProposalFilingRequest, RegulationProposalUpdateRequest, RegulationUpdateRequest, ReroutingCreationRequest, ReroutingUpdateRequest
- ii) Optional otherwise.

### f) MeasureSubType subType (Contextual)

The specific type of this measure.

When requested, this attribute is never left null.

#### Presence:

- i) Mandatory in <u>MCDMOnlyCreationRequest</u>, <u>RegulationCreationRequest</u>, <u>RegulationProposalFilingRequest</u>, <u>ReroutingCreationRequest</u>
- ii) Must be null in RegulationProposalUpdateRequest
- iii) Optional otherwise.

Constraint: See INVALID\_SUBTYPE

#### g) **boolean createdByFMP** (Contextual)

Indicates if the measure has been created by an FMP himself or not. When requested, this attribute is never left null.

- Presence:
- i) Must be null in MCDMOnlyCreationRequest, MCDMOnlyUpdateRequest, RegulationCreationRequest, RegulationProposalFilingRequest, RegulationProposalUpdateRequest, RegulationUpdateRequest, ReroutingCreationRequest, ReroutingUpdateRequest
- ii) Optional otherwise.

### h) **boolean mcdmRequired** (Contextual)

Indicates if full MCDM is required for this regulation.
mcdmRequired is False in case of proposal regulation MCDM workflow.
When requested, this attribute is never left null.
Presence:

- i) Mandatory in <u>RegulationCreationRequest</u>, <u>ReroutingCreationRequest</u>
- ii) Must be null in MCDMOnlyCreationRequest, RegulationProposalFilingRequest, RegulationProposalUpdateRequest

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- iii) Optional otherwise.
- i) HotspotId sourceHotspot (Optional)
   If this regulation was created from a hotspot resolution, id of that hotspot.
   When requested, this attribute is never left null.
- j) MeasureFromScenarioRepository scenarioReference (Optional)
  In measure list context, indicates if this measure is a measure from the scenario repository and if so this field indicates from which scenario and which measure inside that scenario. In create/update context, indicates on which scenario and measure to base the new/updated measure on (for example: to get the rerouting cost criteria to guide profile generation.)
- k) MCDMMeasureTopic mcdmInfo (Optional)
  When requesting scenario measures, (via ScenarioRegulationRetrievalRequest or ScenarioReroutingRetrievalRequest or ScenarioMCDMOnlyRetrievalRequest, the MCDMInfo can optionally be present, (if the measure needs to be coordinated via MCDM on application).

#### (3) Constraints:

a)	Name	APPLICABILITY_PERIOD_CANNOT_BE_GREATER_THAN_24_HOURS
	Attribute applicability	
Description The applicability period must be smaller or equal to 24 hours.		The applicability period must be smaller or equal to 24 hours.

b)	Name	INVALID_SUBTYPE	
	Attribute	subType	
	-	Attribute subType must be equals to GROUND_DELAY when filing a regulation proposal.	

(4) Extended by: RegulationOrMCDMOnly, Rerouting.

# 4.80. MeasureFromScenarioRepository




Figure 4.11. MeasureFromScenarioRepository Class Diagram

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### (2) Attributes:

- a) **ScenarioId scenarioId** (Mandatory)
- b) MeasureId measureId (Mandatory)
- (3) <u>Used by: Measure</u>.

#### 4.81. MeasureId

- (1) Represents a regulation or rerouting identifier.
- (2) Choices:
  - a) RegulationId REGULATION
     The regulation unique identifier.
  - b) **ReroutingId REROUTING**The rerouting unique identifier.
  - c) RegulationId MCDM\_ONLY
    The mcdm only unique identifier.
- (3) <u>Used by:</u> <u>FlightMCDMInfo</u>, <u>MeasureOpLogRetrievalRequest</u>, <u>FlightListByMeasureRequest</u>, <u>MCDMTopicListRequestSelector</u>, <u>NetworkImpactAssessmentRetrievalRequest</u>, <u>MeasureIdAndTV</u>, <u>MeasureFromScenarioRepository</u>, <u>MCDMStatefulTopic</u>.

#### 4.82. MeasureIdAndTV

- (1) Represents a summary of a measures inside a scenario: it gives the measureld and the traffic volume id on which the measure is. In addition it describes for a rerouting measure, the (indirectty) off-loaded traffic volumes.
- (2) Attributes:
  - a) MeasureId measureId (Mandatory)
  - b) <u>TrafficVolumeId</u> tvId (Optional)
  - c) Set<<u>AirspaceId</u>> offLoadAirspaces (Mandatory) Constraint: Size must be comprised between 0 and ∞.
- (3) <u>Used by: ScenarioAttributes.</u>

# 4.83. MeasureListReplyData

- (1) Abstract reply data associated to the reply of the abstract <u>RegulationOrMCDMOnlyListRequest</u> or <u>ReroutingListRequest</u>.
- (2) Attributes:

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

### a) **boolean planTransferred** (Optional)

Indicates if the plan has been transferred to the OPERATIONAL dataset.

When false, it means that the most up-to-date data can be found in the F0RECAST dataset. (See also Forecast and Operational Datasets)

Must be present if the dataset is OPERATIONAL, must be null otherwise.

### b) **boolean planCutOffReached** (Optional)

Indicates if the plan can still be updated in the FORECAST dataset, i.e. if the forecast cutoff time has been reached or not.

Must be present if the dataset is FORECAST, must be null otherwise.

### c) <u>Dataset</u> dataset (Mandatory)

Dataset on which the regulations are requested.

(3) <u>Extended by: RegulationOrMCDMOnlyListReplyData, ReroutingListReplyData.</u>

### 4.84. <<abstract>> MeasureListRequest




Figure 4.12. <<abstract>> MeasureListRequest Class Diagram

- (1) Abstract request to query an NM measure list, as well as to retrieve the measure details.
- (2) <u>Inherits from: Request</u>.
- (3) Attributes:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### a) **Dataset dataset** (Mandatory)

Dataset on which the measures are requested.

See Forecast and Operational Datasets and Simulation Datasets

Constraint: See INVALID QUERY PERIOD RANGE

### b) **DateTimeMinutePeriod** queryPeriod (Mandatory)

Selects the measures of which the applicability period overlaps this queryPeriod. The MeasureListRequest provides the measure list for:

- The tactical day: up-to-date view of the set of measures that exist for today in the NM system, at the time of the request
- ii) One pre-tactical day (tomorrow): the request returns the up-to-date view of the set of measures applying tomorrow in the NM system (hence including cross-midnight measures), at the time of the request.
- iii) 21 post-operations days (yesterday down to 21 days in the past): the request returns the set of measures in the system for that day, as they existed at the end of the day: consequently, a request for a post-ops day always returns the same result regardless of the time at which it is issued in the day.

#### Constraints:

- i) See <a href="INVALID\_QUERY\_PERIOD\_RANGE">INVALID\_QUERY\_PERIOD\_RANGE</a>
- ii) See MAX QUERY PERIOD DURATION IS 2 DAYS

#### c) Set<<u>TrafficVolumeIdWildcard</u>> tvs (Optional)

Selects the regulations applying to the given traffic volumes.

The logical OR operator is meant between the items in the set.

By default, all traffic volumes are considered.

Constraint: Size must be comprised between 1 and 100.

#### d) Set<<u>TrafficVolumeSetIdWildcard</u>> tvSets (Optional)

Selects the regulations applying to a traffic volume belonging to at least one of the given traffic volume sets.

The logical OR operator is meant between the items in the set.

By default, all traffic volumes of all traffic volume sets are considered.

Constraint: Size must be comprised between 1 and 100.

#### (4) Constraints:

a)	Name	MAX_QUERY_PERIOD_DURATION_IS_2_DAYS
	Attribute	queryPeriod
	Description	The maximum duration of queryPeriod is 2 days

b)	Name	INVALID_QUERY_PERIOD_RANGE
	Attributes	queryPeriod, dataset

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Description	The dataset.type on which the measures are requested and the queryPeriod must be set according to the following rules:	
		if the DatasetType is equals to FORECAST the queryPeriod shall be defined within the range [ today today+5d ]
	1 '	if the DatasetType is equals to OPERATIONAL the queryPeriod shall be defined within the range [ today tomorrow ]

(5) <u>Extended by: RegulationOrMCDMOnlyListRequest, ReroutingListRequest.</u>

## 4.85. <<enumeration>> MeasureSubType

- (1) The sub type of the measure.
- (2) Values:
  - a) AIRBORNE HORIZONTAL REROUTING
  - b) AIRBORNE\_LEVEL\_CAP
  - c) **GROUND\_DELAY**
  - d) **GROUND\_HORIZONTAL\_REROUTING**
  - e) GROUND LEVEL CAP
  - f) MILES\_MINUTES\_IN\_TRAIL
  - g) MINIMUM DEPARTURE INTERVAL
  - h) OTHER\_KIND\_OF\_STAM\_MEASURE
  - i) TAKE\_OFF\_NOT\_AFTER
  - j) TAKE\_OFF\_NOT\_BEFORE
  - k) TERMINAL PROCEDURE CHANGE
- (3) <u>Used by: Measure, FlightAtfcmMeasureLocation</u>.

# 4.86. NMOCManagedSimulation

- (1) The simulation is managed (start/stop) and prepared by NMOC for the other users (B2B & B2C) to have a look at the results.
- Optionally the users can modify the measures and tactical updates to evaluate the effect.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- The dataset corresponding to a NMOCManagedSimulation simulation has as type NMOC MANAGED SIMULATION.
- (4) Inherits from: <u>Simulation</u>.
- (5) Attributes:
  - a) **DatasetReference** datasetReference (Optional)

The reference on which this simulation is based (i.e. from which environment data has been copied and where initially the flights and measures have been copied from).

Note that if the datasetReference is none, then it concerns a standalone simulation (typically for a future date with specifically prepared environment and flight data) without a reference.

Constraint: See **INVALID DATASET REFERENCE TYPE** 

#### (6) Constraints:

a)	Name	INVALID_DATASET_REFERENCE_TYPE
	Attribute	datasetReference
	Description	DatasetReference.type must be 0PERATIONAL or FORECAST.

b)	Name	INVALID_SIMULATION_IDENTIFIER_TYPE
	Attribute	dataset
	Description	SimulationIdentifier.simulationType must be NMOC_MANAGED_SIMULATION.

# 4.87. OtherReroutingConstraint

- (1) Describes a rerouting constraint not already listed.
- (2) <u>Inherits from:</u> <u>ReroutingConstraint</u>.

#### 4.88. OTMV

- (1) Definition of an OTMV.
- (2) <u>Attributes:</u>
  - a) <u>TrafficVolumeId</u> trafficVolume (Mandatory) Traffic volume to which this OTMV applies.
  - b) **DurationHourMinute otmvDuration** (Mandatory) The duration of this OTMV.
  - c) OTMVPeak peak (Optional)
    The peak configuration of this OTMV.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

d) **OTMVSustained sustained** (Optional) The sustained configuration of this OTMV.

e) **string remark** (Optional)

<u>Constraint: Pattern:</u> TEXT{1,255}

(3) Used by: PlannedOTMV.

#### 4.89. OtmvAlert

- (1) OTMV alert for a date time period. This indicates which count periods/intervals are involved in an OTMV peak or an OTMV sustained alert: all count periods that start in OtmvAlert.period are considered to have an OTMV alert with OtmvStatus.
- (2) Attributes:
  - a) **DateTimeMinutePeriod period** (Mandatory) Period of the OTMV alert.
  - b) OtmyStatus status (Mandatory)
    Status of the OTMV alert.
- (3) <u>Used by: TrafficCountsReplyData, DeltaCounts.</u>

#### 4.90. OTMVPeak

- (1) OTMV peak data.
- (2) Attributes:
  - a) OTMVThreshold threshold (Mandatory)
    Peak threshold of an OTMV.
- (3) Used by: OTMV.

#### 4.91. OTMVPlan

- (1) OTMV plan for a given traffic volume on a given day.
- (2) An OTMV plan is a special plan in the sense that for a given traffic volume there can be multiple OTMV durations. For each of these durations there exists a plan covering the full day (completely independent of any other duration). In update mode, only one duration can be updated in a single request. For a specific (traffic volume, OTMV duration) plan, there can be cases where there is no data known. So there are (traffic volume, OTMV duration) pairs where there is NO\_DATA at all or only for some periods.
- (3) In a retrieval context, the plan for a (traffic volume, OTMV duration) is said to be 'complete' in the sense that it contains all the plan entries from all involved data sources (including NO\_DATA data source in case no info is known).

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- (4) In an update context, the plan can be complete (if the B2B client designer decided to overwrite the default CACD values) or limited to the (full list) of (pre-)tactical updates with the gaps marked as AIRSPACE (meaning in update context: either NO\_DATA or CACD) datasource (to obtain a complete time partition).
- (5) In any case, periods in the time partition marked with datasource AIRSPACE correspond to removing any potential (pre-)tactical update and hence reset the corresponding values to the CACD definition for that period.
- (6) <u>Inherits from:</u> <u>TacticalConfigurationPlan</u>.
- (7) Attributes:
  - a) <u>TrafficVolumeId</u> trafficVolume (Mandatory) Traffic volume to which this OTMV plan applies.
  - b) Map<<u>DurationHourMinute</u>, <u>OTMVPlanForDuration</u>> otmvPlans (Mandatory)
    The set of durations for which there are OTMV updates and for each duration, the OTMV plan.

If only one specific duration was requested, then the map will only contain the OTMV plan for that duration.

Constraints:

- i) Size must be comprised between 0 and ∞.
- ii) See <u>INCOMPLETE SCHEDULE</u>
- iii) See <u>INVALID SCHEDULE</u>
- iv) See ONLY ONE ENTRY CAN BE UPDATED IN PLAN

#### (8) <u>Constraints:</u>

a)	Name	INCOMPLETE_SCHEDULE
	Attribute	otmvPlans
		CapacityPlanUpdateRequest,OTMVPlanUpdateRequest,RunwayCon- figurationPlanUpdateRequest,SectorConfigurationPlanUpdate- Request,TrafficVolumeActivationPlanUpdateRequest
	•	clientSchedule has gaps and/or overlaps in the time partition or is not covering exactly one day.

b)	Name	ONLY_ONE_ENTRY_CAN_BE_UPDATED_IN_PLAN
Attribute <u>otmvPlans</u>		<u>otmvPlans</u>
		CapacityPlanUpdateRequest,OTMVPlanUpdateRequest,RunwayCon- figurationPlanUpdateRequest,SectorConfigurationPlanUpdate- Request,TrafficVolumeActivationPlanUpdateRequest

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Description	Only one entry in the otmvPlans map attribute can be updated (i.e., for o	
	duration).	

c)	Name	INVALID_SCHEDULE
	Attribute	otmvPlans
		CapacityPlanUpdateRequest,OTMVPlanUpdateRequest,RunwayConfigurationPlanUpdateRequest,SectorConfigurationPlanUpdateRequest,Request,TrafficVolumeActivationPlanUpdateRequest
	•	The duration key used in the otmvPlans map attribute has to be equal to the duration of all OTMVs linked to that duration key.

#### 4.92. OTMVPlanForDuration

(1) The OTMV plan for a specific duration.

#### (2) Attributes:

### a) Set<<u>PlannedOTMV</u>> nmSchedule (Contextual)

The plan resulting from the superimposition of all constraints from all data sources, which the NM system is using as plan for its own calculations.

The NM schedule exposes the complete time partition of the configurations for the day, i.e. the data coming from the various data sources contributing to the NM view of the plan: these data sources are defined in <a href="PlanDataSource">PlanDataSource</a>.

The NM schedule cannot be updated directly by the caller; it is the outcome of updates via the various data sources.

The possible values of <u>dataSource</u> are limited to NO\_DATA, AIRSPACE and TACTICAL. <u>Presence:</u>

- i) Must be null in <u>CapacityPlanUpdateRequest</u>, <u>OTMVPlanUpdateRequest</u>, <u>RunwayConfigurationPlanUpdateRequest</u>, <u>SectorConfigurationPlanUpdateRequest</u>, <u>dateRequest</u>, <u>TrafficVolumeActivationPlanUpdateRequest</u>
- ii) Mandatory otherwise.

Constraint: Size must be comprised between 0 and ∞.

### b) Set<<u>PlannedOTMV</u>> clientSchedule (Mandatory)

(Pre-)tactical OTMVs associated to their applicability period, as maintained by the client. This plan contains only the updated configurations together with an indication that the default CACD values (AIRSPACE datasource) apply when not updated (cf. <a href="PlanDataSource">PlanDataSource</a>). The actual CACD values for these CACD periods can be found in the nmSchedule In an update context, the clientSchedule can be complete (if the B2B client designer decided to overwrite the default CACD values) or limited to the actual differences with regards to the CACD defaults. This is a B2B client designer's decision and depends on how CACD wants to be used in combination with the B2B. If the clientSchedule only contains the actual differences with regards to the CACD defaults, then the clientschedule still needs

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

to contain the full list of (pre-) tactical updates and for the non (pre-) tactically updated periods, an explicit indication that the CACD values need to be used (but without repeating the CACD values themselves). So in any case, the clientschedule needs to be a complete time partition for the full day.

In any case, it is of drastic importance to understand that an entry in the schedule (i.e. a period) overwrites all CACD values in that period.

The possible values of <u>dataSource</u> are limited to AIRSPACE and TACTICAL - the AIRSPACE value meaning that the value associated to the <u>applicabilityPeriod</u> is the CACD one (i.e. CACD or that there is no data defined in the CACD), and the TACTICAL value meaning that this plan entry corresponds to the explicit tactical update expressed via <u>otmv</u>. Constraint: Size must be comprised between 0 and  $\infty$ .

(3) <u>Used by: OTMVPlans, OTMVPlan</u>.

### 4.93. OTMVPlans

- (1) OTMV plans for one or more traffic volumes on a given day.
- An OTMV plan is a special plan in the sense that for a given traffic volume there can be multiple OTMV durations. For each of these durations there exists a plan covering the full day (completely independent of any other duration). In update mode, only one duration can be updated in a single request. For a specific (traffic volume, OTMV duration) plan, there can be cases where there is no data known. So there are (traffic volume, OTMV duration) pairs where there is NO\_DATA at all or only for some periods.
- (3) In a retrieval context, the plan for a (traffic volume, OTMV duration) is said to be 'complete' in the sense that it contains all the plan entries from all involved data sources (including NO\_DATA data source in case no info is known).
- (4) In an update context, the plan can be complete (if the B2B client designer decided to overwrite the default CACD values) or limited to the (full list) of (pre-)tactical updates with the gaps marked as AIRSPACE (meaning in update context: either NO\_DATA or CACD) datasource (to obtain a complete time partition).
- (5) In any case, periods in the time partition marked with datasource AIRSPACE correspond to removing any potential (pre-)tactical update and hence reset the corresponding values to the CACD definition for that period.
- (6) <u>Inherits from: TacticalConfigurationPlan.</u>
- (7) <u>Attributes:</u>
  - a) Map<<u>TrafficVolumeId</u>, Map<<u>DurationHourMinute</u>, <u>OTMVPlanForDuration</u>>>
     tvsOTMVs (Mandatory)
     Constraints:
    - i) Size must be comprised between 0 and  $\infty$ .
    - ii) Item size must be comprised between 0 and  $\infty$ .

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- iii) See INCOMPLETE SCHEDULE
- iv) See <a href="INVALID\_SCHEDULE">INVALID\_SCHEDULE</a>
- v) See ONLY\_ONE\_ENTRY\_CAN\_BE\_UPDATED\_IN\_PLAN

### (8) <u>Constraints:</u>

a)	Name	INCOMPLETE_SCHEDULE
	Attribute	tvs0TMVs
		CapacityPlanUpdateRequest,OTMVPlanUpdateRequest,RunwayCon- figurationPlanUpdateRequest,SectorConfigurationPlanUpdate- Request,TrafficVolumeActivationPlanUpdateRequest
	-	clientSchedule has gaps and/or overlaps in the time partition or is not covering exactly one day.

b)	Name	ONLY_ONE_ENTRY_CAN_BE_UPDATED_IN_PLAN
	Attribute	tvs0TMVs
		CapacityPlanUpdateRequest,OTMVPlanUpdateRequest,RunwayConfigurationPlanUpdateRequest,SectorConfigurationPlanUpdateRequest,Request,TrafficVolumeActivationPlanUpdateRequest
	Description	Only one entry in the otmvPlans map attribute can be updated (i.e., for one duration).

c)	Name	INVALID_SCHEDULE
	Attribute	tvsOTMVs
		CapacityPlanUpdateRequest,OTMVPlanUpdateRequest,RunwayConfigurationPlanUpdateRequest,SectorConfigurationPlanUpdateRequest Request,TrafficVolumeActivationPlanUpdateRequest
	•	The duration key used in the otmvPlans map attribute has to be equal to the duration of all OTMVs linked to that duration key.

(9) <u>Used by: OTMVPlanRetrievalReply, OTMVPlanUpdateRequest, OTMVPlanUpdateReply.</u>

# 4.94. <<enumeration>> OtmvStatus

- (1) Status of a OTMV alert.
- (2) <u>Values:</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Value Description	
PEAK	Above the peak value
SUSTAINED	"Above" the sustained value (taking into account OTMVSus- tained.crossingOccurrences and OTMVSus- tained.elapsed.

Table 4.3. <<enumeration>> OtmvStatus

(3) <u>Used by: LoadStateAtReferenceLocation, OtmvAlert.</u>

### 4.95. OTMVSustained

- (1) OTMV sustained data.
- (2) Attributes:
  - a) **OTMVThreshold threshold** (Mandatory) Sustained threshold of an OTMV.
  - b) int crossingOccurrences (Mandatory)

Number of crossing occurrences of the sustained threshold within elapsed, before this OTMV triggers an alert.

Constraint: Range: [1,9999[.

- c) **DurationHourMinute elapsed** (Mandatory)

  Duration of the time window on which crossingOccurrences are counted.
- (3) Used by: OTMV.

# 4.96. typedef<int> OTMVThreshold

- (1) Threshold type used in OTMVs, in flights per user-defined OTMV duration.
- (2) Range: [0,9998[.
- (3) <u>Used by: OTMVSustained, OTMVPeak.</u>

#### 4.97. OTMVWithDuration

- (1) Composite object which contains trafficVolume and duration .
- (2) Attributes:
  - a) **TrafficVolumeId trafficVolume** (Mandatory) The traffic volume for which the OTMV plan is requested.
  - b) <u>DurationHourMinute</u> otmvDuration (Optional)
    Selects the OTMVs applying for the given traffic volume according to their OTMV duration.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

When not specified, all duration are considered.

(3) <u>Used by: OTMVPlanRetrievalRequest.</u>

#### 4.98. <<strict enumeration>> PlanDataSource

- (1) A source of data for a plan, within or outside NM.
- (2) Values:

#### a) **AIRSPACE**

Data from the NM Airspace system (CACD), the data is either baselined with the AIRAC or results from a live update.

#### b) **MEASURE**

Data resulting from the application of a measure in the NM system.

#### c) NO DATA

There is no data defined in NM.

#### d) TACTICAL

Following a tactical update, typically, from the NOP user (B2B or B2C).

(3) <u>Used by: PlannedOTMV, PlannedCapacity, RunwayConfiguration, PlannedTrafficVolumeActivation, PlannedSectorConfigurationActivation, PlannedRunwayConfigurations.</u>

# 4.99. PlannedCapacities

- (1) Planned Capacities for to be mapped on TrafficVolumeId element in Map.
- (2) Attributes:

### a) Set<<u>PlannedCapacity</u>> nmSchedule (Contextual)

The plan resulting from the superimposition of all constraints from all data sources, which the NM system is using as plan for its own calculations.

The NM schedule exposes the complete time partition of the configurations for the day, i.e. the data coming from the various data sources contributing to the NM view of the plan: these data sources are defined in <a href="PlanDataSource">PlanDataSource</a>.

The NM schedule cannot be updated directly by the caller; it is the outcome of updates via the various data sources.

The possible values of <u>dataSource</u> are limited to NO\_DATA, AIRSPACE, TACTICAL and MEASURE - the MEASURE value being used to express that the <u>capacity</u> is derived from a regulation.

#### Presence:

i) Must be null in <u>CapacityPlanUpdateRequest</u>, <u>OTMVPlanUpdateRequest</u>, <u>RunwayConfigurationPlanUpdateRequest</u>, <u>SectorConfigurationPlanUpdateRequest</u>, <u>dateRequest</u>, <u>TrafficVolumeActivationPlanUpdateRequest</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

ii) Mandatory otherwise.

Constraint: Size must be comprised between 0 and ∞.

#### b) Set<<u>PlannedCapacity</u>> clientSchedule (Mandatory)

(Pre-)tactical capacities associated to their applicability period, as maintained by the client. This plan contains only the updated configurations together with an indication that the default CACD values apply when not updated (cf. <a href="PlanDataSource">PlanDataSource</a>). The actual CACD values for these CACD periods can be found in the nmSchedule

In an update context, the clientSchedule can be complete (if the B2B client designer decided to overwrite the default CACD values) or limited to the actual differences with regards to the CACD defaults. This is a B2B client designer's decision and depends on how CACD wants to be used in combination with the B2B. If the clientSchedule only contains the actual differences with regards to the CACD defaults, then the clientschedule still needs to contain the full list of (pre-) tactical updates and for the non (pre-) tactically updated periods, an explicit indication that the CACD values need to be used (but without repeating the CACD values themselves). So in any case, the clientschedule needs to be a complete time partition for the full day.

In any case, it is of drastic importance to understand that an entry in the schedule (i.e. a period) overwrites all CACD values in that period.

The possible values of <u>dataSource</u> are limited to AIRSPACE and TACTICAL - the AIRSPACE value meaning that the value associated to the <u>applicabilityPeriod</u> is the CACD one (i.e. CACD or that there is no data defined in the CACD), and the TACTICAL value meaning that this plan entry corresponds to the explicit tactical update expressed via <u>capacity</u>. <u>Constraint:</u> Size must be comprised between 0 and  $\infty$ .

(3) <u>Used by: CapacityPlans</u>.

# 4.100. PlannedCapacity

- (1) An entry within a capacity plan.
- (2) Attributes:
  - a) **DateTimeMinutePeriod applicabilityPeriod** (Mandatory) The time period in the plan to which this entry applies.
  - b) PlanDataSource dataSource (Mandatory)

The data source of this entry in the plan. Constraints:

- i) See <u>INVALID\_DATASOURCE</u>
- ii) See <u>VALUE CANNOT BE NULL</u>
- iii) See VALUE MUST BE NULL
- c) Capacity capacity (Optional)
  Capacity
  Constraints:

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

- i) See <u>VALUE\_CANNOT\_BE\_NULL</u>
- ii) See <u>VALUE MUST BE NULL</u>

### (3) Constraints:

a)	Name	VALUE_CANNOT_BE_NULL
	Attributes	dataSource, capacity
		capacity cannot be null if dataSource is TACTICAL. For nmSchedule: capacity cannot be null if dataSource is different from NO_DATA.

b)	Name	VALUE_MUST_BE_NULL
	Attributes	dataSource, capacity
	-	capacity must be null if dataSource is NO_DATA. For clientSchedule: capacity must be null if dataSource is not TAC-TICAL.

c)	Name	INVALID_DATASOURCE
	Attribute	<u>dataSource</u>
		NO_DATA is not a valid dataSource in an update context.  MEASURE is not a valid dataSource in an update context.

(4) <u>Used by: PlannedCapacities</u>.

### 4.101. PlannedOTMV

- (1) An entry within an OTMV plan.
- (2) Attributes:
  - a) **DateTimeMinutePeriod applicabilityPeriod** (Mandatory) The time period in the plan to which this entry applies.
  - b) PlanDataSource dataSource (Mandatory)
    The data source of this entry in the plan.
    Constraints:
    - i) See <a href="INVALID\_DATASOURCE">INVALID\_DATASOURCE</a>
    - ii) See <u>VALUE\_CANNOT\_BE\_NULL</u>
    - iii) See <u>VALUE\_MUST\_BE\_NULL</u>

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

c) OTMV otmv (Optional)

**OTMV** 

**Constraints:** 

- i) See <u>VALUE\_CANNOT\_BE\_NULL</u>
- ii) See <u>VALUE MUST BE NULL</u>

#### (3) Constraints:

a)	Name	VALUE_CANNOT_BE_NULL
	Attributes	dataSource, otmv
		otmv cannot be null if dataSource is TACTICAL.  For nmSchedule: otmv cannot be null if dataSource is different from NO_DATA.

b)	Name	VALUE_MUST_BE_NULL
	Attributes	dataSource, otmv
	-	otmv must be null if dataSource is NO_DATA. For clientSchedule: otmv must be null if dataSource is not TACTICAL.

c)	Name	INVALID_DATASOURCE
	Attribute	dataSource
		NO_DATA is not a valid dataSource in an update context. MEASURE is not a valid dataSource in an update context.

(4) <u>Used by: OTMVPlanForDuration</u>.

# 4.102. PlannedRunwayConfigurations

- (1) An entry within an aerodrome runway configuration plan.
- (2) Attributes:
  - a) **DateTimeMinutePeriod applicabilityPeriod** (Mandatory) The time period in the plan to which this entry applies.
  - b) PlanDataSource dataSource (Mandatory)
    The data source of this entry in the plan.
  - c) Set<<u>RunwayConfiguration</u>> runwayConfigurations (Optional)
    Full set of runway configurations for an aerodrome within applicabilityPeriod
    <u>Constraint:</u> Size must be comprised between 0 and ∞.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

(3) <u>Used by: RunwayConfigurationPlan.</u>

# 4.103. PlannedSectorConfigurationActivation

- An entry within a sector configuration plan its presence in the plan denotes the activation of the associated sector configuration.
- (2) Attributes:
  - a) **DateTimeMinutePeriod applicabilityPeriod** (Mandatory) The time period in the plan to which this entry applies.
  - b) PlanDataSource dataSource (Mandatory)
    The data source of this entry in the plan.
    Constraints:
    - i) See <u>INVALID\_DATASOURCE</u>
    - ii) See <u>VALUE CANNOT BE NULL</u>
    - iii) See <u>VALUE MUST BE NULL</u>
  - c) SectorConfigurationId sectorConfigurationId (Optional)
    Unique Id of the sector configuration, as known in the NM system.
    Constraints:
    - i) See <u>VALUE\_CANNOT\_BE\_NULL</u>
    - ii) See <u>VALUE MUST BE NULL</u>
- (3) Constraints:
  - a) Name VALUE\_CANNOT\_BE\_NULL

    Attributes dataSource, sectorConfigurationId

    Description sectorConfigurationId cannot be null if dataSource is TACTICAL.

    This is applicable for both nmSchedule and clientSchedule.
  - Name VALUE\_MUST\_BE\_NULL

    Attributes dataSource, sectorConfigurationId

    Description sectorConfigurationId must be null if dataSource is not TACTICAL. This is only applicable for the clientSchedule.
  - C) Name INVALID\_DATASOURCE
    Attribute dataSource
    Description NO\_DATA is not a valid dataSource in an update context.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

MEASURE is not a valid dataSource in an update context.

(4) Used by: SectorConfigurationPlan.

### 4.104. PlannedTrafficVolumeActivation

- (1) Denotes whether a traffic volume is active or not during a period.
- (2) Attributes:
  - a) **DateTimeMinutePeriod applicabilityPeriod** (Mandatory) The time period in the plan to which this entry applies.
  - b) PlanDataSource dataSource (Mandatory)
    The data source of this entry in the plan.
    Constraints:
    - i) See <a href="INVALID\_DATASOURCE">INVALID\_DATASOURCE</a>
    - ii) See <u>VALUE\_CANNOT\_BE\_NULL</u>
    - iii) See <u>VALUE\_MUST\_BE\_NULL</u>
  - c) **boolean active** (Optional)
    Indicates if the traffic volume is active or not during applicabilityPeriod Constraints:
    - i) See <u>VALUE CANNOT BE NULL</u>
    - ii) See <u>VALUE MUST BE NULL</u>
- (3) Constraints:

a)	Name	VALUE_CANNOT_BE_NULL
	Attributes	dataSource, active
		active cannot be null if dataSource is TACTICAL. For nmSchedule: active must be true if dataSource is AIRSPACE.

b)	Name	VALUE_MUST_BE_NULL
	Attributes	dataSource, active
	•	active must be null if dataSource is NO_DATA.
		For clientSchedule: active must be null if dataSource is not TACTICAL.

c)	Name	INVALID_DATASOURCE
----	------	--------------------

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Attribute	<u>dataSource</u>
-	NO_DATA is not a valid dataSource in an update context.
MEASURE is not a valid dataSource in an update context.	

(4) <u>Used by: PlannedTrafficVolumeActivations</u>, <u>TrafficVolumeActivationPlan</u>.

### 4.105. PlannedTrafficVolumeActivations

- (1) PlannedTrafficVolumeActivations contains two sets of PlannedTrafficVolumeActivation called client and nm schedules.
- (2) Attributes:
  - a) Set<<u>PlannedTrafficVolumeActivation</u>> nmSchedule (Contextual)

The plan resulting from the superimposition of all constraints from all data sources, which the NM system is using as plan for its own calculations.

The NM schedule exposes the complete time partition of the configurations for the day, i.e. the data coming from the various data sources contributing to the NM view of the plan: these data sources are defined in PlanDataSource.

The NM schedule cannot be updated directly by the caller; it is the outcome of updates via the various data sources.

In nmSchedule the possible values of <u>dataSource</u> are limited to NO\_DATA, AIRSPACE, TACTICAL and MEASURE.

Note that NO\_DATA in nmClientSchedule means either inactive or that no data has been specified.

Presence:

- i) Must be null in <u>CapacityPlanUpdateRequest</u>, <u>OTMVPlanUpdateRequest</u>, RunwayConfigurationPlanUpdateRequest, <u>SectorConfigurationPlanUpdateRequest</u>, <u>dateRequest</u>, <u>TrafficVolumeActivationPlanUpdateRequest</u>
- ii) Mandatory otherwise.

Constraint: Size must be comprised between 0 and ∞.

b) Set<<u>PlannedTrafficVolumeActivation</u>> clientSchedule (Mandatory)

(Pre-)tactical traffic volume activations associated to their applicability period, as maintained by the client. This plan contains only the updated configurations together with an indication (AIRSPACE datasource) that the default CACD/sector config derived values apply when not updated (cf. <a href="PlanDataSource">PlanDataSource</a>). The actual activity for these airspace datasource periods can be found in the nmSchedule

In an update context, the clientSchedule can be complete (if the B2B client designer decided to overwrite the default CACD values) or limited to the actual differences with regards to the AIRSPACE defaults. This is a B2B client designer's decision and depends on how CACD wants to be used in combination with the B2B. If the clientSchedule only contains the actual differences with regards to the AIRSPACE defaults, then the clientschedule still needs to contain the full list of (pre-) tactical updates and for the non (pre-) tactically updated periods, an explicit indication that the AIRSPACE values need to be used (but without repeating the

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

NO\_DATA/CACD/sector config derived values themselves). So in any case, the clientschedule needs to be a complete time partition for the full day.

In any case, it is of drastic importance to understand that an entry in the schedule (i.e. a period) overwrites all CACD/sector config derived values in that period.

The possible values of <u>dataSource</u> are limited to AIRSPACE and TACTICAL - the AIRSPACE value meaning that the value associated to the <u>applicabilityPeriod</u> is the CACD one (i.e. CACD or the TV activation derived from a sector configuration or that there is no data defined in CACD), and the TACTICAL value meaning that this plan entry corresponds to the explicit tactical update expressed via <u>active</u>.

Constraint: Size must be comprised between 0 and ∞.

(3) Used by: TrafficVolumeActivationPlans.

### 4.106. PointLocation

- (1) Point location.
- (2) <u>Inherits from:</u> <u>Location</u>.

### 4.107. Regulation




Figure 4.13. Regulation Class Diagram

- (1) Regulation.
- (2) <u>Inherits from:</u> <u>RegulationOrMCDMOnly</u>.
- (3) Attributes:
  - a) RegulationState regulationState (Contextual)
     Current state of the regulation.
     When requested, this attribute is never left null.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

#### Presence:

- i) Must be null in <a href="RegulationCreationRequest">RegulationUpdateRequest</a>
- ii) Optional otherwise.
- (4) <u>Used by:</u> <u>RegulationListReply, RegulationMessage, RegulationUpdateRequest, RegulationCreationReply, ScenarioRegulationRetrievalReply, RegulationCancelReply, RegulationCreationRequest, RegulationUpdateReply.</u>

### 4.108. RegulationCause

- (1) Describes the cause of a regulation.
- (2) <u>Attributes:</u>
  - a) RegulationReason reason (Mandatory)

    The reason of the regulations due to this regulation cause.
  - b) RegulationLocationCategory locationCategory (Mandatory)
    The location category of the regulations due to this regulation cause.
  - c) int iataDelayCode (Mandatory)
    The IATA delay code of the regulations due to this regulation cause.

    Constraint: Range:  $[0, \infty[$ .
- (3) Used by: Flight.

# 4.109. RegulationExceptionalConstraint

- (1) Groups all exceptional constraints expressed by a regulation for a specific initial constraint period.
- (2) In an initial constraint period, flights can either:
  - a) Be suspended if the flight is not confirmed (and FCM is mandatory) or if the flight has an insufficient minimum runway visible range
  - b) Be shifted
  - c) Use a slot inside the initial constraint period (corresponding to the rates of that period)
- (3) Attributes:
  - a) **DistanceM** runwayVisualRange (Optional)

For departure/arrival regulations: minimum visible range in meters for a flight to use slots in the corresponding constraint period. If the flight has an insufficient runway visual range, the flight is either shifted at the end of the constraint period (if shift is true and the flight has a minimum runwayVisualRange), or is suspended (if shift is false or if the flight has no minimum runwayVisualRange)

Constraint:Range: [0,999[.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

<u>Constraint:</u> See <u>INCONSISTENT\_RUNWAY\_VISUAL\_RANGE\_AND\_FCM\_MANDATORY</u>

### b) **boolean fcmMandatory** (Mandatory)

Indicates if the flight must be confirmed in this regulation before trying to find a slot for this flight in the associated constraint period. If the flight is not confirmed in this exceptional constraint, the flight is suspended.

Constraint: See INCONSISTENT RUNWAY VISUAL RANGE AND FCM MANDATORY

### c) **boolean shift** (Mandatory)

If the flight is not suspended due to fcmMandatory and no minimum visible range is required, flights affected by this constraint must be shifted to the end of the constraint period when trying to find a slot (and possibly further, depending on next constraint periods). If the flight is not suspended due to fcmMandatory but a minimum visible range is required, the flight is shifted if it has an insufficient runwayVisualRange.

#### (4) Constraint:

a)	Name	INCONSISTENT_RUNWAY_VISUAL_RANGE_AND_FCM_MANDATORY
Attributes <u>fcmMandatory</u> , <u>runwayVisualRange</u>		fcmMandatory, runwayVisualRange
		RegulationCreationRequest, RegulationProposalFilingRequest, RegulationUpdateRequest, RegulationProposalUpdateRequest
	Description	If fcmMandatory is true then runwayVisualRange must be null

(5) <u>Used by: RegulationInitialConstraint.</u>

# 4.110. <<enumeration>> RegulationField

- (1) Enumerates the fields that the caller may request to be returned in <u>Regulation</u> objects when returned by <u>RegulationListRequest</u>.
- (2) As a rule, client applications should never request regulation fields that they do not need. Client applications typically implement a query/retrieve pattern:
  - a) Query the small number of most relevant regulation fields to display to the end user
  - b) Retrieve more details for a given regulation when the end user has selected a regulation from the list

### (3) Values:

- a) applicability
- b) autolink
- c) createdByFMP
- d) dataId

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- e) delayConfirmationThreshold
- f) delayTVSet
- g) **externallyEditable**
- h) initialConstraints
- i) lastUpdate
- j) linkedRegulations
- k) location
- ncdmRequired
- m) measureCherryPicked
- n) **noDelayWindow**
- o) protectedLocation
- p) **reason**
- q) regulationState
- r) **remark**
- s) scenarioReference
- t) sourceHotspot
- u) **subType**
- v) **supplementaryConstraints**
- w) updateCapacityRequired
- x) updateTVActivationRequired
- (4) <u>Used by: ScenarioRegulationRetrievalRequest, RegulationListRequest, RegulationPayloadConfiguration.</u>

# 4.111. typedef<string> RegulationId

- Unique id of a regulation measure (inside a given month), allocated by NM or via the user.
- Note that there can be 2 regulations with the same RegulationId over a 2 month period.
- (3) Pattern: UALPHA(UALPHA|DIGIT) {0,5}DIGIT{2}UALPHA{0,1}

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Used by: UpdateFlightInMeasureChoice, ArrivalInformation, MCDMOnlyCancelRequest, ExcludeRe-IncludeFlightInRegulation, MCDMStateUpdateRequest, TargetTakeOffAPIRequest, ATFCMSituationRegulation, ForceFlightInRegulation, RegulationCancelRequest, RegulationOrMCDMOnly, MeasureId, Flight, FlightRegulationLocation, TargetTime, FlightAtfcmMcdmOnlyLocation, FlightAtfcmRegulationLocation, RegulationProposalRevocationRequest.

# 4.112. typedef<string> RegulationIdWildcard

- (1) Either a full regulation id, or a simple wildcard for regulation ids.
- (2) Pattern: (UALPHA|DIGIT) {1,8} | (UALPHA|DIGIT) {0,7}\*
- (3) <u>Used by: RegulationOrMCDMOnlyListRequest.</u>

### 4.113. RegulationInitialConstraint

- (1) Groups all the rate information and exceptional constraints expressed by a regulation for a specific initial constraint period.
- (2) All rate values are expressed as number of slots per hour.
- (3) Attributes:
  - a) **DateTimeMinutePeriod constraintPeriod** (Mandatory) Applicability period of this constraint.
  - b) **int normalRate** (Mandatory)

Normal rate.

Constraint: Range: ] - ∞,∞[.

c) int pendingRate (Mandatory)

Pending rate.

Constraint: Range: ] - ∞,∞[.

d) **int equipmentRate** (Mandatory)

Equipment rate.

Constraint: Range: ] - ∞,∞[.

- e) RegulationExceptionalConstraint exceptionalConstraint (Optional) Exceptional constraints expressed by a regulation for a specific initial constraint period.
- (4) Used by: RegulationOrMCDMOnly.

# 4.114. <<enumeration>> RegulationLocationCategory

- (1) Enumeration of possible location categories for a regulation.
- (2) Values:
  - a) **ARRIVAL**

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices		B2B/23.0.0/Flow

- b) **DEPARTURE**
- c) **ENROUTE**
- (3) Used by: RegulationCause.

# 4.115. <<abstract>> RegulationOrMCDMOnly




Figure 4.14. <<abstract>> RegulationOrMCDMOnly Class Diagram

- (1) Common ancestor of <u>Regulation</u>, <u>RegulationProposal</u> and <u>MCDMOnly</u>.
- (2) The initialConstraints and supplementaryConstraints attributes group all the rate information and exceptional constraints expressed by a regulation.
- (3) A regulation rate describes how many slots per hour the regulation can accept, i.e. the maximal number of flights per hour accepted in the regulation. The regulation applicability period is partitioned into one or more regulation "initial constraint periods": different rates and exceptional constraints apply in each initial constraint period. The superset of initial constraint periods must cover the full applicability period, and cannot overlap it is indeed a time partition.
- (4) A regulation can also have different supplementary rates, each defined on a "supplementary period" (i.e. the period associated to a supplementary rate). The supplementary period can overlap partly or fully with one or more initial constraint periods, and with zero or more other supplementary periods. Within the NM system, the supplementary rate is added to the normal rates for the duration of the supplementary period.
- (5) There are different kinds of regulation rates:
  - a) Normal rates: nominal rate
  - b) Pending rate: rate reserved for late updater, i.e. when a flight changes significantly its profile close to the departure time, the flight has access to pending rate slots (to limit excessive delay deteriorations). Note that pending rate slots are transformed into normal rate slots at some time before the start of the applicability period of the regulation.
  - c) Equipment rate: rate reserved for flights containing the required MLS equipment in their aircraft equipment set.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

(6) <u>Inherits from: Measure</u>.

#### (7) Attributes:

### a) RegulationId regulationId (Mandatory)

The unique id of the regulation. Regulation ids are unique within an AIRAC cycle and contain at least the day (of the month) of the start date of the regulation. Note that the regulation id is immutable.

#### b) RegulationReason reason (Contextual)

Reason that triggered the creation of the regulation.

When requested, this attribute is never left null.

Presence:

- i) Mandatory in <u>MCDMOnlyCreationRequest</u>, <u>RegulationCreationRequest</u>, <u>RegulationProposalFilingRequest</u>
- ii) Optional otherwise.

Constraint: See INVALID REASON DEICING

#### c) <u>TrafficVolumeLocation</u> location (Contextual)

Information related to the location to which this regulation applies. <u>Presence:</u>

- i) Mandatory in MCDMOnlyCreationRequest, RegulationCreationRequest, RegulationProposalFilingRequest
- ii) Optional otherwise.

#### d) ReferenceLocation protectedLocation (Contextual)

Specifies the reference location that the regulation is meant to protect, when the protected reference location is not the reference location specified in location. The protectedLocation value is left null if it is the regulation reference specified in location. Presence:

- i) Must be null in MCDMOnlyCreationRequest, MCDMOnlyUpdateRequest, RegulationCreationRequest, RegulationProposalFilingRequest, RegulationProposalUpdateRequest, RegulationUpdateRequest
- ii) Optional otherwise.

#### e) RegulationInitialConstraint[] initialConstraints (Optional)

Initial constraints.

When requested, this attribute is never left null.

Constraints:

- i) Size must be comprised between 0 and 24.
- ii) See <u>CHERRY PICKED MUST BE TRUE</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- iii) See INCONSISTENT CHERRY PICKED CONSTRAINTS
- iv) See <a href="mailto:INCONSISTENT\_CHERRY\_PICKED\_INITIAL\_CONSTRAINTS">INCONSISTENT\_CHERRY\_PICKED\_INITIAL\_CONSTRAINTS</a>
- f) RegulationSupplementaryConstraint[] supplementaryConstraints (Optional) Supplementary constraints.

When requested, this attribute is never left null.

Constraints:

- i) Size must be comprised between 0 and 24.
- ii) See INCONSISTENT\_CHERRY\_PICKED\_CONSTRAINTS
- g) **string remark** (Contextual)

Remark made by the NM operations, as provided in the Initial Network Plan. This remark typically provides some more details about the reason of the regulation and refers to any NOTAM if applicable.

Presence:

- i) Mandatory in <u>MCDMOnlyCreationRequest</u>, <u>RegulationCreationRequest</u>, <u>RegulationProposalFilingRequest</u>
- ii) Optional otherwise.

Constraint: Pattern: MULTILINE\_TEXT{0,128}

h) **boolean autolink** (Contextual)

Indicates if the local delay given by this regulation is taken into account to compute the delay in other regulations.

When requested, this attribute is never left null.

Presence:

- i) Mandatory in <a href="MCDMOnlyCreationRequest">MCDMOnlyCreationRequest</a>, <a href="RegulationCreationRequest">RegulationCreationRequest</a>
- ii) Must be null in <u>RegulationProposalFilingRequest</u>, <u>RegulationProposalUpdateRequest</u>
- iii) Optional otherwise.
- i) Set<<u>RegulationId</u>> linkedRegulations (Contextual)

The set of regulations which are linked to this regulation.

When requested, this attribute is never left null. Can be empty. Presence:

- i) Must be null in <u>RegulationProposalFilingRequest</u>, <u>RegulationProposalUp-dateRequest</u>
- ii) Optional otherwise.

Constraint: Size must be comprised between 0 and 10.

j) <u>DurationHourMinute</u> noDelayWindow (Optional)

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Defines a time window (a.k.a. "window width") around the ETO within which the regulation does not delay the flight.

In certain cases, the window is applied around the minimum CTO.

Constraint: See INVALID WINDOW WIDTH

#### k) boolean updateCapacityRequired (Contextual)

Indicates that a capacity update will be automatically applied according to the rates of the regulation.

When requested, this attribute is never left null.

Presence:

- i) Mandatory in <u>MCDMOnlyCreationRequest</u>, <u>RegulationCreationRequest</u>, <u>RegulationProposalFilingRequest</u>
- ii) Optional otherwise.

### boolean updateTVActivationRequired (Contextual)

Indicates that a traffic volume activation will be achieved according to the applicability period of the regulation.

When requested, this attribute is never left null.

Presence:

- i) Mandatory in <u>MCDMOnlyCreationRequest</u>, <u>RegulationCreationRequest</u>, <u>RegulationProposalFilingRequest</u>
- ii) Optional otherwise.

### m) <u>TrafficVolumeSetId</u> delayTVSet (Contextual)

The traffic volume set to which the delay of this regulation is associated.

When requested, this attribute is never left null.

Presence:

- i) Must be null in MCDMOnlyCreationRequest, MCDMOnlyUpdateRequest, RegulationCreationRequest, RegulationProposalFilingRequest, RegulationProposalUpdateRequest, RegulationUpdateRequest
- ii) Optional otherwise.

### n) <u>DurationHourMinute</u> delayConfirmationThreshold (Optional)

If present, then the regulation has a delayConfirmationThreshold: all flights that have more delay than the delayConfirmationThreshold get suspended at EOBT - 2H.

#### (8) Constraints:

a)	Name	INCONSISTENT_CHERRY_PICKED_CONSTRAINTS
	Attributes	<pre>measureCherryPicked, initialConstraints, supplementaryCon-</pre>
		<u>straints</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

RegulationProposalFilingRequest, RegulationCreationRequest, RegulationProposalUpdateRequest, RegulationUpdateRequest
If Measure.measureCherryPicked is true then supplementaryConstraints must be null If Measure.measureCherryPicked is false then initialConstraints cannot be null.

b)	Name	INCONSISTENT_CHERRY_PICKED_INITIAL_CONSTRAINTS
	Attributes	measureCherryPicked, initialConstraints
		RegulationProposalFilingRequest, RegulationCreationRequest, RegulationProposalUpdateRequest, RegulationUpdateRequest
	•	If Measure.measureCherryPicked is true then, for each sub-period of initialConstraints, pendingRate and equipmentRate must be zero, and exceptionalConstraint must be null.

c)	Name	CHERRY_PICKED_MUST_BE_TRUE
	Attribute	<u>initialConstraints</u>
	Context	MCDMOnlyCreationRequest, MCDMOnlyUpdateRequest
	Description	The Measure.measureCherryPicked value must be set to true.

d)	Name	INVALID_REASON_DEICING
	Attribute	reason
		RegulationCreationRequest, RegulationProposalFilingRequest, RegulationUpdateRequest, RegulationProposalUpdateRequest
	Description	The Measure.reason value cannot be DEICING.

e)	Name	INVALID_WINDOW_WIDTH
	Attribute	noDelayWindow
		RegulationCreationRequest, RegulationProposalFilingRequest, RegulationUpdateRequest, RegulationProposalUpdateRequest
	Description	The Measure.noDelayWindow value cannot be 0000.

(9) <u>Extended by: RegulationProposal, Regulation, MCDMOnly.</u>

# 4.116. RegulationOrMCDMOnlyListReplyData

(1) Abstract reply data associated to the reply of the abstract <u>RegulationOrMCDMOnlyListRequest</u>.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- (2) <u>Inherits from: MeasureListReplyData</u>.
- (3) <u>Extended by: RegulationProposalListReplyData, MCDMOnlyListReplyData, RegulationListReplyData</u>, Data.

## 4.117. <<abstract>> RegulationOrMCDMOnlyListRequest




Figure 4.15. <<abstract>> RegulationOrMCDMOnlyListRequest Class Diagram

- (1) Abstract request to query an NM regulation list, as well as to retrieve the regulation details. This query method allows the caller to select the regulation fields requested in the reply (see requestedRegulationFields). NM kindly requests its customers to apply the following strategy:
  - a) As a rule, client applications should never request regulation fields that they do not need
  - b) Client applications typically implement a query/retrieve pattern:
    - i) Query the small number of most relevant regulation fields to display to the end user (using this RegulationListRequest)
    - ii) Retrieve more details for a given regulation when the end user has selected a regulation from the list (also using this RegulationListRequest, but with other requested fields)
- (2) The logical AND operator applies between all the query fields described below.
- (3) <u>Inherits from: MeasureListRequest</u>.
- (4) Attributes:
  - a) Set<RegulationIdWildcard> regulations (Optional)
    The set of regulation ids or wildcards.

If specified, the reply returns only the requested regulations.

The logical OR operator is meant between the items in the set.

Constraint: Size must be comprised between 1 and 100.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

b) Set<<u>RegulationReason</u>> reasons (Optional)

Selects the regulations with a reason that matches an entry in this set.

By default, regulations are selected regardless to their reason.

Constraint: Size must be comprised between 1 and 14.

(5) Extended by: RegulationListRequest, RegulationProposalListRequest, MCDMOnlyListRequest.

### 4.118. RegulationProposal




Figure 4.16. RegulationProposal Class Diagram

- (1) Regulation proposals are proposals to NM for creation/modification/cancellation of a regulation (see RegulationProposalListReguest).
- (2) A tailored MCDM process (a subset of the full MCDM process) is used in the proposal regulation and corresponding coordination process.
- (3) There are 2 types of proposal regulations:
  - a) With proposal flights (only supported for cherry picked regulations where the user selects the flights and the delay to attribute to flights): the user proposes a regulation, the MCDM state will be automatically set to draft. Once the regulation has been set to applied (asynchronously by NM systems), the user can add flights to the regulation (includes giving the desired CalculatedTakeOffTime or CalculatedTimeOver).

Once the flights have been added (synchronously), he user can inspect the desired result in the flightlist and counts (with includeProposalFlights).

If the user is not satisfied with the result, he can remove some flights or add some more flights or modify/revoke the proposal (via updateRegulationProposal or revokeRegulationProposal).

Once the user is happy with the results, he should modify the MCDM state to proposed so that it becomes visible to NM.

Once NMOC starts assessing the proposal, the NM actor approvalState is set to standby (i.e. acknowledged) and the MCDMState is set to COORDINATED..

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

When NM accepts (and has implemented the regulation), the NM actor approvalState is set to approved. In addition the MCDM state is set to IMPLEMENTED.

If NM rejects the proposal, the NM actor state is set to rejected and the MCDM state is set to ABANDONED. In this case the user can file a new regulation proposal (resetting the MCDM state to draft).

#### b) Without proposal flights:

When the user proposes a regulation, the MCDM state will be automatically set to PRO-POSED (visible to NM). Once NMOC starts assessing the proposal, the NM actor approval-State is set to STANDBY (i.e. ACKNOWLEDGED).

When NM accepts (and has implemented the regulation), the NM actor approvalState is set to APPROVED. In addition the MCDM state is set to IMPLEMENTED.

If NM rejects the proposal, the NM actor state is set to rejected and the MCDM state is set to ABANDONED. In this case the user can file a new regulation proposal (resetting the MCDM state to PROPOSED).

- (4) <u>Inherits from: RegulationOrMCDMOnly</u>.
- (5) <u>Attributes:</u>
  - a) **RegulationProposalKind kind** (Mandatory)
  - b) RegulationProposalAction action (Contextual)

Describes whether the proposal is to create a new regulation, or to update or cancel an existing one.

Once created, the action of the regulation proposal is immutable.

In order to replace an update by a cancellation, the proposal must be revoked and a new proposal must be filed or alternatively NMOC needs to first accept or reject the proposal. Note that the revoked proposal remains in the NM system (as revoked), until a new proposal is made for the same regulation, in which case the revoked proposal is replaced. When requested, this attribute is never left null.

Presence:

- i) Mandatory in RegulationProposalFilingRequest, RegulationProposalUpdateRequest
- ii) Optional otherwise.
- c) <u>MCDMApprovalState</u> approvalState (Contextual)

Describes the measure approval state (not to be confused with the regulation state) of the MCDM NMOC actor: a.o did NM accept (and implement) the regulation proposal. When requested, this attribute is never left null.

Presence:

- i) Must be null in <u>RegulationProposalFilingRequest</u>, <u>RegulationProposalUp-dateRequest</u>
- ii) Optional otherwise.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### d) MCDMState mcdmState (Contextual)

Describes the regulation proposal MCDM state: a.o is the measure in draft (not visible to NM yet) or proposed or implemented or interrupted (a.o. the measure was cancelled after it had been implemented).

When requested, this attribute is never left null.

When a regulation proposal is filed, the MCDM state is (re-)set by the system.

When the client has filed the request (and optionally added flights to the cherry picked regulation) and the client is happy with the results, then he should set the mcdmState to proposed (to make the proposal visible to NM)): for RegulationProposalWithProposalF-lights only.

NM will then accept or reject the regulationProposal and the MCDM state will go to implemented (in case of accept)/interrupted (in case of reject).

Note that even though the regulation proposal can be accepted by NM, it does not mean that all of the individual flights have been accepted (in case of cherry picked regulation proposal). In order to retrieve for each individual flight, its MCDM state and the NMOC actor approval state, the gueryMCDM service can be used.

In addition, interrupted or abandoned MCDM state for a flight (i.e. in a cherry picked regulation) means that the flight got "un-picked" from that regulation (e.g. due to changes in the flight such that it's forced slot could not be kept).

#### Presence:

- i) Must be null in <u>RegulationProposalFilingRequest</u>, <u>RegulationProposalUpdateRequest</u>
- ii) Optional otherwise.

### e) RegulationState regulationState (Contextual)

Current state of the regulation.

When requested, this attribute is null when kind = ProposalRegulationWithoutProposalFlights.

#### Presence:

- i) Must be null in <u>RegulationProposalFilingRequest</u>, <u>RegulationProposalUp-dateRequest</u>
- ii) Optional otherwise.
- (6) <u>Used by:</u> <u>RegulationProposalRevocationReply, RegulationProposalUpdateReply, RegulationProposalListReply, RegulationProposalFilingRequest, RegulationProposalUpdateRequest, RegulationProposalFilingReply.</u>

# 4.119. <<enumeration>> RegulationProposalAction

- (1) Action requested by a regulation proposal.
- (2) Values:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Value	Description	
The regulation proposal requests NMOC to cancel a regulation NMOC accepts this will result in a cancelled regulation and all the cerned flights will be unforced or de-regulated.		
CREATION	The regulation proposal requests NMOC to create a regulation	
UPDATE	The regulation proposal requests NMOC to update a regulation	

Table 4.4. <<enumeration>> RegulationProposalAction

(3) <u>Used by: RegulationProposal.</u>

# 4.120. <<enumeration>> RegulationProposalField

- (1) Enumerates the fields that the caller may request to be returned in <u>RegulationProposal</u> objects when returned by <u>RegulationProposalListRequest</u>.
- (2) As a rule, client applications should never request regulation proposal fields that they do not need. Client applications typically implement a query/retrieve pattern:
  - a) Query the small number of most relevant regulation proposal fields to display to the end user
  - b) Retrieve more details for a given regulation proposal when the end user has selected a regulation proposal from the list

#### (3) Values:

- a) action
- b) applicability
- c) approvalState
- d) autolink
- e) createdByFMP
- f) dataId
- g) delayConfirmationThreshold
- h) delayTVSet
- i) externallyEditable
- j) initialConstraints
- k) lastUpdate

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- l) linkedRegulations
- m) location
- n) mcdmRequired
- o) mcdmState
- p) measureCherryPicked
- q) **noDelayWindow**
- r) protectedLocation
- s) **reason**
- t) regulationState
- u) **remark**
- v) scenarioReference
- w) sourceHotspot
- x) subType
- y) **supplementaryConstraints**
- z) updateCapacityRequired
- aa) updateTVActivationRequired
- (4) <u>Used by: RegulationProposalListRequest.</u>

# 4.121. <<enumeration>> RegulationProposalKind

- (1) Values:
  - a) RegulationProposalWithProposalFlights
  - b) RegulationProposalWithoutProposalFlights
- (2) <u>Used by: RegulationProposal</u>.

# 4.122. <<enumeration>> RegulationProposalState

- (1) State of a regulation proposal.
- (2) <u>Values:</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Value Description	
ACCEPTED The regulation proposal has been accepted by NMOC	
REJECTED The regulation proposal has been rejected by NMOC	
WAITING The regulation proposal has not been processed by NMOC y	

Table 4.5. <<enumeration>> RegulationProposalState

### 4.123. <<enumeration>> RegulationReason

- (1) Enumeration of possible reasons for a regulation.
- (2) Values:
  - a) ACCIDENT\_INCIDENT
  - b) **AERODROME CAPACITY**
  - c) AERODROME\_SERVICES
  - d) AIRSPACE\_MANAGEMENT
  - e) ATC CAPACITY
  - f) ATC\_EQUIPMENT
  - g) ATC\_INDUSTRIAL\_ACTION
  - h) ATC\_ROUTINGS
  - i) ATC\_STAFFING
  - j) **ENVIRONMENTAL ISSUES**
  - k) NON\_ATC\_INDUSTRIAL\_ACTION
  - I) OTHERS
  - m) SPECIAL EVENT
  - n) WEATHER
- (3) <u>Used by: ATFCMSituationDelays, RegulationOrMCDMOnly, DeltaATFCMSituationDelays, RegulationOrMCDMOnlyListRequest, RegulationCause, ATFCMSituationRegulation.</u>

# 4.124. <<enumeration>> RegulationState

(1) Enumerates the possible states of a regulation in the NM system.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

When created, a regulation starts in the APPLYING state. Once all the flights have been successfully updated, the regulation goes to the APPLIED state. Any subsequent modification to the regulation will put it back to the APPLYING state. Again, once all the flights have been successfully updated, the regulation will go again to the APPLIED state. Once the applicability period is passed, the regulation goes to the TERMINATED state. If the regulation is no longer needed while the applicability period is still in the future (partly or completely), then the regulation state is set to CANCELLING. Once all the flights have been successfully updated, the regulation is set to CANCELLED. CANCELLED and TERMINATED are final regulation states.

#### (3) Values:

Value	Description	
APPLIED	The regulation is activated and the subsequent flight recalculation is finished	
APPLYING	The regulation is activated but the subsequent flight recalculation is not finished yet	
CANCELLED	The regulation is cancelled and the subsequent flight recalculation is finished	
CANCELLING	The regulation is cancelled but the subsequent flight recalculation is not finished yet	
TERMINATED	The regulation is terminated	

Table 4.6. <<enumeration>> RegulationState

(4) <u>Used by: MCDMOnly, RegulationProposal, MCDMOnlyListRequest, Regulation, RegulationListRequest, ATFCMSituationRegulation.</u>

# 4.125. RegulationSupplementaryConstraint

- (1) Supplementary rate information expressed by a regulation for a specific supplementary period, expressed as number of slots per hour.
- (2) Attributes:
  - a) DateTimeMinutePeriod constraintPeriod (Mandatory)
    Applicability period of this constraint.
  - b) int supplementaryRate (Mandatory)
     Supplementary rate.
     Constraint: Range: ] ∞,∞[.
- (3) <u>Used by: RegulationOrMCDMOnly.</u>

# 4.126. <<enumeration>> RepositoryId

- (1) Repository Id.
- (2) Values:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- a) **PREDICT**
- b) SCENARIO
- c) TACT

### 4.127. Rerouting




Figure 4.17. Rerouting Class Diagram

- (1) Reroutings are measures to level cap or reroute flights to avoid an airspace/point or to find shorter/cheaper routes. Typically they are used for ATFCM reasons (for example to avoid a zero rate regulation) or for STAM or for Flight Efficiency (to find more efficient routes) or to handle forecast expected flows (for example NAT traffic). Rerouting can either create a proposal flight (containing a proposed route) or they can modify the FTFM/RTFM point profile directly (used in forecast and simulations) or they can generate proposed routes in operational log messages.
- (2) Inherits from: Measure.
- (3) Attributes:
  - a) ReroutingId reroutingId (Mandatory)
    The unique id of the rerouting.
  - b) Location location (Contextual)
    The type of location used to select the flights.
    When requested, this attribute is never left null.
    Presence:
    - i) Mandatory in <u>ReroutingCreationRequest</u>
    - ii) Optional otherwise.

      <u>Constraint:</u> See <u>ONLY\_TRAFFIC\_VOLUME\_LOCATION\_TYPE\_PERMITTED</u>

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

### c) **FlowId flowId** (Optional)

The traffic flow to/from the CountLocation to wich this rerouting applies.

if null it applies to all the traffic for the CountLocation.

Event if Flow is requested, it can be that no filtering flow is used.

When requested, this attribute is never left null.

### d) ReroutingApplyKind reroutingApplyKind (Contextual)

The apply kind of the rerouting.

When requested, this attribute is never left null.

Presence:

- i) Mandatory in <u>ReroutingCreationRequest</u>
- ii) Optional otherwise.

#### e) <u>ReroutingMeasureState</u> reroutingState (Contextual)

Enumerates the states of the rerouting.

When requested, this attribute is never left null.

Presence:

- i) Must be null in ReroutingCreationRequest, ReroutingUpdateRequest
- ii) Optional otherwise.

### f) ReroutingSourcesAndConstraints sourcesAndConstraints (Contextual)

Describes the rerouting constraints.

When requested, this attribute is never left null.

Presence:

- i) Mandatory in <u>ReroutingCreationRequest</u>
- ii) Optional otherwise.
- g) string remark (Optional)

Remark made by the NM or FMPs. This remark typically provides some more details about the reason and the description of the rerouting.

Constraint: Pattern: TEXT{1,128}((WHITESPACE)(TEXT{1,128})){0,1}

#### h) Set<<u>RestrictionId</u>> disabledRestrictions (Optional)

RAD restrictions that need to be disabled (ENV) before the scenario can be applied. Constraint: Size must be comprised between 0 and  $\infty$ .

#### i) Set<<u>RestrictionId</u>> ignoredRestrictions (Optional)

RAD restrictions that need to be ignored (IFPS before the scenario can be applied. Constraint: Size must be comprised between 0 and  $\infty$ .

#### (4) Constraint:

a)	Name	ONLY_TRAFFIC_VOLUME_LOCATION_TYPE_PERMITTED
----	------	---

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

Attribute	location
	Only the <u>TrafficVolumeLocation</u> type is permitted in <u>ReroutingCreationRequest</u> and <u>ReroutingUpdateRequest</u> .  Note that when retrieving reroutings, there can be other types of location.

(5) <u>Used by:</u> <u>ReroutingUpdateRequest</u>, <u>ReroutingCreationRequest</u>, <u>ReroutingListReply</u>, <u>ReroutingCreationReply</u>, <u>ReroutingCancelReply</u>.

# 4.128. <<enumeration>> ReroutingApplyKind

- (1) Rerouting apply kind. Indicates if it concerns a rerouting for indication or not.
- (2) If it concerns a rerouting for indication, the generated proposed routes can be found in the operational log messages. In addition, in the flight list, the field <a href="reroutingOpportunitiesExist">reroutingOpportunitiesExist</a> can be used to determine if the rerouting succeed to find a new (interesting) route or not.
- (3) Values:

#### a) **EXECUTE**

Indicates it concerns an execute rerouting.

In this case either the FTFM or RTFM are replaced by the rerouting.

No proposal flights are created.

This rerouting applies to flights in a simulation or flights in status planned (typically all flights on the pre-tactical dataset)

### b) FOR\_INDICATION\_WITHOUT\_AUTOMATIC\_PROPOSAL\_FLIGHT

Indicates it concerns a rerouting for indication.

No proposal flights are created.

#### c) FOR INDICATION WITH AUTOMATIC RRN

Indicates it concerns a rerouting for indication.

In addition proposal flights are created and the corresponding RRN messages are or will be sent.

### d) FOR\_INDICATION\_WITH\_AUTOMATIC\_RRP

Indicates it concerns a rerouting for indication.

In addition proposal flights are created and the corresponding RRP messages are or will be sent.

(4) <u>Used by: FlightAtfcmReroutingLocation, Rerouting.</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 4.129. <<abstract>> ReroutingConstraint




Figure 4.18. <<abstract>> ReroutingConstraint Class Diagram

- (1) Ancestor structure for all rerouting constraints.
- (2) <u>Extended by: OtherReroutingConstraint, DeltaLevelReroutingConstraint, AvoidViaAirspaceReroutingConstraint, LevelAndSpeedReroutingConstraint, AvoidViaPointReroutingConstraint.</u>
- (3) <u>Used by: ANDedReroutingConstraints.</u>

# 4.130. <<enumeration>> ReroutingField

- (1) Enumerates the fields that the caller may request to be returned in <u>Rerouting</u> objects when returned by <u>ReroutingListRequest</u>.
- (2) As a rule, client applications should never request rerouting fields that they do not need. Client applications typically implement a query/retrieve pattern:
  - a) Query the small number of most relevant rerouting fields to display to the end user
  - b) Retrieve more details for a given rerouting when the end user has selected a rerouting from the list
- (3) Values:
  - a) applicability
  - b) constraints
  - c) createdByFMP
  - d) dataId
  - e) disabledRestrictions
  - f) externallyEditable
  - g) flowId
  - h) ignoredRestrictions

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- i) lastUpdate
- i) location
- k) mcdmRequired
- neasureCherryPicked
- m) remark
- n) reroutingApplyKind
- o) reroutingState
- p) scenarioReference
- q) **sourceHotspot**
- r) subType
- (4) <u>Used by: ReroutingListRequest, ScenarioReroutingRetrievalRequest.</u>

# 4.131. ReroutingHorizontalConstraints

- (1) Describes the constraints for a horizontal/lateral rerouting.
- (2) Attributes:
  - a) **boolean freezeOutsideZone** (Mandatory) Indicates whether the Freeze Outside IFPZ option is triggered.
  - b) FreezeTP freezeTPs (Mandatory) Indicates the Freeze Terminal procedures kind.
  - boolean useRouteGenerator (Mandatory)
     Generate horizontal route alternatives based on the route generator.
     Constraints:
    - i) See <u>AT LEAST ONE USE SOURCE MUST BE SET TO TRUE</u>
    - ii) See <u>USE PATH FINDER INCONSISTENCY PAIR</u>
  - d) **boolean forRouteGeneratorUseDctAsReference** (Optional) If yes then replace the F15 of the reference by DCT.

    <u>Constraint: See USE PATH FINDER INCONSISTENCY PAIR</u>
  - e) **boolean useRouteCatalogue** (Mandatory)
    Generate horizontal route alternatives based on the route catalogue.

    <u>Constraint: See AT\_LEAST\_ONE\_USE\_SOURCE\_MUST\_BE\_SET\_TO\_TRUE</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### f) **boolean useCurrentFlightsInSystem** (Optional)

Generate horizontal route alternatives based on the flights currently present in NM systems. <u>Constraint:</u> See <u>AT\_LEAST\_ONE\_USE\_SOURCE\_MUST\_BE\_SET\_TO\_TRUE</u>

#### (3) Constraints:

a)	Name	AT_LEAST_ONE_USE_SOURCE_MUST_BE_SET_TO_TRUE
		<u>useRouteGenerator</u> , <u>useRouteCatalogue</u> , <u>useCurrentFlightsIn-</u> System
	•	At least one of 'useRouteGenerator', 'useRouteCatalogue', 'useCurrentFlightsIn-System' needs to be set to true.

b)	Name	USE_PATH_FINDER_INCONSISTENCY_PAIR
	Attributes	forRouteGeneratorUseDctAsReference, useRouteGenerator
	,	if 'forRouteGeneratorUseDctAsReference' is set either to false or to true then 'useRouteGenerator' must be set to true. if 'forRouteGeneratorUseDctAsReference' is not set then 'useRouteGenerator' must be set to false.

(4) <u>Used by:</u> <u>ReroutingSourcesAndConstraints</u>.

# 4.132. typedef<string> ReroutingId

- Unique id of a rerouting measure (for a given day), allocated by NM or via the user.
- Note that there can be 2 reroutings with the same Reroutingld over a 2 day period.
- (3) <u>Pattern:</u> (UALPHA|DIGIT|\*){1,8}
- (4) <u>Used by: UpdateFlightInMeasureChoice, FlightAtfcmReroutingLocation, MeasureId, Rerouting, ReroutingCancelRequest.</u>

# 4.133. typedef<string> ReroutingIdWildcard

- (1) Either a full rerouting id, or a simple wildcard for rerouting ids.
- (2) <u>Pattern:</u> (UALPHA|DIGIT|\*){1,8}
- (3) <u>Used by: ReroutingListRequest.</u>

# 4.134. ReroutingManualConstraints

- (1) Describes a manual only rerouting constraint.
- (2) Attributes:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### a) Set<string> manualField150rField15Portions (Mandatory)

Describes the Field15s or Partial Field15s that are ORed together with the other rerouting constraints: for each concerned flight, each of different Field15 are evaluated together with the other applicable rerouting constraints and the best solution is selected (according to cost criteria)

The manual routes are in ICAO field 15 syntax. Either a complete field15abc can be entered which will replace the original flight route or a (partial) field15c only can be entered. In the latter case the new entered portion will replace the matching portion of the original flight route. The begin and end point (reconnection points) of this portion must be present in the correct order in the original flight route otherwise an error is shown for a flight if none of the given F15 reconnection points match this specific flight. The system will use the RFLs and RSPs specified in the input ICAO field 15, during the profile calculation for the alternative (both for complete field15abc and partial field15c.

When for a partial field15, the reconnection point is either ADEP or ADES, then the special point indicator "ADEP" or "ADES" can be used. If the reconnection point is both ADEP and ADES, then a complete field15abc needs to be entered. When for a partial field15, the speed of the flight does not need to be updated, then the special point indicator "NOSPEED" can be used to indicate that the speeds indicators of the manual F15 do not need to be taken into account. The NOSPEED indicator needs to be the first word of the partial F15. If the ADEP indicator is specified, then the NOSPEED needs to be the second keyword of the F15.

Constraint: Size must be comprised between 0 and  $\infty$ .

(3) <u>Used by: ReroutingSourcesAndConstraints.</u>

# 4.135. <<enumeration>> ReroutingMeasureState

- (1) Enumerates the possible state of a rerouting in the NM system.
- (2) <u>Values:</u>
  - a) **ACTIVATING**
  - b) **APPLIED**
  - c) **CANCELLED**
  - d) **CANCELLING**
- (3) <u>Used by: Rerouting, ReroutingListRequest.</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# 4.136. ReroutingSourcesAndConstraints




Figure 4.19. ReroutingSourcesAndConstraints Class Diagram

- (1) Describes the constraints for a all kind of rerouting.
- (2) Attributes:
  - a) ReroutingHorizontalConstraints reroutingHorizontalConstraints (Optional)

Describes the constraints for a horizontal/lateral rerouting.

<u>Constraint:</u> See <u>AT\_LEAST\_ONE\_CONSTRAINT\_TYPE\_MUST\_BE\_SET</u>

b) boolean useVerticalOrSpeedReroutingSource (Mandatory)

Indicates weather the constraints is for a non horizontal rerouting (i.e. vertical/or speed adaptations).

<u>Constraint:</u> See <u>AT\_LEAST\_ONE\_CONSTRAINT\_TYPE\_MUST\_BE\_SET</u>

- c) ReroutingManualConstraints manualReroutingConstraints (Optional) manual only rerouting constraints

  Constraint: See AT\_LEAST\_ONE\_CONSTRAINT\_TYPE\_MUST\_BE\_SET
- d) Set<ANDedReroutingConstraints oredReroutingConstraints (Optional) A set of rerouting constraints between which the OR operator applies. Constraint: Size must be comprised between 0 and ∞.
- (3) Constraint:

a)	Name	AT_LEAST_ONE_CONSTRAINT_TYPE_MUST_BE_SET
		reroutingHorizontalConstraints, useVerticalOrSpeedReroutingSource, manualReroutingConstraints
	•	At least one of 'reroutingHorizontalConstraints', 'useVerticalOrSpeedReroutingSource', 'manualReroutingConstraints' needs to be set.

(4) <u>Used by: Rerouting.</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### 4.137. RestrictionLocation

- (1) Restriction location.
- (2) <u>Inherits from: Location</u>.
- (3) Attributes:
  - a) <u>KindOfRestriction</u> kindOfRestriction (Mandatory)
    The kind of restriction.

## 4.138. RunwayConfiguration

- (1) A runway configuration at some point in time.
- (2) Attributes:
  - a) RunwayId runway (Mandatory)
     Runway to which this configuration applies.
  - b) RunwayUsage usage (Optional)
    Usage of the runway in this configuration.
  - c) PlanDataSource runwayUsageDataSource (Mandatory)
    The data source of the runwayUsage for this entry in the plan.
    Note that NM prefers not to have any CACD (runwayUsageDataSource = AIRSPACE)
    runway usage when tactically updating runway configurations. If an AIRSPACE runwayUsageDataSource applies, then this means that in NM profile computations, the RunwayUsage is considered unknown (as it is difficult to predict accurately up to one month in advance the wind/runway activation schedule).
  - d) **DurationHourMinute departureTaxiTime** (Optional) Departure taxi time.

Note that the departure taxi time must be specified even if the usage is ARRIVAL or INACT-IVE, so that in the exceptional case where the runway would be used in another way (indicated via DPI) the NM system could still use this taxi time for computing the flight.

- e) PlanDataSource departureTaxiTimeDataSource (Mandatory) The data source of the departureTaxiTime for this entry in the plan.
- f) DurationHourMinute timeToInsertInSequence (Optional)
  Time to insert aircraft in sequence at the aerodrome of departure.
  Note that the timeToInsertInSequence must be specified even if the usage is ARRIVAL or INACTIVE, so that in the exceptional case where the runway would be used in another way (indicated via DPI) the NM system could still use this taxi time for computing the flight.
- g) PlanDataSource timeToInsertInSequenceDataSource (Mandatory) The data source of the timeToInsertInSequence for this entry in the plan.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

h) <u>DurationHourMinute</u> timeToRemoveFromSequence (Optional)

Time to remove aircraft from sequence at the aerodrome of departure. Note that the timeToRemoveFromSequence must be specified even if the usage is ARRIVAL or INACTIVE, so that in the exceptional case where the runway would be used in another way (indicated via DPI) the NM system could still use this taxi time for computing the flight.

- i) <u>PlanDataSource</u> timeToRemoveFromSequenceDataSource (Mandatory) The data source of the timeToRemoveFromSequence for this entry in the plan.
- j) <u>DurationHourMinute</u> arrivalTaxiTime (Optional)
  Arrival taxi time.

Note that the departure taxi time must be specified even if the usage is DEPARTURE or INACTIVE.

- k) PlanDataSource arrivalTaxiTimeDataSource (Mandatory) The data source of the arrivalTaxiTime for this entry in the plan.
- (3) <u>Used by: PlannedRunwayConfigurations</u>.

# 4.139. RunwayConfigurationPlan

- (1) Runway configuration plan for a given aerodrome on a given day.
- (2) A RunwayConfiguration plan is a special plan in the sense that all known runways need to be specified for a given period (PlannedRunwayConfiguration) or else the entire period needs to be marked CACD (AIRSPACE PlanDataSource). In addition, for a (pre-)tactically updated period it is possible to (pre-)tactically update selected runway attributes for selected runways. So each runway attribute (usage, departureTaxTime,...) has an associated dataSource attribute allowing to indicate if that attribute needs to be updated or if CACD data is to be used for that attribute, for that runway and for that specific period. The only constraint is: if a period (PlannedRunwayConfiguration) is marked as TACTICAL updated, then at least one of the attributes of one of the runways needs to be TACTICAL updated (otherwise INVALID\_INPUT replyStatus).
- (3) In addition the RunwayUsage attribute is special in the sense that all runways for a specific TACTICAL updated period need to be either all CACD, or else a mix of DEPARTURE/ARRIVAL/DEPARTURE\_ARRIVALI/INACTIVE).
- (4) Note that NM prefers not to have any CACD (AIRSPACE datasource) RunwayUsage when tactically updating runway configurations. If a CACD RunwayUsage applies, then this means that in NM profile computations, the RunwayUsage is considered unknown (as it is difficult to predict accurately up to one month in advance the wind/runway activation schedule).
- (5) In a retrieval context, the plan is said to be 'complete' in the sense that it contains all the plan entries from all involved data sources.
- (6) In an update context, the plan can be complete (if the B2B client designer decided to overwrite the default CACD values) or limited to the (full list) of (pre-)tactical updates with the gaps marked as AIRSPACE (meaning in update context: CACD) datasource (to obtain a complete time partition).

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- (7) In any case, periods in the time partition marked with datasource AIRSPACE, correspond to removing any potential (pre-)tactical update and hence reset the corresponding values to the CACD definition for that period.
- (8) Inherits from: <u>TacticalConfigurationPlan</u>.
- (9) Attributes:
  - a) AerodromeICAOId aerodrome (Mandatory)
    Aerodrome to which this runway configuration plan belongs.
  - b) Set<RunwayId> knownRunwayIds (Mandatory)

The list of runways that NM knows for the aerodrome, regardless to their usage, e.g. an inactive runway is part of this set.

Constraint: Size must be comprised between 0 and ∞.

c) Set<<u>PlannedRunwayConfigurations</u>> nmSchedule (Contextual)

The plan resulting from the superimposition of all constraints from all data sources, which the NM system is using as plan for its own calculations.

The NM schedule exposes the complete time partition of the configurations for the day, i.e. the data coming from the various data sources contributing to the NM view of the plan: these data sources are defined in PlanDataSource.

The NM schedule cannot be updated directly by the caller; it is the outcome of updates via the various data sources.

Presence:

- i) Must be null in <u>CapacityPlanUpdateRequest</u>, <u>OTMVPlanUpdateRequest</u>, <u>RunwayConfigurationPlanUpdateRequest</u>, <u>SectorConfigurationPlanUpdateRequest</u>, <u>dateRequest</u>, <u>TrafficVolumeActivationPlanUpdateRequest</u>
- ii) Mandatory otherwise.

Constraint: Size must be comprised between 0 and  $\infty$ .

d) Set<<u>PlannedRunwayConfigurations</u>> clientSchedule (Mandatory)

(Pre-)tactical runway configuration of the aerodrome associated to their applicability period, as maintained by the client. This plan contains only the updated configurations together with an indication that the default CACD values apply when not updated (cf. PlanDataSource). The actual CACD values for these CACD periods can be found in the nmSchedule. In an update context, the clientSchedule can be complete (if the B2B client designer decided to overwrite the default CACD values) or limited to the actual differences with regards to the CACD defaults. This is a B2B client designer's decision and depends on how CACD wants to be used in combination with the B2B. If the clientSchedule only contains the actual differences with regards to the CACD defaults, then the clientschedule still needs to contain the full list of (pre-) tactical updates and for the non (pre-) tactically updated periods, an explicit indication that the CACD values need to be used (but without repeating the CACD values themselves). So in any case, the clientschedule needs to be a complete time partition for the full day.

In any case, it is of drastic importance to understand that an entry in the schedule (i.e. a period):

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

- i) Must be complete in the sense that all the aerodrome runways must be present in the entry
- ii) The runway configuration values provided for that period overwrite all CACD values for that same period

#### Constraints:

- i) Size must be comprised between 0 and  $\infty$ .
- ii) See INCOMPLETE SCHEDULE

### (10) Constraint:

a)	Name	INCOMPLETE_SCHEDULE
	Attribute	clientSchedule
		clientSchedule has gaps and/or overlaps in the time partition or is not covering exactly one day.

(11) <u>Used by:</u> <u>RunwayConfigurationPlanUpdateRequest</u>, <u>RunwayConfigurationPlanUpdateReply</u>, <u>RunwayConfigurationPlanRetrievalReply</u>.

# 4.140. <<enumeration>> RunwayUsage

- (1) Possible usages of a runway.
- (2) <u>Values:</u>

#### a) ARRIVAL

The runway is used for arrivals only.

Note that an arrival runway is not considered by the NM system for departure when processing flights, but DPI (Departure Planning Information) messages are still able to use an arrival runway.

#### b) **DEPARTURE**

The runway is used for departures only.

#### c) **DEPARTURE ARRIVAL**

The runway is used for both departures and arrivals.

#### d) INACTIVE

The runway is neither used for depatures or arrivals.

Note that an inactive runway is not considered by the NM system for departure when processing flights, but DPI (Departure Planning Information) messages are still able to use an inactive runway.

(3) <u>Used by:</u> <u>RunwayConfiguration</u>.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

### 4.141. ScenarioAttributes




Figure 4.20. ScenarioAttributes Class Diagram

- (1) Scenario attributes.
- (2) Attributes:
  - a) **string publicationId** (Mandatory)

The published scenariold. For AR,RR,FL type of scenario it is typically the traffic volume name of the scenario.

Constraint: Pattern: TEXT{1,10000}

- b) <u>ScenarioId</u> scenarioId (Mandatory)
- c) Set<<u>ScenarioEvent</u>> scenarioEvents (Optional)

The events associated by the user to this scenario: typically Strike, SKI, ConingencyMUAC Constraint: Size must be comprised between 0 and  $\infty$ .

- d) <u>ScenarioType</u> scenarioType (Mandatory)
- e) Set<<u>TrafficVolumeId</u>> scenarioPublishedTrafficVolumes (Optional)

The trafic volumes(s) of the scenario: i.e. the traffic volume(s) to avoid. For RR/FL type of scenario, it is typically the traffic volume of the scenario measures (but not always: in some cases the scenario measures use a larger traffic volume to avoid/protect some other traffic volume).

Constraint: Size must be comprised between 0 and ∞.

f) Set<<u>ReferenceLocation</u>> scenarioPublishedLocations (Optional)

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

The reference location(s) of the scenario: i.e. the location(s) to avoid. For RR/FL type of scenario, it is typically the reference location of the traffic volume of the scenario (but not always: in some cases the scenario intends to avoid/protect some other reference location). Constraint: Size must be comprised between 0 and  $\infty$ .

### g) Set<<u>AirNavigationUnitId</u>> ownerFMPs (Optional)

The FMP(s) that are the owner of the scenario (e.g. it could happen that the location of the scenario overlaps with multiple ACC/FMP).

Constraint: Size must be comprised between 0 and ∞.

### h) Set<<u>AirspaceId</u>> onLoad (Optional)

The list of published airspaces that will be on-loaded when the scenario is applied. Constraint: Size must be comprised between 0 and  $\infty$ .

### i) Set<<u>AirspaceId</u>> offLoad (Optional)

The list of published airspace that will be off-loaded when the scenario is applied. Constraint: Size must be comprised between 0 and  $\infty$ .

### j) <u>WeeklySchedule</u> weeklyApplicability (Optional)

If the scenario can only be applied during certain periods, this weekly schedule represents this.

Tyical usage is: scenario that are already included in certain RAD restrictions that are always applied during the weekend. So the scenario should be applied during the periods when this RAD is dis-abled (in CACD)

#### k) **string from** (Optional)

The textual representation of the flows (upstream) of the traffic volume of the scenario. Constraint: Pattern: MULTILINE TEXT{1,10000}

### l) string to (Optional)

The textual representation of the flows (downsteam) of the traffic volume of the scenario. <u>Constraint:</u> <u>Pattern:</u> MULTILINE\_TEXT{1,10000}

### m) Set<<u>RestrictionId</u>> scenarioIncludedInRestrictions (Optional)

RAD restrictions (if enabled) that incorporates this scenario: e.g. some RR/FL scenario are included in some RAD.

Constraint: Size must be comprised between 0 and ∞.

#### n) Set<<u>RestrictionId</u>> disabledRestrictions (Optional)

RAD restrictions that need to be disabled (CACD) before the scenario can be applied. Constraint: Size must be comprised between 0 and  $\infty$ .

#### o) Set<<u>RestrictionId</u>> ignoredRestrictions (Optional)

RAD restrictions that need to be ignored (IFPS) before the scenario can be applied. Constraint: Size must be comprised between 0 and  $\infty$ .

### p) Set<string> alternativeIcaoRoutePortions (Optional)

Each suggestedAlternativeRoute represents one possible alternative (partial F15) AR/RR/FL scenario contains examples on how an AO could fly to get around the location to avoid.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

Constraint: Size must be comprised between 0 and ∞.

### q) Set<<u>ScenarioLevelConstraint</u>> levelConstraints (Optional)

Each levelConstraints represents one possible level constraint. Typically it states something like: file below FL240 until clear of sector.

Constraint: Size must be comprised between 0 and ∞.

# r) <u>ScenarioPublicationStatus</u> publicationStatus (Mandatory) The textual representation of the flows (upstream) of the traffic volume of the scenario.

# s) <u>DateTimeMinutePeriodWithUFN</u> applicabilityPeriod (Mandatory) Describes when the scenario is considered applicable: when applicabilityPeriod

Describes when the scenario is considered applicable: when applicabilityPeriod is in the past, the scenario is considered an archived scenario no longer applicable.

# t) string comments (Optional)

Constraint: Pattern: MULTILINE\_TEXT{0,10000}

### u) <u>DateTimeSecond</u> lastModifiedTimeStamp (Mandatory)

The timestamp when the scenario was last modified/saved.

### v) string scenarioValidationErrorsOrWarnings (Optional)

If there are validation errors or warnings with a scenario, the scenarioValidationErrorsOr-Warnings will be present.

Constraint: Pattern: MULTILINE TEXT{1,10000}

### w) Set<<u>MeasureIdAndTV</u>> scenarioMeasures (Optional)

Gives a summary of all the measures inside the scenario and their traffic volume id on which they are based. In addition it describes per rerouting measure, the off-loaded traffic volumes. Constraint: Size must be comprised between 0 and  $\infty$ .

(3) <u>Used by: ScenarioListReply.</u>

# 4.142. typedef<string> ScenarioEvent

- (1) Pattern: TEXT{1,10000}
- (2) <u>Used by: ScenarioAttributes</u>.

# 4.143. typedef<string> ScenarioId

- (1) Pattern: TEXT{1,255}
- (2) <u>Used by: ScenarioMeasureRetrievalRequest, MeasureFromScenarioRepository, ScenarioListRequest, TrafficVolumeScenarios, ScenarioAttributes.</u>

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

## 4.144. ScenarioImpact

(1) Describes the scenario impact: if a scenario measure is applied to solve a problem on a traffic volume, then this scenario impacts the traffic in that problem traffic volume. This class describes the impact (See also <a href="mailto:TrafficVolumeScenarios">TrafficVolumeScenarios</a>).

## (2) Attributes:

## a) <u>CountsValue</u> totalCommonFlights (Mandatory)

The total number of common flight between the problem traffic volume and the solution (scenario) traffic volume.

This corresponds to the total number of flights inside the flow counts for this scenario traffic volume flow.

## b) <u>CountsValue</u> totalOtherFlights (Mandatory)

The total number of flights captured by the solution (scenario) traffic volume that are not captured by the queried ("problem") TrafficVolume. i.e. when the user would apply a relevant scenario measure, then this measure would correctly offload numberCommonFlights from the 'problem' Traffic volume, but additionally it would "penalise" numberOtherFlights that are not even crossing the "problem" Traffic volume.

# c) <u>DateTimeMinutePeriod</u> scenarioTrafficVolumeEntryPeriod (Optional) The (smallest entry count based) period that would be needed for the measure on scenarioTrafficVolume to capture all the common flights. In addition when the measure is applied (with a scenarioTrafficVolumeEntryPeriod), then it will also capture additionally totalOtherFlights.

#### (3) Used by: Flow.

## 4.145. ScenarioLevelConstraint




Figure 4.21. ScenarioLevelConstraint Class Diagram

#### (2) Attributes:

(1)

a) Set<<u>DBEOrPublishedPointId</u>> from (Mandatory)
Constraint: Size must be comprised between 0 and ∞.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- b) <u>LevelConstraintKind</u> levelConstraintKind (Mandatory)
- c) FlightLevel DataType flightLevel (Mandatory)
- d) Set<<u>DBEOrPublishedPointId</u>> until (Mandatory)
  Constraint: Size must be comprised between 0 and ∞.
- (3) Used by: ScenarioAttributes.

## 4.146. ScenarioMeasureRetrievalRequest




Figure 4.22. Scenario Measure Retrieval Request Class Diagram

- (1) Abstract request to query an NM measure list for a scenario, as well as to retrieve the measure details.
- (2) Inherits from: Request.
- (3) Attributes:
  - a) Dataset dataset (Mandatory)
     Dataset for which the retrieve scenario measure is requested. See <u>Forecast and Operational Datasets</u>.
  - b) Set<ScenarioId> scenarios (Mandatory)
    Selects the measures contained in the given list of scenariold.
    Constraint: Size must be comprised between 0 and ∞.
  - c) <u>DateTimeMinutePeriod</u> <u>adaptedMeasureApplicability</u> (Optional) When specified, the measures applicably period is adapted to match AdaptedMeasure-Applicability.

When not specified, the measures returned have their applicability un-changed wrt what is in the scenario repository (this could for example be many years in the past).

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

(4) <u>Extended by: ScenarioMCDMOnlyRetrievalRequest, ScenarioReroutingRetrievalRequest, ScenarioRegulationRetrievalRequest.</u>

## 4.147. typedef<string> ScenarioName

- (1) <u>Pattern:</u> TEXT{1,255}
- (2) <u>Used by: ScenarioListRequest.</u>

## 4.148. <<enumeration>> ScenarioPublicationStatus



Figure 4.23. <<enumeration>> ScenarioPublicationStatus Class Diagram

- (1) Scenario Publication status
- (2) Values:
  - a) **DRAFT**
  - b) **PUBLISHED**
- (3) Used by: ScenarioAttributes.

# 4.149. <<enumeration>> ScenarioTrafficVolumeMatchingKind




Figure 4.24. <<enumeration>> ScenarioTrafficVolumeMatchingKind Class Diagram

- Typically when the end-user has an overload on a "problem" traffic volume (i.e. the queried traffic volume to off-load), then he wants to see which scenarios (solutions) can be applied to off-load that "problem" traffic volume.
- (2) Values:

## a) INDIRECT OFFLOAD

Solution Traffic Volume is indirectly off-loading the "problem" traffic volume. For example when applying a level cap on a sector, often some of the upstream sectors are also impacted (and indirectly off-loaded).

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

## b) **OVERLAPPING\_REFERENCE\_LOCATION**

Solution Traffic Volume is overlapping with the "problem" traffic volume

## c) SAME REFERENCE LOCATION

Solution Traffic Volume is based on the same reference location as the problem traffic volume.

## d) SAME TRAFFIC VOLUME

Solution Traffic Volume is equal to the "problem" traffic volume.

#### (3) <u>Used by: TrafficVolumeScenarios</u>.

# 4.150. <<enumeration>> ScenarioType




Figure 4.25. <<enumeration>> ScenarioType Class Diagram

(1)

## (2) Values:

#### a) AR

The scenario type AR stands for an alternate route scenario: i.e. a scenario with 2 measures in it: a (low rate) regulation for a "non-standard" route and normally a horizontal rerouting to reroute flights into the new "route".

#### b) FL

The scenario type FL stands for Flight Level Capping scenario: i.e. a scenario with 2 measures in it: a (zero rate) regulation and normally a vertical rerouting.

#### c) MIXED

The scenario type Mixed represents all other scenario: for example contingency scenario containing a set of regulations. When such a scenario is aplied, one or more measures of the scenario are applied (but not necessarily all of them).

## d) RAD

The scenario type Restriction stands for a scenario describing what a flight should do if it gets caught by a restriction (typically EU RAD restrictions). The scenario contains 1 rerouting measure.

## e) RR

The scenario type RR stands for Flight Level Capping scenario: i.e. a scenario with 2 measures in it: a (zero rate) regulation and normally a horizontal rerouting.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## f) STAM

The scenario type STAM stands for STAM scenario: i.e. typically a scenario with 1 measure in it: either a cherry picked regulation or a cherry picked level-cap or horizontal rerouting or an MCDM-only measure.

Note that in some cases we could have multiple cherry picked measures inside 1 STAM level cap scenario to describe the different options of where to decent and where to climb up again.

(3) <u>Used by: ScenarioAttributes.</u>

## 4.151. typedef<string> SectorConfigurationId

- (1) Unique id of a sector configuration.
- (2) Pattern: (UALPHA|DIGIT|.) {1,6}
- (3) <u>Used by: SectorConfigurationPlan, PlannedSectorConfigurationActivation</u>.

## 4.152. SectorConfigurationPlan

- (1) Sector configuration plan for a given AUA or sector cluster on a given day.
- (2) In a retrieval context, the plan is said to be 'complete' in the sense that it contains all the plan entries from all involved data sources.
- (3) In an update context, the plan can be complete (if the B2B client designer decided to overwrite the default CACD values) or limited to the (full list) of (pre-)tactical updates with the gaps marked as AIRSPACE datasource (to obtain a complete time partition).
- (4) In any case, periods in the time partition marked with datasource AIRSPACE correspond to removing any potential (pre-)tactical update and hence reset the corresponding values to the CACD definition for that period.
- (5) <u>Inherits from: TacticalConfigurationPlan.</u>
- (6) Attributes:
  - a) AirspaceId airspace (Mandatory)
     AUA or sector cluster to which these sector configurations belong.
  - b) Map<<u>SectorConfigurationId</u>, Set<<u>AirspaceId</u>>> knownConfigurations (Contextual)

The set of sector configuration ids that NM knows for the AUA or sector cluster, and for each sector configuration, the set of sectors that compose it.

Presence:

i) Must be null in <u>CapacityPlanUpdateRequest</u>, <u>OTMVPlanUpdateRequest</u>, <u>RunwayConfigurationPlanUpdateRequest</u>, <u>SectorConfigurationPlanUpdateRequest</u>, <u>dateRequest</u>, <u>TrafficVolumeActivationPlanUpdateRequest</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

ii) Mandatory otherwise.

#### Constraints:

- i) Size must be comprised between 0 and  $\infty$ .
- ii) Item size must be comprised between 0 and  $\infty$ .
- c) Set<<u>PlannedSectorConfigurationActivation</u>> nmSchedule (Contextual)

The plan resulting from the superimposition of all constraints from all data sources, which the NM system is using as plan for its own calculations.

The NM schedule exposes the complete time partition of the configurations for the day, i.e. the data coming from the various data sources contributing to the NM view of the plan: these data sources are defined in PlanDataSource.

The NM schedule cannot be updated directly by the caller; it is the outcome of updates via the various data sources.

The possible values of <u>dataSource</u> are limited to AIRSPACE and TACTICAL - the AIRSPACE value meaning that the value associated to the <u>applicabilityPeriod</u> is the CACD one, and the TACTICAL value meaning that this plan entry corresponds to the explicit tactical update expressed via <u>sectorConfigurationId</u>.

#### Presence:

- i) Must be null in <u>CapacityPlanUpdateRequest</u>, <u>OTMVPlanUpdateRequest</u>, <u>RunwayConfigurationPlanUpdateRequest</u>, <u>SectorConfigurationPlanUpdateRequest</u>, <u>dateRequest</u>, <u>TrafficVolumeActivationPlanUpdateRequest</u>
- ii) Mandatory otherwise.

<u>Constraint:</u> Size must be comprised between 0 and  $\infty$ .

d) Set<PlannedSectorConfigurationActivation> clientSchedule (Mandatory) (Pre-)tactical sector configuration activations of the AUA or sector cluster associated to their applicability period, as maintained by the client. This plan contains only the updated configurations together with an indication that the default CACD values apply when not updated (cf. PlanDataSource). The actual CACD values for these CACD periods can be found in the nmSchedule

In an update context, the clientSchedule can be complete (if the B2B client designer decided to overwrite the default CACD values) or limited to the actual differences with regards to the CACD defaults. This is a B2B client designer's decision and depends on how CACD wants to be used in combination with the B2B. If the clientSchedule only contains the actual differences with regards to the CACD defaults, then the clientschedule still needs to contain the full list of (pre-) tactical updates and for the non (pre-) tactically updated periods, an explicit indication that the CACD values need to be used (but without repeating the CACD values themselves). So in any case, the clientschedule needs to be a complete time partition for the full day.

In any case, it is of drastic importance to understand that an entry in the schedule (i.e. a period) overwrites all CACD values in that period.

The possible values of <u>dataSource</u> are limited to AIRSPACE and TACTICAL - the AIRSPACE value meaning that the value associated to the <u>applicabilityPeriod</u> is the CACD one, and the TACTICAL value meaning that this plan entry corresponds to the explicit tactical update expressed via <u>sectorConfigurationId</u>.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

## Constraints:

- i) Size must be comprised between 0 and  $\infty$ .
- ii) See <u>INCOMPLETE\_SCHEDULE</u>

## (7) Constraint:

a)	Name	INCOMPLETE_SCHEDULE
	Attribute	clientSchedule
	-	clientSchedule has gaps and/or overlaps in the time partition or is not covering exactly one day.

(8) <u>Used by: SectorConfigurationPlanRetrievalReply, SectorConfigurationPlanUpdateReply, SectorConfigu</u>

## 4.153. SegmentLocation

- (1) Segment location: i.e. a part of a route or of a direct route.
- (2) Inherits from: Location.

## 4.154. SetOfAerodromesLocation

- (1) Set of aerodromes location.
- (2) Inherits from: Location.

## 4.155. SignificantDeltaCount

- (1) Compares a before and after situation and indicates if the change is significant. An insignificant change is a change that is considered not relevant.
- (2) Attributes:
  - a) CountsValue beforeCount (Mandatory)
  - b) <u>CountsValue</u> afterCount (Mandatory)
  - c) **boolean isSignificantChange** (Mandatory)
- (3) <u>Used by: DeltaATFCMSituationCounts.</u>

## 4.156. SignificantDeltaDuration

(1) Compares a before and after situation and indicates if the change is significant. An insignificant change is a change that is considered not relevant.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## (2) Attributes:

- a) LongDurationHourMinute beforeCount (Mandatory)
- b) LongDurationHourMinute afterCount (Mandatory)
- c) **boolean isSignificantChange** (Mandatory)
- (3) <u>Used by: DeltaATFCMSituationDelays.</u>

## 4.157. <<abstract>> Simulation




Figure 4.26. <<abstract>> Simulation Class Diagram

- (1) Common ancestor of the different types of simulation.
- (2) Attributes:
  - a) **SimulationName name** (Mandatory) The given name of the simulation.
  - b) **string description** (Mandatory) The description of the simulation.
  - c) <u>DateTimeMinute</u> publicationTime (Contextual)

The time when the simulation became published. For a USER\_MANAGED\_SIMULATION, it is the time when the simulation was started.

Presence:

- i) Mandatory in <u>SimulationListReply</u>, <u>SimulationStartReply</u>
- ii) Must be null in <u>SimulationStartRequest</u>
- iii) Optional otherwise.
- d) string simulationEngineId (Contextual)

The Id of the simulation engine running the simulation (also known as simulation\_ID in B2C). It is mainly needed by NMOC to find back the simulation in case of questions.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

#### Presence:

- i) Mandatory in <u>SimulationListReply</u>, <u>SimulationStartReply</u>
- ii) Must be null in <a href="mailto:SimulationStartRequest">SimulationStartRequest</a>
- iii) Optional otherwise.

## e) <u>DateTimeMinutePeriod</u> simulationPeriod (Mandatory)

The period that is being simulated (e.g. flights have been loaded that are departing/arriving/flying within that period).

When starting a USER\_MANAGED\_SIMULATION, the simulationPeriod needs to be exactly 1 day and it needs to be contained inside the simulation period of the reference. For example, a simulation for an operational datasetReference can either have as period [D, D-1 00:00[ or [D-1 00:00, D-2 00:00[ (See also OPERATIONAL and FORECAST datasets, and SIMULATION datasets.)

## f) Dataset dataset (Contextual)

The dataset of the simulation. This dataset needs to be used in any query on that simulation (for example in the flightlist and regulationlist)

Presence:

- i) Mandatory in <u>SimulationListReply</u>, <u>SimulationStartReply</u>
- ii) Must be null in <a href="mailto:SimulationStartReguest">SimulationStartReguest</a>
- iii) Optional otherwise.

<u>Constraint:</u> See <u>DATASET\_TYPE\_MUST\_BE\_SIMULATION</u>

## (3) Constraint:

a)	Name	DATASET_TYPE_MUST_BE_SIMULATION
	Attribute	dataset
	Description	Dataset must be SIMULATION type.

- (4) <u>Extended by: UserManagedSimulation, NMOCManagedSimulation, StandaloneSimex.</u>
- (5) <u>Used by: SimulationListReply.</u>

## 4.158. SimulationAvailability

- (1) Shows the available (free) user managed simulations and the used user managed simulation for a reference dataset
- (2) Attributes:
  - a) <u>DateTimeMinutePeriod</u> <u>simulatablePeriod</u> (Mandatory) The period within a simulation period needs to be.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

For <u>STANDALONE\_SIMEX</u> simulations, it is typically a 7 day period relatively far in the future.

b) **int availableSimulations** (Mandatory) Constraint: Range: ] - ∞,∞[.

c) int simulationsInUse (Mandatory)
Constraint: Range: ] - ∞,∞[.

(3) Used by: SimulationAvailabilityReply.

## 4.159. typedef<string> SimulationName

(1) <u>Pattern:</u> TEXT{1,40}

(2) Used by: Simulation.

## 4.160. <<enumeration>> SimulationType

- (1) Describes the different types of simulations.
- (2) Values:

## a) NMOC MANAGED SIMULATION

The simulation is managed (start/stop) and prepared by NMOC for the other users (B2B & B2C) to have a look at the results. Optionally the users can create or modify the measures and tactical updates to evaluate the what-if effects.

## b) **STANDALONE SIMEX**

The simulation is a standalone SIMulation Experiment (SIMEX). Special future events are typically prepared and simulated on SIMEX with specially modified environment (CACD) data and forecasted traffic. It can be used as a reference for other simulations to evaluate different alternatives and compare with the STANDALONE\_SIMEX as reference. The simulation is managed (start/stop) and prepared by NMOC for the other users (B2B & B2C) to have a look at the results. Optionally the users can create or modify the measures and tactical updates.

#### c) USER MANAGED SIMULATION

The simulation is managed (start/stop) and prepared by the users (via B2B & B2C) to simulate some measures and evaluate their effect. In addition the user can request other users or NMOC to have a look at proposed solution or to contribute to the simulation.

## 4.161. StandaloneSimex

- (1) The simulation is a standalone SIMulation Experiment (SIMEX).
- (2) It can be used as a reference for other simulations.
- (3) The dataset corresponding to a standalone SIMEX simulation has as type <u>STANDALONE\_SIMEX</u>.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

(4) <u>Inherits from: Simulation</u>.

## 4.162. <<enumeration>> SubTotalsTrafficCountsType

- (1) Enumerates the possible sub totals counts types.
- (2) Values:
  - a) ATC ACTIVATED

ATC activated flights. Note that this also includes terminated flights that were ATC activated.

b) **IFPL** 

Flights created from a flight plan filed to IFPS that are not suspended, nor ATC\_ACTIVATED, nor TACT\_ACTIVATED\_WITH\_FSA, nor TACT\_ACTIVATED\_WITHOUT\_FSA.

c) **PFD** 

Predicted flights (See Forecast and Operational Datasets) that are not suspended

d) RPL

Flights created from a repetitive flight plan that are not suspended and for which no flight plan has been filed yet (by the Airspace user or by IFPS).

e) SUSPENDED

Suspended Flights. Note that suspended flights are not considered part of the <u>Traffic-Type.LOAD</u>.

f) TACT ACTIVATED WITHOUT FSA

TACT activated with no FSA message expected. Note that this also includes terminated flights that were TACT\_ACTIVATED\_WITHOUT\_FSA.

g) TACT\_ACTIVATED\_WITH\_FSA

TACT activated with FSA message expected (but not yet received). Note that this also includes terminated flights that were TACT\_ACTIVATED\_WITH\_FSA.

(3) Used by: Counts.

# 4.163. <<abstract>> TacticalConfigurationPlan

- (1) Common information for all configuration plans on a given day.
- (2) Attributes:
  - a) PlanDataId dataId (Mandatory)

Opaque identifier representing the version of this plan.

<u>Constraint:</u> See <u>INCONSISTENT\_DATAID\_AND\_DATASET\_TYPE</u>

b) **Dataset dataset** (Mandatory)

Dataset to which the plan belongs.

Constraints:

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- i) See <u>INCONSISTENT\_DATAID\_AND\_DATASET\_TYPE</u>
- ii) See <u>INCONSISTENT\_DAY\_AND\_DATASET\_TYPE</u>
- c) <u>DateYearMonthDay</u> day (Mandatory)

Day for which this plan is valid.

Constraint: See INCONSISTENT DAY AND DATASET TYPE

d) **boolean planTransferred** (Optional)

Indicates if the plan has been transferred to the OPERATIONAL dataset. When false, it means that the most up-to-date data can be found in the FORECAST dataset.

e) boolean planCutOffReached (Optional)

Indicates if the plan can still be updated in the F0RECAST dataset, i.e. if the forecast cut-off time has been reached or not.

## (3) Constraints:

a)	Name	INCONSISTENT_DATAID_AND_DATASET_TYPE
	Attributes	dataId, dataset
	•	The dataId must match the one returned by the corresponding retrieval request for the given dataset.

b)	Name	INCONSISTENT_DAY_AND_DATASET_TYPE	
	Attributes	day, dataset	
	Description	The day must be in [ today today+5d ] depending on dataset type i.e.:	
		i) day must be in [ today today+5d ] in an F0RECAST context.	
		ii) day must be in [ today tomorrow ] in an OPERATIONAL context.	
		iii) day has no range constraint in a SIMULATION context.	

(4) <u>Extended by: TrafficVolumeActivationPlans, OTMVPlan, SectorConfigurationPlan, TrafficVolume-ActivationPlan, CapacityPlans, RunwayConfigurationPlan, OTMVPlans.</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.	0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 4.164. <<abstract>> TacticalConfigurationRetrievalRequest




Figure 4.27. <<abstract>> TacticalConfigurationRetrievalRequest Class Diagram

- (1) Abstract request to retrieve a tactical configuration (runway, sector, capacity, TV, OTMV) on a given day.
- (2) <u>Inherits from: Request</u>.
- (3) Attributes:
  - a) Dataset dataset (Mandatory)
     Dataset for which the tactical configuration is requested.
     Constraint: See INCONSISTENT\_DAY\_AND\_DATASET\_TYPE
  - b) DateYearMonthDay day (Mandatory)
    Day for which the tactical configuration is requested.
    Constraint: See INCONSISTENT DAY AND DATASET TYPE

## (4) Constraint:

a)	Name	INCONSISTENT_DAY_AND_DATASET_TYPE
	Attributes	day, dataset
	Description	The day must be in [D-5, D] depending on dataset type i.e.:
		i) day must be in [D-5, D] in an F0RECAST context.
		ii) day must be in [D-1, D] in an OPERATIONAL context.
		iii) day has no range constraint in a SIMULATION context.

(5) <u>Extended by: CapacityPlanRetrievalRequest, RunwayConfigurationPlanRetrievalRequest, TrafficVolumeActivationPlanRetrievalRequest, SectorConfigurationPlanRetrievalRequest, OTMVPlanRetrievalRequest.</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## 4.165. <<abstract>> TrafficCountsReplyData




Figure 4.28. <<abstract>> TrafficCountsReplyData Class Diagram

- (1) Abstract reply returned in response to an abstract <u>TrafficCountsRequest</u>.
- (2) Attributes:
  - a) DateTimeMinutePeriod effectiveTrafficWindow (Mandatory)
    The effective period of time for which counts were requested.
    Flights from within this period have been used in the counts. See also TrafficCounts-Request.trafficWindow.
  - b) Set<Flow> flows (Optional)

The flows for which the traffic counts are requested.

This attribute is set only when requested (i.e., <a href="mailto:TrafficCountsByTrafficVolumeRe-quest.computeFlowCounts">TrafficCountsByTrafficVolumeRe-quest.computeFlowCounts</a> has been set to true)

Constraint: Size must be comprised between 1 and 100.

- c) Map<<u>DateTimeMinutePeriod</u>, Map<<u>TrafficType</u>, <u>Counts</u>>> counts (Optional)
  The traffic counts by period (interval) and by requested traffic type.
  Constraints:
  - i) Size must be comprised between 0 and 1440.
  - ii) Item size must be comprised between 1 and 3.
- d) Map<<u>TrafficType</u>, Set<<u>OtmvAlert</u>>> otmvAlerts (Optional)

The OTMV alerts by traffic type for OTMV duration <u>TrafficCountsRequest.countsInterval.duration</u>.

All count periods(intervals) that start in <a href="OtmvAlert.period">OtmvAlert.period</a> are considered to have an OTMV alert with <a href="OtmvStatus">OtmvStatus</a>.

This attribute is set only when requested (i.e., <u>TrafficCountsByTrafficVolumeRequest.computeOtmvAlerts</u> has been set to true)

<u>Constraints:</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

- i) Size must be comprised between 0 and 3.
- ii) Item size must be comprised between 1 and 1440.
- (3) <u>Extended by: TrafficCountsByPointReplyData, TrafficCountsByTrafficVolumeReplyData, TrafficCountsByAirspaceReplyData, TrafficCountsByAircraftOperatorReplyData, TrafficCountsByAerodromeSetReplyData, TrafficCountsByAerodromeSetReplyData.</u>

# 4.166. <<abstract>> TrafficCountsRequest




Figure 4.29. <<abstract>> TrafficCountsRequest Class Diagram

- (1) Abstract request to query traffic counts.
- (2) <u>Inherits from: Request</u>.
- (3) Attributes:
  - a) Dataset dataset (Mandatory)

Dataset for which the runway configuration plan is requested.

See <u>Forecast and Operational Datasets</u> and <u>Simulation Datasets</u>.

<u>Constraint:</u> See <u>INVALID\_QUERY\_PERIOD\_RANGE</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## b) <u>DateTimeMinutePeriod</u> trafficWindow (Mandatory)

The period of time for which traffic counts are requested.

Typically in a traffic counts reply, more than one traffic count period/interval is returned. For each such period, count values are returned. Each such count period has a duration of countsInterval.duration. The start of the count periods is are separated by countsInterval.step.

The last count period (for which counts are returned) is the count period that starts before trafficWindow. Unt (but the end of that last count period can extend beyond the trafficWindow. Unt, as the duration of that count period is countsInterval.duration). Note that the first count period can start before trafficWindow. Wef as the count period start is rounded down to a multiple of countsInterval.step.

The effectiveTrafficWindow indicates the real traffic window for which flights have been taken into account to compute the different count periods and count values. See CountsInterval.

#### Constraints:

- i) See <u>INVALID QUERY PERIOD RANGE</u>
- ii) See PERIOD EXTENSION CANNOT BE GREATER THAN 24 HOURS

## c) **boolean includeProposalFlights** (Mandatory)

Determines if the selected traffic must include the proposal flights, or only the real flights. If the proposal flights are included, they replace their corresponding real flights. See <a href="Proposal Flights">Proposal Flights</a>.

## d) boolean includeForecastFlights (Mandatory)

Determines if the selected traffic must include the "forecast" flights. In the OPERATIONAL dataset (or in a simulation on OPERATIONAL), a "forecast" flight is a predicted flight (cfmuFlightType = PREDICTED\_FLIGHT). In the FORECAST dataset (or in a simulation on FORECAST), a "forecast" flight is a predicted flight with no intention data.

#### e) Set<<u>TrafficType</u>> trafficTypes (Mandatory)

Requested traffic types. For each traffic type, the count values will be returned. Constraints:

- i) Size must be comprised between 1 and 3.
- ii) See ONLY ONE TRAFFIC TYPE IF FLOW COUNTS

## f) boolean computeSubTotals (Mandatory)

If false then for each traffic type selected a single total is returned. If true then for each traffic type selected detailed sub-totals are returned.

The sub-totals traffic counts types are defined in <u>SubTotalsTrafficCountsType</u>.

## g) <u>CountsInterval</u> countsInterval (Mandatory)

Determines how many count periods need to be returned in the trafficWindow and determines the duration of each period.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

## (4) Constraints:

a)	Name	PERIOD_EXTENSION_CANNOT_BE_GREATER_THAN_24_HOURS
	Attribute	trafficWindow
	Description	The period extension must be smaller or equal to 24 hours.

b)	Name	ONLY_ONE_TRAFFIC_TYPE_IF_FLOW_COUNTS
	Attribute	trafficTypes
	•	Only one traffic type can be requested in trafficTypes when <u>TrafficCounts-</u>
		ByTrafficVolumeRequest.computeFlowCounts is set to true.

c)	Name	INVALID_QUERY_PERIOD_RANGE
	Attributes	trafficWindow, dataset
	Description	The dataset.type from which the traffic counts are requested and the trafficWindow must be set according to the following rules:
		i) if the DatasetType is equals to FORECAST the trafficWindow shall be defined within the range [ today today+5d ]
		ii) if the DatasetType is equals to OPERATIONAL the trafficWindow shall be defined within the range [yesterday 21:00 UTC tomorrow]

(5) <u>Extended by:</u> <u>TrafficCountsByPointRequest, TrafficCountsByAerodromeRequest, TrafficCountsByAirspaceReguest, TrafficCountsByAirspaceReguest, TrafficCountsByAerodromeSetRequest.</u>

## 4.167. TrafficVolumeActivationPlan

- (1) Activation plan for a given traffic volume on a given day.
- (2) A Traffic Volume Activation plan is a special plan in the sense that, there can be cases where there is no data known. So there exist traffic volumes for which there is no data at all or only for some periods. In addition, non-activation is not defined in CACD. Therefore the absence of CACD data (NO\_DATA datasource) means either no data known or in-active. Either way, the absence of data is considered by NM systems as an in-active traffic volume. In addition, sector configuration activations (tactically updated or CACD defined) also over-rule CACD activations of a traffic volume. They can activate or de-activate a traffic volume (also marked by AIRSPACE datasource). The above activations can be over-ruled (set active or in-active) by the tactical updates (B2B or HMI). In addition regulation measures can activate a traffic volume (over-ruling either CACD or B2B/HMI updates). The consolidated info can be found back in the nmSchedule attribute.
- So the (de-)activation of a traffic volume is determined hierarchically by NO\_DATA (least priority), CACD (including derived from sector config), tactical updates (a.o. via B2B), regulation measures

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

(highest priority). In the client schedule the non regulated traffic volumes activations are maintained (just in case the regulation can be cancelled before the end of its applicability period).

- (4) In a retrieval context, the plan is said to be 'complete' in the sense that it contains all the plan entries from all involved data sources (including NO\_DATA data source in case no info is known).
- (5) In an update context, the plan can be complete (if the B2B client designer decided to overwrite the default CACD values/sector configuration derived activation) or limited to the (full list) of (pre)tactical updates with the gaps marked as AIRSPACE (meaning in update context: NO\_DATA or CACD or derived from sector config) datasource (to obtain a complete time partition).
- (6) In any case, periods marked with datasource AIRSPACE in the time partition correspond to removing any potential (pre-)tactical update and hence reset the corresponding values to the NO\_DATA/CACD/"derived from sector config" definition for that period.
- (7) <u>Inherits from: TacticalConfigurationPlan.</u>
- (8) Attributes:
  - a) <u>TrafficVolumeId</u> trafficVolume (Mandatory) Traffic volume to which this activation plan applies.
  - b) Set<<u>PlannedTrafficVolumeActivation</u>> nmSchedule (Contextual)

The plan resulting from the superimposition of all constraints from all data sources, which the NM system is using as plan for its own calculations.

The NM schedule exposes the complete time partition of the configurations for the day, i.e. the data coming from the various data sources contributing to the NM view of the plan: these data sources are defined in PlanDataSource.

The NM schedule cannot be updated directly by the caller; it is the outcome of updates via the various data sources.

In nmSchedule the possible values of <u>dataSource</u> are limited to NO\_DATA, AIRSPACE, TACTICAL and MEASURE.

Note that NO\_DATA in nmClientSchedule means either inactive or that no data has been specified.

Presence:

- i) Must be null in <u>CapacityPlanUpdateRequest</u>, <u>OTMVPlanUpdateRequest</u>, RunwayConfigurationPlanUpdateRequest, <u>SectorConfigurationPlanUpdateRequest</u>, <u>dateRequest</u>, <u>TrafficVolumeActivationPlanUpdateRequest</u>
- ii) Mandatory otherwise.Constraint: Size must be comprised between 0 and ∞.
- c) Set<PlannedTrafficVolumeActivation> clientSchedule (Mandatory)
  (Pre-)tactical traffic volume activations associated to their applicability period, as maintained by the client. This plan contains only the updated configurations together with an indication (AIRSPACE datasource) that the default CACD/sector config derived values apply when not updated (cf. PlanDataSource). The actual activity for these airspace datasource periods can be found in the nmSchedule

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

In an update context, the clientSchedule can be complete (if the B2B client designer decided to overwrite the default CACD values) or limited to the actual differences with regards to the AIRSPACE defaults. This is a B2B client designer's decision and depends on how CACD wants to be used in combination with the B2B. If the clientSchedule only contains the actual differences with regards to the AIRSPACE defaults, then the clientschedule still needs to contain the full list of (pre-) tactical updates and for the non (pre-) tactically updated periods, an explicit indication that the AIRSPACE values need to be used (but without repeating the NO\_DATA/CACD/sector config derived values themselves). So in any case, the clientschedule needs to be a complete time partition for the full day.

In any case, it is of drastic importance to understand that an entry in the schedule (i.e. a period) overwrites all CACD/sector config derived values in that period.

The possible values of <u>dataSource</u> are limited to AIRSPACE and TACTICAL - the AIRSPACE value meaning that the value associated to the <u>applicabilityPeriod</u> is the CACD one (i.e. CACD or the TV activation derived from a sector configuration or that there is no data defined in CACD), and the TACTICAL value meaning that this plan entry corresponds to the explicit tactical update expressed via <u>active</u>.

**Constraints:** 

- i) Size must be comprised between 0 and  $\infty$ .
- ii) See <u>INCOMPLETE\_SCHEDULE</u>

## (9) Constraint:

a)	Name	INCOMPLETE_SCHEDULE
	Attribute	clientSchedule
	•	clientSchedule has gaps and/or overlaps in the time partition or is not covering exactly one day.

## 4.168. TrafficVolumeActivationPlans

- (1) Activation plans for one or more traffic volumes on a given day.
- (2) A Traffic Volume Activation plans contains a map of a special plan in the sense that, there can be cases where there is no data known. So there exist traffic volumes for which there is no data at all or only for some periods. In addition, non-activation is not defined in CACD. Therefore the absence of CACD data (NO\_DATA datasource) means either no data known or in-active. Either way, the absence of data is considered by NM systems as an in-active traffic volume. In addition, sector configuration activations (tactically updated or CACD defined) also over-rule CACD activations of a traffic volume. They can activate or de-activate a traffic volume (also marked by AIR-SPACE datasource). The above activations can be over-ruled (set active or in-active) by the tactical updates (B2B or HMI). In addition regulation measures can activate a traffic volume (over-ruling either CACD or B2B/HMI updates). The consolidated info can be found back in the nmSched-ule attribute.
- (3) So the (de-)activation of a traffic volume is determined hierarchically by NO\_DATA (least priority), CACD (including derived from sector config), tactical updates (a.o. via B2B), regulation measures

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

(highest priority). In the client schedule the non regulated traffic volumes activations are maintained (just in case the regulation can be cancelled before the end of its applicability period).

- (4) In a retrieval context, the plan is said to be 'complete' in the sense that it contains all the plan entries from all involved data sources (including NO\_DATA data source in case no info is known).
- (5) In an update context, the plan can be complete (if the B2B client designer decided to overwrite the default CACD values/sector configuration derived activation) or limited to the (full list) of (pre)tactical updates with the gaps marked as AIRSPACE (meaning in update context: NO\_DATA or CACD or derived from sector config) datasource (to obtain a complete time partition).
- (6) In any case, periods marked with datasource AIRSPACE in the time partition correspond to removing any potential (pre-)tactical update and hence reset the corresponding values to the NO\_DATA/CACD/"derived from sector config" definition for that period.
- (7) <u>Inherits from: TacticalConfigurationPlan.</u>
- (8) Attributes:
  - a) Map<<u>TrafficVolumeId</u>, <u>PlannedTrafficVolumeActivations</u>> tvActivations (Mandatory)

A map of Traffic volumes as keys mapped to its capacities. Constraints:

- i) Size must be comprised between 0 and  $\infty$ .
- ii) See <u>INCOMPLETE SCHEDULE</u>
- (9) Constraint:

a)	Name	INCOMPLETE_SCHEDULE
	Attribute	tvActivations
	•	tvCapacities.clientSchedule has gaps and/or overlaps in the time partition or is not covering exactly one day.

(10) <u>Used by: TrafficVolumeActivationPlanRetrievalReply, TrafficVolumeActivationPlanUpdateReply, TrafficVolumeActivationPlanUpdateRequest.</u>

## 4.169. typedef<string> TrafficVolumeId

- (1) NM unique identifier for a traffic volume.
- (2) Pattern: (ALPHA|DIGIT) {1,8}
- (3) <u>Used by: OTMVPlan, OTMV, NetworkImpactAssessmentRetrievalReply, TrafficVolumeActivation-PlanRetrievalRequest, NetworkImpactAssessmentRetrievalRequest, TrafficVolumeActivationPlans, MeasureIdAndTV, CapacityPlans, ScenarioListRequest, CapacityPlanRetrievalRequest, OTM-VWithDuration, TrafficVolumeActivationPlan, TrafficVolumeScenarios, ScenarioAttributes.</u>

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

## 4.170. TrafficVolumeLocation

- (1) Details the location at which a measure applies.
- (2) <u>Inherits from: Location</u>.
- (3) Attributes:
  - a) ReferenceLocation referenceLocation (Contextual)
    The reference location of the traffic volume to which the measure applies.
    Presence:
    - i) Must be null in <a href="MCDMOnlyCreationRequest">MCDMOnlyUpdateRequest</a>, <a href="RegulationProposalFilingRequest">RegulationProposalFilingRequest</a>, <a href="RegulationUpdateRequest">RegulationUpdateRequest</a>, <a href="ReroutingCreationRequest">ReroutingCreationRequest</a>, <a href="ReroutingUpdateRequest">ReroutingUpdateRequest</a>
    - ii) Optional otherwise.
  - b) <u>TrafficVolumeId</u> id (Mandatory)
    The traffic volume to which the measure applies.
  - c) FlightLevelRange flightLevels (Contextual)
    Flight level range of the traffic volume to which this measure applies.
    Presence:
    - i) Must be null in MCDMOnlyCreationRequest, MCDMOnlyUpdateRequest, RegulationCreationRequest, RegulationProposalFilingRequest, RegulationProposalUpdateRequest, RegulationUpdateRequest, ReroutingCreationRequest, ReroutingUpdateRequest
    - ii) Optional otherwise.
  - d) **string description** (Contextual)

The traffic volume description to which the measure applies. Presence:

- i) Must be null in MCDMOnlyCreationRequest, MCDMOnlyUpdateRequest, RegulationCreationRequest, RegulationProposalFilingRequest, RegulationProposalUpdateRequest, RegulationUpdateRequest, ReroutingCreationRequest, ReroutingUpdateRequest
- ii) Optional otherwise.
- e) Set<<u>TrafficVolumeSetId</u>> setIds (Contextual)

The set of traffic volume sets containing the traffic volume to which this measure applies. Presence:

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices		B2B/23.0.0/Flow

- i) Must be null in <a href="MCDMOnlyCreationRequest">MCDMOnlyUpdateRequest</a>, <a href="RegulationProposalFilingRequest">RegulationProposalFilingRequest</a>, <a href="RegulationUpdateRequest">RegulationUpdateRequest</a>, <a href="ReroutingCreationRequest">ReroutingCreationRequest</a>, <a href="ReroutingUpdateRequest">ReroutingUpdateRequest</a>
- ii) Optional otherwise.<u>Constraint:</u> Size must be comprised between 1 and 200.
- (4) <u>Used by: RegulationOrMCDMOnly.</u>

## 4.171. TrafficVolumeScenarios

- (1) For a traffic volume, represents the scenario's (from the NM scenario repository) that contain measures (regulation or rerouting) based on that traffic volume.
- Typically when the end-user has an overload on a "problem" traffic volume, then he wants to see which scenarios (solutions) can be applied to off-load that "problem" traffic volume. Those scenarios might be based on different traffic volumes that e.g. overlap with the "problem" traffic volume (e.g. in case the current sector configuration has grouped some sectors together).
- This class represents the different scenarios that have measures on one such scenario traffic volume (i.e. solution traffic volume).
- (4) Note that a scenario can have multiple measures: for example a contingency scenario contains multiple measures (on different traffic volumes) that can be used to handle the contingency. When such a scenario is applied one or more measures of the scenario are applied (but not necessarily all measures of the scenario).
- (5) The retrieveRegulationsFromScenario and retrieveReroutingsFromScenario services (flow) can then be used to retrieve the applicable measures themselves from these scenarios.
- The applicable measures are those measures that have as trafficVolumeId, the solution-TrafficVolumeId. Those measures can then be applied via B2B in a NM simulation (to evaluate the impact) or can be requested for implementation via the fileRegulationProposal, createRegulation and createRerouting service requests. (See general text on scenario repository in flow (below))
- <sup>(7)</sup> The queryScenarioRepository can be used to retrieve the details about the scenarios.
- (8) The trafficVolumeMatchingKind describes how the solution traffic volume relates to the problem traffic volume (e.g. they are both traffic volumes on the same reference location or they are overlapping or ... (See for more info: <a href="mailto:trafficVolumeMatchingKind">trafficVolumeMatchingKind</a>)
- (9) Attributes:
  - a) <u>TrafficVolumeId</u> solutionTrafficVolumeId (Mandatory) The (solution) traffic volume of the concerned scenario measures.
  - b) <u>ScenarioTrafficVolumeMatchingKind</u> trafficVolumeMatchingKind (Mandatory)

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices		B2B/23.0.0/Flow

Describes how the solutionTrafficVolumeId relates to the problem traffic volume (e.g. they are both traffic volumes on the same reference location or they are overlapping or ...(See for more info : ScenarioTrafficVolumeMatchingKind )).

c) Set<ScenarioId> scenarios (Mandatory)
The list of scenarios that contain measures on solutionTrafficVolumeId.
Constraint: Size must be comprised between 1 and ∞.

(10) <u>Used by: Flight, Flow</u>.

## 4.172. UpdateFlightInMeasure

- (1) Add, remove or update a flight in a measure. flightUpdate describes the different kind of operations supported on a flight.
- (2) Attributes:
  - a) FlightKeys flightKeys (Mandatory)
     The flight keys.
  - b) **UpdateFlightInMeasureChoice flightUpdate** (Mandatory) Either:
    - · force/unforce the CTOT, or
    - include/exclude the flight from one or more regulations, or
    - · add/remove a flight to/from a measure.
- (3) <u>Used by: UpdateFlightsInMeasureReply, UpdateFlightsInMeasureRequest.</u>

# 4.173. UpdateFlightInMeasureChoice

- (1) Describes the different kind of operations supported on a flight in the context of an UpdateFlight-InMeasure.
- (2) Choices:
  - a) ReroutingId addFlightToRerouting

    Add a flight to a cherry picked rerouting.
  - b) ReroutingId removeFlightFromRerouting Remove a flight from a rerouting.
  - c) RegulationId addFlightToMCDMOnlyMeasure
    Add a flight to the MCDM\_only measure with this measure identifier.
  - d) RegulationId removeFlightFromMCDMOnlyMeasure
    Remove a flight from the MCDM\_only measure with this measure identifier.

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manua FlowServices	B2B/23.0.0/Flow

- e) <u>ForceFlightInRegulation</u> forceFlightInRegulation force a flight in a regulation or add a flight to a cherry picked regulation (by forcing).
- f) RegulationId unforceFlightInRegulation

Unforce a forced flight in a regulation or remove a flight from a cherry picked regulation (by unforcing it will become exempted again).

If the normal flight is forced, then this will result in a proposal to NMOC to unforce the flight from the regulation (in simulations it directly unforces the flight).

Typically in operational dataset context, one needs to submit a proposal for NMOC to review: in the context of a proposal cherry picked regulation (See fileRegulationProposal service) or in the context of modifying the CTOT of a flight in a normal (non-cherry-picked) regulation.

- g) <u>ExcludeReIncludeFlightInRegulation</u> excludeFlightFromRegulation Exclude a flight from 1 or more regulations.
- h) <u>ExcludeReIncludeFlightInRegulation</u> reIncludeFlightInRegulation Re-include a flight in one or more regulations from which the flight is excluded.
- i) void removeProposalFlight

Allows to remove/undo a proposal created by forceFlightInRegulation, unforce-FlightInRegulation, excludeFlightFromRegulation or reIncludeFlightIn-Regulation.

Note that removeFlightFromRerouting needs to be used to remove a proposal created by addFlightToRerouting.

(3) <u>Used by: UpdateFlightInMeasure</u>.

## 4.174. UserManagedSimulation

- (1) The simulation is managed (start/stop) and prepared by the users (via B2B & B2C) to simulate some measures and evaluate their effect.
- (2) In addition the user can request other users or NMOC to have a look at proposed solution or to contribute to the simulation.
- (3) The dataset corresponding to a UserManagedSimulation simulation has as type USER MANAGED SIMULATION
- (4) Inherits from: Simulation.
- (5) <u>Attributes:</u>
  - a) **DatasetReference** datasetReference (Mandatory)

The reference on which this simulation is based (i.e. from which environment data has been copied and where initially the flights and measures have been copied from).

<u>Constraint:</u> See <u>INVALID\_DATASET\_REFERENCE\_TYPE</u>

b) <u>UserId</u> creator (Optional)

DNM	EUROCONTROL
Document Title:	Document Reference:
NM 23.0.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

The B2B or B2C user that created (started) the simulation.

c) AirNavigationUnitId creatorANUId (Optional)
The ANU identifier of the creator.

## (6) Constraints:

a)	Name	INVALID_DATASET_REFERENCE_TYPE
	Attribute	datasetReference
	Description	DatasetReference.type must be 0PERATIONAL or F0RECAST.

b)	Name	INVALID_SIMULATION_IDENTIFIER_TYPE
	Attribute	dataset
	Description	SimulationIdentifier.simulationType must be USER_MANAGED_SIMULATION.

(7) <u>Used by: SimulationStartRequest, SimulationStartReply.</u>

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# **Chapter 5. PRE-OPS Testing**

(1) The data available in the PRE-OPS platform for the current MeasuresService is fed daily from the OPS systems.

DNM		EUROCONTROL
Document Title:		Document Reference:
NM 23.0	.0 - NOP/B2B Reference Manuals - FlowServices	B2B/23.0.0/Flow

# **DOCUMENT FINAL PAGE**

To properly report any fault, or to propose a modification concerning the present document, please refer to:

- for faults, the Systems Incident Management Procedure, ref. STD-CM/PRO/SIMP
- for changes, the IT Change Management Process, ref. STD/ITSM/CHG