


Digital surfaces in DGtal Topology module (since 0.5)

Jacques-Olivier Lachaud

DGtal Meeting, june 2012




UMR 5127


Package Topology, available in DGtal 0.4

1. classical digital topology (*à la Rosenfeld*)

- ▶ Arbitrary adjacencies in \mathbb{Z}^n , but also in subdomains
- ▶ Digital topology = couple of adjacencies (Rosenfeld)
- ▶ Object = Topology + Set
- ▶ Operations : neighborhoods, border, connectedness and connected components, decomposition into digital layers, simple points





Adjacencies



thinning in (6,26)



Package Topology, available in DGtal 0.4

1. classical digital topology (*à la Rosenfeld*)
2. cubical cellular topology + algebraic topology
 - ▶ cells, adjacent and incident cells, faces and cofaces
 - ▶ signed cells, signed incidence, boundary operators



Package Topology, available in DGtal 0.4




1. classical digital topology (*à la Rosenfeld*)
2. cubical cellular topology + algebraic topology
3. digital surface topology (*à la Herman*)
 - ▶ surfels, surfel adjacency, surfel neighborhood
 - ▶ surface tracking (normal, fast), contour tracking in nD



Package Topology, new in DGtal 0.5

Digital Surface

- | | | |
|---------------------------------|---|------------------------|
| surfels / signed $n - 1$ -cells | } | • kind of "dual" graph |
| + adjacencies between surfels | | • kind of manifold |



Package Topology, new in DGtal 0.5




Digital Surface

surfels / signed $n - 1$ -cells	}	• kind of "dual" graph
+ adjacencies between surfels		• kind of manifold

1. High-level `DigitalSurface` class for representing any kind of digital surface
2. Many container classes for digital surfaces
 - ▶ boundary of digital shape
 - ▶ boundary of implicitly defined shape
 - ▶ set of surfels
 - ▶ implicitly defined set of surfels
 - ▶ light containers
3. a `DigitalSurface` is a graph
4. a `DigitalSurface` is a combinatorial surface (with umbrellas)

Direct applications

- marching cubes algorithm
- tracking implicit polynomial surfaces
- representing boundary of regions and frontier between regions
- breadth-first visiting on surfaces
- estimating normals on surfaces



Necessary concepts and classes for digital surfaces

One must choose

- the representation of cellular grid space : model of `CCellularGridSpaceND`
e.g. `KhalimskySpaceND< N, int >, Z2i::KSpace, Z3i::KSpace`
- the kind of adjacency between surfels, `SurfelAdjacency< N >`
- the kind of surface container : model of `CDigitalSurfaceContainer`

```

1  typedef Z3i::Point Point; // 3D digital point
2  typedef Z3i::Domain Domain;
3  typedef Z3i::DigitalSet DigitalSet; // a set of
    digital points
4  typedef Z3i::KSpace KSpace; // 3D cellular grid space
5  typedef SurfelAdjacency<3> SAdj; // surfel adjacency.
6  typedef DigitalSetBoundary<KSpace, DigitalSet>
    Container; // kind of surface container
7  typedef DigitalSurface<Container> MyDigSurf; //
    concrete digital surface

```


Concrete instantiations for digital surfaces

Then, the chosen types are instantiated. Here
 digital surface = boundary of two intersecting balls

```

1    Point p1( -20, -20, -20 ), p2( 20, 20, 20 );
2    KSpace K; K.init( p1, p2, true ); // init space
3    DigitalSet someShape( Domain( p1, p2 ) );
4    Shapes<Domain>::addNorm2Ball( someShape, Point
      (-3,0,0), 4 );
5    Shapes<Domain>::addNorm2Ball( someShape, Point
      (3,0,0), 4 );
6    SAdj surfAdj( true );           // the adjacency
7    Container surfContainer( K, someShape, surfAdj );
8    MyDigSurf digSurf( surfContainer ); // digital
      surface
  
```

Using the digital surface (displays 518) :


```

1    cout << "-_nb_surfels/vertices_="
2    << digSurf.size() << endl;
  
```

How to use digital surfaces (I)

Just enumerating its elements...

```
1   QApplication application( argc, argv );
2   Viewer3D viewer; // QGL viewer
3   viewer.show();
4   for( MyDigSurf::ConstIterator it = digSurf.begin(),
5       itend = digSurf.end(); it != itend; ++it )
6       viewer << *it;
7   viewer << Viewer3D::updateDisplay;
8   return application.exec();
```



Package description

Should contain

- classical digital topology \checkmark /a Rosenfeld
- cartesian cellular topology
- digital surface topology \checkmark /a Herman
- must be the base block of geometric algorithms

Examples

- adjacencies, connected components, simple points, thinning
- cells, boundary operators, incidence, opening, closing
- contours, surfel adjacency, surface tracking
- topological invariants

Location

- `{DGtal}/src/DGtal/topology`
- `{DGtal}/src/DGtal/helpers`
- `{DGtal}/tests/topology`