

```
import numpy as np
import pandas as pd
import numpy.matlib
import matplotlib.pyplot as plt
import seaborn as sns

def calc_distance(X1, X2):
    return (sum((X1 - X2)**2))*0.5

# Assign cluster clusters based on closest centroid
def assign_clusters(centroids, cluster_array):
    clusters = []
    for i in range(cluster_array.shape[0]):
        distances = []
        for centroid in centroids:
            distances.append(calc_distance(centroid,
                                           cluster_array[i]))
        cluster = [z for z, val in enumerate(distances) if val==min(distances)]
        clusters.append(cluster[0])
    return clusters

# Calculate new centroids based on each cluster's mean
def calc_centroids(clusters, cluster_array):
    new_centroids = []
    cluster_df = pd.concat([pd.DataFrame(cluster_array),
                             pd.DataFrame(clusters,
                                             columns=['cluster'])],
                           axis=1)
    for c in set(cluster_df['cluster']):
        current_cluster = cluster_df[cluster_df['cluster']\
                                       ==c][cluster_df.columns[:-1]]
        cluster_mean = current_cluster.mean(axis=0)
        new_centroids.append(cluster_mean)
    return new_centroids

# Calculate variance within each cluster
def calc_centroid_variance(clusters, cluster_array):
```

```

        cluster_mean = current_cluster.mean(axis=0)
        mean_repmat = np.matlib.repmat(cluster_mean,
                                         current_cluster.shape[0],1)
        sum_squares.append(np.sum(np.sum((current_cluster - mean_repmat)**2)))
    return sum_squares

titanic = pd.read_csv('AIML-SGPA.csv')

cluster_data = titanic[['SGPA']].copy(deep=True)
cluster_data.dropna(axis=0, inplace=True)
cluster_data.sort_values(by=['SGPA'], inplace=True)
cluster_array = np.array(cluster_data)

k = 3
cluster_vars = []
centroids = [cluster_array[i+2] for i in range(k)]
clusters = assign_clusters(centroids, cluster_array)
initial_clusters = clusters

print(0, round(np.mean(calc_centroid_variance(clusters, cluster_array))))
print('Cluster Details> ')
for i in range(3):
    centroids = calc_centroids(clusters, cluster_array)
    print(centroids)
    clusters = assign_clusters(centroids, cluster_array)
    cluster_var = np.mean(calc_centroid_variance(clusters,
                                                  cluster_array))

    print('Variance>', cluster_var)
    cluster_vars.append(cluster_var)
    print(i+1, round(cluster_var))

print('Data Points and Cluster category>')
for name, sgpa, clust_id in zip(titanic['Name'], titanic['SGPA'], clusters):
    print(name, sgpa, 'Cluster_ID= ', clust_id)

```

OnlineGDB beta
online compiler and debugger for c/c++

code compile run debug share.

IDE

My Projects




Classroom new

Learn Programming

Programming Questions

Sign Up

Login

   75.9K

main.py

input

Run Debug Stop Share Save Beautify

Traceback (most recent call last):
File "main.py", line 2, in <module>
import pandas as pd
File "/usr/lib/python3/dist-packages/pandas/__init__.py", line 40, in <module>
from pandas.core.api import *
File "/usr/lib/python3/dist-packages/pandas/core/api.py", line 12, in <module>
from pandas.core.series import Series, TimeSeries
File "/usr/lib/python3/dist-packages/pandas/core/series.py", line 2617, in <module>
import pandas.tools.plotting as _gfx
File "/usr/lib/python3/dist-packages/pandas/tools/plotting.py", line 23, in <module>
import pandas.tseries.converter as conv
File "/usr/lib/python3/dist-packages/pandas/tseries/converter.py", line 7, in <module>
import matplotlib.units as units
File "/usr/lib/python3/dist-packages/matplotlib/__init__.py", line 967, in <module>
rcParams = rc_params()
File "/usr/lib/python3/dist-packages/matplotlib/__init__.py", line 876, in rc_params
fname = matplotlib_fname()
File "/usr/lib/python3/dist-packages/matplotlib/__init__.py", line 744, in matplotlib_fname
configdir = _get_configdir()
File "/usr/lib/python3/dist-packages/matplotlib/__init__.py", line 613, in _get_configdir
return _get_config_or_cache_dir(_get_xdg_config_dir())
File "/usr/lib/python3/dist-packages/matplotlib/__init__.py", line 590, in _get_config_or_cache_dir
return _create_tmp_config_dir()
File "/usr/lib/python3/dist-packages/matplotlib/__init__.py", line 522, in _create_tmp_config_dir
tmpdir = os.path.join(tmpdir, 'matplotlib-%s' % getpass.getuser())
File "/usr/lib/python3.4/getpass.py", line 170, in getuser
return pwd.getpuid(os.getuid())[0]
KeyError: 'getpuid(): uid not found: 14054'

...Program finished with exit code 1
Press ENTER to exit console.