HELIOS USER GUIDE · GOVERNANCE

# Auditor / compliance

Procedures, usage, guidelines, and your roles and access

Read-only oversight: you review cases, AI decisions, rulebooks, retention and the audit chain, for internal audit, compliance or a regulator.

| | |
|---|---|
| Platform | HELIOS managed detection and response |
| Guide | 08 of 11 · Auditor / compliance |
| Date | 31 October 2026 |
| Version | Written against HELIOS 809e500 |
| Screenshots | Taken in the HELIOS test environment with test data, signed in as a auditor / compliance. Your screens show your own clients and data. |

# Contents

1. Your role at a glance
2. Roles and access
3. Getting started
4. Your screens
5. Procedures
6. Guidelines
7. Reference

> You have **17** of 50 permissions and **18** pages in your sidebar: Overview, Cases & Alerts, Endpoints, Reports, Compliance, AI Agents, SOC Operations, Response Playbooks, Runbooks, Threat Intelligence, Attack Graph, MITRE ATT&CK Coverage, Tools & Integrations, Rulebooks, Clients, Data Retention, Audit Log, API Tokens.

# 1. Your role at a glance

Read-only oversight: you review cases, AI decisions, rulebooks, retention and the audit chain, for internal audit, compliance or a regulator.

## What you are responsible for

- Verify the audit chain and export it for review.
- Review how cases were handled and what the AI decided, and why.
- Review compliance evidence (CERT-In, DPDP, ISO 27001 mapping) and data retention.

## A typical day or shift

1. Verify the audit chain (Verify chain integrity) before any review or export.
2. Sample cases across clients and read their timeline, AI runs and response actions.

## Who to turn to

Report findings to the SOC manager and the platform admin, or as your audit charter says.

# 2. Roles and access

## What you can see

You work across the clients the MSSP serves. The client switcher at the top focuses every page on one client, or All clients. You see every case queue regardless of security domains.

Your access comes from your role, and HELIOS checks it on the server for every page, button and API call; hiding a button is only a convenience. A change to your role applies on your next click. Everything you do is written to the hash-chained audit log under your name.

## Your pages

Overview, Cases & Alerts, Endpoints, Reports, Compliance, AI Agents, SOC Operations, Response Playbooks, Runbooks, Threat Intelligence, Attack Graph, MITRE ATT&CK Coverage, Tools & Integrations, Rulebooks, Clients, Data Retention, Audit Log, API Tokens, plus My alerts and your two-step sign-in settings in the user menu.

## Your permissions

| What the permission lets you do | You |
|---|---|
| **Cases** | |
| See the overview dashboard (dashboard.view) | Yes |
| See cases in their queues (or their own tenant, for clients) (cases.view) | Yes |
| See every queue, regardless of assigned security domains (cases.view_all) | Yes |
| Acknowledge cases, change status and severity (cases.triage) | No |
| Assign cases to other analysts (cases.assign) | No |
| Escalate or hand off a case to the next tier (cases.escalate) | No |
| Comment on cases and @mention teammates (cases.comment) | No |
| Share cases with the client and external channels (cases.share) | No |
| **Response** | |
| Run containment playbooks (subject to approval) (containment.request) | No |
| Approve or reject pending containment (containment.approve) | No |
| Isolate and release endpoints directly (endpoints.contain) | No |
| **Analysis** | |
| Run log investigations (investigations.run) | No |
| Submit emails and files for forensic analysis (forensics.run) | No |
| Upload raw logs into the detection pipeline (telemetry.ingest) | No |
| Govern AI agents: identities, tokens, revocation (governance.manage) | No |
| **Intelligence and detection** | |

| | |
|---|---|
| Look up threat indicators (intel.view) | **Yes** |
| Edit the blocklist and indicator store (intel.manage) | No |
| See ATT&CK coverage (mitre.view) | **Yes** |
| Switch SIEM detectors on and off (detections.tune) | No |
| See response playbooks (playbooks.view) | **Yes** |
| Author and enable response playbooks (playbooks.manage) | No |
| **AI agents** | |
| See AI agent runs and configuration (ai.view) | **Yes** |
| Dispatch AI agents onto a case (ai.dispatch) | No |
| Rate AI agent output (ai.feedback) | No |
| Configure AI providers, agent profiles and autonomy (ai.configure) | No |
| **Tools and endpoints** | |
| See onboarded security tools (integrations.view) | **Yes** |
| Onboard and configure security tools (integrations.manage) | No |
| See the endpoint inventory and protection coverage (endpoints.view) | **Yes** |
| **Clients and rulebooks** | |
| See client tenants (tenants.view) | **Yes** |
| Create and edit client tenants (tenants.manage) | No |
| Read a client's rulebook: what HELIOS may do on its estate (rulebook.view) | **Yes** |
| Draft changes to a client's rulebook and its allowlist (rulebook.edit) | No |
| Put a client's rulebook in force (client admins sign; staff only on the client's recorded instruction) (rulebook.sign) | No |
| **Compliance and reports** | |
| See regulatory clocks and notices (CERT-In, DPDP) and the ISO 27001 evidence map (compliance.view) | **Yes** |
| Draft regulatory notices, record the client's approval, and file them (compliance.prepare) | No |
| Approve a regulatory notice before it is filed (the report is the client's; staff record a client's approval given elsewhere) (compliance.approve) | No |
| Read client-facing incident reports (reports.view) | **Yes** |
| **SOC operations** | |
| See the on-call rota, pages, runbooks, QA results and digests (operations.view) | **Yes** |
| Edit the on-call rota, runbooks and operations settings (operations.manage) | No |
| Review the weekly sample of what the AI did on its own (qa.review) | No |
| **Commercial** | |

| | |
|---|---|
| Use the Build & Price configurator (pricing.view) | No |
| See internal cost and margin (pricing.margin) | No |
| Edit the price book (pricing.manage) | No |
| See contracts, pilots and invoices (clients: their own) (billing.view) | No |
| Draft and record contracts, issue invoices and record payments (billing.manage) | No |
| **Platform** | |
| Invite users and change roles (users.manage) | No |
| Edit platform settings: company profile, provider keys, forensics thresholds (settings.manage) | No |
| Read the audit chain (audit.view) | **Yes** |
| Export the audit chain (audit.export) | **Yes** |
| Create personal API tokens for the REST API (acting with their own permissions) (api.tokens) | **Yes** |

## How your role fits with the others

| Role | Group | What it is for |
|---|---|---|
| Platform admin | Leadership | Owns the platform: users, AI configuration, price book, everything else. |
| SOC manager | Leadership | Runs the SOC: every queue, approvals, AI autonomy, tool onboarding. |
| Tier-1 triage analyst | Security operations | Works the first-line queue: acknowledges, validates AI triage, escalates. |
| Tier-2 security analyst | Security operations | Primary analysis: investigations, forensics, containment requests. |
| Tier-3 incident responder | Security operations | Owns major incidents: approves containment, isolates endpoints, client comms. |
| Threat hunter | Security operations | Hunts across all tenants with investigations, forensics and intel. |
| Detection engineer | Engineering | Maintains playbooks, detections, tool integrations and ATT&CK coverage. |
| **Auditor / compliance** | Governance | Read-only oversight: cases, AI decisions and the audit chain. |
| Account manager | Commercial | Client onboarding, Build & Price quotes and margins. |
| Client admin | Client | Client-side: their own tenant's cases and tools; approves containment on their estate. |
| Client stakeholder | Client | Client-side read-only: dashboards, incident reports and endpoint coverage. |

# 3. Getting started

## Signing in

1. Open the HELIOS address you were given and sign in with your email and password. A new account gets a temporary password from its administrator.
2. If two-step sign-in is required, set it up the first time: scan the code with an authenticator app, enter a code, and keep the ten recovery codes somewhere safe. Each recovery code works once.
3. If your organisation uses single sign-on, use the sign-in button for your identity provider instead; it satisfies two-step sign-in.
4. Five wrong passwords or codes in a row lock the account for 15 minutes. An administrator can reset your password or your two-step sign-in if you lose your phone.

## Finding your way

- **Sidebar**: your pages, grouped (Operate, Analyze, Intelligence, Platform, Commercial). The arrow at the bottom collapses it.
- **Search or jump to** (Ctrl K or Cmd K): find a case, page or client by name.
- **Client switcher**: All clients, or focus every page on one client.
- **The bell**: your notifications (mentions, hand-offs, approvals, pages). Choose which also reach you by email, SMS or WhatsApp under My alerts.
- **Light, dark or system theme**, and your **user menu**: My alerts, two-step sign-in, Sign out.
- A yellow **Test environment** banner means everything on that installation is test data.

## Install it as an app

HELIOS can be installed from the browser (Install app in the address bar) as a desktop or mobile app with its own window and shortcuts.

# 4. Your screens

Each page you can open, what it is for, and how to use it with your access. Where a page is long, further screenshots show the rest.

## Overview

Your starting page. It shows what needs you now, and it changes with your role: the SOC sees live posture, queues, SLAs and AI activity; account managers see the commercial picture; client users see their own organisation.





Figure 1. Overview, as seen by a auditor / compliance (test environment).

### How to use it

- Needs attention now adds up what is due: cases whose SLA is due or breached, containment awaiting approval, unassigned critical and high cases, and cases assigned to you. Click a figure to open the matching list.
- The Live badge means the figures refresh on their own every 30 seconds; the arrow refreshes now.





Figure 2. Overview, further down the page.





Figure 3. Overview, further down the page.

## Cases & Alerts

Every case HELIOS has opened: detections from your clients' telemetry, vendor alerts, uploaded investigations, email and file analysis, and governed AI agents. Correlated detections for the same user, host or IP join one case instead of opening many.





Figure 4. Cases & Alerts, as seen by a auditor / compliance (test environment).

### How to use it

- Filter by status, severity, source, client and assignee, or search by title. Open a case by clicking its row.
- You see every queue regardless of security domains.
- The SLA badge counts down to the acknowledgement deadline from the client's plan; a red badge means it has been breached.




Figure 5. Cases & Alerts, further down the page.

## A case

Everything about one case on one page: what was detected, what the AI made of it, what has been done

and what is waiting, the evidence, and the discussion.




Figure 6. A case, as seen by a auditor / compliance (test environment).

### How to use it

- The header shows severity, status, the SLA, the tier (T1 triage, T2 analysis, T3 incident response), the security domain, the source, the client and whether AI triaged it. Below are the dates (created, acknowledged, contained, resolved), the assignee, the risk score, the confidence and the client's service plan. Report PDF downloads the incident report.
- AI first response shows the agent's verdict, confidence and engine, its summary, its key findings (each citing evidence: D detections, E events, I indicators, T timeline, C context) and what it asks the analyst to check. It is a first pass: a person confirms or corrects it.
- Indicators shows the case's IPs, domains, URLs, hashes and addresses with their reputation; the arrow re-checks one. Related cases lists earlier or concurrent cases sharing hosts, accounts, indicators or the same agent.
- Regulatory reporting shows whether CERT-In's 6-hour report or the DPDP breach notices apply, the incident types HELIOS proposes, and the notices' state.





Figure 7. A case, further down the page.





Figure 8. A case, further down the page.




Figure 9. A case, further down the page.

## Endpoints

The endpoint inventory and the whole attack surface: devices, servers, cloud, network, identity, IoT/OT

and applications, with how well each is protected.




Figure 10. Endpoints, as seen by a auditor / compliance (test environment).

### How to use it

- The tiles count assets, the average protection score, devices missing essential controls, devices isolated now and devices not seen for seven days.
- Attack surface inventory groups every asset; Protection coverage by control shows the share of computers, servers and phones where each protection layer (EDR, antivirus, disk encryption, MFA…) is active, with the essential ones marked.




Figure 11. Endpoints, further down the page.

## Reports

How the service performed over a period: volume, response times, SLA compliance, AI performance and

analyst workload, each compared with the period before.





Figure 12. Reports, as seen by a auditor / compliance (test environment).

## How to use it

- Pick a period or a month. The figures include median time to acknowledge, contain and resolve, acknowledgement SLA compliance, the mix by severity, source, domain and client, top ATT&CK techniques and indicators, AI runs and analyst agreement, and containment outcomes.
- Download the service report as a PDF for the client.




Figure 13. Reports, further down the page.

## Compliance

Regulatory clocks and evidence: CERT-In's 6-hour incident reports, the DPDP breach notices, and the

ISO/IEC 27001 evidence map.





Figure 14. Compliance, as seen by a auditor / compliance (test environment).

## How to use it

- Clocks running lists every notice not yet filed, nearest deadline first. CERT-In: incidents of the 20 listed types are reported within 6 hours of being noticed. DPDP: the Board and each affected person are told without delay, and the Board gets a detailed report within 72 hours.
- The ISO 27001 view maps 15 Annex A controls to what HELIOS's records show over the period, and shows gaps (controls with nothing behind them) plainly.
- Switch the period (30 days, 90 days, 12 months) at the top.





Figure 15. Compliance, further down the page.





Figure 16. Compliance, further down the page.

## AI Agents

The AI agents that work cases: what they did, how far they may act on their own, which models run them, and how those models scored.





Figure 17. AI Agents, as seen by a auditor / compliance (test environment).

### How to use it

- The tiles show AI runs in the last 30 days, analyst agreement, actions contained automatically, actions the guardrails blocked and the estimated model spend (with the share of input read from the prompt cache).
- The run log lists recent runs with their verdict, model, tokens and outcome.





Figure 18. AI Agents, further down the page.





Figure 19. AI Agents, further down the page.




Figure 20. AI Agents, further down the page.

## SOC Operations

Who is on call and the pages they get, the weekly QA of what the AI did on its own, and the daily digests.




Figure 21. SOC Operations, as seen by a auditor / compliance (test environment).

### How to use it

- The tiles show who is primary and backup on call now, unanswered pages and QA reviews waiting.




Figure 22. SOC Operations, further down the page.

## Response Playbooks

Automated response workflows: what triggers them and the steps they run (containment, collecting logs,

notifying, opening tickets).




Figure 23. Response Playbooks, as seen by a auditor / compliance (test environment).

## How to use it

- Each playbook shows its trigger, its steps and whether it is enabled. Its runs appear on the cases they ran on; steps that need approval wait in Approvals, and steps without a connector are left to do by hand.





Figure 24. Response Playbooks, further down the page.

## Runbooks

Procedures for analysts, attached to the cases they match and worked as checklists on the case.





Figure 25. Runbooks, as seen by a auditor / compliance (test environment).

### How to use it

- A runbook matches cases by ATT&CK technique or title words, narrowed by source and minimum severity. Up to three matching runbooks attach to a case when it is opened, the client's own first.

## Threat Intelligence

Look up indicators (IP, domain, URL, file hash, email address) against the SOC's indicator store, the configured reputation providers and the threat feeds.





Figure 26. Threat Intelligence, as seen by a auditor / compliance (test environment).

### How to use it

- Paste an indicator (defanged forms like hxxp and [.] are fine) and Look up. The result shows the verdict, score, sources, why, and for an IP where it is (country, city and network, from the server's GeoIP database). Results are cached for 24 hours; Bypass cache forces a fresh lookup.




Figure 27. Threat Intelligence, further down the page.

## Attack Graph

Cases joined by the hosts, accounts, addresses, indicators and agents they share. An entity is an attack

chain when its cases together reach more ATT&CK tactics than any one alone.





Figure 28. Attack Graph, as seen by a auditor / compliance (test environment).

## How to use it

- Hover or click a node to see the cases behind it; follow chains across tactics to see an intrusion that several smaller cases make up.





Figure 29. Attack Graph, further down the page.

## MITRE ATT&CK Coverage

Which ATT&CK techniques HELIOS can detect, across built-in detectors, Sigma rules and onboarded

tools, and which it has seen.




Figure 30. MITRE ATT&CK Coverage, as seen by a auditor / compliance (test environment).

## How to use it

- Read coverage by tactic and technique; gaps show where detection is missing.




Figure 31. MITRE ATT&CK Coverage, further down the page.

## Tools & Integrations

The security tools onboarded for each client: how their logs reach HELIOS and how HELIOS acts through

them.





Figure 32. Tools & Integrations, as seen by a auditor / compliance (test environment).

### How to use it

- The tiles count tools onboarded, connected, degraded and waiting for their first event. Protection stack coverage shows which security layers have a tool across your clients; gaps are where an attack can go unseen.
- Each tool shows how it sends logs (push to its ingest URL, HELIOS pulling from the vendor's API, or the HELIOS forwarder), its source health, and whether a response connector can act through it.
- A source silent longer than its limit opens a case: attackers often stop logging first. A client can't go live while a source is dead.





Figure 33. Tools & Integrations, further down the page.





Figure 34. Tools & Integrations, further down the page.

## Rulebooks

Each client's signed rules for what HELIOS may do on its estate. The rules only ever restrict: protected assets and accounts, which actions run automatically, need approval or never happen, blast-radius limits, business hours and change freezes, the approver chain, AI data handling and CERT-In contacts.





Figure 35. Rulebooks, as seen by a auditor / compliance (test environment).

### How to use it

- Pick the client at the top. The page shows the version in force, its hash and when it is due for review.
- The tabs: In force (the rules now applying), Edit, Dry run, Allowlist, Versions, AI models, Autonomy and Policy as code.
- Autonomy: the AI's autonomy ladder per action type for this client, and promotions waiting for approval.

## Clients

The client organisations (tenants): their plan and SLA, status, contacts, and how far they consent to AI

acting on their estate.





Figure 36. Clients, as seen by a auditor / compliance (test environment).

## How to use it

- Each client shows its plan, status (onboarding, active, suspended), licensed endpoints and users, and test clients are badged.

## Data Retention

Where each client's logs are kept and for how long, the encrypted archive, and legal holds.





Figure 37. Data Retention, as seen by a auditor / compliance (test environment).

### How to use it

- Retention by client: Searchable (days) and Kept (days). Where CERT-In's directions apply, Kept can't go below 180. Events attached to a case are kept with the case.
- The page says whether the logs are shown to be in India (the database region and the archive store's region), from what the server is configured with.
- Legal holds stop deletion over a date range (optionally tied to a case); placing and releasing need a reason. Archives download decrypted, and each download is audited.





Figure 38. Data Retention, further down the page.

## Audit Log

The hash-chained record of every action in HELIOS: who did what, when, to which case or object.





Figure 39. Audit Log, as seen by a auditor / compliance (test environment).

### How to use it

- Each entry stores the SHA-256 of its content plus the previous entry's hash, so editing or deleting any row breaks every hash after it. Verify chain integrity recomputes them all and names the first altered entry if there is one.
- Filter by area: cases, detection, investigations, forensics, governance, playbooks, threat intel.
- Export JSON exports the chain for an auditor or a regulator.




Figure 40. Audit Log, further down the page.

## API Tokens

Personal tokens for the REST API, for ticketing systems, SOAR and client portals. A token acts as you:

same role, client and queues.





Figure 41. API Tokens, as seen by a auditor / compliance (test environment).

## How to use it

- New token: give it a name (what will use it), an expiry (90 days by default), and switch on Read & write only if it must change things. Create token shows it once; copy it then. Your tokens lists yours to revoke.
- The page includes the API reference: endpoints, parameters and examples. Calls are limited to 300 a minute per token, and every change through the API is audited.





Figure 42. API Tokens, further down the page.

## A client's rulebook

The rulebook page for one client (here the test client Clinic).





Figure 43. A client's rulebook, as seen by a auditor / compliance (test environment).

## How to use it

- In force shows the assets (never isolated, crown jewels), the people (never disabled, VIPs), each action's mode (automatic from a severity, needs approval, two people), the schedule, the approver chain, and data handling and obligations. The other tabs are as described above.




Figure 44. A client's rulebook, further down the page.

## A client

One client's page: plan and SLA, contacts, consent, onboarding status, tools, users and data keys.





Figure 45. A client, as seen by a auditor / compliance (test environment).

### How to use it

- The page shows the client's open cases, SLA met, mean time to acknowledge and contain, endpoints, and buttons for its Rulebook, Review upgrades & price, and Edit client.





Figure 46. A client, further down the page.





Figure 47. A client, further down the page.

## Daily digests

Once a day, what HELIOS did on its own, what was waiting, and the deadlines coming up.





Figure 48. Daily digests, as seen by a auditor / compliance (test environment).

### How to use it

- Each digest lists actions the AI took without asking (with its autonomy level, rollbacks and QA calls), cases opened and closed, containment waiting for approval, regulatory deadlines within a day, quiet sources and the week's QA results.
- Choose under My alerts whether it also reaches you by email.

# My alerts

Which notifications also reach you outside HELIOS, by email, SMS or WhatsApp.





Figure 49. My alerts, as seen by a auditor / compliance (test environment).

## How to use it

- Every notification lands in the app (the bell at the top). Here choose, per kind of notification, the channels it also comes by, and give your phone number in international format (+91…).
- Deliveries that couldn't go (a channel not set up, no number, over the hourly cap) are listed with the reason.





Figure 50. My alerts, further down the page.

# 5. Procedures

Step by step, for the tasks your role does most.

## 5.1 Verify and export the audit chain

1. Open Audit Log and press Verify chain integrity. It recomputes every entry's hash; an alteration is reported with the first entry affected.
2. Filter to the area under review (cases, detection, forensics…), and Export JSON.

## 5.2 Review an AI decision

1. Open the case; read the AI first response, the evidence it cited, and the grounding (claims it couldn't tie to evidence are dropped).
2. In Response actions, each decision shows the rule that decided it: the response policy's stack of layers, the client's rulebook version, the autonomy ladder.
3. AI Agents shows each model's evaluation scorecard.

## 5.3 Review compliance evidence

1. On Compliance, read the ISO 27001 map for the period: what HELIOS's records show for each control, and the gaps.
2. On Data Retention, check each client's retention against its obligations (180 days minimum where CERT-In applies) and whether the logs are shown to be in India.

# 6. Guidelines

## Do

- Note the chain verification result in your working papers.
- Treat exported data as confidential client data.

## Don't

- Don't share exports outside the review they were made for.

## For everyone

- Never share your account or password; every action is recorded under your name.
- Keep client information inside HELIOS and to the people who need it.
- Treat text inside evidence (command lines, emails, file names) as possibly written by an attacker: it may address 'the AI' or 'the analyst' to mislead. HELIOS flags such text; don't follow it.
- Every action in HELIOS is reversible or recorded, and audited; write down why you did it.

> The client's signed rulebook binds everyone: the AI, playbooks and people. If HELIOS refuses an action, the reason names the rule. Don't work around it in a vendor's console; ask the client to change the rule.

# 7. Reference

## Terms you will see

### Case statuses

| | |
|---|---|
| **Open** | New; nobody has acknowledged it yet. |
| **Triaging** | Someone is looking at it. |
| **Investigating** | Under analysis. |
| **Awaiting approval** | Containment is waiting on someone's yes. |
| **Contained** | The threat is stopped; clean-up may continue. |
| **Resolved** | Closed with a disposition. |
| **False positive** | Closed: it wasn't a threat. |

### Severities

| | |
|---|---|
| **Critical, High, Medium, Low, Info** | Set by the detections and adjustable by analysts. The client's plan sets the acknowledgement SLA for each. |

### Dispositions (when closing)

| | |
|---|---|
| **True positive** | A real threat. |
| **Benign true positive** | Real activity, but expected or authorised (an admin's tool, a pen test). |
| **False positive** | Not what the detection thought. |

### Tiers

| | |
|---|---|
| **T1** | Triage. |
| **T2** | Analysis. |
| **T3** | Incident response. |

### Response action statuses

| | |
|---|---|
| **Suggested** | A recommendation only; autonomy doesn't allow acting. |
| **Pending approval** | Waiting on an approver. |
| **In progress** | The vendor was asked; waiting for it to confirm. Doesn't count as containment yet. |
| **Executed** | Done and confirmed by the vendor (or by an analyst for a manual action). |
| **Manual required** | Approved, but no connector can do it: someone does it in the tool's console and records it. |
| **Blocked** | A guardrail or the client's rulebook refused it; the reason is shown. |
| **Rejected** | An approver said no. |
| **Rolled back** | Undone. |

| | |
|---|---|
| **Failed** | The vendor or HELIOS couldn't do it. |
| **Shadow** | Shadow mode: what the AI would have done, recorded silently and shown once the case closes. |

### AI autonomy (per agent)

| | |
|---|---|
| **Off** | The agent doesn't run. |
| **Suggest only** | It proposes; people decide. |
| **Contain with approval** | Its containment waits for approval. |
| **Auto-contain** | It may act on pre-approved actions above its confidence bar. |

### Autonomy ladder (per client and action type)

| | |
|---|---|
| **L0 observe** | Shadow mode. |
| **L1 suggest** | Suggestions only. |
| **L2 approve** | Acts once approved. |
| **L3 act and notify** | Acts, and tells people at once. |
| **L4 act** | Acts, and reports in the daily digest. |

### Evidence references

| | |
|---|---|
| **D, E, I, T, C** | Detections, events, indicators, timeline entries and context in the case; Q for what the investigation agent's tools returned. Every AI finding cites them. |

## If something doesn't work

- **A page says you don't have access**: your role doesn't include it. Ask your administrator if your job needs it.
- **An action was refused**: the message names the rule (the client's rulebook, a guardrail, the plan or the kill switch).
- **An action is 'Manual required'**: no connector can do it. Do it in the tool's own console, then record what you did on the case.
- **You don't get alerts by SMS or email**: check My alerts for your channel choices, your phone number, and deliveries skipped with their reason.
- **You can't sign in**: after five failures the account locks for 15 minutes; your administrator can reset your password or two-step sign-in.