HELIOS USER GUIDE · CLIENT

Client admin

Procedures, usage, guidelines, and your roles and access

The administrator on the client's side: you see your organisation's incidents and logs, approve containment on your estate, approve the rules HELIOS works under, authorise security tests, and look after your security tools and contracts.

Platform	HELIOS managed detection and response
Guide	10 of 11 · Client admin
Date	1 November 2026
Version	Written against HELIOS aaea8f3
Screenshots	Taken in the HELIOS test environment with test data, signed in as a client admin. Your screens show your own clients and data.

Contents

1. Your role at a glance
2. Roles and access
3. Getting started
4. Your screens
5. Procedures
6. Guidelines
7. Reference

> You have **19** of 54 permissions and **14** pages in your sidebar: Overview, Incidents, Approvals, Endpoints, Service reports, Compliance, Search logs, Security testing, Attack Graph, Security tools, Our rulebook, Rule changes, API Tokens, Contracts & invoices.

1. Your role at a glance

The administrator on the client's side: you see your organisation's incidents and logs, approve containment on your estate, approve the rules HELIOS works under, authorise security tests, and look after your security tools and contracts.

What you are responsible for

- Approve or reject containment on your estate when the SOC or the AI asks.
- Own your rulebook: protected assets and accounts, what may happen automatically, approvers; approve each change for your organisation.
- Read HELIOS's final analysis of each incident and acknowledge it; approve lifting containment when its conditions hold.
- Authorise security tests of your internet-facing assets, and get the findings fixed.
- Approve regulatory notices (CERT-In, DPDP) before the SOC files them.
- Keep your security tools connected; decide which AI models may read your data.
- Sign contracts and keep track of invoices.

A typical day or shift

1. Check Approvals: containment, final analyses, notices and rule changes waiting on you.
2. Read Incidents for what is open and what was done.
3. Read your daily digest: what HELIOS did on its own, what is waiting, deadlines.

Who to turn to

Ask the SOC in the incident's discussion; for contract matters, contact your account manager.

2. Roles and access

What you can see

You see your own organisation only. HELIOS enforces this in the database itself (row-level isolation), so no screen, export or API call can show you another client's data.

Your access comes from your role, and HELIOS checks it on the server for every page, button and API call; hiding a button is only a convenience. A change to your role applies on your next click. Everything you do is written to the hash-chained audit log under your name.

Your pages

Overview, Incidents, Approvals, Endpoints, Service reports, Compliance, Search logs, Security testing, Attack Graph, Security tools, Our rulebook, Rule changes, API Tokens, Contracts & invoices, plus My alerts and your two-step sign-in settings in the user menu.

Your permissions

What the permission lets you do	You
Cases	
See the overview dashboard (dashboard.view)	Yes
See cases in their queues (or their own tenant, for clients) (cases.view)	Yes
See every queue, regardless of assigned security domains (cases.view_all)	No
Acknowledge cases, change status and severity (cases.triage)	No
Assign cases to other analysts (cases.assign)	No
Escalate or hand off a case to the next tier (cases.escalate)	No
Comment on cases and @mention teammates (cases.comment)	Yes
Share cases with the client and external channels (cases.share)	No
Response	
Run containment playbooks (subject to approval) (containment.request)	No
Approve or reject pending containment (containment.approve)	Yes
Isolate and release endpoints directly (endpoints.contain)	No
Analysis	
Run log investigations (investigations.run)	No
Submit emails and files for forensic analysis (forensics.run)	No
Upload raw logs into the detection pipeline (telemetry.ingest)	No
Govern AI agents: identities, tokens, revocation (governance.manage)	No
Intelligence and detection	

Look up threat indicators (intel.view)	No
Edit the blocklist and indicator store (intel.manage)	No
See ATT&CK coverage (mitre.view)	No
Switch SIEM detectors on and off (detections.tune)	No
See response playbooks (playbooks.view)	No
Author and enable response playbooks (playbooks.manage)	No
AI agents	
See AI agent runs and configuration (ai.view)	No
Dispatch AI agents onto a case (ai.dispatch)	No
Rate AI agent output (ai.feedback)	No
Configure AI providers, agent profiles and autonomy (ai.configure)	No
Tools and endpoints	
See onboarded security tools (integrations.view)	**Yes**
Onboard and configure security tools (integrations.manage)	**Yes**
See the endpoint inventory and protection coverage (endpoints.view)	**Yes**
Clients and rulebooks	
See client tenants (tenants.view)	No
Create and edit client tenants (tenants.manage)	No
Read a client's rulebook: what HELIOS may do on its estate (rulebook.view)	**Yes**
Draft changes to a client's rulebook and its allowlist (rulebook.edit)	**Yes**
Put a client's rulebook in force (client admins sign; staff only on the client's recorded instruction) (rulebook.sign)	**Yes**
Log search and security testing	
Search the logs HELIOS holds in Explore (client users: their own) (events.search)	**Yes**
See security tests of a client's internet-facing assets and their reports (clients: their own) (testing.view)	**Yes**
Ask for a security test of a client's own assets, and import scanner results into it (testing.request)	**Yes**
Authorise a security test: client admins for their organisation, HELIOS approvers for the SOC (testing.authorise)	**Yes**
Compliance and reports	
See regulatory clocks and notices (CERT-In, DPDP) and the ISO 27001 evidence map (compliance.view)	**Yes**
Draft regulatory notices, record the client's approval, and file them (compliance.prepare)	No
Approve a regulatory notice before it is filed (the report is the client's; staff record a client's approval given elsewhere) (compliance.approve)	**Yes**
Read client-facing incident reports (reports.view)	**Yes**

SOC operations	
See the on-call rota, pages, runbooks, QA results and digests (operations.view)	No
Edit the on-call rota, runbooks and operations settings (operations.manage)	No
Review the weekly sample of what the AI did on its own (qa.review)	No
Commercial	
Use the Build & Price configurator (pricing.view)	No
See internal cost and margin (pricing.margin)	No
Edit the price book (pricing.manage)	No
See contracts, pilots and invoices (clients: their own) (billing.view)	**Yes**
Draft and record contracts, issue invoices and record payments (billing.manage)	No
Platform	
Invite users and change roles (users.manage)	No
Edit platform settings: company profile, provider keys, forensics thresholds (settings.manage)	No
Read the audit chain (audit.view)	No
Export the audit chain (audit.export)	No
Create personal API tokens for the REST API (acting with their own permissions) (api.tokens)	**Yes**

How your role fits with the others

Role	Group	What it is for
Platform admin	Leadership	Owns the platform: users, AI configuration, price book, everything else.
SOC manager	Leadership	Runs the SOC: every queue, approvals, AI autonomy, tool onboarding.
Tier-1 triage analyst	Security operations	Works the first-line queue: acknowledges, validates AI triage, escalates.
Tier-2 security analyst	Security operations	Primary analysis: investigations, forensics, containment requests.
Tier-3 incident responder	Security operations	Owns major incidents: approves containment, isolates endpoints, client comms.
Threat hunter	Security operations	Hunts across all tenants with investigations, forensics and intel.
Detection engineer	Engineering	Maintains playbooks, detections, tool integrations and ATT&CK coverage.
Auditor / compliance	Governance	Read-only oversight: cases, AI decisions and the audit chain.
Account manager	Commercial	Client onboarding, Build & Price quotes and margins.

Client admin	Client	Client-side: their own tenant's cases and tools; approves containment on their estate.
Client stakeholder	Client	Client-side read-only: dashboards, incident reports and endpoint coverage.

3. Getting started

Signing in

1. Open the HELIOS address you were given and sign in with your email and password. A new account gets a temporary password from its administrator.
2. If two-step sign-in is required, set it up the first time: scan the code with an authenticator app, enter a code, and keep the ten recovery codes somewhere safe. Each recovery code works once.
3. Five wrong passwords or codes in a row lock the account for 15 minutes. An administrator can reset your password or your two-step sign-in if you lose your phone.

Finding your way

- **Sidebar**: your pages, grouped (Operate, Analyze, Intelligence, Platform, Commercial). The arrow at the bottom collapses it.
- **Search or jump to** (Ctrl K or Cmd K): find a case, page or client by name.
- **The bell**: your notifications (mentions, hand-offs, approvals, pages). Choose which also reach you by email, SMS or WhatsApp under My alerts.
- **Light, dark or system theme**, and your **user menu**: My alerts, two-step sign-in, Sign out.
- A yellow **Test environment** banner means everything on that installation is test data.

Install it as an app

HELIOS can be installed from the browser (Install app in the address bar) as a desktop or mobile app with its own window and shortcuts.

4. Your screens

Each page you can open, what it is for, and how to use it with your access. Where a page is long, further screenshots show the rest.

Overview

Your starting page. It shows what needs you now, and it changes with your role: the SOC sees live posture, queues, SLAs and AI activity; account managers see the commercial picture; client users see their own organisation.




Figure 1. Overview, as seen by a client admin (test environment).

How to use it

- The Live badge means the figures refresh on their own every 30 seconds; the arrow refreshes now.
- Your security at a glance: open incidents, SLA met over 30 days, average time to acknowledge and to contain, and your endpoints' average protection score. Below, incidents over the last 14 days and your service plan.
- Waiting for your approval lists containment the SOC proposed on your systems; Review opens the incident to approve or reject it.




Figure 2. Overview, further down the page.




Figure 3. Overview, further down the page.

Incidents

Every case HELIOS has opened: detections from your clients' telemetry, vendor alerts, uploaded investigations, email and file analysis, and governed AI agents. Correlated detections for the same user, host or IP join one case instead of opening many.




Figure 4. Incidents, as seen by a client admin (test environment).

How to use it

- You see only your own organisation's incidents. Open one to read what happened, what was done and what is waiting on you.




Figure 5. Incidents, further down the page.

A case

Everything about one case on one page: what was detected, what the AI made of it, what has been done

and what is waiting, the evidence, and the discussion.




Figure 6. A case, as seen by a client admin (test environment).

How to use it

- The header shows severity, status, the SLA, the tier (T1 triage, T2 analysis, T3 incident response), the security domain, the source, the client and whether AI triaged it. Below are the dates (created, acknowledged, contained, resolved), the assignee, the risk score, the confidence and the client's service plan. Report PDF downloads the incident report.
- Final analysis (HELIOS) appears once HELIOS has worked the case on its own: it collects every log the client's own tools hold about it, investigates, and writes the verdict and confidence, the summary and full report, the root cause, the scope, what happened, the findings and techniques, what is contained, the logs collected by type (and the types the client doesn't send), and open questions.
- Lifting containment: HELIOS never lifts containment on its own. Each release is proposed with its conditions (for a laptop: a clean EDR scan, persistence removed, passwords reset, 24 quiet hours); approve it when they hold.
- Remediation plan: the steps HELIOS can carry out (reset a password, purge a phishing mail, block a C2 address) wait as actions to approve or reject; the rest are tasks with an owner.
- Acknowledge records that your organisation has read the final analysis.
- Response actions lists containment the AI proposed and people requested, each with its status. Approve or Reject what is awaiting approval; the client's rulebook and the response policy still apply.
- Regulatory reporting shows whether CERT-In's 6-hour report or the DPDP breach notices apply, the incident types HELIOS proposes, and the notices' state.
- The discussion takes comments and @mentions. Internal comments stay with the SOC; client-visible ones reach the client.

- You can read the case, its timeline and what was done. Approve or reject containment on your estate from here or from Approvals.




Figure 7. A case, further down the page.




Figure 8. A case, further down the page.




Figure 9. A case, further down the page.




Figure 10. A case, further down the page.




Figure 11. A case, further down the page.




Figure 12. A case, further down the page.




Figure 13. A case, further down the page.




Figure 14. A case, further down the page.




Figure 15. A case, further down the page.

Approvals

Everything waiting on someone's yes, in your scope: containment the response policy held, HELIOS's final analyses to review, playbook runs that need approval, regulatory notices waiting on the client, and

rule changes to approve.




Figure 16. Approvals, as seen by a client admin (test environment).

How to use it

- Each item says what would happen, against what, why it was held, who proposed it, the client, the severity and how long it has waited. Approve or Reject right there.
- Nothing held runs while it waits. The client's approver chain is asked in turn (in the app, by Slack or Teams, email, SMS or WhatsApp); when the chain runs out, the action holds or becomes a suggestion, as the client's rulebook says.
- A two-person rule in the rulebook needs two different approvers; one approval leaves it waiting for the second.
- Rule changes to approve lists changes to the rules containment runs under; Review opens Rule changes.
- As a client admin you see only your organisation's items: containment on your estate, final analyses to acknowledge, notices to approve before filing, and rule changes to approve.




Figure 17. Approvals, further down the page.

Endpoints

The endpoint inventory and the whole attack surface: devices, servers, cloud, network, identity, IoT/OT

and applications, with how well each is protected.




Figure 18. Endpoints, as seen by a client admin (test environment).

How to use it

- The tiles count assets, the average protection score, devices missing essential controls, devices isolated now and devices not seen for seven days.
- Attack surface inventory groups every asset; Protection coverage by control shows the share of computers, servers and phones where each protection layer (EDR, antivirus, disk encryption, MFA…) is active, with the essential ones marked.




Figure 19. Endpoints, further down the page.

Service reports

How the service performed over a period: volume, response times, SLA compliance, AI performance and

analyst workload, each compared with the period before.




Figure 20. Service reports, as seen by a client admin (test environment).

How to use it

- Pick a period or a month. The figures include median time to acknowledge, contain and resolve, acknowledgement SLA compliance, the mix by severity, source, domain and client, top ATT&CK techniques and indicators, AI runs and analyst agreement, and containment outcomes.
- You see your own organisation's report, and can download it as a PDF.




Figure 21. Service reports, further down the page.

Compliance

Regulatory clocks and evidence: CERT-In's 6-hour incident reports, the DPDP breach notices, and the

ISO/IEC 27001 evidence map.




Figure 22. Compliance, as seen by a client admin (test environment).

How to use it

- Clocks running lists every notice not yet filed, nearest deadline first. CERT-In: incidents of the 20 listed types are reported within 6 hours of being noticed. DPDP: the Board and each affected person are told without delay, and the Board gets a detailed report within 72 hours.
- A notice goes to the client for approval before it is filed: approve it here or from Approvals. An edit after approval sends it back.
- The ISO 27001 view maps 15 Annex A controls to what HELIOS's records show over the period, and shows gaps (controls with nothing behind them) plainly.
- Switch the period (30 days, 90 days, 12 months) at the top.




Figure 23. Compliance, further down the page.




Figure 24. Compliance, further down the page.

Search logs

One search over every log HELIOS holds, from all of a client's security tools, the way analysts search Splunk, Chronicle, QRadar or Wazuh. The SOC searches across clients or one at a time; client users search their own organisation's logs only.




Figure 25. Search logs, as seen by a client admin (test environment).

How to use it

- Ask in plain words ("failed sign-ins for alice this week") and Write the search: the search assistant writes it on the model chosen for it, under the client's AI rules. It sees only your question and the field list, never the logs, and what it writes is checked like anything typed. Without a model a built-in translator does it.
- Or type the search: host:FIN-WS-04 type:LOGIN_FAIL -user:svc_*. Terms side by side all match, OR joins two, - or NOT excludes, * is a wildcard, port:>1024 compares, ip:a,b is any of a list, hash:* means it has a value, and a bare word or "phrase" searches everywhere in the event, raw fields included. The ? button lists the fields.
- Pick the time range (15 minutes to 90 days) and, for the SOC, the client or All clients, then Search.
- The histogram shows events over the window: click a bar to zoom into it. The side panel lists the top hosts, accounts, event types, IPs, ports, processes, log sources, products and client tools: click a value to keep only it, or - to exclude it.
- Events are listed newest first; click one for every field, the raw record the tool sent and its OCSF form, with + and - beside each value to filter. Load older fetches the next page.
- Save this search keeps it for later, private or shared with your side (your organisation's users, or the SOC). Export CSV downloads up to 10,000 matching events.
- Scripts and other tools can run the same searches through the REST API (GET /api/v1/events) with an API token.




Figure 26. Search logs, further down the page.




Figure 27. Search logs, further down the page.

Security testing

Tests of a client's own internet-facing assets, on request and under written authorisation from both the client and HELIOS: what an attacker on the internet sees (exposed services, TLS, web headers, email spoofing protection), with results from established scanners in the same report.




Figure 28. Security testing, as seen by a client admin (test environment).

How to use it

- Each test shows its status (waiting for authorisation, authorised, running, report ready, rejected or stopped), the window, who asked, and its open findings by severity. Open one for the detail.
- Request a test: the targets (domains, host names, public IP addresses or URLs; up to 25, no ranges, no private addresses), the checks, the window (up to 30 days) and the rules of engagement (who to call, what's out of bounds, times to avoid).

Attack Graph

Cases joined by the hosts, accounts, addresses, indicators and agents they share. An entity is an attack

chain when its cases together reach more ATT&CK tactics than any one alone.




Figure 29. Attack Graph, as seen by a client admin (test environment).

How to use it

- Hover or click a node to see the cases behind it; follow chains across tactics to see an intrusion that several smaller cases make up.




Figure 30. Attack Graph, further down the page.

Security tools

The security tools onboarded for each client: how their logs reach HELIOS and how HELIOS acts through

them.




Figure 31. Security tools, as seen by a client admin (test environment).

How to use it

- The tiles count tools onboarded, connected, degraded and waiting for their first event. Protection stack coverage shows which security layers have a tool across your clients; gaps are where an attack can go unseen.
- Each tool shows how it sends logs (push to its ingest URL, HELIOS pulling from the vendor's API, or the HELIOS forwarder), its source health, and whether a response connector can act through it.
- Onboard a tool for a client: pick it from the catalog, enter its read-only credentials (encrypted with the client's own key), test the connection, set the collectors running, and turn on the response connector (dry-run first). Generate the forwarder configuration for syslog, Windows event logs and files. Replay records waiting in the dead-letter queue.
- A source silent longer than its limit opens a case: attackers often stop logging first. A client can't go live while a source is dead.




Figure 32. Security tools, further down the page.




Figure 33. Security tools, further down the page.

Our rulebook

Each client's approved rules for what HELIOS may do on its estate. The rules only ever restrict: protected assets and accounts, which actions run automatically, need approval or never happen, blast-radius limits, business hours and change freezes, the approver chain, AI data handling and CERT-In contacts.




Figure 34. Our rulebook, as seen by a client admin (test environment).

How to use it

- The tabs: In force (the rules now applying), Edit, Dry run, Allowlist, Versions, AI models, Autonomy and Policy as code.
- Edit drafts a change, from an industry template or the version in force. Dry run replays the last 30 days of AI proposals under the draft and probes each action. Versions compares any two versions side by side.
- Send the draft for approval. It takes effect only once the client's admin and a HELIOS approver have both approved it, each after reviewing what changes and the dry run on the last 30 days; until then the version in force keeps deciding.
- Approve: client admins approve for their organisation; HELIOS's approvers (SOC managers and admins) approve for HELIOS, and can record a client's approval given elsewhere, naming it. Someone other than the person who asked approves for HELIOS.
- Allowlist: known-good hosts, IPs and accounts, each with an owner, a reason and an expiry. They open no cases, and AI containment against them is only suggested. A new entry applies once the client and HELIOS have approved it.
- Policy as code: export or import the rulebook as YAML, or keep it in Git (GitHub, GitLab or an https URL): a changed file becomes a draft that still needs both approvals here.
- AI models: which models may read the client's evidence (any, region-locked or on-premises only), the client's own providers (bring your own key), a provider per agent, and the monthly AI budget.

- Autonomy: the AI's autonomy ladder per action type for this client. New clients contain on their own from day one (initial containment); a promotion beyond that takes effect once the client and HELIOS approve it.




Figure 35. Our rulebook, further down the page.




Figure 36. Our rulebook, further down the page.

Rule changes

Changes to the rules containment runs under, waiting for approval: new rulebook versions, allowlist entries, more AI autonomy or consent, and platform AI settings. Nothing here is in effect yet: the rules in force keep deciding until every approval a change needs is in.




Figure 37. Rule changes, as seen by a client admin (test environment).

How to use it

- Each change says what it is, the client, who asked and why, and which approvals it still needs: the client's and HELIOS's, or for a platform change, a second HELIOS approver.
- Impact shows exactly what changes (each rule, before and after) and, for a rulebook, the dry run: how the last 30 days of AI containment proposals would have gone under the new version.
- Approve or Reject for your side. Someone other than the person who asked approves for HELIOS. If the rules in force change while it waits, the change goes stale and must be asked again.
- Lowering the AI's autonomy or consent, and the kill switch, apply at once without waiting here.
- Decided lists past changes and who approved or rejected them.




Figure 38. Rule changes, further down the page.

API Tokens

Personal tokens for the REST API, for ticketing systems, SOAR and client portals. A token acts as you:

same role, client and queues.




Figure 39. API Tokens, as seen by a client admin (test environment).

How to use it

- New token: give it a name (what will use it), an expiry (90 days by default), and switch on Read & write only if it must change things. Create token shows it once; copy it then. Your tokens lists yours to revoke.
- The page includes the API reference: endpoints, parameters and examples. Calls are limited to 300 a minute per token, and every change through the API is audited.




Figure 40. API Tokens, further down the page.

Contracts & invoices

Pilots with measured success criteria, contracts and GST invoices.




Figure 41. Contracts & invoices, as seen by a client admin (test environment).

How to use it

- You see your organisation's contracts and issued invoices, and download their PDFs.
- As client admin, sign a contract sent to you here.

A security test

One security test: its scope and the proof of control, both authorisations, the findings and how to fix them, the scanner reports added, and what HELIOS probed.




Figure 42. A security test, as seen by a client admin (test environment).

How to use it

- Scope: the client proves it controls each name with a DNS TXT record (shown on the page) on the name or on _helios-verify.<name>. A host under a verified name, and an address a verified name resolves to, count as verified. Check DNS now re-checks.
- Authorisation: the client's admin authorises, confirming they may permit testing of exactly these assets in this window; a HELIOS approver (SOC manager or admin) who didn't ask for it authorises for HELIOS. Then HELIOS runs it on its own when the window opens, checking the DNS proof again first.
- HELIOS looks and doesn't exploit anything: a TCP connect to well-known ports and the banner a service volunteers, the TLS certificate and protocol, the HTTPS redirect and security headers, SPF and DMARC. Every probe is listed at the bottom.
- Findings are listed worst first, with the evidence and how to fix each. Mark one fixed, or accepted as a risk with the reason (client admins and SOC managers). Run again now re-tests inside the window: what it no longer finds is marked fixed.
- Scanner results: add a report from Tenable Nessus, Greenbone/OpenVAS, OWASP ZAP or Nuclei run under the same authorisation; findings on hosts outside the verified scope are left out.

- Reject (before it runs) or Stop the test (at any point): either side can. Report PDF downloads the report for the client and its auditors.




Figure 43. A security test, further down the page.




Figure 44. A security test, further down the page.




Figure 45. A security test, further down the page.

My alerts

Which notifications also reach you outside HELIOS, by email, SMS or WhatsApp.




Figure 46. My alerts, as seen by a client admin (test environment).

How to use it

- Every notification lands in the app (the bell at the top). Here choose, per kind of notification, the channels it also comes by, and give your phone number in international format (+91…).
- Deliveries that couldn't go (a channel not set up, no number, over the hourly cap) are listed with the reason.




Figure 47. My alerts, further down the page.

5. Procedures

Step by step, for the tasks your role does most.

5.1 Approve or reject containment

1. Open Approvals (or the incident). Each item says what would happen (isolate a device, disable an account, block an address…), why, and who proposed it.
2. Approve if it is right for your business, or Reject with a reason. Nothing held runs while it waits.
3. Approvals also reach you by email, SMS or WhatsApp if you chose that under My alerts.

5.2 Approve a change to your rulebook

1. Open Rule changes (or Approvals). Each change shows exactly what changes against the version in force, and the dry run: how the last 30 days of AI containment would have gone under it.
2. Check the protected assets (never isolate, crown jewels), protected accounts (VIP, break-glass, service), which actions may run automatically and from what severity, business hours and change freezes, and your approver chain.
3. Approve for your organisation, or Reject with a reason. The change takes effect only once HELIOS has approved it too; until then the version in force keeps deciding.

5.3 Read and acknowledge HELIOS's final analysis

1. When HELIOS has contained and investigated an incident, you're notified and it appears under Approvals → Final analyses to acknowledge.
2. Open the incident: the verdict, what happened, what's contained, the logs HELIOS collected from your tools (and the kinds it couldn't see), and the remediation plan.
3. Approve lifting containment when its conditions hold (for a laptop: a clean scan, persistence removed, passwords reset), and the remediation steps you agree with.
4. Press Acknowledge so the SOC knows you've read it; ask questions in the incident's discussion.

5.4 Search your logs

1. Open Search logs. Type a search (user:alice type:LOGIN_FAIL) or ask in plain words and press Write the search.
2. Pick the time range; click the histogram or the values on the left to narrow it; open an event for every field.
3. Save searches you'll reuse (Share with my organisation's users if colleagues need them) or export the events as CSV.

5.5 Authorise a security test

1. On Security testing, request a test (or open the one the SOC asked for): your internet-facing names, public IPs or URLs, the checks, the window and the rules of engagement.
2. Add the DNS TXT record the test shows to your domain, then press Check DNS now until every target is verified.
3. Authorise it, confirming you may permit testing of exactly these assets in this window. It runs once HELIOS has authorised too; Stop the test at any time.
4. Read the findings and the PDF report; mark them fixed (a re-test confirms it) or accept a risk with your reason.

5.6 Approve a regulatory notice

1. When a CERT-In report or DPDP notice is ready, it appears in Approvals and on Compliance.
2. Read the draft. Approve it, or ask the SOC for changes. An edit after approval comes back to you.

5.7 Decide which AI may read your data

1. In Our rulebook → AI, set residency (any provider, region-locked, or on-premises only) and whether personal data is masked before a cloud model sees it.
2. Optionally add your own provider (your Anthropic, Amazon Bedrock or Azure OpenAI account, or an on-premises AI box), pick a provider per agent, and set a monthly AI budget.
3. A model you pick acts on its own only once it has passed HELIOS's evaluation; until then it only suggests.

5.8 Approve a promotion of the AI's autonomy

1. Autonomy is earned per action type: a promotion needs at least 20 decisions in 30 days, 90% agreement with the SOC's analysts, no more than 2% wrong containment, and none on a critical asset.
2. When one is proposed, open Our rulebook → the autonomy ladder; read the record behind it and discuss it with the SOC.
3. Approve or decline it under Rule changes; it takes effect once HELIOS approves too. Your plan, your consent and your rulebook still cap every level.

6. Guidelines

Do

- Keep your never-isolate list and protected accounts current; they bind the SOC's people as well as the AI.
- Name approvers who can be reached at night, and keep their contact details current.
- Set up My alerts so approvals reach you quickly.

Don't

- Don't share your account; invite colleagues as client stakeholders instead.
- Don't approve containment you don't understand: ask the SOC in the incident's discussion first.

For everyone

- Never share your account or password; every action is recorded under your name.
- Keep client information inside HELIOS and to the people who need it.
- Treat text inside evidence (command lines, emails, file names) as possibly written by an attacker: it may address 'the AI' or 'the analyst' to mislead. HELIOS flags such text; don't follow it.
- Every action in HELIOS is reversible or recorded, and audited; write down why you did it.

> The client's approved rulebook binds everyone: the AI, playbooks and people. If HELIOS refuses an action, the reason names the rule. Don't work around it in a vendor's console; ask the client to change the rule.

7. Reference

Terms you will see

Case statuses

Open	New; nobody has acknowledged it yet.
Triaging	Someone is looking at it.
Investigating	Under analysis.
Awaiting approval	Containment is waiting on someone's yes.
Contained	The threat is stopped; clean-up may continue.
Resolved	Closed with a disposition.
False positive	Closed: it wasn't a threat.

Severities

Critical, High, Medium, Low, Info	Set by the detections and adjustable by analysts. The client's plan sets the acknowledgement SLA for each.

Dispositions (when closing)

True positive	A real threat.
Benign true positive	Real activity, but expected or authorised (an admin's tool, a pen test).
False positive	Not what the detection thought.

Tiers

T1	Triage.
T2	Analysis.
T3	Incident response.

Response action statuses

Suggested	A recommendation only; autonomy doesn't allow acting.
Pending approval	Waiting on an approver.
In progress	The vendor was asked; waiting for it to confirm. Doesn't count as containment yet.
Executed	Done and confirmed by the vendor (or by an analyst for a manual action).
Manual required	Approved, but no connector can do it: someone does it in the tool's console and records it.
Blocked	A guardrail or the client's rulebook refused it; the reason is shown.
Rejected	An approver said no.
Rolled back	Undone.

Failed	The vendor or HELIOS couldn't do it.
Shadow	Shadow mode: what the AI would have done, recorded silently and shown once the case closes.

AI autonomy (per agent)

Off	The agent doesn't run.
Suggest only	It proposes; people decide.
Contain with approval	Its containment waits for approval.
Auto-contain	It may act on pre-approved actions above its confidence bar.

Autonomy ladder (per client and action type)

L0 observe	Shadow mode, if the client chose to start there.
L1 suggest	Suggestions only.
L2 approve	Acts once approved.
L3 act and notify	Acts, and tells people at once. New clients start here for initial containment (isolate a host, block an IP, quarantine a file, block a sender, collect logs) and at L2 for everything else.
L4 act	Acts, and reports in the daily digest.

Final analysis

Ready for review	HELIOS has written it; the SOC reviews it and the client acknowledges it.
Reviewed	A person in the SOC has read and accepted it, with an optional note.
Lift proposal	A release of containment HELIOS proposes with its conditions; it runs only once someone approves it.

Rule changes

Waiting for approval	Not in effect; the rules in force keep deciding.
Approved	Every approval it needed is in, and it took effect.
Rejected or withdrawn	Turned down by an approver, or withdrawn by the person who asked.
Stale	The rules in force changed while it waited; ask again.

Security tests

Waiting for authorisation	Asked for; needs every target verified and both authorisations.
Authorised	Runs on its own when the window opens.
Running	HELIOS is probing now.
Report ready	Finished; can run again inside the window.
Rejected or stopped	Turned down before it ran, or stopped by either side.

Evidence references

D, E, I, T, C	Detections, events, indicators, timeline entries and context in the case; Q for what the investigation agent's tools returned. Every AI finding cites them.

If something doesn't work

- **A page says you don't have access**: your role doesn't include it. Ask your administrator if your job needs it.
- **An action was refused**: the message names the rule (the client's rulebook, a guardrail, the plan or the kill switch).
- **An action is 'Manual required'**: no connector can do it. Do it in the tool's own console, then record what you did on the case.
- **You don't get alerts by SMS or email**: check My alerts for your channel choices, your phone number, and deliveries skipped with their reason.
- **You can't sign in**: after five failures the account locks for 15 minutes; your administrator can reset your password or two-step sign-in.