



Stemmarest

Dokumentation des PSE2 Projekt

Jakob Schaerer, Severin Zumbrunn, Ido Gershoni, Joel Niklaus, Ramona Imhof



Copyright © 2015 Team PSE2

PUBLISHED BY ...

....ORG

Licensed under the Creative Commons Attribution-NonCommercial 3.0 Unported License (the “License”). You may not use this file except in compliance with the License. You may obtain a copy of the License at <http://creativecommons.org/licenses/by-nc/3.0>. Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an “AS IS” BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

First printing, March 2013



Contents


I	Project	
1	Introduction	6
2	Database (neo4j)	7
2.1	Structure	7
3	Jersey	9
4	Performance	10
II	Testing	
5	Concept	12
6	Configure the Test-Database	14
7	Unit Test	15
8	Integration Tests	16
9	Benchmark Testing	18

10	Documentation	22
10.1	/user	22
10.2	/user/create	22
10.3	/user/{id}	22
10.4	/user/traditions/{userId}	23
10.5	/textinfo/{textId}	23
10.6	/tradition/witness/{tradId}	24
10.7	/tradition/relation/{tradId}/relationships	24
10.8	/tradition/new	24
10.9	/tradition/get/{tradId}	25
10.10	/tradition/reading/{tradId}/{readId}	25
10.11	/tradition/duplicate/{tradId}	26
11	Services	27
11.1	Baseresource:	27
11.2	/user	27
11.3	/relation	28
11.4	/witness	28
11.5	/tradition	30
11.6	/myresource	32
12	Models	33
12.1	userModel	33
12.2	relationshipModel	33
12.3	duplicateModel	34
12.4	textInfoModel	34
	Bibliography	35
	Books	35
	Articles	35




Project

1	Introduction	6
2	Database (neo4j)	7
2.1	Structure	
3	Jersey	9
4	Performance	10





Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.




2. Database (neo4j)


2.1 Structure









Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.



The performance is tested by benchmark tests. Please consult the chapter Benchmark Tests in the part Testing of this documentation for further technical information.


Figure 4.1: An example to show what will come here.





Testing

5	Concept	12
6	Configure the Test-Database	14
7	Unit Test	15
8	Integration Tests	16
9	Benchmark Testing	18



This chapter describes the test-concept of the Digital Humanities PSE2 Project. The testing is used to assure the quality of the project and for test driven development. All tests are written in a manner they don't have any impact on the architecture of the project.


Integration Tests

Every user story is tested by an integration Test. The integration tests assures the quality of the project. The technique of integration tests is described in the Integration test chapter.


Unit Tests

Unit tests are used for test driven development and are defined by the developer. They are only for the development process and are not referenced in quality audits.

Jersey Overview



In the productive system for every REST call jersey is instantiating the requested resource and providing the service. Each resource object has its own database service, which is closed after each call. In production a embedded neo4j GraphDatabase is used. To achieve a minimal invasive test system the productive database needs to be replaced with a test database. To change the database with minimal test related code in the project, the GraphDatabaseServiceProvider can be configured to return an impermanent Database.



In this Project the `GraphDatabaseService` is a Singleton Object provided by the `GraphDatabaseServiceProvider`. To use a Testdatabase in the Tests the following steps have to be done. A Claswide `GraphDatabaseService` object `db` has to be registered.

```
GraphDatabaseService db;
```

In the `@Before` method the singleton `GraphDatabaseService` provided by the `GraphDatabaseServiceProvider` has to be overwritten by the following line:

```
GraphDatabaseServiceProvider.setImpermanentDatabase();
```



Later the `db` object can be initialized by:

```
db = new GraphDatabaseServiceProvider().getDatabase();
```

In the `@After` method the database has to be closed

```
db.shutdown();
```

With this configuration the impermanent Testdatabase of Neo4j is used during the tests.




For Unit Tests the methods of the resource are called directly.


```
@Test
public void SimpleTest(){
    String actualResponse = userResource.getIt();
    assertEquals(actualResponse, "User!");
}
```

Example

https://github.com/tohotforice/PSE2_DH/blob/e364fcb0c164981281c5799a6bf9f9f9ea5eb503/stemmarest/src/test/java/net/stemmaweb/stemmaserver/UserUnitTest.java



8. Integration Tests



To inject objects into a resource it is mandatory that the resource is created statically at the place the injection is done. This is not possible when the resources are instantiated when a REST call occurs. To solve this JerseyTestServerFactory creates a server where already instantiated resources can be registered. To start a JerseyTestServer a global JerseyTest has to be created.

```
private JerseyTest jerseyTest;
```

The JerseyTestServerFactory creates a JerseyTest with already instantiated resources. This is necessary to inject the mock objects. Multiple resources can be added by chaining .addResource(..).addResource()

```
jerseyTest = JerseyTestServerFactory.newJerseyTestServer()  
    .addResource(userResource).create();  
jerseyTest.setUp();
```

The test is done by calling a webresource of jerseyTest

```
@Test
```




```
public void SimpleTest(){
    String actualResponse = jerseyTest.resource()
        .path("/user").get(String.class);
    assertEquals(actualResponse, "User!");
}
```

Example

https://github.com/tohotforice/PSE2_DH/blob/e364fcb0c164981281c5799a6bf9f9f9ea5eb503/stemmarest/src/test/java/net/stemmaweb/stemmaserver/UserTest.java

DRAFT



9. Benchmark Testing

A main goal of the PSE2 stemmarest project is a good performance compared to the previous RESTful service. To measure the performance benchmark testing is needed. A benchmark test basically calls the RESTful service multiple times and measure the response time. To achieve this *com.carrotsearch.junitbenchmarks* a handy JUnit benchmark test suite is used. This JUnitbenchmarks measure the time which is used to execute a test and can generate visual representations of the measurement.


For the benchmark testing it is of interest to have a variety of different databases. Those databases should differ in their size from small to very huge. This allows to measure the algorithms in extreme situations. To generate valid graphs only limited by disk space the class *RandomGraphGenerator* can be used. By calling the static method *role* a graph is generated according to the parameters.

R Please note that the response time highly depends on the hardware the tests are running on and the actual state of Java's virtual machine.

To reduce the influence of the virtual machine before the measurements 5 warm-up calls are done to bring the virtual machine to live. The hardware which was used for testing is represented in the report.

Setup

All the classes related to the Benchmark Tests can be found in the package *net.stemmaweb.stemmaserver.benchmarktests*. The class *BenchmarkTests* contains all Tests. The classes *Benchmark<n>Nodes* contain the database generation. Here is configured how many nodes the database has. These are also the classes which are run with JUnit test. *BenchmarkTests* can't be run as a JUnit test as it is an abstract class. s




Tests are simply implemented in the `BenchmarkTests` class with the `@Test` annotation. It is best practice only to implement the restcall in this method and only test if `Response.Status` is OK. This assures that as less as possible overhead time is measured. And the integration- and JUnit tests should be done on a other place.

R JUnitBenchmarks measures the time to execute (`@Before`, `@Test`, `@After`). Heavy operations which should not be measured can be done in `@BeforeClass` and `@AfterClass`.

To create a new database test-environment copy the class `Benchmark600Nodes` and rename it to the count of Nodes that should be inserted. In the class itself only two small adjustments need to be done. First change the name of the report file `@BenchmarkMethodChart(filePrefix = "benchmark/benchmark-600Nodes")`. Second adjust the properties of the database which should be generated `rgg.role(db, 2, 1, 3, 100);. role(databaseService, cardinalityOfUsers, cardinalityOfTraditionsPerUser, cardinalityOfWitnessesPerTradition, degreeOfTheTraditionGraphs)`

Run Benchmarktests

The Benchmarktests can be run as every JUnit test. But to generate the report an argument needs to be passed by. Create a JUnit Test as follows:



On the tab Arguments `-Djub.consumers=CONSOLE,H2 -Djub.db.file=.benchmarks` has to be inserted into the VM Arguments input. After the test can be run as usual. After the test execution the reports are stored under *benchmark/*.

- R The execution of the tests will take some time because of the generation of huge graphs. Its recommended not to use the computer during this tests.

RESTful API

10 Documentation 22

- 10.1 /user
- 10.2 /user/create
- 10.3 /user/{id}
- 10.4 /user/traditions/{userId}
- 10.5 /textinfo/{textId}
- 10.6 /tradition/witness/{tradId}
- 10.7 /tradition/relation/{tradId}/relationships
- 10.8 /tradition/new
- 10.9 /tradition/get/{tradId}
- 10.10 /tradition/reading/{tradId}/{readId}
- 10.11 /tradition/duplicate/{tradId}

11 Services 27


- 11.1 Baseresource:
- 11.2 /user
- 11.3 /relation
- 11.4 /witness
- 11.5 /tradition
- 11.6 /myresource

12 Models 33

- 12.1 userModel
- 12.2 relationshipModel
- 12.3 duplicateModel
- 12.4 textInfoModel

Bibliography 35

- Books
- Articles



10. Documentation

10.1 /user

GET /user

Summary

Returns a welcome message

Parameter

Return — SUCCESS. text/plain

"User!"

10.2 /user/create

POST /user/create

Summary

Creates a user.

Parameter application/json

{ "userId":<userId>, "isPublic":<isAdmin> }

Return — CREATED. application/json

{ "userId":<userId>, "isPublic":<isAdmin> }

Return — CONFLICT. application/json

Error: A user with this id already exists

10.3 /user/{id}

GET /user/{id}

Summary

Returns the user as JSON Object

Parameter URL

Id: the user id

Return — OK. application/json

```
{ 'userId': <userId>, 'isAdmin': <isAdmin> }
```

The information about the user

Return — NOT_FOUND. application/json

The information about the user

10.4 /user/traditions/{userId}

GET /user/traditions/{userId}

Summary

List all Traditions of a user

Parameter URL

userId: the id of the user

Return — OK. application/json

```
{ "traditions": [ { "name": <traditionName> } ] }
```

Return — NOT_FOUND. application/json

Error: A user with this id does not exist!

10.5 /textinfo/{textId}

POST /textinfo/{textId}

Summary

Update the textInfo of a tradition.

Parameter URL

textId: the id of the tradition

Parameter application/json

```
{ 'name': <new_name>, 'language': <new_language>, 'isPublic': <is_public>, 'ownerId':  
<new_ownerId> }
```

Return — SUCCESS. application/json

```
{ 'name': <new_name>, 'language': <new_language>, 'isPublic': <is_public>, 'ownerId':  
<new_ownerId> }
```

The new information of the tradition.

Return — **CONFLICT**. **application/json**
"Error: A user with this id does not exist"
If the user does not exist.

Return — **NOT_FOUND**. **application/json**
If the tradition was not found.

10.6 /tradition/witness/{tradId}

GET /tradition/witness/{tradId}

Summary

List all Witness of a tradition

Parameter URL
tradId: the id of the tradition

Return — **OK**. **application/json**

Return — **NOT_FOUND**. **application/json**
Error: A tradition with this id does not exist!

10.7 /tradition/relation/{tradId}/relationships

GET /tradition/relation/{tradId}/relationships

Summary

List all Relationships of a tradition

Parameter URL
tradId: the id of the tradition

Return — **OK**. **application/json**

10.8 /tradition/new

POST /tradition/new

Summary

Create a new tradition.

Parameter text/plain
name: The name of the tradition

Parameter multipart/form-data
language: The language of the tradition
public: 0 if the tradition is not public 1 if the tradition is public
name: The name of the tradition

file: multipart file input stream

Return — CONFLICT. application/json

"Error: No user with this id exists"

Return — INTERNAL_SERVER_ERROR. application/json

"Error: Tradition could not be imported!" *If the server was not able to parse the input file*

Return — OK. application/json

"Tradition imported successfully"

10.9 /tradition/get/{tradId}

GET /tradition/get/{tradId}

Summary

Get a graphml of a tradition

Parameter URL

tradId: the id of the tradition

Return — OK. application/xml

Return — NOT_FOUND. application/json

Error: A tradition with this id does not exist!

10.10 /tradition/reading/{tradId}/{readId}

GET /tradition/reading/{tradId}/{readId}

Summary

Get a specific reading of a tradition

Parameter URL

tradId: the id of the tradition

Parameter URL

readId: the id of the reading

Return — OK. application/json The reading in json

Return — NOT_FOUND. application/json

Error: A tradition with this id does not exist!

Return — NOT_FOUND. application/json

Error: A reading with this id does not exist!

10.11 /tradition/duplicate/{tradId}

POST /tradition/duplicate/{tradId}

Summary

Duplicates readings in a tradition. Is the opposite method of merge.

Parameter URL

tradId: the id of the tradition

Parameter application/json

```
{ 'readings': [readId1, readId2], 'witnesses': ["wit1", "wit2"] }
```

Return — OK. application/json


Successfully duplicated readings

Return — NOT_FOUND. application/json

If the tradition was not found.

Return — NOT_FOUND. application/json

If one of the readings was not found.



11. Services

11.1 Baseresource:

<http://localhost:8080/>

11.2 /user

Method Name: getIt

GET /

Response as text/plain

Method Name: create

POST /create

Request userModel as application/json

Response as application/json

Method Name: getUserById

GET /{userId}

Response as application/json

Method Name: deleteUserById

DELETE /{userId}

Response as text/plain

Parameter userId as string

Method Name: getTraditionsByUserId

GET /traditions/{userId}

Response as application/json

Parameter userId as string

11.3 /relation

Method Name: getIt

GET /

Response as text/plain

Method Name: delete

POST /{textId}/relationships/delete

Request relationshipModel as application/json

Response as text/plain

Parameter textId as string

Method Name: create

POST /{textId}/relationships

Request relationshipModel as application/json

Response as application/json

Parameter textId as string

Method Name: deleteById

DELETE /{textId}/relationships/{relationshipId}

Response as text/plain

Parameter textId as string

Parameter relationshipId as string

11.4 /witness

Method Name: getWitnssAsPlainText

GET /string/rank/{tradId}/{textId}/{startRank}/{endRank}

Response as application/json

Parameter textId as string

Parameter endRank as string

Parameter tradId as string

Parameter startRank as string

Method Name: getWitnessAsPlainText

GET /string/{tradId}/{textId}

Response as application/json

Parameter textId as string

Parameter tradId as string

Method Name: getWitnessAsReadings

GET /list/{tradId}/{textId}

Response as application/json

Parameter textId as string

Parameter tradId as string

Method Name: getNextReadingInWitness

GET /reading/next/{tradId}/{textId}/{readId}

Response as application/json

Parameter textId as string

Parameter readId as long

Parameter tradId as string

Method Name: getPreviousReadingInWitness

GET /reading/previous/{tradId}/{textId}/{readId}

Response as application/json

Parameter textId as string

Parameter readId as long

Parameter tradId as string

11.5 /tradition

Method Name: getAllRelationships

GET /relation/{tradId}/relationships

Response as application/json

Parameter tradId as string

Method Name: deleteUserById

DELETE /{tradId}

Response as text/plain

Parameter tradId as string

Method Name: changeOwnerOfATradition

POST /{textId}

Request textInfoModel as application/json

Response as application/json

Parameter textId as string

Method Name: getReading

GET /reading/{tradId}/{readId}

Response as application/json

Parameter readId as long

Parameter tradId as string

Method Name: getAllTraditions

GET /all

Response as application/json

Method Name: duplicateReading

POST /duplicate/{tradId}

Request duplicateModel as application/json

Response as application/json

Parameter tradId as string

Method Name: mergeReadings

POST /merge/{tradId}/{firstReadId}/{secondReadId}

Response as application/json

Parameter secondReadId as long

Parameter tradId as string

Parameter firstReadId as long

Method Name: splitReading

POST /split/{tradId}/{readId}

Response as application/json

Parameter readId as long

Parameter tradId as string

Method Name: getAllWitnesses

GET /witness/{tradId}

Response as application/json

Parameter tradId as string

Method Name: getTradition

GET /get/{tradId}

Response as application/json

Parameter tradId as string

Method Name: importGraphMl

POST /new

Request as multipart/form-data

Response as application/json

Method Name: getAllReadingsOfTradition

GET /readings/{tradId}

Response as application/json

■ **Parameter** tradId as string

Method Name: getDot

GET /getdot/{tradId}

■ **Response** as application/json


■ **Parameter** tradId as string

11.6 /myresource

Method Name: getIt

GET /

■ **Response** as text/plain



12. Models

12.1 userModel

- Property id as string
- Property isAdmin as string

12.2 relationshipModel

- Property de0 as string
- Property de1 as string
- Property de10 as string
- Property de11 as string
- Property de12 as string
- Property de2 as string
- Property de3 as string
- Property de4 as string
- Property de5 as string
- Property de6 as string
- Property de7 as string
- Property de8 as string


- **Property** de9 as string
- **Property** id as string
- **Property** source as string
- **Property** target as string

12.3 duplicateModel

- **Property** readings as long
- **Property** witnesses as string

12.4 textInfoModel

- **Property** isPublic as string
- **Property** language as string
- **Property** name as string
- **Property** ownerId as string



Bibliography

Books
Articles

DRAFT