

AttentiveCLS Pooler

Team 1: Seungil Lee, Jongchan Park, Eugene Seo, and Dohyung Kim

November 5, 2021

1 Introduction

BERT [1] has become a standard architecture for NLP research ever since it was published. BERT computes the representation for every token, but it uses the output representation of the special token [CLS], for sentence-level tasks (e.g., sentiment analysis). However, various strategies were introduced to get sentence-level representation.

We have designed new pooler named **AttentiveCLS** pooler and evaluated its performance on CoLa, MNLI, RTE and SST-2 tasks, which are the representatives of sentence-level tasks. The results were compared with **MeanMaxTokens** pooler, which is suggested in the homework description, also with the original **BERTPooler** in **huggingface** library (<https://huggingface.co/>).

2 AttentiveCLS Pooler

Though original BERT pooler simply adopts last output of [CLS] token, we tried to exploit information from other tokens as well. Nowadays, attention mechanism is widely used to get the importance of the given sequence, so we added a attention pooling layer on the top of the tokens other than [CLS] token. Then, the output of this attention layer is concatenated with the last output of [CLS] token. We also apply linear transformation with $W \in \mathbb{R}^{H \times 2H}$ and tanh activation just like as the **BERTPooler** in **huggingface** implementation.

The tasks in this homework are as follows:

1. Implement the **MeanMaxTokens** pooler (See **MeanMaxTokensBertPooler** class in **bert_poolers.py**).
2. Implement your own BERT pooler (See **MyBertPooler** class) and describe its architecture and rationale in your report. It does not have to be completely novel.
3. Choose one dataset in GLUE [2], and compare the test performance of three poolers (See **run_glue.py**).
4. Discuss the result. Negative results are fine, the point is how you interpret and explain it.

3 Experiment

The files you should submit are

1. Your team's **bert_poolers_{team_no}.py** (e.g., **bert_poolers_0.py**).
2. Your team's two-page **report_{team_no}.pdf** (e.g., **report_0.pdf**). Use this L^AT_EX file as a template, and do not change style attributes in this file. References are not included in the page-limit.

4 Experiment

Comprehensive evaluation based on clarity, validity, and interestingness. You will get zero points if you violate academic integrity (e.g., plagiarism and data manipulation).

5 Result

References

- [1] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics.
- [2] Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *International Conference on Learning Representations*, 2019.