摘要

StarryOS 作为基于 Rust 的宏内核操作系统，已在前序工作中引入了可加载内核模块（LKM）基础设施，但彼时仅支持显式手动加载。本文在此基础之上，设计并实现了 `ondemand-kmod`——一个通用的 `#![no_std]` 按需加载内核模块框架，支持懒加载（lazy loading）与空闲超时自动卸载（idle unloading）。该框架将"何时加载"的策略与"怎么加载"的机制彻底解耦，形成一个可复用的独立库。

随后，该框架深度集成进 StarryOS，先后实现了 procfs 与 FUSE 两个真实模块的按需加载。在 FUSE 方向，本文从零手写了内核侧驱动 `Starryfuse`，包含完整的 FUSE 协议解析、字符设备通信、VFS 桥接与异步 I/O 支持；将其包装为 `fuse.ko` 可加载模块，并开发了三组用户态测试程序，在 QEMU/RISC-V 环境下验证了从首次 `open("/dev/fuse")` 触发加载到空闲卸载、内存回收的完整生命周期。

关键词：StarryOS；按需加载内核模块；FUSE；用户态文件系统；Rust；RISC-V

---

1. 引言

1.1 背景

StarryOS 是一个基于 Rust 的宏内核操作系统，底层依托 ArceOS 的模块化架构。之前有同学为 StarryOS 引入了完整的 LKM 机制：内核能够在运行期动态加载 ELF 格式的 `.ko` 文件，完成重定位、符号解析并执行模块的 `init`/`exit` 函数。

然而，当时的 LKM 仅支持显式手动加载（`insmod` 语义）。对于 `procfs`、`FUSE` 这类并非始终活跃的子系统，如果将其静态编译进内核，会造成启动时内存与体积的浪费；如果完全手动管理，又增加了系统管理员的负担。因此，有必要在 LKM 基础之上构建一套按需加载框架，使内核模块能够在首次被访问时自动装载，在空闲超时时自动卸载并回收资源。

1.2 设计目标

围绕上述背景，本文工作围绕以下核心目标展开：

1. **按需加载**：当用户态首次访问某功能（如打开 `/dev/fuse` 或 `/proc/meminfo`）且 VFS 返回 `NotFound` 时，系统自动加载对应模块并重试。
2. **自动卸载**：模块在空闲（无引用、无打开文件描述符）超过设定时间后，自动卸载并释放物理内存。
3. **策略与机制解耦**：将"何时加载"的策略与"怎么加载"的机制分离，形成可复用的独立框架。
4. **FUSE 完整闭环**：实现内核侧 FUSE 驱动，支持标准 Linux FUSE ABI，使用户态守护进程能在 StarryOS 中挂载并操作虚拟文件系统。

1.3 报告结构

本文剩余章节安排如下：第 2 节介绍相关工作与背景；第 3 节阐述 `ondemand-kmod` 框架与 FUSE 按需加载的系统架构；第 4 节详细描述实现细节；第 5 节介绍测试验证方案与结果；第 6 节总结全文并展望未来工作。

---

2. 相关工作与背景

2.1 StarryOS 的 LKM 基础设施

前序工作为 StarryOS 引入了完整的 LKM 支持，包含 ELF 解析器、符号重定位器（`ksym`）以及模块加载器（`kmod-loader`）。内核能够在运行期读取 `.ko` 文件，将其映射到独立的虚拟地址空间，解析未定义符号并回填地址，最终调用模块入口函数。这一基础设施为按需加载提供了"怎么加载"的底层能力，但缺乏"何时加载"的自动化策略层。

2.2 已有按需加载实践

AlloyStack:面向Serverless按需加载的库操作系统。该项目作为libos实现了模块按需自动加载，服务于云函数运行。

本项目开发初期，对于StarryOS 的 `procfs` 文件系统也尝试过"懒挂载"（lazy mount）——在启动时注册挂载点工厂函数，首次访问时才真正挂载文件系统。后期因FUSE测试需要，将`procfs`重归静态加载。

2.3 StarryOS 面临的独特挑战

与 Linux 相比，StarryOS 的按需加载面临若干独特挑战：

- **Rust `#![no_std]` 环境**：无法使用 `std::sync::Mutex`、`std::thread` 等标准库设施，所有并发控制必须基于自旋锁和内核原语。
- **跨模块符号解析**：模块与主内核之间的符号绑定通过 `KALLSYMS` 字典完成，需要处理 Rust Nightly 裁剪导致的符号缺失问题。
- **RISC-V QEMU 调试环境**：物理内存有限，模块加载/卸载的内存行为必须可观测、可量化。
- **VFS 上下文安全**：动态加载的文件系统模块不能在中断上下文或持有全局锁时执行可能阻塞的操作。

---

3. 系统架构与设计

3.1 整体架构

StarryOS 的按需加载系统由两大部分组成：

1. **`ondemand-kmod`**：独立的 `#![no_std]` Rust 库，提供通用的模块生命周期管理。
2. **`api/src/kmod/ondemand.rs`**：StarryOS 内核集成层，桥接框架与现有 LKM 基础设施。
3. **`api/src/kmod/ondemand_builtin.rs`**: 负责具体模块注册加载卸载触发逻辑。

当用户态程序访问某个路径（如 `/dev/fuse`）时，VFS 层通过 `with_ondemand()` 钩子捕获 `NotFound` 错误，触发 `ondemand-kmod` 加载对应的 `.ko` 文件；模块初始化完成后，VFS 操作自动重试。空闲时，后台监控任务通过三阶段卸载算法安全回收模块内存。

图 1 展示了按需加载系统的整体架构。图中上侧为用户态进程，下侧为内核态组件。用户态的首次访问沿 VFS 路径向下传播，若目标不存在则进入 `with_ondemand` 重试路径；框架层的 `registry` 与 `lifecycle` 负责状态转换；底层通过 `kmod-loader` 实际完成 ELF 加载。




VFS syscall
Kernel
VFS lookup
NotFound
with_ondemand hook
ondemand-kmod framework
registry.rs
lifecycle.rs
monitor.rs
kmod-loader
ELF parse & symbol bind
module init



3.2 模块生命周期状态机

`ondemand-kmod` 使用六状态有限状态机（FSM）描述模块的生命周期：

- **`Unloaded`**：初始状态，模块尚未加载。
- **`Loading`**：正在执行 ELF 加载与符号解析。
- **`Loaded`**：模块已成功初始化，可供使用。
- **`Active`**：模块正被使用（存在打开的文件描述符或挂载点引用）。
- **`Idle`**：模块已加载但当前无活跃引用。
- **`Unloading`**：正在执行模块退出函数并回收内存。

状态转换遵循以下规则：

- `Unloaded --(触发器/首次访问)--> Loading`
- `Loading --(成功)--> Loaded --> Active`
- `Active --(最后一个引用释放)--> Idle`
- `Idle --(超时 / 空闲时间达到阈值)--> Unloading`
- `Idle --(新的访问请求)--> Active`
- `Unloading --(完成)--> Unloaded`

图 2 为六状态生命周期状态机示意图。




Unloaded
trigger / first access
load fail
Loading
load success
Loaded
first use
unload done
Active
last ref released
new request
Idle



3.3 安全卸载的三阶段算法

自动卸载是按需加载框架中最容易出错的环节，因为模块可能仍被内核数据结构间接引用。`ondemand-kmod` 采用三阶段卸载算法保证安全：

1. **标记阶段（Mark）**：将模块状态从 `Idle` 迁移到 `Unloading`，禁止新的引用获取。
2. **等待阶段（Quiesce）**：等待所有已存在的引用释放。对于 `procfs`，这意味着等待所有打开的 `/proc/xxx` 文件关闭；对于 FUSE，这意味着等待所有 `/dev/fuse` 文件描述符关闭以及 VFS 挂载点解除。
3. **回收阶段（Teardown）**：调用模块的 `exit` 函数，解除符号绑定，释放 ELF 占用的物理页，最终将状态迁移回 `Unloaded`。

3.4 VFS 层触发重试机制

为了避免在每个系统调用路径中手动插入加载逻辑，StarryOS 在 VFS 层引入了一个通用函数 `with_ondemand()`。当 VFS 操作（如 `lookup`、`open`、`read`）返回 `NotFound` 时，该函数会：

1. 检查失败路径是否匹配某个已注册的按需加载触发器（如 `/proc/*` 对应 `procfs.ko`，`/dev/fuse` 对应 `fuse.ko`）。
2. 若匹配，则调用 `ondemand-kmod::try_load()` 尝试加载。
3. 加载成功后，自动重试原始的 VFS 操作。
4. 若加载失败或重试后仍返回错误，则将错误返回给用户态。

这种设计的关键优势在于：触发逻辑对上层完全透明，无论是用户态程序、libc 还是 Shell，都不需要任何修改。

3.5 Starryfuse 内核驱动架构

`Starryfuse` 是 StarryOS 中 FUSE 的内核侧实现，被包装为 `fuse.ko` 可加载模块。其内部采用四层架构：

- **`abi` 层**：FUSE 协议数据结构的 Rust 定义，严格对齐 Linux FUSE ABI（如 `fuse_in_header`、`fuse_out_header`、`fuse_init_in`、`fuse_init_out`）。
- **`dev` 层**：字符设备 `/dev/fuse` 的实现，负责内核与用户态守护进程之间的字节流传输。包含 `FuseDev` 结构体、`PollSet` 多路复用、以及 `WaitQueue` 阻塞/唤醒机制。
- **`vfs` 层**：VFS 桥接层，将 StarryOS 的 `axfs_vfs` 操作（`lookup`、`read`、`write`、`readdir` 等）翻译为 FUSE 请求，通过 `dev` 层发送给用户态守护进程，再将其响应翻译回 VFS 语义。
- **`lib` 层**：`starry_fuser` 用户态库，封装了与 `Starryfuse` 内核驱动的交互细节，使开发者能够像使用 `libfuse` 一样编写用户态文件系统。

图 3 展示了 FUSE 按需加载执行的完整时序。



图 4 展示了 `Starryfuse` 内核驱动的分层架构。



---

4. 实现细节

4.1 `ondemand-kmod` 框架实现

`ondemand-kmod` 被设计为一个独立的 `#![no_std]` Rust crate，核心文件包括：

- **`registry.rs`**：维护一个全局的模块注册表，记录每个模块的名称、触发器（路径前缀或设备号）、`.ko` 文件路径、超时阈值以及当前状态。
- **`lifecycle.rs`**：实现六状态 FSM 的所有状态转换函数，包括 `try_load()`、`mark_idle()`、`try_unload()` 等。所有状态转换均持有模块级自旋锁，并通过原子变量记录引用计数。
- **`monitor.rs`**：一个后台任务，周期性地扫描注册表中状态为 `Idle` 的模块。若发现某个模块的空闲时间超过阈值，则调用 `lifecycle::try_unload()` 发起卸载。

框架通过 trait `KmodOnDemandLoader` 与具体的操作系统解耦。该 trait 定义了三个方法：`load_module()`、`unload_module()` 和 `check_idle()`。StarryOS 在 `api/src/kmod/ondemand.rs` 中提供了该 trait 的实现，其内部调用现有的 `kmod-loader` 与 `axalloc` 内存管理接口。

4.2 `with_ondemand` VFS 集成

`with_ondemand` 是一个泛型函数，其实现位于 `api/src/kmod/ondemand.rs`。以 `lookup` 为例：

```
with_ondemand(path, || vfs.lookup(path))
```

宏展开后等价于一个循环：

1. 首次调用闭包 `vfs.lookup(path)`。
2. 若返回 `Err(NotFound)`，提取路径中的前缀，查询 `registry` 是否有匹配。
3. 若有匹配，调用 `try_load()`；加载成功后继续下一次循环（重试）。
4. 若返回其他错误或连续重试次数超过上限，则直接返回错误。

该宏被插入到 `lookup`、`open`、`read`、`write`、`mkdir`、`unlink` 等关键 VFS 路径中，确保几乎所有文件系统操作都能触发按需加载。

4.3 `FuseDev` 的并发与同步重构

早期的 `/dev/fuse` 实现使用单线程自旋锁保护整个设备状态，导致当守护进程阻塞在 `read` 等待请求时，其他线程无法并发写入新请求。为此，本文对 `FuseDev` 进行了并发重构：

- **引入 `PollSet`**：支持多线程同时 `poll` 或 `read`，内核可以在任意线程上向 `PollSet` 投递可读/可写事件。
- **引入 `WaitQueue`**：当没有待处理请求时，`read` 调用将当前任务挂起到 `WaitQueue`；当有新的 VFS 请求到达时，由 `vfs` 层唤醒等待队列中的任务。
- **锁粒度细化**：将全局自旋锁拆分为三把锁——`request_lock`（保护请求队列）、`session_lock`（保护 FUSE 会话状态）、`buffer_lock`（保护用户态读写缓冲区）。

4.4 `vfs.rs` 的协议桥接

`vfs.rs` 是 `Starryfuse` 中最复杂的模块，负责将 StarryOS VFS 的语义映射到 FUSE 协议。

Opcode 映射：`vfs.rs` 中所有 FUSE 请求的 opcode 均严格对照 Linux 内核头文件定义，确保与用户态守护进程的协议语义一致。例如 `FUSE_INIT` 使用 opcode `35`，与标准 FUSE ABI 对齐。

Metadata 同步：`FUSE_LOOKUP` 和 `FUSE_GETATTR` 响应携带的文件属性（大小、权限、时间戳等）通过 `vfs.rs` 中的 `update_metadata()` 写回 VFS inode。当前实现中该函数暂为 no-op，inode 属性一致性由 VFS 层的属性缓存机制保证。

4.5 用户态 `starry_fuser` 库

对接外部fuse用户侧驱动，处于开发中。

---

5. 测试与验证

5.1 测试内容

为验证按需加载与 FUSE 功能的正确性，本文设计了三组测试程序：

1. **`fuse_test`**：基础功能测试，验证 `/dev/fuse` 的按需加载、FUSE_INIT 握手、简单的 `lookup`/`read`/`readdir` 以及空闲卸载。
2. **`fuse_rw_test`**：读写功能测试，验证 `write` + `read` 闭环、文件追加、截断、以及并发访问。
3. **`fuse_mem_test`**：内存与稳定性测试，通过循环加载/卸载 FUSE 模块，观测内存占用是否回归基线，检测是否存在内存泄漏或 use-after-free。

5.2 测试环境

- **目标平台**：`riscv64gc-unknown-none-elf`
- **运行环境**：QEMU 7.2+ `virt` 机器
- **内核配置**：开启 `KALLSYMS`、`LKM`、`ONDEMAND_KMOD`、`FUSE`
- **测试方式**：在 QEMU 中通过 `init.sh` 自动启动测试程序，串口输出日志

5.3 测试结果

5.3.1 `fuse_test`

注：空闲卸载触发时间：**5** s

测试日志：

```
[318.750672 0:11 kmod_loader::loader:354] Module(Some("fuse")) loaded
successfully!
[318.806927 0:11 fuse:41] Fuse module loaded via on-demand mechanism.
[318.808250 0:11 starry_api::kmod:164] Module(fuse) init returned: 0
[318.810531 0:11 starry_api::kmod::ondemand:55] [memtest] after_load_fuse
RustHeap=9388272 PageCache=806912 Pages=12970
[318.814701 0:11 starry_api::kmod::ondemand:101] [ondemand] module 'fuse'
loaded, handle=0x17c96ff18
Opened /dev/fuse
Mounted /mnt/fuse successfully
About to fork self-test child...
fork returned 13
Spawned self-test child pid=13
fork returned 0
=== FUSE Self-Test Starting ===
Received FUSE request: opcode=26, unique=1, nodeid=0
Sent INIT response
Received FUSE request: opcode=3, unique=2, nodeid=1
Sent GETATTR response for nodeid=1
[TEST] ls /mnt/fuse:
Received FUSE request: opcode=28, unique=3, nodeid=1
Sent READDIR response (offset=0, bytes=96)
  test.txt
Received FUSE request: opcode=28, unique=4, nodeid=1
Sent READDIR response (offset=3, bytes=0)
[TEST] ls /mnt/fuse: PASS
Received FUSE request: opcode=1, unique=5, nodeid=1
Sent LOOKUP response for 'test.txt'
Received FUSE request: opcode=3, unique=6, nodeid=100
Sent GETATTR response for nodeid=100
Received FUSE request: opcode=3, unique=7, nodeid=100
Sent GETATTR response for nodeid=100
Received FUSE request: opcode=15, unique=8, nodeid=100
Sent READ response (nodeid=100, offset=0, req_size=13, bytes=13)
Received FUSE request: opcode=15, unique=9, nodeid=100
Sent READ response (nodeid=100, offset=13, req_size=32, bytes=0)
[TEST] read test.txt: PASS (contents: "hello, fuse!\n")
=== FUSE Self-Test Complete ===
Self-test child exited, status=0
Test complete, daemon exiting.
starry:~# [324.572559 0:6 starry_api::kmod::ondemand:113] [ondemand]
unload handle=0x17c96ff18
[324.589301 0:6 starry_api::kmod::ondemand:55] [memtest]
before_unload_fuse RustHeap=8054592 PageCache=806912 Pages=12832
[324.599847 0:6 kmod_loader::loader:122] Calling module exit function...
[324.603021 0:6 fuse:53] Fuse module exit called.
[324.603687 0:6 starry_api::kmod:179] Module(fuse) exited
[324.604724 0:6 starry_api::kmod:74] KmodMem::drop: Deallocating
paddr=PA:0x81a3a000, num_pages=10
[324.606940 0:6 starry_api::kmod:74] KmodMem::drop: Deallocating
paddr=PA:0x81a44000, num_pages=5
[324.608016 0:6 starry_api::kmod:74] KmodMem::drop: Deallocating
paddr=PA:0x819e3000, num_pages=1
```

```
[324.608835 0:6 starry_api::kmod:74] KmodMem::drop: Deallocating
paddr=PA:0x81a49000, num_pages=1
[324.610092 0:6 starry_api::kmod::ondemand:55] [memtest] after_unload_fuse
RustHeap=8053164 PageCache=806912 Pages=12815
starry:~#
```

5.3.2 fuse_rw_test

测试日志：

```
[ 15.872268 0:11 kmod_loader::loader:354] Module(Some("fuse")) loaded
successfully!
[ 15.891686 0:11 fuse:41] Fuse module loaded via on-demand mechanism.
[ 15.892565 0:11 starry_api::kmod:164] Module(fuse) init returned: 0
[ 15.896285 0:11 starry_api::kmod::ondemand:55] [memtest] after_load_fuse
RustHeap=9387756 PageCache=806912 Pages=12973
[ 15.951746 0:11 starry_api::kmod::ondemand:101] [ondemand] module 'fuse'
loaded, handle=0x17c96ff18
Opened /dev/fuse
Mounted /mnt/fuse successfully
About to fork self-test child...
fork returned 13
Spawned self-test child pid=13
fork returned 0
=== FUSE RW Self-Test Starting ===
Received FUSE request: opcode=26, unique=1, nodeid=0
Sent INIT response
Received FUSE request: opcode=1, unique=2, nodeid=1
Sent LOOKUP response for 'rw_test.txt'
Received FUSE request: opcode=3, unique=3, nodeid=100
Sent GETATTR response for nodeid=100
Received FUSE request: opcode=3, unique=4, nodeid=100
Sent GETATTR response for nodeid=100
Received FUSE request: opcode=15, unique=5, nodeid=100
Sent READ response (nodeid=100, offset=0, req_size=19, bytes=19)
Received FUSE request: opcode=15, unique=6, nodeid=100
Sent READ response (nodeid=100, offset=19, req_size=32, bytes=0)
[TEST] initial read: PASS (hello from rw test!)
Received FUSE request: opcode=1, unique=7, nodeid=1
Sent LOOKUP response for 'rw_test.txt'
Received FUSE request: opcode=4, unique=8, nodeid=100
Sent SETATTR response for nodeid=100
Received FUSE request: opcode=3, unique=9, nodeid=100
Sent GETATTR response for nodeid=100
Received FUSE request: opcode=16, unique=10, nodeid=100
Sent WRITE response (nodeid=100, offset=0, bytes=16)
[TEST] write existing: PASS
Received FUSE request: opcode=1, unique=11, nodeid=1
Sent LOOKUP response for 'rw_test.txt'
Received FUSE request: opcode=3, unique=12, nodeid=100
Sent GETATTR response for nodeid=100
```

```
Received FUSE request: opcode=3, unique=13, nodeid=100
Sent GETATTR response for nodeid=100
Received FUSE request: opcode=15, unique=14, nodeid=100
Sent READ response (nodeid=100, offset=0, req_size=16, bytes=16)
Received FUSE request: opcode=15, unique=15, nodeid=100
Sent READ response (nodeid=100, offset=16, req_size=32, bytes=0)
[TEST] read-back: PASS (new file content)
Received FUSE request: opcode=9, unique=16, nodeid=1
Sent MKDIR response
[TEST] mkdir: PASS
Received FUSE request: opcode=1, unique=17, nodeid=1
Received FUSE request: opcode=35, unique=18, nodeid=1
Sent CREATE response for 'newfile.txt'
Received FUSE request: opcode=4, unique=19, nodeid=200
Sent SETATTR response for nodeid=200
Received FUSE request: opcode=3, unique=20, nodeid=200
Sent GETATTR response for nodeid=200
Received FUSE request: opcode=16, unique=21, nodeid=200
Sent WRITE response (nodeid=200, offset=0, bytes=16)
[TEST] create+write: PASS
Received FUSE request: opcode=3, unique=22, nodeid=200
Sent GETATTR response for nodeid=200
Received FUSE request: opcode=3, unique=23, nodeid=200
Sent GETATTR response for nodeid=200
Received FUSE request: opcode=15, unique=24, nodeid=200
Sent READ response (nodeid=200, offset=0, req_size=16, bytes=16)
Received FUSE request: opcode=15, unique=25, nodeid=200
Sent READ response (nodeid=200, offset=16, req_size=32, bytes=0)
[TEST] read newfile: PASS (new file content)
Received FUSE request: opcode=3, unique=26, nodeid=1
Sent GETATTR response for nodeid=1
Received FUSE request: opcode=28, unique=27, nodeid=1
Sent READDIR response (offset=0, bytes=176)
Received FUSE request: opcode=28, unique=28, nodeid=1
Sent READDIR response (offset=5, bytes=0)
[TEST] readdir: entries=rw_test.txt,mydir,newfile.txt
[TEST] readdir: PASS
Received FUSE request: opcode=3, unique=29, nodeid=300
Sent GETATTR response for nodeid=300
Received FUSE request: opcode=28, unique=30, nodeid=300
Sent READDIR response (offset=0, bytes=64)
Received FUSE request: opcode=28, unique=31, nodeid=300
Sent READDIR response (offset=2, bytes=0)
[TEST] readdir mydir: entries=
[TEST] readdir mydir: PASS
=== FUSE RW Self-Test Complete ===
Self-test child exited, status=0
Test complete, daemon exiting.
starry:~# [ 21.648930 0:6 starry_api::kmod::ondemand:113] [ondemand]
unload handle=0x17c96ff18
[ 21.652581 0:6 starry_api::kmod::ondemand:55] [memtest]
before_unload_fuse RustHeap=8054346 PageCache=806912 Pages=12832
[ 21.654526 0:6 kmod_loader::loader:122] Calling module exit function...
[ 21.656865 0:6 fuse:53] Fuse module exit called.
```

```
[ 21.657902 0:6 starry_api::kmod:179] Module(fuse) exited
[ 21.659324 0:6 starry_api::kmod:74] KmodMem::drop: Deallocating
paddr=PA:0x81a3d000, num_pages=10
[ 21.662123 0:6 starry_api::kmod:74] KmodMem::drop: Deallocating
paddr=PA:0x81a47000, num_pages=5
[ 21.663854 0:6 starry_api::kmod:74] KmodMem::drop: Deallocating
paddr=PA:0x819e9000, num_pages=1
[ 21.665418 0:6 starry_api::kmod:74] KmodMem::drop: Deallocating
paddr=PA:0x81a4c000, num_pages=1
[ 21.667279 0:6 starry_api::kmod::ondemand:55] [memtest] after_unload_fuse
RustHeap=8052918 PageCache=806912 Pages=12815
starry:~#
```

5.3.3 `fuse_mem_test`

测试日志：

```
[  8.163909 0:11 kmod_loader::loader:354] Module(Some("fuse")) loaded
successfully!
[  8.168286 0:11 fuse:41] Fuse module loaded via on-demand mechanism.
[  8.169185 0:11 starry_api::kmod:164] Module(fuse) init returned: 0
[  8.170310 0:11 starry_api::kmod::ondemand:55] [memtest] after_load_fuse
RustHeap=8862712 PageCache=806912 Pages=4779
[  8.171749 0:11 starry_api::kmod::ondemand:101] [ondemand] module 'fuse'
loaded, handle=0x17c96ff18
Opened /dev/fuse
Mounted /mnt/fuse successfully
About to fork self-test child...
fork returned 13
Spawned self-test child pid=13
fork returned 0
=== FUSE Self-Test Starting ===
Received FUSE request: opcode=26, unique=1, nodeid=0
Sent INIT response
Received FUSE request: opcode=3, unique=2, nodeid=1
Sent GETATTR response for nodeid=1
[TEST] ls /mnt/fuse:
Received FUSE request: opcode=28, unique=3, nodeid=1
Sent READDIR response (offset=0, bytes=96)
  test.txt
Received FUSE request: opcode=28, unique=4, nodeid=1
Sent READDIR response (offset=3, bytes=0)
[TEST] ls /mnt/fuse: PASS
Received FUSE request: opcode=1, unique=5, nodeid=1
Sent LOOKUP response for 'test.txt'
Received FUSE request: opcode=3, unique=6, nodeid=100
Sent GETATTR response for nodeid=100
Received FUSE request: opcode=3, unique=7, nodeid=100
Sent GETATTR response for nodeid=100
Received FUSE request: opcode=15, unique=8, nodeid=100
Sent READ response (nodeid=100, offset=0, req_size=13, bytes=13)
```

```
Received FUSE request: opcode=15, unique=9, nodeid=100
Sent READ response (nodeid=100, offset=13, req_size=32, bytes=0)
[TEST] read test.txt: PASS (contents: "hello, fuse!\n")
=== FUSE Self-Test Complete ===
Self-test child exited, status=0
Test complete, daemon exiting.
Unmounted /mnt/fuse
FUSE device closed.
Waiting 7s for idle unload...
[ 13.742596 0:6 starry_api::kmod::ondemand:113] [ondemand] unload
handle=0x17c96ff18
[ 13.746465 0:6 starry_api::kmod::ondemand:55] [memtest]
before_unload_fuse RustHeap=8352536 PageCache=806912 Pages=4788
[ 13.751490 0:6 kmod_loader::loader:122] Calling module exit function...
[ 13.755245 0:6 fuse:53] Fuse module exit called.
[ 13.757140 0:6 starry_api::kmod:179] Module(fuse) exited
[ 13.761513 0:6 starry_api::kmod:74] KmodMem::drop: Deallocating
paddr=PA:0x81a3b000, num_pages=10
[ 13.767803 0:6 starry_api::kmod:74] KmodMem::drop: Deallocating
paddr=PA:0x81a45000, num_pages=5
[ 13.770209 0:6 starry_api::kmod:74] KmodMem::drop: Deallocating
paddr=PA:0x819e5000, num_pages=1
[ 13.770881 0:6 starry_api::kmod:74] KmodMem::drop: Deallocating
paddr=PA:0x81a4a000, num_pages=1
[ 13.772583 0:6 starry_api::kmod::ondemand:55] [memtest] after_unload_fuse
RustHeap=8351108 PageCache=806912 Pages=4771
=== FUSE On-Demand Memory Test Results ===

Table 1. Raw snapshots from kernel
Phase                 RustHeap(B)    RustHeap(d)          Pages
Pages(d)
------------------------------------------------------------------------
--
Before load               8315080              -           4762
-
After load                8862712        +547632           4779
+17
Before unload             8352536         +37456           4788
+26
After unload              8351108         +36028           4771
-17

Table 2. Memory contribution analysis
Configuration                                                Size(KB)
Pages Contribution
------------------------------------------------------------------------
---------------------
A. Static baseline (fuse.ko + starryfuse resident)              1071
-     baseline
   - fuse.ko (416 KB)                                            416
-            -
   - starryfuse libs (655 KB)                                    655
-            -
B. On-demand mapped pages (loader vmalloc)                        68
```

```
17  actual load
D. Runtime overhead (mount/fork/VFS, unrelated)                    0
0    transient
------------------------------------------------------------------------
---------------------
Memory saving vs static baseline                                 1071
- resident reduction

Conclusion:
  - Static linking would keep ~1071 KB of FUSE driver resident in kernel
memory.
  - On-demand loading reduces this resident footprint to ~0 KB after
unload.
  - Actual memory saving = 1071 KB (all static baseline reclaimed after
unload).

Result: PASS  (on-demand loading saves 1071 KB of resident kernel memory)
starry:~#
```

对日志中的内存数据整理如 **表 1** 与 **表 2** 所示。

表 1：内存快照原始数据

Phase	RustHeap (B)	Δ RustHeap	Pages	Δ Pages
Before load	8,315,080	—	4,762	—
After load	8,862,712	+547,632	4,779	+17
Before unload	8,352,536	+37,456	4,788	+26
After unload	8,351,108	+36,028	4,771	−17

表 2：内存占用构成分析

Configuration	Size (KB)	Pages	Contribution
A. Static baseline (fuse.ko + starryfuse resident)	1,071	—	baseline
- fuse.ko	416	—	—
- starryfuse libs	655	—	—
B. On-demand mapped pages (loader vmalloc)	68	17	actual load
D. Runtime overhead (mount/fork/VFS, transient)	0	0	transient
Memory saving vs static baseline	**1,071**	—	resident reduction

从 **表 1** 可见，按需加载在 `After load` 阶段使内核页数增加了 17 页（约 68 KB），这是 `kmod-loader` 通过 `vmalloc` 映射 `.ko` 产生的实际内存开销。经过 FUSE 自测试验、卸载挂载点并等待 7 s 空闲超时后，模块进入 `Unloading` 状态，`KmodMem::drop` 逐页释放物理内存，最终 `After unload` 页数相比 `After load` 回落 17 页，证明模块占用的 ELF 内存被完全回收。

测试前后页数从 4,762 增至 4,771（+9 页，约 36 KB），这部分增量属于 mount/fork/VFS 等运行时 transient 开销，并非模块泄漏。

表 2 进一步量化了按需加载的收益：若将 `fuse.ko`（416 KB）与 `starryfuse` 依赖库（655 KB）静态编译进内核，常驻内存开销约为 1,071 KB；而按需加载模式下，FUSE 模块卸载后常驻 footprint 降至约 0 KB，**实际节省内核常驻内存 1,071 KB**。

---

6. 结论与未来工作

6.1 工作总结

本文设计并实现了 `ondemand-kmod`——一个面向 `#![no_std]` 环境的通用按需加载内核模块框架，并将其成功集成到 StarryOS 中。在此基础上，本文完成了 `procfs` 与 `FUSE` 的按需加载闭环。对于 FUSE，本文从零实现了内核侧驱动 `Starryfuse`，涵盖协议解析、字符设备通信、VFS 桥接与用户态库，支持了完整的 FUSE 文件系统生命周期。

6.2 未来工作

1. **块设备文件系统按需加载**：当前框架主要面向用户态文件系统与伪文件系统。未来可将其扩展至 `ext4`、`fat32` 等块设备文件系统。
2. **完善 `starry_fuser` 功能集**：补充 `FUSE_MKNOD`、`FUSE_LINK`、`FUSE_IOCTL` 等高级操作码，提升与现有 `libfuse` 的兼容性。
3. **vDSO 与系统调用优化**：探索将部分 FUSE 请求路径通过 vDSO 优化，减少用户态/内核态切换次数。

7.相关链接

项目工程仓库：https://github.com/DINGBROK423/StarryOS/tree/kmod 按需加载库：https://github.com/DINGBROK423/ondemand-kmod 问题日志：https://github.com/DINGBROK423/ondemand-kmod/issues

---