Homework-7

1. Write a C program to construct an expression tree for a given expression.

Example: (a-b)+(c*d)

```
#include <stdio.h>
#include <stdlib.h>
#include <ctype.h>
struct node
{
   char data;
   struct node *left, *right;
};
struct node *stack[100];
int top = -1;
struct node *createNode(char c)
{
   struct node *newnode =(struct node *)malloc(sizeof(struct node));
   newnode->data = c;
   newnode->left = NULL;
   newnode->right = NULL;
   return newnode;
```

```
}
void push(struct node *n)
{
   stack[++top] = n;
}
struct node *pop()
{
   return stack[top--];
}
int main()
{
   char postfix[100];
   int i;
   struct node *root, *left, *right;
   printf("Enter postfix expression: ");
   scanf("%99s", postfix);
   for (i = 0; postfix[i] != '\0'; i++)
   {
      if (isalnum((unsigned char)postfix[i]))
      {
         push(createNode(postfix[i]));
```

```
        }
        else
        {
            right = pop();
            left = pop();
            root = createNode(postfix[i]);
            root->left = left;
            root->right = right;
            push(root);
        }
    }
    root = pop();
    printf("Expression tree constructed successfully.\n");
    return 0;
}
```

OUTPUT:

Enter postfix expression: ab-cd*+

Expression tree constructed successfully.

2. Write a C program to check whether a given binary tree is a Binary Search Tree (BST).

```
#include <stdio.h>
```

```
#include <stdlib.h>
#include <limits.h>
struct node
{
   int data;
   struct node *left, *right;
};
struct node *createNode(int data)
{
   struct node *newnode = (struct node *)malloc(sizeof(struct node));
   newnode->data = data;
   newnode->left = NULL;
   newnode->right = NULL;
   return newnode;
}
int isBST(struct node *root, long long min, long long max)
{
   if (root == NULL)
      return 1;
   if (root->data <= min || root->data >= max)
      return 0;
```

```
    return isBST(root->left, min, root->data) &&
           isBST(root->right, root->data, max);
}
int main()
{
    struct node *root;
    root = createNode(50);
    root->left = createNode(30);
    root->right = createNode(70);
    root->left->left = createNode(20);
    root->left->right = createNode(40);
    root->right->left = createNode(60);
    root->right->right = createNode(80);
    if (isBST(root, LLONG_MIN, LLONG_MAX))
        printf("The binary tree is a BST.\n");
    else
        printf("The binary tree is not a BST.\n");
    return 0;
}
```

OUTPUT:

The binary tree is a BST.

3. Write a C program to implement a Max Heap.

```
#include <stdio.h>

int heap[100];

int n = 0;

void insert(int value)

{

   int i, temp;

   i = n;

   heap[n] = value;

   n++;

   while (i > 0 && heap[(i - 1) / 2] < heap[i])

   {

      temp = heap[i];

      heap[i] = heap[(i - 1) / 2];

      heap[(i - 1) / 2] = temp;

      i = (i - 1) / 2;

   }

}

void display()

{

   int i;
```

```
    printf("Max Heap: ");
    for (i = 0; i < n; i++)
        printf("%d ", heap[i]);
    printf("\n");
}
int main()
{
    int count, value, i;
    printf("Enter number of elements: ");
    scanf("%d", &count);
    printf("Enter elements: ");
    for (i = 0; i < count; i++)
    {
        scanf("%d", &value);
        insert(value);
    }
    display();
    return 0;
}
```

OUTPUT:

Enter number of elements: 5

Enter elements: 40 20 30 10 50

Max Heap: 50 40 30 10 20

4. Given an undirected graph the task to check, if there is a cycle in the given graph.

```
#include <stdio.h>

int graph[20][20], visited[20], n;

int hasCycle(int v, int parent)

{

   int i;

   visited[v] = 1;

   for (i = 0; i < n; i++)

   {

      if (graph[v][i])

      {

         if (!visited[i])

         {

            if (hasCycle(i, v))

               return 1;

         }

         else if (i != parent)

            return 1;
```

```
        }
    }
    return 0;
}
int main()
{
    int e, u, v, i;
    printf("Enter number of vertices and edges: ");
    scanf("%d%d", &n, &e);
    printf("Enter edges (u v):\n");
    for (i = 0; i < e; i++)
    {
        scanf("%d%d", &u, &v);
        graph[u][v] = 1;
        graph[v][u] = 1;
    }
    for (i = 0; i < n; i++)
        visited[i] = 0;
    for (i = 0; i < n; i++)
    {
        if (!visited[i] && hasCycle(i, -1))
```

```
        {
            printf("Cycle exists in the graph.\n");
            return 0;
        }
    }
    printf("No cycle exists in the graph.\n");
    return 0;
}
```

OUTPUT:

Enter number of vertices and edges: 3 3

Enter edges (u v):

0 1

1 2

2 0

Cycle exists in the graph.

5. Given an grid consisting of 'L' (Land) and 'W' (Water), count the number of islands.

```
#include <stdio.h>
char grid[5][5] = {
    {'L','L','W','W','W'},
    {'L','L','W','W','L'},
```

```
    {'L','W','W','L','L'},
    {'W','W','W','W','W'},
    {'L','W','L','L','W'}
};
void dfs(int r, int c)
{
    if (r < 0 || r >= 5 || c < 0 || c >= 5 ||
        grid[r][c] == 'W')
        return;
    grid[r][c] = 'W';
    dfs(r + 1, c);
    dfs(r - 1, c);
    dfs(r, c + 1);
    dfs(r, c - 1);
}
int main()
{
    int i, j, count = 0;
    for (i = 0; i < 5; i++)
    {
        for (j = 0; j < 5; j++)
```

```
        {
            if (grid[i][j] == 'L')
            {
                count++;
                dfs(i, j);
            }
        }
    }
    printf("Number of islands = %d", count);
    return 0;
}
```

OUTPUT:

Number of islands = 4

6. Find out the Minimum Spanning Tree using Kruskal's algorithm.

```
#include <stdio.h>
struct Edge
{
    int u, v, w;
};
struct Edge e[100], temp;
int parent[20];
```

```
int find(int x)
{
    while (parent[x] != x)
        x = parent[x];
    return x;
}
int main()
{
    int n, m, i, j, u, v, total = 0, count = 0;
    printf("Enter vertices and edges: ");
    scanf("%d%d", &n, &m);
    printf("Enter edges (u v weight):\n");
    for (i = 0; i < m; i++)
        scanf("%d%d%d", &e[i].u, &e[i].v, &e[i].w);
    for (i = 0; i < n; i++)
        parent[i] = i;
    for (i = 0; i < m - 1; i++)
        for (j = 0; j < m - i - 1; j++)
            if (e[j].w > e[j + 1].w)
            {
                temp = e[j];
```

```
            e[j] = e[j + 1];
            e[j + 1] = temp;
        }
    printf("Edges in MST:\n");
    for (i = 0; i < m && count < n - 1; i++)
    {
        u = find(e[i].u);
        v = find(e[i].v);
        if (u != v)
        {
            parent[u] = v;
            printf("%d - %d : %d\n",
                   e[i].u, e[i].v, e[i].w);
            total += e[i].w;
            count++;
        }
    }
    if (count == n - 1)
        printf("Minimum cost: %d\n", total);
    else
        printf("Spanning tree does not exist\n");
```

```
    return 0;
}
```

OUTPUT:

Enter vertices and edges: 4 5

Enter edges (u v weight):

0 1 10

0 2 6

0 3 5

1 3 15

2 3 4

Edges in MST:

2 - 3 : 4

0 - 3 : 5

0 - 1 : 10

Minimum cost: 19

7. Use Dijkstra's algorithm to find the shortest path from a source to all nodes.

```
#include <stdio.h>
#define INF 99999
int main()
{
```

```
int g[20][20], dist[20], visited[20];
int n, source, i, j, u, min;
printf("Enter number of vertices: ");
scanf("%d", &n);
printf("Enter adjacency matrix:\n");
for (i = 0; i < n; i++)
   for (j = 0; j < n; j++)
   {
      scanf("%d", &g[i][j]);
      if (i != j && g[i][j] == 0)
         g[i][j] = INF;
   }
printf("Enter source vertex: ");
scanf("%d", &source);
for (i = 0; i < n; i++)
{
   dist[i] = g[source][i];
   visited[i] = 0;
}
dist[source] = 0;
visited[source] = 1;
```

```
for (i = 1; i < n; i++)
{
   min = INF;
   u = -1;
   for (j = 0; j < n; j++)
      if (!visited[j] && dist[j] < min)
      {
         min = dist[j];
         u = j;
      }
   if (u == -1)
      break;
   visited[u] = 1;
   for (j = 0; j < n; j++)
      if (!visited[j] && g[u][j] != INF &&
         dist[u] + g[u][j] < dist[j])
         dist[j] = dist[u] + g[u][j];
}
printf("Shortest distances from source %d:\n", source);
for (i = 0; i < n; i++)
{
```

```
        if (dist[i] == INF)
            printf("%d -> %d : Unreachable\n", source, i);
        else
            printf("%d -> %d : %d\n", source, i, dist[i]);
    }
    return 0;
}
```

OUTPUT:

Enter number of vertices: 4

Enter adjacency matrix:

0 4 1 0

4 0 2 5

1 2 0 8

0 5 8 0

Enter source vertex: 0

Shortest distances from source 0:

0 -> 0 : 0

0 -> 1 : 3

0 -> 2 : 1

0 -> 3 : 8

8. Write a program to find an Mother Vertex in the graph.

A Mother Vertex in a graph G=(V,E) is a vertex V such that all other vertices in G can be reached by a pain from V.

```
#include <stdio.h>
int graph[20][20], visited[20], n;
void DFS(int v)
{
   int i;
   visited[v] = 1;
   for (i = 0; i < n; i++)
   {
      if (graph[v][i] && !visited[i])
         DFS(i);
   }
}
int main()
{
   int i, j, candidate = -1, found;
   printf("Enter number of vertices: ");
   scanf("%d", &n);
   printf("Enter adjacency matrix:\n");
   for (i = 0; i < n; i++)
```

```
    for (j = 0; j < n; j++)
        scanf("%d", &graph[i][j]);
for (i = 0; i < n; i++)
{
    for (j = 0; j < n; j++)
        visited[j] = 0;
    DFS(i);
    found = 1;
    for (j = 0; j < n; j++)
    {
        if (!visited[j])
        {
            found = 0;
            break;
        }
    }
    if (found)
    {
        candidate = i;
        break;
    }
```

```
    }
    if (candidate != -1)
        printf("Mother Vertex: %d\n", candidate);
    else
        printf("No Mother Vertex exists.\n");
    return 0;
}
```

OUTPUT:

Enter number of vertices: 4

Enter adjacency matrix:

0 1 1 0

0 0 0 1

0 0 0 1

0 0 0 0

No Mother Vertex exists.

9. A directed graph is strongly connected if there is a path between all pairs of vertices. A strongly connected component of a directed graph is a maximal strongly connected subgraph. Given a graph print all SCC.

```
#include <stdio.h>
int g[20][20], t[20][20];
int visited[20], stack[20];
```

```
int n, top = -1;
void dfs1(int v)
{
   int i;
   visited[v] = 1;
   for (i = 0; i < n; i++)
      if (g[v][i] && !visited[i])
         dfs1(i);
   stack[++top] = v;
}
void dfs2(int v)
{
   int i;
   visited[v] = 1;
   printf("%d ", v);
   for (i = 0; i < n; i++)
      if (t[v][i] && !visited[i])
         dfs2(i);
}
int main()
{
```

```
int i, j, v, component = 0;
printf("Enter number of vertices: ");
scanf("%d", &n);
printf("Enter adjacency matrix:\n");
for (i = 0; i < n; i++)
   for (j = 0; j < n; j++)
   {
      scanf("%d", &g[i][j]);
      t[j][i] = g[i][j];
   }
for (i = 0; i < n; i++)
   visited[i] = 0;
for (i = 0; i < n; i++)
   if (!visited[i])
      dfs1(i);
for (i = 0; i < n; i++)
   visited[i] = 0;
printf("Strongly Connected Components:\n");
while (top != -1)
{
   v = stack[top--];
```

```
        if (!visited[v])
        {
            component++;
            printf("SCC %d: ", component);
            dfs2(v);
            printf("\n");
        }
    }
    return 0;
}
```

OUTPUT:

Enter number of vertices: 4

Enter adjacency matrix:

0 1 0 0

0 0 1 0

1 0 0 0

0 0 0 0

Strongly Connected Components:

SCC 1: 3

SCC 2: 0 1 2

10. A bipartite graph G=(V,E) is a graph such that V can be partitioned into two subsets V_1 and V_2, and no edge has been its vertices in the same subset. Write a program to determine whether a graph is a bipartite graph

```
#include <stdio.h>
int graph[20][20], color[20], n;
int isBipartite()
{
   int queue[20];
   int front, rear, i, u, v;
   for (i = 0; i < n; i++)
      color[i] = -1;
   for (i = 0; i < n; i++)
   {
      if (color[i] != -1)
         continue;
      front = rear = 0;
      queue[rear++] = i;
      color[i] = 0;
      while (front < rear)
      {
         u = queue[front++];
```

```
            for (v = 0; v < n; v++)
            {
                if (graph[u][v])
                {
                    if (color[v] == -1)
                    {
                        color[v] = 1 - color[u];
                        queue[rear++] = v;
                    }
                    else if (color[v] == color[u])
                    {
                        return 0;
                    }
                }
            }
        }
    }
    return 1;
}
int main()
{
```

```
    int i, j;
    printf("Enter number of vertices: ");
    scanf("%d", &n);
    printf("Enter adjacency matrix:\n");
    for (i = 0; i < n; i++)
        for (j = 0; j < n; j++)
            scanf("%d", &graph[i][j]);
    if (isBipartite())
        printf("Graph is Bipartite.\n");
    else
        printf("Graph is not Bipartite.\n");
    return 0;
}
```

OUTPUT:

Enter number of vertices: 4

Enter adjacency matrix:

0 1 1 0

1 0 0 1

1 0 0 1

0 1 1 0

Graph is Bipartite.