
DATA STRUCTURE – 8

1)Simulate BFS and DFS traversals for the given graph.



CODE:

```
#include <stdio.h>
char vertex[V] = {'A', 'B', 'C', 'D', 'E', 'F', 'G'};
int graph[V][V] = {
    {0, 1, 0, 1, 0, 0, 0}, // A
    {1, 0, 0, 0, 1, 1, 0}, // B
    {0, 0, 0, 0, 0, 1, 0}, // C
    {1, 0, 0, 0, 0, 0, 1}, // D
    {0, 1, 0, 0, 0, 0, 1}, // E
    {0, 1, 1, 0, 0, 0, 1}, // F
    {0, 0, 0, 1, 1, 1, 0}  // G
};
int visited[V];
void BFS(int start)
{
    int queue[V], front = 0, rear = 0;
    int i, current;
    for (i = 0; i < V; i++)
        visited[i] = 0;
    queue[rear++] = start;
```

Scanned with OKEN Scanner

```
visited[start] = 1;
while (front < rear)
{
    current = queue[front++];
    printf("%c ", vertex[current]);
    for (i = 0; i < V; i++)
        {
            if (graph[current][i] && !visited[i])
            {
                queue[rear++] = i;
                visited[i] = 1;
            }
        }
    }
}
```

```
void DFS(int current)
{
    int i;

    visited[current] = 1;
    printf("%c ", vertex[current]);

    for (i = 0; i < V; i++)
        {
            if (graph[current][i] && !visited[i])
                DFS(i);
        }
}
```

Scanned with OKEN Scanner

```
int main()
{
    int i;

    printf("BFS Traversal: ");
    BFS(0);

    for (i = 0; i < V; i++)
        visited[i] = 0;

    printf("\nDFS Traversal: ");
    DFS(0);

    printf("\n");
    return 0;
}
```


OUTPUT:

main.c | Output

```
BFS Traversal: A B D E F G C
DFS Traversal: A B E G D F C
```

2)Find out the minimum spanning tree for the given using prim's and kruskal's algorithms.

Scanned with OKEN Scanner



CODE:

```
#include <stdio.h>
#define MAX 100
int parent[MAX];
int find(int x)
{
    while (parent[x] != x)
        x = parent[x];
    return x;
}

int main()
{
    int n, e, i, j, u, v, w;
    int edgeU[MAX], edgeV[MAX], edgeW[MAX];
    int cost[MAX][MAX];
    int selected[MAX] = {0};
    int total, count, min, a, b, temp;

printf("Enter number of vertices and edges: ");
scanf("%d%d", &n, &e);

for (i = 0; i < n; i++)
```

Scanned with OKEN Scanner

```
    for (j = 0; j < n; j++)
        cost[i][j] = (i == j) ? 0 : INF;

printf("Enter edges (u v weight), vertices numbered 0 to %d:\n", n - 1);

for (i = 0; i < e; i++)
{
    scanf("%d%d%d", &u, &v, &w);
    edgeU[i] = u;
    edgeV[i] = v;
    edgeW[i] = w;
    cost[u][v] = cost[v][u] = w;
}

/* Prim's Algorithm */
selected[0] = 1;
total = 0;
count = 0;

printf("\nPrim's MST:\n");

while (count < n - 1)
{
    min = INF;
    a = -1;
    b = -1;

    for (i = 0; i < n; i++)
    {
```

Scanned with OKEN Scanner

```
if (selected[i])
{
    for (j = 0; j < n; j++)
    {
        if (!selected[j] && cost[i][j] < min)
        {
            min = cost[i][j];
            a = i;
            b = j;
        }
    }
}
}

if (a == -1)
{
    printf("Graph is disconnected.\n");
    break;
}

printf("%d - %d : %d\n", a, b, min);
selected[b] = 1;
total += min;
count++;
}

if (count == n - 1)
    printf("Total cost = %d\n", total);
```

Scanned with OKEN Scanner

```
/* Kruskal's Algorithm */
for (i = 0; i < e; i++)
    for (j = i + 1; j < e; j++)
        if (edgeW[i] > edgeW[j])
        {
            temp = edgeW[i];
            edgeW[i] = edgeW[j];
            edgeW[j] = temp;

            temp = edgeU[i];
            edgeU[i] = edgeU[j];
            edgeU[j] = temp;

            temp = edgeV[i];
            edgeV[i] = edgeV[j];
            edgeV[j] = temp;
        }

for (i = 0; i < n; i++)
    parent[i] = i;

total = 0;
count = 0;

printf("\nKruskal's MST:\n");

for (i = 0; i < e && count < n - 1; i++)
{
    u = find(edgeU[i]);
```

Scanned with OKEN Scanner

```
v = find(edgeV[i]);

if (u != v)
{
    printf("%d - %d : %d\n",
          edgeU[i], edgeV[i], edgeW[i]);
        parent[u] = v;
        total += edgeW[i];
        count++;
    }
}

if (count == n - 1)
    printf("Total cost = %d\n", total);
    else
        printf("Graph is disconnected.\n");

    return 0;
}
```

Scanned with OKEN Scanner

OUTPUT:

main.c | Output


```
Enter number of vertices and edges: 5 7
Enter edges (u v weight), vertices numbered 0 to 4:
0 1 1
0 2 7
1 2 5
1 3 4
1 4 3
2 4 6
3 4 2

Prim's MST:
0 - 1 : 1
1 - 4 : 3
4 - 3 : 2
1 - 2 : 5
Total cost = 11

Kruskal's MST:
0 - 1 : 1
3 - 4 : 2
1 - 4 : 3
1 - 2 : 5
Total cost = 11
```

3)To find the minimum spanning tree.

Scanned with OKEN Scanner



CODE:

```
#include <stdio.h>

#define MAX 20

int parent[MAX];

int find(int x)

{

    while (parent[x] != x)

        x = parent[x];

    return x;

}

int main()

{

    int n, e, i, j, u, v, w;

    int cost[MAX][MAX];

    int eu[MAX], ev[MAX], ew[MAX];

    int visited[MAX] = {0};

    int min, a, b, total, count, temp;


printf("Enter number of vertices and edges: ");
```

Scanned with OKEN Scanner

```
scanf("%d%d", &n, &e);

for (i = 0; i < n; i++)
    for (j = 0; j < n; j++)
        cost[i][j] = (i == j) ? 0 : INF;

printf("Enter edges (u v weight), vertices numbered 0 to %d:\n", n - 1);

for (i = 0; i < e; i++)
{
    scanf("%d%d%d", &u, &v, &w);
    eu[i] = u;
    ev[i] = v;
    ew[i] = w;
    cost[u][v] = cost[v][u] = w;
}

/* Prim's Algorithm */
visited[0] = 1;
total = 0;
count = 0;

printf("\nPrim's MST:\n");

while (count < n - 1)
{
    min = INF;
    a = -1;
    b = -1;
```

Scanned with OKEN Scanner

```
for (i = 0; i < n; i++)
    if (visited[i])
        for (j = 0; j < n; j++)
            if (!visited[j] && cost[i][j] < min)
            {
                min = cost[i][j];
                a = i;
                b = j;
            }

if (a == -1)
{
    printf("Graph is disconnected.\n");
    break;
    }

    printf("%d - %d : %d\n", a, b, min);
    visited[b] = 1;
    total += min;
    count++;
}

if (count == n - 1)
    printf("Total cost = %d\n", total);

/* Sort edges for Kruskal's Algorithm */
for (i = 0; i < e; i++)
    for (j = i + 1; j < e; j++)
```

Scanned with OKEN Scanner

```
if (ew[i] > ew[j])
{
    temp = ew[i]; ew[i] = ew[j]; ew[j] = temp;
    temp = eu[i]; eu[i] = eu[j]; eu[j] = temp;
    temp = ev[i]; ev[i] = ev[j]; ev[j] = temp;
}

for (i = 0; i < n; i++)
    parent[i] = i;

total = 0;
count = 0;

printf("\nKruskal's MST:\n");

for (i = 0; i < e && count < n - 1; i++)
{
    u = find(eu[i]);
    v = find(ev[i]);

    if (u != v)
    {
        printf("%d - %d : %d\n", eu[i], ev[i], ew[i]);
        parent[u] = v;
        total += ew[i];
        count++;
    }
}
```

Scanned with OKEN Scanner

```
if (count == n - 1)
    printf("Total cost = %d\n", total);
else
    printf("Graph is disconnected.\n");

return 0;
}
```

OUTPUT:

main.c | Output


```
u  v  w
2  6  1
2  3  7
5  6  1
6  3  5
3  4  3
3  7  4

Prim's MST:
0 - 5 : 3
5 - 6 : 1
6 - 2 : 1
5 - 1 : 2
6 - 3 : 5
3 - 4 : 3
3 - 7 : 4
Total cost = 19

Kruskal's MST:
2 - 6 : 1
5 - 6 : 1
1 - 5 : 2
0 - 5 : 3
3 - 4 : 3
3 - 7 : 4
6 - 3 : 5
Total cost = 19
```

Scanned with OKEN Scanner

4)DAG For topological sorting.



CODE:

```
#include <stdio.h>


int main()
{
    int n, i, j, count = 0;
    int a[20][20], indegree[20] = {0};
    int queue[20], front = 0, rear = -1;
    int topo[20];

    printf("Enter number of vertices: ");
```

Scanned with OKEN Scanner

```
scanf("%d", &n);

printf("Enter adjacency matrix:\n");
for (i = 0; i < n; i++)
    for (j = 0; j < n; j++)
        scanf("%d", &a[i][j]);

for (i = 0; i < n; i++)
    for (j = 0; j < n; j++)
        if (a[i][j] == 1)
            indegree[j]++;

for (i = 0; i < n; i++)
    if (indegree[i] == 0)
        queue[++rear] = i;

while (front <= rear)
{
    int u = queue[front++];
    topo[count++] = u;

    for (j = 0; j < n; j++)
    {
        if (a[u][j] == 1)
{
    indegree[j]--;
    if (indegree[j] == 0)
        queue[++rear] = j;
}
```

Scanned with OKEN Scanner

```
    }
}

if (count != n)
    printf("Graph contains a cycle.\n");
else
    {
        printf("Topological order: ");
        for (i = 0; i < n; i++)
            printf("%d ", topo[i]);
        printf("\n");
    }

    return 0;
}
```

OUTPUT:

Scanned with OKEN Scanner

main.c | Output

```
Enter number of vertices: 6
Enter adjacency matrix:
0 0 0 0 0 0
0 0 0 0 0 0
0 1 0 0 0 0
0 0 0 0 0 0
0 0 0 0 0 0
0 0 0 0 0 0
Topological order: 0 2 3 4 5 1
```

5)Insert 76,93,40,47,10,55 in a hash table of size 7 using linear probing method.

CODE:

```
#include <stdio.h>

#define SIZE 7

int main()

{

    int hash[SIZE];

    int keys[] = {76, 93, 40, 47, 10, 55};

    int i, j, index;


for (i = 0; i < SIZE; i++)

    hash[i] = -1;


for (i = 0; i < 6; i++)

{
```

Scanned with OKEN Scanner

```
index = keys[i] % SIZE;

for (j = 0; j < SIZE; j++)
{
    if (hash[index] == -1)
    {
        hash[index] = keys[i];
        break;
    }

    index = (index + 1) % SIZE;
  }
}

printf("Hash Table:\n");
  for (i = 0; i < SIZE; i++)
    printf("%d : %d\n", i, hash[i]);

  return 0;
}
```

OUTPUT:

Scanned with OKEN Scanner

main.c | Output

```
Hash Table:
0 : 47
1 : 55
2 : 93
3 : 10
4 : -1
5 : 40
6 : 76
```

6)Consider a hash table size= 7, hash function as hash(x) = x%7 and collision resolution strategy to be f(i) = i^2 . Insert 22,30 and 50.

CODE:

```
#include <stdio.h>

#define SIZE 7

int main()
{
    int hash[SIZE];
    int keys[] = {22, 30, 50};
    int i, j, index;


    for (i = 0; i < SIZE; i++)
        hash[i] = -1;


for (i = 0; i < 3; i++)
{
    index = keys[i] % SIZE;


    for (j = 0; j < SIZE; j++)
```

Scanned with OKEN Scanner

```
{
    index = (keys[i] % SIZE + j * j) % SIZE;

    if (hash[index] == -1)
    {
        hash[index] = keys[i];
            break;
        }
    }
}

printf("Hash Table:\n");
for (i = 0; i < SIZE; i++)
    printf("%d : %d\n", i, hash[i]);

    return 0;
}
```

OUTPUT:

main.c | Output

```
Hash Table:
0 : -1
1 : 22
2 : 30
3 : -1
4 : -1
5 : 50
6 : -1
```

Scanned with OKEN Scanner

7)Insert the keys 27,43,692,72 into hash table of size 7 where first hash function is h1(k)= k mod 7 and second hash function is h2(k)= 1+(k mod 5) using double hashing technique.

CODE:

```
#include <stdio.h>


#define SIZE 7

int main()
{
    int hash[SIZE];
    int keys[] = {27, 43, 69, 2, 72};
    int i, j, index, h1, h2;


    for (i = 0; i < SIZE; i++)
        hash[i] = -1;

for (i = 0; i < 5; i++)
{
    h1 = keys[i] % SIZE;
    h2 = 1 + (keys[i] % 5);


    for (j = 0; j < SIZE; j++)
    {
        index = (h1 + j * h2) % SIZE;

if (hash[index] == -1)
{
    hash[index] = keys[i];
    break;
```

Scanned with OKEN Scanner

```
        }
    }
}

printf("Hash Table:\n");
for (i = 0; i < SIZE; i++)
    printf("%d : %d\n", i, hash[i]);

    return 0;
}
```

OUTPUT:

main.c | Output

```
Hash Table:
0 : -1
1 : 43
2 : 2
3 : -1
4 : 69
5 : 72
6 : 27
```

8)"If quadratic probing is used and the table size is prime, then a new element can always be inserted if the table is at least half empty."

Proof

Let the hash table size be \(m\), where \(m\) is a prime number.

In quadratic probing, the positions checked are

h(x), h(x)+1^2, h(x)+2^2, h(x)+3^2,…….

All positions are calculated modulo \(m\).

1. Since the table size m is prime, the first (m+1)/2 probe positions are distinct.

Scanned with OKEN Scanner

2. Therefore, quadratic probing can check at least half of the table's positions without repeating any position.

3. Since the table is at least half empty, at least one of these positions must be empty.

4. Hence, the new element can be inserted into that empty position.

Hence proved.

In simple words: Quadratic probing checks different positions. If at least half the table is empty, one of the positions it checks must be empty, so insertion is possible.

9) Implement a hash data structure and write initialize , find and insert routine for separate chaining hash table creation

CODE:

```
#include <stdio.h>

#include <stdlib.h>

#define SIZE 10


struct node

{

   int data;

   struct node *next;

};


struct node *hashTable[SIZE];

/* Initialize hash table */

void initialize()

{

   int i;
```

Scanned with OKEN Scanner

```
    for (i = 0; i < SIZE; i++)
        hashTable[i] = NULL;
}

/* Hash function */
int hash(int key)
{
    return key % SIZE;
}

/* Find an element */
struct node *find(int key)
{
    int index = hash(key);
    struct node *temp = hashTable[index];

while (temp != NULL)
{
    if (temp->data == key)
        return temp;

    temp = temp->next;
}
    return NULL;
}
void insert(int key)
{
```

Scanned with OKEN Scanner

```
int index = hash(key);
struct node *newNode;

if (find(key) != NULL)
{
    printf("Element already exists\n");
    return;
}

newNode = (struct node *)malloc(sizeof(struct node));
if (newNode == NULL)
{
    printf("Memory allocation failed\n");
    return;
}
    newNode->data = key;
    newNode->next = hashTable[index];
    hashTable[index] = newNode;

    printf("Element inserted successfully\n");
}
void display()
{
    int i;
struct node *temp;

for (i = 0; i < SIZE; i++)
{
    printf("%d: ", i);
```

Scanned with OKEN Scanner

```
temp = hashTable[i];

while (temp != NULL)
{
    printf("%d -> ", temp->data);
    temp = temp->next;
        }

        printf("NULL\n");
    }
}

int main()
{
    int choice, key;

initialize();

while (1)
{
    printf("\n1. Insert\n2. Find\n3. Display\n4. Exit\n");
    printf("Enter choice: ");
    scanf("%d", &choice);

switch (choice)
{
    case 1:
        printf("Enter element: ");
        scanf("%d", &key);
```

Scanned with OKEN Scanner

```
            insert(key);
            break;

        case 2:
            printf("Enter element to find: ");
            scanf("%d", &key);
            if (find(key) != NULL)
                printf("Element found\n");
            else
                printf("Element not found\n");
            break;

        case 3:
            display();
            break;

        case 4:
            return 0;

        default:
            printf("Invalid choice\n");
    }
}
```

OUTPUT:

Scanned with OKEN Scanner

```
1. Insert
2. Find
3. Display
4. Exit
Enter choice: 1
Enter element: 15
Element inserted successfully
Enter choice: 1
Enter element: 25
Element inserted successfully
Enter choice: 3
0: NULL
1: NULL
2: NULL
3: NULL
4: NULL
5: 25 -> 15 -> NULL
6: NULL
7: NULL
8: NULL
9: NULL
Enter choice:
```

Scanned with OKEN Scanner