

Data structures

Homework - 4

1. Implement a Stack using Queue data structure.

```
#include <stdio.h>

#define MAX 100

int queue[MAX];
int front = 0, rear = -1;

void enqueue(int x)
{
    queue[++rear] = x;
}

int dequeue()
{
    return queue[front++];
}

void push(int x)
{
    int i, n;

    n = rear - front + 1;

    enqueue(x);

    for (i = 0; i < n; i++)
    {
        enqueue(dequeue());
    }
}

int pop()
{
    if (front > rear)
    {
        printf("Stack Underflow\n");
        return -1;
    }

    return dequeue();
}
```

```

void display()
{
    int i;

    if (front > rear)
    {
        printf("Stack is Empty\n");
        return;
    }

    printf("Stack: ");

    for (i = front; i <= rear; i++)
    {
        printf("%d ", queue[i]);
    }

    printf("\n");
}

int main()
{
    int choice, x;

    while (1)
    {
        printf("\n1. Push\n");
        printf("2. Pop\n");
        printf("3. Display\n");
        printf("4. Exit\n");

        printf("Enter your choice: ");
        scanf("%d", &choice);

        switch (choice)
        {
            case 1:
                printf("Enter element: ");
                scanf("%d", &x);
                push(x);
                break;

            case 2:
                x = pop();

                if (x != -1)
                    printf("Popped element: %d\n", x);

                break;

```

```

        case 3:
            display();
            break;

        case 4:
            return 0;

        default:
            printf("Invalid choice\n");
    }
}

return 0;
}

```

Output :

```

1. Push
2. Pop
3. Display
4. Exit
Enter your choice: 1
Enter element: 10

```

```

1. Push
2. Pop
3. Display
4. Exit
Enter your choice: 1
Enter element: 20

```

```

1. Push
2. Pop
3. Display
4. Exit
Enter your choice: 1
Enter element: 30

```

```

1. Push
2. Pop
3. Display
4. Exit
Enter your choice: 2
Popped element: 30

```

```

1. Push
2. Pop
3. Display
4. Exit

```

Enter your choice: 3

Stack: 20 10

1. Push

2. Pop

3. Display

4. Exit

Enter your choice: 4

=== Code Execution Successful ===

2. Implement a Queue using Stack data structure.

```
#include <stdio.h>
```

```
#define MAX 100
```

```
int s1[MAX], s2[MAX];
```

```
int top1 = -1, top2 = -1;
```

```
void push1(int x)
```

```
{  
    s1[++top1] = x;  
}
```

```
int pop1()
```

```
{  
    return s1[top1--];  
}
```

```
void push2(int x)
```

```
{  
    s2[++top2] = x;  
}
```

```
int pop2()
```

```
{  
    return s2[top2--];  
}
```

```
void enqueue(int x)
```

```
{  
    if (top1 == MAX - 1)  
    {  
        printf("Queue Overflow\n");  
        return;  
    }  
}
```

```
    push1(x);
```

```

}

int dequeue()
{
    int x;

    if (top1 == -1 && top2 == -1)
    {
        printf("Queue Underflow\n");
        return -1;
    }

    if (top2 == -1)
    {
        while (top1 != -1)
        {
            x = pop1();
            push2(x);
        }
    }

    return pop2();
}

void display()
{
    int i;

    if (top1 == -1 && top2 == -1)
    {
        printf("Queue is Empty\n");
        return;
    }

    printf("Queue: ");

    for (i = top2; i >= 0; i--)
        printf("%d ", s2[i]);

    for (i = 0; i <= top1; i++)
        printf("%d ", s1[i]);

    printf("\n");
}

int main()
{
    int choice, x;

    while (1)

```

```

{
    printf("\n1. Enqueue\n");
    printf("2. Dequeue\n");
    printf("3. Display\n");
    printf("4. Exit\n");

    printf("Enter your choice: ");
    scanf("%d", &choice);

    switch (choice)
    {
        case 1:
            printf("Enter element: ");
            scanf("%d", &x);
            enqueue(x);
            break;

        case 2:
            x = dequeue();

            if (x != -1)
                printf("Dequeued element: %d\n", x);

            break;

        case 3:
            display();
            break;

        case 4:
            return 0;

        default:
            printf("Invalid choice\n");
    }
}

return 0;
}

```

Output :

```

1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 1
Enter element: 10

```

1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 1
Enter element: 20

1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 1
Enter element: 30

1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 3
Queue: 10 20 30

1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 2
Dequeued element: 10

1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 3
Queue: 20 30

1. Enqueue
2. Dequeue
3. Display
4. Exit
Enter your choice: 4

=== Code Execution Successful ===

3. Write a C program using stack data structure to implement managing the history of web pages visited.

```
#include <stdio.h>  
#include <string.h>
```

```

#define MAX 100

char history[MAX][100];
int top = -1;

void visit(char page[])
{
    if (top == MAX - 1)
    {
        printf("History is Full\n");
        return;
    }

    top++;
    strcpy(history[top], page);

    printf("Visited: %s\n", page);
}

void back()
{
    if (top == -1)
    {
        printf("No previous page\n");
        return;
    }

    printf("Going back from: %s\n", history[top]);
    top--;

    if (top != -1)
        printf("Current page: %s\n", history[top]);
    else
        printf("No page in history\n");
}

void display()
{
    int i;

    if (top == -1)
    {
        printf("History is Empty\n");
        return;
    }

    printf("\nWeb Page History:\n");

    for (i = top; i >= 0; i--)
    {

```



```

        printf("%s\n", history[i]);
    }
}

int main()
{
    int choice;
    char page[100];

    while (1)
    {
        printf("\n1. Visit Page\n");
        printf("2. Back\n");
        printf("3. Display History\n");
        printf("4. Exit\n");

        printf("Enter your choice: ");
        scanf("%d", &choice);

        switch (choice)
        {
            case 1:
                printf("Enter web page: ");
                scanf("%s", page);
                visit(page);
                break;

            case 2:
                back();
                break;

            case 3:
                display();
                break;

            case 4:
                return 0;

            default:
                printf("Invalid choice\n");
        }
    }

    return 0;
}

```

Output :

1. Visit Page

2. Back
3. Display History
4. Exit
Enter your choice: 1
Enter web page: GOOGLE
Visited: GOOGLE

1. Visit Page
2. Back
3. Display History
4. Exit
Enter your choice: 1
Enter web page: insta
Visited: insta

1. Visit Page
2. Back
3. Display History
4. Exit
Enter your choice: 1
Enter web page: yt
Visited: yt

1. Visit Page
2. Back
3. Display History
4. Exit
Enter your choice: 2
Going back from: yt
Current page: insta

1. Visit Page
2. Back
3. Display History
4. Exit
Enter your choice: 3

Web Page History:
insta
GOOGLE

1. Visit Page
2. Back
3. Display History
4. Exit
Enter your choice: 4

=== Code Execution Successful ===

4. Write a C program to sort a stack using temporary stack (implement using stack).

```
#include <stdio.h>
```

```
#define MAX 100
```

```
int stack[MAX], temp[MAX];  
int top = -1, ttop = -1;
```

```
void push(int x)  
{  
    stack[++top] = x;  
}
```

```
int pop()  
{  
    return stack[top--];  
}
```

```
void tpush(int x)  
{  
    temp[++ttop] = x;  
}
```

```
int tpop()  
{  
    return temp[ttop--];  
}
```

```
void sortStack()  
{  
    int x;  
  
    while (top != -1)  
    {  
        x = pop();  
  
        while (ttop != -1 && temp[ttop] > x)  
        {  
            push(tpop());  
        }  
  
        tpush(x);  
    }  
    while (ttop != -1)  
    {  
        push(tpop());  
    }  
}
```

```

void display()
{
    int i;

    printf("Stack: ");

    for (i = top; i >= 0; i--)
    {
        printf("%d ", stack[i]);
    }

    printf("\n");
}

int main()
{
    int n, i, x;

    printf("Enter number of elements: ");
    scanf("%d", &n);

    printf("Enter elements:\n");

    for (i = 0; i < n; i++)
    {
        scanf("%d", &x);
        push(x);
    }

    printf("\nOriginal Stack: ");
    display();

    sortStack();

    printf("Sorted Stack: ");
    display();

    return 0;
}

```

Output :

```

Enter number of elements: 5
Enter elements:
12
23
34
45
6

```

Original Stack: Stack: 6 45 34 23 12
Sorted Stack: Stack: 6 12 23 34 45

=== Code Execution Successful ===

5. The Stock Span Problem is a financial problem where we have a series of daily price quotes for a stock denoted by an array and the task is to calculate the span of the stock's price for all days. The span of a stock's price for i^{th} day gives the maximum number of consecutive days leading up to i^{th} day (including current day) where stock's price is less than or equal to its price on day i .

Input (I/p): [100, 80, 60, 70, 60, 75, 85]

Output (O/p): [1, 1, 1, 2, 1, 4, 6]

```
#include <stdio.h>
```

```
#define MAX 100
```

```
int main()
```

```
{
```

```
    int price[MAX], span[MAX];
```

```
    int stack[MAX];
```

```
    int top = -1;
```

```
    int n, i;
```

```
    printf("Enter number of days: ");
```

```
    scanf("%d", &n);
```

```
    printf("Enter stock prices:\n");
```

```
    for (i = 0; i < n; i++)
```

```
    {
```

```
        scanf("%d", &price[i]);
```

```
    }
```

```
    for (i = 0; i < n; i++)
```

```
    {
```

```

while (top != -1 && price[stack[top]] <= price[i])
{
    top--;
}
if (top == -1)
    span[i] = i + 1;
else
    span[i] = i - stack[top];
stack[++top] = i;
}
printf("Stock Span: ");
for (i = 0; i < n; i++)
{
    printf("%d ", span[i]);
}
return 0;
}

```

Output :

Enter number of days: 7

Enter stock prices:

100

80

60

70

60

75

85

Stock Span: 1 1 1 2 1 4 6

=== Code Execution Successful ===

6. Given an array, for each element find the nearest element to its right that has a higher frequency than the current element. If no such element exists, set value to -1. Implement using stack.

Input (I/p): [2, 1, 1, 3, 2, 1]

Output (O/p): [1, -1, -1, 2, 1, -1]

```
#include <stdio.h>
```

```
#define MAX 100
```

```
int main()
```

```
{
```

```
    int arr[MAX], freq[MAX];
```

```
    int stack[MAX], result[MAX];
```

```
    int n, i, j;
```

```
    int top = -1;
```

```
    printf("Enter number of elements: ");
```

```
    scanf("%d", &n);
```

```
    printf("Enter elements:\n");
```

```
    for (i = 0; i < n; i++)
```

```
    {
```

```
        scanf("%d", &arr[i]);
```

```
    }
```

```
    for (i = 0; i < n; i++)
```

```

{
    freq[i] = 0;
    for (j = 0; j < n; j++)
    {
        if (arr[i] == arr[j])
        {
            freq[i]++;
        }
    }
}

for (i = n - 1; i >= 0; i--)
{
    while (top != -1 &&
           freq[stack[top]] <= freq[i])
    {
        top--;
    }

    if (top == -1)
        result[i] = -1;
    else
        result[i] = arr[stack[top]];

    stack[++top] = i;
}

printf("Output: ");
for (i = 0; i < n; i++)

```



```

{
    printf("%d ", result[i]);
}

return 0;
}

```

Output :

Enter number of elements: 6

Enter elements:

2

1

1

3

2

1

Output: 1 -1 -1 2 1 -1

=== Code Execution Successful ===

7. Given a pattern containing only 'I's and 'D's. 'I' for Increasing and 'D' for Decreasing. Devise an algorithm using stack to print minimum number following that pattern. Digits from 1–9 and digits can't repeat.

- Input: D -> Output: 21
- Input: I -> Output: 12
- Input: IDID -> Output: 21435

```
#include <stdio.h>
```

```
#define MAX 100
```

```
int main()

{

    char pattern[MAX];

    int stack[MAX];

    int top = -1;

    int num = 1;

    int i;

    printf("Enter pattern: ");

    scanf("%s", pattern);

    printf("Output: ");

    for (i = 0; pattern[i] != '\0'; i++)

    {

        stack[++top] = num++;

        if (pattern[i] == 'T')

        {

            while (top != -1)

            {

                printf("%d", stack[top--]);

            }

        }

        stack[++top] = num++;

    }

    while (top != -1)

    {

        printf("%d", stack[top--]);

    }

}
```

```

    }

    return 0;

}

```

Output :

Enter pattern: D

Output: 21

=== Code Execution Successful ===

8. Given an array of digits (values are from 0 to 9), find the minimum possible sum of two numbers formed from digits of the array. All digits of given array must be used to form the two numbers. Use Queue for implementation.

- Input (I/p): [6, 8, 4, 5, 2, 3]
- Output (O/p): 604 (*min sum formed by numbers 358 and 246*)

```

#include <stdio.h>

#define MAX 100

int queue[MAX];

int front = 0, rear = -1;

void enqueue(int x)
{
    queue[++rear] = x;
}

int dequeue()
{
    return queue[front++];
}

int main()
{

```

```
int n, i, j, temp;

int num1 = 0, num2 = 0;

printf("Enter number of digits: ");

scanf("%d", &n);

printf("Enter digits:\n");

for(i = 0; i < n; i++)

{

    scanf("%d", &queue[i]);

}

rear = n - 1;

for(i = 0; i < n - 1; i++)

{

    for(j = i + 1; j < n; j++)

    {

        if(queue[i] > queue[j])

        {

            temp = queue[i];

            queue[i] = queue[j];

            queue[j] = temp;

        }

    }

}

for(i = 0; i < n; i++)

{

    if(i % 2 == 0)
```

```

        num1 = num1 * 10 + dequeue();

    else

        num2 = num2 * 10 + dequeue();

    }

    printf("Minimum Sum = %d\n", num1 + num2);

    return 0;

}

```

Output :

Enter number of digits: 6

Enter digits:

6

8

4

5

2

3

Minimum Sum = 604

=== Code Execution Successful ===

9. Given an array and a positive integer k, find the first negative integer for each window (contiguous subarray) of size k. If a window does not contain a negative integer, then print 0 for that window. Implement using queue.

• Example:

Input (I/p): [-8, 2, 3, -6, 10], k = 2

Output (O/p): [-8, 0, -6, -6]

• Explanation (First negative integer for each window of size 2):

[-8, 2] -> -8

[2, 3] -> 0 (*No negative*)

[3, -6] -> -6

[-6, 10] -> -6

```
#include <stdio.h>

#define MAX 100

int main()
{
    int arr[MAX], queue[MAX];

    int front = 0, rear = -1;

    int n, k, i;

    printf("Enter number of elements: ");

    scanf("%d", &n);

    printf("Enter elements:\n");

    for(i = 0; i < n; i++)

        scanf("%d", &arr[i]);

    printf("Enter window size: ");

    scanf("%d", &k);

    printf("Output: ");

    for(i = 0; i < n; i++)
    {
        if(arr[i] < 0)

            queue[++rear] = i;

        if(front <= rear && queue[front] <= i - k)
```

```

        front++;
    if(i >= k - 1)
    {
        if(front <= rear)
            printf("%d ", arr[queue[front]]);
        else
            printf("0 ");
    }
}

return 0;
}

```

Output :

Enter number of elements: 5

Enter elements:

-8

2

3

-6

10

Enter window size: 2

Output: -8 0 -6 -6

=== Code Execution Successful ===

10. Given a matrix of dimension $m \times n$ where each cell in the matrix can have values 0, 1, or 2 which has the following meaning:

0: Empty cell

1: Cells having fresh oranges

2: Cells having rotten oranges

The task is to find the minimum time required so that all oranges become rotten. A rotten orange at index (i, j) can rot other fresh oranges which are its neighbours (up, down, left and right). If impossible to rot every orange then return -1. Use Queue for implementation.

· Input (I/p): [[2, 1, 0, 2, 1], [1, 0, 1, 2, 1], [1, 0, 0, 2, 1]]

· Output (O/p): 2

· Explanation:

At 0th frame:

$$\begin{bmatrix} 2 & 1 & 0 & 2 & 1 \\ 1 & 0 & 1 & 2 & 1 \\ 1 & 0 & 0 & 2 & 1 \end{bmatrix}$$

At 1th frame:

$$\begin{bmatrix} 2 & 2 & 0 & 2 & 2 \\ 2 & 0 & 2 & 2 & 2 \\ 1 & 0 & 0 & 2 & 2 \end{bmatrix}$$

At 2th frame:

$$\begin{bmatrix} 2 & 2 & 0 & 2 & 2 \\ 2 & 0 & 2 & 2 & 2 \\ 2 & 0 & 0 & 2 & 2 \end{bmatrix}$$

```
#include <stdio.h>
```



```
#define MAX 100

struct Node

{

    int row;

    int col;

    int time;

};

int main()

{

    int a[MAX][MAX];

    struct Node queue[MAX * MAX];

    int front = 0, rear = -1;

    int r, c, i, j;

    int fresh = 0;

    int time = 0;

    printf("Enter rows and columns: ");

    scanf("%d %d", &r, &c);

    printf("Enter matrix:\n");

    for(i = 0; i < r; i++)

    {

        for(j = 0; j < c; j++)

        {

            scanf("%d", &a[i][j]);

            if(a[i][j] == 1)

                fresh++;

        }

    }

}
```

```

        if(a[i][j] == 2)
        {
            rear++;

            queue[rear].row = i;

            queue[rear].col = j;

            queue[rear].time = 0;

        }
    }

while(front <= rear)
{
    struct Node current = queue[front++];

    int x = current.row;

    int y = current.col;

    int t = current.time;

    if(t > time)

        time = t;

    if(x > 0 && a[x-1][y] == 1)
    {
        a[x-1][y] = 2;

        fresh--;

        rear++;

        queue[rear].row = x-1;

        queue[rear].col = y;

        queue[rear].time = t + 1;
    }
}

```

```

    }

    if(x < r-1 && a[x+1][y] == 1)
    {
        a[x+1][y] = 2;

        fresh--;

        rear++;

        queue[rear].row = x+1;

        queue[rear].col = y;

        queue[rear].time = t + 1;
    }

    if(y > 0 && a[x][y-1] == 1)
    {
        a[x][y-1] = 2;

        fresh--;

        rear++;

        queue[rear].row = x;

        queue[rear].col = y-1;

        queue[rear].time = t + 1;
    }

    if(y < c-1 && a[x][y+1] == 1)
    {
        a[x][y+1] = 2;

        fresh--;

        rear++;

        queue[rear].row = x;

```

```

        queue[rear].col = y+1;

        queue[rear].time = t + 1;

    }

}

if(fresh > 0)

    printf("Minimum Time = -1\n");

else

    printf("Minimum Time = %d\n", time);

return 0;

}

```

Output :

Enter rows and columns: 3

5

Enter matrix:

2

1

0

2

1

1

0

1

2

1

1

0

0

2

1

Minimum Time = 2

=== Code Execution Successful ===