

DS Homework 2

Name: Thirumurgan

Register Number: 2025115306

1. Define an integer array. Declare an integer pointer and initialize it to point to the first element of the array. Use pointer arithmetic to traverse the array and modify the elements of the array.

code:

```
#include <stdio.h>
int main()
{
    int arr[5] = {20, 30, 40, 50, 60};
    int *ptr;
    ptr = arr;
    printf("Original array: ");
    for(int i = 0; i < 5; i++)
    {
        printf("%d ", *(ptr + i));
    }
    for(int i = 0; i < 5; i++)
    {
        *(ptr + i) = *(ptr + i) + 5;
    }
    printf("\nModified array: ");
    for(int i = 0; i < 5; i++)
    {
        printf("%d ", *(ptr + i));
    }
    return 0;
}
```

output:

Original array: 20 30 40 50 60

Modified array: 25 35 45 55 65

2. Calculate string length using pointer

code:

```
#include <stdio.h>
int main()
{
    char str[100];
    char *p;
    int length = 0;
    printf("Enter a string: ");
    scanf("%s", str);
    p = str;
    while(*p != '\0')
    {
        length++;
        p++;
    }
    printf("Length of string = %d", length);
    return 0;
}
```

output:

Enter a string: thirumurugan

Length of string = 11

3. Write a function that calculates the sum and product of two numbers. Return these two results using pointers passed as arguments to the function.

code:

```
#include <stdio.h>
void calculate(int a, int b, int *sum, int *product)
{
    *sum = a + b;
    *product = a * b;
}
int main()
{
    int a, b, sum, product;
    printf("Enter two numbers: ");
    scanf("%d %d", &a, &b);
    calculate(a, b, &sum, &product);
    printf("Sum = %d\n", sum);
    printf("Product = %d\n", product);
    return 0;
}
```

output:

Enter two numbers: 10 6

Sum = 16

Product = 60

4. Create an array of structures. Use dynamic memory allocation to allocate memory space and use a structure pointer with pointer arithmetic to iterate and access/modify members.

code:

```
#include <stdio.h>
#include <stdlib.h>
struct Student
{
    int id;
    float mark;
};
int main()
{
    struct Student *p;
    int n, i;
    printf("Enter number of students: ");
    scanf("%d", &n);
    p = (struct Student *)malloc(n * sizeof(struct Student));
    for(i = 0; i < n; i++)
    {
        printf("Enter ID and mark for student %d: ", i + 1);
        scanf("%d %f", &(p + i)->id, &(p + i)->mark);
    }
    printf("\nStudent Details:\n");
    for(i = 0; i < n; i++)
    {
        printf("ID = %d, Mark = %.2f\n",
            (p + i)->id, (p + i)->mark);
    }
    free(p);
    return 0;
}
```

output:

Enter number of students: 2

Enter ID and mark for student 1: 10

98

Enter ID and mark for student 2: 18

87

Student Details:

ID = 10, Mark = 98.00

ID = 18, Mark = 87.00

5. Define two functions with same signature. Declare a function pointer and use it to call both functions.

code:

```
#include <stdio.h>
void add(int a, int b)
{
    printf("Addition = %d\n", a + b);
}
void multiply(int a, int b)
{
    printf("Multiplication = %d\n", a * b);
}
int main()
{
    void (*ptr)(int, int);
    ptr = add;
    ptr(10, 8);
    ptr = multiply;
    ptr(10, 8);
    return 0;
}
```

output:

Addition = 18

Multiplication = 80

6. Declare an integer, a pointer and a double pointer. Print the values and addresses at each level.

code:

```
#include <stdio.h>
int main()
{
    int x = 18;
    int *p;
    int **q;
    p = &x;
    q = &p;
    printf("Value of x = %d\n", x);
    printf("Value using pointer = %d\n", *p);
    printf("Value using double pointer = %d\n", **q);
    printf("Address of x = %p\n", (void *)&x);
    printf("Address stored in p = %p\n", (void *)p);
    printf("Address stored in q = %p\n", (void *)q);
    return 0;
}
```

output:

Value of x = 18

Value using pointer = 18

Value using double pointer = 18

Address of x = 0x7ff...

Address stored in p = 0x7ff...

Address stored in q = 0x7ff...

7.Sort an array of floating point numbers using Selection Sort.**code:**

```
#include <stdio.h>
int main()
{
    float a[3];
    int i, j, min;
    float temp;
    printf("Enter 3 floating point numbers:\n");
    for(i = 0; i < 3; i++)
        scanf("%f", &a[i]);
    for(i = 0; i < 3; i++)
    {
        min = i;
        for(j = i + 1; j < 3; j++)
        {
            if(a[j] < a[min])
                min = j;
        }
        temp = a[i];
        a[i] = a[min];
        a[min] = temp;
    }
    printf("Sorted array:\n");

    for(i = 0; i < 3; i++)
        printf("%.2f ", a[i]);
    return 0;
}
```

output:

Enter 3 floating point numbers:

5.5

2.2

4.4

Sorted array:

2.20 4.40 5.50

8.Define a structure (Student with id, name and grade). Create an array of student structures and sort them based on different fields.**code:**

```
#include <stdio.h>
```

```

#include <string.h>
struct Student
{
    int id;
    char name[20];
    float grade;
};
int main()
{
    struct Student s[2], temp;
    int i, j, choice;
    printf("Enter details of 2 students:\n");
    for(i = 0; i < 2; i++)
    {
        printf("\nStudent %d\n", i + 1);
        printf("Enter ID: ");
        scanf("%d", &s[i].id);
        printf("Enter Name: ");
        scanf("%s", s[i].name);
        printf("Enter Grade: ");
        scanf("%f", &s[i].grade);
    }
    printf("\nSort based on:\n");
    printf("1. ID\n");
    printf("2. Name\n");
    printf("3. Grade\n");
    printf("Enter your choice: ");
    scanf("%d", &choice);
    for(i = 0; i < 2; i++)
    {
        for(j = i + 1; j < 2; j++)
        {
            int swap = 0;
            if(choice == 1 && s[i].id > s[j].id)
                swap = 1;
            else if(choice == 2 && strcmp(s[i].name, s[j].name) > 0)
                swap = 1;
            else if(choice == 3 && s[i].grade > s[j].grade)
                swap = 1;
            if(swap)
            {
                temp = s[i];
                s[i] = s[j];
                s[j] = temp;
            }
        }
    }
    printf("\nSorted Student Details:\n");
    printf("ID\tName\tGrade\n");
    for(i = 0; i < 2; i++)
    {
        printf("%d\t%s\t%.2f\n",
            s[i].id, s[i].name, s[i].grade);
    }
    return 0;
}

```

output:

Enter details of 2 students:

Student 1

Enter ID: 102

Enter Name: Ravi

Enter Grade: 8.5

Student 2

Enter ID: 101

Enter Name: Arun

Enter Grade: 9.2

Sort based on:

1. ID

2. Name

3. Grade

Enter your choice: 1

Sorted Student Details:

ID Name Grade

101 Arun 9.20

102 Ravi 8.50

9.Sort a set of negative numbers using radix sort.

code:

```
#include <stdio.h>
#include <stdlib.h>
void radixSort(int a[], int n)
{
    int i, j, max, exp = 1;
    int *b = (int *)malloc(n * sizeof(int));
    max = abs(a[0]);
    for (i = 1; i < n; i++)
    {
        if (abs(a[i]) > max)
            max = abs(a[i]);
    }
    while (max / exp > 0)
    {
        int count[10] = {0};
        for (i = 0; i < n; i++)
            count[(abs(a[i]) / exp) % 10]++;
        for (i = 1; i < 10; i++)
            count[i] += count[i - 1];
        for (i = n - 1; i >= 0; i--)
            b[--count[(abs(a[i]) / exp) % 10]] = a[i];
        for (i = 0; i < n; i++)
            a[i] = b[i];
        exp *= 10;
    }
    for (i = 0; i < n; i++)
        a[i] = -abs(a[i]);
    free(b);
}
int main()
{
    int a[] = {-45, -12, -89, -34, -7};
    int n = 5, i;
    radixSort(a, n);
    printf("Sorted array:\n");
    for (i = 0; i < n; i++)
        printf("%d ", a[i]);
    return 0;
}
```

output:

Sorted array:

-7 -12 -34 -45 -89

10. Write a C program to copy one array to another using pointers

code:

```
#include <stdio.h>
int main()
{
    int a[3], b[3];
    int i;
    int *p, *q;
    printf("Enter 3 elements:\n");
    for (i = 0; i < 3; i++)
        scanf("%d", &a[i]);
    p = a;
    q = b;
    for (i = 0; i < 3; i++)
    {
        *q = *p;
        p++;
        q++;
    }
    printf("First array:\n");
    for (i = 0; i < 3; i++)
        printf("%d ", a[i]);
    printf("\nSecond array:\n");
    for (i = 0; i < 3; i++)
        printf("%d ", b[i]);
    return 0;
}
```

output:

Enter 3 elements:

10

20

30

First array:

10 20 30

Second array:

10 20 30