
# ML/DL for Everyone Season2




Lab 11-4 CNN with MNIST Dataset using Model Ensemble



# NN Implementation Flow in TensorFlow

- 1. Set hyper parameters learning rate, training epochs, batch size, etc.
- 2. Make a data pipelining use tf.data
- 3. Build a neural network model use tf.keras
- Define a loss function cross entropy
- 5. Calculate a gradient use tf. Gradient Tape
- 6. Select an optimizer Adam optimizer
- 7. Define a metric for model's performance accuracy
- 8. (optional) Make a checkpoint for saving
- 9. Train and Validate a neural network model

## **CNN Model Ensemble with MNIST Data**



## **0. Import Libraries**

```
import tensorflow as tf
from tensorflow import keras
from tensorflow.keras.utils import to_categorical
import numpy as np
import matplotlib.pyplot as plt
import os
```

## 1. Set Hyper Parameters

```
learning rate = 0.001
training epochs = 15
batch size = 100
cur dir = os.getcwd()
ckpt dir name = 'checkpoints'
model dir name = 'minst cnn ensemble'
checkpoint dir = os.path.join(cur dir, ckpt dir name, model dir name)
os.makedirs(checkpoint dir, exist ok=True)
checkpoint prefix = os.path.join(checkpoint dir, model dir name)
```

# 2. Make a Data Pipelining

```
mnist = keras.datasets.mnist
(train_images, train_labels), (test_images, test_labels) = mnist.load_data()
train images = train images.astype(np.float32) / 255.
test images = test images.astype(np.float32) / 255.
train images = np.expand dims(train images, axis=-1)
test images = np.expand dims(test images, axis=-1)
train labels = to categorical(train labels, 10)
test labels = to categorical(test labels, 10)
train dataset = tf.data.Dataset.from tensor slices((train images,
        train labels)).shuffle(buffer size=100000).batch(batch size)
test_dataset = tf.data.Dataset.from_tensor_slices((test_images,
        test labels)).batch(batch size)
```

#### 3. Build a Neural Network Model


## Model Subclassing

```
class MNISTModel(tf.keras.Model):
   def init (self):
       super(MNISTModel, self).__init ()
       self.conv1 = keras.layers.Conv2D(filters=32, kernel size=3, padding='SAME',
        activation=tf.nn.relu)
       self.pool1 = keras.layers.MaxPool2D(padding='SAME')
       self.conv2 = keras.layers.Conv2D(filters=64, kernel size=3, padding='SAME',
        activation=tf.nn.relu)
       self.pool2 = keras.layers.MaxPool2D(padding='SAME')
       self.conv3 = keras.layers.Conv2D(filters=128, kernel size=3, padding='SAME',
        activation=tf.nn.relu)
       self.pool3 = keras.layers.MaxPool2D(padding='SAME')
       self.pool3 flat = keras.layers.Flatten()
       self.dense4 = keras.layers.Dense(units=256, activation=tf.nn.relu)
       self.drop4 = keras.layers.Dropout(rate=0.4)
       self.dense5 = keras.layers.Dense(units=10)
```

#### 3. Build a Neural Network Model

### Model Subclassing

```
def call(self, inputs, training=False):
       net = self.conv1(inputs)
       net = self.pool1(net)
       net = self.conv2(net)
       net = self.pool2(net)
       net = self.conv3(net)
       net = self.pool3(net)
       net = self.pool3 flat(net)
       net = self.dense4(net)
       net = self.drop4(net)
       net = self.dense5(net)
       return net
models = []
num models = 3
for m in range(num models):
   models.append(MNISTModel())
```



# 4. Define a Loss Function5. Calculate a Gradient

```
def loss fn(model, images, labels):
   logits = model(images, training=True)
   loss = tf.reduce mean(tf.nn.softmax cross entropy with logits v2(
           logits=logits, labels=labels))
   return loss
def grad(model, images, labels):
   with tf.GradientTape() as tape:
       loss = loss fn(model, images, labels)
   return tape.gradient(loss, model.variables)
```

### 6. Select an Optimizer

# 7. Define a Metric for Model's Performance8. Make a Checkpoint for Saving

```
optimizer = tf.train.AdamOptimizer(learning rate=learning rate)
def evaluate(models, images, labels):
   predictions = tf.zeros like(labels)
   for model in models:
       logits = model(images, training=False)
       predictions += logits
   correct prediction = tf.equal(tf.argmax(predictions, 1),
                        tf.argmax(labels, 1))
   accuracy = tf.reduce mean(tf.cast(correct prediction, tf.float32))
   return accuracy
checkpoints = []
for m in range(num models):
   checkpoints.append(tf.train.Checkpoint(cnn=models[m]))
```

#### 9. Train and Validate a Neural Network Model

```
for epoch in range(training epochs):
   avg loss = 0.; avg train acc = 0.; avg test acc = 0.
   train step = 0; test step = 0
   for images, labels in train dataset:
       for model in models:
           grads = grad(model, images, labels)
           optimizer.apply gradients(zip(grads, model.variables))
           loss = loss_fn(model, images, labels)
           avg loss += loss / num models
       acc = evaluate(models, images, labels)
       avg_train_acc += acc
       train step += 1
   avg loss = avg loss / train step
   avg_train_acc = avg_train_acc / train_step
```

#### 9. Train and Validate a Neural Network Model

```
for images, labels in test_dataset:
      acc = evaluate(models, images, labels)
      avg test acc += acc
      test step += 1
  avg test acc = avg test acc / test step
  print('Epoch:', '{}'.format(epoch + 1), 'loss =', '{:.8f}'.format(avg_loss),
         'train accuracy = ', '{:.4f}'.format(avg train acc),
         'test accuracy = ', '{:.4f}'.format(avg test acc))
  for idx, checkpoint in enumerate(checkpoints):
       checkpoint.save(file prefix=checkpoint prefix+'-{}'.format(idx))
```

Accuracy: 99.47%

## What's Next?

Best CNN with MNIST Dataset