
CS 471/571 (Fall 2023): Introduction to Artificial Intelligence

Lecture 10: MDPs (Part 1)

Thanh H. Nguyen

Source: <http://ai.berkeley.edu/home.html>




Reminder

- Homework 2: CSPs and Games
 - Deadline: Oct 25th, 2023


- Project 2: Multi-agent Search
 - Deadline: November 03, 2023

Non-Deterministic Search




Example: Grid World

- A maze-like problem
 - The agent lives in a grid
 - Walls block the agent's path
- Noisy movement: actions do not always go as planned
 - 80% of the time, the action North takes the agent North (if there is no wall there)
 - 10% of the time, North takes the agent West; 10% East
 - If there is a wall in the direction the agent would have been taken, the agent stays put
- The agent receives rewards each time step
 - Small “living” reward each step (can be negative)
 - Big rewards come at the end (good or bad)
- Goal: maximize sum of rewards




Grid World Actions

Deterministic Grid World




Stochastic Grid World



Markov Decision Processes

- An MDP is defined by:
 - A set of states $s \in S$
 - A set of actions $a \in A$
 - A transition function $T(s, a, s')$
 - Probability that a from s leads to s' , i.e., $P(s' | s, a)$
 - Also called the model or the dynamics
 - A reward function $R(s, a, s')$
 - Sometimes just $R(s)$ or $R(s')$
 - A start state
 - Maybe a terminal state
- MDPs are non-deterministic search problems
 - One way to solve them is with expectimax search
 - We'll have a new tool soon



What is Markov about MDPs?

- “Markov” generally means that given the present state, the future and the past are independent
- For Markov decision processes, “Markov” means action outcomes depend only on the current state

$$\begin{aligned} &P(S_{t+1} = s' | S_t = s_t, A_t = a_t, S_{t-1} = s_{t-1}, A_{t-1}, \dots, S_0 = s_0) \\ &= \\ &P(S_{t+1} = s' | S_t = s_t, A_t = a_t) \end{aligned}$$

- This is just like search, where the successor function could only depend on the current state (not the history)




Andrey Markov
(1856-1922)



Policies


- In deterministic single-agent search problems, we wanted an optimal **plan**, or sequence of actions, from start to a goal
- For MDPs, we want an optimal **policy** π^* :
 $S \rightarrow A$
 - A policy π gives an action for each state
 - An optimal policy is one that maximizes expected utility if followed




Optimal policy when $R(s, a, s') = -0.03$ for all non-terminals s




Optimal Policies




$$R(s) = -0.01$$



$$R(s) = -0.03$$




$$R(s) = -0.4$$



$$R(s) = -2.0$$




Example: Racing




Example: Racing

- A robot car wants to travel far, quickly
- Three states: **Cool**, **Warm**, Overheated
- Two actions: *Slow*, *Fast*
- Going faster gets double reward




Racing Search Tree




MDP Search Trees

- Each MDP state projects an expectimax-like search tree




Utilities of Sequences



Utilities of Sequences

- What preferences should an agent have over reward sequences?
- More or less? $[1, 2, 2]$ or $[2, 3, 4]$
- Now or later? $[0, 0, 1]$ or $[1, 0, 0]$



Discounting

- It's reasonable to maximize the sum of rewards
- It's also reasonable to prefer rewards now to rewards later
- One solution: values of rewards decay exponentially



1

Worth Now



γ

Worth Next Step




γ^2

Worth In Two Steps



Discounting

- How to discount?
 - Each time we descend a level, we multiply in the discount once
- Why discount?
 - Sooner rewards probably do have higher utility than later rewards
 - Also helps our algorithms converge
- Example: discount of 0.5
 - $U([1,2,3]) = 1*1 + 0.5*2 + 0.25*3$
 - $U([1,2,3]) < U([3,2,1])$




Stationary Preferences

- Theorem: if we assume **stationary preferences**:

$$\begin{aligned} [a_1, a_2, \dots] &\succ [b_1, b_2, \dots] \\ &\iff \\ [r, a_1, a_2, \dots] &\succ [r, b_1, b_2, \dots] \end{aligned}$$

- Then: there are only two ways to define utilities

- Additive utility: $U([r_0, r_1, r_2, \dots]) = r_0 + r_1 + r_2 + \dots$
- Discounted utility: $U([r_0, r_1, r_2, \dots]) = r_0 + \gamma r_1 + \gamma^2 r_2 \dots$



Quiz: Discounting

- Given:

10				1
a	b	c	d	e

- Actions: East, West, and Exit (only available in exit states a, e)
- Transitions: deterministic
- Quiz 1: For $\gamma = 1$, what is the optimal policy?
- Quiz 2: For $\gamma = 0.1$, what is the optimal policy?
- Quiz 3: For which γ are West and East equally good when in state d?

10				1
----	--	--	--	---

10				1
----	--	--	--	---




Infinite Utilities?!

- Problem: What if the game lasts forever? Do we get infinite rewards?

- Solutions:

- Finite horizon: (similar to depth-limited search)
 - Terminate episodes after a fixed T steps (e.g. life)
 - Gives nonstationary policies (π depends on time left)



- Discounting: use $0 < \gamma < 1$


$$U([r_0, \dots, r_\infty]) = \sum_{t=0}^{\infty} \gamma^t r_t \leq R_{\max}/(1 - \gamma)$$

- Smaller γ means smaller “horizon” – shorter term focus
- Absorbing state: guarantee that for every policy, a terminal state will eventually be reached (like “overheated” for racing)




Recap: Defining MDPs

- Markov decision processes:
 - Set of states S
 - Start state s_0
 - Set of actions A
 - Transitions $P(s' | s, a)$ (or $T(s, a, s')$)
 - Rewards $R(s, a, s')$ (and discount γ)
- MDP quantities so far:
 - Policy = Choice of action for each state
 - Utility = sum of (discounted) rewards




Solving MDPs



Optimal Quantities

- The value (utility) of a state s :
 $V^*(s)$ = expected utility starting in s and acting optimally
- The value (utility) of a q-state (s,a) :
 $Q^*(s,a)$ = expected utility starting out having taken action a from state s and (thereafter) acting optimally
- The optimal policy:
 $\pi^*(s)$ = optimal action from state s




Snapshot of Demo – Gridworld V Values



Noise = 0.2
Discount = 0.9
Living reward = 0



Snapshot of Demo – Gridworld Q Values



Noise = 0.2
Discount = 0.9
Living reward = 0



Values of States

- Fundamental operation: compute the (expectimax) value of a state
 - Expected utility under optimal action
 - Average sum of (discounted) rewards
 - This is just what expectimax computed!

- Recursive definition of value:

$$V^*(s) = \max_a Q^*(s, a)$$

$$Q^*(s, a) = \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V^*(s')]$$

$$V^*(s) = \max_a \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V^*(s')]$$

