

BOME mapping installation guide for all Pioneer DDJ controllers

Installation video: https://youtu.be/MbGP_ECnWiQ

NOTE 1: *This guide covers all DDJ controllers.
The only difference is the Aliases (page 10) and Output (page 28).
The Annexes have specific pictures for specific DDJs.*

NOTE 2: *This mapping requires the third-party BOME midi translator.
It has a **free** trial for you to test this mapping before buying a license.*

NOTE 3: *Issues? See the FAQ in a pdf, the “gotchas” on page 34, and reconfirm if
you missed a step of this guide.*

Step #0


CONFIRM THAT REKORDBOX PERFORMANCE MODE WORKS PROPERLY IN YOUR SYSTEM!!

Driver Download: <https://www.pioneerdj.com/en/support/software/controller/ddj-1000/#drivers>

Firmware download: <https://www.pioneerdj.com/en/support/software/controller/ddj-1000/#firmware-update>

Rekordbox DJ download: <https://rekordbox.com/en/>

VirtualDJ Instructions (for reference): <https://www.virtualdj.com/manuals/hardware/pioneer/ddj1000/installation.html>



Step #1

BOME TRIAL: INSTALLATION

do not skip any step!


BOME SOFTWARE INSTALLATION:

1. Download and install the BOME trial from
<https://www.bome.com/products/miditranslator#downloads>

MAC-OS SECURITY ENABLE (see page 40 of the BOME manual):

1. **macOS 10.9** and later:
 1. System Preferences → Security & Privacy → Privacy → Accessibility -> Add "BOME"
2. **macOS 10.8** and earlier:
 1. System Preferences → Universal Access → check 'access for assistive devices'
3. **More info:** <https://www.maketecheasier.com/macOS-security-privacy-permissions/>

macOS security:



Step #2

MAP FOR BOME: INSTALLATION

do not skip any step!

PRELIMINARIES:


1. Stop Rekordbox
2. Stop Traktor
3. Expand all files in the zip file
4. Connect the USB cable
5. Turn on your DDJ

INSTALLING BOME MAPPING:

1. Open BOME. DO NOT RUN TRAKTOR!
2. Settings: Import the settings file
 1. Method: menu View; settings; export/import; import; select BMTS file
3. Mapping: load the mapping file
 1. Method: Click menu File; Open; select BMTP file
4. Do not mix up the Settings file with the Mapping file!




BOME: import settings file (BMTS file)





(Example for DDJ-1000; other DDJ are similar. See annexes for details)

BOME: import mapping file (BMTP file)



(Example for DDJ-1000; other DDJ are similar. See annexes for details)

BOME: Aliases



Replace this with your
DDJ-SX2/SZ/SRT etc!


BOME: Devices

Confirm the devices are OPEN!

Ensure ONLY these 2x options are checked:

- “From Traktor” -> device 1 in OPEN
- “to DDJ” -> DDJ-1000 OPEN

Confirm it looks EXACTLY like on the picture



Confirm this “cross” on EXACTLY these aliases

(Example for DDJ-1000; other DDJ are similar. See annexes for details)

Step #3


MAP FOR BOM: VERIFICATION

do not skip any step!

BOME VERIFICATION STEPS:

1. Confirm the “Bome MIDI Translator 1” device is created (longformat)
 1. Method: menu View ; settings ; virtual midi ports ; 1 port; long port names
2. Confirm the 4x midi ports were opened correctly
 1. Method: Click log window; check log
3. Confirm that the Controller talks to BOME
 1. Method: Click log window; click “MIDI-IN/OUT”; Press any button on the controller; confirm they appear in the log file; unclick “MIDI-IN/OUT”
4. Confirm that the BOME clock is running
 1. Method: Click log window; click “rules”; see a lot of messages appearing
 2. unclick “rules” to stop the logging
5. Minimize BOME to keep it running

BOME settings: auto start with windows



BOME settings: long port name device

DDJ-1000 v6.5.0 BOME - Main File - please run before traktor.btmp - Bome MIDI Translator Pro

File Edit MIDI View Help

Project: Untitled Project

Here, you can assign default MIDI ports for the entire project. ...

MIDI INPUT

From Traktor

Port State

Port Name	Port State
Virtual In	open
Bome MIDI Transla...	open
1000	open
me MIDI Translator 1 ...	open

Create Alias

Settings - Bome MIDI Translator Pro

Start-Up

Appearance

Options

Confirm

Virtual MIDI Ports

Serial Ports

Export/Import

Reset

Virtual MIDI Ports

Here you can create virtual MIDI ports that you can use to send MIDI messages directly to other MIDI applications, and receive MIDI messages from other applications. Select the number of virtual ports you need.

Number of virtual ports:

1 Port

Naming of the virtual ports:

☒ Long port names (e.g. "Bome MIDI Translator 1")

☐ Short port names (e.g. "BMP1")

When loading a project file with virtual ports:

☒ Adjust the number of virtual ports

☐ Do not prompt for adjusting the number of virtual ports

OK Cancel

Event Monitor

1: Discovered MIDI INP

2: Discovered MIDI OUT

3: MIDIManager started

4: Loaded Project file

5: Activated preset: I

6: Activated preset: N

7: Activated preset: M

8: Activated preset: S

9: Activated preset: N

10: Activated preset: main Ch2

11: Activated preset: SEEK CH2

12: Opened MIDI IN: Bome MIDI Translator 1 Virtual In

13: Opened MIDI IN: DDJ-1000

14: Opened MIDI OUT: Bome MIDI Translator 1 Virtual Out

15: Opened MIDI OUT: DDJ-1000

Here you can create MIDI Thru connections, i.e. connect MIDI I...

☒ Only display open MIDI ports

Bome MIDI Translator 1 Virtual In

Bome MIDI Translator 1 Virtual Out

Bome Virtual Port 1

Bome Virtual Port 1

DDJ-1000

DDJ-1000

From DDJ

To DDJ

From Traktor

To Traktor

Long port names!

BOME: Correct startup log

The screenshot displays the DDJ-1000 v6.5.0 BOME software interface. The main window is titled "DDJ-1000 v6.5.0 BOME - Main File - please run before t...". The interface includes a menu bar (File, Edit, MIDI, View, Help) and a toolbar with icons for file operations and MIDI settings.

Log Window: The "Log Window" is open, showing a list of events. The first four messages are circled in red and labeled "4x messages here!":

- 1: Discovered MIDI INPUT: Bome MIDI Translator 1 Virtual In, DDJ-1000
- 2: Discovered MIDI OUTPUT: Bome MIDI Translator 1 Virtual Out, DDJ-1000, Microsoft GS Wavetable
- 3: MIDIManager started.
- 4: Loaded Project file: C:\Users\Pedro\Desktop\Z_DRIVE_Pedro\2 Music - Controllers\0_MAPS_Traktor

The log continues with messages for activating presets (NEEDLE CH1, MAIN CH1, SEEK CH1, NEEDLE CH2, MAIN CH2, SEEK CH2) and opening MIDI ports (IN: Bome MIDI Translator 1 Virtual In, IN: DDJ-1000, OUT: Bome MIDI Translator 1 Virtual Out, OUT: DDJ-1000).

MIDI Settings: The "Project: Untitled Project" dialog is open, showing MIDI input and output settings. The "MIDI INPUT" section shows "From Traktor" selected. The "MIDI OUTPUT" section shows "To DDJ" selected. The "MIDI Router" section shows connections between Bome MIDI Translator 1 Virtual In and Out, Bome Virtual Port 1, DDJ-1000, From DDJ, and From Traktor. A red circle highlights the "MIDI INPUT" and "MIDI OUTPUT" sections, and a red arrow points to the "MIDI Router" section.

Annotations:

- A red circle highlights the "Log Window" button in the toolbar.
- A red circle highlights the "MIDI INPUT" and "MIDI OUTPUT" sections in the "Project: Untitled Project" dialog.
- A red circle highlights the "MIDI Router" section in the "Project: Untitled Project" dialog.
- A red arrow points from the "MIDI Router" section to the "MIDI INPUT" and "MIDI OUTPUT" sections.
- A red circle highlights the "MIDI Router" section in the "Project: Untitled Project" dialog.
- A red circle highlights the "MIDI Router" section in the "Project: Untitled Project" dialog.

Text overlays:

- "Do not change this!" (top center)
- "Default is ONLY - 'From Traktor' OPEN - 'to DDJ' OPEN" (top center)
- "confirm devices are OPEN!" (top center)
- "4x messages here!" (left side, pointing to the first four log messages)
- "Do not change this 'cross'!" (bottom right, pointing to the MIDI Router connections)

(Example for DDJ-1000; other DDJ are similar. See annexes for details)

BOME: confirm DDJ talks to BOME

The screenshot shows a MIDI debugging interface. At the top, there are two tabs: "Event Monitor" and "Log Window". The "Log Window" tab is selected and highlighted in green. Below the tabs, a list of four MIDI events is displayed:

- 1: MIDI IN [DDJ-1000]: 93 0C 7F
- 2: MIDI OUT [Bome MIDI Translator 1 Virtual Out]: 93 0C 7F
- 3: MIDI IN [DDJ-1000]: 93 0C 00
- 4: MIDI OUT [Bome MIDI Translator 1 Virtual Out]: 93 0C 00


At the bottom of the window, there is a panel with several checkboxes: "Incoming", "Rules", "Outgoing", "MIDI IN", "MIDI OUT", and "Timestamped". The "MIDI IN" and "MIDI OUT" checkboxes are checked and circled in red. To the right of these checkboxes are two buttons: "Dump Vars" and "Clear".

Two callout boxes provide additional information:

- A box on the right side of the log window states: "Pressing and releasing any button generates 4 log lines. This is always in the DDJ->BMT1 direction". A red line points from this box to the log entries.
- A box below the MIDI IN/OUT checkboxes states: "Activate MIDI debug here". A red line points from this box to the circled checkboxes.

(Example for DDJ-1000; other DDJ are similar. See annexes for details)

BOME: confirm internal clock



(Please click “rules” again to stop the logging)



Step #4

MAP FOR TRAKTOR: INSTALLATION

do not skip any step!


CREATE A BACKUP:

1. Note: the mapping replaces a lot of your settings. In any cases, Traktor always makes automatic backups in “Root_Dir\Backup\Settings”

1. Open Traktor
2. Click Settings
3. Click big “export button” on lower left corner
4. Ensure all settings are clicked
5. Save the file

INSTALL TRAKTOR MAPPING:

1. Click Settings
2. Click big “import button” on lower left corner
3. Accept all checks; PLUS additionally click the “Audio device settings”




INSTALL TRAKTOR MAPPING (second time):

1. Repeat above process a second time. This is only to avoid a Traktor bug that gets the FX list wrong.


MAC-OS AUDIO OUTPUT ROUTING:

1. Set preferences / Output Routing / Internal to: 2 / 3 / 0 / 1

TRAKTOR: create backup of your settings




TRAKTOR: import mapping




(Example for DDJ-1000; other DDJ are similar. See annexes for details)

TRAKTOR: click audio device config



(Example for DDJ-1000; other DDJ are similar. See annexes for details)

TRAKTOR: import mapping (second time)



(Example for DDJ-1000; other DDJ are similar. See annexes for details)

Step #5

MAP FOR TRAKTOR: VERIFICATION

do not skip any step!

TRAKTOR VERIFICATION:

Note: the Preferences window is now quite slow to open. This is another Traktor bug.

1. Confirm the audio device is “DDJ-1000 ASIO” / “DDJ-SZ ASIO” / etc
 1. Method: Settings ; audio setup ; confirm audio device
2. Confirm the Output routing
 1. Method: Settings ; output routing; confirm “internal”; confirm “3 / 4 / 1 / 2”
 2. (see annexes for other DDJs case)
3. Confirm that all 6x pages have exactly “Bome Midi Translator1”
 1. Method: Settings; controller manager; click each of the 6x pages one-by-one; check IN and OUT port
 2. **DO NOT CHANGE TO DDJ-1000 in the controller manager!!!**
 3. **DO NOT FORGET TO CONFIRM ALL 6x PAGES!**
4. Verify that sound is played
 1. Method: Load a track; click Cue and play/pause repeatedly
 2. Use shift+quantize to send a reset command to BOME
5. Verify that BOME sees all the messages
 1. Method: open the bome window; click the “CUE” button; verify that the BOME log displays at least 8x log lines per human click




Beware #1!



Beware #2!

TRAKTOR: check audio device




(Example for DDJ-1000; other DDJ are similar. See annexes for details)


TRAKTOR: check output routing

Important: the below pictures is for DDJ-1000;
the other DDJ are different if they are internal or external mode
See annexes for specific pictures for your DDJ!


Windows: channels
are 3 / 4 / 1 / 2



MacOS: channels
are 2 / 3 / 0 / 1





TRAKTOR: recording settings



TRAKTOR: check MIDI device is long format

first click here

Both IN and OUT = Long format
For ALL 6 PAGES!



BOME: confirm bidirectional flow

Event Monitor ☐ ☒ Log Window ☐ ☒

```
1: MIDI IN [DDJ-1000]: 91 35 7F
2: MIDI OUT [Bome MIDI Translator 1 Virtual Out]: 91 35 7F
3: MIDI IN [Bome MIDI Translator 1 Virtual In]: 90 6A 00
4: MIDI OUT [DDJ-1000]: 90 6A 00
5: MIDI IN [Bome MIDI Translator 1 Virtual In]: 90 35 00
6: MIDI OUT [DDJ-1000]: 90 35 00
7: MIDI IN [Bome MIDI Translator 1 Virtual In]: 91 35 00
8: MIDI OUT [DDJ-1000]: 91 35 00
9: MIDI IN [Bome MIDI Translator 1 Virtual In]: 91 6A 00
10: MIDI OUT [DDJ-1000]: 91 6A 00
11: MIDI IN [Bome MIDI Translator 1 Virtual In]: 92 35 00
12: MIDI OUT [DDJ-1000]: 92 35 00
13: MIDI IN [Bome MIDI Translator 1 Virtual In]: 92 6A 00
14: MIDI OUT [DDJ-1000]: 92 6A 00
15: MIDI IN [Bome MIDI Translator 1 Virtual In]: 93 6A 00
16: MIDI OUT [DDJ-1000]: 93 6A 00
17: MIDI IN [Bome MIDI Translator 1 Virtual In]: 93 35 00
18: MIDI OUT [DDJ-1000]: 93 35 00
19: MIDI IN [DDJ-1000]: 91 35 00
20: MIDI OUT [Bome MIDI Translator 1 Virtual Out]: 91 35 00
```

☐ Incoming ☐ Rules ☐ Outgoing ☒ MIDI IN ☒ MIDI OUT ☐ Timestamped

Dump Vars Clear

Pressing and releasing any button generates at least 8x log lines.
This is both in the DDJ->BMT1 direction and the BMT1->DDJ direction

Stop "rules" log

Step #6

PROPER START SEQUENCE

PROPER START-UP SEQUENCE IF YOU HAVE PROBLEMS:

0) Stop everything

1) Start Laptop

2) Start BOME

3) Start your DDJ

4) Start Traktor

IF ITS STILL NOT WORKING #1

Audio doesn't work:

Re-confirm the DDJ-1000 is your audio device

Re-confirm output routing is 3/4/1/2 in windows and 2/3/0/1 in macOS

Re-confirm Rekordbox performance mode works.

Audio works - but MIDI doesn't :

Re-confirm you have BOME in the macOS accessibility security

Re-confirm you have "Bome midi Translator 1" on all 6x pages in Traktor

MIDI works but jog screens / Leds doesn't :

Reset the jog Screens using shift+quantize

Start components in this order: #1 Laptop #2 DDJ #3 BOME #4 Traktor

IF ITS STILL NOT WORKING #2

*Make a HD video of the verification steps, INCLUDING THE BOME LOG.
Put your phone really close to the screen for me to read the small text!*

*Upload the video to <https://wetransfer.com> and send an email to
pedro.estrela@gmail.com*

ANNEXES

DDJ-1000: forced MIDI mode

In my experience there is **no need** to set the unit to forced MIDI mode.





If this is ever necessary, instructions are on page 26 of the DDJ-1000 manual:

- no USB cable
- power off DDJ
- Press left play + left shift + turn on DDJ
- left Slip Reverse:
 - Off = auto mode
 - ON = forced mode
- Power off DDJ
- Power ON DDJ
- insert USB cable.




AUDIO path







MIDI path



ANNEX: DDJ-800



ANNEX: XDJ-XZ



```
795: MIDIManager stopped.
796: MIDIManager started.
797: Opened MIDI OUTPUT 'Bome MIDI Translator 1 Virtual Out'
798: Opened MIDI OUTPUT 'XDJ-XZ (2)'
799: Opened MIDI OUTPUT 'XDJ-XZ (1)'
800: Opened MIDI INPUT 'Bome MIDI Translator 1 Virtual In'
801: Opened MIDI INPUT 'XDJ-XZ (2)'
802: Opened MIDI INPUT 'XDJ-XZ (1)'
```

☐ Incoming ☐ Rules ☐ Outgoing ☒ MIDI IN ☒ MIDI OUT ☐ Timestamped

ANNEX: DDJ-1000SRT




DDJ-1000SRT specific instructions for the Traktor mapping (for v6.1.X – not yet updated to V6.7.0 BOME)

Please use the specific TSI for the DDJ-1000SRT. This is the same mapping as the DDJ-SZ mapping, but with small customizations to make it work well on the SRT:




- Jog screens are NOT supported. This is because they are not documented on the Pioneer MIDI map file. Please request this in <https://serato.com/forum/discussion/1736390>
- Please put your jog weight to “heavy”
 - This will significantly improve scratching and jogFX
- Audio device in external mode.
 - This means that ALL the pioneer effects (both colorFX and beatFX work for USB sources
 - See next slides for config
- Please avoid VINYL OFF mode. The TSI disables jog touch in this case, but the jog loses resolution compared to VINYL ON mode
- Beatjump buttons added. Please use shift+IN/OUT to configure the loop size (=jump size)
- BeatFX ON/OFF is now for pioneer beatFX only
- Automatic layout changing was removed

ANNEX: DDJ-1000SRT

(note: pictures are for v6.1.X; v6.7.0 will also work, but was not tested yet)




ANNEX: DDJ-SZ





SET PREVIEW TO
SAME VALUES
AS DECK 4!

ANNEX: DDJ-SX3

(Select SX3 device here)




(Select SX3 device here)



SET PREVIEW TO
SAME VALUES
AS DECK 4!

ANNEX: DDJ-SX2

(Select SX2 device here)



(Put SX2 channels here)

