

New architecture and painting properly

- In this Section:
 - A better structure for our Java applications
 - ... and an interesting consequence
 - Improving drawn graphics - "painting properly"

Java application architecture

- Java classes can be used to build applications in many different ways
- The only specific requirement is that the main class used to launch the application has

```
public static void main(String [] args) { ... }
```
- We have been using the JFS application architecture
 - Quite simple
 - Main program is *all in one class*
 - But can look rather confusing
 - Reminder: See next slide...

```
public class Example extends JFrame
    implements ChangeListener {

    private ...;

    public static void main (String[] args) {
        Example frame = new Example();
        frame.setSize(400,100);
        frame.setLocation(50,50);
        frame.setTitle("Title");
        frame.createGUI();
        frame.setVisible(true);
    }

    private void createGUI() { ... }

    public void stateChanged(ChangeEvent e) { ... }

    ...
}
```

Possible confusion

ITNP001 Application architecture and painting
© University of Stirling 2015

3

- For a clearer arrangement, we will separate:
 - The main launcher component - one class
 - The GUI component - another class
 - (and there may be other supporting classes too)
- The main launcher looks like this:

```
public class Example {

    public static void main (String[] args) {
        ExampleGUI frame = new ExampleGUI("Title");
        frame.setLocation(50,50);
        frame.setVisible(true);
    }

}
```

Note: Constructor

- This organizes *instantiation* and *deployment* of the GUI
 - But not its internal details

ITNP001 Application architecture and painting
© University of Stirling 2015

4

- And the GUI class looks like this:

```
public class ExampleGUI extends JFrame
    implements ChangeListener {

    private ...;
    public ExampleGUI(String title) {
        setSize(400,100);
        setTitle(title);
        createGUI();
    }
    private void createGUI() { ... }
    public void stateChanged(ChangeEvent e) { ... }
    ...
}
```

Note: Constructor

Note: No frame.
as the methods are in
this class

- This builds the window but does not control the when/where

ITNP001 Application architecture and painting
© University of Stirling 2015

5

- So, the launch process is:
 - Indicate the main class to the JVM
 - JVM finds the **main** method in it, calls it
 - **main** creates an instance of GUI class
 - GUI constructor is called, builds window
 - **main** places window and makes it visible
 - Event handling starts

ITNP001 Application architecture and painting
© University of Stirling 2015

6

An interesting consequence

- Remember:
 - `new ExampleGUI(...)` *builds a complete new instance*
- We could have *as many StudentRecords as we wished*
 - *So too with ExampleGUIs!*
- So, the launcher `main` method could look like this:

```
public static void main (String[] args) {  
    ExampleGUI frame1 = new ExampleGUI("Title 1");  
    frame1.setLocation(50,50);  
    frame1.setVisible(true);  
    ExampleGUI frame2 = new ExampleGUI("Title 2");  
    frame2.setLocation(100,100);  
    frame2.setVisible(true);  
}
```
- There will be two independently operating windows!

ITNP001 Application architecture and painting
© University of Stirling 2015

7

Painting properly (not in JFS)

- This is a secret that Bell & Parr chose to hide in JFS 4th edition onwards!
 - *They claim that it is hard to understand (I don't agree)*
- What is the problem?
 - *Your drawings do not automatically refresh when the window is created/restored/exposed*
 - *You may already have been irritated by this!*
 - *There is no problem with applications that use only text fields, buttons, sliders, etc*
- Example: The QuickBlind application from the lecture on Decisions and Buttons:



ITNP001 Application architecture and painting
© University of Stirling 2015

8

Analysis

- There seems to be some unfair "magic" at work:
 - JButtons, JSliders, JLabels, etc all seem to re-draw themselves automatically when the window needs refreshing
 - If our JPanel has a background colour set (**setBackground**), then it is filled in automatically
- But *our* drawing/painting actions are only carried out when an ordinary event occurs, for example a button click
 - How can we make them automatic?
- The "magic" works like this:
 - The OS window manager tells the JVM when a window needs refreshing
 - This causes a **PaintEvent**...
 - ... and the JVM calls *every visible widget's* **paintComponent** event handler method

ITNP001 Application architecture and painting
© University of Stirling 2015

9

- Every widget has a method:
public void paintComponent(Graphics g)
 - The JVM automatically *clears* the widget's screen area
 - and passes a suitable **Graphics** for that screen area to the method
 - The method then draws the widget's specific appearance
- Clear enough for JButton, JSlider, etc
- But JPanel's **paintComponent** is *built into the library class* and *cannot know* about our drawing actions!
- So, there is *no* magic! We can exploit this knowledge and play a clever game:
 - We can create an "extended" JPanel...
 - ... "*overriding*" its **paintComponent** with one of our design!
 - "Overriding" = "replacing"

ITNP001 Application architecture and painting
© University of Stirling 2015

10

A QuickBlind that paints properly

- Here is one way to organize the program:
- Where we create a new JPanel, we now have:

```
panel = new JPanel() {  
    public void paintComponent(Graphics g) {  
        super.paintComponent(g); // Important!  
        paintScreen(g);          // Our drawing  
    }  
};
```

- **panel** is assigned a new JPanel object but with its **paintComponent** overridden by a new method
- The new method *must* call the superclass version to do its work (filling in the set background colour)...
- ...and then call *our own* **paintScreen** method - to do the real drawing

- The extended JPanel:
 - Is called an "anonymous inner class"
 - Its bytecode is placed in a file with a name like **WindowBlind\$1.class**
- **paintScreen** is quite straightforward
 - *It can assume that it is given an erased graphics area*
 - All it needs to do is draw the correct picture, e.g:

```
private void paintScreen(Graphics g) {  
    int sliderValue = slider.getValue();  
    g.setColor(Color.black);  
    g.drawRect(120, 80, 60, 100);  
    g.fillRect(120, 80, 60, sliderValue);  
}
```

- That deals with window refreshing
 - *But our own event handlers can now exploit this*

- So, finally, we *remove* the calls of `paintScreen` (or explicit drawing code) from the event handlers `stateChanged` and `actionPerformed`
 - Instead we instruct the JVM *to force a screen refresh* - a "fictitious" `PaintEvent`:
 - ... which will *indirectly* cause our `paintComponent` to be called
- ```
public void stateChanged(ChangeEvent e) {
 repaint(); // Force a screen refresh
}

public void actionPerformed(ActionEvent e) {
 if (e.getSource()==open)
 ...
 if (e.getSource()==close)
 ...
 repaint(); // Force a screen refresh
}
```

- Notes:
  - `repaint()` ; does *not* cause an immediate painting process
  - It instructs the JVM to add a `PaintEvent` to its queue of events to be dealt with
  - Then when the current event handler finishes (returns), the `PaintEvent` "happens"
  - (The JVM "coalesces" multiple `PaintEvents`)
- Here is the improved version running:
- Note:



**End of section**