

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/41715980>

# Local assortativeness in scale-free networks

Article in *EPL (Europhysics Letters)* · October 2008

DOI: 10.1209/0295-5075/84/28002

CITATIONS

58

READS

175

3 authors, including:



**Mahendra Piraveenan**

The University of Sydney

64 PUBLICATIONS 550 CITATIONS

[SEE PROFILE](#)



**Albert Zomaya**

The University of Sydney

909 PUBLICATIONS 11,167 CITATIONS

[SEE PROFILE](#)

Some of the authors of this publication are also working on these related projects:



Virtualized Data Centers [View project](#)



Resource Controller for Stateful Timely Data-flow Framework [View project](#)

## Local assortativeness in scale-free networks

This content has been downloaded from IOPscience. Please scroll down to see the full text.

2010 EPL 89 49901

(<http://iopscience.iop.org/0295-5075/89/4/49901>)

View [the table of contents for this issue](#), or go to the [journal homepage](#) for more

Download details:

IP Address: 124.6.238.2

This content was downloaded on 18/10/2013 at 02:30

Please note that [terms and conditions apply](#).

## Addendum

# Local assortativeness in scale-free networks

M. PIRAVEENAN<sup>1,2</sup>, M. PROKOPENKO<sup>1(a)</sup> and A. Y. ZOMAYA<sup>2</sup>

<sup>1</sup> CSIRO Information and Communications Technology Centre - PO Box 76, Epping, NSW 1710, Australia

<sup>2</sup> Centre for Distributed and High Performance Computing, School of Information Technologies,  
The University of Sydney - NSW 2006, Australia

Original article: *Europhysics Letters (EPL)*, **84** (2008) 28002.

PACS **99.10.Qr** – Addenda

Copyright © EPLA, 2010

Network assortativity is typically defined as

$$r = \frac{1}{\sigma_q^2} \left[ \left( \sum_{jk} jke_{j,k} \right) - \mu_q^2 \right], \quad (1)$$

where  $e_{j,k}$  is the link distribution of the network,  $\mu_q$  is the expectation of the excess degree distribution  $q(k)$  and  $\sigma_q$  is the standard deviation of this distribution.

In the original paper the local assortativity of a given node  $v$  was introduced using the following formula:

$$\rho_v = \frac{\alpha_v - \beta_v}{\sigma_q^2} = \frac{(j+1)(j\bar{k} - \mu_q^2)}{2M\sigma_q^2}, \quad (2)$$

where  $j$  is the node's excess degree,  $\bar{k}$  is the average excess degree of its neighbours,  $\sigma_q \neq 0$ . The contribution  $\alpha_v$  of the node  $v$  to the first term in (1), i.e.,  $\sum_{jk} jke_{j,k}$ , and contribution  $\beta_v$  to the second term in (1), i.e.,  $\mu_q^2$ , are

$$\alpha_v = (j+1) \frac{j\bar{k}}{2M}, \quad \beta_v = (j+1) \frac{\mu_q^2}{2M}. \quad (3)$$

We subsequently found that this formulation has a bias which favours peripheral nodes over hubs, and provide here a better measure (5) which should replace expression (2) in the original paper. The new derivation is summarised below. While the component  $\alpha_v$  captures the precise contribution of each node to the term  $\sum_{jk} jke_{j,k}$ , the component  $\beta_v$  represents the contribution of each node to the term  $\mu_q^2$  with an imprecise scaling. Specifically, the scaling factor  $(j+1)/2M$  in (3) is the correct scaling factor for  $\mu_q$ , rather than  $\mu_q^2$ , and hence,  $\beta_v$  has a bias towards peripheral nodes. The unbiased contribution instead is given by:

$$\hat{\beta}_v = (j+1) \frac{j\mu_q}{2M}. \quad (4)$$

Hence, local assortativity is

$$\hat{\rho}_v = \frac{\alpha_v - \hat{\beta}_v}{\sigma_q^2} = \frac{j(j+1)(\bar{k} - \mu_q)}{2M\sigma_q^2}. \quad (5)$$

If the neighbours' average  $\bar{k}$  is higher than the global average  $\mu_q$ , then the node is assortative. Otherwise, the node is disassortative. Hence, the local assortativity is a scaled difference between the average excess degree of the node's neighbours and the global average excess degree.

<sup>(a)</sup>E-mail: mikhail.prokopenko@csiro.au




Fig. 1: (Colour on-line) Internet Autonomous System level, August, 2008. Local assortativity profiles  $\rho$  (+) and  $\hat{\rho}$  ( $\diamond$ ).

The difference between  $\rho(d)$ , defined by (2), and  $\hat{\rho}(d)$ , defined by (5), is illustrated for Internet Autonomous Systems level (August 2008) in fig. 1. Clearly,  $\hat{\rho}(d) > \rho(d)$  for nodes with smaller  $d$ , and  $\hat{\rho}(d) < \rho(d)$  for the hubs.

\*\*\*

The authors thank Prof. G. Q. ZHANG from the Chinese National Academy of Sciences for posing the question regarding the contribution to  $\mu_q^2$ .