

# LeaFTL: A Learning-based Flash Translation Layer for Solid-State Drives

Jinghan Sun, Shaobo Li, Yunxin Sun, Chao Sun, Dejan Vucinic, and Jian Huang. 2023.

In Proceedings of the 28th ACM International Conference on Architectural Support for Programming Languages and Operating Systems, Volume 2 (ASPLOS 2023).

2024. 08. 07


Presentation by Yeongyu Choi

choiyg@dankook.ac.kr

# Contents


1. Introduction
2. Background
3. LeaFTL
4. Evaluation
5. Conclusion

# Introduction



# Introduction

## Modern SSDs



**Direct LPA-PPA mappings require 8 Bytes per mapping**

**DRAM Capacity can't keep up with SSD Capacity**

# Approaches on Mappings

## Page-Level Mapping:

Direct LPA-PPA mapping for fast lookup

Entire mapping table requires large storage space

## Block-Level Mapping:

Reduce mapping table size by storing via blocks

Overhead in Lookup in flash page

## Hybrid Mapping:

Takes advantage of a mix of Page-level and Block-level Mappings

Incurs in significant GC Overhead



LeaFTL


A Learning-Based Flash Translation Layer for Modern SSDs




Instead of 1:1 mapping in Page-level Mapping

**Exploit learning techniques to identify various LPA-PPA mapping patterns**


# Learning-Based Techniques



(a) Precise Linear Approximation



(b) Inaccurate Linear Approximation



$$PPA = f(LPA) = \lceil K * LPA + I \rceil$$

where  $LPA \in [S_{LPA}, S_{LPA} + L]$

# Learned Index Segment





Figure 6: Types of learned segments in LeaFTL.


# Log-Structured Address Mapping Table




- Non-overlapping segments are sorted by their LPA ranges
- Overlapping segments are allowed across levels



# Conflict Resolution Buffer



- Possible to get **inaccurate PPA**
- Affect to segment **compaction**



- CRB is a nearly sorted list, follows its **insertion deletion and lookup are fast**
- Each LPA takes only 1 byte and its structured guarantees no redundant LPAs

Very space efficient with at most 256 entries

Separate segments


# Log-Structured Table Operations

Workload

Write

LPA  $\in$  206~240

Piecewise Linear Regression



New segments are appended to the topmost level

**If it is approximate it is added to CRB**


# Log-Structured Table Operations

Workload

Write

LPA  $\in$  32~48


Piecewise Linear Regression



New segments are appended to the topmost level


**If it is approximate it is added to CRB**

# Log-Structured Table Operations




Search from the topmost level,  
and always find the first  
matching segment

# Log-Structured Table Operations




# Misprediction Verification with OOB Metadata (OOB: Out-of-Band)






# Verifying Address Translation with OOB Metadata (OOB:Out-of-Band)







# Verifying Address Translation with OOB Metadata (OOB:Out-of-Band)



# Verifying Address Translation with OOB Metadata (OOB:Out-of-Band)




# Optimized Flash Allocation



Flushed flash pages


LPA=76	32	33	34	77	38	41	17	15	36	...	...
--------	----	----	----	----	----	----	----	----	----	-----	-----

Four new linear segments are created



**Flushing flash pages from the write buffer directly is less optimal**


# Optimized Flash Allocation



Flushed flash pages


LPA=32	33	34	38	76	77	41	17	15	36	...	...
--------	----	----	----	----	----	----	----	----	----	-----	-----

Fewer linear segments are created




**Optimization:** Flash pages are sorted by their LPAs before flushed from the write buffer

# Coordinated Garbage Collection




# Coordinated Garbage Collection



**LeaFTL learns new segments to avoid messing up existing segments in GC**

# Put It All Together



# Evaluation

## Implementation Details

- WiscSim Simulator
- A Real 1TB Open-Channel SSD with 16 channels

## Workloads

- Block I/O Traces: from enterprise servers and university servers
- Data-Intensive Applications: FileBench, BenchBase

## SSD configuration

Parameter	Value	Parameter	Value
Capacity	2TB	#Channels	16
Page size	4KB	OOB Size	128B
DRAM size	1GB	Pages/block	256
Read latency	20us	Write latency	200us
Erase	1.5ms	Overprovisioning ratio	20%


## Comparison

- DFTL: Demand-based caching FTL
- S-FTL: Compresses sequential LPA-PPA entries
- LeaFTL with different error bounds (0, 1, 4, 8, 16)




# Evaluation

## Memory Footprint Analysis & Performance Analysis



→ Avg. x2.9 memory saving


Lower is Better



→ Avg. x1.4 reduced storage access latency

# Evaluation

## Misprediction




Error bound  $\gamma = 16$ ,  
misprediction ratio <10% Avg.

Every misprediction incurs in only  
one additional flash read

# Evaluation

## Memory Footprint Analysis on Different $\gamma$



➔ Avg. x1.3 memory saving  
(Real SSD Avg. x1.2)

is Better


➔ Avg. x1.3 reduced storage access latency  
(Real SSD Avg. x1.2)

# Evaluation

## Write Amplification Factor Analysis

WAF, the ratio between the actual and requested flash writes

Lower is Better  
↓



# Conclusion

- LeaFTL uses a simple but effective learning-based technique to reduce memory consumption
- LeaFTL stores learned segments in a log-structured manner to avoid re-learning
- LeaFTL uses OOB metadata to verify its address translation
- LeaFTL consumes 2.9x less memory and improves performance by 1.4x

# Thank you