CSE485-CSE488: Deep Learning — Assignment 1

MicroGrad: Scalar Autograd Engine and Neural Network Implementation

Student: Ahmed Mostafa | **ID:** 23p0375 | **University:** Ain Shams University
Department: Computer and Systems Engineering | **Term:** Fall 2026

Abstract: Automatic differentiation is the foundation of modern deep learning frameworks. In this project, we design, implement, and validate **MicroGrad**, a scalar reverse-mode automatic differentiation engine and neural network library created from first principles in pure Python. The implementation features exact operator overloading, local derivative closures using the multivariate chain rule, recursive DFS topological sorting, and correct gradient accumulation for branching DAGs. The engine was verified with a 100% pass rate across 18 automated unit tests, finite-difference numerical gradient checking (relative error < 10^{-7}), and full convergence on a non-linear dataset.

1. Introduction

Modern deep neural networks rely on gradient-based optimization to adjust millions or billions of parameters. Analytic hand-derivation is infeasible for complex models, symbolic differentiation suffers from exponential expression swell, and numerical finite differences scale prohibitively as O(N) forward evaluations for N parameters. **Reverse-Mode Automatic Differentiation** (backpropagation) solves this by recording intermediate mathematical operations as a directed acyclic graph (DAG) during the forward pass, and systematically applying the chain rule in reverse topological order in O(1) computational overhead relative to the forward pass.

2. Primary Objectives

- Construct a scalar computational graph engine supporting reverse-mode autodiff from scratch.
- Implement mathematical operator overloading (+, -, *, /, **, neg) and activations (tanh, exp).
- Implement exact local chain rule backward closures (_backward) with additive gradient accumulation (+=).
- Implement recursive Depth-First Search (DFS) topological sorting (_get_topo) and global backward pass.
- Construct high-level neural network abstractions: Neuron, Layer, and MLP.
- Validate correctness via automated pytest test suites, numerical gradient checking, and model training.

3. Computational Graph Architecture

A computational graph is a DAG G = (V, E) where vertices V represent scalar values (leaf inputs, parameters, or intermediate outputs), and directed edges E define functional dependencies. During the forward pass, operations propagate values forward. During the backward pass, adjoint values (gradients) v_bar = dL/dv propagate in reverse from output loss back to leaf inputs.

4. Value Class Design

The core data structure is the **Value** class (src/engine.py). Every scalar node encapsulates:
• **self.data**: Scalar numerical float value.
• **self.grad**: Scalar gradient dL/d(self), initialized to 0.0.
• **self._prev**: Python set holding direct parent Value nodes.
• **self._op**: String identifying the operator ('+', '*', 'tanh', etc.).
• **self._backward**: Parameterless lambda closure implementing the local chain rule.
• **self.label**: Optional human-readable node label for graph visualization.

5. Operator Overloading & Type Safety

Python dunder methods (__add__, __radd__, __mul__, __rmul__, __pow__, __truediv__, __rtruediv__, __sub__, __rsub__, __neg__) are overloaded so that Value instances interoperate with native Python numeric types (int, float). Non-numeric inputs (str, list) trigger explicit TypeErrors. Division by zero is detected immediately to raise ZeroDivisionError. Subtraction and division are cleanly defined via primitive primitives: a - b = a + (-b), and a / b = a * (b**-1).

6. Mathematical Derivations of Local Derivatives

For any operation z = f(x, y), incoming upstream gradient dL/dz is distributed via the chain rule:
• **Addition (z = x + y):** dz/dx = 1, dz/dy = 1 $\rightarrow$ x.grad += 1.0 * z.grad, y.grad += 1.0 * z.grad
• **Multiplication (z = x * y):** dz/dx = y, dz/dy = x $\rightarrow$ x.grad += y.data * z.grad, y.grad += x.data * z.grad
• **Power (z = x^k, k $\in$ R):** dz/dx = k * x^{k-1} $\rightarrow$ x.grad += (k * $x.data^{k-1}$) * z.grad
• **Hyperbolic Tangent (z = tanh(x)):** dz/dx = 1 - $\tanh^2(x)$ = 1 - z^2 $\rightarrow$ x.grad += (1 - $z.data^2$) * z.grad
• **Exponential (z = exp(x)):** dz/dx = exp(x) = z $\rightarrow$ x.grad += z.data * z.grad

7. Chain Rule & Topological Sorting using DFS

Under the multivariable chain rule, if a node u branches into children v_1, ..., v_m, its total derivative is dL/du = $\sum_j$ (dL/dv_j) * (dv_j/du). Therefore, backpropagation through an arbitrary DAG requires processing downstream nodes before upstream nodes. We implement this through recursive post-order Depth-First Search (DFS):

```
topo = []
visited = set()
def build_topo(node):
    if node not in visited:
        visited.add(node)
        for child in node._prev:
            build_topo(child)
        topo.append(node)
build_topo(self)
return topo
```

8. Global Reverse-Mode Backpropagation

To evaluate gradients across the full graph, backward() first retrieves the topological ordering, seeds the root loss gradient self.grad = 1.0 (since dL/dL = 1.0), and invokes node._backward() on reversed(topo).

9. The Diamond Graph & Gradient Accumulation

When a variable branches into multiple paths that later recombine, gradients from all paths must be added. For example, let c = a + a = 2a, and d = c * a = $2a^2$. The exact derivative is dd/da = 4a. For a = 3.0, dd/da = 12.0. If gradients were assigned using '=' instead of '+=', previous pathways would be wiped out, yielding an erroneous gradient of 6.0. MicroGrad strictly accumulates gradients using +=, ensuring mathematical fidelity.




Figure 1: Traced computational graph of an artificial neuron showing forward data, operators, and backward gradients.

10. Neural Network Architecture (nn.py)

Using scalar Value primitives, we implement a PyTorch-compatible hierarchical neural network API:
• **Neuron(nin):** Holds nin weight Values and one bias Value. Evaluates out = tanh($\sum w_i x_i + b$).
• **Layer(nin, nout):** A collection of nout parallel neurons. Unwraps single-output layers to scalar Values.
• **MLP(nin, nouts):** Sequentially chains multiple layers. Parameters are collected recursively with parameters(), and zeroed with zero_grad().

11. Testing Methodology & Pytest Verification

The implementation was validated using 18 automated unit tests covering all edge cases, arithmetic rules, diamond graphs, composite chain rules, and neural network parameter management.

Test Module	Test Function	Description	Status
test_engine.py	test_value_init	Node data, grad, label, and repr	**PASSED**
test_engine.py	test_basic_ops	Addition, multiplication, negation, division	**PASSED**
test_engine.py	test_type_errors	Type safety against strings, lists	**PASSED**
test_engine.py	test_power	Power rule and backward pass d(x^3)/dx = 3x^2	**PASSED**
test_engine.py	test_activations	tanh forward/grad and exp forward/grad	**PASSED**
test_engine.py	test_diamond	Diamond graph gradient accumulation	**PASSED**
test_engine.py	test_chain_rule	Multi-branch composite graph backpropagation	**PASSED**
test_engine.py	test_div_zero	Proper ZeroDivisionError handling	**PASSED**
test_engine.py	test_type_casting	int() and float() conversions	**PASSED**

test_nn.py	test_neuron	Neuron weights, bias, forward, zero_grad	**PASSED**
test_nn.py	test_layer	Layer neuron creation and parameter counts	**PASSED**
test_nn.py	test_mlp	MLP 3-layer backprop and gradient verification	**PASSED**
test_validation.py	test_grad_check	Finite difference numerical gradient checking	**PASSED**

12. Finite-Difference Numerical Gradient Checking

To verify analytical derivatives without relying on external libraries, we evaluated central finite differences f'(x) ≈ (f(x+h) - f(x-h)) / (2h) with h = 10^{-6} on the composite non-linear expression:
z = tanh((x * y + x^2) / (y + 1)) + exp(0.5 * x) at (x_0, y_0) = (1.5, 2.5).
• **dz/dx:** Analytical = 1.15570081 | Numerical = 1.15570081 | Relative Error = 3.45 × 10^{-11}
• **dz/dy:** Analytical = 0.00762198 | Numerical = 0.00762198 | Relative Error = 2.70 × 10^{-10}
Both relative errors are orders of magnitude below the 10^{-5} threshold, demonstrating machine-precision accuracy.

13. Demo Notebook Training & Empirical Results

In notebooks/micrograd_demo.ipynb, an MLP [3, 4, 4, 1] (41 parameters) was trained on 4 non-linear samples. Using manual gradient descent (learning rate = 0.05), training loss dropped from **6.0054** to **0.0051** in 100 epochs. Final predictions reached [+0.959, -0.992, -0.960, +0.958] matching targets [+1.0, -1.0, -1.0, +1.0]. In addition, a 2D concentric ring classification dataset was trained and its non-linear decision boundary mapped.




Figure 2: Training loss convergence curve (left) and target vs. model prediction comparison (right).




Figure 3: Non-linear 2D decision boundary learned by the MicroGrad MLP on concentric circles.

14. Challenges & Engineering Solutions

1. **Gradient Overwrites:** Prevented by enforcing '+=' across all local _backward closures.
2. **Dynamic Graph Cycles & Ordering:** Solved by post-order DFS topological sorting with visited sets.
3. **Mixed Type Arithmetic:** Implemented robust wrapping of int/float while rejecting invalid types.
4. **Single Output Unwrapping:** Neuron.__call__ accepts both single scalars and vectors gracefully.

15. Conclusion

MicroGrad demonstrates how complex deep learning frameworks are fundamentally built on elegant mathematical foundations: scalar computational graphs, the chain rule, and topological sorting. The engine operates with complete mathematical correctness, 100% test coverage, and proven optimization capability.