


# RCE tool integration

wingModifier



### Choose Tool Configuration

Create a new tool configuration or choose an inactive one to activate

- ☒ Create a new Common tool configuration
- ☐ Create a new CPACS tool configuration
- ☐ Create a new tool configuration from a template

CPACS Tool (Type: CPACS)  
CPACS Tool with incoming and return directory (Type: CPACS)  
CPACS Tool with return directory (Type: CPACS)

(1) In this example we use the "common tool configuration".

- ☐ Choose an inactive tool configuration to edit:

Selected tool configuration:

(2) Click "Next >"



< Back

Next >

Save As ...

Save and activate

Cancel

## Tool Description

Define some information for the tool

### Tool characteristics

Name\*:

Icon path:



☒ Copy into configuration folder

Group Path:



Documentation:



Description:

This tool demonstrates:

- read a parameter from CPACS
- modify and update a parameter in CPACS

### Contact Information

Name:

E-Mail:

(1) Provide you tool name

(2) Choose a pretty icon

(3) Your tool palette might be structured by groups

(4) Link a documentation

(5) Add description

(6) Provide contact information

(7) Next >



< Back

Next >

Save As ...

Save and update

Cancel

## Inputs and Outputs

Configure the inputs and outputs of the tool


Inputs Outputs Verification

Input	Data type	Handling	Constraint
CPACS_in	File	Single (consumed), Queu...	Required

Add...

Edit...

Remove

 Edit... Input

Name\*: CPACS\_in

Data type\*: File

Handling\*:  
☐ Constant (not consumed)  
☒ Single (consumed)  
☒ Queue (consumed)

Default handling\*: Queue (consumed)

Constraint\*:  
☒ Required  
☐ Required if connected  
☐ Not required

Default constraint\*: Required

OK Cancel

(1) Click "Add"

(2) Define RCE input variable of type "File"

(3) Choose these file handling settings and click "OK"

(4) Next >



< Back

Next >

Save As ...

Save and update

Cancel

## Inputs and Outputs

Configure the inputs and outputs of the tool

Inputs Outputs Verification

Output

CPACS\_out


Data type

File

Add...

Edit...

Remove

 Edit... Output

Name\*: CPACS\_out

Data type\*: File

OK Cancel

(1) Click "Add"

(2) Define RCE output variable of type "File"

(3) Next >



< Back

Next >

Save As ...

Save and update

Cancel

**Tool Properties**

Define properties of the tool

Property groups:

Default

Add...

Rename...

Remove

Property keys for group "Default":

Key	Display name	Define at wo...	Default va...	Comment

Add...

Edit...

Remove

Nothing to do ...

☐ Write key-value properties file at runtime (in "Config" folder)

working/Config/

(1) Next &gt;



&lt; Back

Next &gt;

Save As ...

Save and update

Cancel

**Integrate a Tool as a Workflow Component**

**Launch Settings**

⚠ Currently, only one launch setting is possible

Host	Tool directory	Version	Working directory
RCE	C:\Workspace\Entwicklun...	1.0	RCE temp directory

Add... Edit...

**Edit Launch Settings**

Tool directory\*: C:\Workspace\Entwicklung\CPACS\CPACS\_Seminar\ToolIntegration ...

Version\*: 1.0

Working directory (absolute): ...

☒ Create arbitrary directory in RCE temp directory

☐ Limit parallel executions

OK Cancel

☐ Use a new working directory on each run

**Tool Copying Behaviour**

☒ Do not copy tool

☐ Copy tool to working directory once

☐ Copy tool to working directory on each run

**Clean up choices for working directory(ies) in workflow configuration\***

☐ Never delete working directory(ies)

☒ Delete working directory(ies) when workflow is finished

☒ Keep in case of failed workflow run

☐ Delete working directory(ies) after each run of the tool

☐ Keep in case of failed tool run

\*Defines the user's choices when configuring the component

? < Back Next > Save As ... Save and update Cancel

(1) Add launch setting

(2) Point to tool directory

(3) Select tool version

(4) Select checkboxes like this

(5) Select your preferred copying behavior


(6) Convenient for debugging...

(7) Next >

```
C:\ProgramData\mambaforge_22.9.0.2\Scripts\activate.bat cpacsSeminar  
python run.py
```

and optionally a pre execution, post execution, and tool run imitation

(1) Specify execution commands for Windows and/or Linux

 This example is written in Python, so we need to activate the correct interpreter first.

(2) Select "Tool directory"

Execution command(s) Pre execution script Post execution script Tool run imitation script

☒ Command(s) for Windows ☐ Command(s) for Linux

1 C:\ProgramData\mambaforge\_22.9.0.2\Scripts\activate.bat  
2 cpacsSeminar  
3 python run.py

1

Inputs  
CPACS\_in ▼ Insert

Properties  
▼ Insert

Directories  
Config dir ▼ Insert

Note: Command(s) executed as batch file Note: Command language is Bash

Execution Options  
☐ Exit code other than 0 is not an error  
Execute (command(s), pre execution/post execution/tool run imitation script) from  
☐ Working directory  
☒ Tool directory

Tool run imitation mode  
☐ Support tool run imitation

? < Back Next > Save As ... Save and update Cancel



Integrate a Tool as a Workflow Component

### Execution

Configure the execution command and optionally a pre execution, post execution, and tool run imitation script

Execution command(s)

Pre execution script

Post execution script

Tool run imitation script

```
1 shutil.copyfile("${in:CPACS_in}", os.path.join("${dir:tool}", "ToolInput/CPACS_in.xml"))
```

Inputs

CPACS\_in ▼ Insert

Outputs

CPACS\_out ▼ Insert

Properties

▼ Insert

Directories

Config dir ▼ Insert

Insert copy of file/dir...

Note: Script language is embedded Python 2.5 (plain Python without specific modules)

Tool run imitation mode

☐ Support tool run imitation

?

< Back

Next >

Save As ...

Save and update

Cancel

(1) Insert pre-execution script in Python

**i** Pre-execution: What happens before the actual tool is activated. Use this to create the required folder structure, if necessary, and copy the input file into it.

```
shutil.copyfile("${in:CPACS_in}", os.path.join("${dir:tool}", "ToolInput/CPACS_in.xml"))
```

❗ Post-execution: What happens after the actual tool has finished. Here we're telling RCE where to find the output file. In this example the tool is not copied, it is run locally. So we clean up the input file to avoid any confusion when the workflow is run again.

```
${out:CPACS_out} = os.path.join("${dir:tool}", "ToolOutput/CPACS_out.xml")  
  
# Cleaning up:  
os.remove(os.path.join("${dir:tool}", "ToolInput/CPACS_in.xml"))
```

(1) Insert post-execution script in Python

Integrate a Tool as a Workflow Component

### Execution

Configure the execution command and optionally a pre execution, post execution, and tool run imitation script

Execution command(s)

Pre execution script

Post execution script

Tool run imitation script

```
1 ${out:CPACS_out} = os.path.join("${dir:tool}",  
2 "ToolOutput/CPACS_out.xml")  
3  
4 # Cleaning up:  
5 os.remove(os.path.join("${dir:tool}",  
6 "ToolInput/CPACS_in.xml"))
```

Inputs

CPACS\_in ▼ Insert

Outputs

CPACS\_out ▼ Insert

Properties

▼ Insert

Directories

Config dir ▼ Insert

Additional Properties

Tool exit code ▼ Insert

Insert copy of file/dir...

Note: Script language is embedded Python 2.5 (plain Python without specific modules)

Tool run imitation mode

☐ Support tool run imitation

?

< Back

Next >

Save As ...

Save and update

Cancel

(2) "Save and update/activate"