Laboratory 1

Practice:

1. memory management 1
    - sudo vim hello_world.c
    - cat hello_world.c
        - #include <stdio.h>
        -
        - int main(){
        - printf ("Hello World!");
        - return 0;
        - }
    - gcc -o hello_world hello_world.c
    - objdump -hx hello_world > objdump.txt
        - objdump.txt 3 kB
    - memory sections -> address
        - stack -> **0000000000000740**
        - heap -> **0000000000200dc8**
2. memory management 2
    - sudo vim loop.c
    - cat loop.c

```
#include <stdio.h>


 int main(){
      int x = 1;
      while (x){
            printf ("%d\n", x);
            x++;
            }
       return 0;
}
```

    - gcc -o loop loop.c
    - ./loop
        - in paralel cu urmatoarea comanda (intr-un bash paralel)
    - ps -e | grep loop$
    - cat /proc/{pid_number}/maps > maps.txt
    - cat maps.txt
        - maps.txt 2 kB
        - -> address perms offset dev inode pathname
        - libc si ld -> librarii
            - heap -> **7fffef3c7000-7fffef3e8000 rw-p 00000000 00:00 0 [heap]**
            - stack -> **7ffff6269000-7ffff6a69000 rw-p 00000000 00:00 0 [stack]**
            - vdso -> virtual dynamic shared object, pentru functii virtuale
            - vvar -> variabile folosite de vdso
            - vsyscall -> codul pentru funtii virtuale
    - ldd loop > ldd.txt
    - cat ldd.txt
        - ldd.txt 155 B
        - librariile de care depinde programul + locatia virtuala de memorie
1. threads 1
    - touch thread.c
    - cat thread.c

```
#include <stdio.h>
#include <sys/mman.h>
```

```
#include <string.h>
#include <signal.h>
#include <unistd.h>
#include <stdlib.h>

void f (int flag1, siginfo_t *i, void *flag2) {
    printf("SIGSEGV: %p\n", i->si_addr);

    // function to add permission to write to the pages - function arguments
    mprotect(i->si_addr, sizeof(int), PROT_WRITE);

    // test changes
    *(int*)i->si_addr = 1;
    printf("Change: %d\n", *(int*)i->si_addr);

    _exit(EXIT_SUCCESS);
}

int main () {
        // aloca memorie virtuala
        /* mmap parameters:
                - addr          ->   NULL                                   ->  page-aligned chosen by kernel
                - length   ->   sizeof (int)                        ->  the length of the mapping
                - prot          ->   PROT_READ                          ->  read rights to pages
                - flags       ->   MAP_PRIVATE | MAP_ANONYMOUS      ->  private copy-on-write mapping | mapping not backed
up and initialized with 0
                - fd      ->   0                                        ->  file description
                - offset     ->   0                                     ->  starting the addr at defined offset
        */
        int *ptr  = mmap (NULL, sizeof (int), PROT_READ, MAP_PRIVATE | MAP_ANONYMOUS, 0, 0);
        // resolve write rights
        // int *ptr  = mmap (NULL, sizeof (int), PROT_WRITE | PROT_READ, MAP_PRIVATE | MAP_ANONYMOUS, 0, 0);
        // error handleing
        if (ptr == MAP_FAILED) {
                printf("Error\n");
                return 0;
         }
        printf ("Mmap addr: %p\n", ptr);
        printf ("Init: %d\n", *ptr);

        // writing operation will raise a TypeError sau Segmentation Fault exception depending on used flags
        // const char *text = "hello";
            // memcpy (ptr, text, strlen(text)); //segmentation fault when only read rights
            struct sigaction x;

           x.sa_flags = SA_SIGINFO;
           x.sa_sigaction = f;

           // setup signal handler
           if (sigaction(SIGSEGV, &x, NULL) == -1) {
               perror("Sigaction");
               _exit(EXIT_FAILURE);
           }

           *ptr = 1; // memory violation by modifying the address

               return 0;
      }
```

- gcc -o thread thread.c && ./thread
  1. output:

1.
```
Mmap addr: 0x7f93c2410000
Init: 0
SIGSEGV: 0x7f93c2410000
Change: 1
```

4. threads 2
    - If I send a signal to a process which has more than one thread which thread will handle it?
        - at least one thread (which is not signal blocked) should be able receive signals
        - if there are more threads which can receive signals, a handle mechanism must be implemented in order to chose the thread
            - if there are more threads which are not signal blocked, the system chose a random one : "We can’t predict the thread that will be chosen to run the signal handler"
            - in order to chose a specific thread you can signal block the others or create a handling system
        - signal arrives > thread complete the instruction > thread jump to the signal handler
    - If a thread produces an invalid memory access, which thread will handle it?
        - the memory access produced by a thread will be treated by itself using SIGSEGV