

DM561
Linear Algebra with Applications

Intoduction to Python - Part 3

Marco Chiarandini

Department of Mathematics & Computer Science
University of Southern Denmark

[Based on booklet Python Essentials]

Outline

Matplotlib
Other Data Visualization Libraries
Pandas

1. Matplotlib

2. Other Data Visualization Libraries

3. Pandas

Outline

Matplotlib
Other Data Visualization Libraries
Pandas

1. Matplotlib

2. Other Data Visualization Libraries

3. Pandas

Matplotlib Library in Ipython

In IPython functions with % are extra functions of IPython that add functionalities to the environment. They are called magic functions. Other useful magic function are %timeit to determine running time of a command and %run to run a script from a file.

```
>>> %matplotlib inline  
>>> import matplotlib.pyplot as plt
```

Plotting a Polynomial Function

Let's plot the following polynomial of degree 3:

$$P_3(x) = x^3 - 7x + 6 = (x - 1)(x - 2)(x + 3)$$

The numpy function `numpy.poly1d` takes an array of coefficients of length `n+1` (try `numpy.polyfit?`):

`a[0] * x**n + a[1] * x**(n-1) + ... + a[n-1]*x + a[n]`

```
>>> import numpy as np
>>> a=[1,0,-7,6]
>>> P=np.poly1d(a)
>>> print(P)
      3
  1 x - 7 x + 6

>>> x = np.linspace(-3.5, 3.5, 500)
>>> plt.plot(x, P(x), '-')
>>> plt.axhline(y=0)
>>> plt.title('A polynomial of order 3');
```


Line Plots

```
>>> import numpy as np
>>> from matplotlib import pyplot as plt


>>> y = np.arange(-5,6)**2
>>> y
array([25, 16, 9, 4, 1, 0, 1, 4, 9, 16, 25])
```

Visualize the plot.

```
>>> plt.plot(y) # Draw the line plot.
[<matplotlib.lines.Line2D object at 0x10842d0>]
>>> plt.show() # Reveal the resulting plot.
```



```
>>> x = np.linspace(-5, 5, 50)
>>> y = x**2 # Calculate the range of f(x) = x**2.
>>> plt.plot(x,y)
>>> plt.show()
```



- `plt.ion()`
- `plt.clf()`
- `plt.ioff()`

In IPython Notebook.

- `%matplotlib inline` shows the plot
- `%matplotlib notebook` shows the plot and provides controls to interact with the plot

Plot Customization


For `plt.plot()`

Key	Color	Key	Style
'b'	blue	'-'	solid line
'g'	green	'--'	dashed line
'r'	red	'-.'	dash-dot line
'c'	cyan	':'	dotted line
'k'	black	'o'	circle marker

Other functions

Function	Description
<code>legend()</code>	Place a legend in the plot
<code>title()</code>	Add a title to the plot
<code>xlim()</code> / <code>ylim()</code>	Set the limits of the <code>x</code> - or <code>y</code> -axis
<code>xlabel()</code> / <code>ylabel()</code>	Add a label to the <code>x</code> - or <code>y</code> -axis


```
>>> x1 = np.linspace(-2, 4, 100)
>>> plt.plot(x1, np.exp(x1), 'g:', ←
            linewidth=6, label="Exponential")
>>> plt.title("My title", fontsize=18)
>>> plt.legend(loc="upper left")
>>> plt.show()
```



Function	Description
<code>axes()</code>	Add an axes to the current figure
<code>figure()</code>	Create a new figure or grab an existing figure
<code>gca()</code>	Get the current axes
<code>gcf()</code>	Get the current figure
<code>subplot()</code>	Add a single subplot to the current figure
<code>subplots()</code>	Create a figure and add several subplots to it

```
# 3. Use plt.subplots() to get the figure and all subplots simultaneously.  
>>> fig, axes = plt.subplots(1, 2)  
>>> axes[0].plot(x, 2*x)  
>>> axes[1].plot(x, x**2)
```

Compare `axes()` vs `axis()` (access properties of the current plot)

```

import numpy as np
from matplotlib import pyplot as plt

def make_figure(x,f,name):
    plt.figure(figsize=(9,2))
    ax1 = plt.subplot(141)
    ax1.plot(x, f(x), 'k', lw=2)
    plt.title(name)

    ax2 = plt.subplot(142)
    ax2.semilogx(x, f(x), 'k', lw=2)
    ax2.set_title("Semi-Logarithmic x")

    ax3 = plt.subplot(143)
    ax3.semilogy(x, f(x), 'k', lw=2)
    ax3.set_title("Semi-Logarithmic y")


    ax4 = plt.subplot(144)
    ax4.loglog(x, f(x), 'k', lw=2)
    ax4.set_title("Logarithmic")
    plt.savefig(name+".png")

```

```

xx = np.linspace(.1, 2, 200)
make_figure(xx, lambda xx: np.exp(xx), ←
            "Exponential")
make_figure(xx, lambda xx: xx**3, "←
            Polynomial")
make_figure(xx, lambda xx: np.log(xx), ←
            "Logarithmic")

```





Scatter Plots and Histograms

```
>>> x = np.random.normal(scale=1.5, size=500)
>>> y = np.random.normal(scale=0.5, size=500)


>>> ax1 = plt.subplot(121)
>>> ax1.plot(x, y, 'o', markersize=5, alpha=.5) # transparent circles

>>> ax2 = plt.subplot(122)
>>> ax2.hist(x, bins=np.arange(-4.5, 5.5))
>>> plt.show()
```



3D Surfaces

`np.meshgrid()` given two 1-dimensional coordinate arrays, creates two corresponding coordinate matrices: $(X[i,j], Y[i,j]) = (x[i], y[j])$.



$$X = \begin{bmatrix} 0 & 1 & 2 \\ 0 & 1 & 2 \\ 0 & 1 & 2 \end{bmatrix}$$
$$Y = \begin{bmatrix} 2 & 2 & 2 \\ 1 & 1 & 1 \\ 0 & 0 & 0 \end{bmatrix}$$


```
>>> x, y = [0, 1, 2], [3, 4, 5]      # A rough domain over [0,2]x[3,5].
>>> X, Y = np.meshgrid(x, y)        # Combine the 1-D data into 2-D data.
>>> for trows in zip(X,Y):
...     print(trows)
...
(array([0 1 2]), array([3 3 3]))
(array([0 1 2]), array([4 4 4]))
(array([0 1 2]), array([5 5 5]))
```

3D Surfaces

$$g(x, y) = \sin(x) \sin(y)$$


```
>>> x = np.linspace(-np.pi, np.pi, 200)
>>> y = np.copy(x)
>>> X, Y = np.meshgrid(x, y)
>>> Z = np.sin(X) * np.sin(Y)

# Draw the corresponding 3-D plot using some ↵
#   extra tools.
>>> from mpl_toolkits.mplot3d import Axes3D
>>> fig = plt.figure()
>>> ax = fig.add_subplot(1,1,1, projection='3d')
>>> ax.plot_surface(X, Y, Z)
>>> plt.show()
```



Heat Map and Contour Plot

```
>>> x = np.linspace(-np.pi, np.pi, 100)
>>> y = x.copy()
>>> X, Y = np.meshgrid(x, y)
>>> Z = np.sin(X) * np.sin(Y)          # Calculate  $g(x,y) = \sin(x)\sin(y)$ .
# Plot the heat map of f over the 2-D domain.
>>> plt.subplot(131)
>>> plt.pcolormesh(X, Y, Z, cmap="viridis")
>>> plt.colorbar()
>>> plt.xlim(-np.pi, np.pi)
>>> plt.ylim(-np.pi, np.pi)
# Plot a contour map of f with 10 level curves.
>>> plt.subplot(132)
>>> plt.contour(X, Y, Z, 10, cmap="coolwarm")
>>> plt.colorbar()
# Plot a filled contour map, specifying the level curves.
>>> plt.subplot(133)
>>> plt.contourf(X, Y, Z, [-1, -.8, -.5, 0, .5, .8, 1], cmap="magma")
>>> plt.colorbar()
>>> plt.show()
```



1. Calculate all data that is needed for the animation.
2. Define a figure explicitly with `plt.figure()` and set its window boundaries.
3. Draw empty objects that can be altered dynamically.
4. Define a function to update the drawing objects.
5. Use `matplotlib.animation.FuncAnimation()`.

```
from matplotlib.animation import FuncAnimation
from mpl_toolkits.mplot3d import Axes3D

def sine_animation():
    # 1. Calculate the data to be animated.
    x = np.linspace(0, 2*np.pi, 200)[: -1]
    y = np.sin(x)    #
    # 2. Create a figure and set the window boundaries of the axes.
    fig = plt.figure()
    plt.xlim(0, 2*np.pi)
    plt.ylim(-1.2, 1.2) #
    # 3. Draw an empty line. The comma after 'drawing' is crucial.
    drawing, = plt.plot([], []) #
    # 4. Define a function that updates the line data.
    def update(index):
        drawing.set_data(x[:index], y[:index])
        return drawing,          # Note the comma!
    # 5.
    a = FuncAnimation(fig, update, frames=len(x), interval=10)
```

Further Reading and Tutorials

- <https://www.labri.fr/perso/nrougier/teaching/matplotlib/>.
- https://matplotlib.org/users/pyplot_tutorial.html.
- <http://www.scipy-lectures.org/intro/matplotlib/matplotlib.html>.
- <https://matplotlib.org/2.0.0/examples/animation/index.html>


Outline

1. Matplotlib


2. Other Data Visualization Libraries

3. Pandas

A high-level library on the top of Matplotlib. It's easier to generate certain kinds of plots: eg, heat maps, time series, and violin plots.



Based on R's ggplot2 and the Grammar of Graphics




Bokeh, Plotly, Gleam, Dash and Altair

Create interactive, web-ready plots, as JSON objects, HTML documents, or interactive web applications.


Bokeh is based on the Grammar of Graphics like ggplot.

Gleam is inspired by R's Shiny package.



Geoplotlib, Leaflet and MapBox

Toolbox for plotting geographical data: map-type plots, like choropleths, heatmaps, and dot density maps.



Graph Algorithms, Graph Drawings


```
import matplotlib.pyplot as plt

G = nx.Graph()
G.add_edge(1, 2)
G.add_edge(1, 3)
G.add_edge(1, 5)
G.add_edge(2, 3)
G.add_edge(3, 4)
G.add_edge(4, 5)

# explicitly set positions
pos = {1: (0, 0), 2: (-1, 0.3), 3: (2, 0.17), 4: (4, 0.255), 5: (5, 0.03)}


nx.draw_networkx(G, pos)

# Set margins for the axes so that nodes aren't clipped
ax = plt.gca()
ax.margins(0.20)
plt.axis("off")
plt.show()
```



Street Networks

```
import osmnx as ox  
G = ox.graph_from_bbox(37.79, 37.78, -122.41, -122.43, network_type='drive')  
G_projected = ox.project_graph(G)  
ox.plot_graph(G_projected)
```



Outline

Matplotlib
Other Data Visualization Libraries
Pandas

1. Matplotlib

2. Other Data Visualization Libraries

3. Pandas

Pandas Data Structures: Series

Pandas library for data management and analysis that combines functionality of NumPy, Matplotlib, and SQL

- Series is a one-dimensional array that can hold any datatype, similar to a ndarray but with an index that gives a label to each entry.

```
>>> import pandas as pd
>>>
>>> # Initialize Series of student grades
>>> math = pd.Series(np.random.randint(0,100,4), ['Mark', 'Barbara', 'Eleanor', ↵
    'David'])
>>> english = pd.Series(np.random.randint(0,100,5), ['Mark', 'Barbara', 'David' ↵
    , 'Greg', 'Lauren'])
```

Pandas Data Structures: Data Frames

- DataFrame is a collection of multiple Series. It can be thought of as a 2-dimensional array, where each row is a separate datapoint and each column is a feature of the data. The rows are labelled with an index (as in a Series) and the columns are labelled in the attribute columns.

```
>>> # Create a DataFrame of student grades
>>> grades = pd.DataFrame({"Math": math, "English": english})
>>> grades
```

	Math	English
Barbara	52.0	73.0
David	10.0	39.0
Eleanor	35.0	NaN
Greg	NaN	26.0
Lauren	NaN	99.0
Mark	81.0	68.0

Summary

1. Matplotlib

2. Other Data Visualization Libraries

3. Pandas