

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD		NRCC-PRF-E
Nonresidential Performance Compliance Method		(Page 1 of 51)
Project Name:	CUAC Example	Date Prepared: 2025-12-16

A. General Information					
1	Project Name	CUAC Example			
2	Run Title	Title 24 Analysis			
3	Project Location	123 Main Street			
4	City	San Carlos	5	Standards Version	Compliance 2022
6	Zip code	94070	7	Compliance Software (version)	CBECC 2022.3.2-SP1 (1369)
8	Climate Zone	3	9	Building Orientation (deg)	315
10	Building Type(s)	• High-Rise Residential	11	Weather File	SAN-FRANCISCO-INTL_STYP20.epw
12	Project Scope	• New complete scope	13	Number of Dwelling Units	33
14	Total Conditioned Floor Area in Scope (ft²)	25711	15	Total # of hotel/motel rooms	0
16	Total Unconditioned Floor Area (ft²)	0	17	Fuel Type	Liquefied propane gas
18	Nonresidential Conditioned Floor Area	0	19	Total # of Stories (Habitable Above Grade)	5
20	Residential Conditioned Floor Area	25711			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 2 of 51)

B. PROJECT SUMMARY							
Table B shows which building components are included in the performance calculation. If indicated as not included, the project must show compliance prescriptively if within the permit application.							
Building Components Complying via Performance					Building Components Complying Prescriptively		
Envelope (See Table G)	Nonres	Not Included	Solar Thermal Water Heating (See Table I3)	☐	Performance	The following building components are ONLY eligible for prescriptive compliance and should be documented on the NRCC form listed if within the scope of the permit application (i.e. compliance will not be shown on the NRCC-PRF-E).	
	MultiFam	Performance		☒	Not Included		
Mechanical (See Table H)	Nonres	Not Included	Covered Process: Commercial Kitchens (see Table J)	☐	Performance	Indoor Lighting (Unconditioned) 140.6 & 170.2(e)	NRCC-LTI-E is required
	MultiFam	Performance		☒	Not Included	Outdoor Lighting 140.7 & 170.2(e)	NRCC-LTO-E is required
Domestic Hot Water (See Table I)	Nonres	Not Included	Covered Process: Laboratory Exhaust (see Table J)	☐	Performance	Sign Lighting 140.8 & 170.2(e)	NRCC-LTS-E is required
	MultiFam	Performance		☒	Not Included	Building Components Complying with Mandatory Measures	
Lighting (Indoor Conditioned, see Table K)	Nonres	Not Included	Photovoltaics (see Table F)	☒	Performance	Electrical power systems, commissioning, solar ready, elevator and escalator requirements are mandatory and should be documented on the NRCC form listed if applicable (i.e. compliance will not be shown on the NRCC-PRF-E.)	
	MultiFam	Performance		☐	Not Included	Electrical Power Distribution 110.11	NRCC-ELC-E is required
			Battery (see Table F)	☒	Performance	Commissioning 120.8	NRCC-CXR-E is required
				☐	Not Included	Solar and Battery 110.10	NRCC-SAB-E is required

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 3 of 51)

C1. COMPLIANCE SUMMARY			
COMPLIES ³			
	Time Dependent Valuaton (TDV)		Source Energy Use
	Efficiency ¹ (kBtu/ft ² - yr)	Total ² (kBtu/ft ² - yr)	Total ² (kBtu/ft ² - yr)
Standard Design	49.27	-14.81	1.42
Proposed Design	38.09	-75.71	-1.22
Compliance Margins	11.18	60.9	2.64
	Pass	Pass	Pass
¹ Efficiency measures include improvements like a better building envelope and more efficient equipment ² Compliance Totals include efficiency, photovoltaics and batteries ³ New Construction, Complete Addition Scope: Building complies when all efficiency and total compliance margins are greater than or equal to zero and unmet load hour limits are not exceeded Existing, Addition and Alteration Scope: Building complies when efficiency compliance margin is greater than or equal to zero and unmet load hour limits are not exceeded			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 4 of 51)

C2. TDV ENERGY COMPLIANCE RESULTS FOR PERFORMANCE COMPONENTS (Annual TDV Energy Use, kBtu/ft² - yr)			
COMPLIES²			
Energy Component	Standard Design (TDV)	Proposed Design (TDV)	Compliance Margin (TDV)¹
Space Heating	3.15	2.23	0.92
Space Cooling	2.22	2.66	-0.44
Indoor Fans	10.55	10.5	0.05
Heat Rejection	0	0	0
Pumps & Misc.	0.25	0.25	0
Domestic Hot Water	33.1	22.45	10.65
Indoor Lighting	0	0	0
Flexibility	---	---	---
EFFICIENCY COMPLIANCE TOTAL	49.27	38.09	11.18 (22.7%)
Photovoltaics	-53.71	-103.19	49.48
Batteries	-10.37	-10.61	0.24
TOTAL COMPLIANCE	-14.81	-75.71	60.9 (0%)
¹ Notes: This number in parenthesis following the Compliance Margin in column 4, represents the Percent Better than Standard.			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 5 of 51)

C3. TDV ENERGY RESULTS FOR NON-REGULATED COMPONENTS¹			
Non-Regulated Energy Component	Standard Design (TDV)	Proposed Design (TDV)	Compliance Margin (TDV)¹
Receptacle	59.37	59.37	---
Process	29.67	29.82	-0.15
Other Ltg	9.78	9.78	---
Process Motors	---	---	---
TOTAL (TOTAL COMPLIANCE + NON-REGULATED COMPONENTS)	84.01	23.26	60.75 (72.3%)
¹ Notes: This table is not used for Energy Code Compliance.			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 6 of 51)

C4. SOURCE ENERGY COMPLIANCE RESULTS FOR PERFORMANCE COMPONENTS (Annual SOURCE Energy Use, kBtu/ft² /yr)			
COMPLIES²			
Energy Component	Standard Design (SOURCE)	Proposed Design (SOURCE)	Compliance Margin (SOURCE)¹
Space Heating	0.41	0.29	0.12
Space Cooling	0.02	0.02	0
Indoor Fans	0.96	0.94	0.02
Heat Rejection	0	0	0
Pumps & Misc.	0.03	0.03	0
Domestic Hot Water	3.06	2.15	0.91
Indoor Lighting	0	0	0
Flexibility	---	---	---
EFFICIENCY COMPLIANCE TOTAL	4.48	3.43	1.05 (23.4%)
Photovoltaics	-1.54	-2.97	1.43
Batteries	-1.52	-1.68	0.16
TOTAL COMPLIANCE	1.42	-1.22	2.64 (185.9%)
¹ Notes: This number in parenthesis following the Compliance Margin in column 4, represents the Percent Better than Standard.			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 7 of 51)

C5. SOURCE ENERGY RESULTS FOR NON-REGULATED COMPONENTS¹			
Non-Regulated Energy Component	Standard Design (SOURCE)	Proposed Design (SOURCE)	Compliance Margin (SOURCE)¹
Receptacle	5.59	5.59	---
Process	2.59	2.61	-0.02
Other Ltg	0.94	0.94	---
Process Motors	---	---	---
TOTAL (TOTAL COMPLIANCE + NON-REGULATED COMPONENTS)	10.54	7.92	2.62 (24.9%)
¹ Notes: This table is not used for Energy Code Compliance.			

C6. 'ABOVE CODE' QUALIFICATIONS	
☐ This project is pursuing CalGreen Tier 1	☐ This project is pursuing CalGreen Tier 2

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 8 of 51)

C7. ENERGY USE SUMMARY						
Energy Component	Standard Design Site (MWh)	Proposed Design Site (MWh)	Margin (MWh)	Standard Design Site (MBtu)	Proposed Design Site (MBtu)	Margin (MBtu)
Space Heating	2.8	2	0.8	---	---	---
Space Cooling	0.2	0.3	-0.1	---	---	---
Indoor Fans	9.5	9.4	0.1	---	---	---
Heat Rejection	---	---	---	---	---	---
Pumps & Misc.	0.2	0.2	0	---	---	---
Domestic Hot Water	32.2	23.7	8.5	---	---	---
Indoor Lighting	---	---	---	---	---	---
Flexibility	---	---	---	---	---	---
EFFICIENCY TOTAL	44.9	35.6	9.3	0	0	0
Photovoltaics	-72.1	-137.8	65.7	---	---	---
Batteries	1.3	1.5	-0.2	---	---	---
ENERGY USE SUBTOTAL	-25.9	-100.7	74.8	0	0	0
Receptacle	53.4	53.4	0	---	---	---
Process	27.3	27.4	-0.1	---	---	---
Other Ltg	7.9	7.9	0	---	---	---
Process Motors	---	---	---	---	---	---
ENERGY USE TOTAL	62.7	-12	74.7	0	0	0

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 9 of 51)

C8. ENERGY USE INTENSITY (EUI)				
	Standard Design (kBtu/ft² / yr)	Proposed Design (kBtu/ft² / yr)	Margin (kBtu/ft² / yr)	Margin Percentage
GROSS EUI ¹	17.89	16.69	1.2	6.71
NET EUI ¹	8.32	-1.59	9.91	119.11
¹ Notes: Gross EUI is Energy Use Total (not including PV)/Total Building Area. Net EUI is Energy Use Total (including PV)/Total Building Area.				

D2. MULTIFAMILY REQUIRED SPECIAL FEATURES
• Battery System: 50.7 kWh • Indoor air quality, balanced fan • Floor has high level of insulation • Insulation below roof deck • Northwest Energy Efficiency Alliance (NEEA) rated heat pump water heater; specific brand/model, or equivalent, must be installed • One or more heat pump water heaters have been modeled as demand response compatible

F1. REQUIRED PV SYSTEMS											
01	02	03	04	05	06	07	08	09	10	11	12
DC System Size (kWdc)	Exception¹	Module Type	Array Type	Power Electronics	CFI	Azimuth (deg)	Tilt Input	Array Angle (deg)	Tilt: (x in 12)	Inverter Eff. (%)	Annual Solar Access (%)
85		Standard (14-17%)	Fixed	none	false	180	Degrees	22	4.85	96	100
¹ See Table D1 for any PV exceptions used.											

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 10 of 51)

F1B. PV BATTERY BUILDING TYPE(S)		
01	02	03
Building Occupancy Type* (From Table 140.10-A/B and 170.2-U/V)	Conditioned Floor Area (ft²)	Unconditioned Floor Area (ft²)
Grocery	0	0
High-Rise Multifamily	25711	0
Office, Financial Institutions, Unleased Tenant Space	0	0
Retail	0	0
School	0	0
Warehouse	0	0
Auditorium, Convention Center, Hotel/Motel, Library, Medical Office Building/Clinic, Restaurant, Theater	0	0
None	0	0
<i>*Building Occupancy Types are defined in Section 100.1 of the Energy Code</i>		

F2. BATTERY SYSTEMS¹						
01	02	03	04	05	06	07
Control	Capacity (kWh)	Charging Efficiency	Charging Rate (kW)	Discharging Efficiency	Discharging Rate (kW)	Round Trip Efficiency
TOU	50.7	N/A	12.17	N/A	12.17	0.9
¹ See Table D1 for any Battery exceptions used.						

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 11 of 51)

F3. DWELLING UNIT INFORMATION			
01	02	03	04
Dwelling Unit Name	Dwelling Unit Type	Zone	Zone Group Multiplier
DDU-1-(1/1)	DU-1	S-1-2-BD-699 1-R-2	1
DDU-5-(1/1)	DU-5	S-5-3-BD-971 2-F-2	1
DDU-9-(1/1)	DU-9	S-9-1-BD-520 3-F-2	1
DDU-13-(1/1)	DU-13	S-13-1-BD-503 4-F-2	1
DDU-15-(1/1)	DU-15	S-15-2-BD-875 5-F-2	1
DDU-21-(1/1)	DU-21	S-21-3-BD-918 7-B-2	1
DDU-2-(1/1)	DU-2	S-2-2-BD-699 1-R-3	1
DDU-6-(1/1)	DU-6	S-6-3-BD-971 2-F-3	1
DDU-10-(1/1)	DU-10	S-10-1-BD-520 3-F-3	1
DDU-14-(1/1)	DU-14	S-14-1-BD-504 4-F-3	1
DDU-16-(1/1)	DU-16	S-16-2-BD-875 5-F-3	1
DDU-19-(1/1)	DU-19	S-19-1-BD-505 6-L-3	1
DDU-22-(1/1)	DU-22	S-22-3-BD-918 7-B-3	1
DDU-25-(1/1)	DU-25	S-25-1-BD-501 8-B-3	1
DDU-28-(1/1)	DU-28	S-28-1-BD-503 9-B-3	1
DDU-31-(1/1)	DU-31	S-31-1-BD-503 10-B-3	1
DDU-3-(1/1)	DU-3	S-3-2-BD-699 1-R-4	1
DDU-7-(1/1)	DU-7	S-7-3-BD-977 2-F-4	1
DDU-11-(1/1)	DU-11	S-11-3-BD-1053 3-F-4	1
DDU-17-(1/1)	DU-17	S-17-2-BD-868 5-F-4	1
DDU-20-(1/1)	DU-20	S-20-1-BD-505 6-L-4	1
DDU-23-(1/1)	DU-23	S-23-3-BD-918 7-B-4	1
DDU-26-(1/1)	DU-26	S-26-1-BD-503 8-B-4	1
DDU-29-(1/1)	DU-29	S-29-1-BD-503 9-B-4	1
DDU-32-(1/1)	DU-32	S-32-1-BD-503 10-B-4	1
DDU-4-(1/1)	DU-4	S-4-2-BD-699 1-R-5	1

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 12 of 51)

F3. DWELLING UNIT INFORMATION			
01	02	03	04
Dwelling Unit Name	Dwelling Unit Type	Zone	Zone Group Multiplier
DDU-8-(1/1)	DU-8	S-8-3-BD-977 2-F-5	1
DDU-12-(1/1)	DU-12	S-12-3-BD-1040 3-F-5	1
DDU-18-(1/1)	DU-18	S-18-2-BD-870 5-F-5	1
DDU-24-(1/1)	DU-24	S-24-2-BD-797 7-B-5	1
DDU-27-(1/1)	DU-27	S-27-1-BD-503 8-B-5	1
DDU-30-(1/1)	DU-30	S-30-1-BD-503 9-B-5	1
DDU-33-(1/1)	DU-33	S-33-1-BD-503 10-B-5	1

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 13 of 51)

F4. DWELLING UNIT TYPES						
01	02	03	04	05	06	07
Name	CFA (ft²)	Number of Bedrooms	Number in Building	Space Conditioning Systems Assigned	DHW System Name	IAQ Vent Fan Name
DU-1	762	2	1	DU-1 :Heat Pump System 1:::2:3	MF0-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-2	762	2	1	DU-2 :Heat Pump System 1:::2:3	MF0-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-3	762	2	1	DU-3 :Heat Pump System 1:::2:3	MF0-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-4	762	2	1	DU-4 :Heat Pump System 1:::2:3	MF0-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-5	1057	3	1	DU-5 :Heat Pump System 2:::2:3	MF1-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-6	1057	3	1	DU-6 :Heat Pump System 2:::2:3	MF1-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-7	1047	3	1	DU-7 :Heat Pump System 2:::2:3	MF1-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-8	1047	3	1	DU-8 :Heat Pump System 2:::2:3	MF1-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-9	583	1	1	DU-9 :Heat Pump System 3:::2:3	MF2-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan
DU-10	583	1	1	DU-10 :Heat Pump System 3:::2:3	MF2-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan
DU-11	1142	3	1	DU-11 :Heat Pump System 4:::2:3	MF3-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-12	1150	3	1	DU-12 :Heat Pump System 4:::2:3	MF3-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-13	561	1	1	DU-13 :Heat Pump System 5:::2:3	MF4-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan
DU-14	576	1	1	DU-14 :Heat Pump System 5:::2:3	MF4-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 14 of 51)

F4. DWELLING UNIT TYPES						
01	02	03	04	05	06	07
Name	CFA (ft²)	Number of Bedrooms	Number in Building	Space Conditioning Systems Assigned	DHW System Name	IAQ Vent Fan Name
DU-15	952	2	1	DU-15 :Heat Pump System 6:::2:3	MF5-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-16	952	2	1	DU-16 :Heat Pump System 6:::2:3	MF5-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-17	952	2	1	DU-17 :Heat Pump System 6:::2:3	MF5-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-18	938	2	1	DU-18 :Heat Pump System 6:::2:3	MF5-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-19	574	1	1	DU-19 :Heat Pump System 7:::2:3	MF6-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan
DU-20	574	1	1	DU-20 :Heat Pump System 7:::2:3	MF6-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan
DU-21	997	3	1	DU-21 :Heat Pump System 8:::2:3	MF7-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-22	997	3	1	DU-22 :Heat Pump System 8:::2:3	MF7-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-23	997	3	1	DU-23 :Heat Pump System 8:::2:3	MF7-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-24	878	2	1	DU-24 :Heat Pump System 9:::2:3	MF8-2-BD Rheem PROPH65 T2 RH31	Default Minimum Balanced IAQ Fan
DU-25	561	1	1	DU-25 :Heat Pump System 10:::2:3	MF9-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan
DU-26	561	1	1	DU-26 :Heat Pump System 10:::2:3	MF9-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan
DU-27	561	1	1	DU-27 :Heat Pump System 10:::2:3	MF9-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan
DU-28	561	1	1	DU-28 :Heat Pump System 11:::2:3	MF10-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 15 of 51)

F4. DWELLING UNIT TYPES						
01	02	03	04	05	06	07
Name	CFA (ft ²)	Number of Bedrooms	Number in Building	Space Conditioning Systems Assigned	DHW System Name	IAQ Vent Fan Name
DU-29	561	1	1	DU-29 :Heat Pump System 11:::2:3	MF10-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan
DU-30	561	1	1	DU-30 :Heat Pump System 11:::2:3	MF10-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan
DU-31	561	1	1	DU-31 :Heat Pump System 12:::2:3	MF11-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan
DU-32	561	1	1	DU-32 :Heat Pump System 12:::2:3	MF11-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan
DU-33	561	1	1	DU-33 :Heat Pump System 12:::2:3	MF11-1-BD Rheem PROPH50 T2 RH32	Default Minimum Balanced IAQ Fan

G1. ENVELOPE GENERAL INFORMATION (conditioned spaces only)			
01	02	03	04
Opaque Surfaces & Orientation	Total Gross Surface Area (ft ²)	Total Fenestration Area (ft ²)	Window to Wall Ratio (%)
North-Facing ¹	4216	854	20.26
East-Facing ²	4195	1104	26.32
South-Facing ³	2978	646	21.69
West-Facing ⁴	4049	1014	25.04
Total	15438	3618	23.44
Roof	5216	0	0
Notes ¹ North-Facing is oriented to within 45 degrees of true north, including 4500'00" east of north (NE), but excluding 4500'00" west of north (NW), ² East-Facing is oriented to within 45 degrees of true east, including 4500'00" south of east (SE), but excluding 4500'00" north of east (NE), ³ South-Facing is oriented to within 45 degrees of true south, including 4500'00" west of south (SW), but excluding 4500'00" east of south (SE), ⁴ West-Facing is oriented to within 45 degrees of true west, including 4500'00" north of west (NW), but excluding 4500'00" south of west (SW),			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 16 of 51)

G2B. ROOFING PRODUCT SUMMARY (MULTIFAMILY AND COMMON AREAS)					
01	02	03	04	05	06
Name	Roof Pitch	Roof Rise (x in 12)	Aged Solar Reflectance	Thermal Emittance	SRI
Roof 505	Low slope	0	0.1	0.85	N/A
Roof	Low slope	0	0.1	0.85	N/A
Roof 977	Low slope	0	0.1	0.85	N/A
Roof 1040	Low slope	0	0.1	0.85	N/A
Roof 2	Low slope	0	0.1	0.85	N/A
Roof 3	Low slope	0	0.1	0.85	N/A
Roof 4	Low slope	0	0.1	0.85	N/A
Attic S-18-2-BD-870 5-F-5	Steep slope	3	0.1	0.85	N/A
Attic S-24-2-BD-797 7-B-5	Steep slope	3	0.1	0.85	N/A

G3. ATTIC			
01	02	03	04
Name	Construction	Type	Radiant Barrier
Attic S-18-2-BD-870 5-F-5	Roof-Attic S-18-2-BD-870 5-F-5	Ventilated	No
Attic S-24-2-BD-797 7-B-5	Roof-Attic S-24-2-BD-797 7-B-5	Ventilated	No

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 17 of 51)

G5. OPAQUE SURFACE ASSEMBLY SUMMARY										
01	02	03	04	05	06		07	08	09	10
Surface Name	Construction Type	Area (ft²)	Framing Type	Cavity R-Value	Continuous R-Value		Units	Value	Description of Assembly Layers	Status ¹
					Interior	Exterior				
R-19 Wall	Exterior Walls	15,057	Wood Framed Wall	19	0	0	U-factor	0.0719	Inside Finish: Gypsum Board Cavity / Frame: R-19 / 2x6 Exterior Finish: 3 Coat Stucco	N
Interior Wall - High	Interior Walls	19,366	Wood Framed Wall	13	0	0	U-factor	0.0919	Inside Finish: Gypsum Board Cavity / Frame: R-13 / 2x4 Other Side Finish: Gypsum Board	
Interior Floor - High- L2	Exterior Floors	7,169	Wood Framed Floor	38	0	0	U-factor	0.028	Floor Surface: Carpeted Floor Deck: Wood Siding/sheathing/decking Cavity / Frame: R-38 / 2x12	N
Interior Floor - High	Interior Floors	18,543.9	Wood Framed Floor	0	0	0	U-factor	0.1957	Floor Surface: Carpeted Floor Deck: Wood Siding/sheathing/decking Cavity / Frame: no insul. / 2x12 Ceiling Below Finish: Gypsum Board	N
FLOOR-ROOF ROOF DECK	Cathedral Ceilings	5,216	Built-up Roof	0	39	0	U-factor	0.0243	Roofing: Light Roof (Asphalt Shingle) Roof Deck: Wood Siding/sheathing/decking Cavity / Frame: no insul. / 2x4 Top Chrd Sheathing / Insulation: R-39 Sheathing Inside Finish: Gypsum Board	N
Roof - High	Ceilings (below attic)	1,816	Wood Framed Ceiling	0	0	0	U-factor	0.4812	Cavity / Frame: no insul. / 2x4 Inside Finish: Gypsum Board	N
R-21 Wall	Exterior Walls	381	Wood Framed Wall	21	0	0	U-factor	0.0686	Inside Finish: Gypsum Board Cavity / Frame: R-21 / 2x6 Exterior Finish: 3 Coat Stucco	N
¹ Status: N - New, A - Altered, E - Existing										

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 18 of 51)

G5. OPAQUE SURFACE ASSEMBLY SUMMARY										
01	02	03	04	05	06		07	08	09	10
Surface Name	Construction Type	Area (ft²)	Framing Type	Cavity R-Value	Continuous R-Value		Units	Value	Description of Assembly Layers	Status ¹
					Interior	Exterior				
Roof-Attic S-18-2-BD-870 5-F-5	Attic Roofs	938	Wood Framed Ceiling	39	0	0	U-factor	0.0368	Roofing: Light Roof (Asphalt Shingle) Roof Deck: Wood Siding/sheathing/decking Cavity / Frame: R-13.0 / 2x4 Around Roof Joists: R-26.0 insul.	N
Roof-Attic S-24-2-BD-797 7-B-5	Attic Roofs	878	Wood Framed Ceiling	39	0	0	U-factor	0.0368	Roofing: Light Roof (Asphalt Shingle) Roof Deck: Wood Siding/sheathing/decking Cavity / Frame: R-13.0 / 2x4 Around Roof Joists: R-26.0 insul.	N
¹ Status: N - New, A - Altered, E - Existing										

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 19 of 51)

G6B. OPAQUE DOOR SUMMARY (MULTIFAMILY AND COMMON AREAS)			
01	02	03	04
Name	Area (ft²)	Overall U-factor	Status¹
Door 1 3070 21	21	0.1099	N
Door 1 3070 21 2	21	0.1099	N
Door 1 3070 21 3	21	0.1099	N
Door 1 3070 21 4	21	0.1099	N
Door 1 3070 21 5	21	0.1099	N
Door 1 3070 21 6	21	0.1099	N
Door 1 3070 21 7	21	0.1099	N
Door 1 3070 21 8	21	0.1099	N
Door 1 3070 21 9	21	0.1099	N
Door 1 3070 21 10	21	0.1099	N
Door 1 3070 21 11	21	0.1099	N
Door 1 3070 21 12	21	0.1099	N
Door 1 3070 21 13	21	0.1099	N
Door 1 3070 21 14	21	0.1099	N
Door 1 3070 21 15	21	0.1099	N
Door 1 3070 21 16	21	0.1099	N
Door 1 3070 21 17	21	0.1099	N
Door 1 3070 21 18	21	0.1099	N
Door 1 3070 21 19	21	0.1099	N
Door 1 3070 21 20	21	0.1099	N
Door 1 3070 21 21	21	0.1099	N
Door 1 3070 21 22	21	0.1099	N
Door 1 3070 21 23	21	0.1099	N
Door 1 3070 21 24	21	0.1099	N
¹ Status: N - New, A - Altered, E - Existing			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 20 of 51)

G6B. OPAQUE DOOR SUMMARY (MULTIFAMILY AND COMMON AREAS)			
01	02	03	04
Name	Area (ft ²)	Overall U-factor	Status ¹
Door 1 3070 21 25	21	0.1099	N
Door 1 3070 21 26	21	0.1099	N
Door 1 3070 21 27	21	0.1099	N
Door 1 3070 21 28	21	0.1099	N
Door 1 3070 21 29	21	0.1099	N
Door 1 3070 21 30	21	0.1099	N
Door 1 3070 21 31	21	0.1099	N
Door 1 3070 21 32	21	0.1099	N
Door 1 3070 21 33	21	0.1099	N
¹ Status: N - New, A - Altered, E - Existing			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 21 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window F 5060 30.0	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 2	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 2	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 22 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window F 5060 30.0 5	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2)	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2)	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 5	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2)	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 6	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 6	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 7	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 2	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 7	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 2	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 23 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window F 5060 30.0 8	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FDF	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 8	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FDF	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 9	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FDF	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 10	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FD	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 9	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FD	225	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 11	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left F(2)	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 12	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left F(2)	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 24 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window F 5060 30.0 13	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 2	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 10	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 2	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 11	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 2	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 14	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FDA	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 12	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FDA	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window A 2040 8.0	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FDA	45	1	8	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 15	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 3	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 25 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window D 4060 24.0 13	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 3	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 16	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D 2	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 17	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D 2	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 14	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D 2	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 18	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 4	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 15	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 4	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 19	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 3	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 26 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window D 4060 24.0 16	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 3	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 17	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 3	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 20	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 3	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 18	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 3	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 21	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 5	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 19	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 5	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 22	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 4	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 27 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window D 4060 24.0 20	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 4	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 21	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 4	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 23	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FDF 2	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 22	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FDF 2	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 24	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FDF 2	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 25	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FD 2	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 23	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FD 2	225	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 28 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window D 4060 24.0 24	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back D(2)FA	225	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 25	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back D(2)FA	225	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 26	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back D(2)FA	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window A 2040 8.0 2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back D(2)FA	225	1	8	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 27	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left F(2) 2	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 28	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left F(2) 2	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 29	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 4	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 29 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window D 4060 24.0 26	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 4	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 27	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 4	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 30	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FDA 2	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 28	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FDA 2	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window A 2040 8.0 3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FDA 2	45	1	8	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 31	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 5	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 29	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 5	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 30 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window F 5060 30.0 32	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 6	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 30	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 6	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 33	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 7	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 31	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 7	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 34	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 6	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 32	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 6	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 35	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D 3	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 31 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window F 5060 30.0 36	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D 3	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 33	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D 3	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 37	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 7	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 34	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 7	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 38	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 5	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 35	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 5	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 36	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 5	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 32 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window F 5060 30.0 39	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D(2)	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 37	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D(2)	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 40	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D(2)	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 38	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D(2)	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 41	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FDF 3	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 39	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FDF 3	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 42	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FDF 3	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 33 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window F 5060 30.0 43	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FD 3	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 40	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FD 3	225	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 41	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back D(2)FA 2	225	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 42	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back D(2)FA 2	225	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 44	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back D(2)FA 2	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window A 2040 8.0 4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back D(2)FA 2	225	1	8	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 45	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left F(2) 3	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 34 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window F 5060 30.0 46	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left F(2) 3	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 47	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 6	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 43	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 6	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 44	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 6	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 48	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FDA 3	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 45	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FDA 3	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window A 2040 8.0 5	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FDA 3	45	1	8	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 35 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window F 5060 30.0 49	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 8	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 46	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 8	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 50	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 9	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 47	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 9	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 51	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 10	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 48	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 10	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 52	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 8	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 36 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window D 4060 24.0 49	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 8	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 53	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D 4	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 54	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D 4	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 50	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D 4	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 55	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 9	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 51	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 9	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 56	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 7	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 37 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window D 4060 24.0 52	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 7	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 53	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 7	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 57	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D(2) 2	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 54	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D(2) 2	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 58	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D(2) 2	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 55	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back F(2)D(2) 2	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 59	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FDF 4	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 38 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window D 4060 24.0 56	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FDF 4	135	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 60	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FDF 4	135	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 61	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FD(2)	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 57	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FD(2)	225	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 58	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FD(2)	225	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 62	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 10	225	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 59	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Left FD 10	225	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 39 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window F 5060 30.0 63	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 8	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 60	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 8	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 61	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD(2) 8	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 64	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FDA 4	45	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 62	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FDA 4	45	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window A 2040 8.0 6	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Right FDA 4	45	1	8	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 65	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 11	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 40 of 51)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window D 4060 24.0 63	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 11	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 66	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 12	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 64	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 12	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window F 5060 30.0 67	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 13	315	1	30	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
Window D 4060 24.0 65	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Back FD 13	315	1	24	0.26	NFRC	0.24	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 41 of 51)

H2. DWELLING UNIT HVAC HEATING AND COOLING SYSTEMS												
01	02	03	04	05	06	07	08	09	10	11	12	13
Dwelling Unit Type	Equipment Name	Equipment Type	Quantity	Air Distribution System Name	Fan System name	Heating				Cooling		
						Heat Output at 47	Heat Output at 17	Efficiency Unit	Efficiency	Total Cooling Output	Efficiency Unit	Efficiency
DU-1	Heat Pump System 1	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-2	Heat Pump System 1	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-3	Heat Pump System 1	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-4	Heat Pump System 1	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-5	Heat Pump System 2	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-6	Heat Pump System 2	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-7	Heat Pump System 2	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-8	Heat Pump System 2	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-9	Heat Pump System 3	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-10	Heat Pump System 3	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-11	Heat Pump System 4	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-12	Heat Pump System 4	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-13	Heat Pump System 5	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD											NRCC-PRF-E	
Nonresidential Performance Compliance Method											(Page 42 of 51)	

H2. DWELLING UNIT HVAC HEATING AND COOLING SYSTEMS												
01	02	03	04	05	06	07	08	09	10	11	12	13
Dwelling Unit Type	Equipment Name	Equipment Type	Quantity	Air Distribution System Name	Fan System name	Heating				Cooling		
						Heat Output at 47	Heat Output at 17	Efficiency Unit	Efficiency	Total Cooling Output	Efficiency Unit	Efficiency
DU-14	Heat Pump System 5	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-15	Heat Pump System 6	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-16	Heat Pump System 6	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-17	Heat Pump System 6	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-18	Heat Pump System 6	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-19	Heat Pump System 7	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-20	Heat Pump System 7	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-21	Heat Pump System 8	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-22	Heat Pump System 8	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-23	Heat Pump System 8	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-24	Heat Pump System 9	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-25	Heat Pump System 10	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-26	Heat Pump System 10	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 43 of 51)

H2. DWELLING UNIT HVAC HEATING AND COOLING SYSTEMS												
01	02	03	04	05	06	07	08	09	10	11	12	13
Dwelling Unit Type	Equipment Name	Equipment Type	Quantity	Air Distribution System Name	Fan System name	Heating				Cooling		
						Heat Output at 47	Heat Output at 17	Efficiency Unit	Efficiency	Total Cooling Output	Efficiency Unit	Efficiency
DU-27	Heat Pump System 10	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-28	Heat Pump System 11	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-29	Heat Pump System 11	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-30	Heat Pump System 11	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-31	Heat Pump System 12	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-32	Heat Pump System 12	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2
DU-33	Heat Pump System 12	Room HP N/A	1	N/A	N/A	10,407	N/A	HSPF2	3.3	N/A	CEER	11.2

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 44 of 51)

H10. MULTIFAMILY DWELLING UNIT TYPE CENTRAL / INDIVIDUAL VENTILATION												
01	02	03	04	05	06	07	08	09	10	11	12	13
Dwelling Unit Type	IAQ Option	Central Fan (If applicable)					Individual Fan (if applicable)					
		IAQ Fan Type Type	Supply Airflow CFM	Supply Fan Efficacy W/CFM	Exhaust CFM	Exhaust Fan Efficacy W/CFM	IAQ Fan Type	Count	Airflow CFM	Fan Efficacy W/CFM	Recovery Efficiency SRE	Recovery Efficiency ASRE
DU-1	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	45.36	N/A	N/A	N/A
DU-2	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	45.36	N/A	N/A	N/A
DU-3	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	45.36	N/A	N/A	N/A
DU-4	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	45.36	N/A	N/A	N/A
DU-5	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	61.71	N/A	N/A	N/A
DU-6	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	61.71	N/A	N/A	N/A
DU-7	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	61.41	N/A	N/A	N/A
DU-8	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	61.41	N/A	N/A	N/A
DU-9	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	32.49	N/A	N/A	N/A
DU-10	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	32.49	N/A	N/A	N/A
DU-11	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	64.26	N/A	N/A	N/A
DU-12	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	64.5	N/A	N/A	N/A
DU-13	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	31.83	N/A	N/A	N/A

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 45 of 51)

H10. MULTIFAMILY DWELLING UNIT TYPE CENTRAL / INDIVIDUAL VENTILATION												
01	02	03	04	05	06	07	08	09	10	11	12	13
Dwelling Unit Type	IAQ Option	Central Fan (If applicable)					Individual Fan (if applicable)					
		IAQ Fan Type Type	Supply Airflow CFM	Supply Fan Efficacy W/CFM	Exhaust CFM	Exhaust Fan Efficacy W/CFM	IAQ Fan Type	Count	Airflow CFM	Fan Efficacy W/CFM	Recovery Efficiency SRE	Recovery Efficiency ASRE
DU-14	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	32.28	N/A	N/A	N/A
DU-15	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	51.06	N/A	N/A	N/A
DU-16	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	51.06	N/A	N/A	N/A
DU-17	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	51.06	N/A	N/A	N/A
DU-18	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	50.64	N/A	N/A	N/A
DU-19	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	32.22	N/A	N/A	N/A
DU-20	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	32.22	N/A	N/A	N/A
DU-21	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	59.91	N/A	N/A	N/A
DU-22	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	59.91	N/A	N/A	N/A
DU-23	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	59.91	N/A	N/A	N/A
DU-24	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	48.84	N/A	N/A	N/A
DU-25	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	31.83	N/A	N/A	N/A
DU-26	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	31.83	N/A	N/A	N/A

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 46 of 51)

H10. MULTIFAMILY DWELLING UNIT TYPE CENTRAL / INDIVIDUAL VENTILATION												
01	02	03	04	05	06	07	08	09	10	11	12	13
Dwelling Unit Type	IAQ Option	Central Fan (If applicable)					Individual Fan (if applicable)					
		IAQ Fan Type Type	Supply Airflow CFM	Supply Fan Efficacy W/CFM	Exhaust CFM	Exhaust Fan Efficacy W/CFM	IAQ Fan Type	Count	Airflow CFM	Fan Efficacy W/CFM	Recovery Efficiency SRE	Recovery Efficiency ASRE
DU-27	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	31.83	N/A	N/A	N/A
DU-28	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	31.83	N/A	N/A	N/A
DU-29	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	31.83	N/A	N/A	N/A
DU-30	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	31.83	N/A	N/A	N/A
DU-31	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	31.83	N/A	N/A	N/A
DU-32	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	31.83	N/A	N/A	N/A
DU-33	Default Minimum Balanced IAQ Fan	N/A	N/A	N/A	N/A	N/A	N/A	N/A	31.83	N/A	N/A	N/A

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 47 of 51)

I1. WATER HEATER EQUIPMENT SUMMARY													
01	02	03	04	05	06	07	08	09	10	11	12	13	14
Name	Heater Element Type	Tank Type	Qty	Tank Vol (gal)	Rated Input	Rated Input Unit	Efficiency	Efficiency Unit	Tank Insulation R-value Int/Ext	Standby Loss Fraction	1st Hr. Rating or Flow Rate (gal)	Heat Pump Type	Tank Location or Ambient Condition
2-BD Rheem PROPH65 T2 RH310	Heat Pump	Storage	4	65	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Outside
2-BD Rheem PROPH65 T2 RH311	Heat Pump	Storage	4	65	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Outside
1-BD Rheem PROPH50 T2 RH322	Heat Pump	Storage	2	50	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Outside
2-BD Rheem PROPH65 T2 RH313	Heat Pump	Storage	2	65	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Outside
1-BD Rheem PROPH50 T2 RH324	Heat Pump	Storage	2	50	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Outside
2-BD Rheem PROPH65 T2 RH315	Heat Pump	Storage	4	65	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Outside
1-BD Rheem PROPH50 T2 RH326	Heat Pump	Storage	2	50	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Outside

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 48 of 51)

I1. WATER HEATER EQUIPMENT SUMMARY													
01	02	03	04	05	06	07	08	09	10	11	12	13	14
Name	Heater Element Type	Tank Type	Qty	Tank Vol (gal)	Rated Input	Rated Input Unit	Efficiency	Efficiency Unit	Tank Insulation R-value Int/Ext	Standby Loss Fraction	1st Hr. Rating or Flow Rate (gal)	Heat Pump Type	Tank Location or Ambient Condition
2-BD Rheem PROPH65 T2 RH317	Heat Pump	Storage	3	65	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Outside
2-BD Rheem PROPH65 T2 RH318	Heat Pump	Storage	1	65	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Outside
1-BD Rheem PROPH50 T2 RH329	Heat Pump	Storage	3	50	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Outside
1-BD Rheem PROPH50 T2 RH3210	Heat Pump	Storage	3	50	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Outside
1-BD Rheem PROPH50 T2 RH3211	Heat Pump	Storage	3	50	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Outside

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 49 of 51)

I2. MULTI-FAMILY WATER HEATING SYSTEM DETAIL							
01	02	03	04	05	06	07	08
System Name	Configuration	Type	Qty in System	Dwelling Unit Distribution Type	Water Heater Name	Solar Heating System	Is Compact Distribution
MF0-2-BD Rheem PROPH65 T2 RH31	Domestic Hot Water (DHW)	Unitary	1	HERS Verified Pipe Insulation credit	2-BD Rheem PROPH65 T2 RH310	N/A	No
MF1-2-BD Rheem PROPH65 T2 RH31	Domestic Hot Water (DHW)	Unitary	1	HERS Verified Pipe Insulation credit	2-BD Rheem PROPH65 T2 RH311	N/A	No
MF2-1-BD Rheem PROPH50 T2 RH32	Domestic Hot Water (DHW)	Unitary	1	HERS Verified Pipe Insulation credit	1-BD Rheem PROPH50 T2 RH322	N/A	No
MF3-2-BD Rheem PROPH65 T2 RH31	Domestic Hot Water (DHW)	Unitary	1	HERS Verified Pipe Insulation credit	2-BD Rheem PROPH65 T2 RH313	N/A	No
MF4-1-BD Rheem PROPH50 T2 RH32	Domestic Hot Water (DHW)	Unitary	1	HERS Verified Pipe Insulation credit	1-BD Rheem PROPH50 T2 RH324	N/A	No
MF5-2-BD Rheem PROPH65 T2 RH31	Domestic Hot Water (DHW)	Unitary	1	HERS Verified Pipe Insulation credit	2-BD Rheem PROPH65 T2 RH315	N/A	No
MF6-1-BD Rheem PROPH50 T2 RH32	Domestic Hot Water (DHW)	Unitary	1	HERS Verified Pipe Insulation credit	1-BD Rheem PROPH50 T2 RH326	N/A	No
MF7-2-BD Rheem PROPH65 T2 RH31	Domestic Hot Water (DHW)	Unitary	1	HERS Verified Pipe Insulation credit	2-BD Rheem PROPH65 T2 RH317	N/A	No
MF8-2-BD Rheem PROPH65 T2 RH31	Domestic Hot Water (DHW)	Unitary	1	HERS Verified Pipe Insulation credit	2-BD Rheem PROPH65 T2 RH318	N/A	No
MF9-1-BD Rheem PROPH50 T2 RH32	Domestic Hot Water (DHW)	Unitary	1	HERS Verified Pipe Insulation credit	1-BD Rheem PROPH50 T2 RH329	N/A	No
MF10-1-BD Rheem PROPH50 T2 RH32	Domestic Hot Water (DHW)	Unitary	1	HERS Verified Pipe Insulation credit	1-BD Rheem PROPH50 T2 RH3210	N/A	No
MF11-1-BD Rheem PROPH50 T2 RH32	Domestic Hot Water (DHW)	Unitary	1	HERS Verified Pipe Insulation credit	1-BD Rheem PROPH50 T2 RH3211	N/A	No

K4. INDOOR CONDITIONED LIGHTING MANDATORY LIGHTING CONTROL
Building Level Controls

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 50 of 51)

01	02
Mandatory Demand Response 110.12(c)	Shut-Off Controls 130.1(c) & 160.5(b)4C
Required	Required
See NRCC-LTI-E for mandatory controls	

L. DECLARATION OF REQUIRED CERTIFICATES OF INSTALLATION	
Selections made by Documentation Author indicate which Certificates of Installation must be submitted for the features to be recognized for compliance. These documents must be retained and provided to the building inspector during construction and can be found online	
Building Component	Form/Title
Envelope	NRCI-ENV-E - Envelope (for all buildings)
Plumbing	NRCI-PLB-E - For all buildings with Plumbing Systems
	NRCI-SAB-E - Solar Water Heating, PV and Battery Storage Systems
Indoor Lighting	NRCI-LTI-E - Indoor Lighting (for all buildings)

M. DECLARATION OF REQUIRED CERTIFICATES OF ACCEPTANCE	
Selections made by Documentation Author indicate which Certificates of Acceptance must be submitted for the features to be recognized for compliance. These documents must be provided to the building inspector during construction and must be completed through an Acceptance Test Technician Certification Provider (ATTCP).	
Building Component	Form/Title & System Name(s)
Indoor Lighting	NRCA-LTI-02-A - Occupancy Sensors and Automatic Time Switch Controls.
Indoor Lighting	NRCA-LTI-04-A - Demand Responsive Lighting Controls.

N. DECLARATION OF REQUIRED CERTIFICATES OF VERIFICATION	
Selections made by Documentation Author indicate which Certificates of Verification must be submitted for the features to be recognized for compliance. These documents must be retained and provided to the building inspector during construction and can be found online	
Building Component	Form/Title
Mechanical	NRCV-MCH-27 Indoor Air Quality & Mechanical Ventilation
Mechanical	NRCV-MCH-32 Local Mechanical Exhaust
Plumbing	NRCV-PLB-22-H HERS verified single dwelling unit systems in high-rise residential, hotel/motel application

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 51 of 51)

Documentation Author's Declaration Statement

1. I certify that this Certificate of Compliance documentation is accurate and complete.	
Documentation Author Name:	Documentation Author Signature:
Company:	Signature Date:
Address:	CEA/HERS Certification Identification (if applicable):
City/State/Zip: ,	Phone:

Responsible Person's Declaration statement

I certify the following under penalty of perjury, under the laws of the State of California:		
1. The information provided on this Certificate of Compliance is true and correct. 2. I am eligible under Division 3 of the Business and Professions Code to accept responsibility for the building design or system design identified on this Certificate of Compliance (responsible designer) 3. The energy features and performance specifications, materials, components, and manufactured devices for the building design or system design identified on this Certificate of Compliance conform to the requirements of Title 24, Part 1 and Part 6 of the California Code of Regulations. 4. The building design features or system design features identified on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application. 5. I understand that a registered copy of this Certificate of Compliance shall be made available with the building permit(s) issued for the building, and made available to the enforcement agency for all applicable inspections, and I will take the necessary steps to accomplish this requirement. 6. I understand that a registered copy of this Certificate of Compliance is required to be included with the documentation the builder provides to the building owner at occupancy, and I will take the necessary steps to accomplish these requirements.		
Responsible Designer Name:	Responsible Designer Signature:	
Company:		
Address:	Date Signed:	
City/State/Zip: ,	License #:	
Phone:	Title:	Scope: