

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD		NRCC-PRF-E
Nonresidential Performance Compliance Method		(Page 1 of 25)
Project Name:	040012-OffLrg-CECStd22	Date Prepared: 2025-12-23

A. General Information				
1	Project Name	040012-OffLrg-CECStd22		
2	Run Title			
3	Project Location	- specify -		
4	City	- specify -	5	Standards Version
6	Zip code	95814	7	Compliance Software (version)
8	Climate Zone	12	9	Building Orientation (deg)
10	Building Type(s)	• Nonresidential	11	Weather File
12	Project Scope	• New complete scope	13	Number of Dwelling Units
14	Total Conditioned Floor Area in Scope (ft²)	498589	15	Total # of hotel/motel rooms
16	Total Unconditioned Floor Area (ft²)	0	17	Fuel Type
18	Nonresidential Conditioned Floor Area	498589	19	Total # of Stories (Habitable Above Grade)
20	Residential Conditioned Floor Area	0		

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 2 of 25)

B. PROJECT SUMMARY							
Table B shows which building components are included in the performance calculation. If indicated as not included, the project must show compliance prescriptively if within the permit application.							
Building Components Complying via Performance					Building Components Complying Prescriptively		
Envelope (See Table G)	Nonres	Performance	Solar Thermal Water Heating (See Table I3)	☐	Performance	The following building components are ONLY eligible for prescriptive compliance and should be documented on the NRCC form listed if within the scope of the permit application (i.e. compliance will not be shown on the NRCC-PRF-E).	
	MultiFam	Not Included		☒	Not Included		
Mechanical (See Table H)	Nonres	Performance	Covered Process: Commercial Kitchens (see Table J)	☐	Performance	Indoor Lighting (Unconditioned) 140.6 & 170.2(e)	NRCC-LTI-E is required
	MultiFam	Not Included		☒	Not Included	Outdoor Lighting 140.7 & 170.2(e)	NRCC-LTO-E is required
Domestic Hot Water (See Table I)	Nonres	Performance	Covered Process: Laboratory Exhaust (see Table J)	☐	Performance	Sign Lighting 140.8 & 170.2(e)	NRCC-LTS-E is required
	MultiFam	Not Included		☒	Not Included	Building Components Complying with Mandatory Measures	
Lighting (Indoor Conditioned, see Table K)	Nonres	Performance	Photovoltaics (see Table F)	☒	Performance	Electrical power systems, commissioning, solar ready, elevator and escalator requirements are mandatory and should be documented on the NRCC form listed if applicable (i.e. compliance will not be shown on the NRCC-PRF-E.)	
	MultiFam	Not Included		☐	Not Included	Electrical Power Distribution 110.11	NRCC-ELC-E is required
			Battery (see Table F)	☒	Performance	Commissioning 120.8	NRCC-CXR-E is required
				☐	Not Included	Solar and Battery 110.10	NRCC-SAB-E is required

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 3 of 25)

C1. COMPLIANCE SUMMARY			
COMPLIES ³			
	Time Dependent Valuaton (TDV)		Source Energy Use
	Efficiency ¹ (kBtu/ft ² - yr)	Total ² (kBtu/ft ² - yr)	Total ² (kBtu/ft ² - yr)
Standard Design	92.41	57.77	8.2
Proposed Design	92.41	57.77	8.2
Compliance Margins	0	0	0
	Pass	Pass	Pass
¹ Efficiency measures include improvements like a better building envelope and more efficient equipment ² Compliance Totals include efficiency, photovoltaics and batteries ³ New Construction, Complete Addition Scope: Building complies when all efficiency and total compliance margins are greater than or equal to zero and unmet load hour limits are not exceeded Existing, Addition and Alteration Scope: Building complies when efficiency compliance margin is greater than or equal to zero and unmet load hour limits are not exceeded			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 4 of 25)

C2. TDV ENERGY COMPLIANCE RESULTS FOR PERFORMANCE COMPONENTS (Annual TDV Energy Use, kBtu/ft² - yr)			
COMPLIES²			
Energy Component	Standard Design (TDV)	Proposed Design (TDV)	Compliance Margin (TDV)¹
Space Heating	13.28	13.28	0
Space Cooling	20.81	20.81	0
Indoor Fans	14.11	14.11	0
Heat Rejection	2.79	2.79	0
Pumps & Misc.	5.77	5.77	0
Domestic Hot Water	6.53	6.53	0
Indoor Lighting	29.12	29.12	0
Flexibility	---	---	---
EFFICIENCY COMPLIANCE TOTAL	92.41	92.41	0 (0%)
Photovoltaics	-32.87	-32.87	---
Batteries	-1.77	-1.77	---
TOTAL COMPLIANCE	57.77	57.77	0 (0%)
¹ Notes: This number in parenthesis following the Compliance Margin in column 4, represents the Percent Better than Standard.			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 5 of 25)

C3. TDV ENERGY RESULTS FOR NON-REGULATED COMPONENTS¹			
Non-Regulated Energy Component	Standard Design (TDV)	Proposed Design (TDV)	Compliance Margin (TDV)¹
Receptacle	102.01	102.01	---
Process	---	---	---
Other Ltg	---	---	---
Process Motors	---	---	---
TOTAL (TOTAL COMPLIANCE + NON-REGULATED COMPONENTS)	159.78	159.78	0 (0%)
¹ Notes: This table is not used for Energy Code Compliance.			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 6 of 25)

C4. SOURCE ENERGY COMPLIANCE RESULTS FOR PERFORMANCE COMPONENTS (Annual SOURCE Energy Use, kBtu/ft² /yr)			
COMPLIES²			
Energy Component	Standard Design (SOURCE)	Proposed Design (SOURCE)	Compliance Margin (SOURCE)¹
Space Heating	4.49	4.49	0
Space Cooling	0.83	0.83	0
Indoor Fans	1.02	1.02	0
Heat Rejection	0.12	0.12	0
Pumps & Misc.	0.33	0.33	0
Domestic Hot Water	0.53	0.53	0
Indoor Lighting	2.41	2.41	0
Flexibility	---	---	---
EFFICIENCY COMPLIANCE TOTAL	9.73	9.73	0 (0%)
Photovoltaics	-1.17	-1.17	---
Batteries	-0.36	-0.36	---
TOTAL COMPLIANCE	8.2	8.2	0 (0%)
¹ Notes: This number in parenthesis following the Compliance Margin in column 4, represents the Percent Better than Standard.			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 7 of 25)

C5. SOURCE ENERGY RESULTS FOR NON-REGULATED COMPONENTS¹			
Non-Regulated Energy Component	Standard Design (SOURCE)	Proposed Design (SOURCE)	Compliance Margin (SOURCE)¹
Receptacle	7.55	7.55	---
Process	---	---	---
Other Ltg	---	---	---
Process Motors	---	---	---
TOTAL (TOTAL COMPLIANCE + NON-REGULATED COMPONENTS)	15.75	15.75	0 (0%)
¹ Notes: This table is not used for Energy Code Compliance.			

C6. 'ABOVE CODE' QUALIFICATIONS	
☐ This project is pursuing CalGreen Tier 1	☐ This project is pursuing CalGreen Tier 2

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 8 of 25)

C7. ENERGY USE SUMMARY						
Energy Component	Standard Design Site (MWh)	Proposed Design Site (MWh)	Margin (MWh)	Standard Design Site (MBtu)	Proposed Design Site (MBtu)	Margin (MBtu)
Space Heating	0.2	0.2	0	2401.4	2401.9	-0.5
Space Cooling	287.8	287.8	0	---	---	---
Indoor Fans	274.9	274.9	0	---	---	---
Heat Rejection	35.4	35.3	0.1	---	---	---
Pumps & Misc.	90.6	90.6	0	---	---	---
Domestic Hot Water	131.9	131.9	0	---	---	---
Indoor Lighting	578.1	578.1	0	---	---	---
Flexibility	---	---	---	---	---	---
EFFICIENCY TOTAL	1398.9	1398.8	0.1	2401.4	2401.9	-0.5
Photovoltaics	-839.7	-839.7	0	---	---	---
Batteries	5.2	5.2	0	---	---	---
ENERGY USE SUBTOTAL	564.4	564.3	0.1	2401.4	2401.9	-0.5
Receptacle	2135.6	2135.6	0	---	---	---
Process	---	---	---	---	---	---
Other Ltg	---	---	---	---	---	---
Process Motors	---	---	---	---	---	---
ENERGY USE TOTAL	2700	2699.9	0.1	2401.4	2401.9	-0.5

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 9 of 25)

C8. ENERGY USE INTENSITY (EUI)				
	Standard Design (kBtu/ft² / yr)	Proposed Design (kBtu/ft² / yr)	Margin (kBtu/ft² / yr)	Margin Percentage
GROSS EUI ¹	29.04	29.04	0	0
NET EUI ¹	23.29	23.29	0	0
¹ Notes: Gross EUI is Energy Use Total (not including PV)/Total Building Area. Net EUI is Energy Use Total (including PV)/Total Building Area.				

D1. EXCEPTIONAL CONDITIONS
- The aged solar reflectance and aged thermal emittance must be listed in the Cool Roof Rating Council database of certified products. For projects where initial reflectance is used, the initial reflectance must be listed, and the aged reflectance is calculated by the software program and used in the compliance model. - Required minimum PV capacity limited by SARA.

F1. REQUIRED PV SYSTEMS											
01	02	03	04	05	06	07	08	09	10	11	12
DC System Size (kWdc)	Exception¹	Module Type	Array Type	Power Electronics	CFI	Azimuth (deg)	Tilt Input	Array Angle (deg)	Tilt: (x in 12)	Inverter Eff. (%)	Annual Solar Access (%)
536.94		Standard (14-17%)	Fixed	none	true	150-270	n/a	n/a	<=7:12	96	98
¹ See Table D1 for any PV exceptions used.											

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 10 of 25)

F1B. PV BATTERY BUILDING TYPE(S)		
01	02	03
Building Occupancy Type* (From Table 140.10-A/B and 170.2-U/V)	Conditioned Floor Area (ft²)	Unconditioned Floor Area (ft²)
Grocery	0	0
High-Rise Multifamily	0	0
Office, Financial Institutions, Unleased Tenant Space	498589	0
Retail	0	0
School	0	0
Warehouse	0	0
Auditorium, Convention Center, Hotel/Motel, Library, Medical Office Building/Clinic, Restaurant, Theater	0	0
None	0	0
<i>*Building Occupancy Types are defined in Section 100.1 of the Energy Code</i>		

F2. BATTERY SYSTEMS¹						
01	02	03	04	05	06	07
Control	Capacity (kWh)	Charging Efficiency	Charging Rate (kW)	Discharging Efficiency	Discharging Rate (kW)	Round Trip Efficiency
TOU	949.54	N/A	225.51	N/A	225.51	0.9
¹ See Table D1 for any Battery exceptions used.						

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 11 of 25)

G1. ENVELOPE GENERAL INFORMATION (conditioned spaces only)			
01	02	03	04
Opaque Surfaces & Orientation	Total Gross Surface Area (ft ²)	Total Fenestration Area (ft ²)	Window to Wall Ratio (%)
North-Facing ¹	37417.7	14439.4	38.59
East-Facing ²	24945.1	9625.13	38.59
South-Facing ³	37417.7	14439.4	38.59
West-Facing ⁴	24945.1	9625.13	38.59
Total	124726	48129.1	38.59
Roof	0	0	0
Notes ¹ North-Facing is oriented to within 45 degrees of true north, including 4500'00" east of north (NE), but excluding 4500'00" west of north (NW), ² East-Facing is oriented to within 45 degrees of true east, including 4500'00" south of east (SE), but excluding 4500'00" north of east (NE), ³ South-Facing is oriented to within 45 degrees of true south, including 4500'00" west of south (SW), but excluding 4500'00" east of south (SE), ⁴ West-Facing is oriented to within 45 degrees of true west, including 4500'00" north of west (NW), but excluding 4500'00" south of west (SW),			

G2A. ROOFING PRODUCT SUMMARY (NONRESIDENTIAL)					
01	02	03	04	05	06
Assembly Name	Roof Pitch	Roof Rise (x in 12)	Aged Solar Reflectance	Thermal Emittance	SRI
Base_CZ12-FlatNonresWoodFramingAndOtherRoofU034	LowSlope	N/A	0.63	0.75	N/A

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 12 of 25)

G4. NONRESIDENTIAL AIR BARRIER	
01	02
Building Story Name	Air Barrier
Basement	Air barrier - not verified
GroundFloor	Air barrier - not verified
MidFloor	Air barrier - not verified
HiFloor	Air barrier - not verified
TopFloor	Air barrier - not verified

Not useable for compliance

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 13 of 25)

G5. OPAQUE SURFACE ASSEMBLY SUMMARY										
01	02	03	04	05	06		07	08	09	10
Surface Name	Construction Type	Area (ft²)	Framing Type	Cavity R-Value	Continuous R-Value		Units	Value	Description of Assembly Layers	Status ¹
					Interior	Exterior				
Base_CZ12-SlabOnOrBelow GradeF073	Underground Floor	38,353	N/A	0	N/A	N/A	F-factor	0.73	Slab Type =Unheated slab on grade Insulation Orientation =None Insulation R-Value =none	N
Base_CZ12-BelowGradeWa IIC114	Underground Wall	6,397.66	N/A	0	N/A	N/A	C-factor	1.14	Concrete - Solid Grout - 115 lb/ft3 - 8 in.	N
Base_CZ12-NonresMetalFr ameWallU055	Exterior Wall	124,726	Metal	0	N/A	16.05	U-factor	0.055	Stucco - 7/8 in. Compliance Insulation R14.60 Compliance Insulation R1.41 Compliance Insulation R0.02 Compliance Insulation R0.02 Air - Metal Wall Framing - 16 or 24 in. OC Gypsum Board - 1/2 in.	N
NACM_Interior Wall	Interior Wall	82,552.2	Metal	0	N/A	N/A	U-factor	0.3195	Gypsum Board - 5/8 in. Air - Metal Wall Framing - 16 or 24 in. OC Gypsum Board - 5/8 in.	N
Base_CZ12-FlatNonresWoo dFramingAndOt herRoofU034	Roof	38,353	N/A	0	N/A	28.63	U-factor	0.034	Metal Standing Seam - 1/16 in. Compliance Insulation R28.63	N
NACM_Interior Floor	Interior Floor	460,236	N/A	0	N/A	N/A	U-factor	0.2375	Metal Deck - 1/16 in. Concrete - 140 lb/ft3 - 4 in. Carpet - 3/4 in.	N
NACM_Drop Ceiling	Interior Floor	460,236	N/A	0	N/A	N/A	U-factor	0.2924	Acoustic Tile - 3/4 in.	N
¹ Status: N - New, A - Altered, E - Existing										

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 14 of 25)

G7A. FENESTRATION ASSEMBLY SUMMARY (NONRESIDENTIAL)								
01	02	03	04	05	06	07	08	09
Fenestration Assembly Name	Fenestration Type/ Product Type / Frame Type	Certification Method ¹	Assembly Method	Area (ft ²)	Overall U-factor	Overall SHGC	Overall VT	Status ²
Base_AllCZ_FixedWindowU34	Vertical fenestration Fixed window N/A	NFRC	Manufactured	48,129.1	0.34	0.22	0.42	N
¹ Notes: Newly installed fenestration shall have a certified NFRC Label Certificate or use the CEC default tables found in Table 110.6-A and Table 110.6-B. Center of Glass (COG) values are for the glass-only, determined by the manufacturer, and are shown for ease of verification. Site-built fenestration values are calculated per Nonresidential Appendix NA6 and are used in the analysis. ² Status: N - New, A - Altered, E - Existing								

H1. DRY SYSTEM EQUIPMENT (FURNACES, AIR HANDLING UNITS, HEAT PUMPS, VRF, ECONOMIZERS ETC.)											
01	02	03	04	05	06	07	08	09	10	11	12
Equipment Name	Equipment Type	Qty	Heating				Cooling			Economizer Type (if present)	Status ¹
			Total Heating Output (kBtu/h)	Supp Heat Output (kBtu/h)	Efficiency Unit	Efficiency	Total Cooling Output (kBtu/h)	Efficiency Unit	Efficiency		
BaseAirSys6-Basement	Variable Air Volume Air System	1	362.82	0	N/A	NA - See Boiler	854.85	N/A	NA - See Chiller	Fixed DB	N
BaseAirSys6-Bot	Variable Air Volume Air System	1	537.06	0	N/A	NA - See Boiler	1089.42	N/A	NA - See Chiller	Fixed DB	N
BaseAirSys6-Mid	Variable Air Volume Air System	5	595.67	0	N/A	NA - See Boiler	1183.47	N/A	NA - See Chiller	Fixed DB	N
¹ Status: N - New, A - Altered, E - Existing											

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD											NRCC-PRF-E
Nonresidential Performance Compliance Method											(Page 15 of 25)

H1. DRY SYSTEM EQUIPMENT (FURNACES, AIR HANDLING UNITS, HEAT PUMPS, VRF, ECONOMIZERS ETC.)											
01	02	03	04	05	06	07	08	09	10	11	12
Equipment Name	Equipment Type	Qty	Heating				Cooling			Economizer Type (if present)	Status ¹
			Total Heating Output (kBtu/h)	Supp Heat Output (kBtu/h)	Efficiency Unit	Efficiency	Total Cooling Output (kBtu/h)	Efficiency Unit	Efficiency		
BaseAirSys6-Hi	Variable Air Volume Air System	5	621.08	0	N/A	NA - See Boiler	1243.86	N/A	NA - See Chiller	Fixed DB	N
BaseAirSys6-Top	Variable Air Volume Air System	1	893.18	0	N/A	NA - See Boiler	1113.01	N/A	NA - See Chiller	Fixed DB	N
¹ Status: N - New, A - Altered, E - Existing											

H3. NONRESIDENTIAL / COMMON USE AREA FAN SYSTEMS SUMMARY												
01	02	03	04	05	06	07	08	09	10	11	12	13
Name or Item Tag	Qty	Design OA CFM	Supply Fan				Return / Relief Fan					Status ¹
			CFM	Power	Power Units	Control	Fan Type	CFM	Power	Power Units	Control	
BaseAirSys6-Basement	1	5752.95	25,314	0.54	W/cfm	VSD	N/A	22,782.6	0.54	W/cfm	VSD	N
BaseAirSys6-Bot	1	5752.95	28,254.4	0.54	W/cfm	VSD	N/A	25,429	0.54	W/cfm	VSD	N
BaseAirSys6-Mid	5	5752.95	32,447.7	0.95	W/cfm	VSD	N/A	N/A	N/A	N/A	N/A	N
BaseAirSys6-Hi	5	5752.95	30,936.1	0.95	W/cfm	VSD	N/A	N/A	N/A	N/A	N/A	N
BaseAirSys6-Top	1	5752.95	29,260.4	0.5	W/cfm	VSD	N/A	26,334.4	0.5	W/cfm	VSD	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 16 of 25)

H6. WET SYSTEM EQUIPMENT (boilers, chillers, cooling towers, etc.)									
01	02	03	04	05	06	07	08	09	10
Name or Item Tag	Equipment Type	Parent Fluid System Name	Qty	Vol (gal)	Rated Capacity	Capacity Unit	Rating	Rating Unit	Status¹
Base Blr	Hot Water	BaseHWSys	1	N/A	3,352.5	kBtu/Hr	0.92	Combustion Efficiency	N
Base Blr-2	Hot Water	BaseHWSys	1	N/A	3,352.5	kBtu/Hr	0.92	Combustion Efficiency	N
Base Chlr	Centrifugal	BaseChWSys	1	N/A	5,110.19	kBtu/Hr	0.58	kWperTon	N
Base Chlr-2	Centrifugal	BaseChWSys	1	N/A	5,110.19	kBtu/Hr	0.58	kWperTon	N
Base Tower	Open Tower	BaseCWSys	1	N/A	5,960.26	kBtu/Hr	19.95	HP	N
Base Tower-2	Open Tower	BaseCWSys	1	N/A	5,960.26	kBtu/Hr	19.95	HP	N
¹ Status: N - New, A - Altered, E - Existing									

H7. PUMPS							
01	02	03	04	05	06	07	08
Name or Item Tag	Parent Equipment	Qty	Power	Power Units	GPM	VSD	Status¹
Base HW Pump	Base Blr	1	5	BHP	167.56	☒	N
Base HW Pump-2	Base Blr-2	1	5	BHP	167.56	☒	N
Base CW Pump	Base Tower	1	20	BHP	1196.84	☐	N
Base CW Pump-2	Base Tower-2	1	20	BHP	1196.84	☐	N
Base ChW Pump	Base Chlr	1	15	BHP	510.82	☒	N
Base ChW Pump-2	Base Chlr-2	1	15	BHP	510.82	☒	N
¹ Status: N - New, A - Altered, E - Existing							

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 17 of 25)

H8. SYSTEM SPECIAL FEATURES			
01	02	03	04
System Name	Equipment Type	Interlocks per 140.4(n)¹	Other Special Features and Controls
BaseAirSys6-Basement	Variable Air Volume Air System	N/A	DDC Controls Dual Maximum Reheat Controls Warmest Zone Supply Air Temp. Reset Heat Recovery Optimum Start Fixed DB
BaseAirSys6-Bot	Variable Air Volume Air System	N/A	DDC Controls Dual Maximum Reheat Controls Warmest Zone Supply Air Temp. Reset Heat Recovery Optimum Start Fixed DB
BaseAirSys6-Mid	Variable Air Volume Air System	N/A	DDC Controls Dual Maximum Reheat Controls Warmest Zone Supply Air Temp. Reset Optimum Start Fixed DB
BaseAirSys6-Hi	Variable Air Volume Air System	N/A	DDC Controls Dual Maximum Reheat Controls Warmest Zone Supply Air Temp. Reset Optimum Start Fixed DB
BaseAirSys6-Top	Variable Air Volume Air System	N/A	DDC Controls Dual Maximum Reheat Controls Warmest Zone Supply Air Temp. Reset Optimum Start Fixed DB
<i>Notes: This table includes controls related to the performance path only. For projects using the prescriptive path, mandatory and prescriptive controls requirements are documented on the NRCC-MCH-E.</i>			
¹ Yes = interlocks are provided, No = interlocks are not provided, NA means no operable openings.			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 18 of 25)

H8. SYSTEM SPECIAL FEATURES			
01	02	03	04
System Name	Equipment Type	Interlocks per 140.4(n)¹	Other Special Features and Controls
SHWFluidSysElec	Service Hot Water	N/A	Fixed Temperature Control
BaseHWSys	Hot Water System	N/A	DDC Controls Fixed Temperature Control
BaseCWSys	Condenser Water	N/A	DDC Controls Fixed Temperature Control
BaseChWSys	Chilled Water System	N/A	DDC Controls Outside Air Reset Temperature Control
Notes: This table includes controls related to the performance path only. For projects using the prescriptive path, mandatory and prescriptive controls requirements are documented on the NRCC-MCH-E.			
¹ Yes = interlocks are provided, No = interlocks are not provided, NA means no operable openings.			

H9. NONRESIDENTIAL / COMMON USE AREA & HOTEL/MOTEL VENTILATION						
01	02	03	04	05	06	07
Zone Name	Mechanical Ventilation				Conditioned Area (sf)	DCV or Occupant Sensor Controls, or Both
	Ventilation Function	# of People	Supply OA CFM	Exhaust CFM		
Basement Thermal Zone	Office - Office space	191.76	5752.95	0	38353	N/A
Core_bottom Thermal Zone	Office - Office space	136.29	4088.65	0	27257.6	N/A
Perimeter_bot_ZN_1 Thermal Zone	Office - Office space	16.87	506.04	0	3373.61	N/A
Perimeter_bot_ZN_2 Thermal Zone	Office - Office space	10.87	326.11	0	2174.05	N/A
Perimeter_bot_ZN_3 Thermal Zone	Office - Office space	16.87	506.05	0	3373.64	N/A
Perimeter_bot_ZN_4 Thermal Zone	Office - Office space	10.87	326.11	0	2174.04	N/A
Core_mid Thermal Zone	Office - Office space	136.29	4088.65	0	27257.6	N/A

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 19 of 25)

H9. NONRESIDENTIAL / COMMON USE AREA & HOTEL/MOTEL VENTILATION						
01	02	03	04	05	06	07
Zone Name	Mechanical Ventilation				Conditioned Area (sf)	DCV or Occupant Sensor Controls, or Both
	Ventilation Function	# of People	Supply OA CFM	Exhaust CFM		
Perimeter_mid_ZN_1 Thermal Zone	Office - Office space	16.87	506.04	0	3373.61	N/A
Perimeter_mid_ZN_2 Thermal Zone	Office - Office space	10.87	326.11	0	2174.05	N/A
Perimeter_mid_ZN_3 Thermal Zone	Office - Office space	16.87	506.05	0	3373.64	N/A
Perimeter_mid_ZN_4 Thermal Zone	Office - Office space	10.87	326.11	0	2174.04	N/A
Core_hi Thermal Zone	Office - Office space	136.29	4088.65	0	27257.6	N/A
Perimeter_hi_ZN_1 Thermal Zone	Office - Office space	16.87	506.04	0	3373.61	N/A
Perimeter_hi_ZN_2 Thermal Zone	Office - Office space	10.87	326.11	0	2174.05	N/A
Perimeter_hi_ZN_3 Thermal Zone	Office - Office space	16.87	506.05	0	3373.64	N/A
Perimeter_hi_ZN_4 Thermal Zone	Office - Office space	10.87	326.11	0	2174.04	N/A
Core_top Thermal Zone	Office - Office space	136.29	4088.65	0	27257.6	N/A
Perimeter_top_ZN_1 Thermal Zone	Office - Office space	16.87	506.04	0	3373.61	N/A
Perimeter_top_ZN_2 Thermal Zone	Office - Office space	10.87	326.11	0	2174.05	N/A
Perimeter_top_ZN_3 Thermal Zone	Office - Office space	16.87	506.05	0	3373.64	N/A
Perimeter_top_ZN_4 Thermal Zone	Office - Office space	10.87	326.11	0	2174.04	N/A

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 20 of 25)

H11. ZONAL SYSTEM AND TERMINAL UNIT SUMMARY											
01	02	03	04	05	06	07	08	09	10	11	12
System ID	System Type	Qty	Rated Capacity (kBtuh)		Airflow (cfm)			Fan			VSD
			Heating	Cooling	Design	MIn.	Min. Ratio	Power	Power Units	Cycles	
BaseVAVTrmlUnit	Variable Air Volume Reheat Box	1	126.54	N/A	25,684.1	5,752.95	0.22	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-2	Variable Air Volume Reheat Box	1	175.76	N/A	21,428.8	4,088.65	0.19	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-3	Variable Air Volume Reheat Box	1	72.04	N/A	3,838.17	506.04	0.13	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-4	Variable Air Volume Reheat Box	1	47.62	N/A	2,442.22	326.11	0.13	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-5	Variable Air Volume Reheat Box	1	72.01	N/A	2,566.39	506.05	0.2	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-6	Variable Air Volume Reheat Box	1	47.6	N/A	2,675.58	326.11	0.12	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-7	Variable Air Volume Reheat Box	5	223.48	N/A	23,626.5	4,088.65	0.17	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-8	Variable Air Volume Reheat Box	5	84.14	N/A	3,923.72	506.04	0.13	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-9	Variable Air Volume Reheat Box	5	55.9	N/A	2,496.87	326.11	0.13	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-10	Variable Air Volume Reheat Box	5	84.22	N/A	2,715.78	506.05	0.19	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-11	Variable Air Volume Reheat Box	5	55.95	N/A	2,720.46	326.11	0.12	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-12	Variable Air Volume Reheat Box	5	230.37	N/A	23,591	4,088.65	0.17	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-13	Variable Air Volume Reheat Box	5	86.42	N/A	3,910.52	506.04	0.13	N/A	N/A	N/A	☐

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 21 of 25)

H11. ZONAL SYSTEM AND TERMINAL UNIT SUMMARY											
01	02	03	04	05	06	07	08	09	10	11	12
System ID	System Type	Qty	Rated Capacity (kBtuh)		Airflow (cfm)			Fan			VSD
			Heating	Cooling	Design	MIn.	Min. Ratio	Power	Power Units	Cycles	
BaseVAVTrmlUnit-14	Variable Air Volume Reheat Box	5	57.34	N/A	2,489.29	326.11	0.13	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-15	Variable Air Volume Reheat Box	5	86.54	N/A	2,705.79	506.05	0.19	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-16	Variable Air Volume Reheat Box	5	57.41	N/A	2,718.61	326.11	0.12	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-17	Variable Air Volume Reheat Box	1	426.2	N/A	22,425.8	4,088.65	0.18	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-18	Variable Air Volume Reheat Box	1	106.01	N/A	3,991.13	506.04	0.13	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-19	Variable Air Volume Reheat Box	1	69.9	N/A	2,475.28	326.11	0.13	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-20	Variable Air Volume Reheat Box	1	106.12	N/A	2,571.36	506.05	0.2	N/A	N/A	N/A	☐
BaseVAVTrmlUnit-21	Variable Air Volume Reheat Box	1	69.97	N/A	2,844.8	326.11	0.11	N/A	N/A	N/A	☐

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 22 of 25)

H13. ENERGY RECOVERY SUMMARY									
01	02	03	04	05	06	07	08	09	10
Equipment Name	Equipment Type	Equipment Type	Heating			Cooling			Status ¹
			Sensible	Latent	Total	Sensible	Latent	Total	
BaseAirSys6-Basement	Variable Air Volume Air System	AHRI	0.6	0	0	0.6	0	0	N
BaseAirSys6-Bot	Variable Air Volume Air System	AHRI	0.6	0	0	0.6	0	0	N

¹ Status: N - New, A - Altered, E - Existing

I1. WATER HEATER EQUIPMENT SUMMARY													
01	02	03	04	05	06	07	08	09	10	11	12	13	14
Name	Heater Element Type	Tank Type	Qty	Tank Vol (gal)	Rated Input	Rated Input Unit	Efficiency	Efficiency Unit	Tank Insulation R-value Int/Ext	Standby Loss Fraction	1st Hr. Rating or Flow Rate (gal)	Heat Pump Type	Tank Location or Ambient Condition
WaterHeaterElec	Electricity	Storage	1	179.49	52.32	kW	1	TE	N/A	0	N/A	N/A	N/A

K1. INDOOR CONDITIONED LIGHTING GENERAL INFO					
01	02	03	04	05	06
Occupancy Type ¹	Conditioned Floor Area ² (ft ²)	Installed Lighting Power (Watts)	Lighting Control Credits (Watts)	Additional (Custom) Allowance	
				Area Category Footnotes (Watts)	Area Category Footnotes (Watts)
Office (250 square feet)	498589	299153	0	0	0
Building Totals:	498589	299153	0	0	0

¹ See Table 140.6-C
² See NRCC-LTI--E for unconditioned spaces
³ Lighting information for existing spaces modeled is not included in this table

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 23 of 25)

K4. INDOOR CONDITIONED LIGHTING MANDATORY LIGHTING CONTROL
See NRCC-LTI-E for mandatory controls

L. DECLARATION OF REQUIRED CERTIFICATES OF INSTALLATION	
Selections made by Documentation Author indicate which Certificates of Installation must be submitted for the features to be recognized for compliance. These documents must be retained and provided to the building inspector during construction and can be found online	
Building Component	Form/Title
Envelope	NRCI-ENV-E - Envelope (for all buildings)
Mechanical	NRCI-MCH-E - For all buildings with Mechanical Systems
Plumbing	NRCI-PLB-E - For all buildings with Plumbing Systems
	NRCI-SAB-E - Solar Water Heating, PV and Battery Storage Systems
Indoor Lighting	NRCI-LTI-E - Indoor Lighting (for all buildings)

M. DECLARATION OF REQUIRED CERTIFICATES OF ACCEPTANCE	
Selections made by Documentation Author indicate which Certificates of Acceptance must be submitted for the features to be recognized for compliance. These documents must be provided to the building inspector during construction and must be completed through an Acceptance Test Technician Certification Provider (ATTCP).	
Building Component	Form/Title & System Name(s)
Envelope	NRCA-ENV-02-F - NRFC label verification for fenestration
Indoor Lighting	NRCA-LTI-02-A - Occupancy Sensors and Automatic Time Switch Controls.
Indoor Lighting	NRCA-LTI-03-A - Automatic Daylight Controls.
Indoor Lighting	NRCA-LTI-04-A - Demand Responsive Lighting Controls.
Mechanical	NRCA-MCH-02-A - Outdoor Air must be submitted for all newly installed HVAC units. Note: MCH-02-A can be performed in conjunction with MCH-07-A Supply Fan VFD Acceptance (if applicable) since testing activities overlap
	BaseAirSys6-Basement, BaseAirSys6-Bot, BaseAirSys6-Mid, BaseAirSys6-Hi and BaseAirSys6-Top.
Mechanical	NRCA-MCH-05-A - Air Economizer Controls
	BaseAirSys6-Basement, BaseAirSys6-Bot, BaseAirSys6-Mid, BaseAirSys6-Hi and BaseAirSys6-Top.
Mechanical	NRCA-MCH-07-A Supply Fan Variable Flow Controls
	BaseAirSys6-Basement, BaseAirSys6-Bot, BaseAirSys6-Mid, BaseAirSys6-Hi and BaseAirSys6-Top.

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 24 of 25)

M. DECLARATION OF REQUIRED CERTIFICATES OF ACCEPTANCE	
Selections made by Documentation Author indicate which Certificates of Acceptance must be submitted for the features to be recognized for compliance. These documents must be provided to the building inspector during construction and must be completed through an Acceptance Test Technician Certification Provider (ATTCP).	
Building Component	Form/Title & System Name(s)
Mechanical	NRCA-MCH-08-A Valve Leakage Test
	BaseHWSysSystem and BaseChWSysSystem.
Mechanical	NRCA-MCH-09-A Supply Water Temperature Reset Controls
	BaseChWSysSystem
Mechanical	NRCA-MCH-10-A Hydronic System Variable Flow Controls
	BaseHWSysSystem and BaseChWSysSystem.
Mechanical	NRCA-MCH-11-A Automatic Demand Shed Controls
	BaseAirSys6-Basement, BaseAirSys6-Bot, BaseAirSys6-Mid, BaseAirSys6-Hi and BaseAirSys6-Top., BaseHWSysSystem, BaseCWSysSystem and BaseChWSysSystem.
Mechanical	NRCA-MCH-12-A FDD for Packaged Direct Expansion Units
	BaseAirSys6-Basement, BaseAirSys6-Bot, BaseAirSys6-Mid, BaseAirSys6-Hi and BaseAirSys6-Top.
Mechanical	NRCA-MCH-16-A Supply Air Temperature Reset Controls
	BaseAirSys6-Basement, BaseAirSys6-Bot, BaseAirSys6-Mid, BaseAirSys6-Hi and BaseAirSys6-Top.

N. DECLARATION OF REQUIRED CERTIFICATES OF VERIFICATION	
Selections made by Documentation Author indicate which Certificates of Verification must be submitted for the features to be recognized for compliance. These documents must be retained and provided to the building inspector during construction and can be found online	
Building Component	Form/Title
Mechanical	NRCV-MCH-27 Indoor Air Quality & Mechanical Ventilation

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 25 of 25)

Documentation Author's Declaration Statement

1. I certify that this Certificate of Compliance documentation is accurate and complete.	
Documentation Author Name:	Documentation Author Signature:
Company:	Signature Date:
Address:	CEA/HERS Certification Identification (if applicable):
City/State/Zip: ,	Phone:

Responsible Person's Declaration statement

I certify the following under penalty of perjury, under the laws of the State of California:		
1. The information provided on this Certificate of Compliance is true and correct. 2. I am eligible under Division 3 of the Business and Professions Code to accept responsibility for the building design or system design identified on this Certificate of Compliance (responsible designer) 3. The energy features and performance specifications, materials, components, and manufactured devices for the building design or system design identified on this Certificate of Compliance conform to the requirements of Title 24, Part 1 and Part 6 of the California Code of Regulations. 4. The building design features or system design features identified on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application. 5. I understand that a registered copy of this Certificate of Compliance shall be made available with the building permit(s) issued for the building, and made available to the enforcement agency for all applicable inspections, and I will take the necessary steps to accomplish this requirement. 6. I understand that a registered copy of this Certificate of Compliance is required to be included with the documentation the builder provides to the building owner at occupancy, and I will take the necessary steps to accomplish these requirements.		
Responsible Designer Name:	Responsible Designer Signature:	
Company:		
Address:	Date Signed:	
City/State/Zip: ,	License #:	
Phone:	Title:	Scope: