

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD		NRCC-PRF-E
Nonresidential Performance Compliance Method		(Page 1 of 43)
Project Name:	Jefferson Murreita Bld A	Date Prepared: 2025-12-17

A. General Information					
1	Project Name	Jefferson Murreita Bld A			
2	Run Title	Title 24 Multi Family Compliance			
3	Project Location	Corner of Murrieta Hot Spring Road & Jefferson Road			
4	City	Murrieta	5	Standards Version	Compliance 2022
6	Zip code	92562	7	Compliance Software (version)	CBECC 2022.3.2 (1369)
8	Climate Zone	10	9	Building Orientation (deg)	90
10	Building Type(s)	• High-Rise Residential	11	Weather File	RIVERSIDE_STYP20.epw
12	Project Scope	• New complete scope	13	Number of Dwelling Units	40
14	Total Conditioned Floor Area in Scope (ft²)	35151.9	15	Total # of hotel/motel rooms	0
16	Total Unconditioned Floor Area (ft²)	10665.6	17	Fuel Type	Natural gas
18	Nonresidential Conditioned Floor Area	0	19	Total # of Stories (Habitable Above Grade)	4
20	Residential Conditioned Floor Area	35151.9			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 2 of 43)

B. PROJECT SUMMARY							
Table B shows which building components are included in the performance calculation. If indicated as not included, the project must show compliance prescriptively if within the permit application.							
Building Components Complying via Performance					Building Components Complying Prescriptively		
Envelope (See Table G)	Nonres	Not Included	Solar Thermal Water Heating (See Table I3)	☐	Performance	The following building components are ONLY eligible for prescriptive compliance and should be documented on the NRCC form listed if within the scope of the permit application (i.e. compliance will not be shown on the NRCC-PRF-E).	
	MultiFam	Performance		☒	Not Included		
Mechanical (See Table H)	Nonres	Not Included	Covered Process: Commercial Kitchens (see Table J)	☐	Performance	Indoor Lighting (Unconditioned) 140.6 & 170.2(e)	NRCC-LTI-E is required
	MultiFam	Performance		☒	Not Included	Outdoor Lighting 140.7 & 170.2(e)	NRCC-LTO-E is required
Domestic Hot Water (See Table I)	Nonres	Not Included	Covered Process: Laboratory Exhaust (see Table J)	☐	Performance	Sign Lighting 140.8 & 170.2(e)	NRCC-LTS-E is required
	MultiFam	Performance		☒	Not Included	Building Components Complying with Mandatory Measures	
Lighting (Indoor Conditioned, see Table K)	Nonres	Not Included	Photovoltaics (see Table F)	☒	Performance	Electrical power systems, commissioning, solar ready, elevator and escalator requirements are mandatory and should be documented on the NRCC form listed if applicable (i.e. compliance will not be shown on the NRCC-PRF-E.)	
	MultiFam	Performance		☐	Not Included	Electrical Power Distribution 110.11	NRCC-ELC-E is required
			Battery (see Table F)	☐	Performance	Commissioning 120.8	NRCC-CXR-E is required
				☒	Not Included	Solar and Battery 110.10	NRCC-SAB-E is required

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 3 of 43)

C1. COMPLIANCE SUMMARY			
COMPLIES³			
	Time Dependent Valuaton (TDV)		Source Energy Use
	Efficiency¹ (kBtu/ft² - yr)	Total² (kBtu/ft² - yr)	Total² (kBtu/ft² - yr)
Standard Design	84.42	0.23	2.35
Proposed Design	69.95	-49.45	1.56
Compliance Margins	14.47	49.68	0.79
	Pass	Pass	Pass
¹ Efficiency measures include improvements like a better building envelope and more efficient equipment ² Compliance Totals include efficiency, photovoltaics and batteries ³ New Construction, Complete Addition Scope: Building complies when all efficiency and total compliance margins are greater than or equal to zero and unmet load hour limits are not exceeded Existing, Addition and Alteration Scope: Building complies when efficiency compliance margin is greater than or equal to zero and unmet load hour limits are not exceeded			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 4 of 43)

C2. TDV ENERGY COMPLIANCE RESULTS FOR PERFORMANCE COMPONENTS (Annual TDV Energy Use, kBtu/ft² - yr)			
COMPLIES²			
Energy Component	Standard Design (TDV)	Proposed Design (TDV)	Compliance Margin (TDV)¹
Space Heating	0.61	0.72	-0.11
Space Cooling	25.43	21.52	3.91
Indoor Fans	12.56	5.53	7.03
Heat Rejection	0	0	0
Pumps & Misc.	0.42	0.38	0.04
Domestic Hot Water	23.79	20.19	3.6
Indoor Lighting	21.61	21.61	0
Flexibility	---	---	---
EFFICIENCY COMPLIANCE TOTAL	84.42	69.95	14.47 (17.1%)
Photovoltaics	-76.07	-119.4	43.33
Batteries	-8.12	---	-8.12
TOTAL COMPLIANCE	0.23	-49.45	49.68 (21600%)
¹ Notes: This number in parenthesis following the Compliance Margin in column 4, represents the Percent Better than Standard.			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 5 of 43)

C3. TDV ENERGY RESULTS FOR NON-REGULATED COMPONENTS¹			
Non-Regulated Energy Component	Standard Design (TDV)	Proposed Design (TDV)	Compliance Margin (TDV)¹
Receptacle	46.62	46.62	---
Process	49	48.95	0.05
Other Ltg	8.63	8.63	---
Process Motors	---	---	---
TOTAL (TOTAL COMPLIANCE + NON-REGULATED COMPONENTS)	104.48	54.75	49.73 (47.6%)
¹ Notes: This table is not used for Energy Code Compliance.			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 6 of 43)

C4. SOURCE ENERGY COMPLIANCE RESULTS FOR PERFORMANCE COMPONENTS (Annual SOURCE Energy Use, kBtu/ft² /yr)			
COMPLIES²			
Energy Component	Standard Design (SOURCE)	Proposed Design (SOURCE)	Compliance Margin (SOURCE)¹
Space Heating	0.09	0.1	-0.01
Space Cooling	1.23	1.07	0.16
Indoor Fans	0.98	0.36	0.62
Heat Rejection	0	0	0
Pumps & Misc.	0.06	0.05	0.01
Domestic Hot Water	2.19	1.83	0.36
Indoor Lighting	2.06	2.06	0
Flexibility	---	---	---
EFFICIENCY COMPLIANCE TOTAL	6.61	5.47	1.14 (17.2%)
Photovoltaics	-2.49	-3.91	1.42
Batteries	-1.77	---	-1.77
TOTAL COMPLIANCE	2.35	1.56	0.79 (33.6%)
¹ Notes: This number in parenthesis following the Compliance Margin in column 4, represents the Percent Better than Standard.			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 7 of 43)

C5. SOURCE ENERGY RESULTS FOR NON-REGULATED COMPONENTS¹			
Non-Regulated Energy Component	Standard Design (SOURCE)	Proposed Design (SOURCE)	Compliance Margin (SOURCE)¹
Receptacle	4.56	4.56	---
Process	4.11	4.11	---
Other Ltg	0.89	0.89	---
Process Motors	---	---	---
TOTAL (TOTAL COMPLIANCE + NON-REGULATED COMPONENTS)	11.91	11.12	0.79 (6.6%)
¹ Notes: This table is not used for Energy Code Compliance.			

C6. 'ABOVE CODE' QUALIFICATIONS	
☐ This project is pursuing CalGreen Tier 1	☐ This project is pursuing CalGreen Tier 2

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 8 of 43)

C7. ENERGY USE SUMMARY						
Energy Component	Standard Design Site (MWh)	Proposed Design Site (MWh)	Margin (MWh)	Standard Design Site (MBtu)	Proposed Design Site (MBtu)	Margin (MBtu)
Space Heating	0.7	0.9	-0.2	---	---	---
Space Cooling	23.4	19	4.4	---	---	---
Indoor Fans	14.6	5.7	8.9	---	---	---
Heat Rejection	---	---	---	---	---	---
Pumps & Misc.	0.5	0.5	0	---	---	---
Domestic Hot Water	32.4	28	4.4	---	---	---
Indoor Lighting	28.6	28.6	0	---	---	---
Flexibility	---	---	---	---	---	---
EFFICIENCY TOTAL	100.2	82.7	17.5	0	0	0
Photovoltaics	-130.5	-204.8	74.3	---	---	---
Batteries	2.2	---	---	---	---	---
ENERGY USE SUBTOTAL	-28.1	-122.1	94	0	0	0
Receptacle	59.3	59.3	0	---	---	---
Process	65.3	65.2	0.1	---	---	---
Other Ltg	10.1	10.1	0	---	---	---
Process Motors	---	---	---	---	---	---
ENERGY USE TOTAL	106.6	12.5	94.1	0	0	0

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 9 of 43)

C8. ENERGY USE INTENSITY (EUI)				
	Standard Design (kBtu/ft² / yr)	Proposed Design (kBtu/ft² / yr)	Margin (kBtu/ft² / yr)	Margin Percentage
GROSS EUI ¹	17.66	16.18	1.48	8.38
NET EUI ¹	7.94	0.93	7.01	88.29
¹ Notes: Gross EUI is Energy Use Total (not including PV)/Total Building Area. Net EUI is Energy Use Total (including PV)/Total Building Area.				

D1. EXCEPTIONAL CONDITIONS
PV/Battery Building Type has been modified from software defaults for one or more spaces. Review project's PV/Battery Building Type(s) with documentation author. Refer to Energy Code section 140.10 for Nonresidential or 170.2(g) for more information.

D2. MULTIFAMILY REQUIRED SPECIAL FEATURES
- IAQ Ventilation System: as low as 0.092 W/CFM - Cool roof - Window overhangs and/or fins - Non-standard duct location (any location other than attic) - Central Heat Pump Water Heater - Multifamily: Recirculating with no control (continuous pumping)

F1. REQUIRED PV SYSTEMS											
01	02	03	04	05	06	07	08	09	10	11	12
DC System Size (kWdc)	Exception ¹	Module Type	Array Type	Power Electronics	CFI	Azimuth (deg)	Tilt Input	Array Angle (deg)	Tilt: (x in 12)	Inverter Eff. (%)	Annual Solar Access (%)
120.1		Standard (14-17%)	Fixed	none	true	150-270	n/a	n/a	<=7:12	96	98
¹ See Table D1 for any PV exceptions used.											

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 10 of 43)

F1B. PV BATTERY BUILDING TYPE(S)		
01	02	03
Building Occupancy Type* (From Table 140.10-A/B and 170.2-U/V)	Conditioned Floor Area (ft²)	Unconditioned Floor Area (ft²)
Grocery	0	0
High-Rise Multifamily	34619.6	4989.08
Office, Financial Institutions, Unleased Tenant Space	0	0
Retail	0	0
School	0	0
Warehouse	0	0
Auditorium, Convention Center, Hotel/Motel, Library, Medical Office Building/Clinic, Restaurant, Theater	0	0
None	532.353	5676.52
<i>*Building Occupancy Types are defined in Section 100.1 of the Energy Code</i>		

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 11 of 43)

F3. DWELLING UNIT INFORMATION			
01	02	03	04
Dwelling Unit Name	Dwelling Unit Type	Zone	Zone Group Multiplier
DwellingUnit 1-(1/1)	P1.0(S5)	P1.0 (S5)_L1	1
DwellingUnit 2-(1/1)	P1.0(S3)	P1.0 (S3)_L1	1
DwellingUnit 3-(1/1)	P1.0(S4)	P1.0 (S4)_L1	1
DwellingUnit 4-(1/1)	P1.0(S4)	P1.0 (S2)_L1	1
DwellingUnit 5-(1/1)	P1.0(S4)	P1.0 (S1)_L1	1
DwellingUnit 6-(1/1)	P2.0(S2)	P2.0 (S2)_L1	1
DwellingUnit 7-(1/1)	P2.0(S1)	P2.0 (S1)_L1	1
DwellingUnit 8-(1/1)	P1.1(N1)	P1.1 (N1)_L2	1
DwellingUnit 9-(1/1)	P1.0(S5)	P1.0 (S5)_L2	1
DwellingUnit 10-(1/1)	P1.0(S3)	P1.0 (S3)_L2	1
DwellingUnit 11-(1/1)	P1.0(S4)	P1.0 (S4)_L2	1
DwellingUnit 12-(1/1)	P1.0(S4)	P1.0 (S2)_L2	1
DwellingUnit 13-(1/1)	P1.0(S4)	P1.0 (S1)_L2	1
DwellingUnit 14-(1/1)	P2.3(N1)	P2.3 (N1)_L2	1
DwellingUnit 15-(1/1)	P2.1(N2)	P2.1 (N2)_L2	1
DwellingUnit 16-(1/1)	P2.1(N3)	P2.1 (N3)_L2	1
DwellingUnit 17-(1/1)	P2.0(S2)	P2.0 (S2)_L2	1
DwellingUnit 18-(1/1)	P2.0(S1)	P2.0 (S1)_L2	1
DwellingUnit 19-(1/1)	P1.1(N1)	P1.1 (N1)_L3	1
DwellingUnit 20-(1/1)	P1.0(S5)	P1.0 (S5)_L3	1
DwellingUnit 21-(1/1)	P1.0(S3)	P1.0 (S3)_L3	1
DwellingUnit 22-(1/1)	P1.0(S4)	P1.0 (S4)_L3	1
DwellingUnit 23-(1/1)	P1.0(S4)	P1.0 (S2)_L3	1
DwellingUnit 24-(1/1)	P1.0(S4)	P1.0 (S1)_L3	1
DwellingUnit 25-(1/1)	P2.3(N1)	P2.3 (N1)_L3	1
DwellingUnit 26-(1/1)	P2.1(N2)	P2.1 (N2)_L3	1

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 12 of 43)

F3. DWELLING UNIT INFORMATION			
01	02	03	04
Dwelling Unit Name	Dwelling Unit Type	Zone	Zone Group Multiplier
DwellingUnit 27-(1/1)	P2.1(N3)	P2.1 (N3)_L3	1
DwellingUnit 28-(1/1)	P2.0(S2)	P2.0 (S2)_L3	1
DwellingUnit 29-(1/1)	P2.0(S1)	P2.0 (S1)_L3	1
DwellingUnit 35-(1/1)	P1.1(N1)	P1.1 (N1)_L4	1
DwellingUnit 30-(1/1)	P1.0(S5)	P1.0 (S5)_L4	1
DwellingUnit 31-(1/1)	P1.0(S3)	P1.0 (S3)_L4	1
DwellingUnit 32-(1/1)	P1.0(S4)	P1.0 (S4)_L4	1
DwellingUnit 33-(1/1)	P1.0(S4)	P1.0 (S2)_L4	1
DwellingUnit 34-(1/1)	P1.0(S4)	P1.0 (S1)_L4	1
DwellingUnit 36-(1/1)	P2.3(N1)	P2.3 (N1)_L4	1
DwellingUnit 37-(1/1)	P2.1(N2)	P2.1 (N2)_L4	1
DwellingUnit 38-(1/1)	P2.1(N3)	P2.1 (N3)_L4	1
DwellingUnit 39-(1/1)	P2.0(S2)	P2.0 (S2)_L4	1
DwellingUnit 40-(1/1)	P2.0(S1)	P2.0 (S1)_L4	1

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 13 of 43)

F4. DWELLING UNIT TYPES						
01	02	03	04	05	06	07
Name	CFA (ft²)	Number of Bedrooms	Number in Building	Space Conditioning Systems Assigned	DHW System Name	IAQ Vent Fan Name
P1.0(S5)	742.361	1	4	P1.0(S5) :VFC-1 / 1.5:ResidentialDistributionSystem 1:VFC-1/1.5 Fan:2:3	ResidentialDHWSys _{tem} 1	Individual IAQ Fans
P1.0(S3)	735.606	1	4	P1.0(S3) :VFC-1 / 1.5:ResidentialDistributionSystem 1:VFC-1/1.5 Fan:2:3	ResidentialDHWSys _{tem} 1	Individual IAQ Fans
P1.0(S4)	732.005	1	12	P1.0(S4) :VFC-1 / 1.5:ResidentialDistributionSystem 1:VFC-1/1.5 Fan:2:3	ResidentialDHWSys _{tem} 1	Individual IAQ Fans
P2.0(S2)	1048.32	2	4	P2.0(S2) :VFC-2:ResidentialDistributionSystem 1:VFC-2 Fan:2:3	ResidentialDHWSys _{tem} 1	Individual IAQ Fans
P2.0(S1)	1056.47	2	4	P2.0(S1) :VFC-2:ResidentialDistributionSystem 1:VFC-2 Fan:2:3	ResidentialDHWSys _{tem} 1	Individual IAQ Fans
P1.1(N1)	833.885	1	3	P1.1(N1) :VFC-1 / 1.5:ResidentialDistributionSystem 1:VFC-1/1.5 Fan:2:3	ResidentialDHWSys _{tem} 1	Individual IAQ Fans

F4. DWELLING UNIT TYPES						
01	02	03	04	05	06	07
Name	CFA (ft ²)	Number of Bedrooms	Number in Building	Space Conditioning Systems Assigned	DHW System Name	IAQ Vent Fan Name
P2.3(N1)	1030.86	2	3	P2.3(N1) :VFC- 2:ResidentialDistributionSystem 1:VFC-2 Fan:2:3	ResidentialDHWSystem 1	Individual IAQ Fans
P2.1(N2)	982.949	2	3	P2.1(N2) :VFC- 2:ResidentialDistributionSystem 1:VFC-2 Fan:2:3	ResidentialDHWSystem 1	Individual IAQ Fans
P2.1(N3)	987.143	2	3	P2.1(N3) :VFC- 2:ResidentialDistributionSystem 1:VFC-2 Fan:2:3	ResidentialDHWSystem 1	Individual IAQ Fans

G1. ENVELOPE GENERAL INFORMATION (conditioned spaces only)			
01	02	03	04
Opaque Surfaces & Orientation	Total Gross Surface Area (ft ²)	Total Fenestration Area (ft ²)	Window to Wall Ratio (%)
North-Facing ¹	2740.99	235.35	8.59
East-Facing ²	5383	1032	19.17
South-Facing ³	3799.49	208.69	5.49
West-Facing ⁴	8548	2007.5	23.49

Notes

¹North-Facing is oriented to within 45 degrees of true north, including 4500'00" east of north (NE), but excluding 4500'00" west of north (NW),

²East-Facing is oriented to within 45 degrees of true east, including 4500'00" south of east (SE), but excluding 4500'00" north of east (NE),

³South-Facing is oriented to within 45 degrees of true south, including 4500'00" west of south (SW), but excluding 4500'00" east of south (SE),

⁴West-Facing is oriented to within 45 degrees of true west, including 4500'00" north of west (NW), but excluding 4500'00" south of west (SW),

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 15 of 43)

G1. ENVELOPE GENERAL INFORMATION (conditioned spaces only)			
01	02	03	04
Opaque Surfaces & Orientation	Total Gross Surface Area (ft ²)	Total Fenestration Area (ft ²)	Window to Wall Ratio (%)
Total	20471.5	3483.54	17.02
Roof	9613	0	0
Notes ¹North-Facing is oriented to within 45 degrees of true north, including 4500'00" east of north (NE), but excluding 4500'00" west of north (NW), ²East-Facing is oriented to within 45 degrees of true east, including 4500'00" south of east (SE), but excluding 4500'00" north of east (NE), ³South-Facing is oriented to within 45 degrees of true south, including 4500'00" west of south (SW), but excluding 4500'00" east of south (SE), ⁴West-Facing is oriented to within 45 degrees of true west, including 4500'00" north of west (NW), but excluding 4500'00" south of west (SW),			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 16 of 43)

G2B. ROOFING PRODUCT SUMMARY (MULTIFAMILY AND COMMON AREAS)					
01	02	03	04	05	06
Name	Roof Pitch	Roof Rise (x in 12)	Aged Solar Reflectance	Thermal Emittance	SRI
Roof : GARAGE RIGHT_L1	Low slope	0	0.1	0.85	N/A
Roof : CORRIDOR_L1	Low slope	0	0.1	0.85	N/A
Roof : GARAGE LEFT_L1	Low slope	0	0.1	0.85	N/A
ResidentialCathedralCeiling 4-11	Low slope	0	0.65	0.85	N/A
ResidentialCathedralCeiling 4-6	Low slope	0	0.65	0.85	N/A
ResidentialCathedralCeiling 4-7	Low slope	0	0.65	0.85	N/A
ResidentialCathedralCeiling 4-8	Low slope	0	0.65	0.85	N/A
ResidentialCathedralCeiling 4-9	Low slope	0	0.65	0.85	N/A
ResidentialCathedralCeiling 4-10	Low slope	0	0.65	0.85	N/A
ResidentialCathedralCeiling 4-12	Low slope	0	0.65	0.85	N/A
ResidentialCathedralCeiling 4-13	Low slope	0	0.65	0.85	N/A
ResidentialCathedralCeiling 4-14	Low slope	0	0.65	0.85	N/A
ResidentialCathedralCeiling 4	Low slope	0	0.65	0.85	N/A
ResidentialCathedralCeiling 4-2	Low slope	0	0.65	0.85	N/A
ResidentialCathedralCeiling 4-3	Low slope	0	0.65	0.85	N/A

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 17 of 43)

G2B. ROOFING PRODUCT SUMMARY (MULTIFAMILY AND COMMON AREAS)					
01	02	03	04	05	06
Name	Roof Pitch	Roof Rise (x in 12)	Aged Solar Reflectance	Thermal Emittance	SRI
ResidentialCathedralCeiling 4-4	Low slope	0	0.65	0.85	N/A
ResidentialCathedralCeiling 4-5	Low slope	0	0.65	0.85	N/A

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 18 of 43)

G5. OPAQUE SURFACE ASSEMBLY SUMMARY										
01	02	03	04	05	06		07	08	09	10
Surface Name	Construction Type	Area (ft²)	Framing Type	Cavity R-Value	Continuous R-Value		Units	Value	Description of Assembly Layers	Status¹
					Interior	Exterior				
Ext Wall Cons	Exterior Walls	25,045	Wood Framed Wall	21	0	0	U-factor	0.0647	Inside Finish: Gypsum Board Cavity / Frame: R-21 / 2x6 Sheathing / Insulation: Wood Siding/sheathing/decking Exterior Finish: Synthetic Stucco	N
Interior Floor Cons	Interior Floors	34,145.2	Wood Framed Floor	19	0	0	U-factor	0.0441	Floor Surface: Carpeted Floor Deck: Wood Siding/sheathing/decking Cavity / Frame: R-19 / 2x12 Ceiling Below Finish: Gypsum Board	N
R49 Roof Cons	Cathedral Ceilings	11,726.8	Wood Framed Ceiling	49	0	0	U-factor	0.023	Roofing: Light Roof (Asphalt Shingle) Roof Deck: Wood Siding/sheathing/decking Cavity / Frame: R-49 / 2x12 Sheathing / Insulation: Wood Siding/sheathing/decking Inside Finish: Gypsum Board	N
R-19 Interior Wall	Interior Walls	28,240	Wood Framed Wall	19	0	0	U-factor	0.067	Inside Finish: Gypsum Board Cavity / Frame: R-19 / 2x6 Other Side Finish: Gypsum Board	
T24-IntZB-Wall Cons	Interior Walls	42,873	Wood Framed Wall	0	0	0	U-factor	0.2773	Inside Finish: Gypsum Board Cavity / Frame: no insul. / 2x4 Other Side Finish: Gypsum Board	
T24-IntZB-Clg Cons	Interior Ceiling	1,287.35	Wood Framed Ceiling	0	0	0	U-factor	0.1957	Floor Surface: Carpeted Floor Deck: Wood Siding/sheathing/decking Cavity / Frame: no insul. / 2x12 Ceiling Below Finish: Gypsum Board	N

¹ Status: N - New, A - Altered, E - Existing

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD									NRCC-PRF-E	
Nonresidential Performance Compliance Method									(Page 19 of 43)	
G5. OPAQUE SURFACE ASSEMBLY SUMMARY										
01	02	03	04	05	06		07	08	09	10
Surface Name	Construction Type	Area (ft²)	Framing Type	Cavity R-Value	Continuous R-Value		Units	Value	Description of Assembly Layers	Status¹
					Interior	Exterior				
T24-IntZB-Flr Cons	Interior Floors	636.8	Wood Framed Floor	0	0	0	U-factor	0.1957	Floor Surface: Carpeted Floor Deck: Wood Siding/sheathing/decking Cavity / Frame: no insul. / 2x12 Ceiling Below Finish: Gypsum Board	N
¹ Status: N - New, A - Altered, E - Existing										

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 20 of 43)

G6B. OPAQUE DOOR SUMMARY (MULTIFAMILY AND COMMON AREAS)			
01	02	03	04
Name	Area (ft²)	Overall U-factor	Status¹
ResidentialDoor 1	20	0.2	N
ResidentialDoor 1-2	20	0.2	N
ResidentialDoor 1-3	20	0.2	N
ResidentialDoor 1-4	20	0.2	N
ResidentialDoor 1-5	20	0.2	N
ResidentialDoor 1-6	20	0.2	N
ResidentialDoor 1-6-2	20	0.2	N
ResidentialDoor 1-7	20	0.2	N
ResidentialDoor 1-7-2	20	0.2	N
ResidentialDoor 1-7-3	20	0.2	N
ResidentialDoor 1-7-4	20	0.2	N
ResidentialDoor 1-7-5	20	0.2	N
ResidentialDoor 1-7-6	20	0.2	N
ResidentialDoor 1-6-3	20	0.2	N
ResidentialDoor 1-6-4	20	0.2	N
ResidentialDoor 1-6-5	20	0.2	N
ResidentialDoor 1-6-6	20	0.2	N
ResidentialDoor 1-6-7	20	0.2	N
ResidentialDoor 1-7-6-2	20	0.2	N
ResidentialDoor 1-7-6-2-2	20	0.2	N
ResidentialDoor 1-7-6-2-3	20	0.2	N
ResidentialDoor 1-7-6-2-4	20	0.2	N
ResidentialDoor 1-7-6-2-5	20	0.2	N
ResidentialDoor 1-7-6-2-6	20	0.2	N
¹ Status: N - New, A - Altered, E - Existing			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 21 of 43)

G6B. OPAQUE DOOR SUMMARY (MULTIFAMILY AND COMMON AREAS)			
01	02	03	04
Name	Area (ft²)	Overall U-factor	Status¹
ResidentialDoor 1-6-8	20	0.2	N
ResidentialDoor 1-6-8-2	20	0.2	N
ResidentialDoor 1-6-8-3	20	0.2	N
ResidentialDoor 1-6-8-4	20	0.2	N
ResidentialDoor 1-6-8-5	20	0.2	N
ResidentialDoor 1-7-6-2-7-6	20	0.2	N
ResidentialDoor 1-7-6-2-7	20	0.2	N
ResidentialDoor 1-7-6-2-7-2	20	0.2	N
ResidentialDoor 1-7-6-2-7-3	20	0.2	N
ResidentialDoor 1-7-6-2-7-4	20	0.2	N
ResidentialDoor 1-7-6-2-7-5	20	0.2	N
ResidentialDoor 1-6-8-6	20	0.2	N
ResidentialDoor 1-6-8-6-2	20	0.2	N
ResidentialDoor 1-6-8-6-3	20	0.2	N
ResidentialDoor 1-6-8-6-4	20	0.2	N
ResidentialDoor 1-6-8-6-5	20	0.2	N
¹ Status: N - New, A - Altered, E - Existing			

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 22 of 43)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
ResidentialWindow 57	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.0 (S5)_L1	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 58	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.0 (S5)_L1	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 57-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.0 (S3)_L1	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 58-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.0 (S3)_L1	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 57-2-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.0 (S4)_L1	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 58-3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.0 (S4)_L1	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 57-2-3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.0 (S2)_L1	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 23 of 43)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
ResidentialWindow 58-3-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.0 (S2)_L1	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 57-2-3-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.0 (S1)_L1	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 58-3-2-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.0 (S1)_L1	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 62	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P2.0 (S2)_L1	270	1	85	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.0 (S2)_L1	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : P2.0 (S2)_L1	0	1	8	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 61	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : P2.0 (S2)_L1	0	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 58-3-2-3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P2.0 (S1)_L1	270	1	87.5	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 24 of 43)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window : P2.0 (S1)_L1	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P2.0 (S1)_L1	180	1	10	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 61-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Left) : P2.0 (S1)_L1	0	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.1 (N1)_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.1 (N1)_L2	90	1	70	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 61-2-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.1 (N1)_L2	90	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S5)_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S5)_L2	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 61-2-2-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S5)_L2	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S3)_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S3)_L2	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 25 of 43)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
ResidentialWindow 61-2-2-2-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S3)_L2	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S4)_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S4)_L2	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 61-2-2-2-3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S4)_L2	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S2)_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S2)_L2	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 61-2-2-2-4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S2)_L2	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S1)_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S1)_L2	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 61-2-2-2-5	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S1)_L2	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 26 of 43)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window : STAIRS RIGHT_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : STAIRS RIGHT_L2	0	1	75.35	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : STAIR LEFT_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Left) : STAIR LEFT_L2	180	1	75.35	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.1 (N1)_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P2.1 (N1)_L2	90	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.1 (N2)_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P2.1 (N2)_L2	90	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.1 (N3)_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P2.1 (N3)_L2	270	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.0 (S2)_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : P2.0 (S2)_L2	0	1	8	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Residential Window 65	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : P2.0 (S2)_L2	0	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 27 of 43)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window : P2.0 (S2)_L2 2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P2.0 (S2)_L2	270	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 61-2-2-2-5-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : P2.0 (S1)_L2	0	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.0 (S1)_L2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P2.0 (S1)_L2	270	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.0 (S1)_L2 2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Left) : P2.0 (S1)_L2	180	1	16	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.1 (N1)_L3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.1 (N1)_L3	90	1	70	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 61-2-2-3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.1 (N1)_L3	90	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S5)_L2-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S5)_L3	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 28 of 43)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
ResidentialWindow 61-2-2-2-6	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S5)_L3	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S3)_L3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S3)_L3	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 66	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S3)_L3	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S4)_L3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S4)_L3	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 61-2-2-2-3-2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S4)_L3	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S2)_L3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S2)_L3	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 67	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S2)_L3	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 29 of 43)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window : P1.0 (S2)_L3 2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S2)_L3 2	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 68	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S2)_L3 2	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : STAIRS RIGHT_L3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : STAIRS RIGHT_L3	0	1	75.35	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : STAIR LEFT_L3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Left) : STAIR LEFT_L3	180	1	75.35	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.1 (N1)_L3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P2.1 (N1)_L3	90	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.1 (N2)_L3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P2.1 (N2)_L3	90	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.1 (N3)_L3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P2.1 (N3)_L3	90	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 30 of 43)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window : P2.0 (S2)_L3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : P2.0 (S2)_L3	270	1	16	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 69	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : P2.0 (S2)_L3	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.0 (S2)_L3 2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P2.0 (S2)_L3	90	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 70	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : P2.0 (S1)_L3	0	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.0 (S1)_L3	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P2.0 (S1)_L3	270	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.0 (S1)_L3 2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Left) : P2.0 (S1)_L3	180	1	16	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.1 (N1)_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.1 (N1)_L4	90	1	70	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 31 of 43)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
ResidentialWindow 71	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P1.1 (N1)_L4	90	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S5)_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S5)_L4	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 72	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S5)_L4	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S3)_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S3)_L4	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 73	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S3)_L4	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S4)_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S4)_L4	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 74	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S4)_L4	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 32 of 43)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window : P1.0 (S2)_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S2)_L4	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 75	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S2)_L4	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P1.0 (S1)_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S1)_L4	270	1	45	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
ResidentialWindow 76	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P1.0 (S1)_L4	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : STAIRS RIGHT_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : STAIRS RIGHT_L4	0	1	75.35	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : STAIR LEFT_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Left) : STAIR LEFT_L4	180	1	75.35	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.1 (N1)_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P2.1 (N1)_L4	90	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 33 of 43)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Window : P2.1 (N2)_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P2.1 (N2)_L4	90	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.1 (N3)_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Back) : P2.1 (N3)_L4	90	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.0 (S2)_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : P2.0 (S2)_L4	270	1	16	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Residential Window 77	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : P2.0 (S2)_L4	270	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.0 (S2)_L4 2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P2.0 (S2)_L4	90	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Residential Window 78	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Right) : P2.0 (S1)_L4	0	1	24	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
Window : P2.0 (S1)_L4	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Front) : P2.0 (S1)_L4	270	1	75	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD											NRCC-PRF-E	
Nonresidential Performance Compliance Method											(Page 34 of 43)	
G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status ¹
Window : P2.0 (S1)_L4 2	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	ExtWall (Left) : P2.0 (S1)_L4	180	1	16	0.27	NFRC	0.21	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 35 of 43)

G8. OVERHANG DETAILS						
01	02	03	04	05	06	07
Fenestration Tag/ ID	Azimuth	Depth (ft)	Height from Top of Sill to Overhang (ft)	Right Extent (ft)	Left Extent (ft)	Flap Height
ResidentialWindow 58	270	5.5	8	0	0	0
ResidentialWindow 58-2	270	5.5	8	0	0	0
ResidentialWindow 58-3	270	5.5	8	0	0	0
ResidentialWindow 58-3-2	270	5.5	8	0	0	0
ResidentialWindow 58-3-2-2	270	5.5	8	0	0	0
ResidentialWindow 61	0	5.5	8	0	0	0
ResidentialWindow 61-2	0	5.5	8	0	0	0
ResidentialWindow 61-2-2	90	5.5	8	0	0	0
ResidentialWindow 61-2-2-2	270	5.5	8	0	0	0
ResidentialWindow 61-2-2-2-2	270	5.5	8	0	0	0
ResidentialWindow 61-2-2-2-3	270	5.5	8	0	0	0
ResidentialWindow 61-2-2-2-4	270	5.5	8	0	0	0
ResidentialWindow 61-2-2-2-5	270	5.5	8	0	0	0
ResidentialWindow 65	0	5.5	8	0	0	0
ResidentialWindow 61-2-2-2-5-2	0	5.5	8	0	0	0
ResidentialWindow 61-2-2-3	90	5.5	8	0	0	0

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 36 of 43)

G8. OVERHANG DETAILS						
01	02	03	04	05	06	07
Fenestration Tag/ ID	Azimuth	Depth (ft)	Height from Top of Sill to Overhang (ft)	Right Extent (ft)	Left Extent (ft)	Flap Height
ResidentialWindow 61-2-2-2-6	270	5.5	8	0	0	0
ResidentialWindow 66	270	5.5	8	0	0	0
ResidentialWindow 61-2-2-2-3-2	270	5.5	8	0	0	0
ResidentialWindow 67	270	5.5	8	0	0	0
ResidentialWindow 68	270	5.5	8	0	0	0
ResidentialWindow 69	270	5.5	8	0	0	0
ResidentialWindow 70	0	5.5	8	0	0	0
ResidentialWindow 71	90	5.5	8	0	0	0
ResidentialWindow 72	270	5.5	8	0	0	0
ResidentialWindow 73	270	5.5	8	0	0	0
ResidentialWindow 74	270	5.5	8	0	0	0
ResidentialWindow 75	270	5.5	8	0	0	0
ResidentialWindow 76	270	5.5	8	0	0	0
ResidentialWindow 77	270	5.5	8	0	0	0
ResidentialWindow 78	0	5.5	8	0	0	0

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 37 of 43)

H2. DWELLING UNIT HVAC HEATING AND COOLING SYSTEMS												
01	02	03	04	05	06	07	08	09	10	11	12	13
Dwelling Unit Type	Equipment Name	Equipment Type	Quantity	Air Distribution System Name	Fan System name	Heating				Cooling		
						Heat Output at 47	Heat Output at 17	Efficiency Unit	Efficiency	Total Cooling Output	Efficiency Unit	Efficiency
P1.0(S5)	VFC-1 / 1.5	Central split HP N/A	4	ResidentialDis tributionSyste m 1	VFC-1/1.5 Fan	16,800	12,768	HSPF2	7.8	N/A	EER2 SEER2	12.48 15.2
P1.0(S3)	VFC-1 / 1.5	Central split HP N/A	4	ResidentialDis tributionSyste m 1	VFC-1/1.5 Fan	16,800	12,768	HSPF2	7.8	N/A	EER2 SEER2	12.48 15.2
P1.0(S4)	VFC-1 / 1.5	Central split HP N/A	12	ResidentialDis tributionSyste m 1	VFC-1/1.5 Fan	16,800	12,768	HSPF2	7.8	N/A	EER2 SEER2	12.48 15.2
P2.0(S2)	VFC-2	Central split HP N/A	4	ResidentialDis tributionSyste m 1	VFC-2 Fan	22,600	14,700	HSPF2	7.8	N/A	EER2 SEER2	12.48 15.5
P2.0(S1)	VFC-2	Central split HP N/A	4	ResidentialDis tributionSyste m 1	VFC-2 Fan	22,600	14,700	HSPF2	7.8	N/A	EER2 SEER2	12.48 15.5
P1.1(N1)	VFC-1 / 1.5	Central split HP N/A	3	ResidentialDis tributionSyste m 1	VFC-1/1.5 Fan	16,800	12,768	HSPF2	7.8	N/A	EER2 SEER2	12.48 15.2
P2.3(N1)	VFC-2	Central split HP N/A	3	ResidentialDis tributionSyste m 1	VFC-2 Fan	22,600	14,700	HSPF2	7.8	N/A	EER2 SEER2	12.48 15.5
P2.1(N2)	VFC-2	Central split HP N/A	3	ResidentialDis tributionSyste m 1	VFC-2 Fan	22,600	14,700	HSPF2	7.8	N/A	EER2 SEER2	12.48 15.5
P2.1(N3)	VFC-2	Central split HP N/A	3	ResidentialDis tributionSyste m 1	VFC-2 Fan	22,600	14,700	HSPF2	7.8	N/A	EER2 SEER2	12.48 15.5

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 38 of 43)

H3a. MULTIFAMILY / COMMON USE AREA FAN SYSTEMS SUMMARY				
01	02	03	04	05
Name	Type	Power	Power Units	Status
VFC-1/1.5 Fan	Fixed speed	0.41	W/cfm	N/A
VFC-2 Fan	Fixed speed	0.31	W/cfm	N/A

H3b. MULTIFAMILY / COMMON USE AREA IAQ FAN SYSTEMS SUMMARY					
01	02	03	04	05	06
Name	Type	Airflow (CFM)	Power	Power Units	Status
Corridor IAQ Fan_L01	Exhaust	210	0.31	W/cfm	N/A
Corridor IAQ Fan_L02	Exhaust	230	0.31	W/cfm	N/A
Corridor IAQ FAN_L03	Exhaust	235	0.31	W/cfm	N/A
TEF-1_50	Exhaust	50	0.1	W/cfm	N/A
TEF-1_60	Exhaust	60	0.09	W/cfm	N/A
Corridor IAQ FAN_L04	Exhaust	235	0.31	W/cfm	N/A

H4. MULTIFAMILY HVAC DISTRIBUTION							
01	02	03	04	05	06	07	08
Name	Type	Duct Ins. R-value Supply	Duct Ins. R-value Return	Duct Location Supply	Duct Location Return	Verified Duct Design Surface Area	
						Supply	Return
ResidentialDistributionSystem 1	Conditioned space-entirely (Non-Verified)	R-4.2	R-4.2	Conditioned Zone	Conditioned Zone	n/a	n/a

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 39 of 43)

H9. NONRESIDENTIAL / COMMON USE AREA & HOTEL/MOTEL VENTILATION						
01	02	03	04	05	06	07
Zone Name	Mechanical Ventilation				Conditioned Area (sf)	DCV or Occupant Sensor Controls, or Both
	Ventilation Function	# of People	Supply OA CFM	Exhaust CFM		
Stair-1_L02	General - Unoccupied	0.89	0	0	177.45	N/A
Stair-2_L03	General - Unoccupied	0.89	0	0	177.45	N/A
Stair-1_L03	General - Unoccupied	0.89	0	0	177.45	N/A

H10. MULTIFAMILY DWELLING UNIT TYPE CENTRAL / INDIVIDUAL VENTILATION												
01	02	03	04	05	06	07	08	09	10	11	12	13
Dwelling Unit Type	IAQ Option	Central Fan (if applicable)					Individual Fan (if applicable)					
		IAQ Fan Type Type	Supply Airflow CFM	Supply Fan Efficacy W/CFM	Exhaust CFM	Exhaust Fan Efficacy W/CFM	IAQ Fan Type	Count	Airflow CFM	Fan Efficacy W/CFM	Recovery Efficiency SRE	Recovery Efficiency ASRE
P1.0(S5)	Individual IAQ Fan	N/A	N/A	N/A	N/A	N/A	Exhaust	1	50	0.1	N/A	N/A
P1.0(S3)	Individual IAQ Fan	N/A	N/A	N/A	N/A	N/A	Exhaust	1	50	0.1	N/A	N/A
P1.0(S4)	Individual IAQ Fan	N/A	N/A	N/A	N/A	N/A	Exhaust	1	50	0.1	N/A	N/A
P2.0(S2)	Individual IAQ Fan	N/A	N/A	N/A	N/A	N/A	Exhaust	1	60	0.09	N/A	N/A
P2.0(S1)	Individual IAQ Fan	N/A	N/A	N/A	N/A	N/A	Exhaust	1	60	0.09	N/A	N/A
P1.1(N1)	Individual IAQ Fan	N/A	N/A	N/A	N/A	N/A	Exhaust	1	50	0.1	N/A	N/A
P2.3(N1)	Individual IAQ Fan	N/A	N/A	N/A	N/A	N/A	Exhaust	1	60	0.09	N/A	N/A
P2.1(N2)	Individual IAQ Fan	N/A	N/A	N/A	N/A	N/A	Exhaust	1	60	0.09	N/A	N/A
P2.1(N3)	Individual IAQ Fan	N/A	N/A	N/A	N/A	N/A	Exhaust	1	60	0.09	N/A	N/A

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 40 of 43)

12. MULTI-FAMILY WATER HEATING SYSTEM DETAIL							
01	02	03	04	05	06	07	08
System Name	Configuration	Type	Qty in System	Dwelling Unit Distribution Type	Water Heater Name	Solar Heating System	Is Compact Distribution
ResidentialDHWSystem 1	Domestic Hot Water (DHW)	Central	1	Standard Distribution System	ResidentialDHWSystem 1 - heater	N/A	N/A

13. MULTIFAMILY & HOTEL/MOTEL WATER HEATER EQUIPMENT SUMMARY - CHPWH							
01	02	03	04	05	06	07	08
Name	Brand/Model	Number of Compressors	Primary Tank Volume (gal)	Tank Count	Tank R-value	Tank Location	Air Source
ResidentialDHWSystem 1		4	1497	3	16	Outside	Outside

15. RECIRCULATION LOOPS					
01	02	03	04	05	06
Water Heating System Name	Number of Recirculation Loops	Loop Insulation Thickness (in)	Recirculation Loop Location	Recirculation Pump Power	Recirculation Pump Power Units
ResidentialDHWSystem 1	1	1.5	Conditioned	24	Watts

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 41 of 43)

K1. INDOOR CONDITIONED LIGHTING GENERAL INFO					
01	02	03	04	05	06
Occupancy Type¹	Conditioned Floor Area² (ft²)	Installed Lighting Power (Watts)	Lighting Control Credits (Watts)	Additional (Custom) Allowance	
				Area Category Footnotes (Watts)	Area Category Footnotes (Watts)
Stairwell	532.35	319.41	0	0	0
Building Totals:	532.35	319.41	0	0	0
¹ See Table 140.6-C ² See NRCC-LTI-E for unconditioned spaces ³ Lighting information for existing spaces modeled is not included in this table					

K4. INDOOR CONDITIONED LIGHTING MANDATORY LIGHTING CONTROL
See NRCC-LTI-E for mandatory controls

L. DECLARATION OF REQUIRED CERTIFICATES OF INSTALLATION	
Selections made by Documentation Author indicate which Certificates of Installation must be submitted for the features to be recognized for compliance. These documents must be retained and provided to the building inspector during construction and can be found online	
Building Component	Form/Title
Envelope	NRCI-ENV-E - Envelope (for all buildings)
Mechanical	NRCI-MCH-E - For all buildings with Mechanical Systems
Plumbing	NRCI-PLB-E - For all buildings with Plumbing Systems
	NRCI-SAB-E - Solar Water Heating, PV and Battery Storage Systems
Indoor Lighting	NRCI-LTI-E - Indoor Lighting (for all buildings)
Covered Process	NRCI-PRC-E - Covered Processes

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 42 of 43)

M. DECLARATION OF REQUIRED CERTIFICATES OF ACCEPTANCE	
Selections made by Documentation Author indicate which Certificates of Acceptance must be submitted for the features to be recognized for compliance. These documents must be provided to the building inspector during construction and must be completed through an Acceptance Test Technician Certification Provider (ATTCP).	
Building Component	Form/Title & System Name(s)
Envelope	NRCA-ENV-02-F - NRFC label verification for fenestration
Envelope	NRCA-ENV-03-F. - Daylighting Design PAFs
Mechanical	NRCA-MCH-03-A - Constant Volume Single Zone HVAC
	VFC-1 / 1.5 and VFC-2.
Mechanical	NRCA-MCH-19-A Occupancy Sensor Controls
	VFC-1 / 1.5 and VFC-2.
Mechanical	NRCA-MCH-20-A Multifamily Ventilation
	TEF-1_50 and TEF-1_60.
Mechanical	NRCA-MCH-21-A Multifamily Envelope
	Dwelling Units

N. DECLARATION OF REQUIRED CERTIFICATES OF VERIFICATION	
Selections made by Documentation Author indicate which Certificates of Verification must be submitted for the features to be recognized for compliance. These documents must be retained and provided to the building inspector during construction and can be found online	
Building Component	Form/Title
Mechanical	NRCV-MCH-24 Enclosure Air Leakage
Mechanical	NRCV-MCH-27 Indoor Air Quality & Mechanical Ventilation
Mechanical	NRCV-MCH-32 Local Mechanical Exhaust

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD	NRCC-PRF-E
Nonresidential Performance Compliance Method	(Page 43 of 43)

Documentation Author's Declaration Statement

1. I certify that this Certificate of Compliance documentation is accurate and complete.	
Documentation Author Name:	Documentation Author Signature:
Company:	Signature Date:
Address:	CEA/HERS Certification Identification (if applicable):
City/State/Zip: ,	Phone:

Responsible Person's Declaration statement

I certify the following under penalty of perjury, under the laws of the State of California:		
1. The information provided on this Certificate of Compliance is true and correct. 2. I am eligible under Division 3 of the Business and Professions Code to accept responsibility for the building design or system design identified on this Certificate of Compliance (responsible designer) 3. The energy features and performance specifications, materials, components, and manufactured devices for the building design or system design identified on this Certificate of Compliance conform to the requirements of Title 24, Part 1 and Part 6 of the California Code of Regulations. 4. The building design features or system design features identified on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application. 5. I understand that a registered copy of this Certificate of Compliance shall be made available with the building permit(s) issued for the building, and made available to the enforcement agency for all applicable inspections, and I will take the necessary steps to accomplish this requirement. 6. I understand that a registered copy of this Certificate of Compliance is required to be included with the documentation the builder provides to the building owner at occupancy, and I will take the necessary steps to accomplish these requirements.		
Responsible Designer Name:	Responsible Designer Signature:	
Company:		
Address:	Date Signed:	
City/State/Zip: ,	License #:	
Phone:	Title:	Scope: