



vertica-ml-python1.0 Documentation

Flexible as Python, Fast and Scalable as Vertica

Ouali Badr

March 30, 2020

Executive Summary

This documentation explains the `vertica-ml-python` API by detailing all the functions and by providing significant examples to each one. It allows the user to use his Vertica Database with Python without loading the data in his personal machine first. All the functions execute requests directly in the database in order to gain in efficiency. It combines Vertica aggregations and Python flexibility to create objects similar to the ones available in `pandas` and `sklearn` with the power of a columnar oriented analytic database: Vertica.


`vertica-ml-python` allows users to use the `vDataframe` (Virtual Dataframe). This object keeps in memory all the users modifications in order to use optimised SQL queries to compute all the necessary aggregations. Thanks to this object, the initial relation is intact and will never be modified. The purpose is to explore, preprocess and clean the object without changing the initial relation.

What contains `vertica-ml-python`?

This API contains many functions for:

- Data Exploration, Preprocessing and Cleaning: `vertica_ml_python.vdataframe`
- Machine Learning (Regression, Classification, Clustering): `vertica_ml_python.learn`

`vertica-ml-python` helps to explore, preprocess and clean the data without changing the initial relation. It uses scalable Machine Learning Algorithms such as Logistic Regression, Random Forest, SVM and much more... It allows also to evaluate and to optimise models (Classification/Regression Reports, ROC/PRC curves, Parameters tuning...).



Contents

1 About	11
2 Features	12
3 Quick Start	13
4 Prerequisites	16
4.1 Python Version	16
4.2 Standard Libraries	16
4.3 Installation	16
4.4 Connection to the Database	17
4.4.1 ODBC	17
4.4.2 JDBC	18
5 Jupyter	18
6 Comparison between vertica-ml-python and pandas + scikit	19
6.1 Limitations	19
6.1.1 vertica-ml-python	19
6.1.2 pandas + scikit	19
6.2 Time to load the data	19
6.2.1 vertica-ml-python	19
6.2.2 pandas + scikit	20
6.3 Object Size	20
6.3.1 vertica-ml-python	20
6.3.2 pandas	20
6.4 Time to execute some queries	21
6.4.1 vertica-ml-python	21
6.4.2 pandas	22
6.5 Conclusion	24
7 vertica_ml_python.utilities	24
7.1 Functions	24
7.1.1 drop_model	24
7.1.2 drop_table	24
7.1.3 drop_text_index	25
7.1.4 drop_view	25
7.1.5 load_model	25

7.1.6	pandas_to_vertica	26
7.1.7	read_csv	26
7.1.8	read_json	28
7.1.9	read_vdf	29
7.1.10	to_tablesample	30
7.1.11	vertica_cursor	31
7.1.12	vdf_from_relation	31
7.2	tablesample	32
7.2.1	initialization	32
7.2.2	attributes	32
7.2.3	methods	32
8	vertica_ml_python.vdataframe	33
8.1	Virtual Dataframe	33
8.1.1	why Virtual Dataframe ?	35
8.1.2	initialization	35
8.1.3	attributes	36
8.1.4	methods	36
8.1.4.1	abs	36
8.1.4.2	aggregate / agg	37
8.1.4.3	all	37
8.1.4.4	any	38
8.1.4.5	append	39
8.1.4.6	apply	40
8.1.4.7	applymap	41
8.1.4.8	asfreq	42
8.1.4.9	astype	43
8.1.4.10	at_time	44
8.1.4.11	avg / mean	45
8.1.4.12	bar	45
8.1.4.13	beta	47
8.1.4.14	between_time	48
8.1.4.15	bool_to_int	49
8.1.4.16	boxplot	49
8.1.4.17	catcol	50
8.1.4.18	copy	51
8.1.4.19	corr	51
8.1.4.20	cov	52

8.1.4.21 count	53
8.1.4.22 cummax	54
8.1.4.23 cummin	55
8.1.4.24 cumprod	56
8.1.4.25 cumsum	57
8.1.4.26 current_relation	58
8.1.4.27 datecol	59
8.1.4.28 describe	59
8.1.4.29 drop	61
8.1.4.30 drop_duplicates	62
8.1.4.31 dropna	63
8.1.4.32 dsn_restart	64
8.1.4.33 dtypes	64
8.1.4.34 duplicated	65
8.1.4.35 empty	65
8.1.4.36 eval	66
8.1.4.37 expected_store_usage	66
8.1.4.38 fillna	67
8.1.4.39 filter	68
8.1.4.40 first	69
8.1.4.41 get_columns	70
8.1.4.42 get_dummies	70
8.1.4.43 groupby	72
8.1.4.44 head	72
8.1.4.45 help	73
8.1.4.46 hexbin	74
8.1.4.47 hist	75
8.1.4.48 info	77
8.1.4.49 isin	78
8.1.4.50 join	79
8.1.4.51 kurtosis / kurt	80
8.1.4.52 last	81
8.1.4.53 load	82
8.1.4.54 mad	83
8.1.4.55 mae	84
8.1.4.56 max	84
8.1.4.57 median	85
8.1.4.58 memory_usage	86

8.1.4.59 min	86
8.1.4.60 normalize	87
8.1.4.61 numcol	88
8.1.4.62 outliers	88
8.1.4.63 pivot_table	90
8.1.4.64 plot	92
8.1.4.65 product / prod	94
8.1.4.66 quantile	94
8.1.4.67 rank	95
8.1.4.68 rolling	96
8.1.4.69 sample	98
8.1.4.70 save	98
8.1.4.71 scatter	100
8.1.4.72 scatter_matrix	101
8.1.4.73 select	102
8.1.4.74 sem	103
8.1.4.75 sessionize	104
8.1.4.76 set_cursor	105
8.1.4.77 set_dsn	105
8.1.4.78 shape	106
8.1.4.79 skewness / skew	106
8.1.4.80 sort	107
8.1.4.81 sql_on_off	107
8.1.4.82 statistics	108
8.1.4.83 std	109
8.1.4.84 sum	110
8.1.4.85 tail	111
8.1.4.86 time_on_off	111
8.1.4.87 to_csv	112
8.1.4.88 to_db	113
8.1.4.89 to_pandas	114
8.1.4.90 to_vdf	114
8.1.4.91 var	115
8.1.4.92 version	115
8.2 Virtual Column	116
8.2.1 attributes	116
8.2.2 methods	116
8.2.2.1 abs	116

8.2.2.2	add	117
8.2.2.3	add_copy	118
8.2.2.4	add_prefix	119
8.2.2.5	add_suffix	120
8.2.2.6	aggregate / agg	121
8.2.2.7	apply	121
8.2.2.8	astype	122
8.2.2.9	avg / mean	123
8.2.2.10	bar	123
8.2.2.11	boxplot	124
8.2.2.12	category	126
8.2.2.13	clip	126
8.2.2.14	count	127
8.2.2.15	date_part	128
8.2.2.16	decode	129
8.2.2.17	density	130
8.2.2.18	describe	131
8.2.2.19	discretize	132
8.2.2.20	distinct	134
8.2.2.21	divide / div	134
8.2.2.22	donut	135
8.2.2.23	drop	136
8.2.2.24	dropna	137
8.2.2.25	drop_outliers	138
8.2.2.26	dtype	139
8.2.2.27	ema	139
8.2.2.28	equals / eq	140
8.2.2.29	fillna	141
8.2.2.30	fill_outliers	143
8.2.2.31	ge	144
8.2.2.32	get_dummies	145
8.2.2.33	gt	146
8.2.2.34	head	147
8.2.2.35	hist	148
8.2.2.36	isdate	149
8.2.2.37	isin	149
8.2.2.38	isnum	150
8.2.2.39	kurtosis / kurt	150

8.2.2.40 label_encode	151
8.2.2.41 le	151
8.2.2.42 lt	152
8.2.2.43 mad	153
8.2.2.44 mae	154
8.2.2.45 max	154
8.2.2.46 mean_encode	154
8.2.2.47 median	155
8.2.2.48 min	156
8.2.2.49 mod	156
8.2.2.50 mode	157
8.2.2.51 mul	157
8.2.2.52 neq	158
8.2.2.53 next	159
8.2.2.54 nlargest	160
8.2.2.55 normalize	161
8.2.2.56 nsmallest	161
8.2.2.57 numh	162
8.2.2.58 nunique	163
8.2.2.59 pct_change	163
8.2.2.60 pie	164
8.2.2.61 plot	165
8.2.2.62 pow	168
8.2.2.63 prev	168
8.2.2.64 product / prod	169
8.2.2.65 quantile	170
8.2.2.66 rename	170
8.2.2.67 round	171
8.2.2.68 sem	172
8.2.2.69 skewness / skew	172
8.2.2.70 slice	173
8.2.2.71 std	174
8.2.2.72 str_contains	174
8.2.2.73 str_count	175
8.2.2.74 str_extract	176
8.2.2.75 str_replace	177
8.2.2.76 str_slice	178
8.2.2.77 sub	179

8.2.2.78	sum	180
8.2.2.79	tail	180
8.2.2.80	topk	181
8.2.2.81	to_timestamp	182
8.2.2.82	value_counts	182
8.2.2.83	var	183
9	vertica_ml_python.learn	183
9.1	vertica_ml_python.learn.cluster	184
9.1.1	DBSCAN	184
9.1.2	KMeans	186
9.2	vertica_ml_python.learn.datasets	188
9.2.1	load_amazon	188
9.2.2	load_iris	188
9.2.3	load_smart_meters	189
9.2.4	load_titanic	189
9.2.5	load_winequality	189
9.3	vertica_ml_python.learn.decomposition	189
9.3.1	PCA	189
9.3.2	SVD	191
9.4	vertica_ml_python.learn.ensemble	193
9.4.1	RandomForestClassifier	193
9.4.2	RandomForestRegressor	196
9.5	vertica_ml_python.learn.linear_model	199
9.5.1	LinearRegression	199
9.5.2	ElasticNet	199
9.5.3	Lasso	202
9.5.4	LogisticRegression	202
9.5.5	Ridge	206
9.6	vertica_ml_python.learn.metrics	206
9.6.1	Regression	206
9.6.1.1	explained_variance	206
9.6.1.2	max_error	207
9.6.1.3	median_absolute_error	207
9.6.1.4	mean_absolute_error	207
9.6.1.5	mean_squared_error	207
9.6.1.6	mean_squared_log_error	207
9.6.1.7	regression_report	208

9.6.1.8	r2_score	208
9.6.2	Classification	208
9.6.2.1	accuracy_score	208
9.6.2.2	auc	208
9.6.2.3	classification_report	209
9.6.2.4	confusion_matrix	209
9.6.2.5	critical_success_index	209
9.6.2.6	f1_score	210
9.6.2.7	informedness	210
9.6.2.8	log_loss	210
9.6.2.9	markedness	210
9.6.2.10	matthews_corrcoef	211
9.6.2.11	multilabel_confusion_matrix	211
9.6.2.12	negative_predictive_score	211
9.6.2.13	prc_auc	211
9.6.2.14	precision_score	212
9.6.2.15	recall_score	212
9.6.2.16	specificity_score	212
9.7	vertica_ml_python.learn.model_selection	212
9.7.1	best_k	212
9.7.2	cross_validate	213
9.7.3	train_test_split	215
9.8	vertica_ml_python.learn.naive_bayes	216
9.8.1	MultinomialNB	216
9.9	vertica_ml_python.learn.neighbors	218
9.9.1	KNeighborsClassifier	218
9.9.2	KNeighborsRegressor	220
9.9.3	NearestCentroid	221
9.9.4	LocalOutlierFactor	223
9.10	vertica_ml_python.learn.plot	225
9.10.1	elbow	225
9.10.2	lift_chart	227
9.10.3	prc_curve	227
9.10.4	roc_curve	228
9.11	vertica_ml_python.learn.preprocessing	228
9.11.1	Balance	228
9.11.2	CountVectorizer	229
9.11.3	Normalizer	231

9.11.4 OneHotEncoder	232
9.12 vertica_ml_python.learn.svm	234
9.12.1 LinearSVC	234
9.12.2 LinearSVR	237
9.13 vertica_ml_python.learn.tree	239
9.13.1 DecisionTreeClassifier	239
9.13.2 DecisionTreeRegressor	240
9.13.3 DummyTreeClassifier	240
9.13.4 DummyTreeRegressor	240
10 Contact	240
11 License	240



"Science knows no country, because knowledge belongs to humanity, and is the torch which illuminates the world."

Louis Pasteur

1 About

Nowadays, the 'Big Data' (Tb of data) is now one of the main topics in the Data Science World. Data Scientists are now very important for any organisation. Becoming Data-Driven is mandatory to survive. Vertica is the first real analytic columnar Database and is still the fastest in the market. However, SQL is not enough flexible to be very popular for Data Scientists. Python flexibility is priceless and provides to any user a very nice experience. The level of abstraction is so high that it is enough to think about a function to notice that it already exists. Many Data Science APIs were created during the last 15 years and were directly adopted by the Data Science community (examples: pandas and scikit-learn). However, Python is only working in-memory for a single node process. Even if some famous highly distributed programming languages exist to face this challenge, they are still in-memory and most of the time they can not process on all the data. Besides, moving the data can become very expensive. Data Scientists must also find a way to deploy their data preparation and their models. We are far away from easiness and the entire process can become time expensive.


The idea behind VERTICA ML PYTHON is simple: Combining the Scalability of VERTICA with the Flexibility of Python to give to the community what they need *Bringing the logic to the data and not the opposite*. This version 1.0 is the work of 3 years of new ideas and improvement. I couldn't have my current skills at the beginning of my journey in the Database World. I needed time and great managers to successfully release this version. I want to thank:

- Yassine Faihe for hiring me as intern to start this project. He is a very pragmatic element who exactly knows in advance if we are following the correct roadmap. Without him, this project would have never seen the light.
- Fouad Teban who is the biggest project supporter. He always trusted the project and provided me many customers to help me on the testing.
- Eugenia Moreno who is a great manager and who knows how to efficiently support my ideas and how to guide me to the correct opportunities.


Badr Ouali - Author of the VERTICA ML PYTHON API

2 Features


Vertica ML Python is the perfect combination between Vertica and Python. It uses Vertica Scalability and Python Flexibility to help any Data Scientist achieving his goals by bringing the logic to the data and not the opposite. With VERTICA ML PYTHON, start your journey with easy Data Exploration.



Find patterns that you don't know and Detect Anomalies.



Prepare your data easily and build a model with Highly Scalable Vertica ML. Evaluate your model and try to create the most efficient and performant one.



Everything will happen in one place and where it should be: your Database. Without modifying anything but using the speed of Vertica to aggregate the data.

3 Quick Start

Install the library using the pip command:

```
root@ubuntu:~$ pip3 install vertica_ml_python
```

Install `vertica_python` or `pyodbc` to build a DB cursor:

```
root@ubuntu:~$ pip3 install vertica_python
```

Create a vertica cursor

```
from vertica_ml_python.utilities import vertica_cursor
cur = vertica_cursor("VerticaDSN")
```

Create the Virtual Dataframe of your relation:

```
from vertica_ml_python import vDataframe
vdf = vDataframe("my_relation", cursor = cur)
```

If you don't have data to play, you can easily load well known datasets

```

1 from vertica_ml_python.learn.datasets import load_titanic
2 vdf = load_titanic(cursor = cur)

```

You can now play with the data...

```

1 vdf.describe()
2
3 # Output
4
5      min      25%      50%      75%  \
6 age      0.33     21.0     28.0     39.0  \
7 body      1.0     79.25    160.5    257.5  \
8 fare      0.0     7.8958   14.4542   31.3875  \
9 parch      0.0      0.0      0.0      0.0  \
10 pclass     1.0      1.0      3.0      3.0  \
11 sibsp      0.0      0.0      0.0      1.0  \
12 survived   0.0      0.0      0.0      1.0  \
13
14      max      unique
15 age      80.0         96
16 body     328.0        118
17 fare    512.3292        277
18 parch      9.0         8
19 pclass      3.0         3
20 sibsp      8.0         7
21 survived   1.0         2

```

You can also print the SQL code generation using the `sql_on_off` method.

```

1 vdf.sql_on_off()
2 vdf.describe()
3
4 # Output
5 $ Compute the descriptive statistics of all the numerical columns $
6
7 SELECT SUMMARIZE_NUMCOL("age","body","survived","pclass","parch","fare","sibsp
8      ") OVER ()
9 FROM
10 (SELECT "age" AS "age",
11        "body" AS "body",
12        "survived" AS "survived",
13        "ticket" AS "ticket",
14        "home.dest" AS "home.dest",
15        "cabin" AS "cabin",
16        "sex" AS "sex",
17        "pclass" AS "pclass",
18        "embarked" AS "embarked",
19        "parch" AS "parch",
20        "fare" AS "fare",

```

```

    "name" AS "name",
    "boat" AS "boat",
    "sibsp" AS "sibsp"
FROM public.titanic) final_table

```

With Vertica ML Python, it is now possible to solve a ML problem with four lines of code (two if we don't consider the libraries loading).

```

1 from vertica_ml_python.learn.model_selection import cross_validate
2 from vertica_ml_python.learn.linear_model import RandomForestClassifier
3
4 # Data Preparation
5 vdf["sex"].label_encode()["boat"].fillna(method = "0ifnull")["name"].
    str_extract(' ([A-Za-z]+)\.').eval("family_size", expr = "parch + sibsp +
    1").drop(columns = ["cabin", "body", "ticket", "home.dest"])["fare"].
    fill_outliers().fillna().to_db("titanic_clean")
6
7 # Model Evaluation
8 cross_validate(RandomForestClassifier("rf_titanic", cur, max_leaf_nodes = 100,
    n_estimators = 30), "titanic_clean", ["age", "family_size", "sex", "
    pclass", "fare", "boat"], "survived", cutoff = 0.35)
9
10 # Output
11
12         auc                prc_auc      \
1-fold      0.9877114427860691    0.9530465915039339  \
13 2-fold      0.9965555014605642    0.7676485351425721  \
14 3-fold      0.9927239216549301    0.6419135521132449  \
15 avg          0.992330288634          0.787536226253  \
16 std          0.00362128464093    0.12779562393  \
17
18         accuracy          log_loss      \
1-fold      0.971291866028708    0.0502052541223871  \
19 2-fold      0.983253588516746    0.0298167751798457  \
20 3-fold      0.964824120603015    0.0392745694400433  \
21 avg          0.973123191716          0.0397655329141  \
22 std          0.0076344236729    0.00833079837099  \
23
24         precision          recall      \
1-fold          0.96                0.96  \
25 2-fold      0.9556962025316456          1.0  \
26 3-fold      0.9647887323943662    0.9383561643835616  \
27 avg          0.960161644975          0.966118721461  \
28 std          0.00371376912311    0.025535200301  \
29
30         f1-score                mcc      \
1-fold      0.9687259282082884    0.9376119402985075  \
31 2-fold      0.9867172675521821    0.9646971010878469  \
32 3-fold      0.9588020287309097    0.9240569687684576  \
33 avg          0.97141507483          0.942122003385  \
34 std          0.0115538960753    0.0168949813163  \
35
36         informedness          markedness      \

```


	1-fold	0.9376119402985075	0.9376119402985075	\\
37	2-fold	0.9737827715355807	0.9556962025316456	\\
	3-fold	0.9185148945422918	0.9296324823943662	\\
39	avg	0.943303202125	0.940980208408	\\
	std	0.0229190954261	0.0109037699717	\\
41	csi			
	1-fold	0.9230769230769231		
43	2-fold	0.9556962025316456		
	3-fold	0.9072847682119205		
45	avg	0.928685964607		
	std	0.0201579224026		

Happy Playing !

4 Prerequisites

4.1 Python Version

vertica-ml-python works with at least:

- **Vertica:** => 9.1 (with previous versions, some functions and algorithms may not be available)
- **Python:** => 3.6 - [version 3.5 may works]
- **Python Modules needed for Rendering Capabilities:** matplotlib (=> 3.0) - [other versions of matplotlib may work], numpy (=> 1.9) - [other versions of numpy may work]
- **Other Python Modules:** Except to get rendering capabilities, VERTICA ML Python uses only built-in libraries (statistics, random, math, time and os)

4.2 Standard Libraries

vertica-ml-python library is only using the standard Python libraries such as matplotlib, numpy... Other libraries can be used as anytree for tree visualization or sqlparse for SQL indentation but they are optional.

4.3 Installation

To install vertica-ml-python, you can use the pip command:

```
root@ubuntu:~$ pip3 install vertica_ml_python
```

Or you can get a copy of the source by cloning from the Vertica-ML-Python github project and install with:

```
root@ubuntu:~$ python3 setup.py install
```

You can also drag and drop the vertica_ml_python folder in the site-package folder of the Python framework. In the MAC environment, you can find it in:

/Library/Frameworks/Python.framework/Versions/3.6/lib/python3.6/site-packages

Another way is to call the library from where it is located.

You can then import each library element using the usual Python syntax.

```
1 # to import the vDataframe
  from vertica_ml_python import vDataframe
3 # to import the Logistic Regression
  from vertica_ml_python.learn.linear_model import LogisticRegression
```

Everything is well detailed in the following documentation.

4.4 Connection to the Database

This step is useless if `vertica-python` or `pyodbc` is already installed and you have a DSN in your machine. With this configuration, you do not need to manually create a cursor. It is possible to create a `vDataframe` using directly the DSN (`dsn` parameter of the `vDataframe`).

4.4.1 ODBC

To connect to the database, the user can use an ODBC connection to the Vertica database. `vertica-python` and `pyodbc` provide a cursor that will point to the database. It will be used by the `vertica-ml-python` to create all the different objects.

```
#
2 # vertica_python
  #
4 import vertica_python

6 # Connection using all the DSN information
conn_info = {'host': "10.211.55.14", 'port': 5433, 'user': "dbadmin", '
            password': "XxX", 'database': "testdb"}
8 cur = vertica_python.connect(** conn_info).cursor()

10 # Connection using directly the DSN
    from vertica_ml_python.utilities import to_vertica_python_format # This
        function will parse the odbc.ini file
12 dsn = "VerticaDSN"
    cur = vertica_python.connect(** to_vertica_python_format(dsn)).cursor()
14
  #
16 # pyodbc
  #
18 import pyodbc

20 # Connection using all the DSN information
driver = "/Library/Vertica/ODBC/lib/libverticaodbc.dylib"
22 server = "10.211.55.14"
    database = "testdb"
```

```

24 port = "5433"
    uid = "dbadmin"
26 pwd = "XxX"
    dsn = ("DRIVER={}; SERVER={}; DATABASE={}; PORT={}; UID={}; PWD={};").format(
        driver, server, database, port, uid, pwd)
28 cur = pyodbc.connect(dsn).cursor()

30 # Connection using directly the DSN
    dsn = ("DSN=VerticaDSN")
32 cur = pyodbc.connect(dsn).cursor()

```

4.4.2 JDBC

The user can also use a JDBC connection to the Vertica Database.

```

import jaydebeapi

2 # Vertica Server Details
4 database = "testdb"
    hostname = "10.211.55.14"
6 port = "5433"
    uid = "dbadmin"
8 pwd = "XxX"


10 # Vertica JDBC class name
    jdbc_driver_name = "com.vertica.jdbc.Driver"
12
14 # Vertica JDBC driver path
    jdbc_driver_loc = "/Library/Vertica/JDBC/vertica-jdbc-9.3.1-0.jar"

16 # JDBC connection string
    connection_string = 'jdbc:vertica://' + hostname + ':' + port + '/' + database
18 url = '{}:user={};password={}'.format(connection_string, uid, pwd)
    conn = jaydebeapi.connect(jdbc_driver_name, connection_string, {'user': uid, '
        password': pwd}, jars = jdbc_driver_loc)
20 cur = conn.cursor()

```

5 Jupyter

Jupyter offers a really beautiful interface to use vertica-ml-python.



Besides a lot of guided notebooks will be available in order to understand the library.

6 Comparison between vertica-ml-python and pandas + scikit

All the results of this section are obtained using a single node machine (to have a real comparison) with 128Gb of memory.

6.1 Limitations

6.1.1 vertica-ml-python

vertica-ml-python has no limitation as it uses Vertica to compute all the aggregations it needs. If we want to increase the speed, we can increase the number of nodes or do query tuning by building the appropriate projections.

6.1.2 pandas + scikit

pandas and scikit have real limitations. They both need to load data in memory and we can not increase it indefinitely.

6.2 Time to load the data

6.2.1 vertica-ml-python

If the data is inside a Vertica database, no operation is needed. In the other cases, we need to transfer the data to Vertica. As we are trying to solve the main 'Big Data' issues, the purpose of this library is to avoid moving the data and to bring the logic to the data (not the opposite). It is highly recommended to already have the data in Vertica (even if the time to create the table is still lower than the one to create the pandas.DataFrame).

6.2.2 pandas + scikit

The data must be loaded in memory. It can take a lot of time depending on where the data is. To give a first idea, you can see the following result.

```
# Using 35M of rows (the whole dataset) - Less than 4Gb
2 start_time = time.time()
  expedia_df = pandas.read_sql("SELECT * FROM expedia_train", conn)
4 print(time.time() - start_time)

6 # Output
  1135.22843092306093

8 # Using 10M of rows - Less than 1Gb
10 start_time = time.time()
   expedia_df = pandas.read_sql("SELECT * FROM expedia_train LIMIT 10000000",
   conn)
12 print(time.time() - start_time)

14 # Output
   281.51524472236633

16 # Using 1M of rows - Less than 100Mb
18 start_time = time.time()
   expedia_df = pandas.read_sql("SELECT * FROM expedia_train LIMIT 1000000", conn)
20 print(time.time() - start_time)

22 # Output
   42.53745484352112
```

We can notice the complexity of in-memory processing when reaching Big Data. Besides, the limitation is the power of the single-node machine you are using.

6.3 Object Size

6.3.1 vertica-ml-python

The size of a vDataFrame will never exceed some kilo bytes.

```
1 print(expedia.memory_usage())

3 # Output
  5566
```

6.3.2 pandas

The size of a pandas.DataFrame will be proportional to the dataset volume.

```
print(sys.getsizeof(expedia_df))
```

```
2  
# Output  
4 10846031144
```

More than a GB of memory is used. We can imagine the impact in our personal machine. If the user wants to use `pandas.DataFrame` on very huge dataset, he needs a very powerful machine. Knowing that it is hard to have today a personal machine exceeding 32GB of RAM, the limitation is obvious. These in-memory libraries can only process small datasets (less than 10GB) which is not nowadays 'Big Data' (we can consider the 'Big Data' border as 1TB).

6.4 Time to execute some queries

6.4.1 vertica-ml-python

Let's start with `vertica-ml-python`:

```
# Using 35M of rows (the whole dataset)  
2 #  
# describe  
4 #  
start_time = time.time()  
6 expedia.describe()  
print(time.time() - start_time)  
8  
# Output  
10 94.45896601676941  
12 #  
# categorical hist  
14 #  
start_time = time.time()  
16 expedia["is_mobile"].hist()  
print(time.time() - start_time)  
18  
# Output  
20 0.480072021484375  
22 # Using 10M of rows  
#  
24 # describe  
#  
26 start_time=time.time()  
expedia.describe()  
28 print(time.time() - start_time)  
30 # Output  
28.198142528533936  
32 #
```

```
34 # categorical hist
35 #
36 start_time = time.time()
37 expedia["is_mobile"].hist()
38 print(time.time() - start_time)
39
40 # Output
41 0.4742517471313477
42
43 # Using 1M of rows
44 #
45 # describe
46 #
47 start_time = time.time()
48 expedia.describe()
49 print(time.time() - start_time)
50
51 # Output
52 2.8560750484466553
53
54 #
55 # categorical hist
56 #
57 start_time = time.time()
58 expedia["is_mobile"].hist()
59 print(time.time() - start_time)
60
61 # Output
62 0.3278229236602783
```

6.4.2 pandas

And now pandas:

```
# Using 35M of rows (the whole dataset)
2 #
3 # describe
4 #
5 start_time = time.time()
6 expedia_df.describe()
7 print(time.time() - start_time)
8
9 # Output
10 75.72856092453003
11
12 #
13 # categorical hist
```

```
14 #
    start_time = time.time()
16 expedia_df["is_mobile"].hist()
    print(time.time() - start_time)
18
    # Output
20 3.210484266281128
22
    # Using 10M of rows
    #
24 # describe
    #
26 start_time = time.time()
    expedia_df.describe()
28 print(time.time() - start_time)
30
    # Output
    20.789332389831543
32
    #
34 # categorical hist
    #
36 start_time = time.time()
    expedia_df["is_mobile"].hist()
38 print(time.time() - start_time)
40
    # Output
    0.36867237091064453
42
    # Using 1M of rows
    #
44 # describe
    #
46 #
    start_time = time.time()
48 expedia_df.describe()
    print(time.time() - start_time)
50
    # Output
52 1.2540433406829834
54
    #
    # categorical hist
    #
56 #
    start_time = time.time()
58 expedia_df["is_mobile"].hist()
    print(time.time() - start_time)
60
```



```
# Output
0.08945250511169434
```

6.5 Conclusion

At the end, we have more or less the same execution time with a little advantage to `pandas` for some functions. However, do not forget that `pandas` is in-memory processing. At the end, `vertica-ml-python` is more robust and offers more possibilities by processing the data directly where they live. Besides some functions to prepare the data will be time consuming using `pandas` whereas it will be very fast for `vertica-ml-python` as only the grammar of the different transformations is kept in memory. If the projections are correctly made, we could reduce drastically the processing time. We can also reduce the processing time by increasing the number of nodes. `vertica-ml-python` uses the Python flexibility and Vertica Scalability to help any Python user to follow the entire Data Science cycle without moving the data.

7 `vertica_ml_python.utilities`

Some functions were created to simplify the process. The object `tablesample` stores in memory a small quantity of data which correspond most of the time to a query result. These utilities functions and objects are very important to understand all the `vertica-ml-python` API. They can help also to the process of reading and loading files.

7.1 Functions

7.1.1 `drop_model`

```
def drop_model(name: str, cursor)
```

Drop the Vertica model.

Parameters

- **name:** `<str>`
Name of the model.
- **cursor:** `<object>`
Database Cursor.

7.1.2 `drop_table`

```
def drop_table(name: str, cursor)
```

Drop the Vertica table.

Parameters

- **name:** `<str>`
Name of the table.
- **cursor:** `<object>`
Database Cursor.

7.1.3 drop_text_index

```
def drop_text_index(name: str, cursor)
```

Drop the Vertica text index.

Parameters

- **name:** *<str>*
Name of the text index.
- **cursor:** *<object>*
Database Cursor.

7.1.4 drop_view

```
def drop_view(name: str, cursor)
```

Drop the Vertica view.

Parameters

- **name:** *<str>*
Name of the view.
- **cursor:** *<object>*
Database Cursor.

7.1.5 load_model

```
def load_model(name: str, cursor, test_relation: str = "")
```

Returns the model object.

Parameters

- **name:** *<str>*
Model name.
- **cursor:** *<object>*
Database Cursor.
- **test_relation:** *<str>*, optional
Name of the relation used to test the model. If it is not defined, the test relation will be the same as the one used to train the model.

7.1.6 pandas_to_vertica

```
1 pandas_to_vertica(df, cur, name: str, schema: str = "public", insert: bool =  
    False)
```

Store a pandas DataFrame in the Vertica DB.

Parameters

- **df:** *<object>*
Pandas DataFrame.
- **cursor:** *<object>*
Database Cursor.
- **name:** *<str>*
Name of the table.
- **schema:** *<str>*
Schema of the table.
- **insert:** *<bool>*
Insert into the existing table rather than creating a new one.

7.1.7 read_csv

```
1 read_csv(  
    path: str,  
3    cursor,  
    schema: str = 'public',  
5    table_name: str = '',  
    delimiter: str = ',',  
7    header: bool = True,  
    header_names: list = [],  
9    null: str = '',  
    enclosed_by: str = '"',  
11   escape: str = '\\',  
    skip: int = 1,  
13   genSQL: bool = False,  
    parse_n_lines: int = -1,  
15   insert: bool = False)
```

Read a csv file and store it in the Vertica Database.

Parameters

- **path:** *<str>*
Path to the csv file.
- **cursor:** *<object>*
Database Cursor.

- **schema:** *<str>*, optional
Schema used to store the csv file.
- **table_name:** *<str>*, optional
Table name used to store the csv file.
- **delimiter:** *<str>*, optional
Delimiter used to parse the file.
- **header:** *<bool>*, optional
If set to true it will parse the first line of the csv file to extract the header.
- **header_names:** *<list>*, optional
List with the columns names. If this list has less elements than the csv file, it will generate automatically new names for the missing elements.
- **null:** *<str>*, optional
How the null elements are encoded.
- **enclosed_by:** *<str>*, optional
How the text elements are enclosed.
- **escape:** *<str>*, optional
How the escape is encoded.
- **genSQL:** *<bool>*, optional
Generate the SQL used to create the table.
- **parse_n_lines:** *<int>*, optional
The parser will only parse a limited number of lines to guess the types. This parameter must be used if the file volume is big.
- **insert:** *<bool>*, optional
Ingest the csv file in the corresponding table.

Returns

The Virtual Dataframe of the relation.

Example

```

1 from vertica_ml_python.vdataframe import read_csv
  titanic = read_csv('titanic.csv', cur)
3
4 # Output
5
6   cabin    sex  pclass  embarked  \\
7 0   C22 C26  female      1         S  \\
8 1   C22 C26   male      1         S  \\
9 2   C22 C26  female      1         S  \\
10 3    A36   male      1         S  \\
11 4   None   male      1         C  \\
12 ...    ...    ...    ...    ...  \\
13   parch    fare                                name  \\
14 0      2   151.55000                                Allison, Miss. Helen Loraine  \\
15 1      2   151.55000                Allison, Mr. Hudson Joshua Creighton  \\

```

```

15 2          2      151.55000 Allison, Mrs. Hudson J C (Bessie Wald...  \\
3          0          0.00000                                Andrews, Mr. Thomas Jr  \\
17 4          0      49.50420                                Artagaveytia, Mr. Ramon  \\
...      ...      ...                                ...  \\
19 Name: titanic, Number of rows: 1234, Number of columns: 14

```

7.1.8 read_json

```

1 def read_json(
    path: str,
3     cursor,
    schema: str = 'public',
5     table_name: str = '',
    usecols: list = [],
7     new_name: dict = {},
    insert: bool = False)

```

Read a json file and store it in the Vertica Database.

Parameters

- **path:** <str>
Path to the json file.
- **cursor:** <object>
Database Cursor.
- **schema:** <str>, optional
Schema used to store the json file.
- **table_name:** <str>, optional
Table name used to store the json file.
- **usecols:** <list>, optional
If this parameter is not empty, only the columns considered in the list will be ingested.
- **new_name:** <dict>, optional
During the process, it is possible to change the name of the variables in the json file.
- **insert:** <bool>, optional
Ingest the json file in the corresponding table.

Returns

The Virtual Dataframe of the relation.

Example

```

from vertica_ml_python.vdataframe import read_json
2 titanic = read_json('titanic.json', cur)

4 # Output
      cabin      sex  pclass  embarked  \\
6 0    C22 C26   female      1         S   \\
  1    C22 C26    male      1         S   \\
  2    C22 C26   female      1         S   \\
  3      A36    male      1         S   \\
10 4      None    male      1         C   \\
   ...      ...      ...      ...      ...   \\
12      parch      fare                                name  \\
  0         2    151.55000                      Allison, Miss. Helen Loraine  \\
14 1         2    151.55000                Allison, Mr. Hudson Joshua Creighton  \\
  2         2    151.55000  Allison, Mrs. Hudson J C (Bessie Wald...  \\
16 3         0      0.00000                Andrews, Mr. Thomas Jr  \\
  4         0    49.50420                Artagaveytia, Mr. Ramon  \\
18 ...      ...      ...                                ...  \\
Name: titanic, Number of rows: 1234, Number of columns: 14

```

7.1.9 read_vdf

```

1 read_vdf(path: str, cursor)

```

Read a vdf file and load the corresponding vDataFrame.

Parameters

- **path:** <str>
Path to the csv file.
- **cursor:** <object>
Database Cursor.

Returns

The Virtual Dataframe corresponding to the one described in the vdf file.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.to_vdf('titanic')
  from vertica_ml_python.vdataframe import read_vdf
5 titanic = read_vdf('titanic.vdf', cur)

```

```

7 # Output
    cabin      sex      pclass      embarked  \\
9 0    C22 C26   female        1          S   \\
1 1    C22 C26    male        1          S   \\
11 2    C22 C26   female        1          S   \\
3 3      A36    male        1          S   \\
13 4     None    male        1          C   \\
    ...      ...      ...      ...      ...   \\
15   parch      fare                                name  \\
0     2    151.55000                                Allison, Miss. Helen Loraine  \\
17 1     2    151.55000                        Allison, Mr. Hudson Joshua Creighton  \\
2 2     2    151.55000      Allison, Mrs. Hudson J C (Bessie Wald...  \\
19 3     0     0.00000                                Andrews, Mr. Thomas Jr  \\
4 4     0    49.50420                        Artagaveytia, Mr. Ramon  \\
21 ...      ...      ...      ...      ...  \\
Name: titanic, Number of rows: 1234, Number of columns: 14

```

7.1.10 to_tablesample

```
to_tablesample(query: str, cursor, name = "Sample")
```

Returns the tablesample of the query.

Parameters

- **query:** <str>
SQL query.
- **cursor:** <object>
Database Cursor.
- **name:** <str>, optional
Name of the tablesample.

```

1 from vertica_ml_python.utilities import to_tablesample
2 to_tablesample('SELECT age, survived FROM titanic LIMIT 5', cur)
3
4 #Output
5   age      survived
6 0    2.000          0
7 1   30.000          0
8 2   25.000          0
9 3   39.000          0
10 4   71.000          0
11 Name: Sample, Number of rows: 5, Number of columns: 2

```

7.1.11 vertica_cursor

```
1 vertica_cursor(dsn: str)
```

Returns the Vertica cursor by parsing the DSN (this function will read the ODBCINI file).

Parameters

- **dsn:** <str>
Database DSN.

```
1 from vertica_ml_python.utilities import vertica_cursor
2 vertica_cursor("VerticaDSN").execute("SELECT age FROM titanic LIMIT 1").
3     fetchall()
4
5 #Output
6 [[Decimal('2.000')]]
```

7.1.12 vdf_from_relation

```
1 vdf_from_relation(
2     relation: str,
3     name: str = "VDF",
4     cursor = None,
5     dsn: str = "",
6     schema: str = "")
```

Build a vDataframe using the defined relation.

Parameters

- **relation:** <str>
SQL Relation.
- **name:** <str>, optional
Name of the new vDataframe.
- **cursor:** <object>, optional
Database Cursor.
- **dsn:** <str>, optional
Database DSN.
- **schema:** <str>, optional
Schema of the relation. It will be used to compute Temporary tables.

Returns

The vDataframe of the input relation.

Example


```

from vertica_ml_python.vdataframe import vdf_from_relation
2 relation = "((SELECT 2 AS x, 1 AS y) UNION ALL (SELECT 10 AS x, 4 AS y) UNION
    ALL (SELECT 10 AS x, 5 AS y)) z"
vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
4
# Output
6      x      y
0       2      1
8      10      4
2      10      5
10 Name: VDF, Number of rows: 3, Number of columns: 2

```

7.2 tablesample

The tablesample is the transition from 'Big Data' to 'Small Data'. This object was created to have a nice way of displaying the results and to not have any dependency to any other library. It stores the aggregated result in memory and has some useful method to transform it to pandas.DataFrame or vDataFrame.

7.2.1 initialization

```

class tablesample(
2     values: dict = {}, # Dictionary of the stored columns
    dtype: dict = {}, # Dictionary of the columns types
4     name: str = "Sample") # Object Name

```

7.2.2 attributes

The tablesample has two main attributes:

- **values:** The Dictionary of the stored columns.
- **dtype:** The Dictionary of the columns types.

7.2.3 methods

The tablesample has 4 main methods:

- **transpose(self):** Transpose the tablesample.
- **to_pandas(self):** Convert the tablesample to a pandas.DataFrame.
- **to_sql(self):** Generate the sql to build the tablesample to the DB.
- **to_vdf(self, cursor = None, dsn: str = ""):** Convert the tablesample to a vDataFrame.

8 vertica_ml_python.vdataframe

8.1 Virtual Dataframe

The vDataframe is a Python object which will keep in mind all the user modifications in order to use an optimised SQL query. It will send the optimised SQL query to the database which will aggregate and return the final result. vDataframe will create for each column of the relation a vColumn (Virtual Column) which will store for each column its name and its transformations. Thus, vDataframe allows to do easy data preparation and exploration without modifying the data.

vColumn and vDataframe coexist and one can not live without the other. vColumn will use the vDataframe information and reciprocally. It is imperative to understand both structures to know how to use the entire object.

When the user imputes or filters the data, the vDataframe keeps all the transformations in memory to select for each query the needed data in the main relation. Let's try to understand thanks to an example.

```

# We create the vDataframe
2 titanic = vDataframe('titanic', dsn = 'VerticaDSN')

4 # We filter some values
titanic.filter("fare < 100")

6
84 elements were filtered

8
# We impute the column age
10 titanic["age"].fillna(method = "mean")

12
232 elements were filled

14 # We drop some missing values
titanic["fare"].dropna()

16

/!\ Warning: Nothing was dropped

18
# We encode the column embarked
20 titanic["embarked"].label_encode()

22 # We print all the queries used during the next executions
titanic.sql_on_off()

24
# We summarize our vDataframe
26 titanic.describe()

```

To compute the descriptives statistics, the following query was generated by our vDataframe:

```

1 SELECT SUMMARIZE_NUMCOL("age", "body", "passenger class", "embarked", "parch",
   "fare", "sibsp", "survived") OVER ()
FROM
3   (SELECT COALESCE("age", 29.6471459694989) AS "age",
   "body" AS "body",
5   "passenger class" AS "passenger class",
   "ticket" AS "ticket",

```

```

7      "cabin" AS "cabin",
      "sex" AS "sex",
9      "home.dest" AS "home.dest",
      DECODE("embarked", 'C', 0, 'Q', 1, 'S', 2, 3) AS "embarked",
11     "parch" AS "parch",
      "fare" AS "fare",
13     "name" AS "name",
      "boat" AS "boat",
15     "sibsp" AS "sibsp",
      "survived" AS "survived"
17 FROM
      (SELECT "age" AS "age",
19           "body" AS "body",
           "passenger class" AS "passenger class",
21          "ticket" AS "ticket",
           "cabin" AS "cabin",
23          "sex" AS "sex",
           "home.dest" AS "home.dest",
25          "embarked" AS "embarked",
           "parch" AS "parch",
27          "fare" AS "fare",
           "name" AS "name",
29          "boat" AS "boat",
           "sibsp" AS "sibsp",
31          "survived" AS "survived"
           FROM public.titanic) t1
33 WHERE fare < 100) final_table

```

The vDataFrame will try to keep in mind where the transformations occurred in order to use the appropriate query. In that case, when the user has done a lot of transformations, it is highly recommended to save the vDataFrame in the Database in order to gain in efficiency (using the `to_db` method). We can also see all the modifications using the `info` method.

```

1 titanic.info()
3 #Output
The vDataFrame was modified many times:
5 * {Fri Nov 22 18:06:10 2019} [Filter]: 84 elements were filtered using the
   filter 'fare < 100'
   * {Fri Nov 22 18:06:26 2019} [Fillna]: 232 missing values of the vColumn '"
   age"' were filled.
7 * {Fri Nov 22 18:06:54 2019} [Label Encoding]: Label Encoding was applied to
   the vColumn '"embarked"' using the following mapping:
   C => 0   Q => 1   S => 2

```

8.1.1 why Virtual Dataframe ?

As the vDataframe keeps in mind all the user actions, it can easily be recreated from scratch. Besides, if the connection to the database failed, it is easy to set a new database cursor using the `set_cursor` method or if the connection was made using a DSN the `dsn_restart` method. The Virtual Dataframe will never load data in-memory, all the aggregations are computed thanks to Vertica. The user feels like using pandas whereas the data is not stored in-memory but exactly where it should be (in the Database !).

8.1.2 initialization

```
class vDataframe (
2     input_relation: str, # The relation used to build the vDataframe
    cursor = None, # The DB cursor
4     dsn: str = "", # The DB DSN
    usecols: list = [], # Build the vDataframe using only specific columns
6     schema: str = "") # The relation schema
```

To instantiate a new Virtual Dataframe, the user can use a database cursor and the name of a relation (table or view).

```
from vertica_ml_python import vDataframe
2
vdf = vDataframe(relation, cur)
```

The simplest way is to use directly a DSN (without setting a cursor).

```
1 vdf = vDataframe(relation, dsn = "VerticaDSN")
```

Using this method, the Virtual Dataframe will keep in mind the DSN name and in case of connection failure, the user can restart a connection using the `dsn_restart` method.

Example

```
1 titanic = vDataframe("titanic", cursor)
3 #Output
   age      boat  body  cabin  embarked      fare  \\
5 0   None      1   None   None        S    26.00000  \\
1 1   None     10   None  E101        Q    12.35000  \\
7 2   None     10   None   None        S    16.10000  \\
3 3   None     11   None   None        S    33.00000  \\
9 4   None     13   None   None        Q     7.72080  \\
5 5   None     13   None   None        Q     7.73330  \\
11 ...      ...   ...   ...      ...      ...  \\
--More--
13 Name: titanic, Number of rows: 1234, Number of columns: 14
```

8.1.3 attributes

When the Virtual Dataframe is created, it will create as many Virtual Columns as there are columns in the input relation (`columns` attribute). It will keep in mind the cursor, the relation and the DSN if this connection method is used. It will also create 6 other attributes in order to keep in mind the user modifications.

- `order_by`: how to sort the data
- `where`: all the filters.
- `query_on`: print all the queries executed by the `vDataframe` in the terminal.
- `time_on`: print all the queries elapsed time in the terminal.
- `history`: all the user modifications.
- `saving`: all the user saving.

For example, when the user wants to create a new column in the Virtual Dataframe. It will create a new Virtual Column and it will add it in the list of Virtual Columns (`columns` attribute). If the user wants to delete a column, the Virtual Dataframe will simply delete it from the list of Virtual Columns. The initial relation is then never changed !

8.1.4 methods

8.1.4.1 abs

```
1 vDataframe.abs(self, columns: list = [])
```

Apply the Absolute function to the selected columns.

Parameters

- **columns**: *<list>*, optional
List of Columns. If this parameter is empty, the method will be applied to all the numerical columns.

Returns

The Virtual Dataframe itself.

Example

```
1 from vertica_ml_python.vdataframe import vdf_from_relation
2 relation = "((SELECT 1 AS x, -1 AS y) UNION ALL (SELECT -3 AS x, -4 AS y)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
4
5 #Output
6
7      x      y
8 0      1     -1
9 1     -3     -4
10
11 Name: VDF, Number of rows: 2, Number of columns: 2
12
13 vdf.abs()
```

```

13 #Output
      x      y
15 0      1      1
      1      3      4
17 Name: VDF, Number of rows: 2, Number of columns: 2

```

8.1.4.2 aggregate / agg

```
1 vDataframe.aggregate(self, func: list, columns: list = [])
```

Aggregate all the different columns.

Parameters

- **func:** *<list>*
List of the different aggregations.
- **columns:** *<list>*, optional
List of Columns. If this parameter is empty, all the columns will be aggregated.

Returns

The `tablesample` type containing the aggregations (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataframe` using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.agg(["sum", "min"])

5 #Output
      sum      min
7 "age"      30062.0      0.33
  "body"      19369.0      1.0
9 "passenger class"      2819.0      1.0
  "parch"      467.0      0.0
11 "fare"      41877.3576      0.0
  "sibsp"      622.0      0.0
13 "survived"      450.0      0.0

```

8.1.4.3 all

```
1 vDataframe.all(columns: list)
```

Aggregate the different columns by verifying if all the elements are True.

Parameters

- **columns:** *<list>*
List of the vDataframe Columns.

Returns

The `tablesample` type containing the aggregations (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```
1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT True AS x, False AS y) UNION ALL (SELECT True AS x, True
    AS y)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
   x      y
7 0  True  False
  1  True   True

9 vdf.all(['x', 'y'])

11 #Output
13      bool_and
14 "x"         1.0
15 "y"         0.0
```

8.1.4.4 any

```
1 vDataframe.any(columns: list)
```

Aggregate the different columns by verifying if at least one element is True.

Parameters

- **columns:** *<list>*
List of the vDataframe Columns.

Returns

The `tablesampl` type containing the aggregations (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataFrame` using the `to_vdf` method.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT True AS x, False AS y) UNION ALL (SELECT True AS x, True
    AS y)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
      x      y
7 0  True  False
  1  True   True

9 vdf.any(['x', 'y'])

11 #Output
      bool_or
13 "x"      1.0
15 "y"      1.0

```

8.1.4.5 append

```

1 vDataFrame.append(self, vdf = None, input_relation: str = "")

```

Merge the Virtual Dataframe with another one or an existing relation.

Parameters

- **vdf:** `<vDataFrame>`, optional
The Vertica Dataframe to merge with the current one.
- **input_relation:** `<str>`, optional
The input_relation to merge with the Virtual Dataframe.

Returns

The Virtual Dataframe itself.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation1 = "((SELECT 1 AS x, -1 AS y) UNION ALL (SELECT -3 AS x, -4 AS y)) z"
3 vdf1 = vdf_from_relation(relation1, dsn = "VerticaDSN")

```



```

5 #Output
      x      y
7 0      1     -1
  1     -3     -4
9 Name: VDF, Number of rows: 2, Number of columns: 2

11 relation2 = "((SELECT 9 AS x, -3 AS y) UNION ALL (SELECT -1 AS x, 2 AS y)) z"
   vdf2 = vdf_from_relation(relation2, dsn = "VerticaDSN")
13
   #Output
      x      y
15 0      9     -3
  1     -1      2
17 Name: VDF, Number of rows: 2, Number of columns: 2
19
   vdf1.append(vdf = vdf2)
21
   #Output
      x      y
23 0      1     -1
  1     -3     -4
25 2      9     -3
  3     -1      2
27 Name: VDF, Number of rows: 4, Number of columns: 2

```

8.1.4.6 apply

```
vDataframe.apply(self, func: dict)
```

Apply the input functions to the vDataframe columns.

Parameters

- **func:** <dict>
Dictionary of the different columns with the functions to apply. The function's variable must be written using flower brackets '{}' (Example: EXP({}))

Returns

The Virtual Dataframe itself.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
   relation = "((SELECT 1 AS x, 4 AS y) UNION ALL (SELECT 2 AS x, 9 AS y)) z"

```

```

3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
      x      y
7 0      1      4
  1      2      9
9 Name: VDF, Number of rows: 2, Number of columns: 2

11 vdf.apply({'x': 'EXP({})', 'y': 'SQRT({})'})

13 #Output
              x      y
15 0      2.71828182845905      2.0
  1      7.38905609893065      3.0
17 Name: VDF, Number of rows: 2, Number of columns: 2

```

8.1.4.7 applymap

```

1 vDataframe.applymap(self, func: str, numeric_only: bool = True)

```

Apply the corresponding function to all the vDataframe columns.

Parameters

- **func:** <str>
The function to apply. The function's variable must be written using flower brackets '{}' (Example: EXP({}))
- **numeric_only:** <bool>, optional
Bool to apply the function only on the vDataframe numerical columns.

Returns

The Virtual Dataframe itself.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 1 AS x, 4 AS y) UNION ALL (SELECT 2 AS x, 9 AS y)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
      x      y
7 0      1      4
  1      2      9
9 Name: VDF, Number of rows: 2, Number of columns: 2

11 vdf.applymap('EXP({})')

```

```

13 #Output
15
17
      x      y
0  2.71828182845905  54.5981500331442
1  7.38905609893065  8103.08392757538
Name: VDF, Number of rows: 2, Number of columns: 2

```

8.1.4.8 asfreq

```

1 vDataframe.asfreq(self, ts: str, rule: str, method: dict, by: list = [])

```

Slice the time series using a specific rules and a method for each column.

Parameters

- **ts:** <str>
The time series column to use.
- **rule:** <str>
The slice rule to use (it must be an interval).
- **method:** <dict>
A dictionary of different columns to use and the interpolation method to use. The method can be in {bfill (Back Propagation), ffill (First Element Propagation), linear (Linear Interpolation)}
- **by:** <list>, optional
The columns used to group the elements.

Returns

The Sliced Virtual Dataframe.

Example

```

1 from vertica_ml_python.learn.datasets import load_smart_meters
  sm = load_smart_meters(cur)
3 sm.sort(["id", "time"])
5 #Output
7
8
      time      val      id
0  2014-01-01 11:00:00  0.0290000  0
1  2014-01-01 13:45:00  0.2770000  0
9  2  2014-01-02 10:45:00  0.3210000  0
10 3  2014-01-02 11:15:00  0.3050000  0
11 4  2014-01-02 13:45:00  0.3580000  0
...
13 Name: smart_meters, Number of rows: 11844, Number of columns: 3

```

```

15 sm.asfreq(ts = "time", rule = "1 hour", method = {"val": "linear"}, by = ["id"
    ])
17 #Output
    time      id      val
19 0    2014-01-01 11:00:00    0      0.029
    1    2014-01-01 12:00:00    0    0.119181818181818
    2    2014-01-01 13:00:00    0    0.209363636363636
    3    2014-01-01 14:00:00    0    0.27752380952381
    4    2014-01-01 15:00:00    0    0.279619047619048
    ...      ...      ...
25 Name: smart_meters, Number of rows: 148189, Number of columns: 3

```

8.1.4.9 astype

```
1 vDataframe.astype(self, dtype: dict)
```

Convert the different columns to the input types.

Parameters

- **dtype:** <dict>
A dictionary of different columns and the types to use for the conversion.

Returns

The Virtual Dataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT True AS x, 4 AS y) UNION ALL (SELECT False AS x, 9 AS y))
    z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
5 #Output
    x      y
7 0    True    4
  1   False    9
9 Name: VDF, Number of rows: 2, Number of columns: 2

11 vdf.astype({"x": "int"})
13 #Output
    x      y
15 0    1    4

```

```
1      0      9
17 Name: VDF, Number of rows: 2, Number of columns: 2
```

8.1.4.10 at_time

```
1 vDataframe.at_time(self, ts: str, time: str)
```

Filter the elements of the vDataframe by considering only the events happening at the exact time.

Parameters

- **ts:** <str>
The time series column to use.
- **time:** <str>
The time to consider.

Returns

The Virtual Dataframe itself.

Example

```
1 from vertica_ml_python.learn.datasets import load_smart_meters
2 sm = load_smart_meters(cur)
3
4 #Output
5           time           val      id
6 0  2014-01-01 01:15:00  0.0370000    2
7 1  2014-01-01 02:30:00  0.0800000    5
8 2  2014-01-01 03:00:00  0.0810000    1
9 3  2014-01-01 05:00:00  1.4890000    3
10 4  2014-01-01 06:00:00  0.0720000    5
11 ...          ...          ...     ...
12 Name: smart_meters, Number of rows: 11844, Number of columns: 3
13
14 sm.at_time(ts = "time", time = "12:00")
15
16 #Output
17           time           val      id
18 0  2014-01-04 12:00:00  0.0760000    2
19 1  2014-01-09 12:00:00  0.1610000    6
20 2  2014-01-15 12:00:00  0.0490000    9
21 3  2014-01-19 12:00:00  0.0200000    4
22 4  2014-01-21 12:00:00  0.1440000    7
23 ...          ...          ...     ...
24 Name: smart_meters, Number of rows: 140, Number of columns: 3
```

8.1.4.11 avg / mean

```
vDataframe.avg(columns: list = [])
```

Aggregate the different columns by computing the average of each one.

Parameters

- **columns:** *<list>*, optional
List of the vDataframe Columns. If this parameter is empty, all the numerical columns of the vDataframe will be aggregated.

Returns

The `tablesample` type containing the avg (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.avg()

5 #Output
                                     avg
7 "age"                30.1524573721163
  "body"               164.14406779661
9 "survived"           0.364667747163695
  "pclass"             2.28444084278768
11 "parch"             0.378444084278768
  "fare"               33.9637936739659
13 "sibsp"             0.504051863857374
```

8.1.4.12 bar

```
1 Dataframe.bar(
    self,
3     columns: list,
    method: str = "density",
5     of: str = "",
    max_cardinality: tuple = (6, 6),
7     h: tuple = (None, None),
    hist_type: str = "auto")
```

Draw the corresponding variables Bar Chart.

Parameters


- **columns:** *<list>*
List of the vDataFrame Columns.
- **method:** *<str>*, optional
count | density | avg | min | max | sum
count (default): count is used as aggregation
density: density is used as aggregation
avg | min | max | sum: these aggregations are used only if "of" is informed
- **of:** *<str>*, optional
The column used to compute the aggregation. This parameter is used only if "method" in {avg | min | max | sum}
- **max_cardinality:** *<tuple>*, optional
The maximum cardinality of each column. Under this number the column is automatically considered as categorical.
- **h:** *<tuple>*, optional
The interval size of each column. It is used if the column is numerical. In the other case, if h is not informed. The best "h" will be computed automatically.
- **hist_type:** *<positive int>*, optional
The Bar Chart type. It can be in {fully_stacked | stacked | auto}

Returns


The vDataFrame itself.

Example

```
from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
titanic.bar(columns = ["age", "pclass"], method = "avg", of = "survived")
```



```
titanic.bar(columns = ["age", "pclass"], method = "density", hist_type = "
    fully_stacked")
```



8.1.4.13 beta

```
vDataframe.beta(columns: list = [], focus: str = "")
```

Compute the beta matrix of the corresponding vDataframe columns.

Parameters

- **columns:** *<list>*, optional
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.
- **focus:** *<str>*, optional
Instead of computing a Matrix, a vector including all the information of a specific column will be computed.

Returns

The `tablesamle` type containing the matrix (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```
from vertica_ml_python.learn.datasets import load_titanic
titanic = load_titanic(cur)
titanic.beta(columns = ["age", "fare", "pclass"])
```



```

5 #Output
                                     "age"                                     "fare"                                     "pclass"
7 "age"                               1                               0.696124885853721                               -0.0234150242013145
  "fare"                             1.4365238484091967                               1                               -0.00898230868463811
9 "pclass"                           -42.70762188423708                               -111.3299525889417                               1

```

8.1.4.14 between_time

```

1 vDataframe.between_time(self, ts: str, start_time: str, end_time: str)

```

Filter the elements of the vDataframe by considering only the events happening at the time range.

Parameters

- **ts:** <str>
The time series column to use.
- **start_time:** <str>
The start time.
- **end_time:** <str>
The end time.

Returns

The Virtual Dataframe itself.

Example

```

1 from vertica_ml_python.learn.datasets import load_smart_meters
  sm = load_smart_meters(cur)
3
4 #Output
5
6      time      val      id
7 0  2014-01-01 01:15:00  0.0370000  2
8 1  2014-01-01 02:30:00  0.0800000  5
9 2  2014-01-01 03:00:00  0.0810000  1
10 3  2014-01-01 05:00:00  1.4890000  3
11 4  2014-01-01 06:00:00  0.0720000  5
12 ...
13 Name: smart_meters, Number of rows: 11844, Number of columns: 3
14
15 sm.between_time(ts = "time", start_time = "12:00", end_time = "14:00")
16
17 #Output
18
19      time      val      id
20 0  2014-01-01 13:00:00  0.6220000  4

```

```

19 1      2014-01-01 13:45:00    0.2770000    0
20 2      2014-01-02 12:30:00    0.3970000    5
21 3      2014-01-02 13:45:00    0.3580000    0
22 4      2014-01-03 12:15:00    0.1030000    8
23 ...      ...      ...      ...
Name: smart_meters, Number of rows: 1151, Number of columns: 3

```

8.1.4.15 bool_to_int

```
vDataframe.bool_to_int(self)
```

Convert all the boolean virtual columns to integers.

Returns

The Virtual Dataframe itself.

8.1.4.16 boxplot

```
1 vDataframe.boxplot(self, columns: list = [])
```

Draw the Boxplot of the different vDataframe columns.

Parameters

- **columns:** *<list>*, optional
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.

Returns


The Virtual Dataframe itself.

Example

```

1 from vertica_ml_python.learn.datasets import load_iris
2 iris = load_iris(cur)
3 iris.boxplot(columns = ["PetalLengthCm", "PetalWidthCm", "SepalLengthCm"])

```



8.1.4.17 catcol

```
1 vDataframe.catcol(self, max_cardinality: int = 12)
```

Returns all the different vDataframe categorical columns.

Parameters

- **max_cardinality:** *<int>*, optional
The maximum cardinality of each column. Under this number the column is automatically considered as categorical.

Returns

List of all the categorical columns.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic.catcol()
4
5 #Output
6 ["survived", "sex", "pclass", "embarked", "parch", "sibsp"]
```

8.1.4.18 copy

```
vDataframe.copy(self)
```

Return a copy of the vDataframe.

Returns

The copy of the vDataframe.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic2 = titanic.copy() # titanic2 is now a copy of titanic
```

8.1.4.19 corr

```
1 vDataframe.corr(
    self,
3     columns: list = [],
    method: str = "pearson",
5     cmap: str = "",
    round_nb: int = 3,
7     focus: str = "",
    show: bool = True)
```

Compute the correlation matrix of the vDataframe.

Parameters


- **columns:** <list>, optional
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.
- **method:** <str>, optional
The method must be in pearson (Pearson Coefficient) | kendall (Kendall Coefficient) | spearman (Spearman Coefficient) | biserial (Biserial Point) | cramer (Cramer'sV)
- **cmap:** <str>, optional
Color Maps.
- **round_nb:** <int>, optional
Integer used to round the numerical values.
- **focus:** <str>, optional
Instead of computing a Matrix, a vector including all the information of a specific column will be computed.
- **show:** <bool>, optional
Display the result using matplotlib.

Returns

The `tablesampl` type containing the matrix (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataFrame` using the `to_vdf` method.

Example

```
from vertica_ml_python.learn.datasets import load_titanic
1 titanic = load_titanic(cur)
2 titanic.corr()
```



8.1.4.20 cov

```
vDataFrame.cov(self, columns: list = [], focus: str = "")
```

Compute the covariance matrix of the `vDataFrame`.

Parameters

- **columns:** *<list>*, optional
List of the `vDataFrame` columns. If this parameter is empty, the method will consider all the numerical columns.

- **focus:** *<str>*, optional

Instead of computing a Matrix, a vector including all the information of a specific column will be computed.

Returns

The `tablesampl` type containing the matrix (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataframe` using the `to_vdf` method.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.cov(columns = ["survived", "age", "fare"])

5 #Output
```

	"survived"	"age"	"fare"
"survived"	0.231685181342251	-0.297583583247234	6.69214075159394
"age"	-0.297583583247234	208.169014723609	145.057125218791
"fare"	6.69214075159394	145.057125218791	2769.36114247479

8.1.4.21 count

```
1 vDataframe.count(self, columns: list = [], percent: bool = True)
```

Aggregate the different columns by computing the count (number of non-NULL element) of each one.

Parameters

- **columns:** *<list>*, optional
List of the `vDataframe` Columns. If this parameter is empty, the method will consider all the numerical columns.
- **percent:** *<list>*, optional
If true, compute the percent of non-NULL value of each column.

Returns

The `tablesampl` type containing the counts (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataframe` using the `to_vdf` method.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.count()

5 #Output
```

	count	percent
--	-------	---------

```

7  "age"                997.0      80.794
   "body"              118.0       9.562
9  "survived"          1234.0     100.0
   "ticket"            1234.0     100.0
11 "home.dest"         706.0      57.212
   "cabin"             286.0     23.177
13 "sex"               1234.0     100.0
   "pclass"            1234.0     100.0
15 "embarked"          1232.0     99.838
   "parch"             1234.0     100.0
17 "fare"              1233.0     99.919
   "name"              1234.0     100.0
19 "boat"              439.0      35.575
   "sibsp"             1234.0     100.0

```

8.1.4.22 cummax

```

vDataframe.cummax(
2     self,
      name: str,
4     column: str,
      by: list = [],
6     order_by: list = [])

```

Add a new column to the vDataframe which is the cumulative max of another one.

Parameters

- **name:** <str>
Name of the new feature.
- **column:** <str>
The column used to compute the cumulative max.
- **by:** <list>, optional
The columns used to group the vDataframe elements.
- **order_by:** <list>, optional
The columns used to order the vDataframe elements. If it is empty, the vDataframe will be ordered by the input column.

Returns

The vDataframe itself.

Example

```

from vertica_ml_python.learn.datasets import load_smart_meters
sm = load_smart_meters(cur)
sm.cummax(name = "val_cummax", column = "val", by = ["id"], order_by = ["time"]
    ])
#Output
      time      val  id  val_cummax
0  2014-01-01 11:00:00  0.0290000  0    0.0290000
1  2014-01-01 13:45:00  0.2770000  0    0.2770000
2  2014-01-02 10:45:00  0.3210000  0    0.3210000
3  2014-01-02 11:15:00  0.3050000  0    0.3210000
4  2014-01-02 13:45:00  0.3580000  0    0.3580000
5  2014-01-02 15:30:00  0.1150000  0    0.3580000
6  2014-01-03 08:30:00  0.0710000  0    0.3580000
7  2014-01-04 23:45:00  0.3230000  0    0.3580000
8  2014-01-06 01:15:00  0.0850000  0    0.3580000
9  2014-01-06 21:45:00  0.7130000  0    0.7130000
...
Name: smart_meters, Number of rows: 11844, Number of columns: 4

```

8.1.4.23 cummin

```

vDataframe.cummin(
    self,
    name: str,
    column: str,
    by: list = [],
    order_by: list = [])

```

Add a new column to the vDataframe which is the cumulative min of another one.

Parameters

- **name:** <str>
Name of the new feature.
- **column:** <str>
The column used to compute the cumulative min.
- **by:** <list>, optional
The columns used to group the vDataframe elements.
- **order_by:** <list>, optional
The columns used to order the vDataframe elements. If it is empty, the vDataframe will be ordered by the input column.

Returns

The vDataFrame itself.

Example

```

from vertica_ml_python.learn.datasets import load_smart_meters
sm = load_smart_meters(cur)
sm.cummin(name = "val_cummin", column = "val", by = ["id"], order_by = ["time"]
    ])
#Output
      time      val  id  val_cummin
0  2014-01-01 11:00:00  0.0290000  0  0.0290000
1  2014-01-01 13:45:00  0.2770000  0  0.0290000
2  2014-01-02 10:45:00  0.3210000  0  0.0290000
3  2014-01-02 11:15:00  0.3050000  0  0.0290000
4  2014-01-02 13:45:00  0.3580000  0  0.0290000
5  2014-01-02 15:30:00  0.1150000  0  0.0290000
6  2014-01-03 08:30:00  0.0710000  0  0.0290000
7  2014-01-04 23:45:00  0.3230000  0  0.0290000
8  2014-01-06 01:15:00  0.0850000  0  0.0290000
9  2014-01-06 21:45:00  0.7130000  0  0.0290000
...
Name: smart_meters, Number of rows: 11844, Number of columns: 4

```

8.1.4.24 cumprod

```

vDataFrame.cumprod(
    self,
    name: str,
    column: str,
    by: list = [],
    order_by: list = [])

```

Add a new column to the vDataFrame which is the cumulative product of another one.

Parameters

- **name:** <str>
Name of the new feature.
- **column:** <str>
The column used to compute the cumulative product.
- **by:** <list>, optional
The columns used to group the vDataFrame elements.

- **order_by:** <list>, optional

The columns used to order the vDataframe elements. If it is empty, the vDataframe will be ordered by the input column.

Returns

The vDataframe itself.

Example

```

from vertica_ml_python.learn.datasets import load_smart_meters
sm = load_smart_meters(cur)
sm.cumprod(name = "val_cumprod", column = "val", by = ["id"], order_by = ["
    time"])
#Output

```

	time	val	id	val_cumprod
0	2014-01-01 11:00:00	0.0290000	0	0.029
1	2014-01-01 13:45:00	0.2770000	0	0.008033
2	2014-01-02 10:45:00	0.3210000	0	0.002578593
3	2014-01-02 11:15:00	0.3050000	0	0.000786470865
4	2014-01-02 13:45:00	0.3580000	0	0.00028155656967
5	2014-01-02 15:30:00	0.1150000	0	3.237900551205e-05
6	2014-01-03 08:30:00	0.0710000	0	2.29890939135555e-06
7	2014-01-04 23:45:00	0.3230000	0	7.42547733407843e-07
8	2014-01-06 01:15:00	0.0850000	0	6.31165573396666e-08
9	2014-01-06 21:45:00	0.7130000	0	4.50021053831823e-08
...

```

Name: smart_meters, Number of rows: 11844, Number of columns: 4

```

8.1.4.25 cumsum

```

vDataframe.cumsum(
    self,
    name: str,
    column: str,
    by: list = [],
    order_by: list = [])

```

Add a new column to the vDataframe which is the cumulative sum of another one.

Parameters

- **name:** <str>

Name of the new feature.

- **column:** *<str>*
The column used to compute the cumulative sum.
- **by:** *<list>*, optional
The columns used to group the vDataframe elements.
- **order_by:** *<list>*, optional
The columns used to order the vDataframe elements. If it is empty, the vDataframe will be ordered by the input column.

Returns

The vDataframe itself.

Example

```

1 from vertica_ml_python.learn.datasets import load_smart_meters
2 sm = load_smart_meters(cur)
3 sm.cumsum(name = "val_cumsum", column = "val", by = ["id"], order_by = ["time"]
4         ])
5
6 #Output
7
8      time      val      id      val_cumsum
9 0  2014-01-01 11:00:00  0.0290000  0      0.0290000
10 1  2014-01-01 13:45:00  0.2770000  0      0.3060000
11 2  2014-01-02 10:45:00  0.3210000  0      0.6270000
12 3  2014-01-02 11:15:00  0.3050000  0      0.9320000
13 4  2014-01-02 13:45:00  0.3580000  0      1.2900000
14 5  2014-01-02 15:30:00  0.1150000  0      1.4050000
15 6  2014-01-03 08:30:00  0.0710000  0      1.4760000
16 7  2014-01-04 23:45:00  0.3230000  0      1.7990000
17 8  2014-01-06 01:15:00  0.0850000  0      1.8840000
18 9  2014-01-06 21:45:00  0.7130000  0      2.5970000
19 ...      ...      ...      ...      ...
20 Name: smart_meters, Number of rows: 11844, Number of columns: 4

```

8.1.4.26 current_relation

```
vDataframe.current_relation(self)
```

Returns

Returns the vDataframe current relation.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic["age"].fillna()

```

```

titanic.current_relation()

5
#Output
7 (SELECT COALESCE("age", 30.1524573721163) AS "age", "body" AS "body", "
    survived" AS "survived", "ticket" AS "ticket", "home.dest" AS "home.dest",
    "cabin" AS "cabin", "sex" AS "sex", "pclass" AS "pclass", "embarked" AS "
    embarked", "parch" AS "parch", "fare" AS "fare", "name" AS "name", "boat"
    AS "boat", "sibsp" AS "sibsp" FROM (SELECT "age" AS "age", "body" AS "body
    ", "survived" AS "survived", "ticket" AS "ticket", "home.dest" AS "home.
    dest", "cabin" AS "cabin", "sex" AS "sex", "pclass" AS "pclass", "embarked
    " AS "embarked", "parch" AS "parch", "fare" AS "fare", "name" AS "name", "
    boat" AS "boat", "sibsp" AS "sibsp" FROM public.titanic) t1) final_table

```

8.1.4.27 datecol

```
vDataframe.datecol(self)
```

Returns all the timestamps columns.

Returns

List of all the timestamps columns.

Example

```

1 from vertica_ml_python.learn.datasets import load_smart_meters
  sm = load_smart_meters(cur)
3 sm.datecol()

5 #Output
  ['"time"']

```

8.1.4.28 describe

```

vDataframe.describe(
2     self,
    method: str = "auto",
4     columns: list = [],
    unique: bool = True)

```

Summarise the dataset with mathematical information.

Parameters

- method:** *<str>*, optional
 auto | numerical | categorical
 auto (default): Choose the method 'numerical' if at least one virtual column is numerical, 'categorical' otherwise
 numerical: This mode is used to have only numerical information. Other types are ignored.
 categorical: This mode is available for any type.
- columns:** *<list>*, optional
 The columns used to compute the mathematical information. If this parameter is empty, the method will consider all the vDataFrame columns when the method is 'categorical' otherwise it will only consider the numerical columns.
- unique:** *<bool>*, optional
 Include the cardinality of each element in the computation

Returns

The `tablesampl` type containing the mathematical information (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataFrame using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3
4 #numerical
5 titanic.describe()
7
8 #Output
9
10      count      mean      std  \
11 age      997    30.1524573721163    14.4353046299159  \
12 body     118    164.14406779661    96.5760207557808  \
13 fare    1233    33.963793673966    52.6460729831293  \
14 parch    1234    0.378444084278768    0.868604707790393  \
15 pclass    1234    2.28444084278768    0.842485636190292  \
16 sibsp     1234    0.504051863857374    1.04111727241629  \
17 survived  1234    0.364667747163696    0.481532018641288  \
18
19      min      25%      50%      75%  \
20 age      0.33    21.0    28.0    39.0  \
21 body      1.0    79.25   160.5   257.5  \
22 fare      0.0    7.8958   14.4542   31.3875  \
23 parch      0.0      0.0      0.0      0.0  \
24 pclass      1.0      1.0      3.0      3.0  \
25 sibsp      0.0      0.0      0.0      1.0  \
26 survived  0.0      0.0      0.0      1.0  \
27
28 #categorical
29 titanic.describe(method = "categorical")
30
31 #Output
32
33      dtype  unique  count  \
34 "age"      numeric(6,3)      96    997  \

```

```

31 "body"                int          118      118    \\
   "survived"           int           2      1234    \\
33 "ticket"             varchar(36)    887      1234    \\
   "home.dest"          varchar(100)   359      706     \\
35 "cabin"              varchar(30)    182      286     \\
   "sex"                varchar(20)    2        1234    \\
37 "pclass"             int           3        1234    \\
   "embarked"           varchar(20)    3        1232    \\
39 "parch"              int           8        1234    \\
   "fare"               numeric(10,5)  277      1233    \\
41 "name"               varchar(164)   1232     1234    \\
   "boat"               varchar(100)    26       439     \\
43 "sibsp"              int           7        1234    \\
                                     top      top_percent
45 "age"                24.000          4.413
   "body"                1              0.847
47 "survived"           0              63.533
   "ticket"              CA. 2343         0.81
49 "home.dest"          New York, NY       8.782
   "cabin"                C23 C25 C27       2.098
51 "sex"                male             65.964
   "pclass"              3              53.728
53 "embarked"           S              70.86
   "parch"              0              76.904
55 "fare"              8.05000          4.704
   "name"                Connolly, Miss. Kate 0.162
57 "boat"              13              8.428
   "sibsp"              0              67.747

```

8.1.4.29 drop

```
vDataframe.drop(self, columns: list = [])
```

Drop the selected columns from the vDataframe.

Parameters

- **columns:** *<list>*, optional
List of the vDataframe columns.

Returns

The vDataframe itself.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT True AS x, 4 AS y) UNION ALL (SELECT False AS x, 9 AS y))
              z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
      x      y
7 0    True    4
  1   False    9
9 Name: VDF, Number of rows: 2, Number of columns: 2

11 vdf.drop(["x"])

13 #Output
      y
15 0    4
  1    9
17 Name: y, Number of rows: 2, dtype: int

```

8.1.4.30 drop_duplicates

```

1 vDataFrame.drop_duplicates(self, columns: list = [])

```

Drop the vDataFrame duplicates (the duplicates are defined according to specific columns of the vDataFrame).

Parameters

- **columns:** <list>, optional
List of the vDataFrame columns.

Returns

The vDataFrame itself.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 1 AS x, 4 AS y) UNION ALL (SELECT 1 AS x, 4 AS y) UNION
              ALL (SELECT 1 AS x, 5 AS y)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
      x      y
7 0    1    4
  1    1    4

```

```

9 2      1      5
Name: VDF, Number of rows: 3, Number of columns: 2
11
13 vdf.drop_duplicates()
15
#Output
16      x      y
0      1      4
17 1      1      5
Name: VDF, Number of rows: 2, Number of columns: 2

```

8.1.4.31 dropna

```
vDataframe.dropna(self, columns: list = [])
```

Drop the vDataframe missing values.

Parameters

- **columns:** <list>, optional
List of the vDataframe columns to consider. If this parameter is empty, it will filter all the rows having at least one missing element.

Returns

The vDataframe itself.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
relation = "(SELECT 1 AS x, NULL AS y) UNION ALL (SELECT 1 AS x, 4 AS y)
        UNION ALL (SELECT 1 AS x, 5 AS y) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
5
#Output
6      x      y
7 0      1  None
8 1      1      4
9 2      1      5
Name: VDF, Number of rows: 3, Number of columns: 2
11
13 vdf.dropna()
15
#Output
16      x      y
17 0      1      4

```



```

17 1      1      5
    Name: VDF, Number of rows: 2, Number of columns: 2

```

8.1.4.32 dsn_restart

```
vDataframe.dsn_restart(self)
```

Set a new vDataframe cursor connection using the stored DSN. This method is useful if the connection to the Vertica DB failed.

8.1.4.33 dtypes

```
1 vDataframe.dtypes(self)
```

Returns all the vDataframe columns types.

Returns

The `tablesampl` type containing the columns types (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.dtypes()

5 #Output
                                dtype
7 "age"                numeric(6,3)
  "body"                  int
9 "survived"             int
  "ticket"               varchar(36)
11 "home.dest"           varchar(100)
  "cabin"                varchar(30)
13 "sex"                 varchar(20)
  "pclass"                int
15 "embarked"            varchar(20)
  "parch"                 int
17 "fare"                numeric(10,5)
  "name"                 varchar(164)
19 "boat"                varchar(100)
  "sibsp"                 int

```

8.1.4.34 duplicated

```
vDataframe.duplicated(self, columns: list = [], count: bool = False)
```

Find all the vDataframe duplicates (the duplicates are defined according to specific columns of the vDataframe).

Parameters

- **columns:** *<list>*, optional
List of the vDataframe columns.
- **count:** *<bool>*, optional
If True, the function will return the number of duplicates.

Returns

The `tablesample` type containing the duplicates (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```
1 from vertica_ml_python.vdataframe import vdf_from_relation
2 relation = "((SELECT 1 AS x, 4 AS y) UNION ALL (SELECT 1 AS x, 4 AS y) UNION
3 ALL (SELECT 1 AS x, 5 AS y)) z"
4 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
5
6 #Output
7      x      y
8 0    1      4
9 1    1      4
10 2    1      5
11 Name: VDF, Number of rows: 3, Number of columns: 2
12
13 vdf.duplicated()
14
15 #Output
16      x      y      occurrence
17 0    1      4                2
18 Name: Duplicated Rows, Number of rows: 1, Number of columns: 3
```

8.1.4.35 empty

```
1 vDataframe.empty(self)
```

Returns True if the vDataframe is empty.

8.1.4.36 eval

```
vDataframe.eval(self, name: str, expr: str)
```

Evaluate an expression and create a new column if the expression is correct.

Parameters

- **name:** <str>
Name of the new column
- **expr:** <str>
The expression used to create the new column

Returns

The vDataframe itself.

Example

```
1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 2 AS x, 4 AS y) UNION ALL (SELECT 3 AS x, 4 AS y) UNION
              ALL (SELECT 10 AS x, 5 AS y)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5
6 #Output
7      x      y
0      2      4
9      3      4
2     10      5
11 Name: VDF, Number of rows: 3, Number of columns: 2

13 vdf.eval("z", "x * y")

15 #Output
16      x      y      z
17 0      2      4      8
18 1      3      4     12
19 2     10      5     50
20 Name: VDF, Number of rows: 3, Number of columns: 3
```

8.1.4.37 expected_store_usage

```
vDataframe.expected_store_usage(self, unit = 'b')
```

Expected data volume if the final relation is stored in the Database.

Parameters

- **unit:** <str>, optional
Storage Unit, can be in {b | kb | mb | gb | tb}

Returns

The `tablesampl` type containing the expected store usage of each column (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataframe` using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.expected_store_usage(unit = 'kb')

5 #Output
      expected_size (kb)    max_size (kb)      type
7 "age"                0.0087890625    8.7626953125    numeric(6,3)
  "body"                0.306640625      7.375          int
9 "survived"           1.205078125     77.125          int
  "ticket"             8.2001953125    43.3828125    varchar(36)
11 "home.dest"         13.130859375    68.9453125    varchar(100)
  "cabin"               1.0390625      8.37890625    varchar(30)
13 "sex"                5.640625     24.1015625    varchar(20)
  "pclass"             1.205078125     77.125          int
15 "embarked"           1.203125      24.0625      varchar(20)
  "parch"              1.205078125     77.125          int
17 "fare"               0.0146484375   18.0615234375   numeric(10,5)
  "name"               31.9521484375   197.6328125     varchar(164)
19 "boat"               0.6318359375    42.87109375     varchar(100)
  "sibsp"              1.205078125     77.125          int
21 separator           16.87109375    16.87109375
  header                0.11328125     0.11328125
23 rawsize             83.9326171875   769.05859375

```

8.1.4.38 fillna

```

1 vDataframe.fillna(
    self,
3     val: dict = {},
    method: dict = {},
5     numeric_only: bool = False)

```

Fill the missing values using the input methods. If the parameters `val` and `method` are empty, all the missing values will be filled automatically (using the average of the column for the numerical columns and the mode for the categorical ones)

Parameters

- **val:** *<dict>*, optional
Dictionary of columns with the constant value used to fill their missing values.
- **method:** *<dict>*, optional
Dictionary of columns with the method used to fill their missing values. The method can be in {avg | median | mode}. For more flexibility, use the method `fillna` of the Virtual Column.
- **numeric_only:** *<bool>*, optional
If true, only the numerical columns will be filled

Returns

The `vDataFrame` itself.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
relation = "((SELECT 2 AS x, NULL AS y) UNION ALL (SELECT NULL AS x, 4 AS y)
           UNION ALL (SELECT 10 AS x, 5 AS y)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5
#Output
7      x      y
0      2    None
9    None      4
2     10      5
11 Name: VDF, Number of rows: 3, Number of columns: 2

13 vdf.fillna()

15 #Output
17      x      y
0     2.0    4.5
1     6.0    4.0
19    10.0    5.0
Name: VDF, Number of rows: 3, Number of columns: 2

```

8.1.4.39 filter

```
vDataFrame.filter(self, expr: str = "", conditions: list = [])
```

Filter the elements of the vDataframe using an expression or multiple conditions.

Parameters

- **val:** *<expr>*, optional
The expression used to filter the data.
- **conditions:** *<list>*, optional
A list of conditions used to filter the data.

Returns

The vDataframe itself.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 2 AS x, 1 AS y) UNION ALL (SELECT 10 AS x, 4 AS y) UNION
              ALL (SELECT 10 AS x, 5 AS y)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
      x    y
7 0     2    1
  1    10    4
9 2    10    5
Name: VDF, Number of rows: 3, Number of columns: 2

11 vdf.filter(expr = "x = 10")

13 #Output
      x    y
15 0    10    4
17 1    10    5
Name: VDF, Number of rows: 2, Number of columns: 2

```

8.1.4.40 first

```
vDataframe.first(self, ts: str, offset: str)
```

Keep only the first events of the specific time series.

Parameters

- **ts:** *<str>*
The time series column.

- **offset:** *<list>*, optional
The offset time interval used to filter the data.

Returns

The vDataframe itself.

Example

```

1 from vertica_ml_python.learn.datasets import load_smart_meters
  sm = load_smart_meters(cur)
3 # We only keep the first day of the dataset
  sm.first(ts = "time", offset = "1 day")
5
#Output
7
   time          val    id
0  2014-01-01 01:15:00  0.0370000    2
9  2014-01-01 02:30:00  0.0800000    5
2  2014-01-01 03:00:00  0.0810000    1
11 2014-01-01 05:00:00  1.4890000    3
4  2014-01-01 06:00:00  0.0720000    5
13 ...          ...      ...      ...
Name: smart_meters, Number of rows: 20, Number of columns: 3

```

8.1.4.41 get_columns

```
vDataframe.get_columns(self)
```

Returns the vDataframe columns.

Example

```

1 from vertica_ml_python.learn.datasets import load_smart_meters
  sm = load_smart_meters(cur)
3 sm.get_columns()
5
#Output
["time", "val", "id"]

```

8.1.4.42 get_dummies

```

vDataframe.get_dummies(
2     self,
    columns: list = [],

```

```

4         max_cardinality: int = 12,
5         prefix: str = "",
6         prefix_sep: str = "_",
7         drop_first: bool = False,
8         use_numbers_as_suffix: bool = False)

```

Compute the different columns dummies and add them to the vDataframe.

Parameters

- **columns:** *<list>*, optional
The vDataframe columns to consider.
- **max_cardinality:** *<int>*, optional
The maximum cardinality of a categorical feature. If the cardinality of the feature is higher than this number, it will be skipped.
- **prefix:** *<str>*, optional
Prefix of the dummies.
- **prefix_sep:** *<str>*, optional
Prefix delimiter of the dummies.
- **drop_first:** *<bool>*, optional
Drop the first dummy to avoid the creation of correlated features.
- **use_numbers_as_suffix:** *<bool>*, optional
Use numbers as suffix instead of the different categories.

Returns

The vDataframe itself.

Example

```

from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic.select(["pclass", "sex"]).get_dummies()
4
5 #Output
6
7      sex      pclass      sex_female      pclass_1      pclass_2
8 0   female         1             1             1             0
9 1    male         1             0             1             0
10 2   female         1             1             1             0
11 3    male         1             0             1             0
12 4    male         1             0             1             0
13 ...      ...      ...             ...             ...             ...
14 Name: titanic, Number of rows: 1234, Number of columns: 5

```


8.1.4.43 groupby

```
vDataframe.groupby(self, columns: list, expr: list = [])
```

Group the different categories of the input columns and compute the different aggregations.

Parameters

- **columns:** *<list>*
List of the columns to group with.
- **expr:** *<list>*, optional
List of the different aggregations to apply.

Returns

A new vDataframe corresponding to the group-by result.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic.groupby(columns = ["pclass"], expr = ["AVG(survived)", "COUNT(*)"])
4
5 #Output
6
7      pclass      AVG      COUNT
8 0         1  0.612179487179487    312
9 1         2  0.416988416988417    259
10 2         3  0.227752639517345    663
11 Name: titanic, Number of rows: 3, Number of columns: 3
```

8.1.4.44 head

```
vDataframe.head(self, limit: int = 5)
```

Returns the vDataframe first elements.

Parameters

- **limit:** *<int>*
The number of elements to return.

Returns

The `tablesample` type containing the head of the vDataframe (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_smart_meters
  sm = load_smart_meters(cur)
3 sm.head(limit = 10)

5 #Output
      time          val      id
7 0    2014-01-01 01:15:00    0.0370000    2
  1    2014-01-01 02:30:00    0.0800000    5
9 2    2014-01-01 03:00:00    0.0810000    1
  3    2014-01-01 05:00:00    1.4890000    3
11 4    2014-01-01 06:00:00    0.0720000    5
   5    2014-01-01 07:15:00    2.3060000    9
13 6    2014-01-01 07:45:00    0.1020000    4
   7    2014-01-01 10:45:00    0.0970000    8
15 8    2014-01-01 11:00:00    0.0290000    0
   9    2014-01-01 11:00:00    0.5060000    6
17 ...          ...          ...      ...
  Name: smart_meters, Number of rows: 11844, Number of columns: 3

```

8.1.4.45 help

```
vDataframe.help(self)
```

Prints information about the vDataframe.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.help()

5 #Output

7 #####
  #
9 # Vertica Virtual Dataframe #
  #
11 #####

13 The vDataframe is a Python object which will keep in mind all the user
    modifications in order to use an optimised SQL query. It will send the
    query to the database which will use its aggregations to compute fast
    results. It is created using a view or a table stored in the user database
    and a database cursor. It will create for each column of the table a

```

```

    vColumn (Vertica Virtual Column) which will store for each column its name
    , its imputations and allows to do easy modifications and explorations.
15 vColumn and vDataframe coexist and one can not live without the other. vColumn
    will use the vDataframe information and reciprocally. It is imperative to
    understand both structures to know how to use the entire object.
17 When the user imputes or filters the data, the vDataframe gets in memory all
    the transformations to select for each query the needed data in the input
    relation.
19 As the vDataframe will try to keep in mind where the transformations occurred
    in order to use the appropriate query, it is highly recommended to save
    the vDataframe when the user has done a lot of transformations in order to
    gain in efficiency (using the save method). We can also see all the
    modifications using the history method.
21 If you find any difficulties using vertica_ml_python, please contact me: badr.
    ouali@microfocus.com / I'll be glad to help.
23 For more information about the different methods or the entire vDataframe
    structure, please see the entire documentation

```

8.1.4.46 hexbin

```

1 vDataframe.hexbin(
    self,
3     columns: list,
    method: str = "count",
5     of: str = "",
    cmap: str = '',
7     gridsize: int = 10,
    color: str = "white")

```

Draw the corresponding Hexbin plot.

Parameters

- **columns:** <list>
The two columns used to draw the hexbin (first will be on the x-axis and the second in the y-axis)
- **method:** <str>, optional
count | density | avg | min | max | sum
count (default): count is used as aggregation
density: density is used as aggregation
avg | min | max | sum: these aggregations are used only if "of" is informed


- **of:** *<str>*, optional
The column used to compute the aggregation. This variable is used only if "method" in {avg | min | max | sum}
- **cmap:** *<str>*, optional
Color Maps.
- **gridsize:** *<int>*, optional
Grid Size.
- **color:** *<str>*, optional
Hexbin outline color.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic.hexbin(columns = ["age", "parch"], method = "avg", of = "survived")

```



8.1.4.47 hist

```

1 Dataframe.hist(
2     self,
3     columns: list,
4     method: str = "density",
5     of: str = "",
6     max_cardinality: tuple = (6, 6),
7     h: tuple = (None, None),

```

```
hist_type: str = "auto")
```

Draw the corresponding variables Histogram.

Parameters


- **columns:** *<list>*
List of the vDataframe columns.
- **method:** *<str>*, optional
count | density | avg | min | max | sum
count (default): count is used as aggregation
density: density is used as aggregation
avg | min | max | sum: these aggregations are used only if "of" is informed
- **of:** *<str>*, optional
The column used to compute the aggregation. This parameter is used only if "method" in {avg | min | max | sum}
- **max_cardinality:** *<tuple>*, optional
The maximum cardinality of each column. Under this number the column is automatically considered as categorical.
- **h:** *<tuple>*, optional
The interval size of each column. It is used if the column is numerical. In the other case, if h is not informed. The best "h" will be computed automatically.
- **hist_type:** *<positive int>*, optional
The Histogram type. It can be in {multi | stacked | auto}

Returns


The vDataframe itself.

Example

```
from vertica_ml_python.learn.datasets import load_titanic
titanic = load_titanic(cur)
titanic.hist(columns = ["age", "pclass"], method = "avg", of = "survived")
```



```
titanic.hist(columns = ["age", "fare"], hist_type = "multi")
```



8.1.4.48 info

```
Dataframe.info(self)
```

Summarise all the modifications made to the vDataframe.

Returns

The vDataframe itself.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["sex"].label_encode()
  titanic["age"].fillna()
5 titanic.info()

7 #Output
The vDataframe was modified many times:
9 * {Sat Nov 23 05:33:55 2019} [Label Encoding]: Label Encoding was applied to
   the vColumn '"sex"' using the following mapping:
   female => 0 male => 1
11 * {Sat Nov 23 05:33:55 2019} [Fillna]: 237 missing values of the vColumn '"
   age"' were filled.
```

8.1.4.49 isin

```
1 vDataframe.isin(self, val: dict)
```

Verify if the elements are in the vDataframe.

Parameters

- **val:** <dict>
Dictionary of the different columns and the values to check.

Returns

A list of booleans, result of the values checking.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 #We check if there are a 15 years old and a 50 years old passengers in first
   class
  titanic.isin({"age": [15, 50], "pclass": [1, 1]})
5
7 #Output
[ True,  True ]
```

8.1.4.50 join

```

1 vDataframe.join(
      self,
3      input_relation: str = "",
      vdf = None,
5      on: dict = {},
      how: str = 'natural',
7      expr1: list = [],
      expr2: list = [])

```

Join the vDataframe with another one or another relation.

Parameters

- **input_relation:** <str>, optional
The relation to join with the vDataframe.
- **vdf:** <object>, optional
The vDataframe to join with the current vDataframe.
- **on:** <dict>, optional
Dictionary of the elements which are the main keys of the joins.
- **how:** <str>, optional
The join methods, it must be in {cross | natural | inner | left | right | self}
- **expr1:** <list>, optional
The elements to keep from the Virtual Dataframe. Aliases can be given.
- **expr2:** <list>, optional
The elements to keep from the relation or Virtual Dataframe used to join. Aliases can be given.

Returns

The vDataframe of the join.

Example

```

from vertica_ml_python.vdataframe import vdf_from_relation
2 relation = "((SELECT 0 AS id, 'Fouad' AS name) UNION ALL (SELECT 1 AS id, '
      Colin' AS name) UNION ALL (SELECT 2 AS id, 'Badr' AS name)) z"
vdf1 = vdf_from_relation(relation, dsn = "VerticaDSN")
4
#Output
6      id      name
0       0    Fouad
8       1    Colin
       2    Badr
10 Name: VDF, Number of rows: 3, Number of columns: 2

```



```

12 relation = "((SELECT 0 AS id, 'Apple' AS fav_fruit) UNION ALL (SELECT 1 AS id,
    'Blueberries' AS fav_fruit) UNION ALL (SELECT 2 AS id, 'Mango' AS
    fav_fruit)) z"
vdf2 = vdf_from_relation(relation, dsn = "VerticaDSN")

14
#Output
16      id      fav_fruit
0      0      Apple
18 1      1  Blueberries
2      2      Mango
20 Name: VDF, Number of rows: 3, Number of columns: 2

22 vdf1.join(vdf = vdf2)

24 #Output
      id      name      fav_fruit
26 0      0  Fouad      Apple
1      1  Colin  Blueberries
28 2      2  Badr      Mango
Name: VDF, Number of rows: 3, Number of columns: 3

```

8.1.4.51 kurtosis / kurt

```

1 vDataframe.kurtosis(self, columns: list = [])

```

Aggregate the different columns by computing the unbiased kurtosis using Fisher's definition (kurtosis of normal = 0.0).

Parameters

- **columns:** <list>, optional
List of the vDataframe Columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesample` type containing the kurtosis (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
titanic = load_titanic(cur)
3 titanic.kurt()

5 #Output
      kurtosis
7 "age"      0.15689691331997

```

```

"body"          -1.23864914040606
9 "survived"     -1.68576262213743
"pclass"        -1.34962169484619
11 "parch"       22.6438022640172
"fare"          26.2543152552867
13 "sibsp"       19.2138853382802

```

8.1.4.52 last

```
1 vDataframe.last(self, ts: str, offset: str)
```

Keep only the last events of the specific time series.

Parameters

- **ts:** <str>
The time series column.
- **offset:** <str>
The offset time interval used to filter the data.

Returns

The vDataframe itself.

Example

```

1 from vertica_ml_python.learn.datasets import load_smart_meters
sm = load_smart_meters(cur)
3 sm.last(ts = "time", offset = "1 day")

5 #Output
           time          val      id
7 0    2015-09-10 05:00:00  0.0930000    1
  1    2015-09-10 05:30:00  0.1410000    1
9 2    2015-09-10 06:45:00  0.6030000    2
  3    2015-09-10 07:15:00  0.8480000    3
11 4    2015-09-10 07:30:00  0.0570000    6
   ...          ...          ...    ...
13 Name: smart_meters, Number of rows: 20, Number of columns: 3

15 # We only keep the last day of the dataset

```

8.1.4.53 load

```
1 vDataframe.load(self, offset: int = -1)
```

Load the vDataframe corresponding to the selected saving.

Parameters

- **offset:** *<list>*, optional
The saving position (-1 for the last one)

Returns

Create a new vDataframe which is based on the selected saving.

Examples

```
1 from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic.save()
4 titanic["sex"]
5
6 #Output
7      sex
8 0  female
9 1   male
10 2  female
11 3   male
12 4   male
13 ...   ...
14 Name: sex, Number of rows: 1234, dtype: varchar(20)
15
16 titanic["sex"].label_encode()
17 titanic["sex"]
18
19 #Output
20      sex
21 0      0
22 1      1
23 2      0
24 3      1
25 4      1
26 ...   ...
27 Name: sex, Number of rows: 1234, dtype: int
28
29 titanic = titanic.load()
30 titanic["sex"]
```

```

31 #Output
32
33      sex
0    female
35 1    male
36 2    female
37 3    male
38 4    male
39 ...    ...
Name: sex, Number of rows: 1234, dtype: varchar(20)

```

8.1.4.54 mad

```
vDataframe.mad(self, columns: list = [])
```

Aggregate the different columns by computing the median absolute deviation of each one.

Parameters

- **columns:** *<list>*, optional
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesample` type containing the mad (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic.mad()
4
5 #Output
6
7      mad
8 "age"    8.0
9 "body"   89.5
10 "survived" 0.0
11 "pclass"  0.0
12 "parch"   0.0
13 "fare"    6.9042
14 "sibsp"   0.0

```

8.1.4.55 mae

```
1 vDataframe.mae(self, columns: list = [])
```

Aggregate the different columns by computing the mean absolute error (deviation) of each one.

Parameters

- **columns:** *<list>*, optional
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesampl` type containing the mae (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
   titanic = load_titanic(cur)
3 titanic.mae()

5 #Output
                                     mae
7 "age"                11.254785419447906
  "body"                82.97457627118644
9 "survived"           0.46337036268450094
  "pclass"             0.7689071656916803
11 "parch"             0.5820801231451393
   "fare"              30.625865942462237
13 "sibsp"             0.6829616826333305
```

8.1.4.56 max

```
1 vDataframe.max(self, columns: list = [])
```

Aggregate the different columns by computing the max of each one.

Parameters

- **columns:** *<list>*, optional
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesampl` type containing the max (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.max()

5 #Output
                                max
7 "age"                        80.0
  "body"                      328.0
9 "survived"                   1.0
  "pclass"                    3.0
11 "parch"                     9.0
  "fare"                     512.3292
13 "sibsp"                     8.0

```

8.1.4.57 median

```

1 vDataframe.median(self, columns: list = [])

```

Aggregate the different columns by computing the median of each one.

Parameters

- **columns:** <list>, optional
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesampl` type containing the medians (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.median()

5 #Output
                                median
7 "age"                        28.0
  "body"                      160.5
9 "survived"                   0.0
  "pclass"                    3.0
11 "parch"                     0.0
  "fare"                     14.4542

```

```
13 "sibsp" 0.0
```

8.1.4.58 memory_usage

```
1 vDataframe.memory_usage(self)
```

Memory usage of the object in byte (it will never exceed some kb).

Returns

The `tablesampl` type containing the memory usage of each column (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataframe` using the `to_vdf` method.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.memory_usage(unit = 'kb')

5 #Output
      value
7 object    687
  "age"     182
9  "body"    183
  "survived" 187
11 "ticket"   185
  "home.dest" 188
13 "cabin"    184
  "sex"      182
15 "pclass"   185
  "embarked" 187
17 "parch"    184
  "fare"     183
19 "name"     183
  "boat"     183
21 "sibsp"    184
  total    3267
```

8.1.4.59 min

```
vDataframe.max(self, columns: list = [])
```

Aggregate the different columns by computing the min of each one.

Parameters

- **columns:** *<list>*, optional
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesampl` type containing the min (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.min()

5 #Output
                                min
7 "age"                        0.33
  "body"                       1.0
9 "survived"                   0.0
  "pclass"                     1.0
11 "parch"                     0.0
   "fare"                      0.0
13 "sibsp"                     0.0

```

8.1.4.60 normalize

```

1 vDataframe.normalize(self, columns: list = [], method: str = "zscore")

```

Normalize all the numerical columns of the vDataframe using the corresponding method. Use the `normalize` method of each column for more flexibility.

Parameters

- **columns:** *<list>*, optional
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.
- **method:** *<str>*, optional
The method to be used: {zscore | robust_zscore | minmax}

Returns

The vDataframe itself.

Example


```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.normalize()
  titanic["fare"]
5
#Output
7
                                fare
0      2.2335228377568673306163744003
9      2.2335228377568673306163744003
2      2.2335228377568673306163744003
11     -0.6451344183800711827483251581
4      0.2951864297839290254556257484
13 ...
Name: fare, Number of rows: 1234, dtype: float

```

8.1.4.61 numcol

```
vDataframe.numcol(self)
```

Returns the vDataframe numerical columns.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.numcol()
5
#Output
["age", "body", "survived", "pclass", "parch", "fare", "sibsp"]

```

8.1.4.62 outliers

```

vDataframe.outliers(
2     self,
    columns: list = [],
4     name: str = "distribution_outliers",
    threshold: float = 3.0,
6     robust: bool = False)

```

Find the outliers of the distribution regarding specific columns and create a new Virtual Column to label the outliers.

Parameters

- **columns:** *<list>*, optional
The columns used to compute the outliers.
- **name:** *<str>*, optional
Name of the new feature which will represent the outliers.
- **threshold:** *<float>*, optional
Use the Gaussian distribution to define the outliers. After normalizing the data, if the record is greater than the threshold it will be considered as an outlier.
- **robust:** *<bool>*, optional
Compute the Robust Z-Score instead of the Z-Score to find the outliers.

Returns

The vDataFrame itself.

Example

```
from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
  titanic.outliers()
4
#Output
6 The new vColumn "distribution_outliers" was added to the vDataFrame.
   age      body  survived      ticket      home.dest
   \\\
8 0    2.000    None         0    113781  Montreal, PQ / Chesterville, ON
   \\\
  1    30.000    135         0    113781  Montreal, PQ / Chesterville, ON
   \\\
10 2    25.000    None         0    113781  Montreal, PQ / Chesterville, ON
   \\\
  3    39.000    None         0    112050           Belfast, NI
   \\\
12 4    71.000     22         0    PC 17609  Montevideo, Uruguay
   \\\
...    ...      ...      ...      ...      ...
   \\\
14      cabin      sex  pclass  embarked  parch  \\\
0    C22 C26   female         1          S      2  \\\
16 1    C22 C26    male         1          S      2  \\\
  2    C22 C26   female         1          S      2  \\\
18 3      A36    male         1          S      0  \\\
  4      None    male         1          C      0  \\\
20 ...      ...      ...      ...      ...      ...  \\\
   fare      name      boat  \\\
22 0    151.55000  Allison, Miss. Helen Loraine  None  \\\
  1    151.55000  Allison, Mr. Hudson Joshua Creighton  None  \\\
24 2    151.55000  Allison, Mrs. Hudson J C (Bessie Wald...
```

```

3      0.00000      Andrews, Mr. Thomas Jr      None      \\
26     49.50420      Artagaveytia, Mr. Ramon      None      \\
...      ...      ...      ...      \\
28      sibsp      distribution_outliers
0      1      0
30     1      0
2      1      0
32     0      0
4      0      0
34     ...      ...
Name: titanic, Number of rows: 1234, Number of columns: 15

```

8.1.4.63 pivot_table

```

1 vDataframe.pivot_table(
2     self,
3     columns: list,
4     method: str = "count",
5     of: str = "",
6     h: tuple = (None, None),
7     max_cardinality: tuple = (20, 20),
8     show: bool = True,
9     cmap: str = '',
    with_numbers: bool = True)

```

Draw the corresponding pivot table.

Parameters

- **columns:** *<list>*
The two columns used to build the pivot table.
- **method:** *<str>*, optional
count | density | avg | min | max | sum
count (default): count is used as aggregation
density: density is used as aggregation
avg | min | max | sum: these aggregations are used only if "of" is informed.
- **of:** *<str>*, optional
The column used to compute the aggregation. This variable is used only if "method" in {avg | min | max | sum}
- **max_cardinality:** *<tuple>*, optional
The maximum cardinality of each column. Under this number the column is automatically considered as categorical.
- **h:** *<tuple>*, optional
The interval size of each column. It is used if the column is numerical. In the other case, if h is not informed. The best "h" will be computed automatically. If the column is a date, h represents the interval size in seconds.

- **cmap:** *<str>*, optional
Color Maps
- **show:** *<bool>*, optional
Draw the pivot table using matplotlib.
- **with_numbers:** *<bool>*, optional
If False, draw the pivot table without displaying the numbers.

Returns

The `tablesample` type containing the pivot table (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataFrame` using the `to_vdf` method.


Example

```
titanic.pivot_table(columns = ["fare", "survived"])
```

```
#Output
```

	"fare"/"survived"	0	1
0	[0;47]	698	294
1	[47;94]	61	97
2	[94;141]	6	24
3	[141;188]	6	10
4	[188;235]	8	10
5	[235;282]	4	11
6	[470;517]		4

Pivot Table of "fare" vs "survived"



8.1.4.64 plot

```

1 vDataframe.plot(
2     self,
3     ts: str,
4     columns: list = [],
5     start_date: str = "",
6     end_date: str = "")

```

Plot the time series selected columns.

Parameters

- **ts:** <str>
The time series used to plot the different elements.
- **columns:** <list>, optional
The columns to plot. If empty, all the numerical columns will be plotted.
- **start_date:** <str>, optional
Start Date.

- **end_date:** <str>, optional
End Date.

Returns


The vDataFrame itself.

Example

```

from vertica_ml_python.learn.datasets import load_smart_meters
2 sm = load_smart_meters(cur)
# Slicing and interpolating the time series
4 sm = sm.asfreq(ts = "time", rule = "30 minutes", method = {"val": "linear"},
    by = ["id"])
# Building the features corresponding to the consumption of 3 different homes
6 sm.eval("id0", "DECODE(id, 0, val, NULL)")
sm.eval("id1", "DECODE(id, 1, val, NULL)")
8 sm.eval("id2", "DECODE(id, 2, val, NULL)")
# Drawing the time series
10 sm.plot(ts = "time", columns = ["id0", "id1", "id2"], start_date = "2014-02-01
    00:00:00", end_date = "2014-03-01 00:00:00")

```



8.1.4.65 product / prod

```
vDataframe.product(self, columns: list = [])
```

Aggregate the different columns by computing the product of each one.

Parameters

- **columns:** *<list>*, optional
List of the vDataframe Columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesampl` type containing the products (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.prod()

5 #Output
                                     prod
7 "age"                               inf
  "body"          5.04839415885224e+245
9 "survived"              0.0
  "pclass"              inf
11 "parch"              0.0
   "fare"              0.0
13 "sibsp"              0.0
```

8.1.4.66 quantile

```
1 vDataframe.quantile(self, q: list, columns: list = [])
```

Aggregate the different columns by computing the different selected quantiles of each one.

Parameters

- **q:** *<list>*
List of the different quantiles (each element must be in [0,1]).
- **columns:** *<list>*, optional
List of the vDataframe Columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesampl` type containing the quantiles (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataframe` using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.quantile(q = [0.1, 0.5, 0.9])

5 #Output
                                10.0%      50.0%      90.0%
7 "age"                        14.5       28.0       50.0
  "body"                       37.7      160.5      297.3
9 "survived"                    0.0        0.0        1.0
  "pclass"                     1.0        3.0        3.0
11 "parch"                     0.0        0.0        1.0
  "fare"                       7.5892    14.4542     79.13
13 "sibsp"                     0.0        0.0        1.0

```

8.1.4.67 rank

```

1 vDataframe.rank(self, order_by: list, method: str = "first", by: list = [],
  name = "")

```

Compute the rank of the selected column. This method will add the new feature to the `vDataframe`.

Parameters

- **order_by:** *<list>*
The columns used to order the `vDataframe` elements.
- **method:** *<str>*, optional
Method used to compute the Rank, it must be in {first | dense | percent}
- **by:** *<list>*, optional
The columns used to group the `vDataframe` elements.
- **name:** *<str>*, optional
Name of the new feature.

Returns

The `vDataframe` itself.

Example


```

1 from vertica_ml_python.learn.datasets import load_smart_meters
  sm = load_smart_meters(cur)
3 sm.rank(order_by = ["time"], by = ["id"])

5 #Output
      time          val    id  first_rank_time_by_id
7 0    2014-01-01 11:00:00  0.0290000    0            1
  1    2014-01-01 13:45:00  0.2770000    0            2
9 2    2014-01-02 10:45:00  0.3210000    0            3
  3    2014-01-02 11:15:00  0.3050000    0            4
11 4    2014-01-02 13:45:00  0.3580000    0            5
    ...          ...      ...      ...
13 Name: smart_meters, Number of rows: 11844, Number of columns: 4

```

8.1.4.68 rolling

```

1 vDataframe.rolling(
      self,
3      name: str,
      aggr: str,
5      column: str,
      preceding,
7      following,
      expr: str = "",
9      by: list = [],
      order_by: list = [],
11     method: str = "rows",
      rule: str = "auto")

```

Compute a Moving Window. The method will add the new feature to the vDataframe.

Parameters

- **name:** <str>
Name of the new feature.
- **aggr:** <str>
Aggregation used to compute the Moving Window.
- **column:** <str>
The column used to compute the aggregation.
- **preceding:** <str or list or int or tuple>,
Rule for the preceding elements. It can be an integer if the method is set to 'rows' otherwise an interval. It can also be set to 'unbounded' in order to consider all the elements before the event.
- **following:** <str or list or int or tuple>,
Rule for the following elements. It can be an integer if the method is set to 'rows' otherwise an interval. It can also be set to 'unbounded' in order to consider all the elements after the event.

- **expr:** *<str>*, optional
The expression to consider instead of the aggregation. It can be used if a complex Moving Window is needed.
- **by:** *<list>*, optional
The columns used to group the vDataframe elements.
- **order_by:** *<list>*, optional
The columns used to order the vDataframe elements. If it is empty, the vDataframe will be ordered by the selected column.
- **method:** *<list>*, optional
Method used to compute the Moving Window, it must be in {rows | range} (range is only available if the order_by column is a timestamp)
- **rule:** *<str>*, optional
auto | past | future
auto: Set a regular moving window (past-future)
past: Set a moving window in the past (past-past)
future: Set moving window in the future (future-future)

Returns

The vDataframe itself.

Example

```

from vertica_ml_python.learn.datasets import load_smart_meters
sm = load_smart_meters(cur)
# Computing the highest consumption per home one day preceding and one day
  following the current date
sm.rolling(
    name = "highest_consumption_1p_1f",
    aggr = "max", column = "val",
    preceding = "1 days",
    following = "1 days",
    by = ["id"],
    order_by = ["time"],
    method = "range")

#Output
      time      val  id  val_cummax
      time      val  id  highest_consumption_1p_1f
0  2014-01-01 11:00:00  0  0.3210000
1  2014-01-01 13:45:00  0  0.3580000
2  2014-01-02 10:45:00  0  0.3580000
3  2014-01-02 11:15:00  0  0.3580000
4  2014-01-02 13:45:00  0  0.3580000
...      ...      ...      ...
Name: smart_meters, Number of rows: 11844, Number of columns: 4

```

8.1.4.69 sample

```
vDataframe.sample(self, x: float)
```

Returns a sample of the vDataframe relation.

Parameters

- **x:** *<float>*
A float which indicate the sample value (must be in [0,1]).

Returns

The vDataframe itself.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
   titanic = load_titanic(cur)
3 titanic.sample(x = 0.005)

5 #Output

   name      body      ticket  \
7 0  Mallet, Mrs. Albert (Antoinette Magnin)  None  S.C./PARIS 2079  \
   1      Barry, Miss. Julia  None  330844  \
9 2  Wiklund, Mr. Karl Johan  None  3101266  \
   ...      ...      ...      ...  \

11 sex      survived      fare      sibsp      embarked  \
0  female      1      37.00420      1      C  \
13 1  female      0      7.87920      0      Q  \
   2  male      0      6.49580      1      S  \
15 ...      ...      ...      ...      ...  \

   cabin      age      parch      home.dest      boat  \
17 0  None  24.000      1      Paris / Montreal, PQ      10  \
   1  None  27.000      0      New York, NY  None  \
19 2  None  21.000      0      None  None  \
   ...      ...      ...      ...      ...  \

21 pclass
0      2
23 1      3
   2      3
25 ...      ...

Name: titanic, Number of rows: 6, Number of columns: 14
```

8.1.4.70 save

```
vDataframe.save(self)
```

Save the vDataframe current disposition. In case of unwanted operations, it will be possible to go back by loading a saving using the `load` method.

Returns

The vDataframe itself.

Examples

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.save()
  titanic["sex"]
5
  #Output
7      sex
0    female
9      male
2    female
11     male
4      male
13 ...
Name: sex, Number of rows: 1234, dtype: varchar(20)
15
  titanic["sex"].label_encode()
17 titanic["sex"]
19
  #Output
21     sex
0       0
1       1
23     0
3       1
25     1
...
27 Name: sex, Number of rows: 1234, dtype: int
29
  titanic = titanic.load()
  titanic["sex"]
31
  #Output
33     sex
0    female
35     male
2    female
```

```

37 3      male
    4      male
39 ...      ...
Name: sex, Number of rows: 1234, dtype: varchar(20)

```

8.1.4.71 scatter

```

vDataframe.scatter(
    self,
    columns: list,
    cat_col: str = "",
    max_cardinality: int = 3,
    cat_priority: list = [],
    with_others: bool = True,
    max_nb_points: int = 20000)

```

Draw the scatter plot of the input columns.

Parameters


- **columns:** *<str>*
The two or three columns used to draw the scatter plot.
- **catcol:** *<str>*, optional
The categorical column used as label.
- **max_cardinality:** *<int>*, optional
The maximum cardinality of the categorical column, all the other categories are merged to create the "others" category.
- **cat_priority:** *<list>*, optional
The list of the categories took into account during the computation.
- **with_others:** *<bool>*, optional
Include the "others" category.
- **max_nb_points:** *<int>*, optional
The maximum number of points in the scatter plot. The points are taken randomly from the table.

Examples


```

from vertica_ml_python.learn.datasets import load_iris
2 iris = load_iris(cur)
iris.scatter(columns = ["PetalLengthCm", "SepalLengthCm"], catcol = "Species")

```



```
iris.scatter(columns = ["PetalLengthCm", "SepalLengthCm", "PetalWidthCm"],
             catcol = "Species")
```



8.1.4.72 scatter_matrix

```
vDataframe.scatter(self, columns: list = [])
```


Draw the scatter matrix of the input columns.

Parameters

- **columns:** *<str>*
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.

Examples

```
1 from vertica_ml_python.learn.datasets import load_iris
iris = load_iris(cur)
3 iris.scatter_matrix(columns = ["PetalLengthCm", "SepalLengthCm", "PetalWidthCm"
    " ])
```



8.1.4.73 select

```
1 vDataframe.select(self, columns: list)
```

Select some of the vDataframe columns.

Parameters

- **columns:** *<list>*
List of the columns to select.

Returns

A new vDataFrame containing only the selected columns.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.select(columns = ['pclass', 'age'])

5 #Output
      age      pclass
7 0    2.000         1
  1   30.000         1
9 2   25.000         1
  3   39.000         1
11 4   71.000         1
   ...      ...      ...
13 Name: titanic, Number of rows: 1234, Number of columns: 2

```

8.1.4.74 sem

```

1 vDataFrame.sem(self, columns: list = [])

```

Aggregate the different columns by computing the unbiased standard error of the mean of each element.

Parameters

- **columns:** *<list>*, optional
List of the vDataFrame columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesample` type containing the sem (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataFrame using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.sem()

5 #Output
                                sem
7 "age"          0.457170684605937
  "body"         8.89054334053935
9 "survived"     0.0137077946622731
  "pclass"       0.023983078299543

```



```

11 "parch"          0.0247266111413956
    "fare"          1.49928585339507
13 "sibsp"          0.029637534446613

```

8.1.4.75 sessionize

```

1 vDataframe.sessionize(
    self,
3     ts: str,
    by: list = [],
5     session_threshold = "30 minutes",
    name = "session_id")

```

Create a new feature which will represent the different elements session. A session is defined as a user inactivity during a certain amount of time (called the session threshold).

Parameters

- **ts:** *<str>*
The vDataframe time series.
- **by:** *<list>*
List of the different element used to group the vDataframe (Most of the time it is a user id).
- **session_threshold:** *<str>*, optional
The session threshold. It must be a time interval.
- **name:** *<str>*, optional
Name of the session.

Returns

The vDataframe itself.

Example

```

from vertica_ml_python.vdataframe import vdf_from_relation
2 relation = "((SELECT '2013-01-24 07:06:46'::timestamp AS date_time, 0 AS id)
    UNION ALL (SELECT '2013-01-24 07:07:10'::timestamp AS date_time, 0 AS id)
    UNION ALL (SELECT '2013-01-24 07:08:11'::timestamp AS date_time, 0 AS id)
    UNION ALL (SELECT '2013-01-24 09:01:41'::timestamp AS date_time, 0 AS id)
    UNION ALL (SELECT '2013-01-24 09:10:11'::timestamp AS date_time, 0 AS id))
    z"
vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
4
#Output
6           date_time      id
0    2013-01-24 07:06:46      0

```

```

8 1      2013-01-24 07:07:10      0
9 2      2013-01-24 07:08:11      0
10 3      2013-01-24 09:01:41      0
11 4      2013-01-24 09:10:11      0
12 Name: VDF, Number of rows: 5, Number of columns: 2

14 vdf.sessionize(ts = "date_time", by = ["id"])

16 #Output
      date_time      id      session_id
18 0      2013-01-24 07:06:46      0          0
19 1      2013-01-24 07:07:10      0          0
20 2      2013-01-24 07:08:11      0          0
21 3      2013-01-24 09:01:41      0          1
22 4      2013-01-24 09:10:11      0          1
Name: VDF, Number of rows: 5, Number of columns: 3

```

8.1.4.76 set_cursor

```
1 vDataframe.set_cursor(self, cursor)
```

Replace the current cursor with a new one.

- **cursor:** *<object>*
A Database cursor.

Returns

The vDataframe itself.

8.1.4.77 set_dsn

```
1 vDataframe.set_dsn(self, dsn: str)
```

Replace the current DSN with a new one.

- **dsn:** *<str>*
Vertica DSN.

Returns

The vDataframe itself.

8.1.4.78 shape

```
1 vDataframe.shape(self)
```

Returns the vDataframe shape (Number of rows and columns).

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.shape()

5 #Output
  (1234, 14)
```

8.1.4.79 skewness / skew

```
vDataframe.skewness(self, columns: list = [])
```

Aggregate the different columns by computing the unbiased skewness of each one.

Parameters

- **columns:** <list>, optional
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesampl` type containing the skewness (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.skew()

5 #Output
                                     skewness
7 "age"                             0.408876460779437
  "body"                             0.0617701251569532
9 "survived"                         0.56300284427369
  "pclass"                          -0.576258567091907
11 "parch"                           3.79801928269975
  "fare"                             4.30069918891405
13 "sibsp"                           3.7597831472411
```

8.1.4.80 sort

```
1 vDataframe.sort(self, columns: list = [])
```

Sort the vDataframe using specific columns.

Parameters

- **columns:** *<list>*, optional
The columns used to sort the data.

Returns

The vDataframe itself.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
   titanic = load_titanic(cur)
3 titanic.sort(["fare"])

5 #Output
   fare                                name    boat    sibsp
7 0      None                        Storey, Mr. Thomas    None    0
1 1  0.00000    Chisholm, Mr. Roderick Robert Crispin    None    0
9 2  0.00000                        Andrews, Mr. Thomas Jr    None    0
3 3  0.00000                        Fry, Mr. Richard    None    0
11 4  0.00000                Harrison, Mr. William    None    0
   ...      ...                                ...    ...    ...
13 Name: titanic, Number of rows: 1234, Number of columns: 14
```

8.1.4.81 sql_on_off

```
1 vDataframe.sql_on_off(self)
```

Prints all the sql queries used by the vDataframe for the different computations. If it is already enable, it will turn it off.

Returns

The vDataframe itself.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
   titanic = load_titanic(cur)
3 titanic.sql_on_off()
```

```

titanic.max()
5
#Output
7 $ COMPUTE AGGREGATION(S) $

9 SELECT MAX("age"),
        MAX("body"),
11        MAX("survived"),
        MAX("pclass"),
13        MAX("parch"),
        MAX("fare"),
15        MAX("sibsp")
FROM
17 (SELECT "age" AS "age",
        "body" AS "body",
19        "survived" AS "survived",
        "ticket" AS "ticket",
21        "home.dest" AS "home.dest",
        "cabin" AS "cabin",
23        "sex" AS "sex",
        "pclass" AS "pclass",
25        "embarked" AS "embarked",
        "parch" AS "parch",
27        "fare" AS "fare",
        "name" AS "name",
29        "boat" AS "boat",
        "sibsp" AS "sibsp"
31 FROM public.titanic) final_table

```

8.1.4.82 statistics

```
vDataframe.statistics(self, columns: list = [], skew_kurt_only: bool = False)
```

Summarise the vDataframe with statistical information.

Parameters

- **columns:** *<list>*, optional
The columns used to compute the mathematical information. If this parameter is empty, the method will consider all the vDataframe numerical columns.
- **skew_kurt_only:** *<bool>*, optional
Only compute the skewness and kurtosis.

Returns

The `tablesampl` type containing the statistical information (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataFrame` using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.statistics(columns = ["age", "fare", "pclass"])

5 #Output
                                     "age"                "fare"                "pclass"
7 count                             997.0                1233.0                1234.0
  avg                   30.1524573721163          33.9637936739659          2.28444084278768
9  stddev                   14.4353046299159          52.6460729831293          0.842485636190292
  min                        0.33                      0.0                      1.0
11 10%                        14.5                      7.5892                      1.0
   25%                       21.0                      7.8958                      1.0
13 median                     28.0                     14.4542                      3.0
   75%                       39.0                     31.3875                      3.0
15 90%                       50.0                      79.13                      3.0
  max                        80.0                    512.3292                      3.0
17 skewness                   0.408876460779437          4.30069918891405          -0.576258567091907
  kurtosis                    0.15689691331997          26.2543152552867          -1.34962169484619

```

8.1.4.83 std

```
vDataFrame.std(self, columns: list = [])
```

Aggregate the different columns by computing the standard deviation of each one.

Parameters

- **columns:** *<list>*, optional
List of the `vDataFrame` Columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesampl` type containing the std (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataFrame` using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.std()

```

```

5 #Output
                                     stddev
7 "age"                            14.4353046299159
8 "body"                           96.5760207557808
9 "survived"                        0.481532018641288
10 "pclass"                         0.842485636190292
11 "parch"                          0.868604707790392
12 "fare"                           52.6460729831293
13 "sibsp"                          1.04111727241629

```

8.1.4.84 sum

```

1 vDataframe.sum(self, columns: list = [])

```

Aggregate the different columns by computing the sum of each one.

Parameters

- **columns:** *<list>*, optional
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesample` type containing the sums (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic.sum()

5 #Output
                                     sum
7 "age"                            30062.0
8 "body"                           19369.0
9 "survived"                        450.0
10 "pclass"                         2819.0
11 "parch"                           467.0
12 "fare"                           41877.3576
13 "sibsp"                           622.0

```

8.1.4.85 tail

```
vDataframe.tail(self, limit: int = 5, offset: int = 0)
```

Returns a part of the vDataframe. The tail is not necessary the end of the object.

Parameters

- **limit:** *<int>*, optional
The number of elements to return.
- **offset:** *<int>*, optional
The number of elements to skip.

Returns

The `tablesample` type containing the tail of the vDataframe (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```
1 from vertica_ml_python.learn.datasets import load_smart_meters
  sm = load_smart_meters(cur)
3 sm.tail(limit = 10, offset = 1000)

5 #Output
      time          val      id
7 1000  2014-02-22 16:00:00  0.1250000  9
  1001  2014-02-22 16:30:00  0.8130000  5
9 1002  2014-02-22 18:00:00  0.3360000  3
  1003  2014-02-22 19:30:00  0.3020000  5
11 1004  2014-02-22 20:00:00  0.6970000  0
  1005  2014-02-22 21:45:00  0.2960000  8
13 1006  2014-02-22 21:45:00  0.3090000  9
  1007  2014-02-22 22:00:00  0.3390000  4
15 1008  2014-02-22 22:30:00  0.3500000  1
  1009  2014-02-22 23:15:00  0.5830000  8
17 ...          ...          ...
Name: smart_meters, Number of rows: 11844, Number of columns: 3
```

8.1.4.86 time_on_off

```
vDataframe.time_on_off(self)
```


Prints all the vDataframe queries elapsed time. If it is already enable, it will turn it off.

Returns

The vDataframe itself.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic.time_on_off()
  titanic.max()
5
  #Output
7 Elapsed Time: 0.009672880172729492
  -----
```

8.1.4.87 to_csv

```
vDataframe.to_csv(
2     self,
      name: str,
4     path: str = '',
      sep: str = ',',
6     na_rep: str = '',
      quotechar: str = '"',
8     usecols: list = [],
      header: bool = True,
10     new_header: list = [],
      order_by: list = [],
12     nb_row_per_work: int = 0)
```

Create a csv file from the vDataframe relation.

Parameters

- **name:** <str>
File Name.
- **path:** <str>, optional
File Path.
- **sep:** <str>, optional
Elements separator.
- **na_rep:** <str>, optional
How to represent missing values.

- **quotechar:** *<str>*, optional
How to enclose the varchar.
- **usecols:** *<list>*, optional
Columns to use to write the csv file. If it is empty, all the vDataframe columns will be used.
- **header:** *<bool>*, optional
Write the header.
- **new_header:** *<list>*, optional
Replace the default header by a new one.
- **order_by:** *<list>*, optional
Order the elements using specific columns before writing.
- **nb_row_per_work:** *<int>*, optional
Number of rows to be read during each process of the loop. This parameter can lead to a partially wrong csv files if the data are not sorted correctly. Leave it to 0 to read the entire file on one time.

Returns

The vDataframe itself.

8.1.4.88 to_db

```

vDataframe.to_db(
2     self
    name: str,
4     usecols: list = [],
    relation_type: str = "view",
6     inplace: bool = False)

```

Save the vDataframe relation in the Database. The vDataframe will be then recreated from scratch using the new relation.

Parameters

- **name:** *<str>*
Name of the new relation.
- **usecols:** *<list>*, optional
List of the vDataframe columns to use.
- **relation_type:** *<str>*, optional
The relation type. This parameter can be a 'view' or a 'table'.
- **inplace:** *<bool>*, optional
Load the new relation in the vDataframe.

Returns

The vDataframe itself.

8.1.4.89 to_pandas

```
vDataframe.to_pandas(self)
```

Convert the vDataframe to a pandas.DataFrame. Be careful, if the volume is huge it can break down the system.

Returns

The pandas.DataFrame of the vDataframe.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
   titanic = load_titanic(cur)
3 titanic.to_pandas()

5 #Output
   age  body  survived  ticket  home.dest \
7 0  2.000   NaN        0  113781 Montreal, PQ / Chesterville, ON
  1 30.000 135.0        0  113781 Montreal, PQ / Chesterville, ON
9 2 25.000   NaN        0  113781 Montreal, PQ / Chesterville, ON
  3 39.000   NaN        0  112050 Belfast, NI
11 4 71.000  22.0        0 PC 17609 Montevideo, Uruguay

13      cabin  sex  pclass embarked  parch  fare \
  0 C22 C26  female        1         S      2 151.55000
15 1 C22 C26   male        1         S      2 151.55000
  2 C22 C26  female        1         S      2 151.55000
17 3   A36   male        1         S      0  0.00000
  4   None   male        1         C      0 49.50420

19
                                     name  boat  sibsp
21 0                    Allison, Miss. Helen Loraine  None    1
  1                    Allison, Mr. Hudson Joshua Creighton  None    1
23 2  Allison, Mrs. Hudson J C (Bessie Waldo Daniels)  None    1
  3                    Andrews, Mr. Thomas Jr  None    0
25 4                    Artagaveytia, Mr. Ramon  None    0
[1234 rows x 14 columns]
```

8.1.4.90 to_vdf

```
vDataframe.to_vdf(self, name: str)
```

Save the vDataframe to the vdf format. You can use read_vdf to read this file type and load the vDataframe.

Parameters

- **name:** <str>
Name of the vdf file

Returns

The vDataframe itself.

8.1.4.91 var

```
1 vDataframe.var(self, columns: list = [])
```

Aggregate the different columns by computing the variance of each one.

Parameters

- **columns:** <list>, optional
List of the vDataframe columns. If this parameter is empty, the method will consider all the numerical columns.

Returns

The `tablesampl` type containing the var (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
   titanic = load_titanic(cur)
3 titanic.var()

5 #Output
                                variance
7 "age"                208.378019758472
   "body"              9326.92778502101
9  "survived"          0.231873084976754
   "pclass"            0.709782047186962
11 "parch"             0.754474138395633
   "fare"              2771.60900054498
13 "sibsp"             1.08392517492353
```

8.1.4.92 version

```
1 vDataframe.version(self)
```

Returns the Vertica DB version and useful information on the vDataframe.

Example

```

1 titanic.version()

3 #Output

5 #
6 # VERTICA-ML-PYTHON
7 #
8 # Author: Badr Ouali, Datascientist at Vertica
9 #
10 # You are currently using Vertica Analytic Database v9.2.1-0
11 #
12 # You have a perfectly adapted version for using vDataframe and Vertica ML
13 #
14 # For more information about the vDataframe you can use the help() method
15 (9, 2)

```

8.2 Virtual Column

8.2.1 attributes

When the vDataframe is created, it will create as many vColumn as there are columns in the input relation. The vColumn has only 3 attributes.

- **parent**: the vColumn parent (must be a vDataframe).
- **alias**: the alias of the column.
- **transformations**: list of all the Virtual Column transformations.

The vColumn will be represented by vDataframe[] as they are the Virtual Dataframe main attributes.

8.2.2 methods

8.2.2.1 abs

```

1 vDataframe[].abs(self)

```

Apply the abs function to the column elements.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
           x) UNION ALL (SELECT -9 AS x)) z"

```

```

3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
  vdf["x"]
5
  #Output
7      x
0      5
9      -1
2      2
11     -9
  Name: x, Number of rows: 4, dtype: int
13
  vdf["x"].abs()
15
  #Output
17      x
0      5
19     1
2      2
21     9
  Name: x, Number of rows: 4, dtype: int

```

8.2.2.2 add

```
vDataframe[].add(self, x: float)
```

Add a float to the column elements.

Parameters

- **x:** <float>
A float number.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
    x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
  vdf["x"]
5
  #Output
7      x

```

```

0      5
9      -1
2      2
11     -9
Name: x, Number of rows: 4, dtype: int

13
vdf["x"].add(x = 2)

15
#Output
17      x
0      7
19     1
2      4
21     -7
Name: x, Number of rows: 4, dtype: int

```

8.2.2.3 add_copy

```
vDataframe[].add_copy(self, name: str)
```

Add a column copy to the vDataframe.

Parameters

- **name:** <str>
Copy name.

Returns

The vColumn copy.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
      x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
      x
7 0      5
1 1     -1
9 2      2
3 3     -9
11 Name: x, Number of rows: 4, dtype: int

```

```

13 vdf["x"].add_copy(name = "y")

15 #Output
      x      y
17 0      5      5
18 1     -1     -1
19 2      2      2
20 3     -9     -9
21 Name: VDF, Number of rows: 4, Number of columns: 2

```

8.2.2.4 add_prefix

```
1 vDataframe[].add_prefix(self, prefix: str)
```

Add a prefix to each of the column element.

Parameters

- **prefix:** <str>
The prefix.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
      x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
  vdf["x"]

5 #Output
      x
7 0      5
9 1     -1
10 2      2
11 3     -9
  Name: x, Number of rows: 4, dtype: int

13 vdf["x"].add_prefix(prefix = "elem_")

15 #Output
      x
17 0    elem_5

```



```

19 1      elem_-1
2      elem_2
21 3      elem_-9
Name: x, Number of rows: 4, dtype: varchar(25)

```

8.2.2.5 add_suffix

```
vDataframe[].add_suffix(self, suffix: str)
```

Add a suffix to each of the column element.

Parameters

- **suffix:** <str>
The suffix.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
      x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
vdf["x"]
5
#Output
7      x
0      5
9      -1
2      2
11     -9
Name: x, Number of rows: 4, dtype: int
13
vdf["x"].add_suffix(prefix = "_end")
15
#Output
17      x
0     5_end
19    -1_end
2     2_end
21    -9_end
Name: x, Number of rows: 4, dtype: varchar(24)

```

8.2.2.6 aggregate / agg

```
vDataframe.aggregate(self, func: list)
```

Aggregate the columns using the input aggregations.

Parameters

- **func:** *<list>*
List of the different aggregations.

Returns

The `tablesampl` type containing the aggregations (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataframe` using the `to_vdf` method.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
   titanic = load_titanic(cur)
3 titanic["age"].agg(["sum", "min"])

5 #Output
   "age"
7 sum      30062.0
  min         0.33
```

8.2.2.7 apply

```
vDataframe.apply(self, func: str, copy: bool = False, copy_name: str = "")
```

Apply the input function to the column.

Parameters

- **func:** *<str>*
The function to apply. The function's variable must be written using flower brackets '{}' (Example: EXP({}))
- **copy:** *<bool>*, optional
Create a copy of the column in the `vDataframe` and apply the function on it.
- **copy_name:** *<str>*, optional
Copy name.

Returns

The parent `vDataframe`.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 1 AS x, 4 AS y) UNION ALL (SELECT 2 AS x, 9 AS y)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
      x      y
7 0     1     4
  1     2     9
9 Name: VDF, Number of rows: 2, Number of columns: 2

11 vdf["x"].apply('EXP({})')

13 #Output
              x      y
15 0  2.71828182845905    4
  1  7.38905609893065    9
17 Name: VDF, Number of rows: 2, Number of columns: 2

```

8.2.2.8 astype

```

1 vDataframe[].astype(self, dtype: str)

```

Convert the column to a new data type.

Parameters

- **dtype:** <str>
The new data type.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
      x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
  vdf["x"].dtype()

5 #Output
7 int

9 vdf["x"].astype(dtype = "varchar(3)").dtype()

```

```
11 #Output
    varchar(3)
```

8.2.2.9 avg / mean

```
vDataframe[].avg(self)
```

Returns the column average.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["age"].avg()

5 #Output
  30.1524573721163
```

8.2.2.10 bar

```
vDataframe[].bar(
2     self,
    method: str = "density",
4     of: str = "",
    max_cardinality: int = 6,
6     bins: int = 0,
    h: float = 0,
8     color: str = '#214579')
```

Draw the column bar chart.

Parameters

- **method:** <str>, optional
count | density | avg | min | max | sum
count: count is used as aggregation
density (default): density is used as aggregation
avg | min | max | sum: these aggregations are used only if "of" is informed
- **of:** <str>, optional
The column used to compute the aggregation. This variable is used only if "method" in {avg | min | max | sum}
- **max_cardinality:** <int>, optional
The maximum cardinality of the column. Under this number the column is automatically considered as categorical.


- **bins:** *<int>*, optional
The number of bins of the histogram.
- **h:** *<float>*, optional
The interval size of the column. It is used if the column is numerical. In the other case, if h is not informed. The best "h" will be computed automatically. If the column is a date, h represents the interval size in seconds.
- **color:** *<str>*, optional
The histogram color.

Returns

The parent vDataFrame.

Example

```
from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
titanic["fare"].bar()
```



8.2.2.11 boxplot

```
1 vDataFrame[].boxplot(
    self,
3     by: str = "",
    h: float = 0,
5     max_cardinality: int = 8,
    cat_priority: list = [])
```

Draw the column boxplot.

Parameters


- **by:** *<str>*, optional
The group by column. It is uses to split the different categories to draw a multi boxplot.
- **max_cardinality:** *<int>*, optional
The maximum cardinality of the column. Under this number the column is automatically considered as categorical.
- **h:** *<float>*, optional
The interval size of the column. It is used if the column is numerical. In the other case, if h is not informed. The best "h" will be computed automatically.
- **cat_priority:** *<list>*, optional
The principal categories to show.

Returns


The parent vDataframe.

Example

```
from vertica_ml_python.learn.datasets import load_titanic
titanic = load_titanic(cur)
titanic["age"].boxplot()
```



```
titanic["age"].boxplot(by = "pclass")
```



8.2.2.12 category

```
1 vDataframe[].category(self)
```

Returns the column category.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["name"].category()
5 #Output
  text
```

8.2.2.13 clip

```
vDataframe[].clip(self, lower = None, upper = None)
```

Clip the data by transforming the values lesser than the lower bound to the lower bound itself and the values higher than the upper bound to the upper bound itself. The column will be transformed.

Parameters

- **lower:** <float>, optional
Lower bound.

- **upper:** *<float>*, optional
Upper bound.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
    x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
      x
7 0    5
  1   -1
9 2    2
  3   -9
11 Name: x, Number of rows: 4, dtype: int

13 vdf["x"].clip(lower = -1, upper = 1)

15 #Output
      x
17 0    1
  1   -1
19 2    1
  3   -1
21 Name: x, Number of rows: 4, dtype: int

```

8.2.2.14 count

```

1 vDataframe[].count(self)

```

Returns the column count (number of non-NULL elements).

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["age"].count()

5 #Output
  997

```


8.2.2.15 date_part

```
vDataframe[].date_part(self, field: str)
```

Extract a specific field from the column (only if the column is a timestamp). The column will be transformed.

Parameters

- **field:** <str>

The field to extract. It can be in {CENTURY | DAY | DECADE | DOQ | DOW | DOY | EPOCH | HOUR | ISODOW | ISOWEEK | ISOYEAR | MICROSECONDS | MILLENNIUM | MILLISECONDS | MINUTE | MONTH | QUARTER | SECOND | TIME_ZONE | TIMEZONE_HOUR | TIMEZONE_MINUTE | WEEK | YEAR}

Returns

The parent vDataframe.

Example

```
1 from vertica_ml_python.learn.datasets import load_smart_meters
2 sm = load_smart_meters(cur)
3
4 #Output
5
6      time      val  id
7 0  2014-01-01 01:15:00  0.0370000  2
8 1  2014-01-01 02:30:00  0.0800000  5
9 2  2014-01-01 03:00:00  0.0810000  1
10 3  2014-01-01 05:00:00  1.4890000  3
11 4  2014-01-01 06:00:00  0.0720000  5
12 ...      ...      ...      ...
13 Name: smart_meters, Number of rows: 11844, Number of columns: 3
14
15 sm["time"].date_part("month")
16
17 #Output
18
19      time      val  id
20 0      1  0.0370000  2
21 1      1  0.0800000  5
22 2      1  0.0810000  1
23 3      1  1.4890000  3
24 4      1  0.0720000  5
25 ...      ...      ...      ...
26 Name: smart_meters, Number of rows: 11844, Number of columns: 3
```

8.2.2.16 decode

```
vDataframe[].decode(self, values: dict, others = None)
```

Encode the data using the input bijection.

Parameters

- **values:** *<dict>*
Dictionary of values representing the bijection used to encode the data.
- **others:** *<float>*, optional
How to encode the values which are not in the dictionary of values.

Returns

The parent vDataframe.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic["sex"]
4
5 #Output
6
7      sex
8 0  female
9 1   male
10 2  female
11 3   male
12 4   male
13 ...
14 Name: sex, Number of rows: 1234, dtype: varchar(20)
15
16 titanic["sex"].decode(values = {"male": 1, "female": 0})
17
18 #Output
19
20      sex
21 0      0
22 1      1
23 2      0
24 3      1
25 4      1
26 ...
27 Name: sex, Number of rows: 1234, dtype: int
```

8.2.2.17 density

```
1 vDataframe[].density(  
    self,  
3     a = None,  
    kernel: str = "gaussian",  
5     smooth: int = 200,  
    color: str = '#214579')
```

Draw the column density plot.

Parameters


- **a:** *<float>*, optional
The kernel window. If it is not informed, an optimal one is computed.
- **kernel:** *<str>*, optional
gaussian (default) | logistic | sigmoid | silverman
The Kernel used for the plot.
- **smooth:** *<positive int>*, optional
The number of points used for the smoothing.
- **color:** *<str>*, optional
The density plot color.

Returns

The parent vDataframe.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic  
2 titanic = load_titanic(cur)  
titanic["age"].density()
```



8.2.2.18 describe

```
vDataframe[].describe(method: str = "auto", max_cardinality: int = 6, numcol:
    str = "")
```

Summarise the column with mathematical information.

Parameters

- **method:** <str>, optional
 auto | categorical | numerical | cat_stats
 auto (default): This mode is used to detect the correct category.
 numerical: This mode is used to print numerical information if it is possible.
 categorical: This mode is used to only print the categorical variables information (text or *cardinality* \leq *max_cardinality*).
 cat_stats: This mode is used to compute descriptive statistics of the 'numcol'
- **max_cardinality:** <bool>, optional
 The maximum cardinality of the column. Under this number the column is automatically considered as categorical.
- **numcol:** <str>, optional
 Column to use to compute the descriptive statistics (only used when mode is 'cat_stats')

Returns

The `tablesampl` type containing the mathematical information (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataframe` using the `to_vdf` method.

Note

The mathematical information are different depending on the data type and if they are categorical.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["age"].describe()

5 #Output
                                     value
7 name                             "age"
  dtype          numeric(6,3)
9 unique                      96
  count                997.0
11 mean          30.1524573721163
  std           14.4353046299159
13 min              0.33
  25%              21.0
15 50%              28.0
  75%              39.0
17 max              80.0

19 titanic["pclass"].describe()

21 #Output
                                     value
23 name                             "pclass"
  dtype              int
25 unique                      3
  3                663
27 1                312
  2                259

```

8.2.2.19 discretize

```

1 def discretize(
2     self,
3     method: str = "auto",
4     h: float = 0,
5     bins: int = -1,
6     k: int = 6,
7     new_category: str = 'Others',
8     response: str = "",
9     temp_information: tuple = ("public.vml_temp_view", "public.
10    vml_temp_model"),
11     min_bin_size: int = 20)

```

Discretize the Virtual Column.

Returns

The parent vDataframe.

Parameters

- **method:** *<str>*, optional
 auto | same_width | same_freq | topk | smart
 auto (default): Use method same_width for numerical, cast the other types to varchar
 same_width: Compute regular width bins (only for numerical)
 same_freq: Compute bins with the same number of elements (only for numerical)
 topk: Keep the topk most frequent categories and merge the other into one unique category
 smart: Use the Random Forest on a response column to find the most relevant interval to use for the discretization
- **h:** *<float>*, optional
 The interval size to convert used to convert the column. If this parameter is equal to 0, an optimised interval will be computed.
- **bins:** *<int>*, optional
 Number of bins used for the discretization (must be > 1)
- **k:** *<int>*, optional
 The number of elements to keep when using the 'topk' method
- **new_category:** *<str>*, optional
 The name of the remaining category when using the 'topk' method
- **response:** *<str>*, optional
 Response Column when using the 'smart' method
- **temp_information:** *<tuple>*, optional
 Tuple containing a view name and a model name used to store the Virtual Dataframe in a temporary view and the temporary RF model used to find the splitting values. These elements will be dropped at the end of the computation.
- **min_bin_size:** *<int>*, optional
 Minimum Number of elements in the bin when sing the 'smart' method

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic["fare"]
4
5 #Output
6      fare
7 0    151.55000
8 1    151.55000
9 2    151.55000
10 3     0.00000
11 4    49.50420

```

```

12 ...      ...
Name: fare, Number of rows: 1234, dtype: numeric(10,5)
14
16 titanic["fare"].discretize()
18
19 #Output
20      fare
0      [141;188]
21      [141;188]
22      [141;188]
23      [0;47]
24      [47;94]
25 ...      ...
Name: fare, Number of rows: 1234, dtype: varchar

```

8.2.2.20 distinct

```
1 vDataframe[].distinct(self)
```

Returns all the columns distinct elements.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
titanic = load_titanic(cur)
3 titanic["pclass"].distinct()
5
5 #Output
[1, 2, 3]

```

8.2.2.21 divide / div

```
vDataframe[].divide(self, x: float)
```

Div the column by a float.

Parameters

- **x:** <float>
A float number (!= 0).

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
2 relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
3 x) UNION ALL (SELECT -9 AS x)) z"
4 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
5 vdf["x"]
6
7 #Output
8
9      x
10 0      5
11 1     -1
12 2      2
13 3     -9
14 Name: x, Number of rows: 4, dtype: int
15
16 vdf["x"].div(x = 5)
17
18 #Output
19
20      x
21 0      1.0000000000000000
22 1     -0.2000000000000000
23 2      0.4000000000000000
24 3     -1.8000000000000000
25 Name: x, Number of rows: 4, dtype: numeric(36,18)

```

8.2.2.22 donut

```

1 vDataframe[].donut (
2     self,
3     method: str = "density",
4     of: str = "",
5     max_cardinality: int = 6,
6     h: float = 0)

```

Draw the column donut chart.

Parameters

- **method:** <str>, optional
count | density | avg | min | max | sum
count: count is used as aggregation
density (default): density is used as aggregation
avg | min | max | sum: these aggregations are used only if "of" is informed
- **of:** <str>, optional
The column used to compute the aggregation. This variable is used only if "method" in {avg | min | max | sum}


- **max_cardinality:** *<positive int>*, optional
The maximum cardinality of the column. Under this number the column is automatically considered as categorical.
- **h:** *<float>*, optional
The interval size of the column. It is used if the column is numerical. In the other case, if h is not informed. The best "h" will be computed automatically. If the column is a date, h represents the interval size in seconds.

Returns

The parent vDataframe.

Example

```
from vertica_ml_python.learn.datasets import load_titanic
titanic = load_titanic(cur)
titanic["age"].donut()
```



8.2.2.23 drop

```
vDataframe[].drop(self)
```

Drop the column from the vDataframe.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 5 AS x, -1 AS y) UNION ALL (SELECT -1 AS x, 10 AS y)
    UNION ALL (SELECT 2 AS x, 3 AS y)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
      x      y
7 0      5     -1
  1     -1     10
9 2      2      3
Name: VDF, Number of rows: 3, Number of columns: 2

11 vdf["x"].drop()

13 #Output
      y
15 0     -1
17 1      10
  2       3
19 Name: y, Number of rows: 3, dtype: int

```

8.2.2.24 dropna

```

1 vDataFrame[].dropna(self)

```

Drop the elements having missing values.

Returns

The parent vDataFrame.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 5 AS x, -1 AS y) UNION ALL (SELECT NULL AS x, 10 AS y)
    UNION ALL (SELECT 2 AS x, 3 AS y)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
      x      y
7 0      5     -1
  1  None     10
9 2      2      3
Name: VDF, Number of rows: 3, Number of columns: 2

11

```

```
vdf["x"].dropna()

#Output
   x    y
0  5   -1
1  2    3
Name: VDF, Number of rows: 2, Number of columns: 2
```

8.2.2.25 drop_outliers

```
vDataframe[].drop_outliers(
    self,
    alpha: float = 0.05,
    use_threshold: bool = True,
    threshold: float = 4.0)
```

Drop the columns outliers.

Parameters

- **alpha:** *<float>*, optional
Number representing the outliers threshold. Values lesser than quantile(alpha) or greater than quantile(1-alpha) will be dropped.
- **use_threshold:** *<bool>*, optional
Use the threshold instead of the 'alpha' parameter
- **threshold:** *<float>*, optional
Use the Gaussian distribution to define the outliers. After normalizing the data, if the record is greater than the threshold it will be considered as an outlier.

Returns

The parent vDataframe.

Example

```
from vertica_ml_python.vdataframe import vdf_from_relation
relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS x) UNION ALL (SELECT -9 AS x) UNION ALL (SELECT -600 AS x) UNION ALL (SELECT 100000 AS x)) z"
vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
vdf["x"]

#Output
   x
0  5
1 -1
```

```

2          2
11         -9
4        -600
13       100000
Name: x, Number of rows: 6, dtype: int

15
vdf["x"].div(x = 5)
17
#Output
19      x
0      5
21     -1
2      2
23     -9
Name: x, Number of rows: 4, dtype: int

```

8.2.2.26 dtype

```
vDataframe[].dtype(self)
```

Returns the column data type.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["name"].dtype()
5
#Output
varchar(164)

```

8.2.2.27 ema

```
ema(self, ts: str, by: list = [], alpha: float = 0.5)
```

Compute the exponential moving average of the column using an input time series.

Parameters

- **ts:** <str>
The vDataframe time series.
- **by:** <list>, optional
How to group the data.

- **alpha:** *<float>*, optional
the EMA smoothing factor.

Returns


The parent vDataframe.

Example

```

1 from vertica_ml_python.learn.datasets import load_smart_meters
  sm = load_smart_meters(cur)
3 # Computing the cum sum of each home
  sm.cumsum(name = "val_cumsum", column = "val", by = ["id"], order_by = ["time"
    ])
5 # Building the features corresponding to the cum consumption of the home id 0
  sm.eval("id0", "DECODE(id, 0, val_cumsum, NULL)")
7 # Applying the EMA
  sm["id0"].ema(ts = "time", by = ["id"])
9 # Drawing the time series
  sm["id0"].plot(ts = "time")

```



8.2.2.28 equals / eq

```
vDataframe[].equals(self, x)
```

Verify if each element of the column is equal to the input element.

Parameters

- **x:** *<anytype>*
Float, int or varchar.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
    x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
vdf["x"]

5
#Output
7      x
0      5
9     -1
10     2
11    -9
Name: x, Number of rows: 4, dtype: int

13
vdf["x"].eq(x = -1)

15
#Output
17      x
0    False
19    True
2    False
21    False
Name: x, Number of rows: 4, dtype: boolean

```

8.2.2.29 fillna

```

vDataframe[].fillna(
2     self,
    val = None,
4     method: str = "auto",
    by: list = [],
6     order_by: list = [])

```

Fill the missing values using the input method. If the parameters val and method are empty, all the missing values will be filled automatically (using the average of the column for the numerical columns and the mode for the categorical ones)

Parameters

- **val:** <anytype>, optional
Constant value used to impute the column.

- method:** *<dict>*, optional
 Method used to impute the column.
 auto | avg | median | mode | ffill | backfill
 auto (default): average for numerical and mode for categorical.
 avg: Imputation using the column average.
 median: Imputation using the column median.
 mode: Imputation using the column mode (most occurrent element).
 ffill: Propagation of the first non-NULL element = constant interpolation (only for time series, *order_by* parameter must be defined).
 bfill: Back Propagation of the next non-NULL element = constant interpolation (only for time series, *order_by* parameter must be defined).
- by:** *<list>*, optional
 The columns used to group the main one.
- order_by:** *<list>*, optional
 The columns used to order the data (used only when method is bfill or ffill)

Returns

The parent vDataFrame.

Example

```

from vertica_ml_python.vdataframe import vdf_from_relation
2 relation = "((SELECT 5 AS x) UNION ALL (SELECT NULL AS x) UNION ALL (SELECT 2
    AS x) UNION ALL (SELECT NULL AS x) UNION ALL (SELECT -2 AS x) UNION ALL (
    SELECT 12 AS x)) z"
vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
4
#Output
6      x
0      5
8      None
2      2
10     None
4     -2
12     12
Name: x, Number of rows: 6, dtype: int
14
vdf["x"].fillna()
16
#Output
18      x
0     5.00
20     4.25
2     2.00
22     4.25
4     -2.00

```

```

24 5      12.00
    Name: x, Number of rows: 6, dtype: float

```

8.2.2.30 fill_outliers

```

1 vDataframe[].fill_outliers(
    self,
3     method: str = "winsorize",
    alpha: float = 0.05,
5     use_threshold: bool = True,
    threshold: float = 4.0)

```

Fill the outliers using the input method.

Parameters

- method:** *<dict>*, optional
 Method used to fill the column outliers.
 winsorize | null | mean
 winsorize (default): clip the data using as lower bound quantile(alpha) and as upper bound quantile(1-alpha).
 null: Replace the outliers by the NULL value.
 mean: Replace the upper and lower outliers by their respective average.
- alpha:** *<float>*, optional
 Number representing the outliers threshold. Values lesser than quantile(alpha) or greater than quantile(1-alpha) will be filled.
- use_threshold:** *<bool>*, optional
 Use the threshold instead of the 'alpha' parameter
- threshold:** *<float>*, optional
 Use the Gaussian distribution to define the outliers. After normalizing the data, if the record is greater than the threshold it will be considered as an outlier.

Returns

The parent vDataframe.

Example

```

from vertica_ml_python.vdataframe import vdf_from_relation
2 relation = "((SELECT 5 AS x) UNION ALL (SELECT 600 AS x) UNION ALL (SELECT 2
    AS x) UNION ALL (SELECT -100 AS x) UNION ALL (SELECT -2 AS x) UNION ALL (
    SELECT 12 AS x)) z"
vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
4
#Output
6      x
0      5

```



```

8 1      600
2      2
10 3     -100
4      -2
12 5      12
Name: x, Number of rows: 6, dtype: int

14 vdf["x"].fill_outliers(method = "null")

16 #Output

18      x
0      5
20 1     None
2      2
22 3     None
4      -2
24 5      12
Name: x, Number of rows: 6, dtype: int

```

8.2.2.31 ge

```
1 vDataframe[].ge(self, x: float)
```

Verify if each element of the column is greater or equal to the input element.

Parameters

- **x:** *<float>*
A numerical element.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
      x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
vdf["x"]

5 #Output

7      x
0      5
9 1     -1

```

```

2      2
11     -9
Name: x, Number of rows: 4, dtype: int

13
vdf["x"].ge(x = 2)

15
#Output

17      x
0      True
18     False
19     True
20     False
21
Name: x, Number of rows: 4, dtype: boolean

```

8.2.2.32 get_dummies

```

vDataframe[].get_dummies(
2     self,
3     prefix: str = "",
4     prefix_sep: str = "_",
5     drop_first: bool = True,
6     use_numbers_as_suffix: bool = False)

```

Compute the different columns dummies and add them to the vDataframe.

Parameters

- **prefix:** <str>, optional
Prefix of the dummies.
- **prefix_sep:** <str>, optional
Prefix delimiter of the dummies.
- **drop_first:** <bool>, optional
Drop the first dummy to avoid the creation of correlated features.
- **use_numbers_as_suffix:** <bool>, optional
Use numbers as suffix instead of the different categories.

Returns

The parent vDataframe.

Example

```

from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
titanic = titanic.select(["embarked"])

```

```

4
#Output
6     embarked
0          S
8          S
2          S
10         S
4          C
12     ...     ...
Name: embarked, Number of rows: 1234, dtype: varchar(20)
14
titanic["embarked"].get_dummies()
16
#Output
18     embarked     embarked_C     embarked_Q     embarked_S
20    0          S             0             0             1
22    1          S             0             0             1
24    2          S             0             0             1
    3          S             0             0             1
    4          C             1             0             0
    ...     ...             ...             ...             ...
Name: titanic, Number of rows: 1234, Number of columns: 4

```

8.2.2.33 gt

```
1 vDataframe[].gt(self, x: float)
```

Verify if each element of the column is greater to the input element.

Parameters

- **x:** *<float>*
A numerical element.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
      x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
vdf["x"]
5
#Output
7      x
0      5

```

```

9 1      -1
11 2       2
13 3      -9
   Name: x, Number of rows: 4, dtype: int

15 vdf["x"].gt(x = 2)

17 #Output
   x
0   True
1  False
2  False
21 3  False
   Name: x, Number of rows: 4, dtype: boolean

```

8.2.2.34 head

```
vDataframe[].head(self, limit: int = 5)
```

Returns the column head.

Parameters

- **limit:** <int>, optional
The number of elements to return.

Returns

The `tablesample` type containing the column head (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataframe` using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
   titanic = load_titanic(cur)
3 titanic["fare"].head(limit = 5)

5 #Output
   fare
7 0    151.55000
  1    151.55000
9 2    151.55000
  3     0.00000
11 4    49.50420
   ...
13 Name: fare, Number of rows: 1234, dtype: numeric(10,5)

```

8.2.2.35 hist

```
1 vDataframe[].hist(  
    self,  
3    method: str = "density",  
    of: str = "",  
5    max_cardinality: int = 6,  
    bins: int = 0,  
7    h: float = 0,  
    color: str = '#214579')
```


Draw the column histogram.

Parameters

- **method:** *<str>*, optional
count | density | avg | min | max | sum
count: count is used as aggregation
density (default): density is used as aggregation
avg | min | max | sum: these aggregations are used only if "of" is informed
- **of:** *<str>*, optional
The column used to compute the aggregation. This variable is used only if "method" in {avg | min | max | sum}
- **max_cardinality:** *<int>*, optional
The maximum cardinality of the column. Under this number the column is automatically considered as categorical.
- **bins:** *<int>*, optional
The number of bins of the histogram.
- **h:** *<float>*, optional
The interval size of the column. It is used if the column is numerical. In the other case, if h is not informed. The best "h" will be computed automatically. If the column is a date, h represents the interval size in seconds.
- **color:** *<str>*, optional
The histogram color.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic  
2 titanic = load_titanic(cur)  
titanic["age"].hist()
```



8.2.2.36 isdate

```
1 vDataframe[].isdate(self)
```

Returns True if the column is a date.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic["age"].isdate()
4
5 #Output
6 False
```

8.2.2.37 isin

```
vDataframe.isin(self, val: list)
```

Verify if the different elements are in the column.

Parameters

- **val:** *<list>*
List of values to check.

Returns

The list containing the booleans

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 # We verify if there was someone having 18 years old and someone having 52
  years old
  titanic["age"].isin(val = ["18", "52"])
5
  #Output
7 [ True ,  True ]
```

8.2.2.38 isnum

```
1 vDataframe[].isnum(self)
```

Returns True if the column is numerical.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["age"].isnum()
5
  #Output
  True
```

8.2.2.39 kurtosis / kurt

```
vDataframe[].kurtosis(self)
```

Returns the column unbiased kurtosis using Fisher's definition.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["age"].kurt()
5
  #Output
  0.15689691331997
```

8.2.2.40 label_encode

```
vDataframe[].label_encode(self)
```

Encode the column using a bijection from the different categories to $[0, n - 1]$ (n being the number of elements).

Returns

The parent vDataframe.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic = titanic.select(["embarked"])

5 #Output
   embarked
7 0         S
  1         S
9 2         S
  3         S
11 4         C
   ...     ...
13 Name: embarked, Number of rows: 1234, dtype: varchar(20)

15 titanic["embarked"].label_encode()

17 #Output
   embarked
19 0         2
  1         2
21 2         2
  3         2
23 4         0
   ...     ...
25 Name: embarked, Number of rows: 1234, dtype: int
```

8.2.2.41 le

```
1 vDataframe[].le(self, x: float)
```

Verify if each element of the column is lesser or equal to the input element.

Parameters

- **x:** *<float>*
A numerical element.

Returns

The parent vDataFrame.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
      x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
vdf["x"]
5
#Output
7      x
0      5
9     -1
2      2
11    -9
Name: x, Number of rows: 4, dtype: int
13
vdf["x"].le(x = 2)
15
#Output
17      x
0    False
19    True
2    True
21    True
Name: x, Number of rows: 4, dtype: boolean

```

8.2.2.42 lt

```
vDataFrame[].lt(self, x: float)
```

Verify if each element of the column is lesser to the input element.

Parameters

- **x:** *<float>*
A numerical element.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
    x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
  vdf["x"]
5
#Output
7      x
0      5
9     -1
10     2
11    -9
Name: x, Number of rows: 4, dtype: int
13
vdf["x"].lt(x = 2)
15
#Output
17      x
0    False
19     True
2     False
21     True
Name: x, Number of rows: 4, dtype: boolean

```

8.2.2.43 mad

```
vDataframe[].mad(self)
```

Returns the median absolute deviation of the column.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["age"].mad()
5
#Output
8.0

```

8.2.2.44 mae

```
vDataframe[].mae(self)
```

Returns the mean absolute error (deviation) of the column.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["age"].mae()

5 #Output
  11.254785419447906
```

8.2.2.45 max

```
vDataframe[].max(self)
```

Returns the column max.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["age"].max()

5 #Output
  80.0
```

8.2.2.46 mean_encode

```
vDataframe[].mean_encode(self, response_column: str)
```

Encode the column using the average of the response column for the different categories.

Parameters

- **response_column:** <str>
The response column.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic = titanic.select(["embarked", "survived"])

5 #Output
      survived      embarked
7 0           0           S
  1           0           S
9 2           0           S
  3           0           S
11 4           0           C
   ...      ...      ...
13 Name: titanic, Number of rows: 1234, Number of columns: 2

15 titanic["embarked"].mean_encode(response_column = "survived")

17 #Output
      survived      embarked
19 0           1  0.537549407114625
  1           1  0.537549407114625
21 2           1  0.537549407114625
  3           1  0.537549407114625
23 4           1  0.537549407114625
   ...      ...      ...
25 Name: titanic, Number of rows: 1234, Number of columns: 2

```

8.2.2.47 median

```
1 vDataframe[].median(self)
```

Returns the column median.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["age"].median()

5 #Output

```

```
28.0
```

8.2.2.48 min

```
vDataframe[].min(self)
```

Returns the column min.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["age"].min()

5 #Output
  0.33
```

8.2.2.49 mod

```
vDataframe[].mod(self, n: int)
```

Apply the mod(n) function to the column elements.

Parameters

- **n:** *<int>*
An integer.

Returns

The parent vDataframe.

Example

```
1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
    x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
  vdf["x"]

5 #Output
7      x
0      5
9      -1
```

```

2      2
11     -9
Name: x, Number of rows: 4, dtype: int
13
vdf["x"].mod(n = 2)
15
#Output
17      x
0      1
19     -1
2      0
21     -1
Name: x, Number of rows: 4, dtype: int

```

8.2.2.50 mode

```
vDataframe[].mode(self, dropna: bool = True)
```

Returns the column mode (most occurrent element).

Parameters

- **dropna:** *<bool>*, optional
Do not consider null values as a category.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["pclass"].mode()
5
#Output
3

```

8.2.2.51 mul

```
vDataframe[].mul(self, x: float)
```

Multiply all the column elements by a float.

Parameters

- **x:** *<float>*
A number.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
      x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
vdf["x"]

5
#Output
7      x
0      5
9     -1
2      2
11     -9
Name: x, Number of rows: 4, dtype: int

13
vdf["x"].mul(x = 3)

15
#Output
17      x
0     15
19     -3
2      6
21     -27
Name: x, Number of rows: 4, dtype: int

```

8.2.2.52 neq

```
vDataframe[].neq(self, x)
```

Verify if each element of the column is not equal to the input element.

Parameters

- **x:** <anytype>
Float, int or varchar.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
      x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
vdf["x"]
5
#Output
7      x
0      5
9      -1
2      2
11     -9
Name: x, Number of rows: 4, dtype: int
13
vdf["x"].neq(x = -1)
15
#Output
17      x
0     True
19    False
2      True
21     True
Name: x, Number of rows: 4, dtype: boolean

```

8.2.2.53 next

```
vDataframe[].next(self, order_by: list, by: list = [])
```

Replace the element of the column by the next one.

Parameters

- **order_by:** <list>
How to order the data.
- **by:** <list>, optional
How to group the data.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.learn.datasets import load_smart_meters
sm = load_smart_meters(cur)

```



```

3 sm["val"].add_copy("next")
  sm["next"].next(order_by = ["time"], by = ["id"])
5
#Output
7
   time          val    id    next
0  2014-01-01 11:00:00  0.0290000  0  0.2770000
9  1  2014-01-01 13:45:00  0.2770000  0  0.3210000
2  2014-01-02 10:45:00  0.3210000  0  0.3050000
11 3  2014-01-02 11:15:00  0.3050000  0  0.3580000
4  2014-01-02 13:45:00  0.3580000  0  0.1150000
13 ...          ...          ...          ...
Name: smart_meters, Number of rows: 11844, Number of columns: 4

```

8.2.2.54 nlargest

```
vDataframe[].nlargest(self, n: int = 10)
```

Returns the n largest elements of the vDataframe sorting by a specific column.

Parameters

- **n:** <int>, optional
The number of elements to consider.

Returns

The `tablesampler` type containing the vDataframe n largest elements (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["fare"].nlargest()
5
#Output
7
   age    body  survived    ticket
0  36.000  None         1  PC 17755
1  58.000  None         1  PC 17755
9  35.000  None         1  PC 17755
   cabin    sex  pclass  embarked  parch    fare  \
11 0  B51 B53 B55   male         1         C         1  512.32920  \
   1  B51 B53 B55  female         1         C         1  512.32920  \
13 2      B101   male         1         C         0  512.32920  \
   name    boat  sibsp
15 0  Cardeza, Mr. Thomas Drake Martinez         3         0

```

```

1 Cardeza, Mrs. James Warburton Martine...      3      0
17 2 Lesurer, Mr. Gustave J                      3      0
Name: nlargest, Number of rows: 3, Number of columns: 14

```

8.2.2.55 normalize

```
vDataframe[].normalize(self, method: str = "zscore")
```

normalize the column with a specific method.

Parameters

- **method:** <str>, optional
zscore (default) | robust_zscore | minmax
The method used for the normalization.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["fare"].normalize()

5 #Output
                                     fare
7 0      2.2335228377568673306163744003
  1      2.2335228377568673306163744003
9 2      2.2335228377568673306163744003
  3     -0.6451344183800711827483251581
11 4      0.2951864297839290254556257484
   ...
13 Name: fare, Number of rows: 1234, dtype: float

```

8.2.2.56 nsmaallest

```
vDataframe[].nsmaallest(self, n: int = 10)
```

Returns the n smallest elements of the vDataframe sorting by a specific column.

Parameters

- **n:** *<int>*, optional
The number of elements to consider.

Returns

The `tablesample` type containing the `vDataframe` `n` smallest elements (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataframe` using the `to_vdf` method.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
   titanic = load_titanic(cur)
3 titanic["fare"].nsmallest()

5 #Output
   age      body  survived  ticket
7 0   39.000    None         0   112050
  1    None    None         0   112051
  2    None    None         0   112058
   cabin  sex  pclass  embarked  parch  fare  \
11 0    A36  male      1         S      0  0.00000  \
  1    None  male      1         S      0  0.00000  \
13 2    B102  male      1         S      0  0.00000  \
   name  boat  sibsp
15 0  Andrews, Mr. Thomas Jr    None      0
  1  Chisholm, Mr. Roderick Robert Crispin    None      0
17 2  Fry, Mr. Richard    None      0
Name: nsmallest, Number of rows: 3, Number of columns: 14
```

8.2.2.57 numh

```
vDataframe[].numh(self, method: str = "auto")
```

Returns the interval size to convert the column to categorical using a specific method.

Parameters

- **method:** *<str>*, optional
auto | sturges | freedman_diaconis
auto (default): max of the interval computed by the two available method.
sturges: Use Sturges definition of the best h.
freedman_diaconis: Use Freedman Diaconis definition of the best h.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["fare"].numh()

5 #Output
  47
```

8.2.2.58 nunique

```
vDataframe[].nunique(self, approx: bool = False)
```

Returns the column cardinality.

Parameters

- **approx:** *<bool>*, optional
Returns the approximate cardinality instead of the exact one.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["pclass"].nunique()

5 #Output
  3
```

8.2.2.59 pct_change

```
vDataframe[].pct_change(self, order_by: list, by: list = [])
```

Compute the ratio between the current value and the previous one. The column will be transformed.

Parameters

- **order_by:** *<list>*
The list of elements to order the vDataframe during the process.
- **by:** *<list>*, optional
The columns used to group the main column.

Example

```

1 from vertica_ml_python.learn.datasets import load_smart_meters
  sm = load_smart_meters(cur)
3
4 #Output
5
6      time      val      id
7 0  2014-01-01 01:15:00  0.0370000  2
8 1  2014-01-01 02:30:00  0.0800000  5
9 2  2014-01-01 03:00:00  0.0810000  1
10 3  2014-01-01 05:00:00  1.4890000  3
11 4  2014-01-01 06:00:00  0.0720000  5
12 ...
13 Name: smart_meters, Number of rows: 11844, Number of columns: 3
14
15 sm["val"].pct_change(order_by = ["time"], by = ["id"])
16
17 #Output
18
19      time      val      id
20 0  2014-01-01 11:00:00  9.551724137931034483  0
21 1  2014-01-01 13:45:00  1.158844765342960289  0
22 2  2014-01-02 10:45:00  0.950155763239875389  0
23 3  2014-01-02 11:15:00  1.173770491803278689  0
24 4  2014-01-02 13:45:00  0.321229050279329609  0
25 ...
26 Name: smart_meters, Number of rows: 11844, Number of columns: 3

```

8.2.2.60 pie

```

1 vDataframe[].pie(
2     self,
3     method: str = "density",
4     of: str = "",
5     max_cardinality: int = 6,
6     h: float = 0)

```

Draw the column pie chart.

Parameters

- method:** <str>, optional
 count | density | avg | min | max | sum
 count: count is used as aggregation
 density (default): density is used as aggregation
 avg | min | max | sum: these aggregations are used only if "of" is informed
- of:** <str>, optional
 The column used to compute the aggregation. This variable is used only if "method" in {avg | min | max | sum}


- **max_cardinality:** *<positive int>*, optional
The maximum cardinality of the column. Under this number the column is automatically considered as categorical.
- **h:** *<float>*, optional
The interval size of the column. It is used if the column is numerical. In the other case, if h is not informed. The best "h" will be computed automatically. If the column is a date, h represents the interval size in seconds.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic["pclass"].pie()

```



8.2.2.61 plot

```

1 vDataframe[].plot(
2     self,
3     ts: str,
4     by: str,
5     start_date: str = "",
6     end_date: str = "",
7     color: str = '#214579',
8     area: bool = False)

```

Plot the time series of the column.

Parameters

- **ts:** *<str>*
The time series used to plot the different elements.
- **by:** *<str>*, optional
The column to group with.
- **start_date:** *<str>*, optional
Start Date.
- **end_date:** *<str>*, optional
End Date.
- **color:** *<str>*, optional
Plot color.
- **area:** *<bool>*, optional
To plot an area plot.

Returns


The parent vDataframe.

Example


```

1 from vertica_ml_python.learn.datasets import load_smart_meters
2 sm = load_smart_meters(cur)
3 # Computing the cum sum of each home
4 sm.cumsum(name = "val_cumsum", column = "val", by = ["id"], order_by = ["time"]
5         )
6 # Building the features corresponding to the cum consumption of the home id 0
7 sm.eval("id0", "DECODE(id, 0, val_cumsum, NULL)")
8 # Drawing the time series
9 sm["id0"].plot(ts = "time")


```



```
sm["id0"].plot(ts = "time", area = True)
```



```
1 # Plot by grouping by id
sm.cumsum(name = "val_cumsum", column = "val", by = ["id"], order_by = ["time"]
2 ).filter("id <= 2")
3 sm["val_cumsum"].plot(ts = "time", by = "id")
```



8.2.2.62 pow

```
vDataframe[].pow(self, x: float)
```

Apply the pow(x) function to the column elements.

Parameters

- **x:** <float>
A float representing the power exponent.

Returns

The parent vDataframe.

Example

```
1 from vertica_ml_python.vdataframe import vdf_from_relation
relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
      x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
vdf["x"]
5
#Output
7      x
0      5
9     -1
2      2
11    -9
Name: x, Number of rows: 4, dtype: int
13
vdf["x"].pow(x = 2)
15
#Output
17      x
0    25.0
19     1.0
2      4.0
21    81.0
Name: x, Number of rows: 4, dtype: float
```

8.2.2.63 prev

```
vDataframe[].prev(self, order_by: list, by: list = [])
```

Replace the element of the column by the previous one.

Parameters

- **order_by:** *<list>*
How to order the data.
- **by:** *<list>*, optional
How to group the data.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.learn.datasets import load_smart_meters
  sm = load_smart_meters(cur)
3 sm["val"].add_copy("prev")
  sm["next"].prev(order_by = ["time"], by = ["id"])
5
#Output
7
   time          val    id    prev
0  2014-01-01 11:00:00  0.0290000  0    None
9  1  2014-01-01 13:45:00  0.2770000  0    0.0290000
2  2  2014-01-02 10:45:00  0.3210000  0    0.2770000
11 3  2014-01-02 11:15:00  0.3050000  0    0.3210000
4  4  2014-01-02 13:45:00  0.3580000  0    0.3050000
13 ...          ...          ...    ...
Name: smart_meters, Number of rows: 11844, Number of columns: 4

```

8.2.2.64 product / prod

```
vDataframe[].prod(self)
```

Returns the column product.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["survived"].prod()
5
#Output
0.0

```

8.2.2.65 quantile

```
vDataframe[].quantile(self, x: float)
```

Returns the column selected quantile.

Parameters

- **x:** *<float>*
A float living in [0,1] representing the quantile.

Example

```
1 from vertica_ml_python.vdataframe import vdf_from_relation
2 relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
   x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
4 vdf["x"]
5
6 #Output
7      x
8 0      5
9 1     -1
10 2      2
11 3     -9
12 Name: x, Number of rows: 4, dtype: int
13
14 vdf["x"].quantile(x = 0.1)
15
16 #Output
17 -6.6
```

8.2.2.66 rename

```
1 vDataframe[].rename(self, new_name: str)
```

Change the column alias.

Parameters

- **new_name:** *<str>*
New alias.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
    x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

5 #Output
      x
7 0    5
  1   -1
9 2    2
  3   -9
11 Name: x, Number of rows: 4, dtype: int

13 vdf["x"].rename(new_name = "y")

15 #Output
      y
17 0    5
  1   -1
19 2    2
  3   -9
21 Name: y, Number of rows: 4, dtype: int

```

8.2.2.67 round

```

1 vDataframe[].round(self, n: int)

```

Round the column elements with the input integer.

Parameters

- **n:** *<int>*
The integer used to round the column elements.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = relation = "((SELECT 5.12132 AS x) UNION ALL (SELECT -1.213 AS x)
    UNION ALL (SELECT 2.12347 AS x) UNION ALL (SELECT -9.965 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")

```

```

vdf["x"]
5
#Output
7
      x
0      5.12132
9      -1.21300
2       2.12347
11     -9.96500
Name: x, Number of rows: 4, dtype: numeric(6,5)
13
vdf["x"].round(n = 1)
15
#Output
17
      x
0      5.10000
19     -1.20000
2       2.10000
21     -10.00000
Name: x, Number of rows: 4, dtype: numeric(6,5)

```

8.2.2.68 sem

```
vDataframe[].sem(self)
```

Returns the column unbiased standard error of the mean.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["fare"].std()
5
#Output
1.49928585339507

```

8.2.2.69 skewness / skew

```
vDataframe[].skewness(self)
```

Returns the column unbiased skewness.

Example

```
1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["age"].skew()

5 #Output
  0.408876460779437
```

8.2.2.70 slice

```
slice(self, length: int, unit: str = "second", start: bool = True)
```

Slice the time series.

Parameters

- **length:** *<int>*
Slice size.
- **unit:** *<str>*, optional
Slice size unit.
- **start:** *<bool>*, optional
Consider the floor of the slicing or the next one.

Returns

The parent vDataframe.

Example

```
1 from vertica_ml_python.learn.datasets import load_smart_meters
  sm = load_smart_meters(cur)
3 sm["time"]

5 # Output

7           time
0    2014-01-01 01:15:00
9    2014-01-01 02:30:00
2    2014-01-01 03:00:00
11   2014-01-01 05:00:00
4    2014-01-01 06:00:00
13   ...          ...
   Name: time, Number of rows: 11844, dtype: timestamp

15 sm["time"].slice(length = "1", unit = "hour")
17
```

```

# Output
19
21
23
25
27
    time
0    2014-01-01 01:00:00
1    2014-01-01 02:00:00
2    2014-01-01 03:00:00
3    2014-01-01 05:00:00
4    2014-01-01 06:00:00
...
Name: time, Number of rows: 11844, dtype: timestamp

```

8.2.2.71 std

```
1 vDataframe[].std(self)
```

Returns the column standard deviation.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["fare"].std()

5 #Output
  52.6460729831293

```

8.2.2.72 str_contains

```
vDataframe[].str_contains(self, pat: str)
```

Verify if a regular expression is in each of the column elements. The column will be transformed.

Parameters

- **pat:** <str>
The regular expression.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["name"]

5 #Output
                                name
7 0      Allison, Miss. Helen Loraine
  1      Allison, Mr. Hudson Joshua Creighton
9 2      Allison, Mrs. Hudson J C (Bessie Wald...
  3      Andrews, Mr. Thomas Jr
11 4      Artagaveytia, Mr. Ramon
   ...      ...
13 Name: name, Number of rows: 1234, dtype: varchar(164)

15 titanic["name"].str_contains(' ([A-Za-z+)\.\'')

17 #Output
      name
19 0      True
  1      True
21 2      True
  3      True
23 4      True
   ...      ...
25 Name: name, Number of rows: 1234, dtype: boolean

```

8.2.2.73 str_count

```

1 vDataframe[].str_count(self, pat: str)

```

Compute the number of times a regular expression is in each of the column elements. The column will be transformed.

Parameters

- **pat:** <str>
The regular expression.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)

```



```

3 titanic["name"]

5 #Output

                                name
7 0          Allison, Miss. Helen Loraine
  1      Allison, Mr. Hudson Joshua Creighton
9 2  Allison, Mrs. Hudson J C (Bessie Wald...
  3              Andrews, Mr. Thomas Jr
11 4          Artagaveytia, Mr. Ramon
   ...
13 Name: name, Number of rows: 1234, dtype: varchar(164)

15 titanic["name"].str_count(' ([A-Za-z]+)\.')

17 #Output

      name
19 0      1
  1      1
21 2      1
  3      1
23 4      1
   ...
25 Name: name, Number of rows: 1234, dtype: int

```

8.2.2.74 str_extract

```
1 vDataframe[].str_extract(self, pat: str)
```

Extract the regular expression in each of the column elements. The column will be transformed.

Parameters

- **pat:** <str>
The regular expression.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["name"]

5 #Output

```

```

7      name
0      Allison, Miss. Helen Loraine
1      Allison, Mr. Hudson Joshua Creighton
9 2      Allison, Mrs. Hudson J C (Bessie Wald...
3      Andrews, Mr. Thomas Jr
11 4      Artagaveytia, Mr. Ramon
...      ...
13 Name: name, Number of rows: 1234, dtype: varchar(164)

15 titanic["name"].str_extract(' ([A-Za-z]+)\.')

17 #Output
      name
19 0      Miss.
1      Mr.
21 2      Mrs.
3      Mr.
23 4      Mr.
...      ...
25 Name: name, Number of rows: 1234, dtype: varchar(164)

```

8.2.2.75 str_replace

```
1 vDataframe[].str_replace(self, to_replace: str, value: str = "")
```

Replace the regular expression in each of the column elements by another value. The column will be transformed.

Parameters

- **to_replace:** <str>
The regular expression to replace.
- **value:** <str>, optional
The new value.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
   titanic = load_titanic(cur)
3 titanic["name"]

5 #Output
      name

```

```

0           Allison, Miss. Helen Loraine
1       Allison, Mr. Hudson Joshua Creighton
2 Allison, Mrs. Hudson J C (Bessie Wald...
3           Andrews, Mr. Thomas Jr
11          Artagaveytia, Mr. Ramon
...
13 Name: name, Number of rows: 1234, dtype: varchar(164)

15 titanic["name"].str_replace(' ([A-Za-z]+)\.')

17 #Output
                                name
19 0           Allison, Helen Loraine
1       Allison, Hudson Joshua Creighton
21 2 Allison, Hudson J C (Bessie Waldo Dan...
3           Andrews, Thomas Jr
23 4           Artagaveytia, Ramon
...
25 Name: name, Number of rows: 1234, dtype: varchar(672)

```

8.2.2.76 str_slice

```
1 vDataframe[].str_slice(self, start: int, step: int)
```

Slice the column expression. The column will be transformed.

Parameters

- **start:** *<int>*
Where to start on the expression.
- **step:** *<int>*
The step to use (output expression length).

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
titanic = load_titanic(cur)
3 titanic["name"]

5 #Output
                                name
7 0           Allison, Miss. Helen Loraine
1       Allison, Mr. Hudson Joshua Creighton
9 2 Allison, Mrs. Hudson J C (Bessie Wald...
3           Andrews, Mr. Thomas Jr

```

```

11 4          Artagaveytia, Mr. Ramon
    ...
13 Name: name, Number of rows: 1234, dtype: varchar(164)

15 titanic["name"].str_slice(0, 5)

17 #Output
    name
19 0    Alli
    1    Alli
    2    Alli
    3    Andr
    4    Arta
    ...
25 Name: name, Number of rows: 1234, dtype: varchar(20)

```

8.2.2.77 sub

```
1 vDataframe[].sub(self, x: float)
```

Subtract a float from the column elements.

Parameters

- **x:** *<float>*
A float number.

Returns

The parent vDataframe.

Example

```

1 from vertica_ml_python.vdataframe import vdf_from_relation
  relation = "((SELECT 5 AS x) UNION ALL (SELECT -1 AS x) UNION ALL (SELECT 2 AS
    x) UNION ALL (SELECT -9 AS x)) z"
3 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
  vdf["x"]

5 #Output
7     x
9 0     5
  1    -1
  2     2
11 3    -9
  Name: x, Number of rows: 4, dtype: int

```

```

13 vdf["x"].sub(x = 2)
15
17 #Output
17      x
18 0      3
19 1     -3
20 2      0
21 3    -11
Name: x, Number of rows: 4, dtype: int

```

8.2.2.78 sum

```
vDataframe[].sum(self)
```

Returns the column sum.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
2 titanic = load_titanic(cur)
3 titanic["fare"].sum()
4
5 #Output
6 41877.3576

```

8.2.2.79 tail

```
vDataframe[].tail(self, limit: int = 5, offset: int = 0)
```

Returns a part of the column. The tail is not necessary the end of the object.

Parameters

- **limit:** *<int>*, optional
The number of elements to return.
- **offset:** *<int>*, optional
The number of elements to skip.

Returns

The `tablesample` type containing the tail (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataframe` using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["fare"].tail(limit = 4, offset = 10)

5 #Output
      fare
7 10    35.50000
  11    26.55000
9 12    30.50000
  13    50.49580
11 ...      ...
   Name: fare, Number of rows: 1234, dtype: numeric(10,5)

```

8.2.2.80 topk

```
vDataframe[].topk(self, k: int = -1, dropna: bool = True)
```

Returns the top k most occurrent column elements.

Parameters

- **k:** *<int>*, optional
Number of elements to consider. If this parameter is equal to -1, all the categories will be returned.
- **dropna:** *<bool>*, optional
Do not consider null values as a category.

Returns

The `tablesampl` type containing the column topk categories (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataframe` using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["pclass"].topk()

5 #Output
      count      percent
7 3         663  53.7277147487844
  1         312  25.2836304700162
9 2         259  20.9886547811994

```

8.2.2.81 to_timestamp

```
1 vDataframe[].to_timestamp(self)
```

Convert the column to timestamp.

Returns

The parent vDataframe.

Example

```
1 from vertica_ml_python.vdataframe import vdf_from_relation
2 relation = "((SELECT '2014-01-01' AS x) UNION ALL (SELECT '2014-02-09' AS x))
3           z"
4 vdf = vdf_from_relation(relation, dsn = "VerticaDSN")
5
6 #Output
7           x
8 0    2014-01-01
9 1    2014-02-09
10 Name: x, Number of rows: 2, dtype: varchar(10)
11
12 vdf["x"].to_timestamp()
13
14 #Output
15           x
16 0    2014-01-01 00:00:00
17 1    2014-02-09 00:00:00
18 Name: x, Number of rows: 2, dtype: timestamp
```

8.2.2.82 value_counts

```
1 vDataframe[].value_counts(self, k: int = 30)
```

Returns the top k most occurrent column elements and their respective count.

Parameters

- **k:** <int>, optional
Number of elements to consider. If this parameter is equal to -1, all the categories will be returned.

Returns

The `tablesample` type containing the value counts (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to vDataframe using the `to_vdf` method.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["pclass"].value_counts()

5 #Output
      value
7 name    "pclass"
  dtype      int
9 unique      3
   3         663
   1         312
11  2         259

```

8.2.2.83 var

```
vDataframe[].var(self)
```

Returns the column variance.

Example

```

1 from vertica_ml_python.learn.datasets import load_titanic
  titanic = load_titanic(cur)
3 titanic["fare"].var()

5 #Output
2771.60900054498

```

9 vertica_ml_python.learn

This part of the API was built to apply Highly Distributed and Scalable Machine Learning directly on the data. Many algorithms are available and many metrics are very useful to evaluate precisely the efficiency and performance of the created models. Some models are built-in Vertica functions (Highly Distributed and Highly Scalable) and others are based on SQL code generation. In the different sections some of the algorithms methods parameters could be undefined because of the repetitiveness of the process. We will always use the following notations:

- `X <str>`: List of the predictors columns.
- `y` or `y_true <str>`: Response column.
- `y_score <str>`: Prediction.
- `input_relation <str>`: Input relation used to train the model.

- `test_relation` <str>: Relation used to test the model. If it is empty, the train relation is used as test.
- `vdf` <object>: A Virtual Dataframe.
- `method` <str>: The method to compute the score, it must be in {accuracy | auc | prc_auc | best_cutoff | recall | precision | log_loss | negative_predictive_value | specificity | mcc | informedness | markedness | critical_success_index} for classification and in {r2 | mae (mean absolute error) | mse (mean squared error) | msle (mean squared log error) | max (max error) | median (median absolute error) | var (explained variance)} for regression.
- `cutoff` <float>: Prediction threshold in the case of binary classification. It must be in]0,1[
- `pos_label` <str or int>: Main class in the prediction (the positive class), the other classes will be seen as negative.
- `labels` <list>: Labels to consider during the computation.
- `tree_id` <int>: The tree ID in case of multi-tree models.

All the objects will have all its parameters stored as attribute. For example, it is possible to change the test relation anytime by changing the `test_relation` attribute.

9.1 vertica_ml_python.learn.cluster

9.1.1 DBSCAN

Create a DBSCAN object by using the DBSCAN algorithm as defined by Martin Ester, Hans-Peter Kriegel, Jörg Sander and Xiaowei Xu. This object is using pure SQL to compute all the distances and neighbors. It is also using Python to compute the cluster propagation (non scalable phase). This model is using CROSS JOIN and may be really expensive in some cases. It will index all the elements of the table in order to be optimal (the CROSS JOIN will happen only with IDs which are integers). As DBSCAN is using the p-distance, it is highly sensible to un-normalized data. However, DBSCAN is really robust to outliers and can find non-linear clusters. It is a very powerful algorithm for outliers detection and clustering.

initialization

```

class DBSCAN(
2   name: str,
   cursor,
4   eps: float = 0.5,
   min_samples: int = 5,
6   p: int = 2)

```

Parameters

- **name:** <str>
Name of the relation created after fitting the model.
- **cursor:** <object>
DB cursor.
- **eps:** <float>, optional
The radius of a neighborhood with respect to some point.

- **min_samples:** *<int>*, optional
Minimum number of points required to form a dense region.
- **p:** *<int>*, optional
The p corresponding to the one of the p-distance (distance metric used during the model computation).

Methods

The DBSCAN object has four main methods:

```

# Fit the model with the input columns
2 def fit(self, input_relation: str, X: list, key_columns: list = [], index = ""
    )

4 # Print the model information
def info(self)

6

# Plot the model (only possible if the number of columns <= 3)
8 def plot(self)

10 # Create a vDataframe using the final relation
def to_vdf(self)

```

The index parameter (name of the primary key column in the relation) of the 'fit' method is very important as without it an indexed copy of the main relation will be created (it could be really expensive). It is highly recommended to have a primary key column in the main table to avoid unnecessary computations.

Attributes

The DBSCAN object has two main attributes:

```

1 self.n_cluster # Number of clusters
self.n_noise # Number of elements considered as noise by the algorithm

```

Example

```

from vertica_ml_python import vDataframe
2 from vertica_ml_python.learn.cluster import DBSCAN

4 # Building a normalized relation of the features, we will use
titanic = vDataframe("titanic", cur)
6 # We will use a sample of the data in order to have a beautiful plot
titanic.main_relation += " TABLESAMPLE(10) "
8 titanic = titanic.select(["fare", "age"])
titanic.normalize()
10 titanic.to_db("titanic_normalize")

12 # We can build the model
model = DBSCAN("dbscan_titanic", cur)
14 model.fit("titanic_normalize", ["fare", "age"])


16 # We can see the different information relative to the model

```

```

model.info()
18
# Output
20 DBSCAN was successfully achieved by building 3 cluster(s) and by identifying
    21 elements as noise.
    If you are not happy with the result, do not forget to normalize the data
        before applying DBSCAN. As this algorithm is using the p-distance, it is
            really sensible to the data distribution.
22
# And Plot the model
24 model.plot()

```



9.1.2 KMeans

Create a KMEANS object by using the Vertica Highly Distributed and Scalable KMEANS directly on the data.

Initialization

```

class KMEANS (
2   name: str,
   cursor,
4   n_cluster: int = 8,
   init = "kmeanspp",
6   max_iter: int = 300,
   tol: float = 1e-4)

```

Parameters

- **name:** <str>
Name of the the model. The model is stored in the DB.

- **cursor:** *<object>*
DB cursor.
- **n_cluster:** *<int>*, optional
Number of clusters.
- **init:** *<str or list>*, optional
The method used to find the initial cluster centers. The method can be in {random | kmeanspp}. It can be also a list with the initial cluster centers to use.
- **max_iter:** *<int>*, optional
The maximum number of iterations the algorithm performs.
- **tol:** *<float>*, optional
Determines whether the algorithm has converged. The algorithm is considered converged after no center has moved more than a distance of 'tol' from the previous iteration.

Methods

The KMeans object has four main methods:

```

1 # Add the cluster prediction in a vDataFrame
  def add_to_vdf(self, vdf, name: str = "")
3
  # Drop the model
5 def drop(self)
7
  # Fit the model with the input columns
  def fit(self, input_relation: str, X: list)
9
  # Plot the model (only possible if the number of columns <= 3)
11 def plot(self)

```

Attributes

The KMEANS object has two main attributes:

```

1 self.cluster_centers # Position of the cluster centers
  self.metrics # Different metrics to evaluate the model

```

Example

```

  from vertica_ml_python.learn.cluster import KMeans
2
  # We can build the model
4 model = KMeans("kmeans_iris", cur, n_cluster = 3)
  model.fit("iris", ["PetalLengthCm", "SepalLengthCm"])
6
  # We can see the different metrics relative to the model
8 model.metrics
10
  # Output

```


value

```

12 Between-Cluster Sum of Squares          512.23072
   Total Sum of Squares                   566.03207
14 Total Within-Cluster Sum of Squares    53.801351
   Between-Cluster SS / Total SS         0.9049499969144859
16 converged                             True

18 # And Plot the model
   model.plot()

```



9.2 vertica_ml_python.learn.datasets

Many datasets are available to learn some Data Science basics or to test the API. These functions will store the data in the DB using the specific schema and table name.

9.2.1 load_amazon

```
load_amazon(cursor, schema: str = 'public', name = 'amazon')
```

Load and store the Amazon Dataset (Time Series and Regression).

9.2.2 load_iris

```
load_iris(cursor, schema: str = 'public', name = 'iris')
```

Load and store the Iris Dataset (Classification, Regression and Clustering).

9.2.3 load_smart_meters

```
1 load_smart_meters(cursor, schema: str = 'public', name = 'smart_meters')
```

Load and store the Iris Dataset Smart Meters Dataset (Time series and Clustering).

9.2.4 load_titanic

```
1 load_titanic(cursor, schema: str = 'public', name = 'titanic')
```

Load and store the Titanic Dataset (Classification and Regression).

9.2.5 load_winequality

```
1 load_winequality(cursor, schema: str = 'public', name = 'winequality')
```

Load and store the Wine Quality Dataset (Classification and Regression).

9.3 vertica_ml_python.learn.decomposition

9.3.1 PCA

Create a PCA object by using the Vertica Highly Distributed and Scalable PCA on the data.

initialization

```
1 class PCA(
2     name: str,
3     cursor,
4     n_components: int = 0,
5     scale: bool = False,
6     method: str = "Lapack")
```

Parameters

- **name:** <str>
Name of the model.
- **cursor:** <object>
DB cursor.
- **n_components:** <int>, optional
The number of components to keep in the model. If this value is not provided, all components are kept. The maximum number of components is the number of non-zero singular values returned by the internal call to SVD. This number is less than or equal to SVD (number of columns, number of rows).
- **scale:** <bool>, optional
A Boolean value that specifies whether to standardize the columns during the preparation step: If true use a correlation matrix instead of a covariance matrix.
- **method:** <str>, optional
The method used to calculate PCA, can be set to LAPACK.

Methods

The PCA object has 3 methods:

```

# Drop the model from the DB
2 def drop(self)

4 # Fit the model with the input columns
def fit(self, input_relation: str, X: list)

6 # Build a vdf from the output relation
8 def to_vdf(self, n_components: int = 0, cutoff: float = 1, key_columns: list
    = [], inverse: bool = False)

```

Attributes

The PCA object has only 3 attributes:

```

self.components # The principal components
2 self.explained_variance # The information about singular values found.
self.mean # The information about columns from the input relation used for
    creating the PCA model

```

Example

```

1 from vertica_ml_python.learn.decomposition import PCA

3 # We can build the model
model = PCA("pca_iris", cur)
5 model.fit("iris", ["SepalLengthCm", "SepalWidthCm", "PetalWidthCm", "
    PetalLengthCm"])

7 # We can evaluate the model
model.explained_variance

9 # Output
11
12         value      explained_variance  \
13 1      2.05544174529956      0.924616207174268  \
14 2      0.492182457659266      0.0530155678505349  \
15 3      0.280221177097938      0.0171851395250067  \
16 4      0.153892907978245      0.0051830854501896  \
17 accumulated_explained_variance
18 1      0.924616207174268
19 2      0.977631775024804
20 3      0.99481691454981

21 # We can export the model
model.to_vdf(n_components = 2)

23 # Output

```

```

25          col1          col2
0    -2.68420712510395    0.326607314764391
27    1    -2.71539061563413   -0.169556847556024
2    -2.88981953961792   -0.137345609605025
29    3    -2.74643719730873   -0.311124315751989
4    -2.72859298183131    0.333924563568457
31    ...          ...          ...
Name: pca_table_iris, Number of rows: 150, Number of columns: 2

```

9.3.2 SVD

Create a SVD object by using the Vertica Highly Distributed and Scalable SVD on the data.

initialization

```

class SVD(
2     name: str,
     cursor,
4     n_components: int = 0,
     method: str = "Lapack")

```

Parameters

- **name:** <str>
Name of the model.
- **cursor:** <object>
DB cursor.
- **n_components:** <int>, optional
The number of components to keep in the model. If this value is not provided, all components are kept. The maximum number of components is the number of non-zero singular values returned by the internal call to SVD. This number is less than or equal to SVD (number of columns, number of rows).
- **method:** <str>, optional
The method used to calculate SVD, can be set to LAPACK.

Methods

The SVD object has 3 methods:

```

1 # Drop the model from the DB
  def drop(self)
3
  # Fit the model with the input columns
5 def fit(self, input_relation: str, X: list)
7
  # Build a vdf from the output relation
  def to_vdf(self, n_components: int = 0, cutoff: float = 1, key_columns: list
    = [], inverse: bool = False)

```


Attributes

The SVD object has only 2 attributes:

```
self.singular_values # The right singular vectors.
self.explained_variance # The information about singular values found.
```

Example

```
from vertica_ml_python.learn.decomposition import SVD

# We can build the model
model = SVD("svd_iris", cur)
model.fit("iris", ["SepalLengthCm", "SepalWidthCm", "PetalWidthCm", "
    PetalLengthCm"])

# We can evaluate the model
model.explained_variance

# Output
      value      explained_variance  \
1  95.9506675123581      0.965429688562226  \
2  17.7229532787505      0.0329379703572465  \
3   3.46929666441398      0.00126213998717665  \
4   1.87891236262158      0.000370201093350833  \
      accumulated_explained_variance
1                0.965429688562226
2                0.998367658919472
3                0.999629798906649
4                  1.0

# We can export the model
model.to_vdf(n_components = 2)

# Output
      col1      col2
0  0.0616171171531346  -0.129969428300603
1  0.0580722976924328  -0.111371451741922
2  0.0567633851673065  -0.118294769303341
3  0.0566543139689709  -0.105607729117619
4  0.0612300644170471  -0.13143114177406
...      ...      ...
Name: svd_table_iris, Number of rows: 150, Number of columns: 2
```

9.4 vertica_ml_python.learn.ensemble

9.4.1 RandomForestClassifier

Create a RandomForestClassifier object by using the Vertica Highly Distributed and Scalable Random Forest on the data.

initialization

```

1 class RandomForestClassifier(
2     name: str,
3     cursor,
4     n_estimators: int = 10,
5     max_features = "auto",
6     max_leaf_nodes: int = 1e9,
7     sample: float = 0.632,
8     max_depth: int = 5,
9     min_samples_leaf: int = 1,
10    min_info_gain: float = 0.0,
11    nbins: int = 32)

```

Parameters

- **name:** <str>
Name of the the model. The model is stored in the DB.
- **cursor:** <object>
DB cursor.
- **n_estimators:** <int>, optional
The number of trees in the forest, an integer between 0 and 1000, inclusive.
- **max_features:** <int>, optional
The number of randomly chosen features from which to pick the best feature to split on a given tree node. If this parameter is equal to "auto", it will be equal to the square root of the total number of predictors.
- **max_leaf_nodes:** <int>, optional
The maximum number of leaf nodes a tree in the forest can have, an integer between 1 and 1e9, inclusive.
- **sample:** <float>, optional
The portion of the input data set that is randomly picked for training each tree, a FLOAT between 0.0 and 1.0, inclusive.
- **max_depth:** <int>, optional
The maximum depth for growing each tree, an integer between 1 and 100, inclusive.
- **min_samples_leaf:** <int>, optional
The minimum number of samples each branch must have after splitting a node, an integer between 1 and 1e6, inclusive. A split that causes fewer remaining samples is discarded.
- **min_info_gain:** <float>, optional
The minimum threshold for including a split, a FLOAT between 0.0 and 1.0, inclusive. A split with information gain less than this threshold is discarded.
- **nbins:** <int>, optional
The number of bins to use for continuous features, an integer between 2 and 1000, inclusive.

Methods

The RandomForestClassifier object has many methods:

```

1 # Add the RF prediction in a vDataframe
  def add_to_vdf(self, vdf, name: str = "", cutoff: float = 0.5)
3
  # Compute different metrics to evaluate the model
5 def classification_report(self, cutoff: float = 0.5, labels = [])
7
  # Draw the confusion matrix of the model
  def confusion_matrix(self, pos_label = None, cutoff: float = 0.5)
9
  # Save a table or a view in the DB corresponding to the model predictions for
    all the classes
11 def deploy_to_DB(self, name: str, view: bool = True, cutoff = -1, all_classes:
    bool = False)
13
  # Drop the model from the DB
  def drop(self)
15
  # Export the selected tree to the graphviz format
17 def export_graphviz(self, tree_id: int = 0)
19
  # Compute and plot the feature importance
  def features_importance(self)
21
  # Fit the model with the input columns
23 def fit(self, input_relation: str, X: list, y: str, test_relation: str = "")
25
  # Returns a table sample of the selected tree
  def get_tree(self, tree_id: int = 0)
27
  # Draw the Lift Chart
29 def lift_chart(self, pos_label = None)
31
  # Plot the selected tree
  def plot_tree(self, tree_id: int = 0, pic_path: str = "")
33
  # Draw the PRC Curve
35 def prc_curve(self, pos_label = None)
37
  # Draw the ROC Curve
  def roc_curve(self, pos_label = None)
39
  # Compute the selected metric
41 def score(self, pos_label = None, cutoff: float = 0.5, method: str = "accuracy
    ")

```


Attributes

The RandomForestClassifier object has only one attribute:


```
self.classes # The response column classes
```

Example

```
1 from vertica_ml_python.learn.ensemble import RandomForestClassifier
3 # We can build the model
model = RandomForestClassifier("rf_iris", cur, max_depth = 3, n_estimators =
    20)
5 model.fit("iris", ["PetalLengthCm", "SepalLengthCm", "SepalWidthCm"], "Species")
7 # We can look at the model confusion matrix
model.confusion_matrix()
9
11 # Output
      Iris-setosa   Iris-versicolor   Iris-virginica
Iris-setosa         50             0             0
13 Iris-versicolor         0             46             4
Iris-virginica         0             3             47
15
17 # We can also plot the first tree
model.plot_tree(pic_path = "tree0.png")
19 # Output
[1] (petallengthcm < 1.921875 ?)
21 |-- [2] => Iris-setosa (probability = 1.0)
    |-- [3] (petallengthcm < 4.871875 ?)
        |-- [6] (petallengthcm < 4.687500 ?)
            | |-- [12] => Iris-versicolor (probability = 1.0)
            | |-- [13] => Iris-versicolor (probability = 0.8333333333333333)
            |-- [7] (petallengthcm < 5.056250 ?)
                |-- [14] => Iris-virginica (probability = 0.6666666666666667)
                |-- [15] => Iris-virginica (probability = 1.0)
```



```
# We can also look at the Iris-virginica ROC curve
model.roc_curve(pos_label = 'Iris-virginica')
```



9.4.2 RandomForestRegressor

Create a RandomForestRegressor object by using the Vertica Highly Distributed and Scalable Random Forest on the data.

Initialization

```
class RandomForestRegressor(
    name: str,
    cursor,
    n_estimators: int = 10,
    max_features = "auto",
    max_leaf_nodes: int = 1e9,
    sample: float = 0.632,
    max_depth: int = 5,
    min_samples_leaf: int = 1,
    min_info_gain: float = 0.0,
    nbins: int = 32)
```

Parameters

- **name:** <str>
Name of the the model. The model is stored in the DB.
- **cursor:** <object>
DB cursor.

- **n_estimators:** *<int>*, optional
The number of trees in the forest, an integer between 0 and 1000, inclusive.
- **max_features:** *<int>*, optional
The number of randomly chosen features from which to pick the best feature to split on a given tree node. If this parameter is equal to "auto", it will be equal to the square root of the total number of predictors
- **max_leaf_nodes:** *<int>*, optional
The maximum number of leaf nodes a tree in the forest can have, an integer between 1 and 1e9, inclusive.
- **sample:** *<float>*, optional
The portion of the input data set that is randomly picked for training each tree, a FLOAT between 0.0 and 1.0, inclusive.
- **max_depth:** *<int>*, optional
The maximum depth for growing each tree, an integer between 1 and 100, inclusive.
- **min_samples_leaf:** *<int>*, optional
The minimum number of samples each branch must have after splitting a node, an integer between 1 and 1e6, inclusive. A split that causes fewer remaining samples is discarded.
- **min_info_gain:** *<float>*, optional
The minimum threshold for including a split, a FLOAT between 0.0 and 1.0, inclusive. A split with information gain less than this threshold is discarded.
- **nbins:** *<int>*, optional
The number of bins to use for continuous features, an integer between 2 and 1000, inclusive.

Methods

The RandomForestRegressor object has many methods:

```

1 # Add the RF prediction in a vDataFrame
def add_to_vdf(self, vdf, name: str = "")
3
4 # Save a table or a view in the DB corresponding to the model predictions for
   all the classes
5 def deploy_to_DB(self, name: str, view: bool = True)
7
8 # Drop the model from the DB
def drop(self)
9
10 # Export the selected tree to the graphviz format
11 def export_graphviz(self, tree_id: int = 0)
13
14 # Compute and plot the feature importance
def features_importance(self)
15
16 # Fit the model with the input columns
17 def fit(self, input_relation: str, X: list, y: str, test_relation: str = "")
19
20 # Returns a table sample of the selected tree
def get_tree(self, tree_id: int = 0)
21

```

```

# Plot the selected tree
23 def plot_tree(self, tree_id: int = 0, pic_path: str = "")

# Evaluate the test relation by computing many different metrics
25 def regression_report(self)

# Compute the selected metric
27
29 def score(self, method: str = "r2")

```

Example

```

1 from vertica_ml_python.learn.ensemble import RandomForestRegressor

# We can build the model
3 model = RandomForestRegressor("rf_iris", cur, max_depth = 3, n_estimators =
    20)
5 model.fit("iris", ["PetalLengthCm", "SepalWidthCm", "Species"], "SepalLengthCm
    ")

# We can evaluate the model
7 model.regression_report()

# Output
9
11 explained_variance          0.855205647780937
max_error                    0.995783115048306
13 median_absolute_error      0.207286172097297
mean_absolute_error          0.24878157077602
15 mean_squared_error          0.0988507117473723
r2                            0.85487081683392

# We can also get the graphviz format of the trees
17
19 model.export_graphviz()

# Output
21 digraph Tree{
23 1 [label = "petallengthcm < 4.134375 ?", color="blue"];
 1 -> 2 [label = "yes", color = "black"];
25 1 -> 3 [label = "no", color = "black"];
 2 [label = "petallengthcm < 3.396875 ?", color="blue"];
27 2 -> 4 [label = "yes", color = "black"];
 2 -> 5 [label = "no", color = "black"];
29 4 [label = "petallengthcm < 1.368750 ?", color="blue"];
 4 -> 8 [label = "yes", color = "black"];
31 4 -> 9 [label = "no", color = "black"];
 8 [label = "prediction: 4.600000, variance: 0", color="red"];
33 9 [label = "prediction: 5.014706, variance: 0.0994896", color="red"];
 5 [label = "sepalwidthcm < 2.225000 ?", color="blue"];
35 5 -> 10 [label = "yes", color = "black"];

```

```

5 -> 11 [label = "no", color = "black"];
37 10 [label = "prediction: 6.000000, variance: 0", color="red"];
11 [label = "prediction: 5.622222, variance: 0.0150617", color="red"];
39 3 [label = "sepalwidthcm < 3.425000 ?", color="blue"];
3 -> 6 [label = "yes", color = "black"];
41 3 -> 7 [label = "no", color = "black"];
6 [label = "petallengthcm < 5.609375 ?", color="blue"];
43 6 -> 12 [label = "yes", color = "black"];
6 -> 13 [label = "no", color = "black"];
45 12 [label = "prediction: 6.164706, variance: 0.225813", color="red"];
13 [label = "prediction: 7.175000, variance: 0.189375", color="red"];
47 7 [label = "sepalwidthcm < 3.650000 ?", color="blue"];
7 -> 14 [label = "yes", color = "black"];
49 7 -> 15 [label = "no", color = "black"];
14 [label = "prediction: 7.200000, variance: 0", color="red"];
51 15 [label = "prediction: 7.900000, variance: 7.10543e-15", color="red"];
}

```

9.5 vertica_ml_python.learn.linear_model

9.5.1 LinearRegression

Create a ElasticNet object by using the Vertica Highly Distributed and Scalable Linear Regression on the data. The Linear Regression is the ElasticNet model without regularization. The other parameters stay the same.

initialization

```

def LinearRegression(
2     name: str,
        cursor,
4     tol: float = 1e-4,
        C: float = 1.0,
6     max_iter: int = 100,
        solver: str = 'Newton')

```

9.5.2 ElasticNet

Create a ElasticNet object by using the Vertica Highly Distributed and Scalable Linear Regression on the data.

initialization

```

1 class ElasticNet(
        name: str,
3     cursor,
        penalty: str = 'ENet',
5     tol: float = 1e-4,
        C: float = 1.0,
7     max_iter: int = 100,

```



```

    solver: str = 'CGD',
    l1_ratio: float = 0.5)

```

Parameters

- **name:** *<str>*
Name of the model.
- **cursor:** *<object>*
DB cursor.
- **penalty:** *<str>*, optional
Determines the method of regularization: {None | L1 | L2 | ENet}
- **tol:** *<float>*, optional
Determines whether the algorithm has reached the specified accuracy result.
- **C:** *<float>*, optional
The regularization parameter value. The value must be zero or non-negative.
- **max_iter:** *<int>*, optional
Determines the maximum number of iterations the algorithm performs before achieving the specified accuracy result.
- **solver:** *<int>*, optional
The optimizer method used to train the model: {Newton | BFGS | CGD}
- **l1_ratio:** *<float>*, optional
ENet mixture parameter that defines how much L1 versus L2 regularization to provide.

Methods

The ElasticNet object has many methods:

```

1 # Add the ElasticNet prediction in a vDataframe
  def add_to_vdf(self, vdf, name: str = "")
3
  # Save a table or a view in the DB corresponding to the model predictions for
    all the classes
5 def deploy_to_DB(self, name: str, view: bool = True, cutoff = -1)
7
  # Drop the model from the DB
  def drop(self)
9
  # Compute the importance of each feature
11 def features_importance(self)
13
  # Fit the model with the input columns
  def fit(self, input_relation: str, X: list, y: str, test_relation: str = "")
15
  # Plot the SVM if it is possible (The length of X must be lesser or equal to
    3)
17 def plot(self)

```

```

19 # Compute different metrics to evaluate the model
    def regression_report(self)
21
    # Compute the selected metric
23 def score(self, method: str = "r2")

```

Attributes

The ElasticNet object has only one attribute:

```

1 self.coef # Informations about the model coefficients

```

Example

```

1 from vertica_ml_python.learn.linear_model import ElasticNet


3 # We can build the model
  model = ElasticNet("enet_iris", cur, penalty = "None", tol = 1e-8)
5 model.fit("iris", ["PetalLengthCm", "SepalLengthCm"], "SepalWidthCm")

7 # We can evaluate the model
  model.regression_report()

9
  # Output
11
                                value
explained_variance             0.452452439026576
13 max_error                    0.861565208032992
median_absolute_error          0.203743266177453
15 mean_absolute_error          0.251888470089032
mean_squared_error             0.102254872043582
17 r2                          0.452452439026074

19 # We can also draw the model
  model.plot()

```



9.5.3 Lasso

Create a ElasticNet object by using the Vertica Highly Distributed and Scalable Linear Regression on the data. The Lasso Regression is the ElasticNet model with the L1 regularization. The other parameters stay the same.

initialization

```
def Lasso(
    name: str,
    cursor,
    tol: float = 1e-4,
    max_iter: int = 100,
    solver: str = 'CGD')
```

9.5.4 LogisticRegression

Create a LogisticRegression object by using the Vertica Highly Distributed and Scalable Logistic Regression on the data.

initialization

```
class LogisticRegression(
    name: str,
    cursor,
    penalty: str = 'L2',
    tol: float = 1e-4,
    C: int = 1,
    max_iter: int = 100,
    solver: str = 'CGD',
    l1_ratio: float = 0.5)
```

- **name:** *<str>*
Name of the model.
- **cursor:** *<object>*
DB cursor.
- **penalty:** *<str>*, optional
Determines the method of regularization: {None | L1 | L2 | ENet}
- **tol:** *<float>*, optional
Determines whether the algorithm has reached the specified accuracy result.
- **C:** *<int>*, optional
The regularization parameter value. The value must be zero or non-negative.
- **max_iter:** *<int>*, optional
Determines the maximum number of iterations the algorithm performs before achieving the specified accuracy result.
- **solver:** *<int>*, optional
The optimizer method used to train the model: {Newton | BFGS | CGD}
- **l1_ratio:** *<float>*, optional
ENet mixture parameter that defines how much L1 versus L2 regularization to provide.

Methods

The LogisticRegression object has many methods:

```

1 # Add the LogisticRegression prediction in a vDataframe
  def add_to_vdf(self, vdf, name: str = "", cutoff: float = 0.5)
3
  # Compute different metrics to evaluate the model
5  def classification_report(self, cutoff: float = 0.5)
7
  # Draw the confusion matrix of the model
  def confusion_matrix(self, cutoff: float = 0.5)
9
  # Save a table or a view in the DB corresponding to the model predictions for
    all the classes
11  def deploy_to_DB(self, name: str, view: bool = True, cutoff = -1)
13
  # Drop the model from the DB
  def drop(self)
15
  # Compute the importance of each feature
17  def features_importance(self)
19
  # Fit the model with the input columns
  def fit(self, input_relation: str, X: list, y: str, test_relation: str = "")
21
  # Draw the Lift Chart
23  def lift_chart(self)

```

```

25 # Plot the LogisticRegression if it is possible (The length of X must be
    lesser of equal to 2)
    def plot(self)
27
    # Draw the PRC Curve
29 def prc_curve(self)
31
    # Draw the ROC Curve
    def roc_curve(self)
33
    # Compute the selected metric
35 def score(self, cutoff: float = 0.5, method: str = "accuracy")

```

Attributes

The LogisticRegression object has only one attribute:

```

1 self.coef # Informations about the model coefficients

```


Example

```


1 from vertica_ml_python import vDataframe
  from vertica_ml_python.learn.linear_model import LogisticRegression
3
  # We create dummies
5 iris = vDataframe("iris", cur)
  iris["Species"].get_dummies(use_numbers_as_suffix = True)
7 iris.to_db("iris_dummy")
9
  # We can build the model
  model = LogisticRegression("logit_iris", cur)
11 model.fit("iris_dummy", ["PetalLengthCm"], "Species_0")
13
  # We can evaluate the model
  model.classification_report()
15
  # Output
17
    value
auc                1.0
19 prc_auc           0.9800000000000001
  accuracy          0.9533333333333333
21 log_loss          0.187846851053108
  precision          1.0
23 recall            0.8771929824561403
  f1-score           0.9345794392523363
25 mcc               0.9032106474595007
  informedness       0.8771929824561404
27 markedness        0.9300000000000002
  csi                0.8771929824561403

```

```
29 # We can also draw the model
31 model.plot()
```



```
1 # We can build a new model
model.drop()
3 model.fit("iris_dummy", ["PetalLengthCm", "PetalWidthCm", "SepalLengthCm", "
    SepalWidthCm"], "Species_0")
5 # We can see the features importance
model.features_importance()
```



9.5.5 Ridge

Create a ElasticNet object by using the Vertica Highly Distributed and Scalable Linear Regression on the data. The Ridge Regression is the ElasticNet model with the L2 regularization. The other parameters stay the same.

initialization

```
def Ridge(
    name: str,
    cursor,
    tol: float = 1e-4,
    max_iter: int = 100,
    solver: str = 'Newton')
```

9.6 vertica_ml_python.learn.metrics

Many metrics are available to evaluate a model efficiency. These functions can be used independently of the models. For more flexibility, the input columns can also be SQL expressions.

9.6.1 Regression

9.6.1.1 explained_variance

```
def explained_variance(
    y_true: str,
    y_score: str,
    input_relation: str,
    cursor)
```

Compute the explain variance of 2 input columns.

9.6.1.2 max_error

```
1 def max_error(  
    y_true: str,  
3    y_score: str,  
    input_relation: str,  
5    cursor)
```

Compute the max error of 2 input columns.

9.6.1.3 median_absolute_error

```
1 def median_absolute_error(  
    y_true: str,  
3    y_score: str,  
    input_relation: str,  
5    cursor)
```

Compute the median absolute error of 2 input columns.

9.6.1.4 mean_absolute_error

```
1 def mean_absolute_error(  
    y_true: str,  
3    y_score: str,  
    input_relation: str,  
5    cursor)
```

Compute the mean absolute error of 2 input columns.

9.6.1.5 mean_squared_error

```
1 def mean_squared_error(  
    y_true: str,  
3    y_score: str,  
    input_relation: str,  
5    cursor)
```

Compute the mean squared error of 2 input columns.

9.6.1.6 mean_squared_log_error


```
1 def mean_squared_log_error(  
    y_true: str,  
3    y_score: str,  
    input_relation: str,  
5    cursor)
```

Compute the mean squared log error of 2 input columns.

9.6.1.7 regression_report

```
1 def regression_report(  
    y_true: str,  
3    y_score: str,  
    input_relation: str,  
5    cursor)
```

Compute different regression metrics of 2 input columns.

9.6.1.8 r2_score

```
1 def r2_score(  
    y_true: str,  
3    y_score: str,  
    input_relation: str,  
5    cursor)
```

Compute the r2 score of 2 input columns.

9.6.2 Classification

9.6.2.1 accuracy_score

```
1 def accuracy_score(  
    y_true: str,  
3    y_score: str,  
    input_relation: str,  
5    cursor)
```

Compute the accuracy of 2 input columns.

9.6.2.2 auc

```
1 auc(  
    y_true: str,  
3    y_score: str,  
    input_relation: str,  
5    cursor,  
    pos_label = 1)
```

Compute the AUC (Area Under the ROC) of 2 input columns.

9.6.2.3 classification_report

```
classification_report(  
2    y_true: str = "",  
    y_score: str = "",  
4    input_relation: str = "",  
    cursor = None,  
6    labels: list = [],  
    cutoff: float = 0.5)
```

Compute different classification metrics of 2 input columns.

9.6.2.4 confusion_matrix

```
1 confusion_matrix(  
    y_true: str,  
3    y_score: str,  
    input_relation: str,  
5    cursor,  
    pos_label = 1)
```

Compute the Confusion Matrix of 2 input columns.

9.6.2.5 critical_success_index

```
critical_success_index(  
2    y_true: str,  
    y_score: str,  
4    input_relation: str,  
    cursor,  
6    pos_label = 1)
```

Compute the Critical Success Index of 2 input columns.

9.6.2.6 f1_score

```
f1_score(  
2     y_true: str,  
     y_score: str,  
4     input_relation: str,  
     cursor,  
6     pos_label = 1)
```

Compute the F1 Score of 2 input columns.

9.6.2.7 informedness

```
informedness(  
2     y_true: str,  
     y_score: str,  
4     input_relation: str,  
     cursor,  
6     pos_label = 1)
```

Compute the Informedness of 2 input columns.

9.6.2.8 log_loss

```
log_loss(  
2     y_true: str,  
     y_score: str,  
4     input_relation: str,  
     cursor,  
6     pos_label = 1)
```

Compute the Log Loss of 2 input columns.

9.6.2.9 markedness

```
log_loss(  
2     y_true: str,  
     y_score: str,  
4     input_relation: str,  
     cursor,  
6     pos_label = 1)
```

Compute the Markedness of 2 input columns.

9.6.2.10 matthews_corrcoef

```
matthews_corrcoef(  
2     y_true: str,  
     y_score: str,  
4     input_relation: str,  
     cursor,  
6     pos_label = 1)
```

Compute the Matthews Correlation Coefficient of 2 input columns.

9.6.2.11 multilabel_confusion_matrix

```
multilabel_confusion_matrix(  
2     y_true: str,  
     y_score: str,  
4     input_relation: str,  
     cursor,  
6     labels: list)
```

Compute the Confusion Matrix of 2 input columns in case of Multi Classification.

9.6.2.12 negative_predictive_score

```
negative_predictive_score(  
2     y_true: str,  
     y_score: str,  
4     input_relation: str,  
     cursor,  
6     pos_label = 1)
```

Compute the Negative Predictive Score of 2 input columns.

9.6.2.13 prc_auc

```
prc_auc(  
2     y_true: str,  
     y_score: str,  
4     input_relation: str,  
     cursor,  
6     pos_label = 1)
```

Compute the PRC AUC of 2 input columns.

9.6.2.14 precision_score

```
precision_score(  
2     y_true: str,  
     y_score: str,  
4     input_relation: str,  
     cursor,  
6     pos_label = 1)
```

Compute the Precision Score of 2 input columns.

9.6.2.15 recall_score

```
recall_score(  
2     y_true: str,  
     y_score: str,  
4     input_relation: str,  
     cursor,  
6     pos_label = 1)
```

Compute the Recall Score of 2 input columns.

9.6.2.16 specificity_score

```
specificity_score(  
2     y_true: str,  
     y_score: str,  
4     input_relation: str,  
     cursor,  
6     pos_label = 1)
```

Compute the Specificity Score of 2 input columns.

9.7 vertica_ml_python.learn.model_selection

9.7.1 best_k

```
def best_k(  
2     X: list,  
     input_relation: str,  
4     cursor,  
     n_cluster = (1, 100),  
6     init = "kmeanspp",  
     max_iter: int = 50,  
8     tol: float = 1e-4,  
     elbow_score_stop = 0.8)
```

Find the KMeans K by using a score threshold.

Parameters

- **X:** *<list>*
List of the predictor columns.
- **input_relation:** *<str>*
Relation used to train the model.
- **cursor:** *<object>*
DB cursor.
- **n_cluster:** *<tuple>*, optional
Tuple representing the number of cluster to start with and to end with.
- **init:** *<str or list>*, optional
The method used to find the initial cluster centers. The method can be in {random | kmeanspp}. It can be also a list with the initial cluster centers to use.
- **max_iter:** *<int>*, optional
The maximum number of iterations the algorithm performs.
- **tol:** *<float>*, optional
Determines whether the algorithm has converged. The algorithm is considered converged after no center has moved more than a distance of 'tol' from the previous iteration.
- **elbow_score_stop:** *<float>*, optional
Stop the Parameters Search when this Elbow score is reached.

Example

```

1 from vertica_ml_python.learn.model_selection import best_k
3 best_k(["PetalLengthCm", "PetalWidthCm", "SepalLengthCm", "SepalWidthCm"], "
    iris", cur)
5 # Output
3

```

9.7.2 cross_validate

Compute the K-Fold cross validation of an estimator.

initialization

```

1 def cross_validate(
2     estimator,
3     input_relation: str,
4     X: list,
5     y: str,
6     cv: int = 3,

```

```
pos_label = None ,
cutoff: float = 0.5)
```

Parameters

- **estimator:** *<object>*
Estimator having a fit method and a DB cursor.
- **input_relation:** *<str>*
The relation used to test the estimator.
- **X:** *<list>*
List of the predictor columns.
- **y:** *<str>*
Response Column.
- **cv:** *<int>*, optional
Number of folds.
- **pos_label:** *<anytype>*, optional
The main class in case of classification.
- **cutoff:** *<float>*, optional
The cutoff in case of classification. It must be in]0,1[

Returns

The `tablesampl` type containing different metric to evaluate the estimator (the information will be stored in the `values` attribute). You can convert this object to pandas using the `to_pandas` method or to `vDataFrame` using the `to_vdf` method.

Example

```
from vertica_ml_python.learn.linear_model import LogisticRegression
from vertica_ml_python.learn.model_selection import cross_validate

# We test the estimator
model = LogisticRegression("logit_titanic", cur)
cross_validate(model, "titanic", ["age", "pclass", "fare"], "survived")

# Output
```

	auc	prc_auc	\\
1-fold	0.7269061583577717	0.636432596278644	\\
2-fold	0.6903612550943709	0.580010812173139	\\
3-fold	0.6922692837465568	0.5612045504938292	\\
avg	0.703178899066	0.592549319649	\\
std	0.0167957786056	0.0319658708149	\\
	accuracy	log_loss	\\
1-fold	0.704663212435233	0.277918039898239	\\
2-fold	0.708433734939759	0.280386273274253	\\
3-fold	0.690531177829099	0.282475484333873	\\
avg	0.701209375068	0.280259932502	\\

```

20 std          0.00770593417198      0.00186271243782    \\
    precision          recall    \\
22 1-fold      0.5984848484848485      0.6528925619834711    \\
  2-fold      0.47244094488188976      0.625    \\
24 3-fold      0.49242424242424243      0.5909090909090909    \\
  avg          0.521116678597      0.622933884298    \\
26 std          0.0553124960506      0.0253467854264    \\
    f1-score          mcc    \\
28 1-fold      0.6897262557977386      0.37822641657012745    \\
  2-fold      0.6642216788916055      0.31190453116529854    \\
30 3-fold      0.6503716409376787      0.3006795875598417    \\
  avg          0.668106525209      0.330270178432    \\
32 std          0.0162996002176      0.0342184202053    \\
    informedness      markedness    \\
34 1-fold      0.38385702898854723      0.37267839687194515    \\
  2-fold      0.33369565217391317      0.29153642226882437    \\
36 3-fold      0.31404958677685957      0.28787878787878785    \\
  avg          0.343867422646      0.317364535673    \\
38 std          0.0293923848748      0.0391412996111    \\
    csi
40 1-fold      0.4540229885057471
  2-fold      0.36809815950920244
42 3-fold      0.3672316384180791
  avg          0.396450928811
44 std          0.0407111308106

```

9.7.3 train_test_split

```

train_test_split(input_relation: str, cursor, test_size: float = 0.33,
                 schema_writing: str = "")

```

Build one table and 2 views which can be used to evaluate a model. The table will include all the main relation information with a test column (boolean) which represents if the data belong to the test or train set.

Parameters

- **input_relation:** <str>
The relation used to test the estimator.
- **cursor:** <object>
A DB cursor.
- **test_size:** <float>
Proportion of the test set comparint to the training set.
- **schema_writing:** <str>
Schema used to write the main relation.

Returns

A tuple (name of the train view, name of the test view)

9.8 vertica_ml_python.learn.naive_bayes

9.8.1 MultinomialNB

Create a MultinomialNB object by using the Vertica Highly Distributed and Scalable Naive Bayes on the data.

initialization

```
1 class MultinomialNB(name: str, cursor, alpha: float = 1.0)
```

Parameters

- **name:** <str>
Name of the the model. The model is stored in the DB.
- **cursor:** <object>
DB cursor.
- **alpha:** <float>, optional
A float that specifies use of Laplace smoothing if the event model is categorical, multinomial, or Bernoulli.

Methods

The MultinomialNB object has many methods:

```
1 # Add the MultinomialNB prediction in a vDataframe
2 def add_to_vdf(self, vdf, name: str = "", cutoff: float = 0.5)
3
4 # Compute different metrics to evaluate the model
5 def classification_report(self, cutoff: float = 0.5, labels = [])
6
7 # Draw the confusion matrix of the model
8 def confusion_matrix(self, pos_label = None, cutoff: float = 0.5)
9
10 # Save a table or a view in the DB corresponding to the model predictions for
    all the classes
11 def deploy_to_DB(self, name: str, view: bool = True, cutoff = -1, all_classes:
    bool = False )
12
13 # Drop the model from the DB
14 def drop(self)
15
16 # Fit the model with the input columns
17 def fit(self, input_relation: str, X: list, y: str, test_relation: str = "")
18
19 # Draw the Lift Chart
20 def lift_chart(self, pos_label = None)
21
22 # Draw the PRC Curve
23 def prc_curve(self, pos_label = None)
24
25 # Draw the ROC Curve
```

```

def roc_curve(self, pos_label = None)
27
# Compute the selected metric
29 def score(self, pos_label = None, cutoff: float = 0.5, method: str = "accuracy
    ")

```

Attributes

The MultinomialNB object has only one attribute:

```

1 self.classes # The response column classes

```

Example

```

1 from vertica_ml_python.learn.naive_bayes import MultinomialNB


3 # We can build the model
model = MultinomialNB("nb_titanic", cur)
5 model.fit("titanic", ["age", "pclass", "fare"], "survived")

7 # We can evaluate the model efficiency
model.classification_report()

9
# Output
11
                                     value
auc                                0.6682737629726706
13 prc_auc                          0.5326937341539878
accuracy                          0.53484602917342
15 log_loss                         0.586771724006015
precision                         0.20460358056265984
17 recall                           0.7619047619047619
f1-score                          0.7020729308518686
19 mcc                             0.25963840041342523
informedness                      0.41285874619207963
21 markedness                      0.16328126651307318
csi                               0.19230769230769232

23
# We can also plot the PRC curve
25 model.prc_curve()

```



9.9 vertica_ml_python.learn.neighbors

9.9.1 KNeighborsClassifier

Create a KNeighborsClassifier object by using the K Nearest Neighbors Algorithm. This object is using pure SQL to compute all the distances and final score. It is using CROSS JOIN and may be really expensive in some cases. As KNeighborsClassifier is using the p-distance, it is highly sensible to un-normalized data.

initialization

```

1 class KNeighborsClassifier(
2     name: str,
3     cursor,
4     n_neighbors: int = 20,
5     p: int = 2)

```

Parameters

- **name:** <str>
Name of the relation created after fitting the model.
- **cursor:** <object>
DB cursor.
- **n_neighbors:** <int>, optional
Number of neighbors.
- **p:** <int>, optional
The p corresponding to the one of the p-distance (distance metric used during the model computation).

Methods

The KNeighborsClassifier object has many methods:

```

1 # Compute different metrics to evaluate the model
2 def classification_report(self, cutoff: float = 0.5, labels = [])
3
4 # Draw the confusion matrix of the model
5 def confusion_matrix(self, pos_label = None, cutoff: float = 0.5)
6
7 # Save a table or a view in the DB corresponding to the model predictions for
  all the classes
8 def deploy_to_DB(self, name: str, view: bool = True, cutoff = -1, all_classes:
  bool = False)
9
10 # Fit the model with the input columns
11 def fit(self, input_relation: str, X: list, y: str, test_relation: str = "")
12
13 # Draw the Lift Chart
14 def lift_chart(self, pos_label = None)
15
16 # Draw the PRC Curve
17 def prc_curve(self, pos_label = None)
18
19 # Draw the ROC Curve
20 def roc_curve(self, pos_label = None)
21
22 # Compute the selected metric
23 def score(self, pos_label = None, cutoff: float = 0.5, method: str = "accuracy
  ")

```

Example

```

1 from vertica_ml_python.learn.neighbors import KNeighborsClassifier
2
3 # We can build the model
4 model = KNeighborsClassifier(cur)
5 model.fit("iris", ["SepalLengthCm", "SepalWidthCm"], "Species")
6
7 # We can evaluate the model
8 model.classification_report()
9
10 # Output
11
12          Iris-setosa      Iris-versicolor  \\
13 auc                    0.99      0.7909756097560976  \\
14 prc_auc      0.019615384615384597      0.6462689689983612  \\
15 accuracy          0.980769230769231      0.725274725274725  \\
16 log_loss          0.0171690390452333      0.233867972918641  \\
17 precision          0.98                    0.86  \\
18 recall          1.0      0.7049180327868853  \\
19 f1-score          0.8      0.734496843668771  \\

```

```

19 mcc                0.8082903768654761      0.44556218017702653  \\
   informedness      0.6666666666666666      0.47158469945355197  \\
21 markedness        0.98                    0.4209756097560975  \\
   csi                0.98                    0.6323529411764706  \\
23
   Iris-virginica
   auc                0.79725
25 prc_auc            0.6555011655011654
   accuracy          0.7333333333333333
27 log_loss          0.230656742114622
   precision         0.66
29 recall            0.825
   f1-score          0.7333333333333334
31 mcc                0.485
   informedness      0.4849999999999999
33 markedness        0.4849999999999999
   csi                0.5789473684210527

```

9.9.2 KNeighborsRegressor

Create a KNeighborsRegressor object by using the K Nearest Neighbors Algorithm. This object is using pure SQL to compute all the distances and final score. It is using CROSS JOIN and may be really expensive in some cases. As KNeighborsRegressor is using the p-distance, it is highly sensible to un-normalized data.

initialization

```

class KNeighborsRegressor(
2   name: str,
   cursor,
4   n_neighbors: int = 20,
   p: int = 2)

```

Parameters

- **name:** <str>
Name of the relation created after fitting the model.
- **cursor:** <object>
DB cursor.
- **n_neighbors:** <int>, optional
Number of neighbors.
- **p:** <int>, optional
The p corresponding to the one of the p-distance (distance metric used during the model computation)

Methods

The KNeighborsRegressor object has four main methods:

```

1 # Save a table or a view in the DB corresponding to the model predictions for
   all the classes

```

```

def deploy_to_DB(self, name: str, view: bool = True)
3
# Fit the model with the input columns
5 def fit(self, input_relation: str, X: list, y: str, test_relation: str = "")
7 # Compute different metrics to evaluate the model
def regression_report(self)
9
# Compute the selected metric
11 def score(self, method: str = "r2")

```

Example

```

1 from vertica_ml_python.learn.neighbors import KNeighborsRegressor
3 # We can build the model
model = KNeighborsRegressor(cur)
5 model.fit("iris", ["SepalLengthCm"], "SepalWidthCm")
7 # We can evaluate the model
model.regression_report()
9
# Output
11
12                                     value
13 explained_variance                0.229656749700724
14 max_error                        1.32
15 median_absolute_error             0.2
16 mean_absolute_error               0.2749333333333333
17 mean_squared_error               0.1458453333333333
r2                                0.219037147569338

```

9.9.3 NearestCentroid

Create a NearestCentroid object by using the K Nearest Centroid Algorithm. This object is using pure SQL to compute all the distances and final score. As KNeighborsClassifier is using the p-distance, it is highly sensible to un-normalized data.

initialization

```

1 class NearestCentroid(
    name: str,
3     cursor,
    n_neighbors: int = 20,
5     p: int = 2)

```

Parameters

- **name:** <str>
Name of the relation created after fitting the model.

- **cursor:** *<object>*
DB cursor.
- **p:** *<int>*, optional
The p corresponding to the one of the p-distance (distance metric used during the model computation).

Methods

The NearestCentroid object has many methods:

```

1 # Compute different metrics to evaluate the model
2 def classification_report(self, cutoff: float = 0.5, labels = [])
3
4 # Draw the confusion matrix of the model
5 def confusion_matrix(self, pos_label = None, cutoff: float = 0.5)
6
7 # Save a table or a view in the DB corresponding to the model predictions for
  all the classes
8 def deploy_to_DB(self, name: str, view: bool = True, cutoff = -1, all_classes:
  bool = False)
9
10 # Fit the model with the input columns
11 def fit(self, input_relation: str, X: list, y: str, test_relation: str = "")
12
13 # Draw the Lift Chart
14 def lift_chart(self, pos_label = None)
15
16 # Draw the PRC Curve
17 def prc_curve(self, pos_label = None)
18
19 # Draw the ROC Curve
20 def roc_curve(self, pos_label = None)
21
22 # Compute the selected metric
23 def score(self, pos_label = None, cutoff: float = 0.5, method: str = "accuracy
  ")

```

Attributes

The NearestCentroid object has two main attributes:

```

1 self.centroids # Information on the different centroids
2 self.classes # The response column classes

```

Example

```

1 from vertica_ml_python.learn.neighbors import NearestCentroid
2
3 # We can build the model
4 model = NearestCentroid(cur)
5 model.fit("iris", ["SepalLengthCm", "SepalWidthCm"], "Species")

```

```

6
# We can evaluate the model
8 model.classification_report()

10 # Output

                Iris-setosa                Iris-versicolor  \\
12 auc                0.9646000000000002                0.7232  \\
prc_auc                0.901881291162864                0.5053846970363146  \\
14 accuracy                0.6666666666666667                0.6666666666666667  \\
log_loss                0.22020528846944                0.265883056465362  \\
16 precision                0.0                0.0  \\
recall                0                0  \\
18 f1-score                0.0                0.0  \\
mcc                0                0  \\
20 informedness                -0.33333333333333337                -0.33333333333333337  \\
markedness                0.0                0.0  \\
22 csi                0.0                0.0  \\

                Iris-virginica
24 auc                0.7887
prc_auc                0.5563484355454329
26 accuracy                0.6666666666666667
log_loss                0.249463099665484
28 precision                0.0
recall                0
30 f1-score                0.0
mcc                0
32 informedness                -0.33333333333333337
markedness                0.0
34 csi                0.0

```

9.9.4 LocalOutlierFactor

Create a LocalOutlierFactor object by using the Local Outlier Factor algorithm as defined by Markus M. Breunig, Hans-Peter Kriegel, Raymond T. Ng and Jörg Sander. This object is using pure SQL to compute all the distances and final score. It is using CROSS JOIN and may be really expensive in some cases. It will index all the elements of the table in order to be optimal (the CROSS JOIN will happen only with IDs which are integers). As LocalOutlierFactor is using the p-distance, it is highly sensible to un-normalized data.

initialization

```

class LocalOutlierFactor(
2     name: str,
    cursor,
4     n_neighbors: int = 20,
    p: int = 2)

```

Parameters

- **name:** *<str>*
Name of the relation created after fitting the model.
- **cursor:** *<object>*
DB cursor.
- **n_neighbors:** *<int>*, optional
Number of neighbors to consider when computing the score.
- **p:** *<int>*, optional
The p corresponding to the one of the p-distance (distance metric used during the model computation).

Methods

The LocalOutlierFactor object has five main methods:

```

1 # Fit the model with the input columns
  def fit(self, input_relation: str, X: list, key_columns: list = [], index = ""
    )
3
  # Print the model information
5 def info(self)
7
  # Plot the model (only possible if the number of columns <= 3)
  def plot(self)
9
  # Create a vDataframe using the final relation
11 def to_vdf(self)

```

The index parameter (name of the primary key column in the relation) of the 'fit' method is very important as without it an indexed copy of the main relation will be created (it could be really expensive). It is highly recommended to have a primary key column in the main table to avoid unnecessary computations.

Attributes

The LocalOutlierFactor object has one main attribute:

```

1 self.n_errors # Number of errors

```

Example

```


1 from vertica_ml_python import vDataframe
  from vertica_ml_python.learn.neighbors import LocalOutlierFactor
3
  # Building a normalized relation of the features, we will use
5 titanic = vDataframe("titanic", cur)
  # We will use a sample of the data in order to have a beautiful plot
7 titanic.main_relation += " TABLESAMPLE(10) "
  titanic = titanic.select(["fare", "age"])
9 titanic.normalize()
  titanic.to_db("titanic_normalize")
11
  # We can build the model

```

```

13 model = LocalOutlierFactor("lof_titanic", cur)
14 model.fit("titanic_normalize", ["fare", "age"])
15
16 # We can see the different information relative to the model
17 model.info()
18
19 # Output
20 All the LOF scores were computed.
21
22 # And Plot the model
23 model.plot()

```



9.10 vertica_ml_python.learn.plot

9.10.1 elbow

```

1 def elbow(
2     X: list,
3     input_relation: str,
4     cursor,
5     n_cluster = (1, 15),
6     init = "kmeanspp",
7     max_iter: int = 50,
8     tol: float = 1e-4)

```

Draw the Elbow Curve. This curve is helpful to find the number of clusters of a KMeans model.

Parameters


- **X:** *<list>*
List of the predictor columns.
- **input_relation:** *<str>*
Relation used to train the model.
- **cursor:** *<object>*
DB cursor.
- **n_cluster:** *<tuple or list>*, optional
Tuple representing the number of cluster to start with and to end with. You can also use a list of different cluster values.
- **init:** *<str or list>*, optional
The method used to find the initial cluster centers. The method can be in {random | kmeanspp}. It can be also a list with the initial cluster centers to use.
- **max_iter:** *<int>*, optional
The maximum number of iterations the algorithm performs.
- **tol:** *<float>*, optional
Determines whether the algorithm has converged. The algorithm is considered converged after no center has moved more than a distance of 'tol' from the previous iteration.

Example

```

from vertica_ml_python.learn.plot import elbow
# We can build the model
elbow(["PetalLengthCm", "SepalWidthCm", "SepalLengthCm"], "iris", cur)

```



9.10.2 lift_chart

```
def lift_chart(  
2     y_true: str,  
     y_score: str,  
4     input_relation: str,  
     cursor,  
6     pos_label = 1,  
     nbins: int = 1000)
```

Draw the Lift Curve.

Parameters

- **y_true:** <str>
Response Column.
- **y_score:** <str>
Prediction.
- **input_relation:** <str>
Input Relation.
- **cursor:** <object>
DB cursor.
- **pos_label:** <anytype>, optional
Label of the main class.
- **nbins:** <int>, optional
Number of bins used to compute the curve (= number of points).

9.10.3 prc_curve

```
def prc_curve(  
1     y_true: str,  
3     y_score: str,  
     input_relation: str,  
5     cursor,  
     pos_label = 1,  
7     nbins: int = 1000)
```

Draw the PRC Curve.

Parameters

- **y_true:** <str>
Response Column.
- **y_score:** <str>
Prediction.
- **input_relation:** <str>
Input Relation.

- **cursor:** *<object>*
DB cursor.
- **pos_label:** *<anytype>*, optional
Label of the main class.
- **nbins:** *<int>*, optional
Number of bins used to compute the curve (= number of points).

9.10.4 roc_curve

```
1 def roc_curve(  
    y_true: str,  
3    y_score: str,  
    input_relation: str,  
5    cursor,  
    pos_label = 1,  
7    nbins: int = 1000)
```

Draw the ROC Curve.

Parameters

- **y_true:** *<str>*
Response Column.
- **y_score:** *<str>*
Prediction.
- **input_relation:** *<str>*
Input Relation.
- **cursor:** *<object>*
DB cursor.
- **pos_label:** *<anytype>*, optional
Label of the main class.
- **nbins:** *<int>*, optional
Number of bins used to compute the curve (= number of points).

9.11 vertica_ml_python.learn.preprocessing

9.11.1 Balance

```
1 def Balance(  
    name: str,  
3    input_relation: str,  
    cursor,  
5    y: str,  
    method: str,  
7    ratio = 0.5)
```

Build a view with an equal distribution of the input data based on the response column.

Parameters

- **name:** *<str>*
Output view name.
- **input_relation:** *<str>*
Input Relation.
- **cursor:** *<object>*
DB cursor.
- **y:** *<str>*
Response column.
- **method:** *<str>*, optional
Label of the main class.
- **ratio:** *<float>*, optional
hybrid_sampling | over_sampling | under_sampling
hybrid_sampling (default): Performs over-sampling and under-sampling on different classes so each class is equally represented.
over_sampling: Over-samples on all classes, with the exception of the most majority class, towards the most majority class's cardinality.
under_sampling: Under-samples on all classes, with the exception of the most minority class, towards the most minority class's cardinality.

9.11.2 CountVectorizer

Create a CountVectorizer object which creates the dictionary of the different text columns. During the process, it will create a text index and compute the number of occurrences.

initialization

```

1 class CountVectorizer(
2     name: str,
3     cursor,
4     lowercase: bool = True,
5     max_df: float = 1.0,
6     min_df: float = 0.0,
7     max_features: int = -1,
8     ignore_special: bool = True,
9     max_text_size: int = 2000)

```

Parameters

- **name:** *<str>*
Name of the text index.
- **cursor:** *<object>*
DB cursor.
- **lowercase:** *<bool>*, optional
Convert all the elements to lowercase before processing.

- **max_df:** *<float>*, optional
Keep the words which represent less than this float in the total dictionary distribution.
- **min_df:** *<float>*, optional
Keep the words which represent more than this float in the total dictionary distribution.
- **max_features:** *<int>*, optional
Keep only the top words of the dictionary
- **ignore_special:** *<bool>*, optional
Ignore all the special characters to build the dictionary.
- **max_text_size:** *<int>*, optional
The maximum size of the column which is the concatenation of all the text columns during the fitting.

Methods

The CountVectorizer object has 3 methods:

```

1 # Drop the text index
  def drop(self)
3
  # Fit the model with the input columns
5 def fit(self, input_relation: str, X: list)
7
  # Build a vdf from the output relation
  def to_vdf(self)

```

Attributes

The CountVectorizer object has two attributes:

```

self.stop_words # The words not added to the vocabulary because of some
                 parameters
2 self.vocabulary # The final vocabulary

```

Example

```

from vertica_ml_python.learn.preprocessing import CountVectorizer
2
  # We can build the model
4 model = CountVectorizer("name_voc", cur)
  model.fit("titanic", ["Name"])
6
  # We can export the dictionary
8 model.to_vdf()
10
  # Output

```

	token	df	cnt	rnk
0	mr	0.148163100524828421	734	1
1	miss	0.046023415421881308	228	2
2	mrs	0.037343560758982640	185	3
3	william	0.016148566814695196	80	4

```

16 4          john      0.013726281792490916      68      5
...      ...      ...      ...      ...
18 Name: name_voc, Number of rows: 1841, Number of columns: 4

```

9.11.3 Normalizer

Create a Normalizer object which can be used to normalize the data.

Initialization

```
class Normalizer(name: str, cursor, method: str = "zscore")
```

Parameters

- **name:** <str>
Name of the model.
- **cursor:** <object>
DB cursor.
- **method:** <str>, optional
The normalization method to use: {minmax | zscore | robust_zscore}

Methods

The Normalizer object has 3 methods:

```

1 # Drop the model from the DB
def drop(self)
3
# Fit the model with the input columns
5 def fit(self, input_relation: str, X: list)
7
# Build a vdf from the output relation
def to_vdf(self, reverse = False)

```

Attributes

The Normalizer object has only one attribute:

```
self.param # The information about columns used to normalize the data.
```

Example

```

1 from vertica_ml_python.learn.preprocessing import Normalizer
3
# We can build the model
model = Normalizer("norm_iris", cur)
5 model.fit("iris", ["SepalLengthCm", "SepalWidthCm"])
7
# We can look at the model parameters
model.param

```



```

9
# Output
11      column_name      avg      std_dev
0      sepalengthcm      5.84333333333333      0.828066127977865
13      sepalwidthcm      3.054      0.433594311362172

15 # We can export the model
model.to_vdf()

17
# Output
19      SepalLengthCm      SepalWidthCm
0      -0.897673879196763      1.02861128089724
21      -1.13920048346495      -0.12454037930146
2      -1.38072708773314      0.33672028477802
23      -1.50149038986723      0.10608995273828
4      -1.01843718133086      1.25924161293698
25      ...      ...      ...
Name: norm_iris, Number of rows: 150, Number of columns: 2

```

9.11.4 OneHotEncoder

Create a OneHotEncoder object which can be used to encode the data using dummies.

initialization

```

class OneHotEncoder(
2     name: str,
      cursor,
4     extra_levels: dict = {},
      drop_first: bool = True,
6     ignore_null: bool = True)

```

Parameters

- **name:** <str>
Name of the model.
- **cursor:** <object>
DB cursor.
- **extra_levels:** <dict>, optional
Additional levels in each category that are not in the input relation.
- **drop_first:** <bool>, optional
If true, treat the first level of the categorical variable as the reference level.
- **ignore_null:** <bool>, optional
If false, Null values in input columns are treated as a categorical level.

Methods

The OneHotEncoder object has 3 methods:

```

# Drop the model from the DB
2 def drop(self)

# Fit the model with the input columns
4 def fit(self, input_relation: str, X: list)

# Build a vdf from the output relation
6
8 def to_vdf(self, reverse = False)

```

Attributes

The OneHotEncoder object has only one attribute:

```
self.param # The information about columns used to get the data dummies.
```

Example

```

1 from vertica_ml_python.learn.preprocessing import OneHotEncoder

# We can build the model
3 model = OneHotEncoder("dummies_iris", cur)
4 model.fit("iris", ["Species"])

# We can look at the model parameters
7 model.param

# Output
9
11      category_name      category_level      category_level_index
12 0      species      Iris-setosa      0
13 1      species      Iris-versicolor      1
14 2      species      Iris-virginica      2

# We can export the model
15
17 model.to_vdf()

# Output
19
21      species      species_iris-versicolor      species_iris-virginica
22 0      Iris-setosa      0      0
23 1      Iris-setosa      0      0
24 2      Iris-setosa      0      0
25 3      Iris-setosa      0      0
26 4      Iris-setosa      0      0
27 ...      ...      ...      ...
28 Name: dummies_iris, Number of rows: 150, Number of columns: 3

```

9.12 vertica_ml_python.learn.svm

9.12.1 LinearSVC

Create a LinearSVC object by using the Vertica Highly Distributed and Scalable SVM on the data.

initialization

```

1 class LinearSVC(
    name: str,
3     cursor,
    tol: float = 1e-4,
5     C: float = 1.0,
    fit_intercept: bool = True,
7     intercept_scaling: float = 1.0,
    intercept_mode: str = "regularized",
9     class_weight: list = [1, 1],
    max_iter: int = 100)

```

Parameters

- **name:** *<str>*
Name of the relation created after fitting the model.
- **cursor:** *<object>*
DB cursor.
- **tol:** *<float>*, optional
Used to control accuracy.
- **C:** *<float>*, optional
The weight for misclassification cost. The algorithm minimizes the regularization cost and the misclassification cost.
- **fit_intercept:** *<bool>*, optional
A bool to fit also the intercept.
- **intercept_scaling:** *<float>*, optional
A float value, serves as the value of a dummy feature whose coefficient Vertica uses to calculate the model intercept. Because the dummy feature is not in the training data, its values are set to a constant, by default set to 1.
- **intercept_mode:** *<str>*, optional
A string that specifies how to treat the intercept, one of the following: {regularized | unregularized}
- **class_weight:** *<list>*, optional
Specifies how to determine weights of the two classes. It can be in {None | auto} or a list of 2 elements.
- **max_iter:** *<int>*, optional
The maximum number of iterations that the algorithm performs.

Methods

The LinearSVC object has many methods:

```

# Add the LinearSVC prediction in a vDataframe
2 def add_to_vdf(self, vdf, name: str = "", cutoff: float = 0.5)

# Compute different metrics to evaluate the model
4 def classification_report(self, cutoff: float = 0.5)

# Draw the confusion matrix of the model
6 def confusion_matrix(self, cutoff: float = 0.5)

# Save a table or a view in the DB corresponding to the model predictions for
# all the classes
10 def deploy_to_DB(self, name: str, view: bool = True, cutoff = -1)

# Drop the model from the DB
12 def drop(self)

# Compute the importance of each feature
14 def features_importance(self)

# Fit the model with the input columns
16 def fit(self, input_relation: str, X: list, y: str, test_relation: str = "")

# Draw the Lift Chart
18 def lift_chart(self)

# Plot the SVM if it is possible (The length of X must be lesser or equal to
# 3)
20 def plot(self)

# Draw the PRC Curve
22 def prc_curve(self)

# Draw the ROC Curve
24 def roc_curve(self)

# Compute the selected metric
26 def score(self, cutoff: float = 0.5, method: str = "accuracy")

```

Attributes

The LinearSVC object has only one attribute:

```
1 self.coef # Informations about the model coefficients
```

Example

```


1 from vertica_ml_python import vDataframe
from vertica_ml_python.learn.svm import LinearSVC

```


```
3 # We create dummies
5 iris = vDataframe("iris", cur)
iris["Species"].get_dummies(use_numbers_as_suffix = True)
7 iris.to_db("iris_dummy")

9 # We can build the model
model = LinearSVC("svc_iris", cur)
11 model.fit("iris_dummy", ["PetalLengthCm", "SepalWidthCm", "SepalLengthCm"], "
    Species_0")

13 # We can draw the lift chart of the model
model.lift_chart()
```



```
# We can also draw the model
2 model.plot()
```



9.12.2 LinearSVR

Create a LinearSVR object by using the Highly Distributed and Scalable SVM on the data.

initialization

```

1 class LinearSVR(
2     name: str,
3     cursor,
4     tol: float = 1e-4,
5     C: float = 1.0,
6     fit_intercept: bool = True,
7     intercept_scaling: float = 1.0,
8     intercept_mode: str = "regularized",
9     acceptable_error_margin: float = 0.1,
10    max_iter: int = 100)

```

Parameters

- **name:** <str>
Name of the model.
- **cursor:** <object>
DB cursor.
- **tol:** <float>, optional
Used to control accuracy.
- **C:** <float>, optional
The weight for misclassification cost. The algorithm minimizes the regularization cost and the misclassification cost.

- **fit_intercept:** *<bool>*, optional
A bool to fit also the intercept.
- **intercept_scaling:** *<float>*, optional
A float value, serves as the value of a dummy feature whose coefficient Vertica uses to calculate the model intercept. Because the dummy feature is not in the training data, its values are set to a constant, by default set to 1.
- **intercept_mode:** *<str>*, optional
A string that specifies how to treat the intercept, one of the following: {regularized | unregularized}
- **acceptable_error_margin:** *<float>*, optional
Defines the acceptable error margin. Any data points outside this region add a penalty to the cost function.
- **max_iter:** *<int>*, optional
The maximum number of iterations that the algorithm performs.

Methods

The LinearSVR object has many methods:

```

# Add the LinearSVR prediction in a vDataframe
2 def add_to_vdf(self, vdf, name: str = "")

4 # Save a table or a view in the DB corresponding to the model predictions for
  all the classes
def deploy_to_DB(self, name: str, view: bool = True, cutoff = -1)

6 # Drop the model from the DB
8 def drop(self)

10 # Compute the importance of each feature
def features_importance(self)

12 # Fit the model with the input columns
14 def fit(self, input_relation: str, X: list, y: str, test_relation: str = "")

16 # Plot the SVM if it is possible (The length of X must be lesser or equal to
  3)
def plot(self)

18 # Compute different metrics to evaluate the model
20 def regression_report(self)

22 # Compute the selected metric
def score(self, method: str = "r2")

```

Attributes

The LinearSVR object has only one attribute:

```

1 self.coef # Informations about the model coefficients

```

Example

```

1 from vertica_ml_python.learn.svm import LinearSVR

3 # We can build the model
model = LinearSVR("svc_iris", cur)
5 model.fit("iris", ["SepalLengthCm"], "SepalWidthCm")

7 # We can evaluate the model
model.regression_report()

9
11 # Output
                                     value
11 explained_variance                -0.0357335274222341
13 max_error                        1.3548634384927
13 median_absolute_error             0.287106492764341
15 mean_absolute_error               0.342827242830171
15 mean_squared_error                0.193424390470397
17 r2                               -0.035736010600985

19 # We can also get the model coefficients
model.coef()

21
23 # Output
      predictor      coefficient
23 0      Intercept      2.71974116342001
25 1  sepallengthcm      0.0570869119451395

```

9.13 vertica_ml_python.learn.tree

The four following algorithm have the same methods and attributes than the Random Forest models. Decision trees can be seen as Random Forest with one tree and using the entire dataset. Dummy Trees are infinite depth Decision Trees.

9.13.1 DecisionTreeClassifier

```

1 def DecisionTreeClassifier(
      name: str,
3      cursor,
      max_features = "auto",
5      max_leaf_nodes: int = 1e9,
      max_depth: int = 100,
7      min_samples_leaf: int = 1,
      min_info_gain: float = 0.0,
9      nbins: int = 32)

```

Single Decision Tree Classifier.

9.13.2 DecisionTreeRegressor

```
1 def DecisionTreeRegressor(  
2     name: str,  
3     cursor,  
4     max_features = "auto",  
5     max_leaf_nodes: int = 1e9,  
6     max_depth: int = 100,  
7     min_samples_leaf: int = 1,  
8     min_info_gain: float = 0.0,  
9     nbins: int = 32)
```

Single Decision Tree Regressor.

9.13.3 DummyTreeClassifier

```
1 def DummyTreeClassifier(name: str, cursor)
```

Dummy Tree Classifier. This classifier learns by heart the training data.

9.13.4 DummyTreeRegressor

```
1 def DummyTreeRegressor(name: str, cursor)
```

Dummy Tree Regressor. This regressor learns by heart the training data.

10 Contact

If you have any question or issue, feel free to write it at <https://github.com/vertica/Vertica-ML-Python/issues>. If you really need a specific function or algorithm and it is feasible using Vertica SQL, I can make your wish come true. Write me at badr.ouali@microfocus.com and I will try to find a solution to your problem.

11 License

(c) Copyright [2019] Vertica or one of its affiliates. The library is licensed under the Apache License, Version 2.0 (the "License"); You may not use this file except in compliance with the License. You may obtain a copy of the License at: <http://www.apache.org/licenses/LICENSE-2.0> Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

