

COMP348 — Document Processing and the Semantic Web

Week 06 L1: Advanced Topics in Deep Learning

Diego Mollá

Department of Computer Science
Macquarie University

COMP348 2019H1

Programme

- 1 Text Generation
- 2 Encoder-Decoder Architecture
- 3 Open Challenges in Deep Learning

Reading

- Deep Learning book, section 8.1.

Programme

- 1 Text Generation
- 2 Encoder-Decoder Architecture
- 3 Open Challenges in Deep Learning

Generating Text Sequences

- One of the advances of deep learning versus shallower approaches to machine learning is its ability to process complex contexts.
- This has allowed enormous advances in image and text processing.
- We have seen how to process text sequences for text classification.

Text generation as a particular case of text classification

- Given a piece of text ...
- Predict the next character.

Text Generation as Character Prediction

- Our training data is a set of samples of the form:
 - Text fragment.
 - Next character to predict.
- This kind of data can be gathered from any corpus.
- Given a corpus, we can train a **language model** that can be used to generate text in the same style.




Figure 8.1 of Chollet (2018).

Implementing Character-level LSTM Text Generation

- The architecture of the model is as usual for text classification.
- The “class” to predict is the next character to generate.
- The input is a sequence of characters.
- If we wish to add an embeddings layer, This layer will learn **character embeddings**.

```
model = keras.models.Sequential()  
model.add(layers.Embedding(len(chars), 20, input_len=maxlen))  
model.add(layers.LSTM(128))  
model.add(layers.Dense(len(chars), activation='softmax'))
```

Generating Text

- Remember that the output of a prediction is a probability distribution.
- To generate the next character, we can sample from the probability distribution.
- We can determine how deterministic the sampling is:
 - We can always return the character with highest probability ...
 - Or we can select a character randomly ...
 - Or we can do something in between, according to a “temperature” parameter.

```
import numpy as np
def reweight_distribution(original_distribution, temperature=0.5):
    distribution = np.log(original_distribution) / temperature
    distribution = np.exp(distribution)
    return distribution / np.sum(distribution)
```

Figure: Different Reweightings




Figure 8.2 of Chollet (2018)

Example


See notebook ...

Programme

- 1 Text Generation
- 2 Encoder-Decoder Architecture
- 3 Open Challenges in Deep Learning

The Encoder-Decoder Architecture

- Composed of an **encoder** and a **decoder**.
- Revolutionised machine translation and many other text processing applications.
- The encoder stage can be something non-textual, e.g. images for caption generation.




[https:](https://towardsdatascience.com/understanding-encoder-decoder-sequence-to-sequence-model-679e04af4346)

[//towardsdatascience.com/understanding-encoder-decoder-sequence-to-sequence-model-679e04af4346](https://towardsdatascience.com/understanding-encoder-decoder-sequence-to-sequence-model-679e04af4346)

Training the Encoder-Decoder Architecture

A common approach to train the encoder-decoder architecture is to apply **teacher forcing**:


- Use the target sequence to guide the training of the decoder.
- For example, in an English to French machine translation system, we feed the target French translation to the decoder.



<https://blog.keras.io/a-ten-minute-introduction-to-sequence-to-sequence-learning-in-keras.html>

Attention: An Improvement on the Encoder-Decoder Architecture


Attention is an enhancement in the seq2seq architecture that allows to focus on parts of the input for generation.



https://github.com/tensorflow/tensorflow/blob/r1.13/tensorflow/contrib/eager/python/examples/nmt_with_attention/nmt_with_attention.ipynb

Attention for MT

Very useful to start understanding the decision processes of the model.



Attention in Caption Generation



A woman is throwing a frisbee in a park.


Xu et al. (2015) [arXiv:1502.03044](https://arxiv.org/abs/1502.03044)

Programme

- 1 Text Generation
- 2 Encoder-Decoder Architecture
- 3 Open Challenges in Deep Learning

Interpretability

- It is very difficult to interpret most weights in a neural model.
- Approaches like attention help to visualise some of the processes but much more is needed.
- Current research in image processing can visualise interpretations of middle layers. How to do the same with text?



http://vision03.csail.mit.edu/cnn_art/index.html

Justifiability

How can someone justify a decision made by a neural model?

EBMSummariser - Mozilla Firefox

EBMSummariser

If you happen to land on this page and wonder what this is all about, check [our project page at Macquarie University](#). Use these results at your own risk! [PubMed clinical queries filters]

what is the best treatment for headache? Search

Group 1 Group 2 Group 3 Group 4 Group 5

50 results in 5 groups: Expand All Close All

1. Keywords: migraine; vestibular; without; training; damaging **Quality of Evidence:** [Progress Bar]

Summary: The presenting symptoms were dizziness, headache, fatigue, and imbalance. ... This article provides the practicing neurologist with a comprehensive, evidence-based approach to the diagnosis and management of headache in children and adolescents, with a focus on migraine.

9 results Expand

2. Keywords: ncc; report; via; valproate; clinical **Quality of Evidence:** [Progress Bar]

Summary: To the best of our knowledge, VIA has not been studied in the trigeminal area, where it could be relevant for the control of headache. ... The objective of this study was to evaluate the 22-item Sino-Nasal Outcome Test (SNOT-22) score patterns in patients with confirmed non-sinogenic headache in order to develop negative predictors of CRS.

11 results Expand

Small Training Data

- Deep learning excels when there are large volumes of training data.
- But obtaining labelled training data is expensive ...
 - ⇒ We can add unsupervised and semi-supervised tasks.
- ... and some domains and languages have very little data ...
 - ⇒ Transfer learning: Pre-train on one domain and adapt the learnt model to another domain.

Small Training Data

- Deep learning excels when there are large volumes of training data.
- But obtaining labelled training data is expensive ...
 - ⇒ We can add unsupervised and semi-supervised tasks.
- ... and some domains and languages have very little data ...
 - ⇒ Transfer learning: Pre-train on one domain and adapt the learnt model to another domain.

Small Training Data

- Deep learning excels when there are large volumes of training data.
- But obtaining labelled training data is expensive ...
 - ⇒ We can add unsupervised and semi-supervised tasks.
- ... and some domains and languages have very little data ...
 - ⇒ Transfer learning: Pre-train on one domain and adapt the learnt model to another domain.

Small Training Data

- Deep learning excels when there are large volumes of training data.
- But obtaining labelled training data is expensive ...
 - ⇒ We can add unsupervised and semi-supervised tasks.
- ... and some domains and languages have very little data ...
 - ⇒ **Transfer learning**: Pre-train on one domain and adapt the learnt model to another domain.

Small Training Data

- Deep learning excels when there are large volumes of training data.
- But obtaining labelled training data is expensive ...
 - ⇒ We can add unsupervised and semi-supervised tasks.
- ... and some domains and languages have very little data ...
 - ⇒ **Transfer learning**: Pre-train on one domain and adapt the learnt model to another domain.

Incorporating Knowledge

- Early natural language systems could easily incorporate knowledge.
 - Ontologies, databases, information given by the user, etc.
- Deep learning approaches find this more difficult.
- Question answering and dialogue systems often do not remember what has been said before.

message Where do you live now?

response I live in Los Angeles.

message In which city do you live now?


response I live in Madrid.

message In which country do you live now?


response England, you?

Vinyals & Le (2015) <https://arxiv.org/abs/1506.05869>


Incorporating Linguistic Knowledge



Deep Learning is Not Everything



Deep Learning is with the
“Connectionists” tribe.



Take-home Messages

- 1 Text generation as a task of character (or word) prediction.
- 2 We may want to control the level of randomness when generating text based on a “temperature” parameter.
- 3 Describe the encoder-decoder architecture. What is this architecture good for?
- 4 What is teacher forced training and what is it good for?
- 5 Comment on current open challenges in deep learning.

What's Next

Weeks 7-12

- Semantic Web (Rolf Schwitter).
- Assignment 2 submission deadline on Friday 26 April 2019.