

**NOLLE**

**Damien**

**L3 – Informatique**

**Base de Données (Devoir 2) :**

<b><u>Note :</u></b>	<b><u>Observation :</u></b>
<b>/20</b>	

Q1 :

```
SELECT DISTINCT NomClient
FROM CLIENT
INNER JOIN RESERVATION ON RESERVATION.ID_Client = CLIENT.ID_Client
INNER JOIN HOTEL ON HOTEL.ID_Hotel = RESERVATION.ID_Hotel
INNER JOIN STATION ON STATION.ID_Station = HOTEL.ID_Station
WHERE NomHotel = "Les Ducs de Savoie"
AND NomStation = "Courcheval"
```

Q2 :

```
SELECT DISTINCT HOTEL.NomHotel
FROM HOTEL
INNER JOIN RESERVATION AS R1 ON R1.ID_Hotel = HOTEL.ID_Hotel
INNER JOIN CLIENT AS C1 ON R1.ID_Client = C1.ID_Client
WHERE C1.NomClient = "Dupont"
AND R1.ID_Hotel IN (SELECT R2.ID_Hotel
                    FROM RESERVATION AS R2
                    INNER JOIN CLIENT AS C2 ON R2.ID_Client = C2.ID_Client
                    WHERE C2.NomClient = "Dubois")
```

Q3 :

```
SELECT COUNT(*) AS nb_hotels
FROM HOTEL
INNER JOIN STATION ON STATION.ID_Station = HOTEL.ID_STATION
WHERE NomStation = "Meribel"
```

Q4 :

```
SELECT NomClient
FROM CLIENT
INNER JOIN RESERVATION AS R1 ON R1.ID_Client = CLIENT.ID_Client
WHERE R1.ID_Hotel IN (SELECT R2.ID_Hotel
                      FROM RESRVATION AS R2
                      WHERE R2.ID_Client = "CR148-20-03")
```

Q5 :

```
SELECT NomStation, COUNT(*) AS nb_hotel, SUM(NombrePlaces) AS total_nb_places
FROM STATION
INNER JOIN HOTEL ON HOTEL.ID_Station = STATION.ID_Station
GROUP BY NomStation
```

Q6 :

```
SELECT NomStation
FROM STATION
INNER JOIN HOTEL ON HOTEL.ID_Station = STATION.ID_Station
GROUP BY NomStation
HAVING SUM(NombrePlaces) >= 100
```

Q7 :

```
SELECT R1.ID_Client
FROM RESERVATION AS R1
WHERE NOT EXISTS (SELECT S1.ID_Station
                  FROM STATION AS S1
                  WHERE NOT EXISTS (SELECT HOTEL.ID_Station, R2.ID_Client
                                    FROM RESERVATION AS R2
                                    INNER JOIN HOTEL ON HOTEL.ID_Hotel = R2.ID_Hotel
                                    WHERE HOTEL.ID_Station = S1.ID_Station
                                    AND R2.ID_Client = R1.ID_Client))
```

Q8 :

```
SELECT NomClient
FROM CLIENT
WHERE ID_Client NOT IN (SELECT DISTINCT RESERVATION.ID_Client
                        FROM RESERVATION
                        INNER JOIN HOTEL ON HOTEL.ID_Hotel = RESERVATION.ID_Hotel
                        WHERE ID_Station = 45)
```