

Command-line interface for the DNSFilter API

dnshcli Reference Guide

Complete command reference, tested examples, CSV bulk-import workflows, and output flag usage for every endpoint in the DNSFilter API.

TOOL VERSION

0.1.0

UPDATED

2026-07-13

AUDIENCE

Developers & Administrators

Getting Started

dnsfcli is a command-line tool for the full DNSFilter REST API. Install it once, store your credentials in the OS keychain, and manage every aspect of your DNSFilter account from the terminal — no browser required.

1 Install

Python 3.9 or later is required.

SHELL / INSTALL

```
pip install -e . # or run directly: python dnsfcli.py --help
```

2 Store credentials

Your API token and default organization ID are stored in the OS keychain (macOS Keychain / Windows Credential Manager / Linux Secret Service) and used automatically on every subsequent command.

SHELL / AUTH SETUP

```
python dnsfcli.py auth setup python dnsfcli.py auth setup --org-id 802315 python  
dnsfcli.py auth verify python dnsfcli.py auth show
```

Command Structure

Every command follows the same three-part pattern.

REFERENCE / COMMAND STRUCTURE

```
python dnsfcli.py [endpoint] [function] [--param value ...] # Examples python dnsfcli.py  
policies list python dnsfcli.py policies show --id 285109 python dnsfcli.py policies create --
```

```
name "Guest WiFi" --organization_id 802315 python dnsfcli.py policies update --id 285109
--name "Updated" python dnsfcli.py policies delete --id 285109
```

Global Flags

These flags work on any command and can appear anywhere in the argument list (before the endpoint, between endpoint and function, or after all other flags).

Output & format

--raw, -r	Print the raw JSON response instead of the formatted table.
--json / --jsonl	JSON (or one object per line) on stdout. Automatic when output is piped.
--output FMT	Unified format switch: table, json, jsonl, raw, csv, or none.
--columns a,b,c	Limit table/CSV output to the named columns.
--preset NAME	Apply a named column preset from config (column_presets.NAME).
--format TMPL	Render each row through a template — both "{name} ({id})" and "{[{.name}]}" styles work.
--format-preset N	Apply a named format template from config (format_presets.NAME).
--bundle NAME	Apply a named command bundle from config (columns + filter + sort + format).
--pick FIELD	Print a single field, one value per line — ideal for piping.
--jq PATH	Extract a dotted path (data.0.name) from the response before output.
--to-csv FILE	Write the response to FILE as CSV (use - for stdout).
--to-json FILE	Write the response to FILE as JSON.
--to-markdown FILE	Write the response to FILE as a Markdown table (use - for stdout).
--tee FILE	Save a copy of everything printed to FILE.
--quiet, -q	Suppress status chatter; result data still prints.
--no-color	Disable ANSI colour output (NO_COLOR env also honoured).

Filtering, sorting & aggregation

--filter EXPR	Keep matching rows: field=value, field!=value, field~substr, field>N, >=, <, <=.
--filter-mode or	OR logic across multiple --filter flags (default: AND).
--grep REGEX	Keep rows where any field matches the regex.
--unique FIELD	Drop rows with a duplicate value in FIELD.
--sort FIELD	Sort by field; prefix with - for descending (--sort -created_at).
--limit N / --last N	Return at most N results / the last N results.
--count	Print the result count only.

<code>--count-by FIELD</code>	Frequency table of FIELD values.
<code>--group-by FIELD</code>	Group results by FIELD value.
<code>--sum / --avg / --min / --max F</code>	Aggregate a numeric field and print one value.
<code>--select a,b / --exclude a,b</code>	Keep only (or remove) the named fields from every item.
<code>--not-null F / --is-null F</code>	Keep rows where FIELD is (or is not) null.

Pagination

<code>--all</code>	Fetch every page of paginated results.
<code>--page N / --page-size N</code>	Request a specific page / page size.
<code>--max-pages N</code>	Cap the number of pages fetched by <code>--all</code> .
<code>--paginate-until E</code>	Stop <code>--all</code> pagination once any item matches filter expression E.

Batch & CSV input

<code>--from-csv FILE</code>	Read input rows from FILE — one API call per row (use - for stdin).
<code>--template</code>	Print a blank CSV import template for this command and exit. No auth needed.
<code>--skip-rows N / --max-rows N</code>	Resume an interrupted batch / cap rows processed.
<code>--batch-report FILE</code>	Write a JSON run summary (per-row outcomes, counts) to FILE.
<code>--on-error MODE</code>	stop or continue when a batch row fails.
<code>--errors-to-csv FILE</code>	Write failed rows to FILE for later retry (<code>--retry-errors-csv</code>).
<code>--confirm-each</code>	Prompt before each batch row.
<code>--validate-only</code>	Validate the CSV and exit without calling the API.
<code>--dry-run / --plan</code>	Show what would be sent without making any API calls.
<code>--yes, -y</code>	Skip confirmation prompts.

Transformation

<code>--add-field K=V</code>	Inject a static field into every result item.
<code>--transform F=EXPR</code>	Compute a new field from a restricted expression (<code>ratio=blocked/total</code>).
<code>--map FIELD=OP</code>	Transform a field value: upper, lower, strip, title, truncate:N.
<code>--join EP:LK=RK</code>	Client-side join: fetch endpoint EP, match local key LK to remote key RK.
<code>--rename A=B</code>	Rename field A to B in the output.
<code>--flatten</code>	Flatten nested objects into dotted keys.
<code>--strip-nulls</code>	Remove null-valued keys from every item.

Multi-organization

<code>--each-org</code>	Run the command once per organization on the account.
<code>--org-csv FILE</code>	Load the <code>--each-org</code> organization list from a CSV file.
<code>--org-filter REGEX</code>	Restrict <code>--each-org</code> to organizations whose name matches.
<code>--max-orgs N</code>	Cap the number of organizations processed.

<code>--parallel-orgs</code>	Process organizations concurrently (<code>--org-concurrency N</code>).
Watch, monitor & CI	
<code>--watch N</code>	Re-run the command every N seconds (Ctrl-C to stop).
<code>--watch-until EXPR</code>	Stop watching once any result matches the filter expression.
<code>--watch-diff</code>	Show only what changed between watch ticks.
<code>--alert EXPR</code>	Ring the terminal bell and print a banner when a result matches.
<code>--fail-on-empty</code>	Exit 1 when the result list is empty (messages go to stderr).
<code>--fail-on-pattern E</code>	Exit 1 when any result row matches filter expression E.
<code>--exec CMD</code>	Run a shell command per result row with {field} substitution (values are shell-quoted).
Connection & authentication	
<code>--api-key TOKEN</code>	Override the keychain token for this call only (prefer <code>DNSF_API_KEY</code>).
<code>--org-id ID</code>	Override the stored organization ID for this call only.
<code>--profile NAME</code>	Use a named credential profile.
<code>--timeout N / --connect-timeout N</code>	Read / connect timeouts in seconds.
<code>--rate N</code>	Client-side request-per-second cap.
<code>--retry N</code>	Retry attempts for failed batch rows.
<code>--header K=V</code>	Add a custom request header (scrubbed from history logs).
<code>--proxy URL</code>	Route requests through a proxy (scrubbed from history logs).
<code>--env-file FILE</code>	Load KEY=VALUE pairs into the environment before running.
<code>--cache-ttl N</code>	Serve identical GETs from a local cache for N seconds.

Discovery

Explore every available endpoint and function without leaving the terminal.

SHELL / DISCOVERY

```
# List all 36 endpoint groups python dnsfcli.py endpoints # List all functions for one
endpoint python dnsfcli.py endpoints policies # Get a pre-filled CSV template for any write
operation python dnsfcli.py policies create --template python dnsfcli.py policies create --
template > policies-template.csv
```

agent-local-users

Agent local user management.

bulk-delete

Bulk delete agent local users.

```
SHELL / AGENT-LOCAL-USERS BULK-DELETE
```

```
python dnsfcli.py agent-local-users bulk-delete --ids ["1001","1002","1003"]
```

bulk-delete-counts

Count agent local users matching bulk-delete criteria.

```
SHELL / AGENT-LOCAL-USERS BULK-DELETE-COUNTS
```

```
python dnsfcli.py agent-local-users bulk-delete-counts
```

bulk-delete-show

Show a bulk-delete job.

```
SHELL / AGENT-LOCAL-USERS BULK-DELETE-SHOW
```

```
python dnsfcli.py agent-local-users bulk-delete-show \ --id 9b2f6c04-5a1e-4d37-8c2a-f0e1d2c3b4a5
```

delete

Permanently delete a resource by ID.

```
SHELL / AGENT-LOCAL-USERS DELETE
```

```
python dnsfcli.py agent-local-users delete \ --id 9b2f6c04-5a1e-4d37-8c2a-f0e1d2c3b4a5
```

list

Retrieve a paginated list of resources.

```
SHELL / AGENT-LOCAL-USERS LIST
```

```
python dnsfcli.py agent-local-users list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

```
SHELL / AGENT-LOCAL-USERS LIST-ALL
```

```
python dnsfcli.py agent-local-users list-all
```

show

Retrieve a single resource by ID.

```
SHELL / AGENT-LOCAL-USERS SHOW
```

```
python dnsfcli.py agent-local-users show \ --id 9b2f6c04-5a1e-4d37-8c2a-f0e1d2c3b4a5
```

update

Update an existing resource by ID.

```
SHELL / AGENT-LOCAL-USERS UPDATE
```

```
python dnsfcli.py agent-local-users update \ --id 9b2f6c04-5a1e-4d37-8c2a-f0e1d2c3b4a5 \ --friendly_name "Jane Smith Laptop" \ --policy_id 285109
```

api-keys

API key management.

create

Create a new resource.

```
SHELL / API-KEYS CREATE
```

```
python dnsfcli.py api-keys create --name "CI Pipeline Key" --expiry 2027-05-31
```

delete

Permanently delete a resource by ID.

```
SHELL / API-KEYS DELETE
```

```
python dnsfcli.py api-keys delete --id 20981
```

list

Retrieve a paginated list of resources.

```
SHELL / API-KEYS LIST
```

```
python dnsfcli.py api-keys list --page 1 --per_page 25
```

revoke

Revoke an API key immediately without deleting it.

```
SHELL / API-KEYS REVOKE
```

```
python dnsfcli.py api-keys revoke --id 20981
```

show

Retrieve a single resource by ID.

```
SHELL / API-KEYS SHOW
```



```
python dnsfcli.py api-keys show --id 20981
```

application-categories

Application category reference.

list

Retrieve a paginated list of resources.

```
SHELL / APPLICATION-CATEGORIES LIST
```

```
python dnsfcli.py application-categories list --page 1 --per_page 25
```

show

Retrieve a single resource by ID.

```
SHELL / APPLICATION-CATEGORIES SHOW
```

```
python dnsfcli.py application-categories show --id 12345
```

applications

Application catalog.

list

Retrieve a paginated list of resources.

```
SHELL / APPLICATIONS LIST
```

```
python dnsfcli.py applications list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

```
SHELL / APPLICATIONS LIST-ALL
```

```
python dnsfcli.py applications list-all
```

show

Retrieve a single resource by ID.

```
SHELL / APPLICATIONS SHOW
```

```
python dnsfcli.py applications show --id 12345
```

billing

Billing and subscription.

create

Create a new resource.

```
SHELL / BILLING CREATE
```

```
python dnsfcli.py billing create \ --organization_id 802315 \ --payment_token  
tok_visa_4242
```

get-address

Retrieve the billing address for an organization.

```
SHELL / BILLING GET-ADDRESS
```

```
python dnsfcli.py billing get-address --organization_id 802315
```

show

Retrieve a single resource by ID.

```
SHELL / BILLING SHOW
```

```
python dnsfcli.py billing show
```

update-address

Update the billing address for an organization.

```
SHELL / BILLING UPDATE-ADDRESS
```

```
python dnsfcli.py billing update-address \ --organization_id 802315 \ --first_name Jane \ --last_name Smith \ --line1 "123 Main St" \ --city Denver \ --state Colorado \ --zip 80202 \ --country US
```

block-pages

Custom block page configuration.

create

Create a new resource.

```
SHELL / BLOCK-PAGES CREATE
```

```
python dnsfcli.py block-pages create \ --name "Corporate Block Page" \ --block_org_name "Acme Corp" \ --block_email_addr admin@company.com
```

delete

Permanently delete a resource by ID.

```
SHELL / BLOCK-PAGES DELETE
```

```
python dnsfcli.py block-pages delete --id 12345
```

list

Retrieve a paginated list of resources.

```
SHELL / BLOCK-PAGES LIST
```

```
python dnsfcli.py block-pages list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

```
SHELL / BLOCK-PAGES LIST-ALL
```

```
python dnsfcli.py block-pages list-all
```

show

Retrieve a single resource by ID.

```
SHELL / BLOCK-PAGES SHOW
```

```
python dnsfcli.py block-pages show --id 12345
```

update

Update an existing resource by ID.

```
SHELL / BLOCK-PAGES UPDATE
```

```
python dnsfcli.py block-pages update \ --id 12345 \ --name "Corporate Block Page  
Updated"
```

categories

DNS filtering category reference.

list

Retrieve a paginated list of resources.

```
SHELL / CATEGORIES LIST
```

```
python dnsfcli.py categories list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

```
SHELL / CATEGORIES LIST-ALL
```

```
python dnsfcli.py categories list-all
```

show

Retrieve a single resource by ID.

```
SHELL / CATEGORIES SHOW
```

```
python dnsfcli.py categories show --id 12345
```

collections

Collection user membership.

users-add

Add a user to an organization or collection.

```
SHELL / COLLECTIONS USERS-ADD
```

```
python dnsfcli.py collections users-add --collection_id 7788 --id 42618
```

users-list

List users within a specific organization or collection.

```
SHELL / COLLECTIONS USERS-LIST
```

```
python dnsfcli.py collections users-list --collection_id 7788
```

users-remove

Remove a user from a collection.

```
SHELL / COLLECTIONS USERS-REMOVE
```

```
python dnsfcli.py collections users-remove --collection_id 7788 --id 12345
```

users-show

Retrieve a specific user within an organization or collection.

```
SHELL / COLLECTIONS USERS-SHOW
```

```
python dnsfcli.py collections users-show --collection_id 7788 --id 12345
```


current-user

Authenticated user profile.

show

Retrieve a single resource by ID.

```
SHELL / CURRENT-USER SHOW  
python dnsfcli.py current-user show
```

update

Update an existing resource by ID.

```
SHELL / CURRENT-USER UPDATE  
python dnsfcli.py current-user update --first_name Jane --last_name Smith
```

dictionary

API dictionary / reference data.

qp-methods

Retrieve the list of supported QP method types.

```
SHELL / DICTIONARY QP-METHODS  
python dnsfcli.py dictionary qp-methods
```

domains

Domain lookup and classification.

bulk-lookup

Classify multiple domains in a single request.

```
SHELL / DOMAINS BULK-LOOKUP
```

```
python dnsfcli.py domains bulk-lookup
```

suggest-threat

Submit a domain for threat-intel review.

```
SHELL / DOMAINS SUGGEST-THREAT
```

```
python dnsfcli.py domains suggest-threat
```

user-lookup

Look up a domain for an authenticated user session.

```
SHELL / DOMAINS USER-LOOKUP
```

```
python dnsfcli.py domains user-lookup
```

enterprise-connections

Enterprise SSO connection management.

create

Create a new resource.

SHELL / ENTERPRISE-CONNECTIONS CREATE

```
python dnsfcli.py enterprise-connections create \ --client_id my-client-id \ --client_secret my-secret \ --discovery_url "https://idp.company.com/.well-known/openid-configuration" \ --strategy oidc \ --display_name "Company SSO"
```

delete

Permanently delete a resource by ID.

SHELL / ENTERPRISE-CONNECTIONS DELETE

```
python dnsfcli.py enterprise-connections delete --id 12345
```

list

Retrieve a paginated list of resources.

SHELL / ENTERPRISE-CONNECTIONS LIST

```
python dnsfcli.py enterprise-connections list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

SHELL / ENTERPRISE-CONNECTIONS LIST-ALL

```
python dnsfcli.py enterprise-connections list-all
```

show

Retrieve a single resource by ID.

SHELL / ENTERPRISE-CONNECTIONS SHOW

```
python dnsfcli.py enterprise-connections show --id 12345
```

update

Update an existing resource by ID.

```
SHELL / ENTERPRISE-CONNECTIONS UPDATE
```

```
python dnsfcli.py enterprise-connections update \ --id 12345 \ --display_name "Company  
SSO Updated"
```

invoices

Invoice history.

current

Retrieve the current billing period's invoice.

```
SHELL / INVOICES CURRENT
```

```
python dnsfcli.py invoices current
```

list

Retrieve a paginated list of resources.

```
SHELL / INVOICES LIST
```

```
python dnsfcli.py invoices list --page 1 --per_page 25
```

show

Retrieve a single resource by ID.

```
SHELL / INVOICES SHOW
```

```
python dnsfcli.py invoices show --id 12345
```

ip-addresses

IP address management.

create

Create a new resource.

SHELL / IP-ADDRESSES CREATE

```
python dnsfcli.py ip-addresses create \ --address 203.0.113.5 \ --organization_id 802315 \ --network_id 736401
```

delete

Permanently delete a resource by ID.

SHELL / IP-ADDRESSES DELETE

```
python dnsfcli.py ip-addresses delete --id 12345
```

list

Retrieve a paginated list of resources.

SHELL / IP-ADDRESSES LIST

```
python dnsfcli.py ip-addresses list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

SHELL / IP-ADDRESSES LIST-ALL

```
python dnsfcli.py ip-addresses list-all
```

myip

Return the public IP address of the calling client.

SHELL / IP-ADDRESSES MYIP

```
python dnsfcli.py ip-addresses myip
```

show

Retrieve a single resource by ID.

```
SHELL / IP-ADDRESSES SHOW
```

```
python dnsfcli.py ip-addresses show --id 12345
```

update

Update an existing resource by ID.

```
SHELL / IP-ADDRESSES UPDATE
```

```
python dnsfcli.py ip-addresses update --id 12345 --address 203.0.113.5
```

verify

Verify whether an IP address is registered.

```
SHELL / IP-ADDRESSES VERIFY
```

```
python dnsfcli.py ip-addresses verify
```

mac-addresses

MAC address management.

create

Create a new resource.

```
SHELL / MAC-ADDRESSES CREATE
```

```
python dnsfcli.py mac-addresses create \ --organization_id 802315 \ --address  
"AA:BB:CC:DD:EE:FF" \ --filter_value "Reception Printer" \ --policy_id 285109
```

delete

Permanently delete a resource by ID.

```
SHELL / MAC-ADDRESSES DELETE
```

```
python dnsfcli.py mac-addresses delete --id 12345
```

list

Retrieve a paginated list of resources.

```
SHELL / MAC-ADDRESSES LIST
```

```
python dnsfcli.py mac-addresses list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

```
SHELL / MAC-ADDRESSES LIST-ALL
```



```
python dnsfcli.py mac-addresses list-all
```

show

Retrieve a single resource by ID.

```
SHELL / MAC-ADDRESSES SHOW
```

```
python dnsfcli.py mac-addresses show --id 12345
```

update

Update an existing resource by ID.

```
SHELL / MAC-ADDRESSES UPDATE
```

```
python dnsfcli.py mac-addresses update \ --id 12345 \ --address "AA:BB:CC:DD:EE:FF" \ --  
filter_value "Updated Label"
```

metrics

Organization usage metrics.

org-usage

Organization usage metrics.

```
SHELL / METRICS ORG-USAGE
```

```
python dnsfcli.py metrics org-usage --id 802315
```

org-usage-detailed

Detailed organization usage metrics.

SHELL / METRICS ORG-USAGE-DETAILED

```
python dnsfcli.py metrics org-usage-detailed --id 802315
```

networks

Network management.

bulk-create

Create multiple resources in a single async job.

```
SHELL / NETWORKS BULK-CREATE  
python dnsfcli.py networks bulk-create
```

bulk-create-show

Check the status of a bulk-create job.

```
SHELL / NETWORKS BULK-CREATE-SHOW  
python dnsfcli.py networks bulk-create-show --id 736401
```

bulk-destroy

Delete multiple resources in a single async job.

```
SHELL / NETWORKS BULK-DESTROY  
python dnsfcli.py networks bulk-destroy
```

bulk-destroy-show

Check the status of a bulk-destroy job.

```
SHELL / NETWORKS BULK-DESTROY-SHOW  
python dnsfcli.py networks bulk-destroy-show --id 736401
```

bulk-update

Update multiple resources in a single operation.

```
SHELL / NETWORKS BULK-UPDATE
```

```
python dnsfcli.py networks bulk-update --ids 736401,736402 --policy_id 285109
```

bulk-update-show

Check the status of a bulk-update job.

```
SHELL / NETWORKS BULK-UPDATE-SHOW
```

```
python dnsfcli.py networks bulk-update-show --id 736401
```

counts

Return counts of resources matching optional filters.

```
SHELL / NETWORKS COUNTS
```

```
python dnsfcli.py networks counts
```

create

Create a new resource.

```
SHELL / NETWORKS CREATE
```

```
python dnsfcli.py networks create \ --name "HQ Network" \ --organization_id 802315 \ --  
policy_ids ["285109"] \ --physical_address "123 Main St, Denver CO"
```

delete

Permanently delete a resource by ID.

```
SHELL / NETWORKS DELETE
```

```
python dnsfcli.py networks delete --id 736401
```

geo

Return geographic information for resources.

```
SHELL / NETWORKS GEO
```

```
python dnsfcli.py networks geo
```

lan-ip-show

Retrieve a single LAN IP address entry.

```
SHELL / NETWORKS LAN-IP-SHOW
```

```
python dnsfcli.py networks lan-ip-show --id 736401 --lan_ip_id 9901
```

lan-ip-update

Update the name of a LAN IP address entry.

```
SHELL / NETWORKS LAN-IP-UPDATE
```

```
python dnsfcli.py networks lan-ip-update \ --id 736401 \ --lan_ip_id 9901 \ --name  
"Reception Desk"
```

lan-ips

List LAN IP addresses registered to a network.

```
SHELL / NETWORKS LAN-IPS
```

```
python dnsfcli.py networks lan-ips --id 736401
```

list

Retrieve a paginated list of resources.

```
SHELL / NETWORKS LIST
```

```
python dnsfcli.py networks list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

```
SHELL / NETWORKS LIST-ALL
```

```
python dnsfcli.py networks list-all
```

lookup

Find a resource matching a specific value.

```
SHELL / NETWORKS LOOKUP
```

```
python dnsfcli.py networks lookup
```

msp

List resources visible to the MSP account.

```
SHELL / NETWORKS MSP
```

```
python dnsfcli.py networks msp
```

msp-all

List all resources visible to the MSP account.

```
SHELL / NETWORKS MSP-ALL
```

```
python dnsfcli.py networks msp-all
```

secret-key-create

Generate a new network secret key.

```
SHELL / NETWORKS SECRET-KEY-CREATE
```

```
python dnsfcli.py networks secret-key-create --id 736401
```

secret-key-delete

Delete the network secret key.

```
SHELL / NETWORKS SECRET-KEY-DELETE
```

```
python dnsfcli.py networks secret-key-delete --id 736401
```

secret-key-update

Rotate the network secret key.

```
SHELL / NETWORKS SECRET-KEY-UPDATE
```

```
python dnsfcli.py networks secret-key-update --id 736401
```

show

Retrieve a single resource by ID.

```
SHELL / NETWORKS SHOW
```

```
python dnsfcli.py networks show --id 736401
```

subnets

List all subnets across all networks.

```
SHELL / NETWORKS SUBNETS
```

```
python dnsfcli.py networks subnets
```

subnets-create

Add a subnet IP range to a network.

```
SHELL / NETWORKS SUBNETS-CREATE
```

```
python dnsfcli.py networks subnets-create \ --id 736401 \ --name "Sales Floor" \ --from  
10.0.1.0 \ --to 10.0.1.255
```

subnets-delete

Remove a subnet from a network.

```
SHELL / NETWORKS SUBNETS-DELETE
```

```
python dnsfcli.py networks subnets-delete --id 736401 --subnet_id 4455
```

subnets-list

List subnets within a specific network.

```
SHELL / NETWORKS SUBNETS-LIST
```

```
python dnsfcli.py networks subnets-list --id 736401
```

subnets-show

Retrieve a specific subnet.

```
SHELL / NETWORKS SUBNETS-SHOW
```

```
python dnsfcli.py networks subnets-show --id 736401 --subnet_id 4455
```


subnets-update

Update an existing subnet's name or IP range.

SHELL / NETWORKS SUBNETS-UPDATE

```
python dnsfcli.py networks subnets-update \ --id 736401 \ --subnet_id 4455 \ --name  
"Sales Floor Renamed" \ --from 10.0.1.0 \ --to 10.0.1.255
```

update

Update an existing resource by ID.

SHELL / NETWORKS UPDATE

```
python dnsfcli.py networks update \ --id 736401 \ --name "HQ Network Updated" \ --  
organization_id 802315
```

organizations

Organization management.

bulk-update

Update multiple resources in a single operation.

SHELL / ORGANIZATIONS BULK-UPDATE

```
python dnsfcli.py organizations bulk-update \ --organization_ids ["802315","802316"] \ --  
gdpr true
```

cancel

Cancel an organization's subscription.

SHELL / ORGANIZATIONS CANCEL

```
python dnsfcli.py organizations cancel --id 802315
```

create

Create a new resource.

```
SHELL / ORGANIZATIONS CREATE
```

```
python dnsfcli.py organizations create \ --name "New Client Corp" \ --billing_contact_email  
admin@company.com \ --sku professional
```

delete

Permanently delete a resource by ID.

```
SHELL / ORGANIZATIONS DELETE
```

```
python dnsfcli.py organizations delete --id 802315
```

list

Retrieve a paginated list of resources.

```
SHELL / ORGANIZATIONS LIST
```

```
python dnsfcli.py organizations list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

```
SHELL / ORGANIZATIONS LIST-ALL
```

```
python dnsfcli.py organizations list-all
```

settings

Retrieve organization-level settings.

```
SHELL / ORGANIZATIONS SETTINGS
```

```
python dnsfcli.py organizations settings
```

show

Retrieve a single resource by ID.

```
SHELL / ORGANIZATIONS SHOW
```

```
python dnsfcli.py organizations show --id 802315
```

update

Update an existing resource by ID.

```
SHELL / ORGANIZATIONS UPDATE
```

```
python dnsfcli.py organizations update \ --id 802315 \ --name "New Client Corp Updated"
```

users-create

Add a new user to an organization.

```
SHELL / ORGANIZATIONS USERS-CREATE
```

```
python dnsfcli.py organizations users-create \ --organization_id 802315 \ --email  
admin@company.com \ --first_name Jane \ --last_name Smith \ --role administrator
```

users-delete

Remove a user from an organization or collection.

SHELL / ORGANIZATIONS USERS-DELETE

```
python dnsfcli.py organizations users-delete \ --organization_id 802315 \ --id 802315
```

users-list

List users within a specific organization or collection.

SHELL / ORGANIZATIONS USERS-LIST

```
python dnsfcli.py organizations users-list --organization_id 802315
```

users-resend-invite

Re-send the email invitation to an org user.

SHELL / ORGANIZATIONS USERS-RESEND-INVITE

```
python dnsfcli.py organizations users-resend-invite \ --organization_id 802315 \ --id 802315
```

users-show

Retrieve a specific user within an organization or collection.

SHELL / ORGANIZATIONS USERS-SHOW

```
python dnsfcli.py organizations users-show --organization_id 802315 --id 802315
```

users-update

Update a user's role or details within an organization.

SHELL / ORGANIZATIONS USERS-UPDATE

```
python dnsfcli.py organizations users-update \ --organization_id 802315 \ --id 802315 \ --role read_only
```

policies

DNS filtering policy management.

add-allowed-application

Allow a specific application on a policy.

```
SHELL / POLICIES ADD-ALLOWED-APPLICATION
```

```
python dnsfcli.py policies add-allowed-application --id 12345 --name TikTok
```

add-blacklist-category

Block all domains in a category on a policy.

```
SHELL / POLICIES ADD-BLACKLIST-CATEGORY
```

```
python dnsfcli.py policies add-blacklist-category --id 12345 --category_id 2
```

add-blacklist-domain

Block a specific domain on a policy.

```
SHELL / POLICIES ADD-BLACKLIST-DOMAIN
```

```
python dnsfcli.py policies add-blacklist-domain \ --id 12345 \ --domain  
malware.example.com \ --note "Flagged by threat intel"
```

add-blocked-application

Block a specific application on a policy.

```
SHELL / POLICIES ADD-BLOCKED-APPLICATION
```

```
python dnsfcli.py policies add-blocked-application --id 12345 --name TikTok
```

add-whitelist-domain

Allow a specific domain on a policy.

```
SHELL / POLICIES ADD-WHITELIST-DOMAIN
```

```
python dnsfcli.py policies add-whitelist-domain \ --id 12345 \ --domain internal.corp.com
```

application

List policies with application filtering enabled.

```
SHELL / POLICIES APPLICATION
```

```
python dnsfcli.py policies application
```

application-update

Update application filtering settings across policies.

```
SHELL / POLICIES APPLICATION-UPDATE
```

```
python dnsfcli.py policies application-update
```

bulk-add-allowlist

Add domains to the allowlist on multiple policies at once.

```
SHELL / POLICIES BULK-ADD-ALLOWLIST
```

```
python dnsfcli.py policies bulk-add-allowlist \ --policy_ids ["285109","331207"] \ --domains  
["safe.com","trusted.org"]
```

bulk-add-blocklist

Add domains to the blocklist on multiple policies at once.

```
SHELL / POLICIES BULK-ADD-BLOCKLIST
```

```
python dnsfcli.py policies bulk-add-blocklist \ --policy_ids ["285109","331207"] \ --domains ["evil.com","malware.net"]
```

bulk-remove-allowlist

Remove domains from the allowlist on multiple policies.

```
SHELL / POLICIES BULK-REMOVE-ALLOWLIST
```

```
python dnsfcli.py policies bulk-remove-allowlist \ --policy_ids ["285109"] \ --domains ["safe.com"]
```

bulk-remove-blocklist

Remove domains from the blocklist on multiple policies.

```
SHELL / POLICIES BULK-REMOVE-BLOCKLIST
```

```
python dnsfcli.py policies bulk-remove-blocklist \ --policy_ids ["285109"] \ --domains ["evil.com"]
```

create

Create a new resource.

```
SHELL / POLICIES CREATE
```

```
python dnsfcli.py policies create \ --name "Guest WiFi" \ --organization_id 802315 \ --allow_unknown_domains true \ --google_safesearch true \ --youtube_restricted true \ --youtube_restricted_level strict
```

delete

Permanently delete a resource by ID.

```
SHELL / POLICIES DELETE
```

```
python dnsfcli.py policies delete --id 12345
```

list

Retrieve a paginated list of resources.

```
SHELL / POLICIES LIST
```

```
python dnsfcli.py policies list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

```
SHELL / POLICIES LIST-ALL
```

```
python dnsfcli.py policies list-all
```

permissive-mode

Check whether permissive mode is enabled for a policy.

```
SHELL / POLICIES PERMISSIVE-MODE
```

```
python dnsfcli.py policies permissive-mode --id 12345
```

remove-allowed-application

Remove an application from the allowlist on a policy.

```
SHELL / POLICIES REMOVE-ALLOWED-APPLICATION
```



```
python dnsfcli.py policies remove-allowed-application --id 12345 --name TikTok
```

remove-blacklist-category

Unblock a category on a policy.

```
SHELL / POLICIES REMOVE-BLACKLIST-CATEGORY
```

```
python dnsfcli.py policies remove-blacklist-category --id 12345 --category_id 2
```

remove-blacklist-domain

Remove a domain from the blocklist on a policy.

```
SHELL / POLICIES REMOVE-BLACKLIST-DOMAIN
```

```
python dnsfcli.py policies remove-blacklist-domain \ --id 12345 \ --domain  
malware.example.com
```

remove-blocked-application

Remove an application from the blocklist on a policy.

```
SHELL / POLICIES REMOVE-BLOCKED-APPLICATION
```

```
python dnsfcli.py policies remove-blocked-application --id 12345 --name TikTok
```

remove-whitelist-domain

Remove a domain from the allowlist on a policy.

```
SHELL / POLICIES REMOVE-WHITELIST-DOMAIN
```

```
python dnsfcli.py policies remove-whitelist-domain \ --id 12345 \ --domain  
internal.corp.com
```

set-permissive-mode

Enable or disable permissive mode on a policy.

```
SHELL / POLICIES SET-PERMISSIVE-MODE
```

```
python dnsfcli.py policies set-permissive-mode --id 12345
```

show

Retrieve a single resource by ID.

```
SHELL / POLICIES SHOW
```

```
python dnsfcli.py policies show --id 12345
```

update

Update an existing resource by ID.

```
SHELL / POLICIES UPDATE
```

```
python dnsfcli.py policies update \ --id 12345 \ --name "Guest WiFi Updated" \ --  
organization_id 802315 \ --interstitial true
```

policy-ips

Policy IP associations.

list

Retrieve a paginated list of resources.

```
SHELL / POLICY-IPS LIST
```

```
python dnsfcli.py policy-ips list --page 1 --per_page 25
```

show

Retrieve a single resource by ID.

```
SHELL / POLICY-IPS SHOW
```

```
python dnsfcli.py policy-ips show --id 285109
```

psa-integrations

PSA integration links.

redirect-link

Get the PSA integration redirect link.

```
SHELL / PSA-INTEGRATIONS REDIRECT-LINK  
python dnsfcli.py psa-integrations redirect-link
```

scheduled-policies

Scheduled policy management.

create

Create a new resource.

```
SHELL / SCHEDULED-POLICIES CREATE  
python dnsfcli.py scheduled-policies create \ --name "School Hours" \ --organization_id  
802315 \ --policy_ids ["285109"] \ --timezone America/Denver
```

delete

Permanently delete a resource by ID.

```
SHELL / SCHEDULED-POLICIES DELETE  
python dnsfcli.py scheduled-policies delete --id 12345
```

list

Retrieve a paginated list of resources.

```
SHELL / SCHEDULED-POLICIES LIST
```

```
python dnsfcli.py scheduled-policies list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

```
SHELL / SCHEDULED-POLICIES LIST-ALL
```

```
python dnsfcli.py scheduled-policies list-all
```

show

Retrieve a single resource by ID.

```
SHELL / SCHEDULED-POLICIES SHOW
```

```
python dnsfcli.py scheduled-policies show --id 12345
```

update

Update an existing resource by ID.

```
SHELL / SCHEDULED-POLICIES UPDATE
```

```
python dnsfcli.py scheduled-policies update \ --id 12345 \ --name "School Hours Updated"  
\ --timezone America/Chicago
```

scheduled-reports

Scheduled report management.

create

Create a new resource.

```
SHELL / SCHEDULED-REPORTS CREATE
```

```
python dnsfcli.py scheduled-reports create \ --organization_id 802315 \ --frequency  
weekly \ --day_of_week 1 \ --include_threat_summary true \ --send_to_dashboard_users  
true
```

delete

Permanently delete a resource by ID.

```
SHELL / SCHEDULED-REPORTS DELETE
```

```
python dnsfcli.py scheduled-reports delete --id 12345
```

list

Retrieve a paginated list of resources.

```
SHELL / SCHEDULED-REPORTS LIST
```

```
python dnsfcli.py scheduled-reports list --page 1 --per_page 25
```

preview-create

Generate an immediate preview of a scheduled report.

```
SHELL / SCHEDULED-REPORTS PREVIEW-CREATE
```

```
python dnsfcli.py scheduled-reports preview-create \ --organization_id 802315 \ --  
include_threat_summary true
```

preview-show

Retrieve the result of a report preview job.

```
SHELL / SCHEDULED-REPORTS PREVIEW-SHOW
```

```
python dnsfcli.py scheduled-reports preview-show --id 12345
```

show

Retrieve a single resource by ID.

```
SHELL / SCHEDULED-REPORTS SHOW
```

```
python dnsfcli.py scheduled-reports show --id 12345
```

update

Update an existing resource by ID.

```
SHELL / SCHEDULED-REPORTS UPDATE
```

```
python dnsfcli.py scheduled-reports update --id 12345 --frequency monthly
```

traffic-reports

DNS traffic analytics and reporting (all GET).

qps

Queries per second.

```
SHELL / TRAFFIC-REPORTS QPS
```

```
python dnsfcli.py traffic-reports qps \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

qps-active-agents

QPS for active agents.

```
SHELL / TRAFFIC-REPORTS QPS-ACTIVE-AGENTS
```

```
python dnsfcli.py traffic-reports qps-active-agents \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

qps-active-collections

QPS for active collections.

```
SHELL / TRAFFIC-REPORTS QPS-ACTIVE-COLLECTIONS
```

```
python dnsfcli.py traffic-reports qps-active-collections \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

qps-active-organizations

QPS for active organizations.

```
SHELL / TRAFFIC-REPORTS QPS-ACTIVE-ORGANIZATIONS
```

```
python dnsfcli.py traffic-reports qps-active-organizations \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

qps-active-users

QPS for active users.

```
SHELL / TRAFFIC-REPORTS QPS-ACTIVE-USERS
```



```
python dnsfcli.py traffic-reports qps-active-users \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

query-logs

Query log export.

```
SHELL / TRAFFIC-REPORTS QUERY-LOGS
```

```
python dnsfcli.py traffic-reports query-logs \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

top-agents

Top agents by query volume.

```
SHELL / TRAFFIC-REPORTS TOP-AGENTS
```

```
python dnsfcli.py traffic-reports top-agents \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

top-application-categories

Top application categories.

```
SHELL / TRAFFIC-REPORTS TOP-APPLICATION-CATEGORIES
```

```
python dnsfcli.py traffic-reports top-application-categories \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

top-categories

Top DNS categories.

```
SHELL / TRAFFIC-REPORTS TOP-CATEGORIES
```

```
python dnsfcli.py traffic-reports top-categories \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

top-collections

Top collections by query volume.

```
SHELL / TRAFFIC-REPORTS TOP-COLLECTIONS
```

```
python dnsfcli.py traffic-reports top-collections \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

top-domains

Top queried domains.

```
SHELL / TRAFFIC-REPORTS TOP-DOMAINS
```

```
python dnsfcli.py traffic-reports top-domains \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

top-networks

Top networks by query volume.

```
SHELL / TRAFFIC-REPORTS TOP-NETWORKS
```

```
python dnsfcli.py traffic-reports top-networks \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

top-organizations

Top organizations by query volume.

```
SHELL / TRAFFIC-REPORTS TOP-ORGANIZATIONS
```

```
python dnsfcli.py traffic-reports top-organizations \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

top-organizations-requests

Top organizations by request count.

```
SHELL / TRAFFIC-REPORTS TOP-ORGANIZATIONS-REQUESTS
```

```
python dnsfcli.py traffic-reports top-organizations-requests \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

top-users

Top users by query volume.

```
SHELL / TRAFFIC-REPORTS TOP-USERS
```

```
python dnsfcli.py traffic-reports top-users \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-applications-agents-stats

Total application stats by agent.

```
SHELL / TRAFFIC-REPORTS TOTAL-APPLICATIONS-AGENTS-STATS
```

```
python dnsfcli.py traffic-reports total-applications-agents-stats \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-applications-collections-stats

Total application stats by collection.

```
SHELL / TRAFFIC-REPORTS TOTAL-APPLICATIONS-COLLECTIONS-STATS
```

```
python dnsfcli.py traffic-reports total-applications-collections-stats \ --start_date  
2025-01-01 \ --end_date 2025-01-31
```

total-applications-networks-stats

Total application stats by network.

```
SHELL / TRAFFIC-REPORTS TOTAL-APPLICATIONS-NETWORKS-STATS  
  
python dnsfcli.py traffic-reports total-applications-networks-stats \ --start_date  
2025-01-01 \ --end_date 2025-01-31
```

total-applications-organizations-stats

Total application stats by organization.

```
SHELL / TRAFFIC-REPORTS TOTAL-APPLICATIONS-ORGANIZATIONS-STATS  
  
python dnsfcli.py traffic-reports total-applications-organizations-stats \ --start_date  
2025-01-01 \ --end_date 2025-01-31
```

total-applications-stats

Total application stats.

```
SHELL / TRAFFIC-REPORTS TOTAL-APPLICATIONS-STATS  
  
python dnsfcli.py traffic-reports total-applications-stats \ --start_date 2025-01-01 \ --  
end_date 2025-01-31
```

total-applications-users-stats

Total application stats by user.

```
SHELL / TRAFFIC-REPORTS TOTAL-APPLICATIONS-USERS-STATS
```

```
python dnsfcli.py traffic-reports total-applications-users-stats \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-categories

Total queries by category.

```
SHELL / TRAFFIC-REPORTS TOTAL-CATEGORIES
```

```
python dnsfcli.py traffic-reports total-categories \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-categories-agents

Total category stats by agent.

```
SHELL / TRAFFIC-REPORTS TOTAL-CATEGORIES-AGENTS
```

```
python dnsfcli.py traffic-reports total-categories-agents \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-categories-collections

Total category stats by collection.

```
SHELL / TRAFFIC-REPORTS TOTAL-CATEGORIES-COLLECTIONS
```

```
python dnsfcli.py traffic-reports total-categories-collections \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-categories-organizations

Total category stats by organization.

```
SHELL / TRAFFIC-REPORTS TOTAL-CATEGORIES-ORGANIZATIONS
```

```
python dnsfcli.py traffic-reports total-categories-organizations \ --start_date 2025-01-01 \
--end_date 2025-01-31
```

total-categories-users

Total category stats by user.

```
SHELL / TRAFFIC-REPORTS TOTAL-CATEGORIES-USERS
```

```
python dnsfcli.py traffic-reports total-categories-users \ --start_date 2025-01-01 \ --
end_date 2025-01-31
```

total-category-stats

Total category stats.

```
SHELL / TRAFFIC-REPORTS TOTAL-CATEGORY-STATS
```

```
python dnsfcli.py traffic-reports total-category-stats \ --start_date 2025-01-01 \ --
end_date 2025-01-31
```

total-client-stats

Total client (agent) stats.

```
SHELL / TRAFFIC-REPORTS TOTAL-CLIENT-STATS
```

```
python dnsfcli.py traffic-reports total-client-stats \ --start_date 2025-01-01 \ --end_date
2025-01-31
```

total-collections

Total queries by collection.

```
SHELL / TRAFFIC-REPORTS TOTAL-COLLECTIONS
```

```
python dnsfcli.py traffic-reports total-collections \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-collections-agents

Total collection stats by agent.

```
SHELL / TRAFFIC-REPORTS TOTAL-COLLECTIONS-AGENTS
```

```
python dnsfcli.py traffic-reports total-collections-agents \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-collections-organizations

Total collection stats by organization.

```
SHELL / TRAFFIC-REPORTS TOTAL-COLLECTIONS-ORGANIZATIONS
```

```
python dnsfcli.py traffic-reports total-collections-organizations \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-collections-users

Total collection stats by user.

```
SHELL / TRAFFIC-REPORTS TOTAL-COLLECTIONS-USERS
```

```
python dnsfcli.py traffic-reports total-collections-users \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-deployments

Total deployments.

```
SHELL / TRAFFIC-REPORTS TOTAL-DEPLOYMENTS
```

```
python dnsfcli.py traffic-reports total-deployments \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-domain-requests

Total requests per domain.

```
SHELL / TRAFFIC-REPORTS TOTAL-DOMAIN-REQUESTS
```

```
python dnsfcli.py traffic-reports total-domain-requests \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-domain-stats

Total domain stats.

```
SHELL / TRAFFIC-REPORTS TOTAL-DOMAIN-STATS
```

```
python dnsfcli.py traffic-reports total-domain-stats \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-domains

Total unique domains queried.

```
SHELL / TRAFFIC-REPORTS TOTAL-DOMAINS
```

```
python dnsfcli.py traffic-reports total-domains \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-domains-collections

Total domains by collection.

```
SHELL / TRAFFIC-REPORTS TOTAL-DOMAINS-COLLECTIONS
```



```
python dnsfcli.py traffic-reports total-domains-collections \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-domains-organizations

Total domains by organization.

```
SHELL / TRAFFIC-REPORTS TOTAL-DOMAINS-ORGANIZATIONS
```

```
python dnsfcli.py traffic-reports total-domains-organizations \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-domains-users

Total domains by user.

```
SHELL / TRAFFIC-REPORTS TOTAL-DOMAINS-USERS
```

```
python dnsfcli.py traffic-reports total-domains-users \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-organizations-requests

Total requests by organization.

```
SHELL / TRAFFIC-REPORTS TOTAL-ORGANIZATIONS-REQUESTS
```

```
python dnsfcli.py traffic-reports total-organizations-requests \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-organizations-stats

Total stats by organization.

```
SHELL / TRAFFIC-REPORTS TOTAL-ORGANIZATIONS-STATS
```

```
python dnsfcli.py traffic-reports total-organizations-stats \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-requests

Total DNS requests.

```
SHELL / TRAFFIC-REPORTS TOTAL-REQUESTS
```

```
python dnsfcli.py traffic-reports total-requests \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-requests-agents

Total requests by agent.

```
SHELL / TRAFFIC-REPORTS TOTAL-REQUESTS-AGENTS
```

```
python dnsfcli.py traffic-reports total-requests-agents \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-requests-collections

Total requests by collection.

```
SHELL / TRAFFIC-REPORTS TOTAL-REQUESTS-COLLECTIONS
```

```
python dnsfcli.py traffic-reports total-requests-collections \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-requests-geo

Total requests by geography.

```
SHELL / TRAFFIC-REPORTS TOTAL-REQUESTS-GEO
```

```
python dnsfcli.py traffic-reports total-requests-geo \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-requests-organizations

Total requests by organization.

```
SHELL / TRAFFIC-REPORTS TOTAL-REQUESTS-ORGANIZATIONS
```

```
python dnsfcli.py traffic-reports total-requests-organizations \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-requests-users

Total requests by user.

```
SHELL / TRAFFIC-REPORTS TOTAL-REQUESTS-USERS
```

```
python dnsfcli.py traffic-reports total-requests-users \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-roaming-clients

Total roaming client stats.

```
SHELL / TRAFFIC-REPORTS TOTAL-ROAMING-CLIENTS
```

```
python dnsfcli.py traffic-reports total-roaming-clients \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-threats

Total threats blocked.

```
SHELL / TRAFFIC-REPORTS TOTAL-THREATS
```

```
python dnsfcli.py traffic-reports total-threats \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-threats-agents

Total threats by agent.

```
SHELL / TRAFFIC-REPORTS TOTAL-THREATS-AGENTS
```

```
python dnsfcli.py traffic-reports total-threats-agents \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-threats-collections

Total threats by collection.

```
SHELL / TRAFFIC-REPORTS TOTAL-THREATS-COLLECTIONS
```

```
python dnsfcli.py traffic-reports total-threats-collections \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-threats-organizations

Total threats by organization.

```
SHELL / TRAFFIC-REPORTS TOTAL-THREATS-ORGANIZATIONS
```

```
python dnsfcli.py traffic-reports total-threats-organizations \ --start_date 2025-01-01 \ --end_date 2025-01-31
```

total-threats-users

Total threats by user.

```
SHELL / TRAFFIC-REPORTS TOTAL-THREATS-USERS
```

```
python dnsfcli.py traffic-reports total-threats-users \ --start_date 2025-01-01 \ --end_date  
2025-01-31
```

user-agent-bulk-deletes

Bulk agent deletion jobs.

counts

Return counts of resources matching optional filters.

```
SHELL / USER-AGENT-BULK-DELETES COUNTS  
python dnsfcli.py user-agent-bulk-deletes counts
```

create

Create a new resource.

```
SHELL / USER-AGENT-BULK-DELETES CREATE  
python dnsfcli.py user-agent-bulk-deletes create \ --ids ["9b2f6c04-5a1e-4d37-8c2a-  
f0e1d2c3b4a5"]
```

show

Retrieve a single resource by ID.

```
SHELL / USER-AGENT-BULK-DELETES SHOW  
python dnsfcli.py user-agent-bulk-deletes show \ --id 9b2f6c04-5a1e-4d37-8c2a-  
f0e1d2c3b4a5
```

user-agent-bulk-updates

Bulk agent update jobs.

counts

Return counts of resources matching optional filters.

```
SHELL / USER-AGENT-BULK-UPDATES COUNTS
```

```
python dnsfcli.py user-agent-bulk-updates counts
```

create

Create a new resource.

```
SHELL / USER-AGENT-BULK-UPDATES CREATE
```

```
python dnsfcli.py user-agent-bulk-updates create \ --ids ["9b2f6c04-5a1e-4d37-8c2a-f0e1d2c3b4a5"] \ --policy_id 285109
```

has-mixed

Check whether the selected agents have mixed field values.

```
SHELL / USER-AGENT-BULK-UPDATES HAS-MIXED
```

```
python dnsfcli.py user-agent-bulk-updates has-mixed \ --ids ["9b2f6c04-5a1e-4d37-8c2a-f0e1d2c3b4a5"]
```

show

Retrieve a single resource by ID.

```
SHELL / USER-AGENT-BULK-UPDATES SHOW
```

```
python dnsfcli.py user-agent-bulk-updates show \ --id 9b2f6c04-5a1e-4d37-8c2a-f0e1d2c3b4a5
```

user-agent-cleanups

Agent cleanup jobs.

create

Create a new resource.

```
SHELL / USER-AGENT-CLEANUPS CREATE
```

```
python dnsfcli.py user-agent-cleanups create \ --organization_ids ["802315"] \ --  
inactive_for 30
```

show

Retrieve a single resource by ID.

```
SHELL / USER-AGENT-CLEANUPS SHOW
```

```
python dnsfcli.py user-agent-cleanups show \ --id 9b2f6c04-5a1e-4d37-8c2a-  
f0e1d2c3b4a5
```

update

Update an existing resource by ID.

```
SHELL / USER-AGENT-CLEANUPS UPDATE
```

```
python dnsfcli.py user-agent-cleanups update \ --id 9b2f6c04-5a1e-4d37-8c2a-  
f0e1d2c3b4a5 \ --start true \ --inactive_for 30
```

user-agent-csv-exports

Agent CSV export jobs.

create

Create a new resource.

```
SHELL / USER-AGENT-CSV-EXPORTS CREATE
```

```
python dnsfcli.py user-agent-csv-exports create --organization_ids ["802315"]
```

show

Retrieve a single resource by ID.

```
SHELL / USER-AGENT-CSV-EXPORTS SHOW
```

```
python dnsfcli.py user-agent-csv-exports show \ --id 9b2f6c04-5a1e-4d37-8c2a-  
f0e1d2c3b4a5
```

user-agent-releases

Agent release information.

list

Retrieve a paginated list of resources.

```
SHELL / USER-AGENT-RELEASES LIST
```

```
python dnsfcli.py user-agent-releases list --page 1 --per_page 25
```

relay

Retrieve the relay channel's latest agent release.

```
SHELL / USER-AGENT-RELEASES RELAY
```

```
python dnsfcli.py user-agent-releases relay
```

user-agents

Roaming agent (client) management.

counts

Return counts of resources matching optional filters.

```
SHELL / USER-AGENTS COUNTS
```

```
python dnsfcli.py user-agents counts
```

CSV

Export all roaming agents to CSV format.

```
SHELL / USER-AGENTS CSV
```

```
python dnsfcli.py user-agents csv
```

delete

Permanently delete a resource by ID.

```
SHELL / USER-AGENTS DELETE
```

```
python dnsfcli.py user-agents delete --id 9b2f6c04-5a1e-4d37-8c2a-f0e1d2c3b4a5
```

dequeue-uninstall

Dequeue a pending uninstall request for an agent.

```
SHELL / USER-AGENTS DEQUEUE-UNINSTALL
```

```
python dnsfcli.py user-agents dequeue-uninstall
```

list

Retrieve a paginated list of resources.

```
SHELL / USER-AGENTS LIST
```

```
python dnsfcli.py user-agents list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

```
SHELL / USER-AGENTS LIST-ALL
```

```
python dnsfcli.py user-agents list-all
```

show

Retrieve a single resource by ID.

```
SHELL / USER-AGENTS SHOW
```

```
python dnsfcli.py user-agents show --id 9b2f6c04-5a1e-4d37-8c2a-f0e1d2c3b4a5
```

tags

List all tags assigned to roaming agents.

```
SHELL / USER-AGENTS TAGS
```

```
python dnsfcli.py user-agents tags
```

uninstall-pin

Retrieve the uninstall PIN for roaming agents.

```
SHELL / USER-AGENTS UNINSTALL-PIN
```

```
python dnsfcli.py user-agents uninstall-pin
```

update

Update an existing resource by ID.

```
SHELL / USER-AGENTS UPDATE
```

```
python dnsfcli.py user-agents update \ --id 9b2f6c04-5a1e-4d37-8c2a-f0e1d2c3b4a5 \ --friendly_name Finance-Laptop \ --policy_id 285109 \ --tags ["managed","finance"]
```

users

User management.

change-password

Change the current user's password.

```
SHELL / USERS CHANGE-PASSWORD
```

```
python dnsfcli.py users change-password --new_password NewSecurePass123!
```

list

Retrieve a paginated list of resources.

```
SHELL / USERS LIST
```

```
python dnsfcli.py users list --page 1 --per_page 25
```

list-all

Retrieve all resources without pagination limits.

```
SHELL / USERS LIST-ALL
```

```
python dnsfcli.py users list-all
```

show

Retrieve a single resource by ID.

```
SHELL / USERS SHOW
```

```
python dnsfcli.py users show --id 12345
```

v2-agent-local-users

v2 Agent local user endpoints.

counts

Return counts of resources matching optional filters.

```
SHELL / V2-AGENT-LOCAL-USERS COUNTS
```

```
python dnsfcli.py v2-agent-local-users counts
```

csv-export

Create an async CSV export job.

```
SHELL / V2-AGENT-LOCAL-USERS CSV-EXPORT
```

```
python dnsfcli.py v2-agent-local-users csv-export --organization_ids ["802315"]
```

csv-export-show

Check the status of a CSV export job.

```
SHELL / V2-AGENT-LOCAL-USERS CSV-EXPORT-SHOW
```

```
python dnsfcli.py v2-agent-local-users csv-export-show \ --id 9b2f6c04-5a1e-4d37-8c2a-f0e1d2c3b4a5
```

v2-current-user

v2 Current user endpoints.

suppress-license-warning

Suppress the license warning for the current user.

```
SHELL / V2-CURRENT-USER SUPPRESS-LICENSE-WARNING  
python dnsfcli.py v2-current-user suppress-license-warning
```

ui-settings

Retrieve the current user's UI settings.

```
SHELL / V2-CURRENT-USER UI-SETTINGS  
python dnsfcli.py v2-current-user ui-settings
```

ui-settings-update

Update the current user's UI settings.

```
SHELL / V2-CURRENT-USER UI-SETTINGS-UPDATE  
python dnsfcli.py v2-current-user ui-settings-update --theme_mode dark
```

v2-dictionary

v2 Dictionary / reference data.

cyber-sight-activity-types

List available Cyber Sight activity types.

```
SHELL / V2-DICTIONARY CYBER-SIGHT-ACTIVITY-TYPES
```

```
python dnsfcli.py v2-dictionary cyber-sight-activity-types
```

vpn-settings-state-types

List available VPN settings state types.

```
SHELL / V2-DICTIONARY VPN-SETTINGS-STATE-TYPES
```

```
python dnsfcli.py v2-dictionary vpn-settings-state-types
```


v2-networks

v2 Network export endpoints.

csv-export

Create an async CSV export job.

```
SHELL / V2-NETWORKS CSV-EXPORT
```

```
python dnsfcli.py v2-networks csv-export --organization_ids ["802315"]
```

csv-export-show

Check the status of a CSV export job.

```
SHELL / V2-NETWORKS CSV-EXPORT-SHOW
```

```
python dnsfcli.py v2-networks csv-export-show --id 736401
```

v2-user-agents

v2 Agent management.

update-settings

Update settings for a specific roaming agent.

```
SHELL / V2-USER-AGENTS UPDATE-SETTINGS
```

```
python dnsfcli.py v2-user-agents update-settings \ --id 9b2f6c04-5a1e-4d37-8c2a-f0e1d2c3b4a5
```

From the team at

DNSFilter