Aim:

Create an interface for stack with push and pop operations. Implement the stack in two ways fixed-size stack and Dynamic stack (stack size is increased when the stack is full).

Note: Please don't change the package name.

Source Code:

q29794/StaticAndDynamicStack.java

```
package q29794;
interface IntStack{
   void push(int item);
   int pop();
}
class FixedStack implements IntStack{
   private int stck[];
   private int tos;
   FixedStack(int size){
      stck = new int[size];
      tos = -1;
   }
   public void push(int item){
      if(tos == stck.length-1)
       System.out.println("Stack is full and increased");
       else
       stck[++tos]=item;
   }
   public int pop(){
      if(tos<0){
         System.out.println("Stack underflow");
         return 0;
      }
      else
      return stck[tos--];
   }
}
class StaticAndDynamicStack{
   public static void main(String args[]){
      FixedStack mystack=new FixedStack(0);
      FixedStack mystack1=new FixedStack(5);
      FixedStack mystack2=new FixedStack(10);
      for(int i=0;i<1;i++)
         mystack.push(i);
      for(int i=0;i<5;i++)
         mystack1.push(i);
      for(int i=0;i<10;i++)
         mystack2.push(i);
      System.out.println("Stack in mystack1:");
      for(int i=0;i<5;i++)
         System.out.println(mystack1.pop());
```

```
      System.out.print("Stack in mystack2 :\n");
      for(int i=0;i<4;i++)
         System.out.println(mystack2.pop());
      mystack2.pop();
      for(int i=1;i<6;i++)
         System.out.println(mystack2.pop());
      System.out.println(mystack.pop());
   }
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
Stack is full and increased
Stack in mystack1:
4
3
2
1
0
Stack in mystack2 :
9
8
7
6
4
3
2
1
0
Stack underflow
0

ID: 224G1A0559