
GeoNode Developers Workshop Documentation

Release 2.0

GeoNode

February 06, 2013

CONTENTS

| | | |
|----------|---|-----------|
| 1 | Introduction to GeoNode development | 3 |
| 1.1 | GeoNode Components | 3 |
| 1.2 | Standards | 4 |
| 1.3 | GeoNode Architecture | 6 |
| 1.4 | Development References | 7 |
| 2 | Development Prerequisites and Core Modules | 9 |
| 2.1 | GeoNode's Development Prerequisites | 9 |
| 2.2 | GeoNode's Core Modules | 12 |
| 3 | Customized GeoNode Projects | 17 |
| 3.1 | Introduction to GeoNode Projects | 17 |
| 3.2 | Setting up your GeoNode Project | 18 |
| 3.3 | Theming your GeoNode Project | 22 |
| 3.4 | Adding Additional Modules to your GeoNode Project | 22 |
| 3.5 | Integrating your Project with other Systems | 22 |
| 4 | Setting up a GeoNode development environment | 23 |
| 4.1 | GeoNode Development Tools | 23 |
| 4.2 | Git Repository Setup | 23 |
| 4.3 | Installing GeoNode's Python Package | 23 |
| 4.4 | Pavement.py and Paver | 23 |
| 4.5 | Manually Deploying your Development Environment | 23 |
| 5 | Loading Data into a GeoNode | 25 |
| 5.1 | GeoServer Data Configuration | 25 |
| 5.2 | Using ogr2ogr to load data into GeoNode | 25 |
| 5.3 | Loading OSM Data into GeoNode | 25 |
| 6 | GeoNode APIs | 27 |
| 6.1 | OGC Services | 27 |
| 6.2 | GeoServer REST API | 27 |
| 6.3 | GeoServers Import and Print APIs | 27 |
| 6.4 | GeoNode's Ad-Hoc API | 27 |
| 7 | GeoNode debugging techniques | 29 |
| 7.1 | Debugging GeoNode's Python Components | 29 |
| 7.2 | Debugging GeoNode in the Browser | 29 |
| 7.3 | Debugging GeoServer | 29 |

| | | |
|----------|---|-----------|
| 8 | GeoNode's development process | 31 |
| 8.1 | GeoNode's Issue Tracking System | 31 |
| 8.2 | Testing in GeoNode | 31 |
| 8.3 | GeoNode's Patch Review Process | 31 |
| 8.4 | GeoNode Improvement Proposals | 31 |
| 8.5 | GeoNode's Roadmap Process | 31 |
| 8.6 | Development Resources | 31 |

Welcome to the GeoNode Developers Workshop! This workshop will teach how to develop with and for the [GeoNode](#) software application.

Introduction to GeoNode development Learn about GeoNode's core components, its Architecture, the tools it is developed with and the standards it supports.

Development Prerequisites and Core Modules Learn about the pre-requisites you will need in order to develop with GeoNode. Take a look at its core modules and how they work together to provide a complete web mapping tool.

Customized GeoNode Projects Learn how existing projects leverage GeoNode and create your own GeoNode based project.

Setting up a GeoNode development environment Learn how to set up a GeoNode development environment so you can contribute to GeoNode's core.

Loading Data into a GeoNode Learn how to load data into a GeoNode with GeoServer, on the command line or programatically with scripts.

GeoNode APIs Learn about the APIs GeoNode leverages and provides.

GeoNode debugging techniques Learn how to debug GeoNode instances and projects.

GeoNode's development process Learn about GeoNode's development process and how to work with the GeoNode community.

INTRODUCTION TO GEONODE DEVELOPMENT

This module will introduce you to the components that GeoNode is built with, the standards that it supports and the services it provides based on those standards, and an overview its architecture.

GeoNode is a web based GIS tool, and as such, in order to do development on GeoNode itself or to integrate it into your own application, you should be familiar with basic web development concepts as well as with general GIS concepts.

A set of reference links on these topics is included at the end of this module.

1.1 GeoNode Components

GeoNode's architecture is based on a set of core tools and libraries that provide the building blocks on which the application is built. Having a basic understanding of each of these components is critical to your success as developer working with GeoNode.

Lets look at each of these components and discuss how they are used within the GeoNode application.

1.1.1 Django

GeoNode is based on [Django](#) which is a high level Python web development framework that encourages rapid development and clean pragmatic design. Django is based on the Model View Controller (MVC) architecture pattern, and as such, GeoNode models layers, maps and other modules with Django's [Model](#) module and and these models are used via Django's [ORM](#) in views which contain the business logic of the GeoNode application and are used to drive HTML templates to display the web pages within the application.

1.1.2 GeoServer

[GeoServer](#) is a an open source software server written in Java that provides OGC compliant services which publish data from many spatial data sources. GeoServer is used as the core GIS component inside GeoNode and is used to render the layers in a GeoNode instance, create map tiles from the layers, provide for downloading those layers in various formats and to allow for transactional editing of those layers.

1.1.3 GeoExplorer

[GeoExplorer](#) is a web application, based on the [GeoExt](#) framework, for composing and publishing web maps with OGC and other web based GIS Services. GeoExplorer is used inside GeoNode to provide many of the GIS and

cartography functions that are a core part of the application.

1.1.4 PostgreSQL and PostGIS

PostgreSQL and **PostGIS** are the database components that store and manage spatial data and information for GeoNode and the django modules that it is composed of, pycsw and GeoServer. All of these tables and data are stored within a geonode database in PostgreSQL. GeoServer uses PostGIS to store and manage spatial vector data for each layer which are stored as a separate table in the database.

1.1.5 pycsw

pycsw is an OGC CSW server implementation written in Python. GeoNode uses pycsw to provide an OGC compliant standards-based CSW metadata and catalogue component of spatial data infrastructures, supporting popular geospatial metadata standards such as Dublin Core, ISO 19115, FGDC and DIF.

1.1.6 Geospatial Python Libraries

GeoNode leverages several geospatial python libraries including **gsconfig** and **OWSLib**. **gsconfig** is used to communicate with GeoServer's REST Configuration API to configure GeoNode layers in GeoServer. **OWSLib** is used to communicate with GeoServer's OGC services and can be used to communicate with other OGC services.

1.1.7 Django Pluggables

GeoNode uses a set of Django plugins which are usually referred to as pluggables. Each of these pluggables provides a particular set of functionality inside the application from things like Registration and Profiles to interactivity with external sites. Being based on Django enables GeoNode to take advantage of the large ecosystem of these pluggables out there, and while a specific set is included in GeoNode itself, many more are available for use in applications based on GeoNode.

1.1.8 jQuery

jQuery is a feature-rich javascript library that is used within GeoNode to provide an interactive and responsive user interface as part of the application. GeoNode uses several jQuery plugins to provide specific pieces of functionality, and the GeoNode development team often adds new features to the interface by adding additional plugins.

1.1.9 Bootstrap

Bootstrap is a front-end framework for laying out and styling the pages that make up the GeoNode application. It is designed to ensure that the pages render and look and behave the same across all browsers. GeoNode customizes bootstraps default style and its relatively easy for developers to customize their own GeoNode based site using existing Bootstrap themes or by customizing the styles directly.

1.2 Standards

GeoNode is based on a set of Open Geospatial Consortium (OGC) standards. These standards enable GeoNode installations to be interoperable with a wide variety of tools that support these OGC standards and enable federation

with other OGC compliant services and infrastructure. Reference links about these standards are also included at the end of this module.

GeoNode is also based on Web Standards ...

1.2.1 Open Geospatial Consortium (OGC) Standards

Web Map Service (WMS)

The Web Map Service (WMS) specification defines an interface for requesting rendered map images across the web. It is used within GeoNode to display maps in the pages of the site and in the GeoExplorer application to display rendered layers based on default or custom styles.

Web Feature Service (WFS)

The Web Feature Service (WFS) specification defines an interface for reading and writing geographic features across the web. It is used within GeoNode to enable downloading of vector layers in various formats and within GeoExplorer to enable editing of Vector Layers that are stored in a GeoNode.

Web Coverage Service (WCS)

The Web Coverage Service (WCS) specification defines an interface for reading and writing geospatial raster data as “coverages” across the web. It is used within GeoNode to enable downloading of raster layers in various formats.

Catalogue Service for Web (CSW)

The Catalogue Service for Web (CSW) specification defines an interface for exposing a catalogue of geospatial meta-data across the web. It is used within GeoNode to enable any application to search GeoNode’s catalogue or to provide federated search that includes a set of GeoNode layers within another application.

Tile Mapping Service (TMS/WMTS)

The Tile Mapping Service (TMS) specification defines an interface for retrieving rendered map tiles over the web. It is used within GeoNode to enable serving of a cache of rendered layers to be included in GeoNode’s web pages or within the GeoExplorer mapping application. Its purpose is to improve performance on the client vs asking the WMS for rendered images directly.

1.2.2 Web Standards

HTML

CSS

REST

1.3 GeoNode Architecture

1.3.1 Django Architecture

- MVC
- WSGI

1.3.2 GeoNode and GeoServer

- Configuration via the REST API
- Authentication and Authorization

1.3.3 GeoNode and PostgreSQL/PostGIS

- Configuration and Application Information
- Vector Data Layer Storage

1.3.4 GeoNode and pycsw

GeoNode is built with pycsw embedded as the default CSW server component.

Publishing

Since pycsw is embedded in GeoNode, layers published within GeoNode are automatically published to pycsw and discoverable via CSW. No additional configuration or actions are required to publish layers, maps or documents to pycsw.

Discovery

GeoNode's CSW endpoint is deployed available at `http://localhost:8000/catalogue/csw` and is available for clients to use for standards-based discovery. See <http://pycsw.org/docs/tools.html> for a list of CSW clients and tools.

1.3.5 Javascript in GeoNode

- GeoExplorer
- jQuery Functionality

1.4 Development References

1.4.1 Basic Web based GIS Concepts and Background

- OGC Services
 - <http://www.opengeospatial.org/>
 - http://en.wikipedia.org/wiki/Open_Geospatial_Consortium
- Web Application Architecture
 - http://en.wikipedia.org/wiki/Web_application
 - <http://www.w3.org/2001/tag/2010/05/WebApps.html>
 - <http://www.amazon.com/Web-Application-Architecture-Principles-Protocols/dp/047051860X>
- AJAX and REST
 - [http://en.wikipedia.org/wiki/Ajax_\(programming\)](http://en.wikipedia.org/wiki/Ajax_(programming))
 - http://en.wikipedia.org/wiki/Representational_state_transfer
- OpenGeo Suite
 - <http://workshops.opengeo.org/suiteintro/>
 - <http://suite.opengeo.org/opengeo-docs/>
- GeoServer Administration
 - <http://suite.opengeo.org/opengeo-docs/geoserver/>
 - <https://docs.google.com/a/opengeo.org/presentation/d/15fvUDYg0TO6WGFQIMLM2J1qiTVBYpfjCp0aQBDT0GrM/edit#>
 - <http://suite.opengeo.org/docs/sysadmin/index.html#sysadmin>
- PostgreSQL and PostGIS Administration - <http://workshops.opengeo.org/postgis-intro/> - <http://workshops.opengeo.org/postgis-spatialdbtips/>

1.4.2 Core development tools and libraries

- python
 - <http://docs.python.org/2/tutorial/>
 - <http://www.learnpython.org/>
 - <http://learnpythonthehardway.org/book/>
- django
 - <https://docs.djangoproject.com/en/dev/intro/tutorial01/>
 - <https://code.djangoproject.com/wiki/Tutorials>
- javascript
 - <http://www.crockford.com/javascript/inheritance.html>
 - <http://geoext.org/tutorials/quickstart.html>
- jquery
 - <http://www.w3schools.com/jquery/default.asp>

- http://docs.jquery.com/Tutorials:Getting_Started_with_jQuery
 - <http://www.jquery-tutorial.net/>
- bootstrap
 - <http://twitter.github.com/bootstrap/>
 - <http://www.w3resource.com/twitter-bootstrap/tutorial.php>
- geotools/geoscript/geoserver
 - <http://docs.geotools.org/stable/tutorials/feature/csv2shp.html>
 - <http://geoscript.org/tutorials/index.html>
 - <http://docs.geotools.org/stable/tutorials/>
 - <https://github.com/dwins/gsconfig.py/blob/master/README.rst>
- geopython
 - <http://pycsw.org/docs/documentation.html>
 - <http://geopython.github.com/OWSLib/>
 - <https://github.com/toblerity/shapely>
 - <https://github.com/sgillies/Fiona>
 - <http://pypi.python.org/pypi/pyproj>
- gdal/ogr
 - http://www.gdal.org/gdal_utilities.html
 - http://www.gdal.org/ogr_utilities.html

DEVELOPMENT PREREQUISITES AND CORE MODULES

This module will introduce you to the

2.1 GeoNode's Development Prerequisites

2.1.1 Basic Shell Tools

ssh and sudo

ssh and sudo are very basic terminal skills which you will need to deploy, maintain and develop with GeoNode. If you are not already familiar with their usage, you should review the basic descriptions below and follow the external links to learn more about how to use them effectively as part of your development workflow.

ssh is the network protocol used to connect to a remote server where you run your GeoNode instance whether on your own network or on the cloud. You will need to know how to use the ssh command from the terminal on your unix machine or how to use a ssh client like putty or winscp on windows. You may need to use pki certificates to connect to your remote server, and should be familiar with the steps and options necessary to connect this way. More information about ssh can be found in the links below.

- <http://winscp.net/eng/docs/ssh>

sudo is the command used to execute a terminal command as the superuser when you are logged in with a normal user. You will use sudo in order to start, stop and restart key services on your GeoNode instance. If you are not able to grant yourself these privileges on the machine you are using for your GeoNode instance, you may need to consult with your network administrator to arrange for your user to be granted sudo permissions. More information about sudo can be found in the links below.

- <http://en.wikipedia.org/wiki/Sudo>

bash

Bash is the most common unix shell which will usually be the default on servers where you will be deploying your GeoNode instance. You should be familiar with the most common bash commands in order to be able to deploy, maintain and modify a geonode instance. More information about Bash and common bash commands can be found in the links below.

- [http://en.wikipedia.org/wiki/Bash_\(Unix_shell\)](http://en.wikipedia.org/wiki/Bash_(Unix_shell))

apt

apt is the packaging tool that is used to install GeoNode on ubuntu and other debian based systems. You will need to be familiar with adding Personal Package Archives to your list of install sources, and will need to be familiar with basic apt commands. More information about apt can be found in the links below.

- http://en.wikipedia.org/wiki/Advanced_Packaging_Tool

2.1.2 Python Development Tools

The GeoNode development process relies on several widely used python development tools in order to make things easier for developers and other users of the systems that GeoNode developers work on or where GeoNodes are deployed. They are considered best practices for modern python development, and you should become familiar with these basic tools and be comfortable using them on your own projects and systems.

virtualenv

virtualenv is a tool used to create isolated python development environments such that the the versions of project dependencies are sandboxed from the system-wide python packages. This eliminates the commonly encountered problem of different projects on the same system using different versions of the same library. You should be familiar with how to create and activate virtual environments for the projects you work on. More information about virtualenv can be found in the links below.

- <http://pypi.python.org/pypi/virtualenv>
- <http://www.virtualenv.org/en/latest/>

virtualenvwrapper is a wrapper around the virtualenv package that makes it easier to create and switch between virtual environments as you do development. Using it will make your life much easier, so its recommended that you install and configure it and use its commands as part of your virtualenv workflow. More info about virtualenvwrapper can be found in the links below.

- <http://www.doughellmann.com/projects/virtualenvwrapper/>

pip

pip is a tool for installing and managing python packages. Specifically it is used to install and upgrade packages found in the Python Package Index. GeoNode uses pip to install itself, and to manage all of the python dependencies that are needed as part of a GeoNode instance. As you learn to add new modules to your geonode, you will need to become familiar with the use of pip and about basic python packaging usage. More information about pip can be found in the links below.

- <http://www.pip-installer.org/en/latest/>
- <http://pypi.python.org/pypi/pip>
- [http://en.wikipedia.org/wiki/Pip_\(Python\)](http://en.wikipedia.org/wiki/Pip_(Python))

miscellaneous

ipython is a set of tools to make your python development and debugging experience easier. The primary tool you want to use is an interactive shell that adds introspection, integrated help and command completion and more. While not strictly required to do GeoNode development, learning how to use ipython will make your development more productive and pleasant. More information about ipython can be found in the links below.

- <http://ipython.org/>
- <http://pypi.python.org/pypi/ipython>
- <https://github.com/ipython/ipython>
- <http://en.wikipedia.org/wiki/IPython>

pdb is a standard python module that is used to interactively debug your python code. It supports setting conditional breakpoints so you can step through the code line by line and inspect your variables and perform arbitrary execution of statements. Learning how to effectively use *pdb* will make the process of debugging your application code significantly easier. More information about *pdb* can be found in the links below.

- <http://docs.python.org/2/library/pdb.html>

2.1.3 Django

GeoNode is built on top of the *Django web framework*, and as such, you will need to become generally familiar with Django itself in order to become a productive GeoNode developer. Django has excellent documentation, and you should familiarize yourself with Django by following the Django workshop and reading through its documentation as required.

Model Template View

Django is based on the Model Template View paradigm (more commonly called Model View Controller). Models are used to define objects that you use in your application and Django's ORM is used to map these models to a database. Views are used to implement the business logic of your application and provide objects and other context for the templates. Templates are used to render the context from views into a page for display to the user. You should become familiar with this common paradigm used in most modern web frameworks, and how it is specifically implemented and used in Django. The Django tutorial itself is a great place to start. More information about MTV in Django can be found in the links below.

- <http://en.wikipedia.org/wiki/Model%E2%80%93view%E2%80%93controller>
- <http://www.codinghorror.com/blog/2008/05/understanding-model-view-controller.html>
- <https://docs.djangoproject.com/en/1.4/>

HTTP Request Response

Django and all other web frameworks are based on the HTTP Request Response cycle. Requests come in to the server from remote clients which are primarily web browsers, but also can be api clients, and the server returns with a Response. You should be familiar with these very basic HTTP principles and become familiar with the way that Django implements them. More information about HTTP, Requests and Responses and Django's implementation in the links below.

- <http://devhub.fm/http-requestresponse-basics/>
- http://en.wikipedia.org/wiki/Hypertext_Transfer_Protocol
- <https://docs.djangoproject.com/en/dev/ref/request-response/>

Management Commands

Django projects have access to a set of management commands that are used to manage your project. Django itself provides a set of these commands, and django apps (including GeoNode) can provide their own. Management commands are used to do things like synchronize your models with your database, load data from fixtures or back up your

database with fixtures, start the development server, initiate the debugger and many other things. GeoNode provides management commands for synchronizing with a GeoServer or updating the layers already in your GeoNode. You should become familiar with the basic management commands that come with Django, and specifically with the commands that are part of GeoNode. The GeoNode specific commands are covered in section. More information about management commands can be found in the links below.

- <https://docs.djangoproject.com/en/dev/ref/django-admin/>

Django Admin Interface

Django provides a build-in management console that administrators and developers can use to look at the data in the database that is part of the installed applications. Administrators can use this console to perform many common administration tasks that are a necessary part of running a GeoNode instance, and as a developer, you will use this interface during your development process to inspect the database and the data stored in your models. More information about the django admin interface can be found in the links below.

- <https://docs.djangoproject.com/en/dev/ref/contrib/admin/>

Template Tags

Django templates make use of a set of tags to inject, filter and format content into a rendered HTML page. Django itself includes a set of built-in template tags and filters that you will use in your own templates, and GeoNode provides a geonode specific set of tags that are used in the GeoNode templates. You should become familiar with the built-in tag set and with GeoNode's specific tags as you work on developing your own templates or extending from GeoNode's. More information about Django template tags can be found in the links below.

- <https://docs.djangoproject.com/en/dev/ref/templates/builtins/>

2.2 GeoNode's Core Modules

GeoNode is made up of a set of core Django pluggable modules (known as apps in Django) that provide the functionality of the application. Together they make up the key components of a GeoNode site. While your own use case and implementation may not require that you work directly on these modules, it is important that you become familiar with their layout, structure and the functionality that they provide. You may need to import these apps into your own apps, and as such, becoming familiar with them is an important step in becoming a proficient GeoNode developer.

2.2.1 geonode.layers

geonode.layers is the most key GeoNode module. It is used to represent layers of data stored in a GeoNode's paired GeoServer. The layer model class inherits fields from the ResourceBase class which provides all of the fields necessary for the metadata catalogue, and adds fields that map the object to its corresponding layer in GeoServer. When your users upload a layer via the user interface, the layer is imported to GeoServer and a record is added to GeoNode's database to represent that GeoServer layer within GeoNode itself.

The Layer model class provides a set of helper methods that are used to perform operations on a Layer object, and also to return things such as the list of Download or Metadata links for that layer. Additional classes are used to model the layers Attributes, Styles, Contacts and Links. The Django signals framework is used to invoke specific functions to synchronize with GeoServer before and after the layer is saved.

The views in the layers app are used to perform functions such as uploading, replacing, removing or changing the points of contact for a layer, and views are also used to update layer styles, download layers in bulk or change a layers permissions.

The forms module in the layer app is used to drive the user interface forms necessary for performing the business logic that the views provide.

The Layers app also includes a set of templates that are paired with views and used to drive the user interface. A small set of layer template tags is also used to help drive the layer explore and search pages.

Some helper modules such as `geonode.layers.metadata` and `geonode.layers.ows` are used by the layer views to perform specific functions and help keep the main views module more concise and legible.

Additionally, the GeoNode specific management commands are a part of the `geonode.layers` app.

You should spend some time to review the layers app through GitHub's code browsing interface.

<https://github.com/GeoNode/geonode/tree/master/geonode/layers>

2.2.2 geonode.maps

The `geonode.maps` app is used to group together GeoNodes multi layer map functionality. The `Map` and `MapLayer` objects are used to model and implement maps created with the `GeoExplorer` application. The `Map` object also extends from the `ResourceBase` class which provides the ability to manage a full set of metadata fields for a `Map`.

The views in the maps app perform many of the same functions as the views in the layers app such as adding, changing, replacing or removing a map and also provide the endpoints for returning the map configuration from the database that is used to initialize the `GeoExplorer` app.

The maps app also includes a set of forms, customization of the Django admin, some utility functions and a set of templates and template tags.

You can familiarize yourself with the maps app on GitHub.

<https://github.com/GeoNode/geonode/tree/master/geonode/layers>

2.2.3 geonode.security

The `geonode.security` app is used to provide object level permissions within the GeoNode Django application. It is a custom Django authentication backend and is used to assign Generic, User and Group Permissions to Layers, Maps and other objects in the GeoNode system. Generic permissions are used to enable public anonymous or authenticated viewing and/or editing of your data layers and maps, and User and Group specific permissions are used to allow specific users or groups to access and edit your layers.

2.2.4 geonode.search

The `geonode.search` module provides the search API that is used to drive the GeoNode search pages. It is configured to index layers, maps, documents and profiles, but is extensible to allow you to use it to index your own model classes. This module is currently based on the Django ORM and as such has a limited set of search features, but the GeoNode development team is actively working on making it possible to use this module with more feature-rich search engines.

2.2.5 geonode.catalogue

The `geonode.catalogue` app provides a key set of metadata catalogue functions within GeoNode itself. GeoNode is configured to use an integrated version of the `pycsw` library to perform these functions, but can also be configured to use any OGC compliant CS-W implementation such as `GeoNetwork` or `Deegree`. The metadata app allows users to import and/or edit metadata for their layers, maps and documents, and it provides an OGC compliant search interface for use in federating with other systems.

2.2.6 geonode.geoserver

The `geonode.geoserver` module is used to interact with GeoServer from within GeoNode's python code. It relies heavily on the `gsconfig` library which addresses GeoServer's REST configuration API. Additionally, the `geonode.geoserver.uploader` module is used to interact with GeoServers Importer API for uploading and configuring layers.

2.2.7 geonode.people

The `geonode.people` module is used to model and store information about both GeoNode users and people outside of the system who are listed as Points of Contact for particular layers. It is the foundational module for GeoNode's social features. It provides a set of forms for users to edit and manage their own profiles as well as to view and interact with the profiles of other users.

2.2.8 geoexplorer

GeoNode's core GIS client functions are performed by GeoExplorer. The GeoExplorer app is in turn based on GeoExt, OpenLayers and ExtJS. It provides functionality for constructing maps, styling layers and connecting to remote services. GeoExplorer is the reference implementation of the OpenGeo Suite SDK which is based on GXP. GeoNode treats GeoExplorer as an external module that is used out of the box in GeoNode, but it is possible for you to create your own Suite SDK app and integrate it with GeoNode.

2.2.9 Static Site

The front end of GeoNode is composed of a set of core templates, specific templates for each module, cascading style sheets to style those pages and a set of javascript modules that provide the interactive functionality in the site.

Templates

GeoNode includes a basic set of core templates that use Django's template inheritance system to provide a modular system for constructing the web pages in GeoNode's interface. These core templates drive the overall page layout and things like the home page. You will start the process of customizing your GeoNode instance by overriding these templates, so you should familiarize yourself with their tructure and how they inherit from each other to drive the pages.

Additionally, most of the apps described above have their own set of templates that are used to drive the pages for each module. You may also want to override these templates for your own purposes and as such should familiarize yourself with a few of the key ones.

CSS

GeoNode's css is based on Twitter's Bootstrap Library which uses the lessc dynamic stylesheet language. GeoNode extends from the basic Bootstrap style and you are able to create your own bootstrap based style to customize the look and feel of your own GeoNode instance. Sites like bootswatch.com also provide ready made styles that you can simply drop in to your project to change the style.

Javascript

The interactive functionality in GeoNode pages is provided by the jQuery javascript framework and a set of jQuery plugins. The core set of GeoNode javascript modules closely aligns with the apps described above, and there are also

a few pieces of functionality provided as javascript modules that are used through out all of the apps. You are able to add your own jQuery code and/or plugins to perform interactive functionality in your own application.

CUSTOMIZED GEONODE PROJECTS

This module will teach you about how to setup your own GeoNode based project and how to customize your project by changing the theme, adding additional modules and how to integrate your project with other systems. When complete, you should understand how Downstream GeoNode projects work, and how to setup your own for your own use cases and needs.

3.1 Introduction to GeoNode Projects

GeoNode enables you to setup a complete site by simply by installing the packages and adding your data. If instead you want to create your own project based on GeoNode, there are a several options available to you that enable you to customize the look and feel of your GeoNode site, to add additional modules that are necessary for your own use case and to integrate your GeoNode project with other external sites and services.

This module assumes that you have installed a GeoNode site with the Ubuntu Packages and that you have a working GeoNode based on that setup. If you want to follow this same methodology on a different platform or setup, you should follow this module and adapt as necessary for your desired deployment environment.

3.1.1 Overview

GeoNode by itself is an out of the box, full featured Spatial Data Infrastructure Solution, but many GeoNode implementations require either customization of the default site, or the use of additional modules whether they be third-party Django Pluggables or modules developed by a GeoNode implementor himself. There are quite a few existing Downstream GeoNode projects some of which follow the methodology described in this module. You should familiarize yourself with these projects and how and why they extend GeoNode. You should also carefully think about what customization and additional modules you need for your own GeoNode based project and research the options that are available to you. The [Django Packages](#) site is a great place to start looking for existing modules that may meet your needs.

3.1.2 Existing Downstream GeoNode Projects

- Harvard Worldmap
- MapStory
- Risiko/SAFE

3.1.3 Django Template Projects

GeoNode follows the django template projects paradigm introduced in Django 1.4. At a minimum, a django project consists of a settings.py file and a urls.py file and django apps are used to add specific pieces of functionality. The GeoNode development team has created a template project which contains these required files with all the GeoNode configuration you need to get up and running with your own GeoNode project. If you would like learn more about Django projects and Apps, you should consult the [Django Documentation](#)

3.2 Setting up your GeoNode Project

This section will walk you through the steps necessary to setup your own GeoNode project. It assumes that you have installed GeoNode from the ubuntu packages and that you have a working GeoNode site.

3.2.1 Setup Steps

If you are working remotely, You should first connect to the machine that has your GeoNode installed on it. You will need to perform the following steps in a directory where you intend to keep your newly created project.

1. Activate GeoNode's Virtual Environment:

```
$ source /var/lib/geonode/bin/activate
```

2. Create your GeoNode project from the Template:

```
$ django-admin.py startproject --template=https://github.com/GeoNode/geonode-project/zipball/master my_geonode
$ cd my_geonode
```

3. Update your local_settings.py:

You will need to check the local_settings.py that is included with the template project and be sure that it reflects your own local environment. You should pay particular attention to the Database settings especially if you intend to reuse the database that was setup with your base GeoNode installation.

4. Synchronize your Database:

```
$ python manage.py syncdb --all
```

5. Run the test server:


```
$ python manage.py runserver
```

6. Visit your new GeoNode Site.

<http://localhost:8000>

3.2.2 Source Code Revision Control


It is recommended that you immediately put your new project under source code revision control. The GeoNode development team uses Git and GitHub purpose and recommends that you do the same. If you do not already have a GitHub account, it is recommended that you set one up. A full review of Git and distributed Source Code Revision Control systems is beyond the scope of this tutorial, but you may find the [Git Book](#) useful if you are not already familiar with these concepts.



1. Create a new Repository in GitHub:

You should use the GitHub user interface to create a new repository for your new project.

Creating a new GitHub Repository From GitHub's Homepage




Specifying new GitHub Repository Parameters

Your new Empty GitHub Repository

2. Initialize your own repository:

```
$ git init
```

3. Add the remote repository reference to your local git configuration:



```
$ git remote add
```

4. Add your project files to the repository:

```
$ git add .
```

5. Commit your changes:

```
$ git commit -am "Initial commit"
```

6. Push to the remote repository:

```
$ git push origin master
```

3.2.3 Deploying your GeoNode Project

Now that your own project is setup, you will need to replace the existing default configuration with configuration for your own project in order to visit your new project site.

1. Update Apache Configuration
2. Check GeoServer Configuration
3. Check Database Configuration

3.2.4 Staying in Sync with Mainline GeoNode

One of the primary reasons that we setup your own GeoNode project using this method is so that you can stay in sync with mainline geonode as the core GeoNode development team makes new releases. Your own project should not be adversely affected by these upstream changes, but you will receive bug fixes and other improvements by staying in sync.

1. Upgrade GeoNode:

```
$ apt-get update
$ apt-get install geonode
```

2. Verify that your new project works with the upgraded GeoNode:

```
$ python manage.py runserver
```

Visit <http://localhost:8000/>

3.3 Theming your GeoNode Project

3.3.1 Logos and Graphics

3.3.2 Templates and Static Pages

3.3.3 Cascading Style Sheets

3.3.4 Other Theming Options

Bootswatch

3.4 Adding Additional Modules to your GeoNode Project

3.4.1 Intro to Django Pluggables

3.4.2 Adding your own Django Module

3.4.3 Adding a 3rd Party Blog Module

3.4.4 Adding Other Modules

3.5 Integrating your Project with other Systems

3.5.1 Third Party Integration Overview

3.5.2 OGC Services

3.5.3 Google Earth

3.5.4 qGIS

3.5.5 OpenStreetMap

3.5.6 Wordpress

3.5.7 MapBox

SETTING UP A GEONODE DEVELOPMENT ENVIRONMENT

This module will lead you through the steps necessary to install a GeoNode development environment.

4.1 GeoNode Development Tools

4.2 Git Repository Setup

4.3 Installing GeoNode's Python Package

4.4 Pavement.py and Paver

4.5 Manually Deploying your Development Environment

LOADING DATA INTO A GEONODE

This module will walk you through the various options available to load data into your GeoNode from GeoServer, on the command-line or programatically. You can choose from among these techniques depending on what kind of data you have and how you have your geonode setup.

5.1 GeoServer Data Configuration

5.2 Using ogr2ogr to load data into GeoNode

5.3 Loading OSM Data into GeoNode

GEONODE APIS

6.1 OGC Services

6.2 GeoServer REST API

6.3 GeoServers Import and Print APIs

6.4 GeoNode's Ad-Hoc API

GEONODE DEBUGGING TECHNIQUES

7.1 Debugging GeoNode's Python Components

7.2 Debugging GeoNode in the Browser

7.3 Debugging GeoServer

GEONODE'S DEVELOPMENT PROCESS

8.1 GeoNode's Issue Tracking System

8.2 Testing in GeoNode

8.2.1 Unit Tests

8.2.2 Integration Tests

8.2.3 Javascript Tests

8.3 GeoNode's Patch Review Process

8.4 GeoNode Improvement Proposals

8.5 GeoNode's Roadmap Process

8.6 Development Resources