



The Cloned Dynamics Approach for Lyapunov Exponents Calculation

FILIPE IEDA FAZANARO | filipe.fazanaro@ufabc.edu.br

DESCRIPTION

This repository contains scripts developed using MATLAB and C languages which are used to implement the Cloned Dynamics methodology. This approach aims to compute the Lyapunov exponents associate to nonlinear dynamical systems, specially the ones with some kind of non-smoothness.

1 History

The Cloned Dynamics approach was proposed by Diogo Coutinho Soriano (https://www.diogosoriano.com/) and me, with the help and oriented by our professors and friends, Dr. Romis Attux, Dr. Ricardo Suyama and Dr. Marconi Kolm Madrid, during the very beginning of our phd, in 2008, inspired by the thesis of a good friend, Prof. Dr. Reinaldo Gonçalves Nogueira, titled "Técnicas Alternativas de Reconhecimento de Caos em Sistemas com Dinâmica Complexa: Análise de um Sistema com Descontinuidade" (http://repositorio.unicamp.br/jspui/handle/REPOSIP/260285; in portuguese). In his work, Prof. Reinaldo proposed an implementation which was capable to compute the Lyapunov spectrum of non-smooth nonlinear dynamical system, particularly, systems subject to impacts. The system studied was a pendulum with restrictions.

The main idea of the Cloned Dynamics approach is to compute the Lyapunov exponents (or the Lyapunov spectrum). To improve its understanding, consider, for instance, a continuous time third order nonlinear dynamical system, as the Duffing and the Van der Pol oscillators [Guckenheimer and Holmes, 2000] and the Chua's circuit [Fazanaro et al., 2010; Parker and Chua, 1989]. Initially, one has to made copies (clones) of the original dynamical system; in this case, three copies. Each copy is perturbed by a infinitesimal δ . The four systems - the original one and the clones - are all evaluated during a small time interval. In the end, the Gram-Schimidt orthonormalization needs to be applied to correct the 'collapse effect which can be observed due to the expansion of the most divergence direction. The Cloned Dynamics approach was proposed in [Soriano et al., 2012b] to study the effects of the FitzHugh-Nagumo neuronal model driven by a square wave external function.





2 How To Cite

The Cloned Dynamics approach was used do develop some works. The main results were published in some important journals, such as Chaos [Fazanaro et al., 2013], Communications in Nonlinear Science and Numerical Simulation [Fazanaro et al., 2016], International Journal of Bifurcation and Chaos [Soriano et al., 2012a, 2018], and in a few conferences and symposiums as [Fazanaro et al., 2010, 2012].

To cite the Cloned Dynamics approach, please use the following:

```
@ARTICLE{ article: SorianoFazanaro 2012,
  author = {Soriano, D.C.; Fazanaro, F.I.; Suyama, R.; Oliveira, J.R.; Attux, R.; Madrid, M
      .K.},
          = {{A method for Lyapunov spectrum estimation using cloned dynamics and its
  title
      application to the discontinuously-excited FitzHugh-Nagumo model}},
 journal = {Nonlinear Dynamics},
          = \{2012\},
 year
 volume = \{67\},
          = \{413 - -424\},
  pages
 number = \{1\},
 month
          = \{Jan\},
  doi
          = \{10.1007/s11071-011-9989-2\}
}
```





3 Organization of the Repository

The repository is organized based on the following folder structure:

- Aux_Functions: you need to add this folder to you MATLAB path. It contains some auxiliary functions, as, for instance, the implementation of 4th order Runge-Kutta integration.
- MATLAB: in this folder, you will find the implementations of some of the most important dynamical systems, as the Duffing Oscillator, the Chua oscillator, the FitzHugh-Nagumo neuronal model, and others. Is was employed the MATLAB language. There are comments and descriptions inside the scripts to improve the understanding of each code.

You will find the scripts to generate the time evolution of each state variable, the Poincaré section, the implementation of the Cloned Dynamics approach to compute the Lyapunov exponents and the Lyapunov spectrum (the value of the exponent related to the variation of one constant of the model).

- MATLAB_parfor: the computation of the Lyapunov exponents is usually very computational expensive. Here, it was implemented the computation of the Lyapunov spectrum using the Parallel computational toolbox of the MATLAB. It is necessary to adjust the number of cores used during each simulation.
- C: as a great friend of mine, André Luiz Delai (http://lattes.cnpq.br/4609660221170758), usually says, "C is the mother language of all". In this folder, there are some implementations using the C language, basically, only to compute the Lyapunov exponents and the Lyapunov spectrum. As discussed in the work [citar CNCNS], it is possible to improve the computational cost to (i.e. decrease the total amount of time to) realize such computation when compare to the MATLAB implementation.

[?]



4 Versions

- xx / June / 2020:
 - v01 initial version.





References

- Fazanaro, F. I., Soriano, D. C., Madrid, M. K., Suyama, R., Attux, R., and Oliveira, J. R. Cálculo do espectro de Lyapunov via dinâmicas clonadas e sua aplicação no circuito de Chua. In *XVIII Congresso Brasileiro de Automática (CBA 2010)*, pages 2511–2518, Bonito–MS–Brazil, Sept. 2010. URL https://www.researchgate.net/publication/236019546_Calculo_do_espectro_de_Lyapunov_via_dinamicas_clonadas_e_sua_aplicacao_no_circuito_de_Chua. (In Portuguese).
- Fazanaro, F. I., Soriano, D. C., Suyama, R., Madrid, M. K., Attux, R., and Oliveira, J. R. Information Generation and Lagrangian Coherent Structures in Multiscroll Attractors. In *3rd IFAC Conference on Analysis and Control of Chaotic Systems 2012. 3rd IFAC CHAOS 2012.*, volume 3, pages 47–52, Cancún, México, Jun. 20–22 2012. doi:10.3182/20120620-3-mx-3012.00010.
- Fazanaro, F. I., Soriano, D. C., Suyama, R., Madrid, M. K., Attux, R., and Oliveira, J. R. Characterization of Multiscroll Attractors using Lyapunov Exponents and Lagrangian Coherent Structures. *Chaos*, 23 (2):023105, Jun. 2013. doi:10.1063/1.4802428.
- Fazanaro, F. I., Soriano, D. C., Suyama, R., Madrid, M. K., Oliveira, J. R., Muñoz, I. B., and Attux, R. Numerical characterization of nonlinear dynamical systems using parallel computing: The role of GPUs approach. *Communication in Nonlinear Science and Numerical Simulation*, 37:143–162, Aug. 2016. doi:10.1016/j.cnsns.2015.12.021.
- Guckenheimer, J. and Holmes, P. *Nonlinear Oscillations, Dynamical Systems, and Bifurcations of Vector Fields*, volume 42 of *Applied Mathematical Sciences*. Springer, 2000. doi:10.1007/978-1-4612-1140-2.
- Parker, T. S. and Chua, L. O. *Practical Numerical Algorithms for Chaotic Systems*. Springer-Verlag, 1989. doi:10.1007/978-1-4612-3486-9.
- Soriano, D. C., Attux, R., Suyama, R., and Romano, J. M. T. Searching for specific periodic and chaotic oscillations in a periodically-excited hodgkin-huxley model. *International Journal of Bifurcation and Chaos*, 22(1):1230006, Jan 2012a. doi:10.1142/S0218127412300066.
- Soriano, D. C., Fazanaro, F. I., Suyama, R., Oliveira, J. R., Attux, R., and Madrid, M. K. A method for Lyapunov spectrum estimation using cloned dynamics and its application to the discontinuously-excited FitzHugh-Nagumo model. *Nonlinear Dynamics*, 67(1):413–424, Jan. 2012b. doi:10.1007/s11071-011-9989-2.
- Soriano, D. C., dos Santos, O. V., Suyama, R., Fazanaro, F. I., and Attux, R. Conditional lyapunov exponents and transfer entropy in coupled bursting neurons under excitation and coupling mismatch. *Communications in Nonlinear Science and Numerical Simulation*, 56:419–433, Mar 2018. doi:10.1016/j.cnsns.2017.08.022.