

```
% Example_5_2.m
%
% This is Example 5.2 from the paper 'Geometric modelling of
% polycrystalline materials: Laguerre tessellations and periodic
% semi-discrete optimal transport' by D.P. Bourne, M. Pearce & S.M. Roper.
%
% In this example we monitor the number of Newton iterations and
% backtracking steps in 100 draws of 100,000 log-normally distributed
% grain volumes.

clear
```

Specify box dimensions

```
bx=[1,1,1];
```

Specify periodicity

```
periodic=true;
```

Specify maximal percentage error

```
percent_tol=1;
```

Specify number of seeds (grains)

```
n=[1000]; % Set n=[100000] to reproduce example from paper
nn=length(n);
```

Specify number of experiments

```
nexp=100;
```

Log-normal backtracking

```
% Parameters in log-normal distribution
ln_mean=1; % mean
std_dev=0.35; % standard deviation
sigma=sqrt((log(1+(std_dev/ln_mean)^2))); % log-normal parameter sigma
mu=-0.5*sigma^2+log(ln_mean); % log-normal parameter mu

disp('Log-normal')
```

```
Log-normal
```

```
for idx_n=1:nn

    % For each number of seeds
    disp(sprintf('Calculating run times for n = %d',n(idx_n)));

    % Initial guess is always w=0
    w_0=zeros(n(idx_n),1);
```

```

for idx_exp=1:nexp
    % For each experiment
    fprintf('\t Experiment number %d',idx_exp);

    % Seed locations
    X=rand(n(idx_n),3);

    % Compute target volumes:
    % Draw radii from log-normal distribution
    rad=lognrnd(mu,sigma,n(idx_n),1);
    % Calculate the corresponding grain volumes
    % (we don't need the factor 4pi/3 as we'll be renormalising)
    target_vols=rad.^3;
    % Normalise the volumes so that they add to the volume of the box
    target_vols=target_vols*prod(bx)/sum(target_vols); % target volumes of the grains

    % Store the X and target_vols in case later interrogation is required
    X_ln{idx_n,idx_exp}=X;
    tv_ln{idx_n,idx_exp}=target_vols;

    % Time the damped Newton method
    tic
    [w,max_percent_err,actual_vols,EXITFLAG,back_track_steps,newton_step_errors,w_steps] =
    t=toc;

    fprintf(' : completed in %f\n',t);

    % Store the solution for w
    w_ln{idx_n,idx_exp}=w;

    % Store the details of each Newton iteration and the error after each Newton iteration
    runtime_ln(idx_n,idx_exp)=t; % run times
    back_track_ln{idx_n,idx_exp}=back_track_steps; % number of backtracking steps
    newton_errors_ln{idx_n,idx_exp}=newton_step_errors; % volume errors
end

disp(sprintf('Average run time %f',mean(runtime_ln(idx_n,:))));
end

```

Calculating run times for n = 1000

```

Experiment number 1
: completed in 1.042100
Experiment number 2
: completed in 0.990089
Experiment number 3
: completed in 1.192071
Experiment number 4
: completed in 1.077584
Experiment number 5
: completed in 1.002131
Experiment number 6
: completed in 1.043316
Experiment number 7
: completed in 1.304515
Experiment number 8
: completed in 1.396532

```

Experiment number 9
: completed in 0.996712
Experiment number 10
: completed in 1.035925
Experiment number 11
: completed in 1.059413
Experiment number 12
: completed in 1.232525
Experiment number 13
: completed in 1.404224
Experiment number 14
: completed in 0.889686
Experiment number 15
: completed in 1.304110
Experiment number 16
: completed in 1.019343
Experiment number 17
: completed in 1.265257
Experiment number 18
: completed in 1.125614
Experiment number 19
: completed in 1.064318
Experiment number 20
: completed in 1.295671
Experiment number 21
: completed in 1.077892
Experiment number 22
: completed in 1.557409
Experiment number 23
: completed in 1.203210
Experiment number 24
: completed in 1.382126
Experiment number 25
: completed in 1.233199
Experiment number 26
: completed in 1.264140
Experiment number 27
: completed in 1.603400
Experiment number 28
: completed in 1.531639
Experiment number 29
: completed in 1.256970
Experiment number 30
: completed in 1.265272
Experiment number 31
: completed in 1.310663
Experiment number 32
: completed in 1.520637
Experiment number 33
: completed in 1.152994
Experiment number 34
: completed in 0.995557
Experiment number 35
: completed in 1.249189
Experiment number 36
: completed in 1.322670
Experiment number 37
: completed in 1.529212
Experiment number 38
: completed in 1.569904
Experiment number 39
: completed in 1.168303
Experiment number 40
: completed in 1.550462

Experiment number 41
: completed in 1.232540
Experiment number 42
: completed in 1.586489
Experiment number 43
: completed in 1.515356
Experiment number 44
: completed in 1.175128
Experiment number 45
: completed in 1.445730
Experiment number 46
: completed in 1.244150
Experiment number 47
: completed in 1.283798
Experiment number 48
: completed in 1.639055
Experiment number 49
: completed in 1.198793
Experiment number 50
: completed in 1.387115
Experiment number 51
: completed in 1.511974
Experiment number 52
: completed in 1.227046
Experiment number 53
: completed in 1.309677
Experiment number 54
: completed in 1.762916
Experiment number 55
: completed in 1.363067
Experiment number 56
: completed in 1.084791
Experiment number 57
: completed in 1.648994
Experiment number 58
: completed in 1.200732
Experiment number 59
: completed in 1.436852
Experiment number 60
: completed in 1.708129
Experiment number 61
: completed in 1.669034
Experiment number 62
: completed in 1.540095
Experiment number 63
: completed in 1.222775
Experiment number 64
: completed in 1.245343
Experiment number 65
: completed in 1.704411
Experiment number 66
: completed in 1.252242
Experiment number 67
: completed in 1.486437
Experiment number 68
: completed in 1.410086
Experiment number 69
: completed in 1.571898
Experiment number 70
: completed in 1.126115
Experiment number 71
: completed in 1.433958
Experiment number 72
: completed in 1.248139

```

    Experiment number 73
: completed in 1.196393
    Experiment number 74
: completed in 1.213115
    Experiment number 75
: completed in 1.178006
    Experiment number 76
: completed in 1.166810
    Experiment number 77
: completed in 1.174117
    Experiment number 78
: completed in 1.635863
    Experiment number 79
: completed in 1.369495
    Experiment number 80
: completed in 1.323882
    Experiment number 81
: completed in 1.582584
    Experiment number 82
: completed in 1.957933
    Experiment number 83
: completed in 1.841797
    Experiment number 84
: completed in 2.359346
    Experiment number 85
: completed in 2.492234
    Experiment number 86
: completed in 2.570375
    Experiment number 87
: completed in 2.938443
    Experiment number 88
: completed in 1.851986
    Experiment number 89
: completed in 1.864190
    Experiment number 90
: completed in 1.290329
    Experiment number 91
: completed in 1.235012
    Experiment number 92
: completed in 1.267284
    Experiment number 93
: completed in 1.152928
    Experiment number 94
: completed in 1.355644
    Experiment number 95
: completed in 1.202549
    Experiment number 96
: completed in 1.108274
    Experiment number 97
: completed in 1.196332
    Experiment number 98
: completed in 1.113747
    Experiment number 99
: completed in 1.214443
    Experiment number 100
: completed in 1.239828
Average run time 1.374518

```

Plot the results

```

% Assume that n is a 1 x nn array of cell numbers
% Assume that back_track_ln is an nn x nexp cell array of backtracking information

```

```

[nn,nexp]=size(back_track_ln);

for k=1:nn
    back_track_exp=back_track_ln(k,:);

    % First find maximum number of Newton steps
    newt_steps=cellfun('length',back_track_exp);
    mns=max(newt_steps);
    data=-1*ones(nexp,mns);

    % Extract the data from the backtracking cell array
    for j=1:nexp
        data(j,1:length(back_track_exp{j}))=back_track_exp{j};
    end

    % Sort the data for ease of visualisation
    data=sortrows(data);

    % The maximum number of backtracking steps
    mbs=max(max(data));

    % Make a new figure, one for each number of cells
    figure(k)

    % Plot the number of backtracking steps
    image(1:mns,1:nexp,data,'CDataMapping','scaled')
    title(sprintf('$n=%d$',n(k)),'Interpreter','latex','FontSize',12)

    % Make a discrete palette
    cmap=jet(mbs+2);
    % Make -1 correspond to white
    cmap(1,:)=[1 1 1];

    colormap(cmap);
    cbh=colorbar;
    ch=(mbs)/(mbs+1);
    cbh.Ticks=linspace(0.5*ch, mbs-0.5*ch, mbs+1) ; %Create 8 ticks from zero to 1
    cbh.TickLabels=num2cell(0:mbs);
    cbh.Limits=[0,mbs];
    xlabel('Newton iteration','Interpreter','latex','FontSize',12)
    ylabel('Experiment number','Interpreter','latex','FontSize',12)
    xlim([0.5,mns+0.5]);
    ylim([0.5,nexp+0.5]);

    set(gca,'YDir','normal','TickLabelInterpreter','latex','FontSize',10,'box','off');
    set(gca,'XTickLabelMode','manual');
    set(gca,'XTickLabels',num2cell(1:mns));
    set(gca,'XTickMode','manual');
    set(gca,'XTick',1:mns);

    hold on
    for l=1:mns-1
        plot(0.5+[1 1],[0.5,nexp+0.5],'k');
    end

```

```

end

for l=1:nexp
    % Number of Newton steps
    ns=sum(data(l,:)>=0);
    plot([0 ns+0.5],0.5+[1 1]*l,'w','LineWidth',0.25);
end
hold off

set(cbh,'TickLabelInterpreter','latex');
axis square

end

```

